

Package ‘CexoR’

March 30, 2021

Version 1.28.0

Date 2020-06-29

Type Package

Title An R package to uncover high-resolution protein-DNA interactions in ChIP-exo replicates

Author Pedro Madrigal <bioinformatics.engineer@gmail.com>

Description Strand specific peak-pair calling in ChIP-exo replicates. The cumulative Skellam distribution function (package 'skellam') is used to detect significant normalised count differences of opposed sign at each DNA strand (peak-pairs). Irreproducible discovery rate (IDR) for overlapping peak-pairs across biological replicates is estimated using the package 'idr'.

Depends R (>= 2.10.0), S4Vectors, IRanges

Maintainer Pedro Madrigal <bioinformatics.engineer@gmail.com>

Imports Rsamtools, GenomeInfoDb, GenomicRanges, rtracklayer, idr, RColorBrewer, genomation

Suggests RUnit, BiocGenerics, BiocStyle

License Artistic-2.0 | GPL-2 + file LICENSE

LazyLoad yes

LazyData yes

biocViews Transcription, Genetics, Sequencing

git_url <https://git.bioconductor.org/packages/CexoR>

git_branch RELEASE_3_12

git_last_commit 3641236

git_last_commit_date 2020-10-27

Date/Publication 2021-03-29

R topics documented:

CexoR-package	2
cexor	3
plotcexor	5
Index	7

CexoR-package

An R package to uncover high-resolution protein-DNA interactions in ChIP-exo replicates

Description

Strand specific peak-pair calling in ChIP-exo replicates. The cumulative Skellam distribution function (package 'skellam') is used to detect significant normalised count differences of opposed sign at each DNA strand (peak-pairs). Irreproducible discovery rate for overlapping peak-pairs across biological replicates is estimated using the package 'idr'.

Details

Package:	CexoR
Type:	Package
Version:	1.19.3
Date:	2018-07-03
License:	Artistic-2.0 GPL-2 + file LICENSE
LazyLoad:	yes

Author(s)

Pedro Madrigal,

Maintainer: Pedro Madrigal <bioinformatics.engineer@gmail.com>

References

Madrigal P (2015) CexoR: an R/Bioconductor package to uncover high-resolution protein-DNA interactions in ChIP-exo replicates. *EMBNet.journal* 21: e837.

Skellam JG (1946) The frequency distribution of the difference between two Poisson variates belonging to different populations. *J R Stat Soc Ser A* 109: 296.

Li Q, Brown J, Huang H, Bickel P (2011) Measuring reproducibility of high-throughput experiments. *Ann Appl Stat* 5: 1752-1779.

Rhee HS, Pugh BF (2011) Comprehensive genome-wide protein-DNA interactions detected at single-nucleotide resolution. *Cell* 147: 1408-1419.

Examples

```
## hg19. chr2:1-1,000,000. CTCF data from Rhee and Pugh (2011)

owd <- setwd(tempdir())

rep1 <- "CTCF_rep1_chr2_1-1e6.bam"
rep2 <- "CTCF_rep2_chr2_1-1e6.bam"
rep3 <- "CTCF_rep3_chr2_1-1e6.bam"
r1 <- system.file("extdata", rep1, package="CexoR", mustWork = TRUE)
r2 <- system.file("extdata", rep2, package="CexoR", mustWork = TRUE)
```

```

r3 <- system.file("extdata", rep3, package="CexoR", mustWork = TRUE)

chipexo <- cexor(bam=c(r1,r2,r3), chrN="chr2", chrL=1e6, idr=0.01, p=1e-12, N=3e4)

plotcexor(bam=c(r1,r2,r3), peaks=chipexo, EXT=500)

setwd(owd)

```

cexor

*ChIP-exo peak-pair calling with replicates***Description**

ChIP-exo peak-pair calling with replicates.

Usage

```

cexor(bam, chrN, chrL, p=1e-9, dpeaks=c(0,150), dpairs=100, idr=0.01,
N=5e6, bedfile=TRUE, mu=2.6, sigma=1.3, rho=0.8, prop=0.7)

```

Arguments

bam	BAM alignment files of biological replicates.
chrN	Vector of chromosome names.
chrL	Vector of chromosome sizes (bp).
p	P-value cutoff (should be relaxed, e.g. 1e-3, to allow the correct estimation of the irreproducible discovery rate (idr). However, this depends on the sequencing depth. For datasets with high number of tag counts, 1e-9 can be appropriate. See the vignette for more information.)
dpeaks	Min. and max. allowed distance between peak pairs located at opposed strands in a replicate (bp).
dpairs	Max. allowable distance between peak-pair centres across replicates (bp).
idr	Irreproducible discovery rate cutoff [0-1].
N	Genome is divided in blocks of N bp. for processing. N must be not higher than the size of the smallest chromosome.
bedfile	Generate BED files of ChIP-exo reproducible peak pairs.
mu	A starting value for the mean of the reproducible component (see 'idr' package).
sigma	A starting value for the standard deviation of the reproducible component (see 'idr' package).
rho	A starting value for the correlation coefficient of the reproducible component (see 'idr' package).
prop	A starting value for the proportion of reproducible component (see 'idr' package).

Details

Strand specific peak-pair calling in ChIP-exo replicates. The cumulative Skellam distribution function (package 'skellam') is used to detect significant normalized count differences of opposed sign at each DNA strand (peak-pairs). Irreproducible discovery rate for overlapping peak-pairs across biological replicates is estimated using the package 'idr'. The internal functions `pskellam` and `pskellam.sp` from the Jerry W. Lewis' 'skellam' R package (version 0.0-8-7) are used to calculate the cumulative Skellam distribution (see LICENSE file).

Value

A list containing the following elements:

- `bindingEvents` A GRanges object with reproducible peak pair locations. The metadata 'value' indicates the Irreproducible discovery rate (IDR) estimated at this region, while 'repI.neg.log10pvalue' indicates $-\log_{10}(\text{p-value})$ for the replicate I. 'Stouffer.pvalue' and 'Fisher.pvalue' report the combined p-value considering they come from independent significance tests.
- `bindingCentres` A GRanges object with centre position of reproducible peak pair locations. The metadata 'value' indicates the Irreproducible discovery rate (IDR) estimated at this region, while 'repI.neg.log10pvalue' indicates $-\log_{10}(\text{p-value})$ for the replicate I. 'Stouffer.pvalue' and 'Fisher.pvalue' report the combined p-value considering they come from independent significance tests.
- `pairedPeaksRep1` A GRangesList object with the location of peak pairs retrieved at each replicate. The metadata 'score' indicates $-\log_{10}(\text{p-value})$.

Author(s)

Pedro Madrigal, <bioinformatics.engineer@gmail.com>

References

Madrigal P (2015) CexoR: an R/Bioconductor package to uncover high-resolution protein-DNA interactions in ChIP-exo replicates. *EMBnet.journal* 21: e837.

See Also

[CexoR-package](#)

Examples

```
## hg19. chr2:1-1,000,000. CTCF data from Rhee and Pugh (2011)

owd <- setwd(tempdir())

rep1 <- "CTCF_rep1_chr2_1-1e6.bam"
rep2 <- "CTCF_rep2_chr2_1-1e6.bam"
rep3 <- "CTCF_rep3_chr2_1-1e6.bam"
r1 <- system.file("extdata", rep1, package="CexoR", mustWork = TRUE)
r2 <- system.file("extdata", rep2, package="CexoR", mustWork = TRUE)
r3 <- system.file("extdata", rep3, package="CexoR", mustWork = TRUE)

chipexo <- cexor(bam=c(r1,r2,r3), chrN="chr2", chrL=1e6, idr=0.01, p=1e-12, N=3e4)
```

```
plotcexor(bam=c(r1,r2,r3), peaks=chipexo, EXT=500)

setwd(owd)
```

plotcexor

Visualization of ChIP-exo peak-pair calling with replicates

Description

Visualization of ChIP-exo peak-pair calling with replicates.

Usage

```
plotcexor(bam, peaks, EXT=500)
```

Arguments

bam	BAM alignment files of biological replicates.
peaks	Object (list) output of the function 'cexor'.
EXT	Extension (bp) upstream and downstream the central position of reproducible peak pair locations for visualization purposes.

Details

Visualization of ChIP-exo peak-pair calling with replicates.

Value

R plot.

Author(s)

Pedro Madrigal, <bioinformatics.engineer@gmail.com>

References

Madrigal P (2015) CexoR: an R/Bioconductor package to uncover high-resolution protein-DNA interactions in ChIP-exo replicates. *EMBnet.journal* 21: e837.

See Also

[CexoR-package](#)

Examples

```
## hg19. chr2:1-1,000,000. CTCF data from Rhee and Pugh (2011)

owd <- setwd(tempdir())

rep1 <- "CTCF_rep1_chr2_1-1e6.bam"
rep2 <- "CTCF_rep2_chr2_1-1e6.bam"
rep3 <- "CTCF_rep3_chr2_1-1e6.bam"
r1 <- system.file("extdata", rep1, package="CexoR", mustWork = TRUE)
r2 <- system.file("extdata", rep2, package="CexoR", mustWork = TRUE)
r3 <- system.file("extdata", rep3, package="CexoR", mustWork = TRUE)

chipexo <- cexor(bam=c(r1,r2,r3), chrN="chr2", chrL=1e6, idr=0.01, p=1e-12, N=3e4)

plotcexor(bam=c(r1,r2,r3), peaks=chipexo, EXT=500)

setwd(owd)
```

Index

CexoR (CexoR-package), [2](#)

cexor, [3](#)

CexoR-package, [2](#)

plotcexor, [5](#)