

Package ‘microbiomeExplorer’

March 30, 2021

Type Package

Title Microbiome Exploration App

Version 1.0.1

Date 2020-10-27

Description The MicrobiomeExplorer R package is designed to facilitate the analysis and visualization of marker-gene survey feature data.

It allows a user to perform and visualize typical microbiome analytical workflows either through the command line or an interactive

Shiny application included with the package. In addition to applying common analytical workflows the application enables automated analysis report generation.

License MIT + file LICENSE

Imports shinyjs, shinydashboard, shinycssloaders, shinyWidgets, rmarkdown ($\geq 1.9.0$), DESeq2, RColorBrewer, dplyr, tidyr, rlang, knitr, readr, DT ($\geq 0.12.0$), biomformat, tools, stringr, vegan, matrixStats, heatmaply, car, broom, limma, reshape2, tibble, forcats, lubridate, methods, plotly ($\geq 4.9.1$)

Depends shiny, magrittr, metagenomeSeq, Biobase

Suggests V8, testthat ($\geq 2.1.0$)

DeploySubPath microbiomeExplorer

biocViews Classification, Clustering, GeneticVariability, DifferentialExpression, Microbiome, Metagenomics, Normalization, Visualization, MultipleComparison, Sequencing, Software, ImmunoOncology

Encoding UTF-8

RoxygenNote 7.1.1

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/microbiomeExplorer>

git_branch RELEASE_3_12

git_last_commit 17f035a

git_last_commit_date 2020-10-28

Date/Publication 2021-03-29

Author Joseph Paulson [aut],
 Janina Reeder [aut, cre],
 Mo Huang [aut],
 Genentech [cph, fnd]

Maintainer Janina Reeder <reederj1@gene.com>

R topics documented:

abundanceHeatmap	4
abundanceHeatmapUI	5
addFeatData	5
addPhenoData	6
add_plotly_config	6
add_plotly_layout	7
aggFeatures	7
aggregationTab	8
aggregationTabUI	8
alphaDiversity	9
alphaDiversityUI	10
avgAbundance	10
avgAbundanceUI	11
betaDiversity	12
betaDiversityUI	13
betaInput	13
betaInputUI	14
buildEmptyPlotlyPlot	14
buildPlottingDF	15
calculatePCAs	15
computeCI_Interval	16
computeDistMat	17
corrAnalysis	17
corrAnalysisUI	18
corrFeature	19
corrInput	20
corrInputUI	21
corrPhenotype	21
createHeader	22
dataInput	23
dataInputUI	24
designPairs	24
diffAnalysis	25
diffAnalysisUI	26
diffInput	26
diffInputUI	27
diffTable	27
diffTableUI	28
extendPhenoData	29
featAbundance	29
featAbundanceUI	30
featureAnalysis	31
featureAnalysisUI	31

featureCorr	32
featureCorrUI	33
featureInput	33
featureInputUI	34
featureTable	35
featureTableUI	35
fileUpload	36
fileUploadUI	37
filterByPheno	37
filterMEData	38
generateReport	39
getFeatModCode	40
getFileType	40
getFilterChoices	41
getLegendLevel	41
getPhenoChanges	42
getPhenoModCode	42
getWidths	43
heatmapInput	43
heatmapInputUI	44
interAnalysis	44
interAnalysisUI	45
intraAnalysis	46
intraAnalysisUI	47
intraInput	47
intraInputUI	48
longAnalysis	49
longAnalysisUI	50
longInput	50
longInputUI	51
longResults	52
longResultsUI	53
makeQCPlot	53
normalizeData	54
parseInteractionName	55
phenotypeCorr	55
phenotypeCorrUI	56
phenotypeTable	57
phenotypeTableUI	57
plotAbundance	58
plotAlpha	59
plotAvgAbundance	60
plotBeta	61
plotHeatmap	62
plotLongFeature	63
plotlyHistogram	64
plotlySampleBarplot	65
plotSingleFeature	66
readData	67
relAbundance	67
relAbundanceUI	68
replaceWithUnknown	69

reportList	69
reportListUI	70
reportRow	71
reportRowUI	71
rollDownFeatures	72
runDiffTest	72
runMicrobiomeExplorer	73

Index 74

abundanceHeatmap *Abundance Heatmap module - server*

Description

Abundance Heatmap module - server

Usage

```
abundanceHeatmap(
  input,
  output,
  session,
  aggDat,
  featLevel,
  colorOptions,
  levelOpts,
  hmSort,
  hmFeatList,
  reset
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
aggDat	aggregated MRExperiment
featLevel	chosen feature level (aggregation level)
colorOptions	reactive storing filters selected via data input
levelOpts	all available level choices for this dataset
hmSort	reactive storing sorting method for heatmap
hmFeatList	reactive storing list of features to include in heatmap
reset	boolean reactive which resets the module if TRUE

Value

R code needed to generate the heatmap

Author(s)

Janina Reeder

abundanceHeatmapUI	<i>Abundance Heatmap module - UI</i>
--------------------	--------------------------------------

Description

Abundance Heatmap module - UI

Usage

```
abundanceHeatmapUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

box holding the UI code

Author(s)

Janina Reeder

addFeatData	<i>Add feature data to MRobj.</i>
-------------	-----------------------------------

Description

This function adds feature data to the featureData slot in an MRExperiment object.

Usage

```
addFeatData(MRobj, featdata = NULL)
```

Arguments

MRobj	An MRExperiment object.
featdata	Feature data frame or file path.

Value

An updated MRExperiment object.

addPhenoData	<i>Add phenotype data to object.</i>
--------------	--------------------------------------

Description

This function adds phenotype data to the phenoData slot in an MExperiment object.

Usage

```
addPhenoData(MRobj, phenodata = NULL)
```

Arguments

MRobj	An MExperiment object.
phenodata	Phenotype data frame or file path.

Value

An updated MExperiment object.

add_plotly_config	<i>Adds a config call based on plotly::config</i>
-------------------	---------------------------------------------------

Description

Adds a config call based on plotly::config

Usage

```
add_plotly_config(.data)
```

Arguments

.data	plotly data object to apply the config call to
-------	------------------------------------------------

Value

plotly::config call

add_plotly_layout *Adds a layout call based on plotly::layout*

Description

Adds a layout call based on plotly::layout

Usage

```
add_plotly_layout(.data, plotTitle, xaxis_text, ylab)
```

Arguments

.data	plotly data object to apply the layout call to
plotTitle	plot title to use
xaxis_text	x axis label to use
ylab	y axis label to use

Value

plotly::layout call

aggFeatures *Aggregates counts by level*

Description

This function aggregates counts by a level specified in the featureData slot of the MRexperiment object.

Usage

```
aggFeatures(MRobj, level = NULL, sort = TRUE)
```

Arguments

MRobj	An MRexperiment object.
level	Level to aggregate over. If NULL, no aggregation occurs.
sort	boolean determining if resulting aggregated MRexperiment should be sorted based on rowSums; default is TRUE

Value

Aggregated MRexperiment object or matrix depending on out.

Examples

```
data("mouseData", package = "metagenomeSeq")
aggFeatures(mouseData, level = "genus")
```

aggregationTab *Aggregation module server function*

Description

Aggregation module server function

Usage

```
aggregationTab(  
  input,  
  output,  
  session,  
  resetInput,  
  levelOpts,  
  chosenLevel,  
  meData  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
resetInput	boolean updated to TRUE if new data is available
levelOpts	available levels to aggregate on (depends on input data)
chosenLevel	previously selected level (passed from different instance)
meData	the main MRExperiment object

Value

reactive list holding aggregated object, aggregation code and boolean on normalization

Author(s)

Janina Reeder

aggregationTabUI *Aggregation module ui function*

Description

Aggregation module ui function

Usage

```
aggregationTabUI(id)
```


Arguments

id namespace identifier

Value

box holding aggregation input elements

Author(s)

Janina Reeder

Examples

```
aggregationTabUI("atu_id")
```

alphaDiversity

Alpha Diversity module - server

Description

Alpha Diversity module - server

Usage

```
alphaDiversity(
  input,
  output,
  session,
  aggDat,
  featLevel,
  intraSettings,
  colorOptions,
  reset
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
aggDat	aggregated MRExperiment
featLevel	chosen feature level (aggregation level)
intraSettings	analysis settings as passed over from analysis input module
colorOptions	phenotype selections: used for color choices
reset	boolean reactive which resets the module if TRUE

Value

R code used to make the alpha diversity plot

Author(s)

Janina Reeder

alphaDiversityUI *Alpha Diversity module - UI*

Description

Alpha Diversity module - UI

Usage

```
alphaDiversityUI(id)
```

Arguments

id namespace identifier

Value

box holding the UI code

Author(s)

Janina Reeder

avgAbundance *Relative abundance plot module - server*

Description

Relative abundance plot module - server

Usage

```
avgAbundance(  
  input,  
  output,  
  session,  
  aggDat,  
  featLevel,  
  featureSettings,  
  normalizedData,  
  reset  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
aggDat	aggregated MRExperiment
featLevel	chosen feature level (aggregation level)
featureSettings	analysis input settings passed over to this module
normalizedData	boolean indicating whether data has been normalized
reset	boolean reactive which resets the module if TRUE

Value

list storing plot clicks and number of features displayed (passed to feature plot module) as well as the R code to make plot

avgAbundanceUI	<i>Relative abundance plot module - UI</i>
----------------	--------------------------------------------

Description

Relative abundance plot module - UI

Usage

```
avgAbundanceUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

box containing the ui code

Author(s)

Janina Reeder

`betaDiversity`*Beta Diversity module - server*

Description

Beta Diversity module - server

Usage

```
betaDiversity(  
  input,  
  output,  
  session,  
  aggDat,  
  aggLevel,  
  colorOptions,  
  shapeOptions,  
  betadistance,  
  betaSettings,  
  reset  
)
```

Arguments

<code>input</code>	shiny input
<code>output</code>	shiny output
<code>session</code>	shiny session
<code>aggDat</code>	MRExperiment storing data
<code>aggLevel</code>	aggregation level
<code>colorOptions</code>	phenotype selection options for color
<code>shapeOptions</code>	phenotype selection options for shape
<code>betadistance</code>	distance measured used for beta diversity analysis
<code>betaSettings</code>	input choices for beta diversity
<code>reset</code>	boolean reactive which resets the module if TRUE

Value

R code needed to generate the beta diversity plot

Author(s)

Janina Reeder

betaDiversityUI	<i>Beta Diversity module - UI</i>
-----------------	-----------------------------------

Description

Beta Diversity module - UI

Usage

```
betaDiversityUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

box holding the ui code

Author(s)

Janina Reeder

betaInput	<i>Server side for the analysis input module handling analysis control</i>
-----------	----------------------------------------------------------------------------

Description

Server side for the analysis input module handling analysis control

Usage

```
betaInput(input, output, session, meData, adonisOptions, reset)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
meData	MRExperiment object storing all data
adonisOptions	phenodata columns ready for adonis analysis
reset	reactive boolean determining if all inputs should be reset

Value

list holding all chosen values and the selected feature

Author(s)

Janina Reeder

betaInputUI	<i>Main beta analysis input module. Set up to handle all analysis tabs in the app depending on given parameters</i>
-------------	---------------------------------------------------------------------------------------------------------------------

Description

Main beta analysis input module. Set up to handle all analysis tabs in the app depending on given parameters

Usage

```
betaInputUI(id)
```

Arguments

id	element identifier - namespace
----	--------------------------------

Value

box containing ui element

Author(s)

Janina Reeder

buildEmptyPlotlyPlot	<i>Creates an empty plotly plot using the given labels on the x and y axis</i>
----------------------	--------------------------------------------------------------------------------

Description

Creates an empty plotly plot using the given labels on the x and y axis

Usage

```
buildEmptyPlotlyPlot(xaxis_text, ylab)
```

Arguments

xaxis_text	x axis label
ylab	y axis label

Value

call to plotly_empty

buildPlottingDF	<i>Sets up a dataframe used by several plotting functions by joining the required data with relevant phenotype data</i>
-----------------	-------------------------------------------------------------------------------------------------------------------------

Description

Sets up a dataframe used by several plotting functions by joining the required data with relevant phenotype data

Usage

```
buildPlottingDF(
  df,
  phenoTable,
  x_var = NULL,
  facet1 = NULL,
  facet2 = NULL,
  col_by = NULL,
  col_name = col_by,
  id_var = NULL
)
```

Arguments

df	dataframe storing plotting data values
phenoTable	pData of the MRexperiment; all following parameters must be a column of the phenoTable
x_var	main plotting variable
facet1	column-based faceting (can be NULL)
facet2	row-based faceting (can be NULL)
col_by	coloring factor (can be NULL)
col_name	character to be used as name for col_by
id_var	variable used to connect samples longitudinally (can be NULL)

Value

dataframe obtained by joining df and relevant columns of phenoTable

calculatePCAs	<i>Function to compute the PCAs for a given distance matrix</i>
---------------	-----------------------------------------------------------------

Description

Function to compute the PCAs for a given distance matrix

Usage

```
calculatePCAs(distmat, pcas)
```

Arguments

distmat the distance matrix
pcas 2-element vector of PCAs to include in results

Value

the x slot limited to pcas after calling stats::prcomp on distmat

Examples

```
data("mouseData", package = "metagenomeSeq")  
aggdat <- aggFeatures(mouseData, level = "genus")  
distmat <- computeDistMat(aggdat, dist_method = "bray")  
calculatePCAs(distmat, c(1,2))
```

computeCI_Interval *Helper function to calculate the confidence interval for a cor.test*

Description

Helper function to calculate the confidence interval for a cor.test

Usage

```
computeCI_Interval(num, mS, method)
```

Arguments

num number of samples
mS results of cor.test
method statistical method used for cor.test

Value

named vector holding lower and upper thresholds

computeDistMat	<i>Function to compute the distance matrix using vegdist from the vegan package</i>
----------------	-------------------------------------------------------------------------------------

Description

Function to compute the distance matrix using vegdist from the vegan package

Usage

```
computeDistMat(aggdat, dist_method, log = TRUE, nfeatures = nrow(aggmat))
```

Arguments

aggdat	aggregated MRExperiment
dist_method	distance method from vegan package (See ?vegan::vegdist for details)
log	transform count matrix to log2; default is TRUE
nfeatures	number of features to use; default is all

Value

distance as dist

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
computeDistMat(aggdat, dist_method = "bray")
```

corrAnalysis	<i>corr Analysis Module - server</i>
--------------	--------------------------------------

Description

corr Analysis Module - server

Usage

```
corrAnalysis(  
  input,  
  output,  
  session,  
  data,  
  levelOpts,  
  chosenLevel,  
  resetInput,  
  aggData  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
data	the main data object returned from data_input_module
levelOpts	available levels to aggregate on (depends on input data)
chosenLevel	previously selected level (passed from different instance)
resetInput	reactive boolean determining if reset is required
aggData	the aggregated MRExperiment object

Value

reactive holding code to be used in reports

corrAnalysisUI *corr Analysis Module - UI*

Description

corr Analysis Module - UI

Usage

```
corrAnalysisUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

fluidRow containing the ui code

Author(s)

Janina Reeder

Examples

```
corrAnalysisUI("coranalysis_id")
```

corrFeature *Scatterplot of two features*

Description

This function plots a scatterplot of two features along with sample correlation statistics.

Usage

```
corrFeature(
  aggdat,
  feat1,
  feat2,
  log = TRUE,
  method = c("spearman", "pearson", "kendall"),
  addRegression = TRUE,
  col_by = NULL,
  facet1 = NULL,
  facet2 = NULL,
  plotTitle = "",
  xlab = NULL,
  ylab = NULL,
  allowWebGL = TRUE,
  pwidth = 550,
  pheight = 200
)
```

Arguments

aggdat	aggregated MRExperiment
feat1	Feature 1.
feat2	Feature 2.
log	Log2 transform data. Default is TRUE.
method	Correlation coefficient. One of "spearman" (default), "pearson", or "kendall".
addRegression	boolean parameter indicating whether linear regression line should be drawn; default: TRUE
col_by	Phenotype for coloring.
facet1	Phenotype for facet 1.
facet2	Phenotype for facet 2.
plotTitle	Plot title. Default is no title.
xlab	X-axis label. Default is feat1.
ylab	Y-axis label. Default is feat2.
allowWebGL	boolean indicating if WebGL should be used for large data
pwidth	overall plot width; default is 550
pheight	overall plot height; default is 200

Value

list holding plotly plot and lm fit

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
corrFeature(aggdat, feat1 = "Bacteroides", feat2 = "Prevotella")
```

 corrInput

Server side for the analysis input module handling analysis control

Description

Server side for the analysis input module handling analysis control

Usage

```
corrInput(
  input,
  output,
  session,
  type,
  meData,
  facetOptions = NULL,
  reset,
  aggDat = reactive(NULL)
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
type	of the correlation (feature vs phenotype)
meData	MRExperiment object storing all data
facetOptions	named vector of available facet choices
reset	reactive boolean determining if all inputs should be reset
aggDat	aggregated MRExperiment object (default is NULL)

Value

list holding all chosen values and the selected feature

Author(s)

Janina Reeder

corrInputUI	<i>Main correlation analysis input module. Handles correlation analysis tab in the app</i>
-------------	--------------------------------------------------------------------------------------------

Description

Main correlation analysis input module. Handles correlation analysis tab in the app

Usage

```
corrInputUI(id, type)
```

Arguments

id	element identifier - namespace
type	determines if 'feature' or 'pheno' correlation

Value

box containing ui element

Author(s)

Janina Reeder

corrPhenotype	<i>Scatterplot of a feature and a phenotype</i>
---------------	-------------------------------------------------

Description

This function plots a scatterplot of a feature and a phenotype along with sample correlation statistics.

Usage

```
corrPhenotype(
  aggdat,
  feature,
  phenotype,
  log = TRUE,
  method = c("spearman", "pearson", "kendall"),
  addRegression = TRUE,
  col_by = NULL,
  facet1 = NULL,
  facet2 = NULL,
  plotTitle = "",
  xlab = NULL,
  ylab = NULL,
  allowWebGL = TRUE,
  pwidth = 550,
  pheight = 200
)
```

Arguments

aggdat	aggregated MRExperiment
feature	Feature input.
phenotype	Phenotype input (must be numeric)
log	Log2 transform data. Default is TRUE.
method	Correlation coefficient. One of "spearman" (default), "pearson", or "kendall".
addRegression	boolean parameter indicating whether linear regression line should be drawn; default: TRUE
col_by	Phenotype for coloring.
facet1	Phenotype for facet 1.
facet2	Phenotype for facet 2. (WIP/TODO)
plotTitle	Plot title. Default is no title.
xlab	X-axis label. Default is feat1.
ylab	Y-axis label. Default is feat2.
allowWebGL	boolean indicating if WebGL should be used for large data
pwidth	overall plot width; default is 550
pheight	overall plot height; default is 200

Value

list holding plotly plot and lm fit

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
corrPhenotype(aggdat, feature = "Bacteroides", phenotype = "relativeTime")
```

createHeader	<i>Makes header for R script</i>
--------------	----------------------------------

Description

This function makes the header for the report R script to be rendered by knitr into Rmarkdown and rendered into HTML, PDF, or Word.

Usage

```
createHeader(
  title = "MicrobiomeExplorer Report",
  author = "",
  date = "",
  data.source = "",
  output = getOption("me.reportformat"),
  toc = TRUE
)
```

Arguments

title	Title of the report.
author	Author of the report.
date	Date of the report.
data.source	R code used to obtain the dataset
output	Output of Rmarkdown file.
toc	Table of contents. Default is TRUE.

Details

This was adapted from <https://yihui.name/knitr/demo/stitch/>

Value

A character vector where each element is a line in the R script.

dataInput	<i>Main Data input server where the user selects files to upload to the app or connects to database</i>
-----------	---------------------------------------------------------------------------------------------------------

Description

Main Data input server where the user selects files to upload to the app or connects to database

Usage

```
dataInput(
  input,
  output,
  session,
  dataSource,
  dataFilterRep,
  qcRep,
  addPheno,
  resetReports
)
```

Arguments

input	module input
output	module output
session	app session
dataSource	reactive Value storing commands for loading data
dataFilterRep	reactive Value storing commands for filtering data
qcRep	reactive Value storing commands for producing qc plots
addPheno	reactive boolean keeping track of phenodata changes
resetReports	reactive boolean indicating whether reports need to be reset

Value

list of reactives containing the uploaded and filtered data as well as the filterChoices on phenotypes

Author(s)

Janina Reeder

dataInputUI	<i>Main Data input UI where the user selects files to upload to the app or connects to database</i>
-------------	-----------------------------------------------------------------------------------------------------

Description

Main Data input UI where the user selects files to upload to the app or connects to database

Usage

```
dataInputUI(id)
```

Arguments

id	module identifier
----	-------------------

Value

fluidRow holding UI interface

Author(s)

Janina Reeder

Examples

```
dataInputUI("datainput_id")
```

designPairs	<i>Produce design matrix of pairwise comparisons</i>
-------------	------------------------------------------------------

Description

This function takes in the levels of a factor phenotype and outputs a design matrix of all pairwise comparisons.

Usage

```
designPairs(levels)
```

Arguments

levels	Character vector of the levels of a factor phenotype
--------	------------------------------------------------------

Value

A model matrix

diffAnalysis	<i>diff Analysis Module - server</i>
--------------	--------------------------------------

Description

diff Analysis Module - server

Usage

```
diffAnalysis(
  input,
  output,
  session,
  data,
  levelOpts,
  chosenLevel,
  resetInput,
  aggData,
  normalizedData
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
data	the main data object returned from data_input_module
levelOpts	available levels to aggregate on (depends on input data)
chosenLevel	previously selected level (passed from different instance)
resetInput	reactive boolean determining if reset is required
aggData	the aggregated MRExperiment object
normalizedData	boolean indicating if normalization was done

Value

reactive holding code to be used in reports

Author(s)

Janina Reeder

diffAnalysisUI *Diff Analysis Module - UI*

Description

Diff Analysis Module - UI

Usage

```
diffAnalysisUI(id)
```

Arguments

id namespace identifier

Value

fluidRow containing the ui code

Author(s)

Janina Reeder

Examples

```
diffAnalysisUI("diffanalysis_id")
```

diffInput *Server side for the analysis input module handling analysis control*

Description

Server side for the analysis input module handling analysis control

Usage

```
diffInput(input, output, session, meData, facetOptions = NULL, reset)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
meData	MRExperiment object storing all data
facetOptions	named vector of available facet choices
reset	reactive boolean determining if all inputs should be reset

Value

list holding all chosen values and the selected feature

Author(s)

Janina Reeder

diffInputUI	<i>Main diffanalysis input module. Set up to handle diff analysis tabs in the app depending on given parameters</i>
-------------	---------------------------------------------------------------------------------------------------------------------

Description

Main diffanalysis input module. Set up to handle diff analysis tabs in the app depending on given parameters

Usage

```
diffInputUI(id)
```

Arguments

id	element identifier - namespace
----	--------------------------------

Value

box containing ui element

Author(s)

Janina Reeder

diffTable	<i>Differential analysis module server code</i>
-----------	-------------------------------------------------

Description

Differential analysis module server code

Usage

```
diffTable(
  input,
  output,
  session,
  aggDat,
  featLevel,
  diffSettings,
  reset,
  normalized
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
aggDat	aggregated MRExperiment
featLevel	chosen feature level (aggregation level)
diffSettings	reactive storing values selected in analysis input interface
reset	boolean reactive which resets the module if TRUE
normalized	boolean reactive indicating if data has been normalized

Value

list containing R code for analysis and for feature plots

Author(s)

Janina Reeder

diffTableUI

Differential Analysis module UI

Description

Differential Analysis module UI

Usage

```
diffTableUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

row containing the UI elements

Author(s)

Janina Reeder

extendPhenoData	<i>Extends existing phenodata for an object</i>
-----------------	-------------------------------------------------

Description

This function adds phenotype data to the phenoData slot in an MRExperiment object.

Usage

```
extendPhenoData(MRobj, phenodata = NULL)
```

Arguments

MRobj	An MRExperiment object.
phenodata	Phenotype data frame or file path.

Value

An updated MRExperiment object.

featAbundance	<i>Feature plot module - server</i>
---------------	-------------------------------------

Description

Feature plot module - server

Usage

```
featAbundance(  
  input,  
  output,  
  session,  
  aggDat,  
  featLevel,  
  intraSettings,  
  selectedFeat,  
  featName,  
  numOfFeats,  
  ylabMode,  
  normalizedData,  
  reset  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
aggDat	aggregated MRExperiment
featLevel	chosen feature level (aggregation level)
intraSettings	analysis settings passed over from analysis input module
selectedFeat	feature selected via drop down element of analysis input
featName	plotly click event passed via relative abundance
numOfFeats	number of features shown in relative abundance plot (affects plotly click data)
ylabMode	character indication if raw \"Reads\" or \"Percentage\" should be shown
normalizedData	boolean indicating whether data has been normalized
reset	boolean reactive which resets the module if TRUE

Value

R code needed to build the feature plot

Author(s)

Janina Reeder

featAbundanceUI	<i>Feature plot module - UI</i>
-----------------	---------------------------------

Description

Feature plot module - UI

Usage

```
featAbundanceUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

box holding the UI code

featureAnalysis *feature Analysis Module - server*

Description

feature Analysis Module - server

Usage

```
featureAnalysis(  
  input,  
  output,  
  session,  
  data,  
  resetInput,  
  aggData,  
  normalizedData  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
data	the main data object returned from data_input_module
resetInput	reactive boolean determining if reset is required
aggData	the aggregated MRExperiment object
normalizedData	boolean indicating if normalization was done

Value

reactive holding code to be used in reports

Author(s)

Janina Reeder

featureAnalysisUI *feature Analysis Module - UI*

Description

feature Analysis Module - UI

Usage

```
featureAnalysisUI(id)
```

Arguments

id namespace identifier

Value

fluidRow containing the ui code

Author(s)

Janina Reeder

Examples

```
featureAnalysisUI("featureanalysis_id")
```

featureCorr

Feature correlation analysis server module

Description

Feature correlation analysis server module

Usage

```
featureCorr(
  input,
  output,
  session,
  aggDat,
  colorOptions,
  corFeatBase,
  corFeat2,
  corFacet1,
  corFacet2,
  corMethod,
  reset
)
```

Arguments

input	module input
output	module output
session	app session
aggDat	aggregated MRExperiment
colorOptions	reactive storing filters available via data input
corFeatBase	first correlation feature
corFeat2	second correlation feature
corFacet1	first correlation facet

corFacet2	second correlation facet
corMethod	correlation method to use
reset	boolean reactive which resets the module if TRUE

Value

R code used to do the correlation analysis (character)

Author(s)

Janina Reeder

featureCorrUI	<i>Feature correlation analysis module UI</i>
---------------	-----------------------------------------------

Description

Feature correlation analysis module UI

Usage

```
featureCorrUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

box containing the UI elements

Author(s)

Janina Reeder

featureInput	<i>Server side for the feature analysis input module</i>
--------------	----------------------------------------------------------

Description

Server side for the feature analysis input module

Usage

```
featureInput(
  input,
  output,
  session,
  meData,
  facetOptions = NULL,
  reset,
  aggDat = reactive(NULL)
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
meData	MRExperiment object storing all data
facetOptions	named vector of available facet choices
reset	reactive boolean determining if all inputs should be reset
aggDat	aggregated MRExperiment object (default is NULL)

Value

list holding all chosen values and the selected feature

Author(s)

Janina Reeder

featureInputUI	<i>Main feature analysis input module. Set up to handle all analysis tabs in the app depending on given parameters</i>
----------------	------------------------------------------------------------------------------------------------------------------------

Description

Main feature analysis input module. Set up to handle all analysis tabs in the app depending on given parameters

Usage

```
featureInputUI(id)
```

Arguments

id	element identifier - namespace
----	--------------------------------

Value

box containing ui element

Author(s)

Janina Reeder

featureTable	<i>Feature table module server code</i>
--------------	-----------------------------------------

Description

Feature table module server code

Usage

```
featureTable(input, output, session, meData, featureModRep)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
meData	MRExperiment storing the data
featureModRep	reactiveValue storing modifications performed on fData

Value

feature table server fragment - no return value

Author(s)

Janina Reeder

featureTableUI	<i>Feature table UI module</i>
----------------	--------------------------------

Description

Feature table UI module

Usage

```
featureTableUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

fluidRow containing the UI code for feature tables

Author(s)

Janina Reeder

Examples

```
featureTableUI("feature_id")
```

fileUpload

Module handling file upload for the application: server

Description

Module handling file upload for the application: server

Usage

```
fileUpload(
  input,
  output,
  session,
  meData,
  meName,
  initializeData,
  addPheno,
  dataSource,
  resetFile = reactive(NULL)
)
```

Arguments

input	module input
output	module output
session	app session
meData	main reactive storing the MRexperiment data
meName	main reactive storing the filename uploaded
initializeData	reactiveVal keeping track of new uploads to reset data
addPheno	reactiveVal keeping track of phenodata changes
dataSource	reactive Value storing commands for loading data
resetFile	indicating if module should be reset

Value

boolean denoting successful upload of a file

Author(s)

Janina Reeder

fileUploadUI	<i>Module handling file upload for the application: UI In a deployed version this module should be replaced with database access</i>
--------------	--------------------------------------------------------------------------------------------------------------------------------------

Description

Module handling file upload for the application: UI In a deployed version this module should be replaced with database access

Usage

```
fileUploadUI(id)
```

Arguments

id	module identifier
----	-------------------

Value

div holding ui elements

Author(s)

Janina Reeder

filterByPheno	<i>Function to filter the MRexperiment by certain phenotype values</i>
---------------	------------------------------------------------------------------------

Description

Function to filter the MRexperiment by certain phenotype values

Usage

```
filterByPheno(MRobj, rm_phenovalues)
```

Arguments

MRobj	the MRexperiment to subset
rm_phenovalues	list of named vectors with names corresponding to column names in pData and values representing phenotypes within the column

Value

the filtered MRobj

Author(s)

Janina Reeder

Examples

```
data("mouseData", package = "metagenomeSeq")
filterByPheno(MRobj = mouseData,
  rm_phenovalues = list("diet" = c("BK"), "mouseID" = c("PM1", "PM10")))
```

filterMEData*Function to filter the MRExperiment data by numerical parameters*

Description

Function to filter the MRExperiment data by numerical parameters

Usage

```
filterMEData(MRobj, minpresence = 1, minfeats = 2, minreads = 2)
```

Arguments

MRobj	MRExperiment object to filter
minpresence	minimum sample presence per feature
minfeats	minimum number of features per sample
minreads	minimum number of reads per sample

Value

the filtered MRobj

Author(s)

Janina Reeder

Examples

```
data("mouseData", package = "metagenomeSeq")
filterMEData(MRobj = mouseData, minpresence = 4, minfeats = 300)
```

generateReport	<i>Generates report</i>
----------------	-------------------------

Description

This function generates the pieces of the report, which includes the R script, Rmarkdown file, and any Rmarkdown outputs.

Usage

```
generateReport(  
  rcode,  
  filename = "report",  
  dir = "out",  
  title = "MicrobiomeExplorer Report",  
  author = "",  
  date = "`r format(Sys.time(), '%d %B, %Y')`",  
  data.source = "",  
  output = c("html_document"),  
  toc = TRUE,  
  intro_text = NULL  
)
```

Arguments

rcode	A named list where each element corresponds to a different analysis (Alpha diversity, Beta diversity). The name of the list is used to denote the first part of the code chunks in each analysis section (alpha, beta). Each element is itself a list of R commands corresponding to a code chunk.
filename	Name of output files. Default is "report".
dir	Directory of output. Default is "out".
title	Title of the report.
author	Author of the report.
date	Date of the report.
data.source	R code used to obtain the dataset
output	Output of Rmarkdown file. Options defined in global.R
toc	Table of contents. Default is TRUE.
intro_text	Introductory text to include with the report (optional)

Details

Adapted from <https://yihui.name/knitr/demo/stitch/>

Value

A character vector where each element is a line in the R script.

getFeatModCode	<i>Helper function returning the fData modifications as strings for report generation</i>
----------------	-------------------------------------------------------------------------------------------

Description

Helper function returning the fData modifications as strings for report generation

Usage

```
getFeatModCode(featureanno)
```

Arguments

featureanno type of feature annotation; values are "Mark unknown" or "Roll down"

Value

String containing R code performing the modification

getFileType	<i>Helper function assigning different file extensions to specific short texts identifying the types</i>
-------------	----------------------------------------------------------------------------------------------------------

Description

Helper function assigning different file extensions to specific short texts identifying the types

Usage

```
getFileType(fileext)
```

Arguments

fileext the file extension found after '.'

Value

character string for the filetype

Author(s)

Janina Reeder

getFilterChoices	<i>Helper function to filter phenodata for interesting phenotypes to be used for filtering or subsetting</i>
------------------	--------------------------------------------------------------------------------------------------------------

Description

Helper function to filter phenodata for interesting phenotypes to be used for filtering or subsetting

Usage

```
getFilterChoices(MRobj)
```

Arguments

MRobj the MRExperiment storing the data

Value

list of named vectors with names being pData column headers and values being unique entries; columns with only one entry or those with different values for each samples are omitted

Author(s)

Janina Reeder

getLegendLevel	<i>Function to find a non-empty facet in the last row. This will be the one to be connected to the plot legend to avoid duplicates within</i>
----------------	-----------------------------------------------------------------------------------------------------------------------------------------------

Description

Function to find a non-empty facet in the last row. This will be the one to be connected to the plot legend to avoid duplicates within

Usage

```
getLegendLevel(df2, facets, facet2s)
```

Arguments

df2 plotting data frame
facets column facets
facet2s row facets

Value

the name of the column-based facet which can be used as legend

getPhenoChanges	<i>Helper function returning the code used to modify the data types of the pheno table</i>
-----------------	--------------------------------------------------------------------------------------------

Description

Helper function returning the code used to modify the data types of the pheno table

Usage

```
getPhenoChanges(phenotype, datatype)
```

Arguments

phenotype	name of the phenotype column header
datatype	variable type to assign to column

Value

String storing code to perform modification

Author(s)

Janina Reeder

getPhenoModCode	<i>Helper function returning the code used to modify the phenotable as a string</i>
-----------------	-------------------------------------------------------------------------------------

Description

Helper function returning the code used to modify the phenotable as a string

Usage

```
getPhenoModCode(name, pheno1, pheno2)
```

Arguments

name	interaction name
pheno1	first interaction phenotype
pheno2	second interaction phenotype

Value

String storing code to perform modification

Author(s)

Janina Reeder

getWidths	<i>Helper function to account for issues plotly has with very small widths (these end up being 1 and cover the entire plotting area)</i>
-----------	------------------------------------------------------------------------------------------------------------------------------------------

Description

Helper function to account for issues plotly has with very small widths (these end up being 1 and cover the entire plotting area)

Usage

```
getWidths(df2, facets, x_var, drop = TRUE)
```

Arguments

df2	dataframe storing plotting data
facets	column facets
x_var	x variable
drop	passed on as .drop to dplyr::group_by

Value

widths for each facet

heatmapInput	<i>Server side for the analysis input module handling analysis control</i>
--------------	----------------------------------------------------------------------------

Description

Server side for the analysis input module handling analysis control

Usage

```
heatmapInput(input, output, session, meData, reset, aggDat = reactive(NULL))
```

Arguments

input	shiny input
output	shiny output
session	shiny session
meData	MRExperiment object storing all data
reset	reactive boolean determining if all inputs should be reset
aggDat	aggregated MRExperiment object (default is NULL)

Value

list holding all chosen values and the selected feature

Author(s)

Janina Reeder

heatmapInputUI	<i>Heatmap analysis input module. Set up to handle all analysis tabs in the app depending on given parameters</i>
----------------	-------------------------------------------------------------------------------------------------------------------

Description

Heatmap analysis input module. Set up to handle all analysis tabs in the app depending on given parameters

Usage

```
heatmapInputUI(id)
```

Arguments

id	element identifier - namespace
----	--------------------------------

Value

box containing ui element

Author(s)

Janina Reeder

interAnalysis	<i>inter Analysis Module - server</i>
---------------	---------------------------------------

Description

inter Analysis Module - server

Usage

```
interAnalysis(  
  input,  
  output,  
  session,  
  data,  
  levelOpts,  
  chosenLevel,  
  resetInput,  
  aggData  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
data	the main data object returned from data_input_module
levelOpts	available levels to aggregate on (depends on input data)
chosenLevel	previously selected level (passed from different instance)
resetInput	reactive boolean determining if reset is required
aggData	the aggregated MRExperiment object

Value

reactive holding code to be used in reports

interAnalysisUI *inter Analysis Module - UI*

Description

inter Analysis Module - UI

Usage

```
interAnalysisUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

fluidRow containing the ui code

Author(s)

Janina Reeder

Examples

```
interAnalysisUI("interanalysis_id")
```

intraAnalysis *Intra Analysis Module - server*

Description

Intra Analysis Module - server

Usage

```
intraAnalysis(  
  input,  
  output,  
  session,  
  data,  
  levelOpts,  
  chosenLevel,  
  resetInput,  
  aggData,  
  normalizedData  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
data	the main data object returned from data_input_module
levelOpts	available levels to aggregate on (depends on input data)
chosenLevel	previously selected level (passed from different instance)
resetInput	reactive boolean determining if reset is required
aggData	the aggregated MRExperiment object
normalizedData	boolean indicating if normalization was done

Value

reactive holding code to be used in reports

Author(s)

Janina Reeder

intraAnalysisUI	<i>Intra Analysis Module - UI</i>
-----------------	-----------------------------------

Description

Intra Analysis Module - UI

Usage

```
intraAnalysisUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

fluidRow containing the ui code

Author(s)

Janina Reeder

Examples

```
intraAnalysisUI("intraanalysis_id")
```

intraInput	<i>Server side for the intra analysis input module</i>
------------	--------------------------------------------------------

Description

Server side for the intra analysis input module

Usage

```
intraInput(  
  input,  
  output,  
  session,  
  meData,  
  facetOptions = NULL,  
  reset,  
  aggDat = reactive(NULL)  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
meData	MRExperiment object storing all data
facetOptions	named vector of available facet choices
reset	reactive boolean determining if all inputs should be reset
aggDat	aggregated MRExperiment object (default is NULL)

Value

list holding all chosen values and the selected feature

Author(s)

Janina Reeder

intraInputUI	<i>Main intra analysis input module. Set up to handle all analysis tabs in the app depending on given parameters</i>
--------------	----------------------------------------------------------------------------------------------------------------------

Description

Main intra analysis input module. Set up to handle all analysis tabs in the app depending on given parameters

Usage

```
intraInputUI(id)
```

Arguments

id	element identifier - namespace
----	--------------------------------

Value

box containing ui element

Author(s)

Janina Reeder

longAnalysis *long Analysis Module - server*

Description

long Analysis Module - server

Usage

```
longAnalysis(  
  input,  
  output,  
  session,  
  data,  
  levelOpts,  
  chosenLevel,  
  resetInput,  
  aggData,  
  normalizedData  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
data	the main data object returned from data_input_module
levelOpts	available levels to aggregate on (depends on input data)
chosenLevel	previously selected level (passed from longerent instance)
resetInput	reactive boolean determining if reset is required
aggData	the aggregated MRExperiment object
normalizedData	boolean indicating if normalization was done

Value

reactive holding code to be used in reports

Author(s)

Janina Reeder

longAnalysisUI	<i>Long Analysis Module - UI</i>
----------------	----------------------------------

Description

Long Analysis Module - UI

Usage

```
longAnalysisUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

fluidRow containing the ui code

Author(s)

Janina Reeder

Examples

```
longAnalysisUI("longanalysis_id")
```

longInput	<i>Server side for the analysis input module handling analysis control</i>
-----------	----------------------------------------------------------------------------

Description

Server side for the analysis input module handling analysis control

Usage

```
longInput(  
  input,  
  output,  
  session,  
  meData,  
  facetOptions = NULL,  
  reset,  
  aggDat = reactive(NULL)  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
meData	MRExperiment object storing all data
facetOptions	named vector of available facet choices
reset	reactive boolean determining if all inputs should be reset
aggDat	aggregated MRExperiment

Value

list holding all chosen values and the selected feature

Author(s)

Janina Reeder

longInputUI	<i>Main diffanalysis input module. Set up to handle diff analysis tabs in the app depending on given parameters</i>
-------------	---------------------------------------------------------------------------------------------------------------------

Description

Main diffanalysis input module. Set up to handle diff analysis tabs in the app depending on given parameters

Usage

```
longInputUI(id)
```

Arguments

id	element identifier - namespace
----	--------------------------------

Value

box containing ui element

Author(s)

Janina Reeder

longResults	<i>Longitudinal analysis module server code</i>
-------------	-------------------------------------------------

Description

Longitudinal analysis module server code

Usage

```
longResults(  
  input,  
  output,  
  session,  
  aggDat,  
  featLevel,  
  longSettings,  
  normalizedData,  
  reset  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
aggDat	aggregated MRExperiment
featLevel	chosen feature level (aggregation level)
longSettings	reactive storing values selected in analysis input interface
normalizedData	reactive boolean indicating if data has been normalized
reset	boolean reactive which resets the module if TRUE

Value

list containing R code for analysis and for feature plots

Author(s)

Janina Reeder

longResultsUI	<i>Longitudinal Analysis module UI</i>
---------------	----------------------------------------

Description

Longitudinal Analysis module UI

Usage

```
longResultsUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

row containing the UI elements

Author(s)

Janina Reeder

makeQCPlot	<i>Plots sequencing statistics scatterplot</i>
------------	------------------------------------------------

Description

This function makes a scatterplot of read and feature counts for each sample. It was adjusted based on original work by Mo Huang

Usage

```
makeQCPlot(  
  MObj,  
  col_by = NULL,  
  log = "none",  
  filter_feat = 0,  
  filter_read = 0,  
  allowWebGL = TRUE,  
  pwidth = 550,  
  pheight = 550  
)
```

Arguments

MRobj	metagenomeSeq object to be plotted
col_by	factor by which to color the points
log	character indicating which (if any) axes should be shown as log
filter_feat	Numeric Y-coordinate to draw horizontal dashed line to indicate feature filtering. If 0 (default), no line is drawn.
filter_read	Numeric X-coordinate to draw vertical dashed line to indicate read count filtering. If 0 (default), no line is drawn.
allowWebGL	boolean indicating if WebGL should be added
pwidth	overall plot width; default is 550 (125 are added for legend)
pheight	overall plot height; default is 550

Value

the plotly QC plot

Author(s)

Janina Reeder

Examples

```
data("mouseData", package = "metagenomeSeq")
makeQCPlot(mouseData)
```

normalizeData	<i>Calls appropriate normalization functions depending on input parameter The two available methods included in the package are based on either calculating proportions or by using cumulative sum scaling (CSS), Paulson, et al. Nat Meth 2013.</i>
---------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Description

Calls appropriate normalization functions depending on input parameter The two available methods included in the package are based on either calculating proportions or by using cumulative sum scaling (CSS), Paulson, et al. Nat Meth 2013.

Usage

```
normalizeData(MRobj, norm_method)
```

Arguments

MRobj	the MRExperiment
norm_method	method to use for normalization; CSS or Proportional

Value

the normalized MRobj

Examples

```
data("mouseData", package = "metagenomeSeq")
normalizeData(mouseData, norm_method = "CSS")
```

parseInteractionName *Helper function used to build a correct interactionName based on the chosen columns*

Description

Helper function used to build a correct interactionName based on the chosen columns

Usage

```
parseInteractionName(interactionName)
```

Arguments

interactionName
as chosen by user. This may not be good to store internally

Value

updated interactionName or warning/error string

phenotypeCorr *Phenotype correlation analysis server module*

Description

Phenotype correlation analysis server module

Usage

```
phenotypeCorr(  
  input,  
  output,  
  session,  
  aggDat,  
  colorOptions,  
  corFeatBase,  
  corPheno,  
  corFacet1,  
  corFacet2,  
  corMethod,  
  reset  
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
aggDat	aggregated MRExperiment
colorOptions	reactive storing filters available via data input
corFeatBase	first correlation feature
corPheno	correlation phenotype
corFacet1	first correlation facet
corFacet2	second correlation facet
corMethod	correlation method to use
reset	boolean reactive which resets the module if TRUE

Value

R code used to do the correlation analysis (character)

Author(s)

Janina Reeder

phenotypeCorrUI *Phenotype correlation analysis module*

Description

Phenotype correlation analysis module

Usage

```
phenotypeCorrUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

box containing the UI element

Author(s)

Janina Reeder

phenotypeTable *Phenotype table server module*

Description

Phenotype table server module

Usage

```
phenotypeTable(input, output, session, meData, phenoModRep, addPheno)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
meData	MRExperiment storing the data
phenoModRep	reactive Value storing any phenotable modifications made
addPheno	reactive boolean keeping track of pheno data modifications

Value

phenotype table server fragment - no return value

Author(s)

Janina Reeder

phenotypeTableUI *Phenotype table UI module*

Description

Phenotype table UI module

Usage

```
phenotypeTableUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

fluidRow holding the ui code

Author(s)

Janina Reeder

Examples

```
phenotypeTableUI("phenotype_id")
```

plotAbundance	<i>Plot relative abundance</i>
---------------	--------------------------------

Description

This function plots the relative abundance of the top abundant features.

Usage

```
plotAbundance(
  aggdat,
  level,
  x_var = "SAMPLE_ID",
  ind = seq_len(10),
  plotTitle = "",
  ylab = "Reads",
  facet1 = NULL,
  facet2 = NULL,
  source = "A",
  pwidth = 650,
  pheight = 150
)
```

Arguments

aggdat	aggregated MRExperiment object
level	Feature level.
x_var	Phenotype to aggregate over on X-axis. Default by "SAMPLE_ID".
ind	Indices of top abundant features to plot. Rest of features are aggregated and displayed as "other".
plotTitle	Plot title. Default shows no title.
ylab	Y-axis label. Default is "Reads"
facet1	Phenotype for facet 1.
facet2	Phenotype for facet 2.
source	name of the plot (needed for event handling); default is "A"
pwidth	overall plot width; default is 650
pheight	overall plot height; default is 150

Value

plotly plot

Author(s)

Janina Reeder

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
plotAbundance(aggdat, level = "genus", x_var = "diet")
```

plotAlpha

Plot alpha diversity

Description

This function plots the alpha diversity. See `?vegan::diversity` for details on the available index

Usage

```
plotAlpha(
  aggdat,
  level,
  index = c("shannon", "simpson", "invsimpson", "richness"),
  x_var = "SAMPLE_ID",
  ylab = index,
  col_by = NULL,
  facet1 = NULL,
  facet2 = NULL,
  plotTitle = "",
  pwidth = 500,
  pheight = 150
)
```

Arguments

aggdat	aggregated MRExperiment
level	Feature level
index	Diversity index, one of "shannon", "simpson", "invsimpson" or "richness" (=number of features). Default is "shannon".
x_var	Phenotype to aggregate over on X-axis. Default by "SAMPLE_ID".
ylab	Y-axis label. Default is "Reads".
col_by	Phenotype for coloring.
facet1	Phenotype for facet 1.
facet2	Phenotype for facet 2.
plotTitle	Plot title. By default, no title is used.
pwidth	overall plot width; default is 650
pheight	overall plot height; default is 150

Value

plotly plot object

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
plotAlpha(aggdat, level = "genus", index = "shannon", x_var = "diet")
```

plotAvgAbundance	<i>Plot average relative abundance</i>
------------------	----------------------------------------

Description

This function plots the average relative abundance of the top abundant features.

Usage

```
plotAvgAbundance(
  aggdat,
  level,
  ind = seq_len(10),
  plotTitle = "",
  ylab = "Reads",
  facet1 = NULL,
  facet2 = NULL,
  source = "A",
  pwidth = 500,
  pheight = 150
)
```

Arguments

aggdat	aggregated MRExperiment object
level	Feature level.
ind	Indices of top abundant features to plot. Rest of features are aggregated and displayed as "other".
plotTitle	Plot title. Default shows no title.
ylab	Y-axis label. Default is "Reads"
facet1	Phenotype for facet 1.
facet2	Phenotype for facet 2.
source	name of the plot (needed for event handling); default is "A"
pwidth	overall plot width; default is 500
pheight	overall plot height; default is 150

Value

plotly plot

Author(s)

Janina Reeder

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
plotAvgAbundance(aggdat, level = "genus")
```

plotBeta

*Plot beta diversity***Description**

This functions plots the beta diversity as a PCoA plot.

Usage

```
plotBeta(
  aggdat,
  dim = c(1, 2),
  log = TRUE,
  dist_method = "bray",
  pcas = NULL,
  nfeatures = nrow(aggdat),
  col_by = NULL,
  shape_by = NULL,
  plotTitle = "",
  xlab = NULL,
  ylab = NULL,
  pt_size = 8,
  plotText = NULL,
  confInterval = NULL,
  allowWebGL = TRUE,
  pwidth = 550,
  pheight = 550
)
```

Arguments

aggdat	aggregated MRExperiment
dim	Vector of length 2 specifying which dimensions to plot.
log	Log2 transform data. Default is TRUE.
dist_method	Which distance method to use. See <code>?vegan::vegdist</code> for more <code>vegdist()</code> for options. Default is "bray".
pcas	precalculated pcas to avoid recalculation via CalcPCs
nfeatures	Number of top features in terms of standard deviation. Default is all.
col_by	Phenotype for coloring.
shape_by	Phenotype for shape.
plotTitle	Plot title. By default, becomes PCoA (codedist.method).
xlab	X-axis label. By default, shows dimension and percent variance explained.

ylab	Y-axis label. By default, shows dimension and percent variance explained.
pt_size	the size of the markers
plotText	adonis text to be added to plot
confInterval	numeric value indicating confidence level for ellipses
allowWebGL	boolean indicating if WebGL should be used
pwidth	overall plot width; default is 550 (125 are added for legend)
pheight	overall plot height; default is 550

Value

plotly plot object

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
plotBeta(aggdat)
```

plotHeatmap

Plot heatmap

Description

This function plots a heatmap of feature abundance.

Usage

```
plotHeatmap(
  aggdat,
  features = NULL,
  log = TRUE,
  sort_by = c("Fano", "MAD", "Variance"),
  nfeat = 50,
  col_by = NULL,
  row_by = NULL,
  plotTitle = ""
)
```

Arguments

aggdat	aggregated MRExperiment
features	Vector of features to plot. If NULL, the top 'nfeat' features in terms of 'sort_by' will be plotted.
log	Log2 transform data. Default is TRUE.
sort_by	Dispersion measure to sort features, one of "Fano", "MAD", and "Variance"
nfeat	Number of features to display. Default is 50.
col_by	Vector of phenotypes for coloring.
row_by	Name of feature level for coloring.
plotTitle	Plot title. By default, no title.

Value

plotly heatmap

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
plotHeatmap(aggdat, sort_by = "Fano")
```

plotLongFeature	<i>Plot longitudinal features</i>
-----------------	-----------------------------------

Description

This function plots the reads of a particular feature over different time points.

Usage

```
plotLongFeature(
  aggdat,
  feature,
  x_var,
  id_var = "SAMPLE_ID",
  plotTitle = NULL,
  ylab = "Reads",
  log = FALSE,
  showLines = TRUE,
  fixedHeight = NULL,
  x_levels = NULL,
  pwidth = 650
)
```

Arguments

aggdat	aggregated MRExperiment
feature	Feature to plot.
x_var	Phenotype to show along on X-axis.
id_var	phenotype used to connect data points. Default is "SAMPLE_ID"
plotTitle	Plot title. Default shows no title.
ylab	Y-axis label. Default is "Reads"
log	Log2 transform data. Default is FALSE.
showLines	add lines between the points
fixedHeight	sets a specific plot height (differential analysis)
x_levels	restrict to specific levels of x_var (differential analysis)
pwidth	overall plot width; default is 650

Value

plotly object holding long feature plot

Author(s)

Janina Reeder, Mo Huang

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
plotLongFeature(aggdat, feature = "Prevotella", x_var = "diet",
                id_var = "mouseID")
```

plotlyHistogram

Function plotting a plotly histogram on the given histvalue

Description

Function plotting a plotly histogram on the given histvalue

Usage

```
plotlyHistogram(
  histvalue,
  plotTitle,
  xaxisTitle = "",
  yaxisTitle = "",
  pwidth = 200,
  pheight = 200
)
```

Arguments

histvalue	the value to plot as a histogram
plotTitle	title of the plot
xaxisTitle	name of xaxis; default is ""
yaxisTitle	name of yaxis; default is ""
pwidth	overall plot width; default is 200
pheight	overall plot height; default is 200

Value

plotly plot object

Examples

```
data("mouseData", package = "metagenomeSeq")
plotlyHistogram(histvalue = colSums(MRcounts(mouseData) > 0),
  plotTitle = "Feature distribution",
  xaxisTitle = "features", yaxisTitle = "frequency")
```

plotlySampleBarplot *Function plotting a barplot showing number of OTUs per samples*

Description

Function plotting a barplot showing number of OTUs per samples

Usage

```
plotlySampleBarplot(  
  MObj,  
  col_by = NULL,  
  xaxisTitle = "",  
  yaxisTitle = "",  
  pwidth = 600,  
  pheight = 450,  
  sortbyfreq = FALSE,  
  pheno_sort = NULL,  
  x_levels = NULL  
)
```

Arguments

MObj	containing data to plot
col_by	phenotype to color bars by; default is NULL
xaxisTitle	name of xaxis; default is ""
yaxisTitle	name of yaxis; default is ""
pwidth	overall plot width; default is 600
pheight	overall plot height; default is 450
sortbyfreq	boolean determining if bars should be sorted by frequency; default is FALSE
pheno_sort	order of pheno levels to sort by; ignored if sortbyfreq is TRUE
x_levels	character vector holding x values in order to be shown

Value

plotly plot object

Examples

```
data("mouseData", package = "metagenomeSeq")  
plotlySampleBarplot(mouseData)
```

plotSingleFeature *Plot features*

Description

This function plots the reads of a particular feature or set of features.

Usage

```
plotSingleFeature(  
  aggdat,  
  feature = "other",  
  x_var = "SAMPLE_ID",  
  ind = seq_len(10),  
  plotTitle = NULL,  
  ylab = "Reads",  
  xlab = NULL,  
  facet1 = NULL,  
  facet2 = NULL,  
  log = FALSE,  
  showPoints = FALSE,  
  fixedHeight = NULL,  
  x_levels = NULL,  
  pwidth = 500  
)
```

Arguments

aggdat	aggregated MRExperiment
feature	Feature to plot.
x_var	Phenotype to aggregate over on X-axis. Default by "SAMPLE_ID".
ind	Indices of top abundant features to plot. Needed to determine appropriate color
plotTitle	Plot title. Default shows no title.
ylab	Y-axis label. Default is "Reads"
xlab	X-axis label. If NULL, x_var will be used as label.
facet1	Phenotype for facet 1.
facet2	Phenotype for facet 2.
log	Log2 transform data. Default is FALSE.
showPoints	add points for each sample on plot
fixedHeight	sets a specific plot height (differential analysis)
x_levels	restrict to specific levels of x_var (differential analysis)
pwidth	overall plot width; default is 650

Value

plotly plot object

Author(s)

Janina Reeder

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
plotSingleFeature(aggdat, feature = "Prevotella", x_var = "diet")
```

readData

*Reads in data***Description**

This function reads in an MRexperiment object saved as an RDS file, a Biom file, or a tab - delimited count matrix with features as rows and samples as columns.

Usage

```
readData(filepath, type = "RDS")
```

Arguments

filepath	Relative or absolute file path of data object.
type	The type of file to be read; default is "RDS", other options are "RDATA", "BIOM", "TAB", "CSV"

Value

An MRexperiment object.

relAbundance

*Relative abundance plot module - server***Description**

Relative abundance plot module - server

Usage

```
relAbundance(
  input,
  output,
  session,
  aggDat,
  featLevel,
  intraSettings,
  normalizedData,
  reset
)
```

Arguments

input	shiny input
output	shiny output
session	shiny session
aggDat	aggregated MRExperiment
featLevel	chosen feature level (aggregation level)
intraSettings	analysis input settings passed over to this module
normalizedData	boolean indicating whether data has been normalized
reset	boolean reactive which resets the module if TRUE

Value

list storing plot clicks and number of features displayed (passed to feature plot module) as well as the R code to make plot

relAbundanceUI	<i>Relative abundance plot module - UI</i>
----------------	--------------------------------------------

Description

Relative abundance plot module - UI

Usage

```
relAbundanceUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

box containing the ui code

Author(s)

Janina Reeder

replaceWithUnknown	<i>Helper function to replace any un-annotated features with the term unknown</i>
--------------------	-----------------------------------------------------------------------------------

Description

Helper function to replace any un-annotated features with the term unknown

Usage

```
replaceWithUnknown(feacol)
```

Arguments

feacol vector of entries to be replaced where needed (fData column)

Value

modified feacol

Author(s)

Janina Reeder

Examples

```
data("mouseData", package = "metagenomeSeq")
feacol <- fData(mouseData)[["genus"]]
feacol[feacol == "NA"] <- NA
replaceWithUnknown(feacol)
```

reportList	<i>Report tab module server</i>
------------	---------------------------------

Description

Report tab module server

Usage

```
reportList(
  input,
  output,
  session,
  dataSource,
  preprocessRep,
  qcRep,
  analysisRep,
  aggIndex,
  reset
)
```

Arguments

input	module input
output	module output
session	app session
dataSource	R code to obtain data for rendering
preprocessRep	R code containing preprocessing steps of data
qcRep	R Code to generate QC plots
analysisRep	R Code to generate all analyses saved to reports
aggIndex	boolean value representing aggregation steps in analysisRep
reset	boolean reactive which resets the module if TRUE

Value

report list server fragment - no return value

Author(s)

Janina Reeder

reportListUI	<i>report tab ui</i>
--------------	----------------------

Description

report tab ui

Usage

```
reportListUI(id)
```

Arguments

id	namespace identifier
----	----------------------

Value

fluidRow holding ui elements

Author(s)

Janina Reeder

Examples

```
reportListUI("reportlist_id")
```

reportRow	<i>Report Row</i>
-----------	-------------------

Description

Report Row

Usage

```
reportRow(input, output, session, type, content)
```

Arguments

input	module input
output	module output
session	app session
type	boolean indicating whether checkbox should be included
content	R code to show

Value

reactive boolean indicating whether row is selected

Author(s)

Janina Reeder

reportRowUI	<i>Report row module consisting of a checkbox, image and description/R code area</i>
-------------	--------------------------------------------------------------------------------------

Description

Report row module consisting of a checkbox, image and description/R code area

Usage

```
reportRowUI(id, type)
```

Arguments

id	namespace identifier
type	boolean indicating if a selector checkbox should be added

Value

div holding the UI code

Author(s)

Janina Reeder

rollDownFeatures	<i>Helper function which rolls down annotated from closest higher order with annotation</i>
------------------	---------------------------------------------------------------------------------------------

Description

Helper function which rolls down annotated from closest higher order with annotation

Usage

```
rollDownFeatures(featrow)
```

Arguments

featrow vector of entries to be replaced where needed (fData row)

Value

modified featurerow

Author(s)

Janina Reeder

Examples

```
data("mouseData", package = "metagenomeSeq")
featrow <- fData(mouseData)[5,]
rollDownFeatures(featrow)
```

runDiffTest	<i>Performs differential abundance testing</i>
-------------	------------------------------------------------

Description

This function performs differential abundance testing between groups of a specified phenotype. Four methods are available: limma, Kruskal-Wallis, ZILN and DESeq2 (see details).

Usage

```
runDiffTest(
  aggdat,
  level,
  phenotype,
  phenolevels = NULL,
  log = TRUE,
  coef = NULL,
  method = c("limma", "Kruskal-Wallis", "ZILN", "DESeq2")
)
```


Arguments

aggdat	aggregated MRExperiment
level	Feature level.
phenotype	Phenotype to test.
phenolevels	levels of the phenotype to restrict the comparison to
log	Log2 transform data. Default is TRUE.
coef	Numeric which indicates which pairwise comparison to analyze when there are more than two groups. Corresponds to the column number of the model matrix produced by <code>designPairs()</code> . If NULL, a test of any difference between all groups is performed.
method	Differential testing method. One of "limma" (default), "Kruskal-Wallis", "ZILN", or "DESeq2".

Details

limma is a differential expression tool for microarray data using linear models. It can also be applied to microbiome data.

The Kruskal-Wallis test is a non-parametric rank test which examines if groups come from the same distribution. A significant result indicates at least one group is distributionally different than another group.

ZILN is a zero-inflated log-normal model implemented in `fitFeatureModel()` of the `metagenomeSeq` package.

DESeq2 performs differential gene expression analysis based on the negative binomial distribution

Value

data.frame holding results of the differential analysis

Examples

```
data("mouseData", package = "metagenomeSeq")
aggdat <- aggFeatures(mouseData, level = "genus")
runDiffTest(aggdat = aggdat, level = "genus",
            phenotype = "diet", method = "Kruskal-Wallis")
```

`runMicrobiomeExplorer` *Main function to start the Microbiome Explorer Shiny app via a command line call*

Description

Main function to start the Microbiome Explorer Shiny app via a command line call

Usage

```
runMicrobiomeExplorer()
```

Value

the shiny application

Index

abundanceHeatmap, 4
abundanceHeatmapUI, 5
add_plotly_config, 6
add_plotly_layout, 7
addFeatData, 5
addPhenoData, 6
aggFeatures, 7
aggregationTab, 8
aggregationTabUI, 8
alphaDiversity, 9
alphaDiversityUI, 10
avgAbundance, 10
avgAbundanceUI, 11

betaDiversity, 12
betaDiversityUI, 13
betaInput, 13
betaInputUI, 14
buildEmptyPlotlyPlot, 14
buildPlottingDF, 15

calculatePCAs, 15
computeCI_Interval, 16
computeDistMat, 17
corrAnalysis, 17
corrAnalysisUI, 18
corrFeature, 19
corrInput, 20
corrInputUI, 21
corrPhenotype, 21
createHeader, 22

dataInput, 23
dataInputUI, 24
designPairs, 24, 73
diffAnalysis, 25
diffAnalysisUI, 26
diffInput, 26
diffInputUI, 27
diffTable, 27
diffTableUI, 28

extendPhenoData, 29

featAbundance, 29
featAbundanceUI, 30
featureAnalysis, 31
featureAnalysisUI, 31
featureCorr, 32
featureCorrUI, 33
featureInput, 33
featureInputUI, 34
featureTable, 35
featureTableUI, 35
fileUpload, 36
fileUploadUI, 37
filterByPheno, 37
filterMEData, 38
fitFeatureModel, 73

generateReport, 39
getFeatModCode, 40
getFileType, 40
getFilterChoices, 41
getLegendLevel, 41
getPhenoChanges, 42
getPhenoModCode, 42
getWidths, 43

heatmapInput, 43
heatmapInputUI, 44

interAnalysis, 44
interAnalysisUI, 45
intraAnalysis, 46
intraAnalysisUI, 47
intraInput, 47
intraInputUI, 48

longAnalysis, 49
longAnalysisUI, 50
longInput, 50
longInputUI, 51
longResults, 52
longResultsUI, 53

makeQCPlot, 53

normalizeData, 54

parseInteractionName, 55
phenotypeCorr, 55
phenotypeCorrUI, 56
phenotypeTable, 57
phenotypeTableUI, 57
plotAbundance, 58
plotAlpha, 59
plotAvgAbundance, 60
plotBeta, 61
plotHeatmap, 62
plotLongFeature, 63
plotlyHistogram, 64
plotlySampleBarplot, 65
plotSingleFeature, 66

readData, 67
relAbundance, 67
relAbundanceUI, 68
replaceWithUnknown, 69
reportList, 69
reportListUI, 70
reportRow, 71
reportRowUI, 71
rollDownFeatures, 72
runDiffTest, 72
runMicrobiomeExplorer, 73

vegdist, 61