

# Using the ACME package

Sean Davis<sup>‡\*</sup>

April 30, 2024

<sup>‡</sup>Genetics Branch  
National Cancer Institute  
National Institutes of Health

## Contents

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>Overview of ACME</b>                                   | <b>1</b> |
| <b>2</b> | <b>Getting Started using ACME</b>                         | <b>2</b> |
| 2.1      | Generating files for viewing in genome browsers . . . . . | 4        |

## 1 Overview of ACME

Data obtained from high-density oligonucleotide tiling arrays present new computational challenges for users. ACME (Algorithm for Capturing Microarray Enrichment) is a method for determining genomic regions of enrichment in the context of tiling microarray experiments. ACME identifies signals or "peaks" in tiled array data using a user-defined sliding window of n-base-pairs and a threshold (again, user-defined) strategy to assign a probability value (p-value) of enrichment to each probe on the array. This approach has been applied successfully to at least two different genomic applications involving tiled arrays: ChIP-chip and DNase-chip. However, it can potentially be applied to tiling array data whenever regions of relative enrichment are expected.

The ACME algorithm is quite straightforward. Using a user-defined quantile of the data, called the threshold, any probes in the data that are above that threshold are considered positive probes. For example, if a user chooses a threshold of 0.95, then, of course, 5 percent of the total data are going to be positive probes. To look for enrichment, a sliding window of fix number of base pairs (the chosen window size) is examined centered on each probe. Enrichment is calculated using a chi-square of the number of expected positive probes in the window as compared to the expected number. A p-value is then assigned to each probe.

---

\*sdavis2@mail.nih.gov

Note that these p-values are not corrected for multiple comparisons and should be used as a guide to determining regions of interest rather than a strict statistical significance level.

## 2 Getting Started using ACME

```
> library(ACME)
```

This loads the ACME library.

To illustrate the package, we begin by loading some example data from two nimblegen arrays. The arrays were custom-designed to assay HOX genes in a ChIP-chip experiment.

```
> datdir <- system.file('extdata',package='ACME')
> fnames <- dir(datdir)
> example.agff <- read.resultsGFF(fnames,path=datdir)

[1] "Reading /tmp/RtmpnIQP6t/Rinst1e7b456620c91c/ACME/extdata/testsamp1.gff"
[1] "Reading /tmp/RtmpnIQP6t/Rinst1e7b456620c91c/ACME/extdata/testsamp2.gff"

> example.agff
```

```
ACMESet (storageMode: lockedEnvironment)
assayData: 190181 features, 2 samples
  element names: exprs
protocolData: none
phenoData
  sampleNames: testsamp1 testsamp2
  varLabels: fullfnames
  varMetadata: labelDescription
featureData
  featureNames: 74065 74066 ... 103913 (190181 total)
  fvarLabels: chromosome source ... comment (8 total)
  fvarMetadata: labelDescription
experimentData: use 'experimentData(object)'
Annotation:
```

Now, `a` is an R data structure (of class `ACMESet`) that contains the data from two test GFF files.

```
> calc <- do.aGFF.calc(example.agff,window=1000,thresh=0.95)
```

```
Working on sample 1
```

```
Working on chromosome:
```

```
chr1 chr10 chr11 chr12 chr13 chr14 chr15 chr16 chr17 chr18 chr19 chr2 chr20
```


```
Working on chromosome:
```

```
chr1 chr10 chr11 chr12 chr13 chr14 chr15 chr16 chr17 chr18 chr19 chr2 chr20
```

The function `do.aGFF.calc` takes as input an *ACMESet* object, a window size (usually 2-3 times the expected fragment size from the experiment and large enough to include about 10 probes, at least), and a threshold which will be used to determine which probes are counted as positive in the chi-square test.

If desired, the results can be plotted in an R graphics window. The raw signal intensities of each oligonucleotide (Chip/total genomic DNA) will be displayed as grey points; corresponding P values will be displayed in red. The dotted horizontal line represents the threshold as defined in the call to `do.aGFF.calc`. In the following example, R plots the results from an arbitrarily chosen region on chromosome 1, genome coordinates 10,000-50,000.

```
> plot(calc, chrom='chr1', sample=1)
```



And one can find significant regions of interest using:

```
> regs <- findRegions(calc)  
> regs[1:5,]
```

|                  | Length    | TF    | StartInd     | EndInd | Sample       | Chromosome | Start     |
|------------------|-----------|-------|--------------|--------|--------------|------------|-----------|
| testsamp1.chr1.1 | 918       | FALSE | 1            | 918    | testsamp1    | chr1       | 18370933  |
| testsamp1.chr1.2 | 1         | TRUE  | 919          | 919    | testsamp1    | chr1       | 18515429  |
| testsamp1.chr1.3 | 1806      | FALSE | 920          | 2725   | testsamp1    | chr1       | 27803112  |
| testsamp1.chr1.4 | 2         | TRUE  | 2726         | 2727   | testsamp1    | chr1       | 160510960 |
| testsamp1.chr1.5 | 183       | FALSE | 2728         | 2910   | testsamp1    | chr1       | 160512520 |
|                  | End       |       | Median       |        | Mean         |            |           |
| testsamp1.chr1.1 | 18514188  |       | 5.164139e-01 |        | 5.003686e-01 |            |           |
| testsamp1.chr1.2 | 18515429  |       | 1.308413e-05 |        | 1.308413e-05 |            |           |
| testsamp1.chr1.3 | 160504694 |       | 4.912989e-01 |        | 5.041074e-01 |            |           |
| testsamp1.chr1.4 | 160511031 |       | 7.101277e-10 |        | 7.101277e-10 |            |           |
| testsamp1.chr1.5 | 161743150 |       | 6.079601e-01 |        | 5.724538e-01 |            |           |

## 2.1 Generating files for viewing in genome browsers

The Affymetrix Integrated Genome Browser (IGB) is a very fast, cross-platform (Java-based) genome browser that can display data in many formats. By generating so-called “sgr” files, one can view both the raw data and the calculated p-values in a fully interactive manner. A simple function, `write.sgr`, will generate such files that can then be loaded into that browser. The function also serves as a model for how to generate other file formats. With minor modifications, other formats can be generated.

```
> # write both calculated values and raw data
> write.sgr(calc)
```

```
./testsamp1_thresh0.95.sgr
./testsamp1_raw.sgr
./testsamp2_thresh0.95.sgr
./testsamp2_raw.sgr
```

```
> # OR write only calculated data
> write.sgr(calc,raw=FALSE)
```

```
./testsamp1_thresh0.95.sgr
./testsamp2_thresh0.95.sgr
```

Export to the UCSC genome browser bedGraph format is also supported.

```
> # or for the UCSC genome browser
> write.bedGraph(calc)
```

```
./testsamp1_thresh0.95.bed
./testsamp1_raw.bed
./testsamp2_thresh0.95.bed
./testsamp2_raw.bed
```