

Package ‘enrichplot’

September 27, 2024

Title Visualization of Functional Enrichment Result

Version 1.25.2

Description The 'enrichplot' package implements several visualization methods for interpreting functional enrichment results obtained from ORA or GSEA analysis. It is mainly designed to work with the 'clusterProfiler' package suite. All the visualization methods are developed based on 'ggplot2' graphics.

Depends R (>= 3.5.0)

Imports aplot (>= 0.2.1), DOSE (>= 3.31.2), ggfun (>= 0.1.3), ggnewscale, ggplot2, ggraph, graphics, grid, igraph, methods, plyr, purrr, RColorBrewer, reshape2, rlang, stats, utils, scatterpie, shadowtext, GOSemSim, magrittr, ggtree, yulab.utils (>= 0.1.6)

Suggests clusterProfiler, dplyr, europepmc, ggupset, knitr, rmarkdown, org.Hs.eg.db, prettydoc, tibble, tidyr, ggforce, AnnotationDbi, ggplotify, ggribes, grDevices, gridExtra, ggrepel (>= 0.9.0), ggstar, scales, ggtreeExtra, tidydr

Remotes YuLab-SMU/tidydr

VignetteBuilder knitr

License Artistic-2.0

URL <https://yulab-smu.top/biomedical-knowledge-mining-book/>

BugReports <https://github.com/GuangchuangYu/enrichplot/issues>

biocViews Annotation, GeneSetEnrichment, GO, KEGG, Pathways, Software, Visualization

Encoding UTF-8

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/enrichplot>

git_branch devel

git_last_commit 1c5e810

git_last_commit_date 2024-08-25

Repository Bioconductor 3.20

Date/Publication 2024-09-26

Author Guangchuang Yu [aut, cre] (<<https://orcid.org/0000-0002-6485-8781>>), Chun-Hui Gao [ctb] (<<https://orcid.org/0000-0002-1445-7939>>)

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Contents

enrichplot-package	2
autofacet	3
barplot.enrichResult	3
cnetplot	4
color_palette	7
dotplot	8
dotplot2	11
drag_network	12
emapplot	13
emapplot_cluster	18
fortify.compareClusterResult	18
geom_gsea_gene	19
ggtable	20
goplot	20
gseadist	22
gseaplot	22
gseaplot2	24
gsearank	25
gsInfo	25
heatplot	26
pairwise_termsim	27
plotting.clusterProfile	28
pmcplot	29
reexports	30
ridgeplot	30
set_enrichplot_color	31
ssplot	32
treeplot	34
upsetplot	39
volplot	40
Index	42

enrichplot-package *enrichplot: Visualization of Functional Enrichment Result*

Description

The 'enrichplot' package implements several visualization methods for interpreting functional enrichment results obtained from ORA or GSEA analysis. It is mainly designed to work with the 'clusterProfiler' package suite. All the visualization methods are developed based on 'ggplot2' graphics.

Author(s)

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com> ([ORCID](#))

Other contributors:

- Chun-Hui Gao <gaospecial@gmail.com> ([ORCID](#)) [contributor]

See Also

Useful links:

- <https://yulab-smu.top/biomedical-knowledge-mining-book/>
- Report bugs at <https://github.com/GuangchuangYu/enrichplot/issues>

autofacet

automatically split barplot or dotplot into several facets

Description

automatically split barplot or dotplot into several facets

Usage

```
autofacet(by = "row", scales = "free", levels = NULL)
```

Arguments

by	one of 'row' or 'column'
scales	wether 'fixed' or 'free'
levels	set facet levels

Value

a ggplot object

barplot.enrichResult *barplot*

Description

barplot of enrichResult

Usage

```
## S3 method for class 'enrichResult'  
barplot(  
  height,  
  x = "Count",  
  color = "p.adjust",  
  showCategory = 8,  
  font.size = 12,  
  title = "",  
  label_format = 30,  
  ...  
)
```

Arguments

height	enrichResult object
x	one of 'Count' and 'GeneRatio'
color	one of 'pvalue', 'p.adjust' and 'qvalue'
showCategory	number of categories to show
font.size	font size
title	plot title
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters
...	other parameter, ignored

Value

ggplot object

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
barplot(x)
# use `showCategory` to select the displayed terms. It can be a number or a vector of terms.
barplot(x, showCategory = 10)
categorys <- c("urinary bladder cancer", "bronchiolitis obliterans",
               "aortic aneurysm", "esophageal cancer")
barplot(x, showCategory = categorys)
```

cnetplot

cnetplot

Description

Gene-Concept Network

Usage

```
cnetplot(x, ...)

## S4 method for signature 'enrichResult'
cnetplot(x, ...)

## S4 method for signature 'list'
cnetplot(x, ...)

## S4 method for signature 'gseaResult'
cnetplot(x, ...)

## S4 method for signature 'compareClusterResult'
```

```

cnetplot(x, ...)

cnetplot.enrichResult(
  x,
  showCategory = 5,
  foldChange = NULL,
  layout = "kk",
  colorEdge = FALSE,
  circular = FALSE,
  node_label = "all",
  cex_category = 1,
  cex_gene = 1,
  cex_label_category = 1,
  cex_label_gene = 1,
  color_category = "#E5C494",
  color_gene = "#B3B3B3",
  shadowtext = "all",
  color.params = list(foldChange = NULL, edge = FALSE, category = "#E5C494", gene =
    "#B3B3B3"),
  cex.params = list(category_node = 1, gene_node = 1, category_label = 1, gene_label = 1),
  hilight.params = list(category = NULL, alpha_hilight = 1, alpha_no_hilight = 0.3),
  ...
)

```

Arguments

x	Enrichment result.
...	Additional parameters
showCategory	A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed.
foldChange	Fold Change of nodes, the default value is NULL. If the user provides the Fold Change value of the nodes, it can be used to set the color of the gene node. Will be removed in the next version.
layout	Layout of the map, e.g. 'star', 'circle', 'gem', 'dh', 'graphopt', 'grid', 'mds', 'randomly', 'fr', 'kk', 'drl' or 'lgl'.
colorEdge	Logical, whether coloring edge by enriched terms, the default value is FALSE. Will be removed in the next version.
circular	Logical, whether using circular layout, the default value is FALSE. Will be removed in the next version.
node_label	Select which labels to be displayed. one of 'category', 'gene', 'all'(the default) and 'none'.
cex_category	Number indicating the amount by which plotting category nodes should be scaled relative to the default, the default value is 1. Will be removed in the next version.
cex_gene	Number indicating the amount by which plotting gene nodes should be scaled relative to the default, the default value is 1. Will be removed in the next version.
cex_label_category	Scale of category node label size, the default value is 1. Will be removed in the next version.

<code>cex_label_gene</code>	Scale of gene node label size, the default value is 1. Will be removed in the next version.
<code>color_category</code>	Color of category node. Will be removed in the next version.
<code>color_gene</code>	Color of gene node. Will be removed in the next version.
<code>shadowtext</code>	select which node labels to use shadow font, one of 'category', 'gene', 'all' and 'none', default is 'all'.
<code>color.params</code>	list, the parameters to control the attributes of highlighted nodes and edges. see the <code>color.params</code> in the following. <code>color.params</code> control the attributes of highlight, it can be referred to the following parameters: <ul style="list-style-type: none"> • <code>foldChange</code> Fold Change of nodes for <code>enrichResult</code>, or size of nodes for <code>compareClusterResult</code>, the default value is <code>NULL</code>. • <code>edge</code> Logical, whether coloring edge by enriched terms, the default value is <code>FALSE</code>. • <code>category</code> Color of category node. • <code>gene</code> Color of gene node.
<code>cex.params</code>	list, the parameters to control the size of nodes and lables. see the <code>cex.params</code> in the following. <code>cex.params</code> control the attributes of highlight, it can be referred to the following parameters: <ul style="list-style-type: none"> • <code>foldChange</code> only used in <code>compareClusterResult</code> object, fold Change of nodes, the default value is <code>NULL</code>. If the user provides the Fold Change value of the nodes, it can be used to set the size of the gene node. • <code>category_node</code> Number indicating the amount by which plotting category nodes should be scaled relative to the default, the default value is 1. • <code>gene_node</code> Number indicating the amount by which plotting gene nodes should be scaled relative to the default, the default value is 1. • <code>category_label</code> Scale of category node label size, the default value is 1. • <code>gene_label</code> Scale of gene node label size, the default value is 1.
<code>hilight.params</code>	list, the parameters to control the attributes of highlighted nodes and edges. see the <code>hilight.params</code> in the following. <code>hilight.params</code> control the attributes of highlight, it can be referred to the following parameters: <ul style="list-style-type: none"> • <code>category</code> category nodes to be highlight. • <code>alpha_hilight</code> alpha of highlighted nodes. • <code>alpha_no_hilight</code> alpha of unhighlighted nodes.

Details

plot linkages of genes and enriched concepts (e.g. GO categories, KEGG pathways)

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
  library(DOSE)
  data(geneList)
  de <- names(geneList)[1:100]
  x <- enrichDO(de)
  x2 <- pairwise_termsim(x)
  cnetplot(x2)
  # use `layout` to change the layout of map
  cnetplot(x2, layout = "star")
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.
  cnetplot(x2, showCategory = 10)
  categorys <- c("pre-malignant neoplasm", "intestinal disease",
                "breast ductal carcinoma", "non-small cell lung carcinoma")
  cnetplot(x2, showCategory = categorys)
# 'compareClusterResult' object is also supported.
  library(clusterProfiler)
  library(DOSE)
  library(org.Hs.eg.db)
  data(gcSample)
  xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
  xx2 <- pairwise_termsim(xx)
  cnetplot(xx2)

## End(Not run)
```

color_palette

color_palette

Description

create color palette for continuous data

Usage

```
color_palette(colors)
```

Arguments

colors colors of length ≥ 2

Value

color vector

Author(s)

guangchuang yu

Examples

```
color_palette(c("red", "yellow", "green"))
```

dotplot

dotplot

Description

dotplot for enrichment result

Usage

```
dotplot(object, ...)
```

```
## S4 method for signature 'enrichResult'
```

```
dotplot(  
  object,  
  x = "GeneRatio",  
  color = "p.adjust",  
  showCategory = 10,  
  size = NULL,  
  split = NULL,  
  font.size = 12,  
  title = "",  
  orderBy = "x",  
  label_format = 30,  
  ...  
)
```

```
## S4 method for signature 'gseaResult'
```

```
dotplot(  
  object,  
  x = "GeneRatio",  
  color = "p.adjust",  
  showCategory = 10,  
  size = NULL,  
  split = NULL,  
  font.size = 12,  
  title = "",  
  orderBy = "x",  
  label_format = 30,  
  ...  
)
```

```
## S4 method for signature 'compareClusterResult'
```

```
dotplot(  
  object,  
  x = "Cluster",  
  color = "p.adjust",  
  showCategory = 5,  
  split = NULL,  
  font.size = 12,  
  title = "",  
  by = "geneRatio",
```



```
    size = NULL,
    includeAll = TRUE,
    label_format = 30,
    ...
)

## S4 method for signature 'enrichResultList'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

## S4 method for signature 'gseaResultList'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

dotplot.enrichResult(
  object,
  x = "geneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  decreasing = TRUE
)

dotplot.compareClusterResult(
  object,
```

```

x = "Cluster",
colorBy = "p.adjust",
showCategory = 5,
by = "geneRatio",
size = "geneRatio",
split = NULL,
includeAll = TRUE,
font.size = 12,
title = "",
label_format = 30,
group = FALSE,
shape = FALSE,
facet = NULL,
strip_width = 15
)

```

Arguments

object	compareClusterResult object
...	additional parameters
x	variable for x-axis, one of 'GeneRatio' and 'Count'
color	variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'
showCategory	A number or a list of terms. If it is a number, the first n terms will be displayed. If it is a list of terms, the selected terms will be displayed.
size	variable that used to scale the sizes of categories, one of "geneRatio", "Percentage" and "count"
split	apply 'showCategory' to each category specified by the 'split', e.g., "ONTOLOGY", "category" and "intersect". Default is NULL and do nothing
font.size	font size
title	figure title
orderBy	The order of the Y-axis
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters
by	one of "geneRatio", "Percentage" and "count"
includeAll	logical
decreasing	logical. Should the orderBy order be increasing or decreasing?
colorBy	variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'
group	a logical value, whether to connect the nodes of the same group with wires.
shape	a logical value, whether to use nodes of different shapes to distinguish the group it belongs to
facet	apply 'facet_grid' to the plot by specified variable, e.g., "ONTOLOGY", "category" and "intersect".
strip_width	width of strip text, a.k.a facet label.

Value

plot

Author(s)

Guangchuang Yu

Examples

```
## Not run:
  library(DOSE)
  data(geneList)
  de <- names(geneList)[1:100]
  x <- enrichDO(de)
  dotplot(x)
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.
dotplot(x, showCategory = 10)
categorys <- c("pre-malignant neoplasm", "intestinal disease",
              "breast ductal carcinoma", "non-small cell lung carcinoma")
dotplot(x, showCategory = categorys)
# It can also graph compareClusterResult
data(gcSample)
library(clusterProfiler)
library(DOSE)
library(org.Hs.eg.db)
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
xx2 <- pairwise_termsim(xx)
library(ggstar)
dotplot(xx2)
dotplot(xx2, shape = TRUE)
dotplot(xx2, group = TRUE)
dotplot(xx2, x = "GeneRatio", group = TRUE, size = "count")

## End(Not run)
```

dotplot2

dotplot2

Description

compare two clusters in the compareClusterResult object

Usage

```
dotplot2(object, x = "FoldEnrichment", vars = NULL, label = "auto", ...)
```

Arguments

object	a compareClusterResult object
x	selected variable to visualize in x-axis
vars	selected Clusters to be compared, only length of two is supported
label	to label the Clusters in the plot, should be a named vector
...	additional parameters passed to dotplot

Value

a ggplot object

Author(s)

Guangchuang Yu

drag_network	<i>Drag the nodes of a network to update the layout of the network</i>
--------------	--

Description

Drag the nodes of a network to update the layout of the network

Usage

```
drag_network(p, g = NULL)
```

Arguments

p the network diagram as a ggplot/gg/ggraph object.
g an corresponding igraph object. Default is to extract from the 'ggraph' attribute.

Value

an updated ggplot/gg/ggraph object

Examples

```
## Not run:  
library(igraph)  
library(ggraph)  
  
flow_info <- data.frame(from = c(1,2,3,3,4,5,6),  
                       to = c(5,5,5,6,7,6,7))  
g = graph_from_data_frame(flow_info)  
p <- ggraph(g, layout='nicely') + geom_node_point() + geom_edge_link()  
pp <- drag_network(p)  
  
## End(Not run)
```

 emapplot

emapplot

Description

Enrichment Map for enrichment result of over-representation test or gene set enrichment analysis

Usage

```

emapplot(x, ...)

## S4 method for signature 'enrichResult'
emapplot(x, showCategory = 30, ...)

## S4 method for signature 'gseaResult'
emapplot(x, showCategory = 30, ...)

## S4 method for signature 'compareClusterResult'
emapplot(x, showCategory = 30, ...)

emapplot.enrichResult(
  x,
  showCategory = 30,
  layout = NULL,
  coords = NULL,
  color = "p.adjust",
  min_edge = 0.2,
  cex_label_category = 1,
  cex_category = 1,
  cex_line = 1,
  shadowtext = TRUE,
  label_style = "shadowtext",
  repel = FALSE,
  node_label = "category",
  with_edge = TRUE,
  group_category = FALSE,
  group_legend = FALSE,
  cex_label_group = 1,
  nWords = 4,
  label_format = 30,
  clusterFunction = stats::kmeans,
  nCluster = NULL,
  layout.params = list(layout = NULL, coords = NULL),
  edge.params = list(show = TRUE, min = 0.2),
  cex.params = list(category_node = 1, category_label = 1, line = 1),
  hilight.params = list(category = NULL, alpha_hilight = 1, alpha_no_hilight = 0.3),
  cluster.params = list(cluster = FALSE, method = stats::kmeans, n = NULL, legend =
    FALSE, label_style = "shadowtext", label_words_n = 4, label_format = 30),
  ...
)

```

```

emapplot.compareClusterResult(
  x,
  showCategory = 30,
  layout = NULL,
  coords = NULL,
  split = NULL,
  pie = "equal",
  legend_n = 5,
  cex_category = 1,
  cex_line = 1,
  min_edge = 0.2,
  cex_label_category = 1,
  shadowtext = TRUE,
  with_edge = TRUE,
  group_category = FALSE,
  label_format = 30,
  group_legend = FALSE,
  node_label = "category",
  label_style = "shadowtext",
  repel = FALSE,
  cex_label_group = 1,
  nWords = 4,
  clusterFunction = stats::kmeans,
  nCluster = NULL,
  cex_pie2axis = 1,
  pie.params = list(pie = "equal", legend_n = 5),
  layout.params = list(layout = NULL, coords = NULL),
  edge.params = list(show = TRUE, min = 0.2),
  cluster.params = list(cluster = FALSE, method = stats::kmeans, n = NULL, legend =
    FALSE, label_style = "shadowtext", label_words_n = 4, label_format = 30),
  cex.params = list(category_node = 1, category_label = 1, line = 1, pie2axis = 1,
    label_group = 1),
  hilight.params = list(category = NULL, alpha_hilight = 1, alpha_no_hilight = 0.3),
  ...
)

```

Arguments

x	Enrichment result.
...	additional parameters
	additional parameters can refer the following parameters.
	<ul style="list-style-type: none"> • force Force of repulsion between overlapping text labels. Defaults to 1. • nudge_x, nudge_y Horizontal and vertical adjustments to nudge the starting position of each text label. • direction "both", "x", or "y" – direction in which to adjust position of labels. • ellipse_style style of ellipse, one of "ggforce" an "polygon". • ellipse_pro numeric indicating confidence value for the ellipses, it can be used only when ellipse_style = "polygon". • alpha the transparency of ellipse fill.

- type The type of ellipse. The default "t" assumes a multivariate t-distribution, and "norm" assumes a multivariate normal distribution. "euclid" draws a circle with the radius equal to level, representing the euclidean distance from the center.

showCategory	A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed.
layout	Layout of the map, e.g. 'star', 'circle', 'gem', 'dh', 'graphopt', 'grid', 'mds', 'randomly', 'fr', 'kk', 'drl' or 'lgl'. Will be removed in the next version. Will be removed in the next version.
coords	a data.frame with two columns: 'x' for X-axis coordinate and 'y' for Y-axis coordinate. Will be removed in the next version.
color	Variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'.
min_edge	The minimum similarity threshold for whether two nodes are connected, should be between 0 and 1, default value is 0.2. Will be removed in the next version.
cex_label_category	Scale of category node label size. Will be removed in the next version.
cex_category	Number indicating the amount by which plotting category nodes should be scaled relative to the default. Will be removed in the next version.
cex_line	Scale of line width. Will be removed in the next version.
shadowtext	a logical value, whether to use shadow font.
label_style	style of group label, one of "shadowtext" and "ggforce". Will be removed in the next version.
repe1	whether to correct the position of the label. Defaults to FALSE.
node_label	Select which labels to be displayed, one of 'category', 'group', 'all' and 'none'.
with_edge	Logical, if TRUE, draw the edges of the network diagram. Will be removed in the next version.
group_category	a logical, if TRUE, group the category. Will be removed in the next version.
group_legend	Logical, if TRUE, the grouping legend will be displayed. The default is FALSE. Will be removed in the next version.
cex_label_group	Numeric, scale of group labels size, the default value is 1. Will be removed in the next version.
nWords	Numeric, the number of words in the cluster tags, the default value is 4. Will be removed in the next version.
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels. Will be removed in the next version.
clusterFunction	function of Clustering method, such as stats::kmeans(the default), cluster::clara, cluster::fanny or cluster::pam. Will be removed in the next version.
nCluster	Numeric, the number of clusters, the default value is square root of the number of nodes. Will be removed in the next version.
layout.params	list, the parameters to control the layout. see the layout.params in the following. layout.params control the attributes of layout, it can be referred to the following parameters: <ul style="list-style-type: none"> • layout Layout of the map, e.g. 'star', 'circle', 'gem', 'dh', 'graphopt', 'grid', 'mds', 'randomly', 'fr', 'kk', 'drl' or 'lgl'..

	<ul style="list-style-type: none"> • <code>coords</code> a data.frame with two columns: 'x' for X-axis coordinate and 'y' for Y-axis coordinate.
<code>edge.params</code>	<p>list, the parameters to control the edge. see the <code>edge.params</code> in the following. <code>edge.params</code> control the attributes of edge, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>show</code> Logical, if TRUE (the default), draw the edges of the network diagram. • <code>min</code> The minimum similarity threshold for whether two nodes are connected, should between 0 and 1, default value is 0.2.
<code>cex.params</code>	<p>list, the parameters to control the edge. see the <code>cex.params</code> in the following. <code>cex.params</code> control the attributes of edge, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>category_node</code> Number indicating the amount by which plotting category nodes should be scaled relative to the default. • <code>category_label</code> Scale of category node label size. • <code>line</code> Scale of line width. • <code>pie2axis</code> It is used to adjust the relative size of the pie chart on the coordinate axis, the default value is 1. • <code>label_group</code> Numeric, scale of group labels size, the default value is 1.
<code>hilight.params</code>	<p>list, the parameters to control the attributes of highlighted nodes and edges. see the <code>hilight.params</code> in the following. <code>hilight.params</code> control the attributes of highlight, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>category</code> category nodes to be highlight. • <code>alpha_hilight</code> alpha of highlighted nodes. • <code>alpha_no_hilight</code> alpha of unhighlighted nodes.
<code>cluster.params</code>	<p>list, the parameters to control the attributes of highlighted nodes and edges. see the <code>cluster.params</code> in the following. <code>cluster.params</code> control the attributes of highlight, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>cluster</code> a logical, if TRUE, group the category. • <code>method</code> function of Clustering method, such as <code>stats::kmeans</code>(the default), <code>cluster::clara</code>, <code>cluster::fanny</code> or <code>cluster::pam</code>. • <code>n</code> Numeric, the number of clusters, the default value is square root of the number of nodes. • <code>legend</code> Logical, if TRUE, the grouping legend will be displayed. The default is FALSE. • <code>label_style</code> style of group label, one of "shadowtext" and "ggforce". • <code>label_words_n</code> Numeric, the number of words in the cluster tags, the default value is 4. • <code>label_format</code> a numeric value sets wrap length, alternatively a custom function to format axis labels.
<code>split</code>	separate result by 'category' variable
<code>pie</code>	proportion of clusters in the pie chart, one of 'equal' (default) and 'Count' Will be removed in the next version.
<code>legend_n</code>	number of circle in legend Will be removed in the next version.
<code>cex_pie2axis</code>	It is used to adjust the relative size of the pie chart on the coordinate axis, the default value is 1. Will be removed in the next version.

pie.params list, the parameters to control the attributes of pie nodes. see the pie.params in the following. pie.params control the attributes of pie nodes, it can be referred to the following parameters:

- pie proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'.
- legend_n number of circle in legend.

Details

This function visualizes gene sets as a network (i.e. enrichment map). Mutually overlapping gene sets tend to cluster together, making it easier for interpretation. When the similarity between terms meets a certain threshold (default is 0.2, adjusted by parameter 'min_edge'), there will be edges between terms. The stronger the similarity, the shorter and thicker the edges. The similarity between terms is obtained by function 'pairwise_termsim', the details of similarity calculation can be found in its documentation: [pairwise_termsim](#).

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
x2 <- pairwise_termsim(x)
emapplot(x2)
# use `layout` to change the layout of map
emapplot(x2, layout = "star")
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.
emapplot(x2, showCategory = 10)
categorys <- c("pre-malignant neoplasm", "intestinal disease",
              "breast ductal carcinoma")
emapplot(x2, showCategory = categorys)

# It can also graph compareClusterResult
library(clusterProfiler)
library(DOSE)
library(org.Hs.eg.db)
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
xx2 <- pairwise_termsim(xx)
emapplot(xx2)

## End(Not run)
```

emapplot_cluster	<i>Functional grouping network diagram for enrichment result of over-representation test or gene set enrichment analysis</i>
------------------	--

Description

This function has been replaced by ‘emapplot‘.

Usage

```
emapplot_cluster(x, ...)
```

Arguments

x	enrichment result
...	additional parameters. Please refer to: emapplot .

Value

ggplot2 object

fortify.compareClusterResult	<i>fortify</i>
------------------------------	----------------

Description

convert compareClusterResult to a data.frame that ready for plot
 convert enrichResult object for ggplot2

Usage

```
## S3 method for class 'compareClusterResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "geneRatio",
  split = NULL,
  includeAll = TRUE,
  ...
)

## S3 method for class 'enrichResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "Count",
```

```

    order = FALSE,
    drop = FALSE,
    split = NULL,
    ...
  )

```

Arguments

model	'enrichResult' or 'compareClusterResult' object
data	not use here
showCategory	Category numbers to show
by	one of Count and GeneRatio
split	separate result by 'split' variable
includeAll	logical
...	additional parameter
order	logical
drop	logical

Value

data.frame
data.frame

Author(s)

Guangchuang Yu

geom_gsea_gene	<i>geom_gsea_gene</i>
----------------	-----------------------

Description

label genes in running score plot

Usage

```

geom_gsea_gene(
  genes,
  mapping = NULL,
  geom = ggplot2::geom_text,
  ...,
  geneSet = NULL
)

```

Arguments

genes	selected genes to be labeled
mapping	aesthetic mapping, default is NULL
geom	geometric layer to plot the gene labels, default is geom_text
...	additional parameters passed to the 'geom'
geneSet	choose which gene set(s) to be label if the plot contains multiple gene sets

Value

ggplot object

Author(s)

Guangchuang Yu

ggtable

ggtable

Description

plot table

Usage

```
ggtable(d, p = NULL)
```

Arguments

d data frame

p ggplot object to extract color to color rownames(d), optional

Value

ggplot object

Author(s)

guangchuang yu

goplot

goplot

Description

plot induced GO DAG of significant terms

Usage

```
goplot(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)
```

```
## S4 method for signature 'enrichResult'
goplot(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)

## S4 method for signature 'gseaResult'
goplot(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)

goplot.enrichResult(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)
```

Arguments

x	enrichment result.
showCategory	number of enriched terms to display
color	variable that used to color enriched terms, e.g. pvalue, p.adjust or qvalue
layout	layout of the map
geom	label geom, one of 'label' or 'text'
...	additional parameter

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(clusterProfiler)
data(geneList, package = "DOSE")
de <- names(geneList)[1:100]
```

```
yy <- enrichGO(de, 'org.Hs.eg.db', ont="BP", pvalueCutoff=0.01)
goplot(yy)
goplot(yy, showCategory = 5)

## End(Not run)
```

gseadist

gseadist

Description

plot logFC distribution of selected gene sets

Usage

```
gseadist(x, IDs, type = "density")
```

Arguments

x	GSEA result
IDs	gene set IDs
type	one of 'density' or 'boxplot'

Value

distribution plot

Author(s)

Guangchuang Yu

gseaplot

gseaplot

Description

visualize analyzing result of GSEA

Usage

```
gseaplot(x, geneSetID, by = "all", title = "", ...)
```

```
## S4 method for signature 'gseaResult'
gseaplot(
  x,
  geneSetID,
  by = "all",
  title = "",
  color = "black",
  color.line = "green",
```

```
    color.vline = "#FA5860",  
    ...  
  )  
  
gseaplot.gseaResult(  
  x,  
  geneSetID,  
  by = "all",  
  title = "",  
  color = "black",  
  color.line = "green",  
  color.vline = "#FA5860",  
  ...  
)
```

Arguments

x	object of gsea result
geneSetID	geneSet ID
by	one of "runningScore" or "position"
title	plot title
...	additional parameters
color	color of line segments
color.line	color of running enrichment score line
color.vline	color of vertical line which indicating the maximum/minimal running enrichment score

Details

plotting function for gseaResult

Value

ggplot2 object
ggplot2 object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)  
data(geneList)  
x <- gseDO(geneList)  
gseaplot(x, geneSetID=1)
```

`gseaplot2``gseaplot2`

Description

GSEA plot that mimic the plot generated by broad institute's GSEA software

Usage

```
gseaplot2(  
  x,  
  geneSetID,  
  title = "",  
  color = "green",  
  base_size = 11,  
  rel_heights = c(1.5, 0.5, 1),  
  subplots = 1:3,  
  pvalue_table = FALSE,  
  ES_geom = "line"  
)
```

Arguments

<code>x</code>	<code>gseaResult</code> object
<code>geneSetID</code>	gene set ID
<code>title</code>	plot title
<code>color</code>	color of running enrichment score line
<code>base_size</code>	base font size
<code>rel_heights</code>	relative heights of subplots
<code>subplots</code>	which subplots to be displayed
<code>pvalue_table</code>	whether add pvalue table
<code>ES_geom</code>	geom for plotting running enrichment score, one of 'line' or 'dot'

Value

plot

Author(s)

Guangchuang Yu

gsearank	<i>gsearank</i>
----------	-----------------

Description

plot ranked list of genes with running enrichment score as bar height

Usage

```
gsearank(x, geneSetID, title = "", output = "plot")
```

Arguments

x	gseaResult object
geneSetID	gene set ID
title	plot title
output	one of 'plot' or 'table' (for exporting data)

Value

ggplot object

Author(s)

Guangchuang Yu

gsInfo	<i>gsInfo</i>
--------	---------------

Description

extract gsea result of selected geneSet

Usage

```
gsInfo(object, geneSetID)
```

Arguments

object	gseaResult object
geneSetID	gene set ID

Value

data.frame

Author(s)

Guangchuang Yu

heatplot

heatplot

Description

heatmap like plot for functional classification

Usage

```
heatplot(x, showCategory = 30, ...)  
  
## S4 method for signature 'enrichResult'  
heatplot(x, showCategory = 30, ...)  
  
## S4 method for signature 'gseaResult'  
heatplot(x, showCategory = 30, ...)  
  
heatplot.enrichResult(  
  x,  
  showCategory = 30,  
  symbol = "rect",  
  foldChange = NULL,  
  pvalue = NULL,  
  label_format = 30  
)
```

Arguments

x	enrichment result.
showCategory	number of enriched terms to display
...	Additional parameters
symbol	symbol of the nodes, one of "rect"(the default) and "dot" by default wraps names longer than 30 characters
foldChange	fold Change.
pvalue	pvalue of genes
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels.

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
heatplot(x)
```

```
pairwise_termsim      pairwise_termsim
```

Description

Get the similarity matrix

Usage

```
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'enrichResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'gseaResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'compareClusterResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

pairwise_termsim.enrichResult(
  x,
  method = "JC",
  semData = NULL,
  showCategory = 200
)

pairwise_termsim.compareClusterResult(
  x,
  method = "JC",
  semData = NULL,
  showCategory = 200
)
```

Arguments

x	enrichment result.
method	method of calculating the similarity between nodes, one of "Resnik", "Lin", "Rel", "Jiang", "Wang" and "JC"(Jaccard similarity coefficient) methods.
semData	GOSemSimDATA object, can be obtained through godata function in GOSem-Sim package.
showCategory	number of enriched terms to display, default value is 200.

Details

This function add similarity matrix to the termsim slot of enrichment result. Users can use the 'method' parameter to select the method of calculating similarity. The Jaccard correlation coefficient(JC) is used by default, and it applies to all situations. When users want to calculate the correlation between GO terms or DO terms, they can also choose "Resnik", "Lin", "Rel" or "Jiang" (they are semantic similarity calculation methods from GOSemSim packages), and at this time, the user needs to provide 'semData' parameter, which can be obtained through [godata](#) function in GOSemSim package.

Examples

```
## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOSemSim)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
  universe      = names(geneList),
  OrgDb         = org.Hs.eg.db,
  ont           = "BP",
  pAdjustMethod = "BH",
  pvalueCutoff  = 0.01,
  qvalueCutoff  = 0.05,
  readable      = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method="Wang", semData = d)
emapplot(ego2)
emapplot_cluster(ego2)

## End(Not run)
```

plotting.clusterProfile

plotting-clusterProfile

Description

Internal plot function for plotting compareClusterResult

Usage

```
plotting.clusterProfile(
  clProf.reshape.df,
  x = ~Cluster,
  type = "dot",
  colorBy = "p.adjust",
  by = "geneRatio",
  title = "",
  font.size = 12
)
```

Arguments

<code>clProf.reshape.df</code>	data frame of compareCluster result
<code>x</code>	x variable
<code>type</code>	one of dot and bar
<code>colorBy</code>	one of pvalue or p.adjust
<code>by</code>	one of percentage and count
<code>title</code>	graph title
<code>font.size</code>	graph font size

Value

ggplot object

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

pmcplot

pmcplot

Description

PubMed Central Trend plot

Usage

```
pmcplot(query, period, proportion = TRUE)
```

Arguments

<code>query</code>	query terms
<code>period</code>	period of query in the unit of year
<code>proportion</code>	If TRUE, use <code>query_hits/all_hits</code> , otherwise use <code>query_hits</code>

Value

ggplot object

Author(s)

guangchuang yu

reexports

Objects exported from other packages

Description

These objects are imported from other packages. Follow the links below to see their documentation.

aplot [plot_list](#)

ggplot2 [facet_grid](#), [ggtitle](#)

ridgeplot

ridgeplot

Description

ridgeline plot for GSEA result

Usage

```
ridgeplot(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  ...
)

## S4 method for signature 'gseaResult'
ridgeplot(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  ...
)

ridgeplot.gseaResult(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  orderBy = "NES",
  decreasing = FALSE
)
```

Arguments

x	gseaResult object
showCategory	A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed.
fill	one of "pvalue", "p.adjust", "qvalue"
core_enrichment	whether only using core_enriched genes
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels.
...	additional parameters by default wraps names longer than 30 characters
orderBy	The order of the Y-axis
decreasing	logical. Should the orderBy order be increasing or decreasing?

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
x <- gseDO(geneList)
ridgeplot(x)
```

set_enrichplot_color *set_enrichplot_color*

Description

helper function to set color for enrichplot

Usage

```
set_enrichplot_color(
  colors = get_enrichplot_color(2),
  type = "color",
  name = NULL,
  .fun = NULL,
  reverse = TRUE,
  ...
)
```

Arguments

colors	user provided color vector
type	one of 'color', 'colour' or 'fill'
name	name of the color legend
.fun	force to use user provided color scale function
reverse	whether reverse the color scheme, default is TRUE as it is more significant for lower pvalue
...	additional parameter that passed to the color scale function

Value

a color scale

ssplot	<i>ssplot</i>
--------	---------------

Description

Similarity space plot of enrichment analysis results.

Usage

```
ssplot(x, ...)
```

```
## S4 method for signature 'enrichResult'
```

```
ssplot(x, showCategory = 30, ...)
```

```
## S4 method for signature 'gseaResult'
```

```
ssplot(x, showCategory = 30, ...)
```

```
## S4 method for signature 'compareClusterResult'
```

```
ssplot(x, showCategory = 30, ...)
```

```
ssplot.enrichResult(
  x,
  showCategory = 30,
  drfun = NULL,
  with_edge = FALSE,
  dr.params = list(),
  group_category = TRUE,
  node_label = "group",
  ...
)
```

```
ssplot.compareClusterResult(
  x,
  showCategory = 30,
  split = NULL,
  pie = "equal",
```



```

drfun = NULL,
with_edge = FALSE,
cex_pie2axis = 0.0125,
dr.params = list(),
group_category = TRUE,
node_label = "group",
...
)

```

Arguments

x	Enrichment result.
...	additional parameters additional parameters can refer the following parameters. <ul style="list-style-type: none"> • <code>coords</code> a data.frame with two columns: 'x' for X-axis coordinate and 'y' for Y-axis coordinate. • <code>color</code> Variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'. the starting position of each text label. • <code>cex_line</code> Scale of line width. • <code>min_edge</code> The minimum similarity threshold for whether two nodes are connected, should between 0 and 1, default value is 0.2. • <code>cex_label_category</code> Scale of category node label size. • <code>cex_category</code> Number indicating the amount by which plotting category nodes should be scaled relative to the default. • <code>shadowtext</code> a logical value, whether to use shadow font. • <code>label_style</code> style of group label, one of "shadowtext" and "ggforce". • <code>repel</code> whether to correct the position of the label. Defaults to FALSE. • <code>group_legend</code> Logical, if TRUE, the grouping legend will be displayed. The default is FALSE. • <code>cex_label_group</code> Numeric, scale of group labels size, the default value is 1. • <code>nWords</code> Numeric, the number of words in the cluster tags, the default value is 4. • <code>label_format</code> a numeric value sets wrap length, alternatively a custom function to format axis labels. • <code>clusterFunction</code> function of Clustering method, such as <code>stats::kmeans</code>(the default), <code>cluster::clara</code>, <code>cluster::fanny</code> or <code>cluster::pam</code>. • <code>nCluster</code> Numeric, the number of clusters, the default value is square root of the number of nodes. additional parameters can refer the <code>emapplot</code> function: emapplot .
<code>showCategory</code>	A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed.
<code>drfun</code>	The function used for dimension reduction, e.g. <code>stats::cmdscale</code> (the default), <code>vegan::metaMDS</code> , or <code>ape::pcoa</code> .
<code>with_edge</code>	Logical, if TRUE, draw the edges of the network diagram. Will be removed in the next version.
<code>dr.params</code>	list, the parameters of <code>tidydr::dr</code> . one of 'category', 'group', 'all' and 'none'.
<code>group_category</code>	a logical, if TRUE, group the category. Will be removed in the next version.

node_label	Select which labels to be displayed, one of 'category', 'group', 'all' and 'none'.
split	separate result by 'category' variable
pie	proportion of clusters in the pie chart, one of 'equal' (default) and 'Count' Will be removed in the next version.
cex_pie2axis	It is used to adjust the relative size of the pie chart on the coordinate axis, the default value is 0.0125.

Value

ggplot object

Examples

```
## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOsemSim)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
  universe      = names(geneList),
  OrgDb         = org.Hs.eg.db,
  ont           = "BP",
  pAdjustMethod = "BH",
  pvalueCutoff  = 0.01,
  qvalueCutoff  = 0.05,
  readable      = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method = "Wang", semData = d)
ssplot(ego2)

## End(Not run)
```

treeplot

treeplot

Description

Functional grouping tree diagram for enrichment result of over-representation test or gene set enrichment analysis.

Usage

```
treeplot(x, ...)
```

S4 method for signature 'enrichResult'

```
treeplot(x, ...)
```

S4 method for signature 'gseaResult'

```
treeplot(x, ...)
```

```
## S4 method for signature 'compareClusterResult'
treeplot(x, ...)

treeplot.enrichResult(
  x,
  showCategory = 30,
  color = "p.adjust",
  nWords = 4,
  nCluster = 5,
  cex_category = 1,
  label_format = NULL,
  label_format_cladelab = 30,
  label_format_tiplab = NULL,
  fontsize = 4,
  offset = rel(1),
  offset_tiplab = rel(1),
  hclust_method = "ward.D",
  group_color = NULL,
  extend = 0.3,
  hilight = TRUE,
  hexpand = 0.1,
  align = "both",
  hilight.params = list(hilight = TRUE, align = "both"),
  offset.params = list(bar_tree = rel(1), tiplab = rel(1), extend = 0.3, hexpand = 0.1),
  cluster.params = list(method = "ward.D", n = 5, color = NULL, label_words_n = 4,
    label_format = 30),
  ...
)

treeplot.compareClusterResult(
  x,
  showCategory = 5,
  color = "p.adjust",
  nWords = 4,
  nCluster = 5,
  cex_category = 1,
  split = NULL,
  label_format = NULL,
  label_format_cladelab = 30,
  label_format_tiplab = NULL,
  fontsize = 4,
  offset = rel(1),
  pie = "equal",
  legend_n = 3,
  offset_tiplab = rel(1),
  hclust_method = "ward.D",
  group_color = NULL,
  extend = 0.3,
  hilight = TRUE,
  geneClusterPanel = "heatMap",
  hexpand = 0.1,
```

```

align = "both",
cluster.params = list(method = "ward.D", n = 5, color = NULL, label_words_n = 4,
  label_format = 30),
highlight.params = list(hilight = TRUE, align = "both"),
clusterPanel.params = list(clusterPanel = "heatMap", pie = "equal", legend_n = 3,
  colnames_angle = 0),
offset.params = list(bar_tree = rel(1), tiplab = rel(1), extend = 0.3, hexpand = 0.1),
...
)

```

Arguments

x	enrichment result.
...	additional parameters
showCategory	number of enriched terms to display
color	variable that used to color enriched terms, e.g. pvalue, p.adjust or qvalue
nWords	The number of words in the cluster tags. Will be removed in the next version.
nCluster	The number of clusters, the default value is 5. Will be removed in the next version.
cex_category	Number indicating the amount by which plotting category. nodes should be scaled relative to the default. Will be removed in the next version.
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels.
label_format_cladelab	label_format for group labels, a numeric value sets wrap length, alternatively a custom function to format axis labels. Will be removed in the next version.
label_format_tiplab	label_format for tiplabs, a numeric value sets wrap length, alternatively a custom function to format axis labels. Will be removed in the next version.
fontsize	The size of text, default is 4.
offset	rel object or numeric value, distance bar and tree, offset of bar and text from the clade, default is rel(1), meaning $1 * 1.2 * x_range_of_tree$ plus distance_between_tree_and_tiplab ($1 * (1.2 * x_range_of_tree + distance_between_tree_and_tiplab)$). Will be removed in the next version.
offset_tiplab	tiplab offset, rel object or numeric value, the bigger the number, the farther the distance between the node and the branch. The default is rel(1), when geneClusterPanel = "pie", meaning $1 * max_radius_of_the_pies$; when geneClusterPanel = "heatMap", meaning $1 * 0.16 * column_number_of_heatMap * x_range_of_tree$; when geneClusterPanel = "dotplot", meaning $1 * 0.09 * column_number_of_dotplot * x_range_of_tree$. Will be removed in the next version.
hclust_method	Method of hclust. This should be (an unambiguous abbreviation of) one of "ward.D", "ward.D2", "single", "complete", "average" (= UPGMA), "mcquitty" (= WPGMA), "median" (= WPGMC) or "centroid" (= UPGMC). Will be removed in the next version.
group_color	A vector of group colors, the length of the vector should be the same as nCluster. Will be removed in the next version.
extend	Numeric, extend the length of bar, default is 0.3. Will be removed in the next version.

highlight	Logical value, if TRUE(default), add <code>ggtree::geom_highlight()</code> layer. Will be removed in the next version.
hexpand	expand x limits by amount of <code>xrange * hexpand</code> . Will be removed in the next version.
align	control the align direction of the edge of high light rectangular. Options is 'none', 'left', 'right', 'both (default)'. Will be removed in the next version.
highlight.params	list, the parameters to control the attributes of highlight layer. see the <code>highlight.params</code> in the following. <code>highlight.params</code> control the attributes of highlight layer, it can be referred to the following parameters: <ul style="list-style-type: none"> • <code>highlight</code> Logical value, if TRUE(default), add <code>ggtree::geom_highlight()</code> layer. • <code>align</code> control the align direction of the edge of high light rectangular. Options is 'none', 'left', 'right', 'both (default)'.
offset.params	list, the parameters to control the offset. see the <code>offset.params</code> in the following. <code>offset.params</code> control the attributes of offset, it can be referred to the following parameters: <ul style="list-style-type: none"> • <code>bar_tree</code> rel object or numeric value, distance bar and tree, offset of bar and text from the clade, default is <code>rel(1)</code>, meaning $1 * 1.2 * x_range_of_tree$ plus <code>distance_between_tree_and_tiplab</code> ($1 * (1.2 * x_range_of_tree + distance_between_tree_and_tiplab)$). • <code>tiplab</code> <code>tiplab</code> offset, rel object or numeric value, the bigger the number, the farther the distance between the node and the branch. The default is <code>rel(1)</code>, when <code>clusterPanel = "pie"</code>, meaning $1 * max_radius_of_the_pies$; when <code>clusterPanel = "heatMap"</code>, meaning $1 * 0.16 * column_number_of_heatMap * x_range_of_tree$; when <code>clusterPanel = "dotplot"</code>, meaning $1 * 0.09 * column_number_of_dotplot * x_range_of_tree$. • <code>extend</code> Numeric, extend the length of bar, default is 0.3. • <code>hexpand</code> expand x limits by amount of <code>xrange * hexpand</code>.
cluster.params	list, the parameters to control the attributes of highlighted nodes and edges. see the <code>cluster.params</code> in the following. <code>cluster.params</code> control the attributes of highlight, it can be referred to the following parameters: <ul style="list-style-type: none"> • <code>method</code> function of Clustering method, such as <code>stats::kmeans</code>(the default), <code>cluster::clara</code>, <code>cluster::fanny</code> or <code>cluster::pam</code>. • <code>n</code> Numeric, the number of clusters, the default value is square root of the number of nodes. • <code>color</code> A vector of group colors, the length of the vector should be the same as <code>nCluster</code>. • <code>label_words_n</code> Numeric, the number of words in the cluster tags, the default value is 4. • <code>label_format</code> A numeric value sets wrap length, alternatively a custom function to format axis labels.
split	Separate result by 'category' variable.
pie	Used only when <code>geneClusterPanel = "pie"</code> , proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'. Will be removed in the next version.
legend_n	Number of circle in legend, the default value is 3. Will be removed in the next version.
geneClusterPanel	one of "heatMap"(default), "dotplot", "pie". Will be removed in the next version.

`clusterPanel.params`

list, the parameters to control the attributes of cluster panel. see the `clusterPanel.params` in the following. `clusterPanel.params` control the attributes of cluster panel, it can be referred to the following parameters:

- `clusterPanel` one of "heatMap"(default), "dotplot", "pie".
- `pie pUsed` only when `ClusterPanel = "pie"`, proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'.
- `legend_n` number of circle in legend.
- `colnames_angle` set the angle of colnames.

Details

This function visualizes gene sets as a tree. Gene sets with high similarity tend to cluster together, making it easier for interpretation.

Value

ggplot object

Examples

```
## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOsemSim)
library(ggplot2)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
  universe = names(geneList),
  OrgDb = org.Hs.eg.db,
  ont = "BP",
  pAdjustMethod = "BH",
  pvalueCutoff = 0.01,
  qvalueCutoff = 0.05,
  readable = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method = "Wang", semData = d)
treeplot(ego2, showCategory = 30)
# use `highlight = FALSE` to remove ggtree::geom_highlight() layer.
treeplot(ego2, showCategory = 30, highlight = FALSE)
# use `offset` parameter to adjust the distance of bar and tree.
treeplot(ego2, showCategory = 30, highlight = FALSE, offset = rel(1.5))
# use `offset_tiplab` parameter to adjust the distance of nodes and branches.
treeplot(ego2, showCategory = 30, highlight = FALSE, offset_tiplab = rel(1.5))
keep <- rownames(ego2@termsim)[c(1:10, 16:20)]
keep
treeplot(ego2, showCategory = keep)
treeplot(ego2, showCategory = 20,
  group_color = c("#999999", "#E69F00", "#56B4E9", "#009E73", "#F0E442"))
# It can also graph compareClusterResult
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichKEGG",
```

```
                                organism="hsa", pvalueCutoff=0.05)
xx <- pairwise_termsim(xx)
treepplot(xx)

# use `geneClusterPanel` to change the gene cluster panel.
treepplot(xx, geneClusterPanel = "dotplot")

treepplot(xx, geneClusterPanel = "pie")

## End(Not run)
```

upsetplot

upsetplot method

Description

upsetplot method generics

Usage

```
upsetplot(x, ...)

## S4 method for signature 'enrichResult'
upsetplot(x, n = 10, ...)

## S4 method for signature 'gseaResult'
upsetplot(x, n = 10, ...)
```

Arguments

x	object
...	additional parameters
n	number of categories to be plotted

Value

plot

Author(s)

Guangchuang Yu

Examples

```
require(DOSE)
data(geneList)
de=names(geneList)[1:100]
x <- enrichDO(de)
upsetplot(x, 8)
```

`volplot`*volplot*

Description

volcano plot for enrichment result

Usage

```
volplot(  
  x,  
  color = "zScore",  
  xintercept = 1,  
  yintercept = 2,  
  showCategory = 5,  
  label_format = 30,  
  ...  
)  
  
## S4 method for signature 'enrichResult'  
volplot(  
  x,  
  color = "zScore",  
  xintercept = 1,  
  yintercept = 2,  
  showCategory = 5,  
  label_format = 30,  
  ...  
)  
  
volplot.enrichResult(  
  x,  
  color = "zScore",  
  xintercept = 1,  
  yintercept = 2,  
  showCategory = 5,  
  label_format = 30,  
  font.size = 12,  
  size = 5  
)
```

Arguments

<code>x</code>	enrichment result.
<code>color</code>	selected variable to color the dots
<code>xintercept</code>	value to set x intercept
<code>yintercept</code>	value to set y intercept
<code>showCategory</code>	number of most significant enriched terms or selected terms to display determined by the variable selected to color the dots

<code>label_format</code>	a numeric value sets wrap length, alternatively a custom function to format axis labels.
<code>...</code>	Additional parameters
<code>font.size</code>	font size for <code>'theme_dose()'</code>
<code>size</code>	font size to label selected categories specified by <code>showCategory</code>

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
volplot(x)
```

Index

- * **internal**
 - enrichplot-package, 2
 - reexports, 30
- autofacet, 3
- barplot.enrichResult, 3
- cnetplot, 4
 - cnetplot,compareClusterResult-method (cnetplot), 4
 - cnetplot,enrichResult-method (cnetplot), 4
 - cnetplot,gseaResult-method (cnetplot), 4
 - cnetplot,list-method (cnetplot), 4
 - cnetplot.enrichResult (cnetplot), 4
 - color_palette, 7
- dotplot, 8
 - dotplot,compareClusterResult,ANY-method (dotplot), 8
 - dotplot,compareClusterResult-method (dotplot), 8
 - dotplot,enrichResult-method (dotplot), 8
 - dotplot,enrichResultList,ANY-method (dotplot), 8
 - dotplot,enrichResultList-method (dotplot), 8
 - dotplot,gseaResult-method (dotplot), 8
 - dotplot,gseaResultList,ANY-method (dotplot), 8
 - dotplot,gseaResultList-method (dotplot), 8
 - dotplot.compareClusterResult (dotplot), 8
 - dotplot.enrichResult (dotplot), 8
 - dotplot2, 11
 - drag_network, 12
- emapplot, 13, 18, 33
 - emapplot,compareClusterResult-method (emapplot), 13
 - emapplot,enrichResult-method (emapplot), 13
- emapplot,gseaResult-method (emapplot), 13
- emapplot.compareClusterResult (emapplot), 13
- emapplot.enrichResult (emapplot), 13
- emapplot_cluster, 18
- enrichplot (enrichplot-package), 2
- enrichplot-package, 2
- facet_grid, 30
- facet_grid (reexports), 30
- fortify.compareClusterResult, 18
- fortify.enrichResult (fortify.compareClusterResult), 18
- geom_gsea_gene, 19
- ggtable, 20
- ggtitle, 30
- ggtitle (reexports), 30
- godata, 27, 28
- goplot, 20
 - goplot,enrichResult-method (goplot), 20
 - goplot,gseaResult-method (goplot), 20
 - goplot.enrichResult (goplot), 20
- gseadist, 22
- gseaplot, 22
 - gseaplot,gseaResult-method (gseaplot), 22
 - gseaplot.gseaResult (gseaplot), 22
- gseaplot2, 24
- gsrank, 25
- gsInfo, 25
- heatplot, 26
 - heatplot,enrichResult-method (heatplot), 26
 - heatplot,gseaResult-method (heatplot), 26
 - heatplot.enrichResult (heatplot), 26
- pairwise_termsim, 17, 27
- pairwise_termsim,compareClusterResult-method (pairwise_termsim), 27

pairwise_termsim, enrichResult-method
(pairwise_termsim), 27

pairwise_termsim, gseaResult-method
(pairwise_termsim), 27

pairwise_termsim.compareClusterResult
(pairwise_termsim), 27

pairwise_termsim.enrichResult
(pairwise_termsim), 27

plot_list, 30

plot_list (reexports), 30

plotting.clusterProfile, 28

pmcplot, 29

reexports, 30

ridgeplot, 30

ridgeplot, gseaResult-method
(ridgeplot), 30

ridgeplot.gseaResult (ridgeplot), 30

set_enrichplot_color, 31

ssplot, 32

ssplot, compareClusterResult-method
(ssplot), 32

ssplot, enrichResult-method (ssplot), 32

ssplot, gseaResult-method (ssplot), 32

ssplot.compareClusterResult (ssplot), 32

ssplot.enrichResult (ssplot), 32

treeplot, 34

treeplot, compareClusterResult-method
(treeplot), 34

treeplot, enrichResult-method
(treeplot), 34

treeplot, gseaResult-method (treeplot),
34

treeplot.compareClusterResult
(treeplot), 34

treeplot.enrichResult (treeplot), 34

upsetplot, 39

upsetplot, enrichResult, ANY-method
(upsetplot), 39

upsetplot, enrichResult-method
(upsetplot), 39

upsetplot, gseaResult (upsetplot), 39

upsetplot, gseaResult-method
(upsetplot), 39

volplot, 40

volplot, enrichResult-method (volplot),
40

volplot.enrichResult (volplot), 40