

Package ‘rexposome’

October 17, 2020

Version 1.10.0

Title Exposome exploration and outcome data analysis

Maintainer Carles Hernandez-Ferrer <carles.hernandez@isglobal.org>

Description Package that allows to explore the exposome and to perform association analyses between exposures and health outcomes.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

VignetteBuilder knitr

Depends R (>= 3.5), Biobase

Imports methods, utils, stats, lsr, FactoMineR, stringr, circlize, corrplot, ggplot2, reshape2, pryr, S4Vectors, imputeLCMD, scatterplot3d, glmnet, gridExtra, grid, Hmisc, gplots, gtools, scales, lme4, grDevices, graphics, ggrepel, mice

Suggests mclust, flexmix, testthat, BiocStyle, knitr, rmarkdown

biocViews Software, BiologicalQuestion, Infrastructure, DataImport, DataRepresentation, BiomedicalInformatics, ExperimentalDesign, MultipleComparison, Classification, Clustering

git_url <https://git.bioconductor.org/packages/rexposome>

git_branch RELEASE_3_11

git_last_commit ff660bc

git_last_commit_date 2020-04-27

Date/Publication 2020-10-16

Author Carles Hernandez-Ferrer [aut, cre],
Juan R. Gonzalez [aut]

R topics documented:

classification	3
clustering	3
correlation	5
expo	5
expos	6

ExposomeClust	7
ExposomeCorr	8
ExposomePCA	9
ExposomeSet	11
exposureNames	15
expo_c	15
extract	16
ExWAS	16
exwas	18
ex_imp	19
familyNames	20
highAndLow	21
ilod	22
imExposomeSet	23
imputation	25
imputeLOD	26
loadExposome	26
loadImputed	28
me	29
mExWAS	29
mexwas	31
ndim	31
normalityTest	32
pca	33
phenotypeNames	33
plot3PCA	34
plotClassification	35
plotCorrelation	35
plotEffect	36
plotEXP	37
plotExwas	37
plotFamily	38
plotHistogram	39
plotLOD	40
plotMissings	40
plotPCA	41
plotPHE	42
plotVolcano	43
readExposome	43
rexposome	45
standardize	46
tableLOD	47
tableMissings	47
tef	48
toES	49
trans	49
volcano_plot	50

classification	<i>Method to get the classification of the samples from an <code>ExposomeClust</code>.</i>
----------------	--

Description

Method to get the classification of the samples from an `ExposomeClust`.

Usage

```
classification(object)
```

Arguments

object An [ExposomeClust](#) to get the samples' classification.

Value

A labelled vector with the classification of each exposure.

See Also

[clustering](#) as a constructor for [ExposomeClust](#), [plotClassification](#) to plot the groups

Examples

```
data("eclust")
tt <- classification(expo_c)
table(tt)
```

clustering	<i>Method to perform clustering on the samples of an <code>ExposomeSet</code></i>
------------	---

Description

This method allows to create an [ExposomeClust](#) object from an [ExposomeSet](#) object by clustering samples through the exposure levels. The method is flexible to accept any clustering method (method) that allows to obtain a classification (cmethod) of the samples. The function assigned to argument method must have an argument called data, waiting for the matrix of exposures (samples as rows, exposures as columns). If the result object of the method has no accessor `$classification`, then a cmethod is required and will be applied on the result of method to obtain a labelled vector with the samples' classification.

Usage

```
clustering(object, method, cmethod, ..., warnings = TRUE)
```

Arguments

object	ExposomeSet containing the exposures used for the clustering process
method	Function applied to the exposures of object. This function must have an argument named as data that will receive the matrix of exposures.
cmethod	(optional) Function to obtain the classification from the object generated with method.
...	Passed to content of method.
warnings	(default TRUE) If set to FALSE warnings will not be displayed.

Value

ExposomeClust with the original exposures and the classification of each exposure.

Note

The function assigned to cmethod will be directly applied to the result of the method as: cmethod(model); being model the result of method.

See Also

[classification](#) to see how to obtain the classification of the samples from an [ExposomeClust](#), [plot-Classification](#) to plot the groups

Examples

```
data("exposome")

# EXAMPLE 1: Clustering with mclust
library(mclust)
c <- clustering(expo[12:32, ], method = Mclust, G = 2)
table(classification(c)) # This works since the result of Mclust has an accessor
# $classification

# EXAMPLE 2: Clustering with flexmix
library(flexmix)
# First we create a function to apply flexmix to the ExposomeSet
flexmix_clust <- function(data, ...) {
  data <- as.matrix(data)
  flexmix(formula = data~1, ...)
}

# Then if we apply the method to the ExposomeSet it will crash:
# c <- clustering(expo[12:32, ], method = flexmix_clust, k = 2, model = FLXMCmvnorm())
# Because the method does not know how to obtain the classification for the result
# since flexmix has not an accessor called $classification

# We create a function to get the classification
flexmix_clas <- function(model, ...) {
  return(clusters(model))
}

# We put it to the ExposomeClust
c <- clustering(expo[12:32, ], method = flexmix_clust, cmethod = flexmix_clas,
  k = 2, model = FLXMCmvnorm())
```

```
classification(c) # This works because the ExposomeClust has a way to get
                  # the classification
```

correlation	<i>Creation of an ExposomeCorr from an ExposomeSet.</i>
-------------	---

Description

Method to calculate the correlation between the exposures of an [ExposomeSet](#). Only numerical-exposures (non categorical) will be computed. The function creates and returns an [ExposomeCorr](#) object.

Usage

```
correlation(object, ..., warnings = TRUE)
```

Arguments

object	ExposomeSet which exposures will be used to calculate their correlation
...	Other arguments passed to cor , cramersV or to lm .
warnings	(default TRUE) If set to FALSE warnings will not be displayed.

Value

ExposomeCorr with the correlation between the selected exposures and their description

See Also

[plotCorrelation](#) to plot the correlations of an [ExposomeCorr](#), [clustering](#) to see how the exposures can cluster samples, [pca](#) to compute PCA on exposures

Examples

```
data("exposome")
expo.c <- correlation(expo)
expo.c
expo.c.table <- extract(expo.c)
```

expo	<i>ExposomeSet for testing purposes</i>
------	---

Description

ExposomeSet with full set of 104 exposures, 1200 simulated samples and 4 phenotypes (asthma status, BMI measure, sex, and age).

Usage

```
data("exposome")
```

Format

An object of class `ExposomeSet` of dimension 104 x 1200 x 4.

Value

An `ExposomeSet` object.

Examples

```
data("exposome")
dim(expo)
exposureNames(expo)
familyNames(expo)
sampleNames(expo)
phenotypeNames(expo)
```

expos

Returns the exposures matrix of an `ExposomeSet`.

Description

Given an [ExposomeSet](#) it returns the inner matrix of exposures, having the exposures as columns and the samples as rows.

Usage

```
expos(object)
```

Arguments

object An [ExposomeSet](#).

Value

A matrix of exposures

Examples

```
data("exposome")
expos(expo)[1:3, 1:3]
```

ExposomeClust *Class ExposomeClust*

Description

Class `ExposomeClust` obtained from [clustering](#) on an `ExposomeSet` object, represents the groups of samples created applying a clustering method on the `ExposomeSet`' exposures.

Usage

```
## S4 method for signature 'ExposomeClust,ANY'
plot(x, y, ...)

## S4 method for signature 'ExposomeClust'
classification(object)

## S4 method for signature 'ExposomeClust'
plotClassification(object, type = "heatmap", ...)

## S4 method for signature 'ExposomeClust'
sampleNames(object)
```

Arguments

<code>x</code>	Object of class <code>ExposomeClust</code>
<code>y</code>	NOT USED
<code>...</code>	Argument given to <code>heatmap.2</code>
<code>object</code>	An object of class <code>ExposomeClust</code>
<code>type</code>	(default "heatmap") Type of plot.

Value

An object of class `ExposomeClust`

Methods (by generic)

- `plot`: Wrapper for `plotClassification` method.
- `classification`: Return classe assigned to each sample
- `plotClassification`: Draws a heatmap for the samples' classification.
- `sampleNames`: Method to obtain samples' names

Slots

`model` Result obtained on applying method on the exposures.

`method` Function used to perform the clustering of the exposures.

`call` Call used to create this object.

`samples` Name of the exposures after the clustering process.

See Also

[clustering](#) to apply a clustering on an [ExposomeSet](#) and create an [ExposomeClust](#).

 ExposomeCorr

Class ExposomeCorr

Description

Class ExposomeCorr contains a matrix of correlations between continuous exposures calculated using [cor](#). It also contains the description of each exposures (fData of the original [ExposomeSet](#)) in order to maintain a coherence with the original source. It extends [eSet-class](#).

Usage

```
## S4 method for signature 'ExposomeCorr,ANY'
plot(x, y, ...)

## S4 method for signature 'ExposomeCorr'
dim(x)

## S4 method for signature 'ExposomeCorr'
extract(object, sort, ...)

## S4 method for signature 'ExposomeCorr'
plotCorrelation(object, type = c("circos", "matrix"),
  ...)
```

Arguments

x	Object of class ExposomeCorr
y	NOT USED
...	Arguments passed to corrplot when type="matrix".
object	An ExposomeCorr object.
sort	NOT USED
type	To choose between "circos" and "matrix".

Value

An object of class ExposomeCorr

Methods (by generic)

- plot: Wrapper for plotClassification method.
- dim: Return the dimension of the internal matrix of correlation.
- extract: Return the raw correlation matrix
- plotCorrelation: Draws both a matrix of circos plot of correlations

Slots

assayData Contains the correlation matrix (see [eSet](#), [AssayData](#)).

featureData Contains the description of the exposures including the family where they belong (see [eSet](#), [AnnotatedDataFrame](#)).

See Also

[pca](#) to study the behaviour between samples and exposures in an [ExposomeSet](#)

ExposomePCA	<i>Class ExposomePCA</i>
-------------	--------------------------

Description

Class ExposomePCA contains a matrix of exposures used to compute the PCA, also a table of phenotypes and a set containing the multiple results of computing the PCA.

Usage

```
## S4 method for signature 'ExposomePCA,ANY'
plot(x, y, ...)

## S4 method for signature 'ExposomePCA'
exposureNames(object)

## S4 method for signature 'ExposomePCA'
extract(object, table = "exposures", ...)

## S4 method for signature 'ExposomePCA'
ndim(object)

## S4 method for signature 'ExposomePCA'
phenotypeNames(object)

## S4 method for signature 'ExposomePCA'
plot3PCA(object, cmpX, cmpY, cmpZ, phenotype, main,
  angle = 35, pch = 16, legend = TRUE, plines = TRUE)

## S4 method for signature 'ExposomePCA'
plotEXP(object, exposure)

## S4 method for signature 'ExposomePCA'
plotPCA(object, set, cmpX = 1, cmpY = 2,
  show.exposures = FALSE, show.samples = FALSE, phenotype)

## S4 method for signature 'ExposomePCA'
plotPHE(object, phenotype, exp2fac = 5)
```

Arguments

x	Object of class ExposomePCA
y	NOT USED
...	NOT USED
object	An ExposomePCA object
table	Can takes values "exposures" or "individuals".
cmpX	PC to place in X-axis
cmpY	PC to place in Y-axis
cmpZ	PC to place in Z-axis
phenotype	(when set="samples") A phenotype can be selected so the samples are coloured by its value.
main	Title
angle	Point of view
pch	Size of the dots
legend	Boolean to show or hide the legend
plines	Boolean to show of hide the dotted lines that helps to place the dots in the X/Y axes
exposure	Vector of exposures to be shown in the plot
set	Can take values "exposures", "samples" or "all"
show.exposures	When set to TRUE, labels for exposures are shown
show.samples	When set to TRUE, labels for samples are shown
exp2fac	Number of different values to considere an exposures continuous

Value

An object of class ExposomePCA

Methods (by generic)

- plot: Wrapper for plotPCA method.
- exposureNames: Getter to obtain the exposures's names.
- extract: Method to extract the raw results of the PCA.
- ndim: Number of principal components in an ExposomePCA.
- phenotypeNames: Getter to obtain the phenotype's names.
- plot3PCA: Methdo to draw a 3D plot for PCA
- plotEXP: Plot correlation between exposures and PCA
- plotPCA: Methdo to draw a 2D plot for PCA
- plotPHE: Plot association score between phentotypes and PCA

Slots

pca list containing all elements of the PCA

phenoData Contains the phenotypes or variables experimenter-supplied (see [eSet](#), [AnnotatedDataFrame](#)).

featureData Contains the description of the exposures including the family where they belong (see [eSet](#), [AnnotatedDataFrame](#)).

See Also

[correlation](#) to study the correlation between exposures in a [ExposomeSet](#)

ExposomeSet	<i>Class ExposomeSet</i>
-------------	--------------------------

Description

Class `ExposomeSet` contains the exposure levels, the exposure's description and the samples phenotype. It is the starting object for `rexposome` package and extends `eSet`.

Usage

```
## S4 method for signature 'ExposomeSet,ANY'
plot(x, y, ...)

## S4 method for signature 'ExposomeSet'
clustering(object, method, cmethod, ...,
           warnings = TRUE)

## S4 method for signature 'ExposomeSet'
correlation(object, ..., warnings = TRUE)

## S4 method for signature 'ExposomeSet'
dim(x)

## S4 method for signature 'ExposomeSet'
expos(object)

## S4 method for signature 'ExposomeSet'
exposureNames(object)

## S4 method for signature 'ExposomeSet'
exwas(object, formula, filter, family, ..., baselevels,
      tef = TRUE, verbose = FALSE, warnings = TRUE)

## S4 method for signature 'ExposomeSet'
familyNames(object, by.exposure = FALSE)

## S4 method for signature 'ExposomeSet'
highAndLow(object, ngroups = 3,
           intervals = c("standard", "extreme"), select, drop = FALSE,
           warnings = TRUE)

## S4 method for signature 'ExposomeSet'
ilod(object, seed = 1234, lod.col = "LOD",
     pNA = 0.2, tLog = FALSE, method = "QRILC", warnings = TRUE, ...)

## S4 method for signature 'ExposomeSet'
imputation(object, select, ..., messages = FALSE)
```


y	NOT USED
...	Argument sent given method.
object	An ExposomeSet object.
method	Method to be used.
cmethod	Function implementing a systems to retrieve classification from clustering output
warnings	If set to TRUE shows intermediate warnings.
formula	Formula, not including exposures, to be tested.
filter	Expression to be used to filter ExposomeSet
family	Family describing the nature of the health outcome
baselevels	Labeled vector with the default base level for categorical exposures.
tef	If TRUE it computed the threshold for effective tests.
verbose	If set to TRUE is shows messages on progression.
by.exposure	If set to TRUE it returns the family which each exposure belongs
ngroups	Number of intervals to be used
intervals	If "standard" all levels are kept, if "extreme" intermediate levels are set to NA.
select	Vector selecting the exposures to be used.
drop	If set to TRUE exposures are replaced
seed	Numeric seed
lod.col	Indicator of the column where the LOD is located
pNA	Maximum percentage allowed of values under LOD
tLog	If set to TRUE it transforms all the exposures to lod before the imputation.
messages	If set to TRUE messages from mice's function will be displayed.
phenotype	Health outcome to be used as dependent variable.
exposure	Vector of exposures to be used.
th	Threshold of P-Value used to consider normality
min.val	Minimum number of observations to perform test
na.rm	If set to TRUE removes NA values
npc	Number of PC to be kept
group	Phenotype to group exposures
group2	Phenotype to group exposures
scatter	If set to true it shows the samples value in the plot
na.omit	If set to TRUE, NA values are discarded
density	If set to TRUE a density plot is drawn on the histogram
show.trans	If set to TRUE, three extra plots are drawn with usual transformations
x.max	Threshold for x axis (in %)
sort	If set to TRUE, results are ordered
set	Can take values "exposures" or "phenotypes".
output	Can take values "n" (count) or "p" (percentage)
fun	Function to be used in the transformation process

Value

An object of class `ExposomeSet`

Methods (by generic)

- `plot`: Wrapper for `plotFamily` method.
- `clustering`: Performs clustering on samples based on exposure levels.
- `correlation`: Computes correlation on exposures.
- `dim`: Returns the number of exsures, samples and phenotypes.
- `expos`: Returns a `data.frame` with exposures.
- `exposureNames`: Getter to obtain the exposures's names.
- `exwas`: Performs an EXposome-Wide Association Study
- `familyNames`: Getter to obtain the families's names of the family of each exposure.
- `highAndLow`: Performs a discretization of continuous exposures.
- `ilod`: Imputation of under-LOD values of exposures.
- `imputation`: Imputation of missing values of exposures.
- `mexwas`: Performs a Multiple-EXposure-Wide Association Study.
- `normalityTest`: Test the normality of each exposure.
- `pca`: Performs a PCA
- `phenotypeNames`: Getter to obtain the phenotypes's names.
- `plotFamily`: Draws a boxplot or accumulated-bar plot for each exposure in a given family.
- `plotHistogram`: Draws an histogram of a given continuous exposure or a pie chart if a given categorycal exposure.
- `plotLOD`: Draws a barchart with the amount of under-LOD values.
- `plotMissings`: Draws a bar-plot with the amount of missing values.
- `standardize`: Standardization of exposures.
- `Summary`: Summary of both continuous and categorical exposures
- `tableLOD`: Returns a vector with the number of under-LOD values per exposure.
- `tableMissings`: Returns a vector with the number of missing values per exposure.
- `trans`: Transformation of exposures.

Slots

`assayData` Contains the exposures matrix with column number equal to `nrow(phenoData)` (see [eSet](#), [AssayData](#)).

`featureData` Contains the description of the exposures including the family where they belong (see [eSet](#), [AnnotatedDataFrame](#)).

`phenoData` Contains the phenotypes or variables experimenter-supplied (see [eSet](#), [AnnotatedDataFrame](#)).

See Also

[readExposome](#) to create an `ExposomeSet` from files, [loadExposome](#) to create an `ExposomeSet` from `data.frames`

exposureNames	<i>Getter to obtain the exposures's names of an ExposomeSet or ExposomePCA</i>
---------------	--

Description

Getter to obtain the exposures's names of an ExposomeSet or ExposomePCA

Usage

```
exposureNames(object)
```

Arguments

object [ExposomeSet](#) that will be queried for the exposures's names.

Value

The name of the exposures as a character vector.

Warning

[exposureNames](#) collides with [featureNames](#) of [eSet](#). Although in `rexposome 1.0.0` both function can be used as synonyms, this usage is discouraged and it is not assured.

See Also

[phenotypeNames](#) to get the phenotypes, [familyNames](#) to get the families of exposures

Examples

```
data("exposome")
exposureNames(expo)
```

expo_c	<i>ExposomeClust for testing purposes</i>
--------	---

Description

`ExposomeClust` created from an `ExposomeSet` with full set of 104 exposures, 1200 simulated samples and 4 phenotypes (asthma status, BMI measure, sex, and age). The clustering was done using `hclust` and `cutree` with `k = 3`.

Usage

```
data("eclust")
```

Format

An object of class `ExposomeClust` of dimension 99 x 1200 x 5.

Value

An `ExposomeSet` object.

Examples

```
data("eclust")
dim(expo_c)
table(classification(expo_c))
```

extract	<i>Raw data from ExWAS, ExposomeClust and ExposomeCorr.</i>
---------	---

Description

Returns internal table of results of objects of class `ExWAS`, `ExposomeClust` and `ExposomeCorr`.

Usage

```
extract(object, ...)
```

Arguments

object	Object of class <code>ExWAS</code> , <code>ExposomeClust</code> or <code>ExposomeCorr</code>
...	NO USED

Value

A `data.frame` containing the raw result from `PsyGeNET` or a `data.frame` with the result Jaccard Index for each disease.

ExWAS	<i>Class ExWAS</i>
-------	--------------------

Description

Class `ExWAS` obtained from `exwas` method of an `ExposomeSet` object, contains the result of testing the association of exposures of an `ExposomeSet` to its phenotypes. "ExWAS" is the acronym of "Exposome-Wide Association Study". The function can be applied to one of to many phenotypes in the `ExposomeSet` object.

Usage

```

## S4 method for signature 'ExWAS,ANY'
plot(x, y, ...)

## S4 method for signature 'ExWAS'
extract(object, sort = TRUE, ...)

## S4 method for signature 'ExWAS'
names(x)

## S4 method for signature 'ExWAS'
plotEffect(x, y, select, xlab, ylab)

## S4 method for signature 'ExWAS'
plotExwas(object, ..., subtitles, color, exp.order, labels,
  show.effective = TRUE)

## S4 method for signature 'ExWAS'
plotVolcano(x, p.value = -log10(0.001),
  show.effect = FALSE)

## S4 method for signature 'ExWAS'
tef(object)

```

Arguments

x	Object of class ExWAS
y	An ExWAS object
...	NOT USED
object	An object of class ExWAS, mExWAS or n1ExWAS.
sort	If TRUE, the results are ordered by pvalue.
select	(optional) Vector with the selected exposures
xlab	(optional) Label for x-axis
ylab	(optional) Label for y-axis
subtitles	Character vector with the "subtitle" for each plot when given more than one ExWAS.
color	(optional) A vector of colors. The vector must have length equal to the number of families. The vector must be names with the name of the families.
exp.order	(optional) Order of the exposures.
labels	(optional) Character vector with the labels for each exposure. It must be labeled vector.
show.effective	(default TRUE) draws a brown line on the threshold given by the effective number of tests.
p.value	(default $-\log_{10}(0.001)$) Is the threshold from where the exposures can be taken as significant.
show.effect	(default false) Apply exp to obtained beta.

Value

An object of class ExWAS

Methods (by generic)

- `plot`: Wrapper for `plotExwas` method.
- `extract`: Method to obtain the matrix of association scores
- `names`: Method to obtain the Threshold for effective tests (TEF)
- `plotEffect`: Draws a plot with the confidence interval of each exposure. Allows to compare two ExWAS instances.
- `plotExwas`: Method to plot a manhatan plot for association between exposures and phenotypes
- `plotVolcano`: Method to plot a volcano plot for association between exposures and phenotypes
- `tef`: Method to obtain the Threshold for effective tests (TEF)

Slots

`effective` Number containing the effective number of tests.

`formula` Tested formula.

`comparison` Result of performing the test to find association between levels of exposures and phenotype.

`description` Description of the exposures used in the ExWAS. (in description file).

See Also

[exwas](#) to perform an Exposome-Wide Association Study and to create an [ExWAS](#), [mexwas](#) to perform a Multivariate Exposome-Wide Association Study and to create a [mExWAS](#)

exwas

Testing the association between an exposure and a phenotype of an ExposomeSet

Description

The `exwas` method performs an "Exposome-Wide Association Study" (ExWAS) using the exposures in [ExposomeSet](#) and one of its phenotype.

Usage

```
exwas(object, formula, filter, family, ..., baselevels, tef = TRUE,
       verbose = FALSE, warnings = TRUE)
```

Arguments

object	ExposomeSet that will be used for the ExWAS.
formula	formula indicating the test to be done. If any exposure is included it will be used as covariate. <code>exwas</code> metho will perform the test for each exposure.
filter	expression to be used to filter the individuals included into the test.
family	Family of the distribution followed by the health outcome to be tested (gaussian, binomial, ... check glm).
...	NOT USED
baselevels	(optional) If set, must be a labeled vector with the default base level for categorical exposures.
tcf	(default TRUE) If TRUE it computed the effective number of tests and the threshold for the effective number of tests. Usually it needs imputed data.
verbose	(default FALSE) If set to true messages along the tests are shown.
warnings	(default TRUE) If set to FALSE warnings will not be displayed.

Value

An `codeExWAS` object with the result of the association study

References

An Environment-Wide Association Study (ExWAS) on Type 2 Diabetes Mellitus. Chirag J. Patel, Jayanta Bhattacharya, Atul J. Butte. May 20, 2010 Plos One

Evaluating the effective numbers of independent tests and significant p-value thresholds in commercial genotyping arrays and public imputation reference datasets. Miao-Xin Li, Juilian M. Y. Yeung, Stacey S. Cherny and Pak C. Sham. May 2012 Hum Genet.

See Also

[extract](#) to obtain a table with the result of the ExWAS, [plotExwas](#) to plot the results of the ExWAS

Examples

```
data(exposome)
w1 <- exwas(expo[1:5, ], asthma~1, family = "binomial")
w2 <- exwas(expo[1:5, ], asthma~sex+age, family = "binomial")
w3 <- exwas(expo[1:5, ], asthma~age, family = "binomial", filter = sex=="boy")
```

ex_imp

imExposomeSet *for testing purposes*

Description

`imExposomeSet` created from the raw data included in the package. The creation process is illustrated in the vignette.

Usage

```
data("ex_imp")
```

Format

An object of class `imExposomeSet` of dimension 47 x 109 x 10.

Value

An `imExposomeSet` object.

Examples

```
data("ex_imp")
ex_imp
```

familyNames

Getter to obtain the exposures's names of an ExposomeSet.

Description

This method returns the name of the families in an [ExposomeSet](#), but it can return a vector, labeled with the exposures in the [ExposomeSet](#), containing the family belonging to each exposure.

Usage

```
familyNames(object, by.exposure = FALSE)
```

Arguments

`object` `ExposomeSet` that will be queried for the exposures's family-names.

`by.exposure` (default `FALSE`) If `TRUE` a vector labeled with each exposure name will be returned with the family of each exposures. If `FALSE` a vector with the (unique) name of the families of exposures will be returned.

Value

The families of the exposures into the [ExposomeSet](#), or the family of each exposure into the [ExposomeSet](#).

See Also

[exposureNames](#) to get the name of the exposures, [phenotypeNames](#) to get the phenotypes

Examples

```
data("exposome")
# Get families
familyNames(expo)
# Get the family of each exposure
familyNames(expo, by.exposure = TRUE)
```

highAndLow	<i>Function to convert continuous exposures to categorical exposures</i>
------------	--

Description

This method allows to convert continuous exposures of an `ExposomeSet` to categorical exposures using the n-percentile groups, defined by `ngroups` argument. By default, all levels are kept but if `intervals` is set to "extrem", the levels between the extremes (aka. lowes and highest) are discarded and their values set to NA.

Usage

```
highAndLow(object, ngroups = 3, intervals = "standard", select,
           drop = FALSE, warnings = TRUE)
```

Arguments

<code>object</code>	An object of class <code>ExposomeSet</code> .
<code>ngroups</code>	(default 3) Number of intervals to be created.
<code>intervals</code>	(default "standard") If set to "standard" all levels are set. If set to "extreme" obly lowes and highest levels are kept (others are set to NA).
<code>select</code>	(optional) Subset of exposures where the discretization is applied. If missing, all exposures are used.
<code>drop</code>	(default FALSE) If set to FALSE original exposures are kept and discretized exposures are add to <code>ExposomeSet</code> . If set to TRUE, original exposures are replaced by categorical exposures.
<code>warnings</code>	(default TRUE) If set to FALSE warnings are not shown.

Value

A new `ExposomeSet` with categorical exposures.

See Also

[trans](#) to transform exposures, [standardize](#) to standardize exposures.

Examples

```
# No drop
data("exposome")
exp.hl <- highAndLow(expo, intervals = "standard", select = "ldde_lip")
dim(exp.hl)
# exposures  samples phenotyes
#      105      1200          4
dim(expo)
# exposures  samples phenotyes
#      104      1200          4
# exps.hl has 107 exposures: the original 104 plus the new
#           3 factored exposures

# Drop
```

```

exp.hl <- highAndLow(expo, intervals = "standard",
  select = "ldde_lip", drop = TRUE)
dim(exp.hl)
# exposures  samples phenotypes
#      104      1200         4
dim(expo)
# exposures  samples phenotypes
#      104      1200         4

```

ilod

Function to impute under-LOD values from an ExposomeSet

Description

This function is a wrapper of the functions `impute.MinProb` from the package `imputeLCMD`.

Usage

```

ilod(object, seed = 1234, lod.col = "LOD", pNA = 0.2, tLog = FALSE,
  method = "QRILC", warnings = TRUE, ...)

```

Arguments

<code>object</code>	ExposomeSet which exposures will be imputed.
<code>seed</code>	(default 1234) Seed to make the imputation reproducible.
<code>lod.col</code>	(default "LOD") Name of the column in <code>fData</code> with the threshold of the LOD.
<code>pNA</code>	(default 0.2) Maximum percentage allowed of values under LOD
<code>tLog</code>	(default FALSE) If set to TRUE it transforms all the exposures to lod before the imputation.
<code>method</code>	(default "QRILC") Method to be used to impute the under-LOD values. Two allowed: QRILC method (value "QRILC") and stochastic minimal value approach (value "MinProb").
<code>warnings</code>	(default TRUE) If set to FALSE warnings will not be displayed.
<code>...</code>	Arguments passed to <code>impute.QRILC</code> or <code>impute.MinProb</code> from <code>imputeLCMD</code> .

Value

A new `ExposomeSet` with the imputed exposures.

See Also

[plotMissings](#) to plot the missing data of an `ExposomeSet`, [tableMissings](#) to get a table with the missing data of an `ExposomeSet`

Examples

```

## Not run:
#Being x an ExposomeSet
x <- ilod(x)

## End(Not run)

```

imExposomeSet	<i>Class imExposomeSet</i>
---------------	----------------------------

Description

Class `imExposomeSet` was designed to store the exposures obtained after a multiple imputation process done using `mice`. The `data.frame` obtained from `mice` has the particularity to contain the columns `.imp` and `.id` joint to phenotypes and exposures. The slots `assayData`, `featureData`, and `phenoData` are coordinated.

Usage

```
## S4 method for signature 'imExposomeSet,ANY'
plot(x, y, ...)

## S4 method for signature 'imExposomeSet'
dim(x)

## S4 method for signature 'imExposomeSet'
expos(object)

## S4 method for signature 'imExposomeSet'
exposureNames(object)

## S4 method for signature 'imExposomeSet'
extract(object, rid = -1, ...)

## S4 method for signature 'imExposomeSet'
exwas(object, formula, filter, family, ...,
       baselevels, tef = TRUE, verbose = FALSE, warnings = TRUE)

## S4 method for signature 'imExposomeSet'
familyNames(object, by.exposure = FALSE)

## S4 method for signature 'imExposomeSet'
phenotypeNames(object)

## S4 method for signature 'imExposomeSet'
plotFamily(x, family, group, group2,
           scatter = FALSE, na.omit = TRUE)

## S4 method for signature 'imExposomeSet'
sampleNames(object)

## S4 method for signature 'imExposomeSet'
x[[i]]

## S4 method for signature 'imExposomeSet,ANY,ANY,ANY'
x[i, j, k, ..., drop = FALSE]

## S4 method for signature 'imExposomeSet'
```

toES(object, rid = 1)

Arguments

x	An imExposomeSet object.
y	NOT USED
...	Other used arguments
object	An object of class imExposomeSet
rid	Number of the imputation to be extracted
formula	Formula, not including exposures, to be tested.
filter	Expression to be used to filter ExposomeSet
family	Family describing the nature of the health outcome
baselevels	Labeled vector with the base-level of the categorical exposures
tef	If set to TRUE the threshold for effective test is computed.
verbose	If set to TRUE it shows messages on progression.
warnings	If set to TRUE it shows warnings on progression.
by.exposure	If set to TRUE it returns the family which each exposure belongs
group	Phenotype to group exposures
group2	NOT USED
scatter	If set to true it shows the samples value in the plot
na.omit	NOT USED
i	Character corresponding to selected exposures.
j	Character corresponding to selected sample names.
k	Character corresponding to selected phenotypes.
drop	NOT USED

Value

An object of class `imExposomeSet`

Methods (by generic)

- `plot`: Wrapper for `plotFamily` method.
- `dim`: Returns the number of exsures, samples and phenotypes.
- `expos`: Returns a `data.frame` with exposures.
- `exposureNames`: Method to obtain samples' names
- `extract`: Method to extract exposures for a single imputation
- `exwas`: Performs an EXposome-Wide Association Study
- `familyNames`: Getter to obtain the families's names of the family of each exposure.
- `phenotypeNames`: Getter to obtain the families's names of the family of each exposure.
- `plotFamily`: Draws a boxplot or accumulated-bar plot for each exposure in the all imputed sets.
- `sampleNames`: Method to obtain samples' names
- `[[]`: Get an `ExposomeSet` with the selected imputation
- `[`: Subset an `imExposomeSet`
- `toES`: Returns an [ExposomeSet](#) with ethe given imputation.

Slots

nimputation Number of imputations done with mice.
 assayData data.frame containing .imp, .id and the exposures.
 featureData data.frame containing the description of the exposures.
 phenoData data.frame containing .imp, .id and the phenotypes.

Note

Sample order is not guarantee

See Also

[loadImputed](#) to create an imExposomeSet from data.frames

 imputation

Function to impute missing values from an ExposomeSet

Description

This function is a wrapper of the functions mice and complete from the package mice. Also to the impute from the package Hmisc. The function is designed to use those functions to impute missing values on exposures (not in phenotypes).

Usage

```
imputation(object, select, ..., messages = FALSE)
```

Arguments

object	ExposomeSet which exposures will be imputed.
select	Exposures to be imputed. If missing, all exposes will be imputed.
...	Argument given to function mice of package mice (printFlag is set from messages).
messages	(default FALSE) If set to TRUE messages from mice's function will be displayed.

Value

A new ExposomeSet with the imputed exposures.

See Also

[plotMissings](#) to plot the missing data of an ExposomeSet, [tableMissings](#) to get a table with the missing data of an ExposomeSet

Examples

```
## Not run:
#Being x an ExposomeSet
x <- imputation(x)

## End(Not run)
```

<code>imputeLOD</code>	<i>Function to impute values under limit of detection</i>
------------------------	---

Description

Homologous function to the `ilod` method of `ExposomeSet` for a given `data.frame` of exposures and a vector of threshold. The use of this function is related to HELIX Project.

Usage

```
imputeLOD(x, lod, description = NULL, pNA = 0.2, pLOD = 0, log = TRUE,
          seed = NULL)
```

Arguments

<code>x</code>	<code>data.frame</code> containing the exposures as columns and the samples as rows.
<code>lod</code>	vector containing the
<code>description</code>	1 means values under LOD while 2 means quantifiable value, 3
<code>pNA</code>	(default: 0.2) maximum percentage of allowed missing data
<code>pLOD</code>	(default: 0) minimum percentave of values under LOD
<code>log</code>	(default: NA) log transformation to normalize data
<code>seed</code>	(default: NULL)

Value

A new `data.frame` with the imputed exposures.

Examples

```
## Not run:
inma.imp <- imputeLOD(x = raw, lod = lod, description = desc,
                    pNA = pNA, pLOD = pLOD, log = log, seed = seed)

## End(Not run)
```

<code>loadExposome</code>	<i>Creation of an <code>ExposomeSet</code> from <code>data.frames</code></i>
---------------------------	--

Description

Given three `data.frames` that defines the exposome (measures of exposome, exposome description and individuals phenotype) it loads them and creates an object of type `ExposomeSet`.

Usage

```
loadExposome(exposures, description, phenotype, description.famCol = "family",
            exposures.asFactor = 5, warnings = TRUE)
```

Arguments

exposures	data.frame of exposures.
description	data.frame with the description of the exposures (relation between exposures and exposure-family).
phenotype	data.frame with the phenotypes of interest.
description.famCol	(default "family") Index where the family's name (per exposures) is found in file "description". It can be both numeric or character.
exposures.asFactor	(default 5) The exposures with more than this number of unique items will be considered as "continuous" while the exposures with less or equal number of items will be considered as "factor".
warnings	(default TRUE) If TRUE shows useful information/warnings from the process of loading the exposome.

Details

The rows of the exposure's data.frames, that corresponds to samples' names, must be the same than the phenotype's data.frames. In the same way, the columns in exposure's data.frames must be the same in description data.frame.

Value

An object of class [ExposomeSet](#).

Note

[ExposomeSet](#)'s fData will contain some inner columns called .std, .trn, .fct and .type in order to trace the transformations an exposure suffers and to know, at any moment, if an exposure is categorical or continuous. The "description" file can contain a column called type with values "factor" and "numeric" to specify how an exposure needs to be understood. If given, this column will be renamed to .type. If not given, it will be created using exposures.asFactor value.

See Also

[ExposomeSet](#) for class description, [readExposome](#) for constructor from txt/csv files.

Examples

```
path <- file.path(path.package("rexposome"), "extdata")
description <- file.path(path, "description.csv")
phenotype <- file.path(path, "phenotypes.csv")
exposures <- file.path(path, "exposures.csv")
dd <- read.csv(description, header=TRUE)
ee <- read.csv(exposures, header=TRUE)
pp <- read.csv(phenotype, header=TRUE)
rownames(dd) <- dd[, 2]
dd <- dd[, -2]
rownames(ee) <- ee[, 1]
ee <- ee[, -1]
rownames(pp) <- pp[, 1]
pp <- pp[, -1]
exp <- loadExposome(
```

```

exposures = ee,
description = dd,
phenotype = pp,
description.famCol = "Family"
)

```

loadImputed

Creation of an imExposomeSet from data.frames

Description

Given a `data.frame` from code with the multiple imputations of both exposures and phenotypes, join with a `data.frame` with exposures' description, and object of class `imExposomeSet` is created.

Usage

```

loadImputed(data, description, description.famCol = "family",
description.expCol = "exposure", exposures.asFactor = 5,
warnings = TRUE)

```

Arguments

<code>data</code>	The <code>data.frame</code> of both exposures and phenotypes obtained from mice.
<code>description</code>	<code>data.frame</code> with the description of the exposures (relation between exposures and exposure-family).
<code>description.famCol</code>	(default "family") Index where the family's name (per exposures) if found in file "description". It can be both numeric or character.
<code>description.expCol</code>	(default "exposures") Index where the exposure's name if found in file "description". It can be both numeric or character.
<code>exposures.asFactor</code>	(default 5) The exposures with more than this number of unique items will be considered as "continuous" while the exposures with less or equal number of items will be considered as "factor".
<code>warnings</code>	(default TRUE) If TRUE shows useful information/warnings from the process of loading the exposome.

Details

The coordination of the information is based in the columns `.imp` and `.id` from the `data.frame` obtained from mice. The division of exposures and phenotypes is based in description `data.frame`, that are the exposures. Hence, the elements in the main `data.frame` that are not in the description, are the phenotypes.

Value

An object of class `imExposomeSet`.

See Also

[imExposomeSet](#) for class description

Examples

```

data("me") # me is an imputed matrix of exposure and phenotypes
path <- file.path(path.package("rexposome"), "extdata")
description <- file.path(path, "description.csv")
dd <- read.csv(description, header=TRUE, stringsAsFactors=FALSE)
dd <- dd[dd$Exposure %in% colnames(me), ]
ex_imp <- loadImputed(data = me, description = dd,
description.famCol = "Family",
description.expCol = "Exposure")

```

me	<i>data.frame for testing purposes</i>
----	--

Description

data.frame created with mice used to test and illustrate the creation of imExposomeSet.

Usage

```
data("me")
```

Format

An object of class data.frame with 654 rows and 57 columns.

Value

A data.frame.

Examples

```

data("me")
dim(me)
colnames(me)

```

mExWAS	<i>Class mExWAS</i>
--------	---------------------

Description

Class mExWAS obtained from [mexwas](#) method of an [ExposomeSet](#) object, contains the result of testing the multiple models of exposures of an ExposomeSet to a set of given phenotypes. "mExWAS" is the # acronym of "Multivariate Exposome-Wide Association Study".

Usage

```
## S4 method for signature 'mExWAS,ANY'
plot(x, y, ...)

## S4 method for signature 'mExWAS'
extract(object, type = "test", sort = TRUE)

## S4 method for signature 'mExWAS'
plotExwas(object, ..., subtitles, color, exp.order, labels,
  show.effective = TRUE)
```

Arguments

x	Object of class mExWAS
y	NOT USED
...	Other used arguments.
object	object of class mExWAS.
type	(default "test"). Can take "test" or "raw" to obtain a data.frame of glmnet result.
sort	NOT USED
subtitles	NOT USED
color	NOT USED
exp.order	NOT USED
labels	NOT USED
show.effective	NOT USED

Value

An object of class mExWAS

Methods (by generic)

- plot: Wrapper for plotExwas method.
- extract: Method to obtain the generated model
- plotExwas: Method to plot a heap-map with the coefficient of each exposure

Slots

result klist with the fitted model and result.
 phenotype Name of the phenotype used in the analysis.
 description feature data from original ExposomeSet.

See Also

[mexwas](#) to perform a Multivariate Exposome-Wide Association Study and to create a mExWAS, [exwas](#) to perform an Exposome-Wide Association Study and to create an ExWAS

mexwas	<i>Testing the association between an exposure and a phenotype of an ExposomeSet using a multivariate approach.</i>
--------	---

Description

The mexwas method performs an "Multi Exposome-Wide Association Study" (m-ExWAS) using the exposures in [ExposomeSet](#) and one of its phenotype. It uses the packages `glmnet` and `partDSA`.

Usage

```
mexwas(object, phenotype, family, warnings = TRUE)
```

Arguments

object	ExposomeSet that will be used for the ExWAS.
phenotype	Target phenotype used for the study. If missing all the phenotypes in the ExposomeSet will be used.
family	It must describe the nature of the outcome. Can take values "gaussian", "binomial", "poisson", "multinomial", "cox" or "mgaussian".
warnings	(default TRUE) If set to FALSE warnings will not be displayed.

Value

Returns an object of class [mExWAS](#)

See Also

[extract](#) to obtain a table with the result of the ExWAS, [plotExwas](#) to plot the results of the ExWAS

Examples

```
data("exposome")
wt <- mexwas(expo[3:7, 1:100], phenotype = "asthma", family = "binomial")
```

ndim	<i>Number of principal components in an ExposomePCA.</i>
------	--

Description

Number of principal components in an ExposomePCA.

Usage

```
ndim(object)
```

Arguments

object	ExposomePCA to obtain the number of components.
--------	---

Value

The number of components in the ExposomePCA.

See Also

[plotPCA](#) to plot the PCA values of an [ExposomePCA](#), [clustering](#) to see how the exposures can cluster samples, [correlation](#) to compute the correlation between exposures

Examples

```
data("exposome")
epca <- pca(expo[3:7, 1:100])
ndim(epca)
```

normalityTest	<i>It creates a data.frame of boolean indicating if the exposures follows a normal distribution or not.</i>
---------------	---

Description

This functions uses [shapiro.test](#) to test the normality of the exposures and returns a data.frame with a boolean value and a p-value for each exposure.

Usage

```
normalityTest(object, exposure, th = 0.05, min.val = 5, na.rm = TRUE,
  warnings = TRUE)
```

Arguments

object	ExposomeSet with the exposome to be tested.
exposure	Name of the exposure to be tested, if missing all the exposures will be tested.
th	(by default 0.05) Threshold to considere an exposure to follow a normal distribution.
min.val	(by default 5) Minimum number of values not missings to test the exposures.
na.rm	(by default TRUE) Removes the NA values to test the normality on the exposure.
warnings	(by default: TRUE) Show warnings if required.

Value

A data.frame with three columns: exposure, normality and p.value. "exposure" column contains the name of each exposure. "normalty" column contains a logical value indicating if the obtained p-value is under the given threshold. "p.value" column contains the obtained p-value from [shapiro.test](#).

See Also

[plotHistogram](#) to draw the shape of an exposure, [plotMissings](#) to draw a plot with the missing data an [ExposomeSet](#), [imputation](#) to impute missing data on the exposures of an [ExposomeSet](#)

Examples

```
data("exposome")
normalityTest(expo)
```

pca

*Creation of an ExposomePCA from an ExposomeSet.***Description**

Method to calculate a PCA based on the exposures of an [ExposomeSet](#). Only numerical-exposures (non categorical) will be computed. The function returns an [ExposomePCA](#) object. This PCA is performed by using [FactoMineR](#) package.

Usage

```
pca(object, npc = 10)
```

Arguments

object	ExposomeSet which exposures will be used for the PCA
npc	(by default 10) number of dimensions kept in the results

Value

An ExposomePCA with the values of the PCA.

See Also

[plotPCA](#) to plot the PCA values of an [ExposomePCA](#), [clustering](#) to see how the exposures can cluster samples, [correlation](#) to compute the correlation between exposures

Examples

```
data("exposome")
epca <- pca(expo[12:20, ])
```

phenotypeNames

*Getter to obtain the phenotype's names of an ExposomeSet or ExposomePCA.***Description**

Getter to obtain the phenotype's names of an ExposomeSet or ExposomePCA.

Usage

```
phenotypeNames(object)
```

Arguments

object	ExposomeSet that will be queried for the phenotype's names.
--------	---

Value

The name of the phenotypes as a character vector.

See Also

[exposureNames](#) to get the name of the exposures, [familyNames](#) to get the families of exposures

Examples

```
data("exposome")
phenotypeNames(expo)
```

plot3PCA

Plotting PCA in a 3D space

Description

Method to draw a plot for samples using three PC contained in an [ExposomePCA](#)

Usage

```
plot3PCA(object, cmpX, cmpY, cmpZ, phenotype, main, angle = 35, pch = 16,
  legend = TRUE, plines = TRUE)
```

Arguments

object	An onbject of class ExposomePCA
cmpX	Component to be placed at X axis
cmpY	Component to be placed at Y axis
cmpZ	Component to be placed at Z axis
phenotype	Used to color samples by phenotype
main	Title for the plot
angle	(default 35) angle between x and y axis.
pch	(default 16) plotting "character", i.e. symbol to use.
legend	(default TRUE) If TRUE shows the legend.
plines	(default TRUE) If TRUE it draws the lines from each dot to the base plane.

Value

A list with different graphics option from `scatterplot3d`.

See Also

[pca](#) to compute PCA on an [ExposomeSet](#), [plotPCA](#) to plot the PCA, [ExposomePCA](#) as main class

```
data("exposome") epca <- pca(expo[3:7, 1:100]) plot3PCA(epca, cmpX = 1, cmpY = 2, cmpZ = 3,
  phenotype = "sex")
```

plotClassification	<i>Draw the profile of the levels exposures after a classification with a clustering method</i>
--------------------	---

Description

Draw the profile of the levels exposures after a classification with a clustering method

Usage

```
plotClassification(object, type = "heatmap", ...)
```

Arguments

object	Object of class <code>ExposomeClust</code>
type	Two types are available: "heatmap" or "valuemap".
...	NOT USED

Value

A list with different graphics parameters.

See Also

[clustering](#) as a constructor for `ExposomeClust`, [classification](#) to see how to obtain the classification of the samples from an `ExposomeClust`

Examples

```
## Not run:
data("eclust")
plotClassification(expo_c)

## End(Not run)
```

plotCorrelation	<i>It draws both circos or matrix plot for the correlation in <code>ExposomeCorr</code></i>
-----------------	---

Description

While the circos plot can be used to see the general behaviours intra and extra families of exposures, the matrix plot allows for a detailed view of the correlations within an `ExposomeCorr` object.

Usage

```
plotCorrelation(object, type = "circos", ...)
```

Arguments

object	ExposomeCorr which correlations will be plotted.
type	(default "circos") Can take both "circos" or "matrix".
...	Arguments given to corrrplot of package corrplot if a matrix is draw. Moreover extra arguments are can be passed to inner functions to draw both the matrix and the circos of correlations.

Value

A list with different graphics parameters.

See Also

[correlation](#) as a constructor for [ExposomeCorr](#) objects, [pca](#) to compute PCA on exposures

Examples

```
data("exposome")
expo.c <- correlation(expo)
plotCorrelation(expo.c, type="circos")
plotCorrelation(expo.c, type="matrix")
```

plotEffect

Function to draw a plot of the pvalues stored in an ExWAS object

Description

This function draws a sort of manhattan plots using the p-value of the association of the exposures with phenotypes of an ExWAS object.

Usage

```
plotEffect(x, y, select, xlab, ylab)
```

Arguments

x	An ExWAS object which effect will be plotted.
y	(optional) Another ExWAS object. If provided its effects will be plotted in Y-axis.
select	(optional) Character with exposures to be shown.
xlab	(optional) Label for X-axis.
ylab	(optional) Label for Y-axis.

Value

An object of class ggplot.

See Also

[exwas](#) as a constructor for [ExWAS](#) objects, [extract](#) to obtain a table with the result of the ExWAS

Examples

```
data(exposome)
w1 <- exwas(expo[1:5, ], asthma~1, family = "binomial")
w2 <- exwas(expo[1:5, ], asthma~sex+age, family = "binomial")
plotEffect(w1, w2)
```

plotEXP

*Plot correlation between exposures and PCA***Description**

Function used to plot the correlation between the exposures in an [ExposomePCA](#) and the values for each component of the PCA in the same [ExposomePCA](#)

Usage

```
plotEXP(object, exposure)
```

Arguments

object An object of class [ExposomePCA](#)
exposure (optional) to select a set of exposures to be plotted. If not given all are used.

Value

An object of class ggplot.

See Also

[pca](#) to compute PCA on an [ExposomeSet](#), [plotPHE](#) to plot the P-Value of association between phenotypes and PCA, [ExposomePCA](#) as main class

Examples

```
data("exposome")
epca <- pca(expo[3:7, 1:100])
plotEXP(epca)
```

plotExwas

*Function to draw a plot of the pvalues stored in an ExWAS object***Description**

This function draws a sort of manhattan plots using the p-value of the association of the exposures with phenotypes of an ExWAS object.

Usage

```
plotExwas(object, ..., subtitles, color, exp.order, labels,
  show.effective = TRUE)
```

Arguments

object	An ExWAS object which p-values will be plotted.
...	Other objects of class ExWAS.
subtitles	(optional) Characters used as "subtitle" when more than one ExWAS is given.
color	(optional) Character vector of HTML colors, labeled with family's names. Used to colore the exposures.
exp.order	(optional) Character vector of exposures used to order and subset the plot.
labels	(optional) Character vector with the labels for each exposure. It must be labeled vector.
show.effective	(default TRUE) If set to FALSE, line showing effective test threshold is not shown.

Value

An object of class ggplot.

See Also

[exwas](#) as a constructor for [ExWAS](#) objects, [extract](#) to obtain a table with the result of the ExWAS

Examples

```
data(exposome)
w1 <- exwas(expo[1:5, ], asthma~1, family = "binomial")
plotExwas(w1)
```

plotFamily

It draws the profile of the exposome in an ExposomeSet

Description

This function draw a profile of the full exposome into an [ExposomeSet](#) or the profile of the exposures in a specific family. For continuous families, box-plots are drawn; while for categorical families accumulative bar-charts.

Usage

```
plotFamily(x, family, group, group2, scatter = TRUE, na.omit = TRUE)
```

Arguments

x	ExposomeSet which exposome will be plotted.
family	Name of the family that will be drawn. 'all' is allowed to draw a grid with all the families.
group	If set it displays the family grouped by the given phenotype.
group2	If set it displays the family grouped by the given phenotype.
scatter	(default TRUE) If the family to be plotted is continuous, the samples will be shown.
na.omit	(default TRUE) Do not show NA values.

Value

A ggplot object if a family was selected. `invisible()` if argument `family` was set to "all".

See Also

[plotHistogram](#) to draw the shape of an exposure, [plotMissings](#) to plot the missing data from an [ExposomeSet](#)

Examples

```
data("exposome")
plt <- plotFamily(expo, family = "Metals")
plt <- plt + ggplot2::ggtitle("Metals")
plt
plt <- plotFamily(expo, family = "Indoor air")
plt <- plt + ggplot2::ggtitle("Indoor air")
plt
```

plotHistogram

It draws a histogram for each exposure in an ExposomeSet

Description

It draws a grid with an histogram per exposure in an [ExposomeSet](#).

Usage

```
plotHistogram(x, select, density = TRUE, show.trans = FALSE)
```

Arguments

<code>x</code>	ExposomeSet which exposome will be plotted.
<code>select</code>	Name fo the exposure to be plotted. If missing, all exposures will be used.
<code>density</code>	(default TRUE) If TRUE a density plot is drawn overlapping the histogram.
<code>show.trans</code>	(default FALSE) If set to TRUE it will draw a panel of auxiliar plots with the continuous exposure transformed with log and sqrt.

Value

A ggplot object.

See Also

[plotFamily](#) to draw the profile of a family of exposures, [plotMissings](#) to plot the missing data from an [ExposomeSet](#)

Examples

```
data("exposome")
plotHistogram(expo[1:3, ], select = "ldde_lip")
```

plotLOD	<i>It draws a chart with the percentage of under-LOD values in an ExposomeSet</i>
---------	---

Description

This function can be used to draw the amount of under-LOD values in the exposures of an [ExposomeSet](#).

Usage

```
plotLOD(object, lod.col = "LOD", x.max = 100, sort = TRUE)
```

Arguments

object	ExposomeSet which exposome will be plotted.
lod.col	(default "LOD") Name of the column in fData containing the LOD thresholds.
x.max	(default 100) Fix the maximum value of the X-axis.
sort	(default TRUE) If TRUE the chart will be ordered from the features with less missing data to the ones with more under-LOD values.

Value

A ggplot object.

See Also

[plotFamily](#) to draw the profile of a family of exposures, [plotHistogram](#) to draw the shape of an exposure, [tableMissings](#) to get a table with the missing data of an ExposomeSet, [imputation](#) to impute missing data on the exposures of an ExposomeSet

Examples

```
data("exposome")
# The included has no missing data
plotLOD(expo)
```

plotMissings	<i>It draws a chart with the percentage of missing in an ExposomeSet</i>
--------------	--

Description

This function can be used to draw the number of missing data in exposures and in phenotypes of an [ExposomeSet](#).

Usage

```
plotMissings(object, set, x.max = 100, sort = TRUE)
```


Arguments

object	ExposomeSet which exposome will be plotted.
set	Can be set to "exposures" or to "phenotypes".
x.max	(default 100) Fix the maximum value of the X-axis.
sort	(default TRUE) If TRUE the chart will be ordered from the features with less missing data to the ones with more missing data.

Value

A ggplot object.

See Also

[plotFamily](#) to draw the profile of a family of exposures, [plotHistogram](#) to draw the shape of an exposure, [tableMissings](#) to get a table with the missing data of an [ExposomeSet](#), [imputation](#) to impute missing data on the exposures of an [ExposomeSet](#)

Examples

```
data("exposome")
# The included has no missing data
plotMissings(expo, set = "exposures")
plotMissings(expo, set = "phenotypes")
```

plotPCA

Plotting PCA

Description

Method to draw a plot for PCA contained in an [ExposomePCA](#)

Usage

```
plotPCA(object, set, cmpX = 1, cmpY = 2, show.exposures = FALSE,
        show.samples = FALSE, phenotype)
```

Arguments

object	An object of class ExposomePCA
set	Group ("all", "samples" or "exposures") that will be plotted.
cmpX	(default: 1) component to be placed at X axis
cmpY	(default: 2) component to be placed at Y axis
show.exposures	(default: FALSE) If set to true, labels indicating the exposures are shown.
show.samples	(default: FALSE) If set to true, labels indicating the samples are shown.
phenotype	If set is set to "samples" can be used to color samples by phenotype

Value

An object of class ggplot or an object of class gtable if argument set was set to "all".

See Also

[pca](#) to compute PCA on an [ExposomeSet](#), [plotPCA](#) to plot the PCA, [ExposomePCA](#) as main class

Examples

```
data("exposome")
epca <- pca(expo[3:7, 1:100])
# A grid with exposures space, samples space and explained variance
plotPCA(epca, set = "all")
# Only exposures space
plotPCA(epca, set = "exposures") + ggplot2::theme(legend.position = "bottom")
# Only samples space
plotPCA(epca, set = "samples")
# Only samples space but coloured by phenotype
plotPCA(epca, set = "samples", phenotype = "sex") +
ggplot2::theme(legend.position = "bottom")
```

plotPHE

Plot association score between phenotypes and PCA

Description

Function used to plot the association between the phenotypes in an [ExposomePCA](#) and the values for each component of the PCA in the same [ExposomePCA](#)

Usage

```
plotPHE(object, phenotype, exp2fac = 5)
```

Arguments

object	An object of class ExposomePCA
phenotype	(optional) to select a set of phenotypes to be plotted. If not given all are used.
exp2fac	(default, 5) Threshold to consider a phenotype categorical (less or equal to) or continuous (more than).

Value

An object of class `ggplot`.

See Also

[pca](#) to compute PCA on an [ExposomeSet](#), [plotEXP](#) to plot the correlation between exposures and PCA, [ExposomePCA](#) as main class

Examples

```
data("exposome")
epca <- pca(expo[3:7, 1:100])
plotPHE(epca)
```

plotVolcano	<i>Function to draw a plot of the pvalues stored in an ExWAS object</i>
-------------	---

Description

This function draws a sort of manhattan plots using the p-value of the association of the exposures with phenotypes of an ExWAS object.

Usage

```
plotVolcano(x, p.value = -log10(0.001), show.effect = FALSE)
```

Arguments

x	An ExWAS object which effect will be plotted.
p.value	(default "-log10(0.001)") Threshold for P-Value.
show.effect	(default FALSE) Applies an exponential transformation on the effects of the exposures.

Value

An object of class ggplot.

See Also

[exwas](#) as a constructor for [ExWAS](#) objects, [extract](#) to obtain a table with the result of the ExWAS, [plotEffect](#) to see or compare effects of one or two models.

readExposome	<i>Creation of an ExposomeSet from files</i>
--------------	--

Description

Given the files that defines the exposome (measures of exposome, exposome description and individuals phenotype) it loads them and creates an object of type [ExposomeSet](#).

Usage

```
readExposome(exposures, description, phenotype, sep = ",",
  na.strings = c("NA", "-", "?", " ", "")), exposures.samCol = "sample",
  description.expCol = "exposure", description.famCol = "family",
  phenotype.samCol = "sample", exposures.asFactor = 5, warnings = TRUE)
```

Arguments

<code>exposures</code>	String with the path to the file with the matrix of exposures.
<code>description</code>	String with the path to the file with the description of the exposures (relation between exposures and exposure-family).
<code>phenotype</code>	String with the path to the file with the phenotypes of interest.
<code>sep</code>	(default <code>" , "</code>) Separator used by <code>read.table</code> to load the files "exposures", "description" and "phenotype".
<code>na.strings</code>	(default <code>c("NA", "-", "?", " ", "")</code>) Character defining the NA values in exposure's files.
<code>exposures.samCol</code>	(default <code>"sample"</code>) Index where the samples' name are found in file "exposures". It can be both character or numeric.
<code>description.expCol</code>	(default <code>"exposure"</code>) Index where the exposures' name are found in file "description". It can be both numeric or character.
<code>description.famCol</code>	(default <code>"family"</code>) Index where the family's name (per exposures) if found in file "description". It can be both numeric or character.
<code>phenotype.samCol</code>	(default <code>"sample"</code>) Index where the sample's name are found in file "phenotype". It can be both numeric or character.
<code>exposures.asFactor</code>	(default 5) The exposures with more than this number of unique items will be considered as "continuous" while the exposures with less or equal number of items will be considered as "factor".
<code>warnings</code>	(default TRUE) If TRUE shows useful information/warnings from the process of loading the exposome.

Details

The rows of the exposure's file, that corresponds to samples' names, must be the same than the phenotype's file. In the same way, the columns in exposure's file must be the same found as rows in description file.

Value

An object of class `ExposomeSet`.

Note

`ExposomeSet`'s `fData` will contain some inner columns called `.std`, `.trn`, `.fct` and `.type` in order to trace the transformations an exposure suffers and to know, at any moment, if an exposure is categorical or continuous. The "description" file can contain a column called `type` with values `"factor"` and `"numeric"` to specify how an exposure needs to be understood. If given, this column will be renamed to `.type`. If not given, it will be created using `exposures.asFactor` value.

See Also

`ExposomeSet` for class description, `loadExposome` for constructor from loaded data.frames

Examples

```
## Locate the data-files
path <- file.path(path.package("rexposome"), "extdata")
description <- file.path(path, "description.csv")
phenotype <- file.path(path, "phenotypes.csv")
exposures <- file.path(path, "exposures.csv")

## Create ExposomeSet from files
exp <- readExposome(
  exposures = exposures,
  description = description,
  phenotype = phenotype,
  exposures.samCol = 1,
  description.expCol = 2,
  description.famCol = 1,
  phenotype.samCol = 1
)
```

rexposome

rexposome: Package for exposome exploration and outcome data analysis

Description

#' @section exposures loading and exposures management: rexposome offers two methods to bring exposome data to R and Bioconductor. [readExposome](#) allows to read three txt-like files (.csv, .tsv, ...) while [loadExposome](#) is used with matrix and data.frames. The class obtained is an [ExposomeSet](#), a class based in eSet for exposome data management.

exposures processing

The packages offers a wide set of functions to preprocess exposome data. Method [trans](#) allow to transform the exposures, method [normalityTest](#) allows to check for normality in exposome, [standardize](#) allows to standardize the exposures, among others. Finally, [impute](#) and [ilod](#) allow to use mice, Hmisc and imputeLCMD for exposure missing data and exposure under-lod data imputation.

exposures analyses

the two methods [exwas](#) and [mexwas](#) allows to test the association between exposures and health outcomes (phenotype data).

exposures plotting

The methods [plotFamily](#) allows to see how the exposures behaves within families. [plotCorrelation](#) helps to understand how exposures are related between themselves. [plotClassification](#) allows to visually detect clusters of samples that share the same pattern of levels of exposures.

```

standardize      #' Summary of an ExposomeSet. #' #' Given an ExposomeSet is
                  shows a summary for its exposures or #' its phenotypes. #' #' @name
                  Summary #' @rdname Summary-methods #' @aliases Summary #'
                  @param object codeExposomeSet with 'set' will be summarized. #'
                  @param set Set to be summarized ("exposures" or "phenotypes"). #'
                  @param select Subsetting of exposures of phenotypes. #' @return A
                  basic description of the exposures in the ExposomeSet #' @examples
                  #' data("exposome") #' Summary(expo, set = "exposures") #' @export
                  Summary setGeneric("Summary", function(object, set=c("exposures",
                  "phenotypes"), select) standardGeneric("Summary") ) Standardize of
                  an ExposomeSet.

```

Description

Given an [ExposomeSet](#) it standardizes the exposures by using mean/sd if method is "normal" or by using median/mad if method is "robust".

Usage

```

standardize(object, select, method = "normal", na.rm = TRUE,
            warnings = TRUE)

```

Arguments

object	ExposomeSet with exposures to be standardized.
select	Subsetting of exposures of phenotypes.
method	(default "normal") Character selecting the method to be applied ("normal" "iqr" or "robust").
na.rm	(by default TRUE) Removes NA data to perform standardization.
warnings	(default TRUE) If set to FALSE warnings are not shown.

Value

An [ExposomeSet](#) with the selected exposures standardized and keeping the others exposures as the original input object.

See Also

[highAndLow](#) to transform the continuous exposures to levelled factors, [trans](#) to transform the exposures

Examples

```

data("exposome")
exp.sn <- standardize(expo, method = "normal", select = "lbde100_lip")
exp.rs <- standardize(expo, method = "iqr", select = "lbde100_lip")
exp.rs <- standardize(expo, method = "robust", select = "lbde100_lip")

```

tableLOD	<i>It creates a vector with the amount of under-LOD exposures in an ExposomeSet</i>
----------	---

Description

This function can be used to obtain a table with the under-LOD data in exposures of an [ExposomeSet](#).

Usage

```
tableLOD(object, output = "n", lod.col = "LOD", sort = TRUE)
```

Arguments

object	ExposomeSet which exposome will be plotted.
output	(default "n") Can be "n" for number of values, and "p" for percentage.
lod.col	(default "LOD") Name of the column in fData containing the LOD thresholds.
sort	(default TRUE) If TRUE the chart will be ordered from the features with less missing data to the ones with more under-LOD values.

Value

A numeric vector with number of under-LOD values per exposure. The vector is labeled with the exposure's names.

See Also

[plotFamily](#) to draw the profile of a family of exposures, [plotHistogram](#) to draw the shape of an exposure, [plotMissings](#) to draw a plot with the missing data an [ExposomeSet](#), [imputation](#) to impute missing data on the exposures of an [ExposomeSet](#)

Examples

```
data("exposome")
# The included has no missing data
tableLOD(expo, output = "n")
```

tableMissings	<i>It creates a vector with the amount of missing in an ExposomeSet</i>
---------------	---

Description

This function can be used to obtain a table with the missing data in exposures and in phenotypes of an [ExposomeSet](#).

Usage

```
tableMissings(object, set, output = "n", sort = TRUE)
```

Arguments

object	ExposomeSet which exposome will be plotted.
set	Can be set to "exposures" or to "phenotypes".
output	(default "n") Can be "n" for number of values, and "p" for percentage.
sort	(default TRUE) If TRUE the chart will be ordered from the features with less missing data to the ones with more missing data.

Value

A numeric vector with number of missing values per exposure. The vector is labeled with the exposure's names.

See Also

[plotFamily](#) to draw the profile of a family of exposures, [plotHistogram](#) to draw the shape of an exposure, [plotMissings](#) to draw a plot with the missing data an [ExposomeSet](#), [imputation](#) to impute missing data on the exposures of an [ExposomeSet](#)

Examples

```
data("exposome")
# The included has no missing data
tableMissings(expo, set = "exposures")
tableMissings(expo, set = "phenotypes")
```

 tef

Function to get the Threshold for effective tests (TEF)

Description

Function to get the Threshold for effective tests (TEF)

Usage

```
tef(object)
```

Arguments

object	An ExWAS object
--------	-----------------

Value

A number indicating the effective threshold.

References

Evaluating the effective numbers of independent tests and significant p-value thresholds in commercial genotyping arrays and public imputation reference datasets. Miao-Xin Li, Juilian M. Y. Yeung, Stacey S. Cherny and Pak C. Sham. May 2012 Hum Genet.

See Also

[exwas](#) as a constructor for [ExWAS](#) objects

Examples

```
data(exposome)
w1 <- exwas(expo[1:5, ], asthma~1, family = "binomial")
w2 <- exwas(expo[1:5, ], asthma~sex+age, family = "binomial")
tef(w1)
tef(w2)
```

toES

Method to convert an imExposomeSet to an ExposomeSet

Description

This methods allows to select an imputed-set and use it to create an [ExposomeSet](#) from an [imExposomeSet](#).

Usage

```
toES(object, rid = 1)
```

Arguments

object	An object of class imExposomeSet
rid	(default 1) Number of the imputation to be extracted

Value

An object of class [ExposomeSet](#)-

Examples

```
data("ex_imp")
toES(ex_imp, rid = 1)
```

trans

Function to apply a transformation to the exposures of an Exposome-Set

Description

The exposures in an [ExposomeSet](#) can be transformed using this function. transform applies a function fun to the selected exposures.

Usage

```
trans(object, fun, select, by.exposure = FALSE, ...)
```

Arguments

object	ExposomeSet which exposures will be transformed.
fun	Function to be applied on the exposures.
select	If not set, receive the name of all exposures. It can takes a character vector to select specific exposures.
by.exposure	(default FALSE) If TRUE applies fun to each exposure (given as a vector). If FALSE the matrix of exposures is given to fun.
...	Argument given to fun.

Value

A new ExposomeSet with selected exposures transformed with fun.

See Also

[highAndLow](#) to transform the continuous exposures to levelled factors, [standardize](#) to standardize by normal or robust methods the exposures

Examples

```
data("exposome")
exp.t <- trans(expo, fun = log, select = "ldde_lip")
```

volcano_plot

Function to draw a Volcano Plot

Description

Function that takes two numeric vectors (P-Value and fold change) and draws a volcano plot using [ggplot2](#)

Usage

```
volcano_plot(pval, fc, names, size = 2, tFC = 2, tPV = -log10(0.001),
  show.effect = FALSE)
```

Arguments

pval	numeric vector of P.Values
fc	numeric vector of fold change
names	character vector with the feature's names.
size	(default 2) Sice of the labels in case they are placed.
tFC	(default 2) fold change threshold. It can be set to NULL to do not filter.
tPV	(default $-\log_{10}(0.001)$) P-Value threshold. It can be set to NULL to not filter.
show.effect	(default FALSE) If set to TRUE, the X-axis will should $2^{\log_{2}FC}$ instead to teh default $\log_{2}FC$.

Value

A ggplot object

Examples

```
data(exposome)
w1 <- extract(exwas(expo[1:20, ], asthma~1, family = "binomial"))
volcano_plot(w1$pvalue, w1$effect, rownames(w1))
```

Index

- * **datasets**
 - ex_imp, 19
 - expo, 5
 - expo_c, 15
 - me, 29
- [(imExposomeSet), 23
- [, imExposomeSet, ANY, ANY, ANY-method
 - (imExposomeSet), 23
- [[, imExposomeSet-method
 - (imExposomeSet), 23
- AnnotatedDataFrame, 9, 10, 14
- AssayData, 9, 14
- classification, 3, 4, 35
- classification, ExposomeClust-method
 - (ExposomeClust), 7
- clustering, 3, 3, 5, 7, 8, 32, 33, 35
- clustering, ExposomeSet-method
 - (ExposomeSet), 11
- cor, 5, 8
- correlation, 5, 11, 32, 33, 36
- correlation, ExposomeSet-method
 - (ExposomeSet), 11
- corrplot, 36
- cramersV, 5
- dim, ExposomeCorr-method (ExposomeCorr),
 - 8
- dim, ExposomeSet-method (ExposomeSet), 11
- dim, imExposomeSet-method
 - (imExposomeSet), 23
- eSet, 9–11, 14, 15
- eSet-class, 8
- ex_imp, 19
- expo, 5
- expo_c, 15
- expos, 6
- expos, ExposomeSet-method (ExposomeSet),
 - 11
- expos, imExposomeSet-method
 - (imExposomeSet), 23
- ExposomeClust, 3, 4, 7, 7, 8, 35
- ExposomeClust-class (ExposomeClust), 7
- ExposomeCorr, 5, 8, 8, 36
- ExposomeCorr-class (ExposomeCorr), 8
- ExposomePCA, 9, 10, 32–34, 37, 41, 42
- ExposomePCA-class (ExposomePCA), 9
- ExposomeSet, 3, 5–9, 11, 11, 12, 13, 15, 16,
 - 18, 20, 24, 26, 27, 29, 31–34, 37–49
- ExposomeSet-class (ExposomeSet), 11
- exposureNames, 15, 15, 20, 34
- exposureNames, ExposomePCA-method
 - (ExposomePCA), 9
- exposureNames, ExposomeSet-method
 - (ExposomeSet), 11
- exposureNames, imExposomeSet-method
 - (imExposomeSet), 23
- extract, 16, 19, 31, 36, 38, 43
- extract, ExposomeCorr-method
 - (ExposomeCorr), 8
- extract, ExposomePCA-method
 - (ExposomePCA), 9
- extract, ExWAS-method (ExWAS), 16
- extract, imExposomeSet-method
 - (imExposomeSet), 23
- extract, mExWAS-method (mExWAS), 29
- ExWAS, 16, 17, 18, 30, 36, 38, 43, 49
- exwas, 16, 18, 18, 30, 36, 38, 43, 45, 49
- exwas, ExposomeSet-method (ExposomeSet),
 - 11
- exwas, imExposomeSet-method
 - (imExposomeSet), 23
- ExWAS-class (ExWAS), 16
- FactoMineR, 33
- familyNames, 15, 20, 34
- familyNames, ExposomeSet-method
 - (ExposomeSet), 11
- familyNames, imExposomeSet-method
 - (imExposomeSet), 23
- featureNames, 15
- ggplot2, 50
- glm, 19
- highAndLow, 21, 46, 50

- highAndLow, ExposomeSet-method
(ExposomeSet), 11
- ilod, 22, 26, 45
- ilod, ExposomeSet-method (ExposomeSet),
11
- imExposomeSet, 23, 24, 28, 49
- imExposomeSet-class (imExposomeSet), 23
- imExposomeSet-methods (imExposomeSet),
23
- imputation, 25, 32, 40, 41, 47, 48
- imputation, ExposomeSet-method
(ExposomeSet), 11
- impute, 45
- impute.MinProb, 22
- imputeLOD, 26
- lm, 5
- loadExposome, 14, 26, 44, 45
- loadImputed, 25, 28
- me, 29
- mExWAS, 18, 29, 30, 31
- mexwas, 18, 29, 30, 31, 45
- mexwas, ExposomeSet-method
(ExposomeSet), 11
- mExWAS-class (mExWAS), 29
- names, ExWAS-method (ExWAS), 16
- ndim, 31
- ndim, ExposomePCA-method (ExposomePCA), 9
- normalityTest, 32, 45
- normalityTest, ExposomeSet-method
(ExposomeSet), 11
- pca, 5, 9, 33, 34, 36, 37, 42
- pca, ExposomeSet-method (ExposomeSet), 11
- phenotypeNames, 15, 20, 33
- phenotypeNames, ExposomePCA-method
(ExposomePCA), 9
- phenotypeNames, ExposomeSet-method
(ExposomeSet), 11
- phenotypeNames, imExposomeSet-method
(imExposomeSet), 23
- plot, ExposomeClust, ANY-method
(ExposomeClust), 7
- plot, ExposomeCorr, ANY-method
(ExposomeCorr), 8
- plot, ExposomePCA, ANY-method
(ExposomePCA), 9
- plot, ExposomeSet, ANY-method
(ExposomeSet), 11
- plot, ExWAS, ANY-method (ExWAS), 16
- plot, imExposomeSet, ANY-method
(imExposomeSet), 23
- plot, mExWAS, ANY-method (mExWAS), 29
- plot3PCA, 34
- plot3PCA, ExposomePCA-method
(ExposomePCA), 9
- plotClassification, 3, 4, 35, 45
- plotClassification, ExposomeClust-method
(ExposomeClust), 7
- plotCorrelation, 5, 35, 45
- plotCorrelation, ExposomeCorr-method
(ExposomeCorr), 8
- plotEffect, 36, 43
- plotEffect, ExWAS-method (ExWAS), 16
- plotEXP, 37, 42
- plotEXP, ExposomePCA-method
(ExposomePCA), 9
- plotExwas, 19, 31, 37
- plotExwas, ExWAS-method (ExWAS), 16
- plotExwas, mExWAS-method (mExWAS), 29
- plotFamily, 38, 39–41, 45, 47, 48
- plotFamily, ExposomeSet-method
(ExposomeSet), 11
- plotFamily, imExposomeSet-method
(imExposomeSet), 23
- plotHistogram, 32, 39, 39, 40, 41, 47, 48
- plotHistogram, ExposomeSet-method
(ExposomeSet), 11
- plotLOD, 40
- plotLOD, ExposomeSet-method
(ExposomeSet), 11
- plotMissings, 22, 25, 32, 39, 40, 47, 48
- plotMissings, ExposomeSet-method
(ExposomeSet), 11
- plotPCA, 32–34, 41, 42
- plotPCA, ExposomePCA-method
(ExposomePCA), 9
- plotPHE, 37, 42
- plotPHE, ExposomePCA-method
(ExposomePCA), 9
- plotVolcano, 43
- plotVolcano, ExWAS-method (ExWAS), 16
- read.table, 44
- readExposome, 14, 27, 43, 45
- rexposome, 45
- rexposome-package (rexposome), 45
- sampleNames, ExposomeClust-method
(ExposomeClust), 7
- sampleNames, imExposomeSet-method
(imExposomeSet), 23
- shapiro.test, 32

standardize, [21](#), [45](#), [46](#), [50](#)
standardize, ExposomeSet-method
(ExposomeSet), [11](#)
Summary, ExposomeSet-method
(ExposomeSet), [11](#)

tableLOD, [47](#)
tableLOD, ExposomeSet-method
(ExposomeSet), [11](#)
tableMissings, [22](#), [25](#), [40](#), [41](#), [47](#)
tableMissings, ExposomeSet-method
(ExposomeSet), [11](#)

tef, [48](#)
tef, ExWAS-method (ExWAS), [16](#)
toES, [49](#)
toES, imExposomeSet-method
(imExposomeSet), [23](#)
trans, [21](#), [45](#), [46](#), [49](#)
trans, ExposomeSet-method (ExposomeSet),
[11](#)

volcano_plot, [50](#)