

Package ‘HiCParser’

April 8, 2026

Type Package

Title Parser for HiC data in R

Date 2025-07-22

Version 1.2.0

URL <https://github.com/emaigne/HiCParser>

BugReports <https://github.com/emaigne/HiCParser/issues>

Description This package is a parser to import HiC data into R.
It accepts several type of data: tabular files, Cooler `.cool`` or `.mcool`` files, Juicer `.hic`` files or HiC-Pro `.matrix`` and `.bed`` files.
The HiC data can be several files, for several replicates and conditions.
The data is formatted in an InteractionSet object.

License LGPL

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

biocViews Software, HiC, DataImport

Imports data.table, InteractionSet, GenomicRanges,
SummarizedExperiment, Rcpp (>= 1.0.12), S4Vectors, gtools,
pbapply, BiocGenerics, Seqinfo

LinkingTo Rcpp

Suggests rhdf5, BiocStyle, knitr, sessioninfo, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/HiCParser>

git_branch RELEASE_3_22

git_last_commit c089341

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2026-04-07

Author Zytnicki Matthias [aut],
Maigné Élise [aut, cre]

Maintainer Maigné Élise <elise.maigne@inrae.fr>

Contents

HiCParser-package	2
mergeInteractionSet	2
parseCool	3
parseHiC	4
parseHiCPro	5
parseTabular	6

Index	8
--------------	----------

HiCParser-package	<i>A multiple format Hi-C data parser</i>
-------------------	---

Description

This package is a parser to import HiC data into R. It accepts several type of data: tabular files, Cooler '.cool' or '.mcool' files, Juicer '.hic' files or HiC-Pro '.matrix' and '.bed' files. The HiC data can be several files, for several replicates and conditions. The data is formatted in an InteractionSet object.

Author(s)

Maintainer: Maigné Élise <elise.maigne@inrae.fr>

Authors:

- Zytnicki Matthias <matthias.zytnicki@inrae.fr>

See Also

Useful links:

- <https://github.com/emaigne/HiCParser>
- Report bugs at <https://github.com/emaigne/HiCParser/issues>

mergeInteractionSet	<i>Merge two InteractionSet objects</i>
---------------------	---

Description

Merge two different [InteractionSet](#).

Usage

```
mergeInteractionSet(interactionSet1, interactionSet2, fill = NA)
```

Arguments

interactionSet1	The first InteractionSet .
interactionSet2	The second InteractionSet .
fill	Fill missing values with this.

Value

The merged [InteractionSet](#).

Examples

```
path <- system.file("extdata", "hicsample_21.cool", package = "HiCParser")
object1 <- parseCool(path, conditions = 1, replicates = 1)
# Creating an object with a different condition
object2 <- parseCool(path, conditions = 2, replicates = 1)
objectMerged <- mergeInteractionSet(object1, object2)
```

parseCool

Parser for data in cool format

Description

Parses interactions in `.cool` or `.mcool` format and returns an `InteractionSet` object.

Usage

```
parseCool(paths, binSize = NA, conditions, replicates)
```

Arguments

paths	A vector of paths to <code>.cool</code> or <code>.mcool</code> files.
binSize	The resolution (span of each position in number of bases). Optionally provided to select the appropriate resolution in <code>.mcool</code> files. Defaults to <code>NULL</code> .
conditions	A vector of condition names repeated along the replicates.
replicates	A vector of replicate names repeated along the conditions.

Details

To read `.cool` or `.mcool` files, the `rhdf5` package is required. Please install it before running the function.

Value

An `InteractionSet`.

Examples

```
# EXAMPLE FOR .cool FORMAT
# Path to each file
pathsCool <- c(
  "path/to/condition-1.replicate-1.cool",
  "path/to/condition-1.replicate-2.cool",
  "path/to/condition-1.replicate-3.cool",
  "path/to/condition-2.replicate-1.cool",
  "path/to/condition-2.replicate-2.cool",
  "path/to/condition-2.replicate-3.cool"
)
```

```

# Condition and replicate of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)
if (FALSE) {
  library(rhdf5)
  object <- parseCool(
    paths,
    conditions = conditions,
    replicates = replicates
  )
}

# EXAMPLE FOR .mcool FORMAT
# Resolution
binSize <- 500000
# Path to each file
paths <- c(
  "path/to/condition-1.replicate-1.mcool",
  "path/to/condition-1.replicate-2.mcool",
  "path/to/condition-1.replicate-3.mcool",
  "path/to/condition-2.replicate-1.mcool",
  "path/to/condition-2.replicate-2.mcool",
  "path/to/condition-2.replicate-3.mcool"
)
# Condition and replicate of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)
if (FALSE) {
  # Instantiation of data set
  library(rhdf5)
  object <- parseCool(
    paths,
    conditions = conditions,
    replicates = replicates,
    binSize = binSize
  )
}

```

parseHiC

Parser for data in hic format

Description

Parses interactions in .hic format and returns an InteractionSet object.

Usage

```
parseHiC(paths, binSize, conditions, replicates)
```

Arguments

paths	A vector of paths to .hic files.
binSize	The resolution (span of each position in number of bases) to select within the .hic files.

conditions A vector of condition names repeated along the replicates.
 replicates A vector of replicate names repeated along the conditions.

Value

An InteractionSet.

Examples

```
# Path to each file
paths <- c(
  "path/to/condition-1.replicate-1.hic",
  "path/to/condition-1.replicate-2.hic",
  "path/to/condition-1.replicate-3.hic",
  "path/to/condition-2.replicate-1.hic",
  "path/to/condition-2.replicate-2.hic",
  "path/to/condition-2.replicate-3.hic"
)
# Replicate and condition of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)
# Resolution to select
binSize <- 500000
if (FALSE) {
  # Instantiation of data set
  hic.experiment <- parseHiC(
    paths,
    conditions = conditions,
    replicates = replicates,
    binSize = binSize
  )
}
```

parseHiCPro

Parser for HiCPro data

Description

Parses interactions in pairs of .matrix and .bed files and returns an InteractionSet object.

Usage

```
parseHiCPro(matrixPaths, bedPaths, conditions, replicates)
```

Arguments

matrixPaths A vector of paths to HiC-Pro matrix files.
 bedPaths A vector of paths to HiC-Pro bed files.
 conditions A vector of condition names repeated along the replicates.
 replicates A vector of replicate names repeated along the conditions.

Value

An InteractionSet.

Examples

```
# Path to each matrix file
matrixPaths <- c(
  "path/to/condition-1.replicate-1.matrix",
  "path/to/condition-1.replicate-2.matrix",
  "path/to/condition-1.replicate-3.matrix",
  "path/to/condition-2.replicate-1.matrix",
  "path/to/condition-2.replicate-2.matrix",
  "path/to/condition-2.replicate-3.matrix"
)

# Path to each bed file
bedPaths <- c(
  "path/to/condition-1.replicate-1.bed",
  "path/to/condition-1.replicate-2.bed",
  "path/to/condition-1.replicate-3.bed",
  "path/to/condition-2.replicate-1.bed",
  "path/to/condition-2.replicate-2.bed",
  "path/to/condition-2.replicate-3.bed"
)

# Condition and replicate of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)

if (FALSE) {
  # Instantiation of data set
  hic.experiment <- parseHiCPro(
    matrixPaths = matrixPaths,
    bedPaths = bedPaths,
    conditions = conditions,
    replicates = replicates
  )
}
```

parseTabular

Parser for tabular data

Description

Read the file, produce an InteractionSet object.

Usage

```
parseTabular(path, sep = '\t')
```

Arguments

path A path to a tabular file.
sep The separator of the tabular file. Default to tabulation.

Details

Accepts a tabular file with chromosome, position 1, position 2, and multiple replicate columns listing interaction counts. Null interactions do not have to be listed. Values must be separated by tabulations. The header must be chromosome position 1 position 2 x.y x.y x.y ... with x replaced by condition names and y replaced by replicate names.

Value

An InteractionSet object.

Examples

```
path <- system.file("extdata", "hicsample_21.tsv", package = "HiCParser")
object <- parseTabular(path, sep = "\t")
```

Index

HiCParser (HiCParser-package), [2](#)
HiCParser-package, [2](#)

InteractionSet, [2](#), [3](#)

mergeInteractionSet, [2](#)

parseCool, [3](#)

parseHiC, [4](#)

parseHiCPro, [5](#)

parseTabular, [6](#)