

Package ‘iCOBRA’

October 12, 2016

Type Package

Title Comparison and Visualization of Ranking and Assignment Methods

Version 1.0.2

Date 2015-10-10

Description This package provides functions for calculation and visualization of performance metrics for evaluation of ranking and binary classification (assignment) methods. It also contains a shiny application for interactive exploration of results.

License GPL (>=2)

LazyData TRUE

Collate 'AllGenerics.R' 'COBRADData.R' 'COBRAPerformance.R'
'COBRAPlot.R' 'calculate_performance.R' 'cobradata_example.R'
'helpers_general.R' 'plot_methods.R' 'printHead.R' 'shiny.R'

Depends R (>= 3.2)

Imports shiny (>= 0.9.1.9008), shinydashboard, shinyBS, reshape2,
ggplot2, scales, ROCR, dplyr, DT, limma, methods, UpSetR

Suggests knitr, testthat

VignetteBuilder knitr

biocViews Classification

RoxygenNote 5.0.1

NeedsCompilation no

Author Charlotte Soneson [aut, cre]

Maintainer Charlotte Soneson <charlottesoneson@gmail.com>

R topics documented:

basemethods	3
calculate_adjp	3
calculate_performance	4
COBRAapp	6

COBRAData-class	7
cobradata_example	8
COBRAPerformance-class	9
COBRAPlot-class	11
coerce	12
corr	13
deviation	14
Extract	15
faceted	16
fdrnbr	17
fdrnbrcurve	18
fdrtp	19
fdrtpcurve	20
fpc	21
fpr	22
maxsplit	23
onlyshared	24
overlap	25
padj	26
plotcolors	27
plot_corr	28
plot_deviation	29
plot_fdrnbrcurve	30
plot_fdrtpcurve	31
plot_fpc	32
plot_fpr	33
plot_overlap	34
plot_roc	34
plot_scatter	35
plot_tpr	36
plot_upset	37
prepare_data_for_plot	38
pval	40
reorder_levels	41
roc	42
scatter	43
score	44
splv	45
stratiflevels	46
tpr	46
truth	47
Index	49

basemethods	<i>Accessor function for basemethods</i>
-------------	--

Description

Accessor function to extract the methods that are represented in an COBRAPerformance or COBRAPlot object.

Usage

```
basemethods(x, ...)
```

```
## S4 method for signature 'COBRAPerformance'  
basemethods(x)
```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.

Value

A character vector of all methods represented in the object.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)  
cobrapperf <- calculate_performance(cobradata_example,  
                                   binary_truth = "status",  
                                   aspects = "fdrtprcurve")  
basemethods(cobrapperf)
```

calculate_adjp	<i>Calculate adjusted p-values</i>
----------------	------------------------------------

Description

Calculate adjusted p-values for methods where only nominal p-values are available in an COBRADData object.

Usage

```
calculate_adjp(cobradata, method = "BH")
```

Arguments

cobradata	An COBRADData object.
method	A character string giving the method (selected from <code>p.adjust.methods()</code>) that will be used to perform the adjustment.

Value

An COBRADData object, extended with the calculated adjusted p-values.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobradata_example <- calculate_adjp(cobradata_example, method = "BH")
```

calculate_performance *Calculate performance measures*

Description

Calculate performance measures from a given collection of p-values, adjusted p-values and scores provided in an COBRADData object.

Usage

```
calculate_performance(cobradata, binary_truth = NULL, cont_truth = NULL,
  aspects = c("fdrtpr", "fdrtprcurve", "fdrnbr", "fdrnbrcurve", "tpr", "fpr",
  "roc", "fpc", "overlap", "corr", "scatter", "deviation"), thrs = c(0.01,
  0.05, 0.1), splv = "none", maxsplit = 3, onlyshared = FALSE,
  thr_venn = 0.05, type_venn = "adjp", topn_venn = 100)
```

Arguments

cobradata	An COBRADData object.
binary_truth	A character string giving the name of the column of truth(cobradata) that contains the binary truth (true assignment of variables into two classes, represented by 0/1).
cont_truth	A character string giving the name of the column of truth(cobradata) that contains the continuous truth (a continuous value that the observations can be compared to).
aspects	A character vector giving the types of performance measures to calculate. Must be a subset of <code>c("fdrtpr", "fdrtprcurve", "fdrnbr", "fdrnbrcurve", "tpr", "fpr", "roc", "fpc", "overlap", "corr", "scatter", "deviation")</code> .


```
      "tpr", "roc"),  
  thrs = c(0.01, 0.05, 0.1), splv = "none")
```

COBRAapp

Interactive shiny app to visualize results

Description

Interactive shiny app for visualization of results. The app can be initialized with an COBRADData object. If no object is provided, truth and results are loaded into the app from text files (see the Instructions tab of the app for formatting instructions). Properly formatted text files can also be obtained using the function [COBRADData_to_text](#).

Usage

```
COBRAapp(cobradata = NULL, autorun = FALSE)
```

Arguments

cobradata	An (optional) COBRADData object. If not given, the user can load results from text files.
autorun	A logical indicating whether the app calculations should start automatically on launch, or wait for the user to press the 'Start calculation!' button.

Value

Returns (and runs) an object representing the shiny app.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)  
## Not run:  
COBRAapp(cobradata_example)  
  
## End(Not run)
```

COBRADData-class COBRADData *object and constructor*

Description

The COBRADData class contains slots to hold calculated p-values, adjusted p-values and general 'scores' for a set of features. The slots can contain values from multiple methods, and each method can contribute to one or more slots. The class also contains a slot giving the 'truth' (a binary assignment and/or a continuous score) for each feature, as well as additional annotations that can be used to stratify the performance calculations.

Usage

```
COBRADData(pval = data.frame(), padj = data.frame(), score = data.frame(),
           truth = data.frame(), object_to_extend = NULL)
```

```
COBRADData_from_text(truth_file, result_files, feature_id)
```

```
COBRADData_to_text(cobradata, truth_file, result_files, feature_id)
```

Arguments

pval	A data frame with features as rows and methods as columns, containing nominal p-values. Missing values (NAs) are allowed. The row names should be feature names.
padj	A data frame with features as rows and methods as columns, containing adjusted p-values. Missing values (NAs) are allowed. The row names should be feature names.
score	A data frame with features as rows and methods as columns, containing generic scores. In case of comparison to a binary truth, larger values of the scores should correspond to 'more significant' features. Missing values (NAs) are allowed. The row names should be feature names.
truth	A data frame with features as rows columns containing feature annotations such as, e.g., binary and continuous truths and additional annotations that can be used to stratify the performance calculations. The row names should be feature names.
object_to_extend	An COBRADData object to extend with the provided information.
truth_file	A character string giving the path to a file with true labels and other feature annotations.
result_files	A character vector giving path(s) to file(s) with results (p-values, adjusted p-values, scores) for one or more methods. The column names of these files must be of the form "method:measure", where measure is one of P, adjP or score, depending on what is given in the column.

feature_id	A character string giving the name of the column in the truth and result files that encodes the feature identifier.
cobradata	An COBRADData object

Details

If adjusted p-values are missing for some methods, for which nominal p-values are available, the adjusted p-values can be calculated using the `calculate_adjp` function.

The text files generated by `COBRADData_to_text` can be used as input to `iCOBRAapp`, when it is called without an input argument.

Value

`COBRADData` and `COBRADData_from_text` return a `COBRADData` object.

Author(s)

Charlotte Soneson

Examples

```
## Empty COBRADData object:
COBRADData()

## COBRADData object from individual data frames
set.seed(123)
pval <- data.frame(m1 = runif(100), m2 = runif(100),
                  row.names = paste0("F", 1:100))
truth <- data.frame(status = round(runif(100)),
                   row.names = paste0("F", 1:100))
cobradata <- COBRADData(pval = pval, truth = truth)
```

cobradata_example *Example data set with three differential gene expression methods*

Description

A data set consisting of p-values, adjusted p-values and estimated log fold changes (in the 'scores' slot) obtained by three methods for differential expression analysis of RNA-seq data, applied to a small synthetic data set of 3,858 human genes. The values are stored in an `COBRADData` object together with a 'truth' data frame containing the true differential expression status for each gene as well as various additional annotations such as the true log fold change, the number of isoforms of the gene and the average expression level.

Usage

```
cobradata_example
```


Format

An COBRADData object with four slots:

pval data frame with p-values for 2,399 genes, from three different methods.

padj data frame with adjusted p-values for 2,399 genes, from two different methods.

score data frame with estimated log fold changes for 2,399 genes, from three different methods.

truth data frame with true differential expression status (status column), the number of isoforms (n_isoforms column), the true log fold change (logFC and logFC_cat columns) and average expression level (expr and expr_cat columns) for 3,858 genes.

Value

An COBRADData object.

COBRAPerformance-class

COBRAPerformance *object and constructor*

Description

The COBRAPerformance class holds various types of calculated performance measures. Objects from this class are typically generated from COBRADData objects by means of the function [calculate_performance](#).

Usage

```
COBRAPerformance(fdrtptr = data.frame(), fdrtprcurve = data.frame(),
  fdrnbr = data.frame(), fdrnbrcurve = data.frame(), tpr = data.frame(),
  fpr = data.frame(), splv = "", roc = data.frame(), fpc = data.frame(),
  deviation = data.frame(), onlyshared = NA, overlap = data.frame(),
  maxsplit = NA_integer_, corr = data.frame(), scatter = data.frame())
```

Arguments

fdrtptr	A data frame containing observed FDR and TPR values at various adjusted p-value thresholds.
fdrtprcurve	A data frame containing observed FDR and TPR values for a (potentially large) number of cutoffs applied to a 'score' (that can be p-value, adjusted p-value or a more general score).
fdrnbr	A data frame containing observed FDR and the number of features considered to be significant at various adjusted p-value thresholds.
fdrnbrcurve	A data frame containing observed FDR and number of features considered to be significant for a (potentially large) number of cutoffs applied to a 'score' (that can be p-value, adjusted p-value or a more general score).
tpr	A data frame containing observed TPR values at various adjusted p-value thresholds.

fpr	A data frame containing observed FPR values at various adjusted p-value thresholds.
splv	A character string giving the name of the stratification factor, "none" if the results are not stratified.
roc	A data frame containing observed FPR and TPR values for a (potentially large) number of cutoffs applied to a 'score' (that can be p-value, adjusted p-value or a more general score), which can be used to generate a ROC curve.
fpc	A data frame containing observed numbers of false positive findings among the N top-ranked features (ranked by p-values, adjusted p-values or more general scores), for a (potentially large) number of Ns, which can be used to generate a false positive curve.
deviation	A data frame containing deviations between observed scores and true scores.
onlyshared	A logical value indicating whether only features shared between the results and the truth should be retained, or if all features present in the truth should be used.
overlap	A data frame or list of data frames with binary values indicating, for each of a number of methods and number of features, whether the method consider the feature 'positive' (significant, 1) or 'negative' (non-significant, 0). If it is a list of data frames, each list element corresponds to one level of a stratifying factor.
maxsplit	A numeric value indicating the largest number of levels to retain if the results have been stratified by an annotation.
corr	A data frame containing observed (Pearson and Spearman) correlation values between observed and true scores.
scatter	A data frame containing observed 'scores' (p-values, adjusted p-values or more general scores) and true scores, which can be used to generate scatter plots.

Value

An COBRAPerformance object.

Author(s)

Charlotte Soneson

Examples

```
## Empty COBRAPerformance object  
COBRAPerformance()
```

COBRAPlot-class COBRAPlot *object and constructor*

Description

The COBRAPlot class is similar to the COBRAPerformance class in that it holds various types of calculated performance measures. However, it also contains other attributes that are necessary for plotting, such as color assignments. Several COBRAPlot objects can be generated from the same COBRAPerformance object, without having to go through the potentially time consuming task of recalculating all performance measures. Objects from this class are typically generated from an COBRAPerformance objects by means of the function [prepare_data_for_plot](#).

Usage

```
COBRAPlot(fdrtptr = data.frame(), fdrtprcurve = data.frame(),
  fdrnbr = data.frame(), corr = data.frame(), fdrnbrcurve = data.frame(),
  tpr = data.frame(), fpr = data.frame(), roc = data.frame(),
  scatter = data.frame(), onlyshared = NA, fpc = data.frame(),
  overlap = data.frame(), plotcolors = "", splv = "",
  deviation = data.frame(), maxsplit = NA_integer_, faceted = NA)
```

Arguments

fdrtptr	A data frame containing observed FDR and TPR values at various adjusted p-value thresholds.
fdrtprcurve	A data frame containing observed FDR and TPR values for a (potentially large) number of cutoffs applied to a 'score' (that can be p-value, adjusted p-value or a more general score).
fdrnbr	A data frame containing observed FDR and the number of features considered to be significant at various adjusted p-value thresholds.
corr	A data frame containing observed (Pearson and Spearman) correlation values between observed and true scores.
fdrnbrcurve	A data frame containing observed FDR and number of features considered to be significant for a (potentially large) number of cutoffs applied to a 'score' (that can be p-value, adjusted p-value or a more general score).
tpr	A data frame containing observed TPR values at various adjusted p-value thresholds.
fpr	A data frame containing observed FPR values at various adjusted p-value thresholds.
roc	A data frame containing observed FPR and TPR values for a (potentially large) number of cutoffs applied to a 'score' (that can be p-value, adjusted p-value or a more general score), which can be used to generate a ROC curve.
scatter	A data frame containing observed 'scores' (p-values, adjusted p-values or more general scores) and true scores, which can be used to generate scatter plots.

onlyshared	A logical value indicating whether only features shared between the results and the truth should be retained, or if all features present in the truth should be used.
fpc	A data frame containing observed numbers of false positive findings among the N top-ranked features (ranked by p-values, adjusted p-values or more general scores), for a (potentially large) number of Ns, which can be used to generate a false positive curve.
overlap	A data frame or list of data frames with binary values indicating, for each of a number of methods and number of features, whether the method consider the feature 'positive' (significant, 1) or 'negative' (non-significant, 0). If it is a list of data frames, each list element corresponds to one level of a stratifying factor.
plotcolors	A character vector giving the color for each method (or method-stratification level combination).
splv	A character string giving the name of the stratification factor, "none" if the results are not stratified.
deviation	A data frame containing deviations between observed scores and true scores.
maxsplit	A numeric value indicating the largest number of levels to retain if the results have been stratified by an annotation.
facetted	A logical indicating whether the data is prepared for a facetted plot (separating different stratification levels into different panels) or for displaying all values in one plot panel.

Value

An COBRAPlot object.

Author(s)

Charlotte Soneson

Examples

```
## Empty COBRAPlot object
cobraplot <- COBRAPlot()
```

coerce

Convert an object to another class

Description

Convert object between COBRAPerformance and COBRAPlot classes.

Arguments

from The object that is to be coerced into another class.

Author(s)

Charlotte Soneson

Examples

```

data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status",
                                   aspects = "fdrtpr")
cobraplot <- prepare_data_for_plot(cobrapperf)

## Coerce COBRAPerformance object into COBRAPlot object
as(cobrapperf, "COBRAPlot")

## Coerce COBRAPlot object into COBRAPerformance object
as(cobraplot, "COBRAPerformance")

```

 corr

Accessor and replacement functions for corr slot

Description

Accessor and replacement functions for the corr slot in an COBRAPerformance or COBRAPlot object.

Usage

```

corr(x, ...)

corr(x, ...) <- value

## S4 method for signature 'COBRAPerformance'
corr(x)

## S4 replacement method for signature 'COBRAPerformance,data.frame'
corr(x) <- value

## S4 replacement method for signature 'COBRAPlot,data.frame'
corr(x) <- value

```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A data frame giving correlation values for each method and each stratification level.

Value

The accessor function returns a data frame giving correlation values for each method and each stratification level.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example, cont_truth = "logFC",
                                   aspects = "corr")
head(corr(cobrapperf))
```

deviation

Accessor and replacement functions for deviation slot

Description

Accessor and replacement functions for the deviation slot in an COBRAPerformance or COBRAPlot object.

Usage

```
deviation(x, ...)

deviation(x, ...) <- value

## S4 method for signature 'COBRAPerformance'
deviation(x)

## S4 replacement method for signature 'COBRAPerformance,data.frame'
deviation(x) <- value

## S4 replacement method for signature 'COBRAPlot,data.frame'
deviation(x) <- value
```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A data frame giving information necessary to plots of deviations between observed and true scores for each method and each stratification level.

Value

The accessor function returns a data frame giving information necessary to plots of deviations between observed and true scores for each method and each stratification level.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobraperf <- calculate_performance(cobradata_example, cont_truth = "logFC",
                                 aspects = "deviation")
head(deviation(cobraperf))
```

Extract

Subsetting COBRADData, COBRAPerformance or COBRAPlot objects

Description

Functions to subset COBRADData, COBRAPerformance or COBRAPlot objects. COBRADData objects are subset by features (rows), while COBRAPerformance and COBRAPlot objects are subset by methods (columns). Numeric indices are not allowed, since not all slots may be arranged in the same order.

Usage

```
## S4 method for signature 'COBRADData'
x[i, j = "missing", drop = "missing"]

## S4 method for signature 'COBRAPerformance'
x[i = "missing", j, drop = "missing"]

## S4 method for signature 'COBRAPlot'
x[i = "missing", j, drop = "missing"]
```

Arguments

x	An COBRADData, COBRAPerformance or COBRAPlot object.
i	For COBRADData objects, a character vector of feature names to retain.
j	For COBRAPerformance and COBRAPlot objects, a character vector with method names to retain.
drop	not used.

Value

A subset of the original object, of the same class

Examples

```

data(cobradata_example)
cobradata_example[c("ENSG00000000457", "ENSG00000000971",
                    "ENSG00000000460"), ]
cobraperf <- calculate_performance(cobradata_example,
                                 binary_truth = "status",
                                 aspects = "fdrtpr")

cobraperf[, c("voom")]
cobraplot <- prepare_data_for_plot(cobraperf)
cobraplot[, c("voom")]

```

 faceted

Accessor and replacement functions for faceted slot

Description

Accessor and replacement functions for the faceted slot in an COBRAPlot object.

Usage

```

faceted(x, ...)

faceted(x, ...) <- value

## S4 method for signature 'COBRAPlot'
faceted(x)

## S4 replacement method for signature 'COBRAPlot,logical'
faceted(x) <- value

```

Arguments

x	An COBRAPlot object.
...	Additional arguments.
value	A logical value, indicating whether the object is formatted for faceted plots (visualizing each stratification level in a separate panel) or not.

Value

The accessor function returns a logical value, indicating whether the object is formatted for faceted plots (visualizing each stratification level in a separate panel) or not.

Author(s)

Charlotte Soneson

Examples

```

data(cobradata_example)
cobraperf <- calculate_performance(cobradata_example,
                                binary_truth = "status",
                                aspects = "fdrtpr")
cobraplot <- prepare_data_for_plot(cobraperf)
facetted(cobraplot)

```

fdrnbr

*Accessor and replacement functions for fdrnbr slot***Description**

Accessor and replacement functions for the fdrnbr slot in an COBRAPerformance or COBRAPlot object.

Usage

```

fdrnbr(x, ...)

fdrnbr(x, ...) <- value

## S4 method for signature 'COBRAPerformance'
fdrnbr(x)

## S4 replacement method for signature 'COBRAPerformance,data.frame'
fdrnbr(x) <- value

## S4 replacement method for signature 'COBRAPlot,data.frame'
fdrnbr(x) <- value

```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A data frame giving information about the observed FPR and the number of features called positive for each method and each stratification level, at various adjusted p-value thresholds.

Value

The accessor function returns a data frame giving information about the observed FPR and the number of features called positive for each method and each stratification level, at various adjusted p-value thresholds.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status",
                                   aspects = "fdrnbr")

head(fdrnbr(cobrapperf))
```

fdrnbrcurve

Accessor and replacement functions for fdrnbrcurve slot

Description

Accessor and replacement functions for the fdrnbrcurve slot in an COBRAPerformance or COBRAPlot object.

Usage

```
fdrnbrcurve(x, ...)

fdrnbrcurve(x, ...) <- value

## S4 method for signature 'COBRAPerformance'
fdrnbrcurve(x)

## S4 replacement method for signature 'COBRAPerformance,data.frame'
fdrnbrcurve(x) <- value

## S4 replacement method for signature 'COBRAPlot,data.frame'
fdrnbrcurve(x) <- value
```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A data frame giving information necessary to generate curves of observed FDR vs number of features called positive for each method and each stratification level.

Value

The accessor function returns a data frame giving information necessary to generate curves of observed FDR vs number of features called positive for each method and each stratification level.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status",
                                   aspects = "fdrnbrcurve")

head(fdrnbrcurve(cobrapperf))
```

fdrtptr*Accessor and replacement functions for fdrtptr slot*

Description

Accessor and replacement functions for the `fdrtptr` slot in an `COBRAPerformance` or `COBRAPlot` object.

Usage

```
fdrtptr(x, ...)
```

```
fdrtptr(x, ...) <- value
```

```
## S4 method for signature 'COBRAPerformance'
```

```
fdrtptr(x)
```

```
## S4 replacement method for signature 'COBRAPerformance,data.frame'
```

```
fdrtptr(x) <- value
```

```
## S4 replacement method for signature 'COBRAPlot,data.frame'
```

```
fdrtptr(x) <- value
```

Arguments

<code>x</code>	An <code>COBRAPerformance</code> or <code>COBRAPlot</code> object.
<code>...</code>	Additional arguments.
<code>value</code>	A data frame giving information about the observed FPR and TPR for each method and each stratification level, at various adjusted p-value thresholds.

Value

The accessor function returns a data frame giving information about the observed FPR and TPR for each method and each stratification level, at various adjusted p-value thresholds.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status",
                                   aspects = "fdrtp")
head(fdrtp(cobrapperf))
```

fdrtpcurve

Accessor and replacement functions for fdrtpcurve slot

Description

Accessor and replacement functions for the fdrtpcurve slot in an COBRAPerformance or COBRAPlot object.

Usage

```
fdrtpcurve(x, ...)
fdrtpcurve(x, ...) <- value

## S4 method for signature 'COBRAPerformance'
fdrtpcurve(x)

## S4 replacement method for signature 'COBRAPerformance,data.frame'
fdrtpcurve(x) <- value

## S4 replacement method for signature 'COBRAPlot,data.frame'
fdrtpcurve(x) <- value
```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A data frame giving information necessary to generate curves of observed FDR vs TPR for each method and each stratification level.

Value

The accessor function returns a data frame giving information necessary to generate curves of observed FDR vs TPR for each method and each stratification level.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status",
                                   aspects = "fdrtprcurve")
head(fdrtprcurve(cobrapperf))
```

fpc

Accessor and replacement functions for fpc slot

Description

Accessor and replacement functions for the fpc slot in an COBRAPerformance or COBRAPlot object.

Usage

```
fpc(x, ...)
```

```
fpc(x, ...) <- value
```

```
## S4 method for signature 'COBRAPerformance'
fpc(x)
```

```
## S4 replacement method for signature 'COBRAPerformance,data.frame'
fpc(x) <- value
```

```
## S4 replacement method for signature 'COBRAPlot,data.frame'
fpc(x) <- value
```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A data frame giving information necessary to generate false positive curves for each method and each stratification level.

Value

The accessor function returns a data frame giving information necessary to generate false positive curves for each method and each stratification level.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobraperf <- calculate_performance(cobradata_example,
                                binary_truth = "status", aspects = "fpc")
head(fpc(cobraperf))
```

fpr

Accessor and replacement functions for fpr slot

Description

Accessor and replacement functions for the fpr slot in an COBRAPerformance or COBRAPlot object.

Usage

```
fpr(x, ...)

fpr(x, ...) <- value

## S4 method for signature 'COBRAPerformance'
fpr(x)

## S4 replacement method for signature 'COBRAPerformance,data.frame'
fpr(x) <- value

## S4 replacement method for signature 'COBRAPlot,data.frame'
fpr(x) <- value
```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A data frame giving information about the observed FPR for each method and each stratification level, at various adjusted p-value thresholds.

Value

The accessor function returns a data frame giving information about the observed FPR for each method and each stratification level, at various adjusted p-value thresholds.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status", aspects = "fpr")
head(fpr(cobrapperf))
```

maxsplit*Accessor and replacement functions for maxsplit slot*

Description

Accessor and replacement functions for the maxsplit slot in an COBRAPerformance or COBRAPlot object.

Usage

```
maxsplit(x, ...)

maxsplit(x, ...) <- value

## S4 method for signature 'COBRAPerformance'
maxsplit(x)

## S4 replacement method for signature 'COBRAPerformance,numeric'
maxsplit(x) <- value

## S4 replacement method for signature 'COBRAPlot,numeric'
maxsplit(x) <- value
```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A numeric value giving the maximal number of strata to retain.

Value

The accessor function returns a numeric value giving the maximal number of strata to retain.

Author(s)

Charlotte Soneson

Examples

```

data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status",
                                   aspects = "fdrtpr", splv = "expr_cat",
                                   maxsplit = 3)

maxsplit(cobrapperf)

```

onlyshared

Accessor and replacement functions for onlyshared slot

Description

Accessor and replacement functions for the onlyshared slot in an COBRAPerformance or COBRAPlot object.

Usage

```

onlyshared(x, ...)

onlyshared(x, ...) <- value

## S4 method for signature 'COBRAPerformance'
onlyshared(x)

## S4 replacement method for signature 'COBRAPerformance,logical'
onlyshared(x) <- value

## S4 replacement method for signature 'COBRAPlot,logical'
onlyshared(x) <- value

```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A logical indicating whether only features that are shared between result and truth are retained, or if all features in the truth are used.

Value

The accessor function returns a logical indicating whether only features that are shared between result and truth are retained, or if all features in the truth are used.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobraperf <- calculate_performance(cobradata_example,
                                  binary_truth = "status",
                                  aspects = "fdrtpr")

head(onlyshared(cobraperf))
```

overlap

Accessor and replacement functions for overlap slot

Description

Accessor and replacement functions for the `overlap` slot in an `COBRAPerformance` or `COBRAPlot` object.

Usage

```
overlap(x, ...)

overlap(x, ...) <- value

## S4 method for signature 'COBRAPerformance'
overlap(x)

## S4 replacement method for signature 'COBRAPerformance,list_df'
overlap(x) <- value

## S4 replacement method for signature 'COBRAPlot,list_df'
overlap(x) <- value
```

Arguments

<code>x</code>	An <code>COBRAPerformance</code> or <code>COBRAPlot</code> object.
<code>...</code>	Additional arguments.
<code>value</code>	A data frame or a list, giving information about which feature that are classified as 'positive' by each method and for each stratification level.

Value

The accessor function returns a data frame or a list, giving information about which feature that are classified as 'positive' by each method and for each stratification level.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobraperf <- calculate_performance(cobradata_example,
                                 binary_truth = "status",
                                 aspects = "overlap")

head(overlap(cobraperf))
```

padj

Accessor and replacement functions for padj slot

Description

Accessor and replacement functions for the padj slot in an COBRADData object.

Usage

```
padj(x, ...)

padj(x, ...) <- value

## S4 method for signature 'COBRADData'
padj(x)

## S4 replacement method for signature 'COBRADData,data.frame'
padj(x) <- value
```

Arguments

x	An COBRADData object.
...	Additional arguments.
value	A data frame containing adjusted p-values for each feature and each method.

Value

The accessor function returns a data frame containing adjusted p-values for each feature and each method.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
head(padj(cobradata_example))
```

plotcolors

Accessor and replacement functions for plotcolors slot

Description

Accessor and replacement functions for the plotcolors slot in an COBRAPlot object.

Usage

```
plotcolors(x, ...)  
  
plotcolors(x, ...) <- value  
  
## S4 method for signature 'COBRAPlot'  
plotcolors(x)  
  
## S4 replacement method for signature 'COBRAPlot,character'  
plotcolors(x) <- value
```

Arguments

x	An COBRAPlot object.
...	Additional arguments.
value	A character vector giving the colors assigned to each of the methods (or method/stratification level combinations) represented in the COBRAPlot object.

Value

The accessor function returns a character vector giving the colors assigned to each of the methods (or method/stratification level combinations) represented in the COBRAPlot object.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)  
cobrapperf <- calculate_performance(cobradata_example,  
                                   binary_truth = "status",  
                                   aspects = "fdrtpr")  
  
cobraplot <- prepare_data_for_plot(cobrapperf)  
plotcolors(cobraplot)
```

`plot_corr`*Plot correlations*

Description

Plot correlations between observations and a continuous truth value.

Usage

```
plot_corr(cobraplot, title = "", stripsize = 15, titlecol = "black",
          pointsize = 5, xaxisrange = c(-1, 1), corrtype = "pearson")
```

Arguments

<code>cobraplot</code>	An COBRAPlot object.
<code>title</code>	A character string giving the title of the plot.
<code>stripsize</code>	A numeric value giving the size of the strip text, when the results are stratified by an annotation.
<code>titlecol</code>	A character string giving the color of the title.
<code>pointsize</code>	A numeric value giving the size of the plot characters.
<code>xaxisrange</code>	A numeric vector with two elements, giving the lower and upper boundary of the x-axis, respectively.
<code>corrtype</code>	A character string giving the type of correlation to show. Either "pearson" or "spearman".

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example, cont_truth = "logFC",
                                  aspects = "corr")
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
                                  incltruth = TRUE)
plot_corr(cobraplot, corrtype = "spearman")
```

plot_deviation	<i>Plot deviations</i>
----------------	------------------------

Description

Plot the deviations between observed scores and the continuous truth variable.

Usage

```
plot_deviation(cobraplot, title = "", stripsize = 15, titlecol = "black",  
  xaxisrange = NULL, plottype = "boxplot", dojitter = TRUE,  
  transf = "raw")
```

Arguments

cobraplot	An COBRAPlot object.
title	A character string giving the title of the plot.
stripsize	A numeric value giving the size of the strip text, when the results are stratified by an annotation.
titlecol	A character string giving the color of the title.
xaxisrange	A numeric vector with two elements, giving the lower and upper boundary of the x-axis, respectively.
plottype	Either "boxplot" or "violin", indicating what type of plot to make.
dojitter	A logical indicating whether to include jittered data points or not.
transf	A character indicating the transformation to apply to the deviations before plotting. Must be one of "raw", "absolute" or "squared"

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)  
cobrapperf <- calculate_performance(cobradata_example, cont_truth = "logFC",  
  aspects = "deviation")  
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",  
  incltruth = TRUE)  
plot_deviation(cobraplot)
```

plot_fdrnbrcurve *Plot number of significant features vs FDR*

Description

Plot the number of features considered significant vs observed false discovery rate (FDR), for given adjusted p-value thresholds and/or as curves traced out by considering all threshold values.

Usage

```
plot_fdrnbrcurve(cobraplot, title = "", stripsize = 15,
  titlecol = "black", pointsize = 5, xaxisrange = c(0, 1),
  plottype = c("curve", "points"), linewidth = 1)
```

Arguments

cobraplot	An COBRAPlot object.
title	A character string giving the title of the plot.
stripsize	A numeric value giving the size of the strip text, when the results are stratified by an annotation.
titlecol	A character string giving the color of the title.
pointsize	A numeric value giving the size of the plot characters.
xaxisrange	A numeric vector with two elements, giving the lower and upper boundary of the x-axis, respectively.
plottype	A character vector giving the type of plot to construct. Can be any combination of the two elements "curve" and "points".
linewidth	The line width used for plotting

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
  binary_truth = "status",
  aspects = c("fdrnbr", "fdrnbrcurve"))
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
  incltruth = TRUE)
plot_fdrnbrcurve(cobraplot, plottype = c("curve", "points"))
```

plot_fdrtpcurve *Plot TPR vs FDR*

Description

Plot observed true positive rate (TPR) vs observed false discovery rate (FDR), for given adjusted p-value thresholds and/or as curves traced out by considering all threshold values.

Usage

```
plot_fdrtpcurve(cobraplot, title = "", stripsize = 15,
  titlecol = "black", pointsize = 5, xaxisrange = c(0, 1),
  yaxisrange = c(0, 1), plottype = c("curve", "points"), linewidth = 1)
```

Arguments

cobraplot	An COBRAPlot object.
title	A character string giving the title of the plot.
stripsize	A numeric value giving the size of the strip text, when the results are stratified by an annotation.
titlecol	A character string giving the color of the title.
pointsize	A numeric value giving the size of the plot characters.
xaxisrange	A numeric vector with two elements, giving the lower and upper boundary of the x-axis, respectively.
yaxisrange	A numeric vector with two elements, giving the lower and upper boundary of the y-axis, respectively.
plottype	A character vector giving the type of plot to construct. Can be any combination of the two elements "curve" and "points".
linewidth	The line width used for plotting

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
  binary_truth = "status",
  aspects = c("fdrtp", "fdrtpcurve"))
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
  incltruth = TRUE)
plot_fdrtpcurve(cobraplot, plottype = c("curve", "points"))
```

`plot_fpc`*Plot FP curves*

Description

Plot false positive curves, indicating the number of false positives among the top-ranked N variables, for varying values of N.

Usage

```
plot_fpc(cobraplot, title = "", stripsize = 15, titlecol = "black",
         maxnfdc = 500, linewidth = 1)
```

Arguments

<code>cobraplot</code>	An COBRAPlot object.
<code>title</code>	A character string giving the title of the plot.
<code>stripsize</code>	A numeric value giving the size of the strip text, when the results are stratified by an annotation.
<code>titlecol</code>	A character string giving the color of the title.
<code>maxnfdc</code>	A numeric value giving the largest N to consider.
<code>linewidth</code>	The line width used for plotting

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                  binary_truth = "status", aspects = "fpc")
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
                                  incltruth = TRUE)
plot_fpc(cobraplot, maxnfdc = 750)
```

plot_fpr

Plot FPR

Description

Plot observed false positive rate (FPR) for given adjusted p-value thresholds.

Usage

```
plot_fpr(cobraplot, title = "", stripsize = 15, titlecol = "black",
         pointsize = 5, xaxisrange = c(0, 1))
```

Arguments

cobraplot	An COBRAPlot object.
title	A character string giving the title of the plot.
stripsize	A numeric value giving the size of the strip text, when the results are stratified by an annotation.
titlecol	A character string giving the color of the title.
pointsize	A numeric value giving the size of the plot characters.
xaxisrange	A numeric vector with two elements, giving the lower and upper boundary of the x-axis, respectively.

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                  binary_truth = "status", aspects = "fpr")
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
                                   incltruth = TRUE)
plot_fpr(cobraplot, xaxisrange = c(0, 0.25))
```

plot_overlap	<i>Plot Venn diagram</i>
--------------	--------------------------

Description

Plot a Venn diagram showing the overlaps among sets of significant feature for a given adjusted p-value threshold. Optionally, the truth can be included as a "perfect" method. Note that maximally five methods (including the truth, if applicable) can be compared.

Usage

```
plot_overlap(cobraplot, ...)
```

Arguments

cobraplot	An COBRAPlot object.
...	Additional arguments to <code>limma::vennDiagram</code> .

Value

Nothing, displays a graph

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status",
                                   aspects = "overlap")
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
                                   incltruth = TRUE)
plot_overlap(cobraplot)
```

plot_roc	<i>Plot ROC curves</i>
----------	------------------------

Description

Plot receiver operating characteristics (ROC) curves.

Usage

```
plot_roc(cobraplot, title = "", stripsize = 15, titlecol = "black",
         xaxisrange = c(0, 1), yaxisrange = c(0, 1), linewidth = 1)
```

Arguments

cobraplot	An COBRAPlot object.
title	A character string giving the title of the plot.
stripsize	A numeric value giving the size of the strip text, when the results are stratified by an annotation.
titlecol	A character string giving the color of the title.
xaxisrange	A numeric vector with two elements, giving the lower and upper boundary of the x-axis, respectively.
yaxisrange	A numeric vector with two elements, giving the lower and upper boundary of the y-axis, respectively.
linewidth	The line width used for plotting

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status", aspects = "roc")
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
                                   incltruth = TRUE)
plot_roc(cobraplot)
```

plot_scatter

Plot scatter plots

Description

Plot scatter plots, indicating the relationship between observed values and a continuous truth.

Usage

```
plot_scatter(cobraplot, title = "", stripsize = 10, titlecol = "black",
             pointsize = 3, doflip = FALSE, dolog = FALSE)
```

Arguments

cobraplot	An COBRAPlot object.
title	A character string giving the title of the plot.
stripsize	A numeric value giving the size of the strip text, when the results are stratified by an annotation.
titlecol	A character string giving the color of the title.
pointsize	A numeric value giving the size of the plot characters.
doflip	A logical indicating whether to flip the axes when results are stratified by an annotation. By default (doflip = FALSE), stratification levels are shown as columns and methods as rows in the plot.
dolog	A logical indicating whether to log10-transform values before plotting.

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example, cont_truth = "logFC",
                                   aspects = "scatter")
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
                                   incltruth = TRUE)
plot_scatter(cobraplot)
```

plot_tpr

Plot TPR

Description

Plot observed true positive rate (TPR) for given adjusted p-value thresholds.

Usage

```
plot_tpr(cobraplot, title = "", stripsize = 15, titlecol = "black",
         pointsize = 5, xaxisrange = c(0, 1))
```

Arguments

cobraplot	An COBRAPlot object.
title	A character string giving the title of the plot.
stripsize	A numeric value giving the size of the strip text, when the results are stratified by an annotation.
titlecol	A character string giving the color of the title.
pointsize	A numeric value giving the size of the plot characters.
xaxisrange	A numeric vector with two elements, giving the lower and upper boundary of the x-axis, respectively.

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status", aspects = "tpr")
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
                                   incltruth = TRUE)
plot_tpr(cobraplot)
```

plot_upset *Create UpSet plots*

Description

Generate UpSet plots showing the overlaps among sets of significant feature for a given adjusted p-value threshold. Optionally, the truth can be included as a "perfect" method. Note that if the results are stratified, only one category at a time can be displayed.

Usage

```
plot_upset(cobraplot, stratum = NULL, ...)
```

Arguments

cobraplot	An COBRAPlot object.
stratum	If results are stratified, the category to plot results for. Can be numeric or categorical (the name of the category).
...	Additional arguments to UpSetR: :upset.

Value

Nothing, displays a graph

Author(s)

Charlotte Soneson

References

Lex and Gehlenborg (2014): Points of view: Sets and intersections. *Nature Methods* 11, 779.

Lex et al (2014): UpSet: Visualization of intersecting sets. *IEEE Transactions on Visualization and Computer Graphics* 20(12), 1983-1992.

Examples

```
data(cobradata_example)
cobraperf <- calculate_performance(cobradata_example,
                                binary_truth = "status",
                                aspects = "overlap")
cobraplot <- prepare_data_for_plot(cobraperf, colorscheme = "Dark2",
                                incltruth = TRUE)

plot_upset(cobraplot)
plot_upset(cobraplot, order.by = "freq", decreasing = TRUE)

cobraperf <- calculate_performance(cobradata_example,
                                binary_truth = "status",
                                aspects = "overlap",
                                splv = "expr_cat")
cobraplot <- prepare_data_for_plot(cobraperf, colorscheme = "Dark2",
                                incltruth = TRUE)
plot_upset(cobraplot, stratum = "[2.85e+00,1.45e+01)")
```

prepare_data_for_plot *Prepare data for plotting*

Description

Prepare performance data provided in an COBRAPerformance object (obtained by [calculate_performance](#)) for plotting.

Usage

```
prepare_data_for_plot(cobraperf, keepmethods = NULL, incloverall = TRUE,
                     colorscheme = "hue_pal", faceted = TRUE, incltruth = TRUE)
```

Arguments

cobraperf	An COBRAPerformance object.
keepmethods	A character vector consisting of methods to retain for plotting (these should be a subset of basemethods(cobraperf)), or NULL (indicating that all methods represented in cobraperf should be retained).
inclooverall	A logical indicating whether the "overall" results should be included if the results are stratified by an annotation.
colorscheme	<p>Either a character string giving the color palette to use to define colors for the different methods, or a character vector with colors to use. The available pre-defined palettes depend on the number of different methods to distinguish. The choices are:</p> <ul style="list-style-type: none"> - Accent (max 8 methods) - Dark2 (max 8 methods) - Paired (max 12 methods) - Pastel1 (max 9 methods) - Pastel2 (max 8 methods) - Set1 (max 9 methods) - Set2 (max 8 methods) - Set3 (max 12 methods) - hue_pal - rainbow - heat - terrain - topo - cm <p>If the number of allowed methods is exceeded, the colorscheme defaults to hue_pal.</p>
faceted	A logical indicating whether the results should be split into subpanels when stratified by an annotation (TRUE), or kept in the same panel but shown with different colors (FALSE).
incltruth	A logical indicating whether the truth should be included in Venn diagrams.

Value

An COBRAPlot object

Author(s)

Charlotte Soneson

Examples

```

data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
  binary_truth = "status",
  cont_truth = "none",
  aspects = c("fdrtpr", "fdrtprcurve",
             "tpr", "roc"),
  thrs = c(0.01, 0.05, 0.1), splv = "none")
cobraplot <- prepare_data_for_plot(cobrapperf, keepmethods = NULL,
  colorscheme = "Dark2")

## User-specified colors
cobraplot2 <- prepare_data_for_plot(cobrapperf, keepmethods = NULL,
  colorscheme = c("blue", "red", "green"))

```

pval

Accessor and replacement functions for pval slot

Description

Accessor and replacement functions for the pval slot in an COBRADData object.

Usage

```

pval(x, ...)

pval(x, ...) <- value

## S4 method for signature 'COBRADData'
pval(x)

## S4 replacement method for signature 'COBRADData,data.frame'
pval(x) <- value

```

Arguments

x	An COBRADData object.
...	Additional arguments.
value	A data frame containing p-values for each feature and each method.

Value

The accessor function returns a data frame containing p-values for each feature and each method.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
head(pval(cobradata_example))
```

reorder_levels	<i>Reorder levels in COBRAPlot object</i>
----------------	---

Description

Reorder levels in COBRAPlot object to achieve desired ordering in figure legends etc. If `facetted(cobraplot)` is TRUE, the releveling will be applied to the "method" column. If `facetted(cobraplot)` is FALSE, it will be applied to the "fullmethod" column.

Usage

```
reorder_levels(cobraplot, levels)
```

Arguments

<code>cobraplot</code>	A COBRAPlot object
<code>levels</code>	A character vector giving the order of the levels. Any values not present in the COBRAPlot object will be removed. Any methods present in the COBRAPlot object but not contained in this vector will be added at the end.

Value

A COBRAPlot object

Author(s)

Charlotte Soneson

Examples

```
## Not run:
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status", aspects = "fpr")
cobraplot <- prepare_data_for_plot(cobrapperf, colorscheme = "Dark2",
                                   incltruth = TRUE)
cobraplot <- reorder_levels(cobraplot, c("voom", "edgeR"))
plot_fpr(cobraplot, xaxisrange = c(0, 0.25))

## End(Not run)
```

roc *Accessor and replacement functions for roc slot*

Description

Accessor and replacement functions for the roc slot in an COBRAPerformance or COBRAPlot object.

Usage

```
roc(x, ...)  
  
roc(x, ...) <- value  
  
## S4 method for signature 'COBRAPerformance'  
roc(x)  
  
## S4 replacement method for signature 'COBRAPerformance,data.frame'  
roc(x) <- value  
  
## S4 replacement method for signature 'COBRAPlot,data.frame'  
roc(x) <- value
```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A data frame giving information necessary to generate ROC curves for each method and each stratification level.

Value

The accessor function returns a data frame giving information necessary to generate ROC curves for each method and each stratification level.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)  
cobrapperf <- calculate_performance(cobradata_example,  
                                   binary_truth = "status", aspects = "roc")  
head(roc(cobrapperf))
```

`scatter`*Accessor and replacement functions for scatter slot*

Description

Accessor and replacement functions for the scatter slot in an COBRAPerformance or COBRAPlot object.

Usage

```
scatter(x, ...)
```

```
scatter(x, ...) <- value
```

```
## S4 method for signature 'COBRAPerformance'
```

```
scatter(x)
```

```
## S4 replacement method for signature 'COBRAPerformance,data.frame'
```

```
scatter(x) <- value
```

```
## S4 replacement method for signature 'COBRAPlot,data.frame'
```

```
scatter(x) <- value
```

Arguments

`x` An COBRAPerformance or COBRAPlot object.

`...` Additional arguments.

`value` A data frame giving information necessary to generate scatter plots of observed vs true values for each method and each stratification level.

Value

The accessor function returns a data frame giving information necessary to generate scatter plots of observed vs true values for each method and each stratification level.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobraperf <- calculate_performance(cobradata_example, cont_truth = "logFC",
                                 aspects = "scatter")
head(scatter(cobraperf))
```

score	<i>Accessor and replacement functions for score slot</i>
-------	--

Description

Accessor and replacement functions for the score slot in an COBRADData object.

Usage

```
score(x, ...)  
  
score(x, ...) <- value  
  
## S4 method for signature 'COBRADData'  
score(x)  
  
## S4 replacement method for signature 'COBRADData,data.frame'  
score(x) <- value
```

Arguments

x	An COBRADData object.
...	Additional arguments.
value	A data frame containing scores for each feature and each method.

Value

The accessor function returns a data frame containing scores for each feature and each method.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)  
head(score(cobradata_example))
```

`splv`*Accessor and replacement functions for splv slot*

Description

Accessor and replacement functions for the `splv` slot in an `COBRAPerformance` or `COBRAPlot` object.

Usage

```
splv(x, ...)
```

```
splv(x, ...) <- value
```

```
## S4 method for signature 'COBRAPerformance'
```

```
splv(x)
```

```
## S4 replacement method for signature 'COBRAPerformance,character'
```

```
splv(x) <- value
```

```
## S4 replacement method for signature 'COBRAPlot,character'
```

```
splv(x) <- value
```

Arguments

`x` An `COBRAPerformance` or `COBRAPlot` object.

`...` Additional arguments.

`value` A character string giving the name of a feature annotation to use for stratification.

Value

The accessor function returns a character string giving the name of a feature annotation to use for stratification.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status",
                                   aspects = "fdrtpr", splv = "expr_cat")
splv(cobrapperf)
```

stratiflevels	<i>Accessor function for stratification levels</i>
---------------	--

Description

Accessor function to extract the stratification levels that are represented in an COBRAPerformance or COBRAPlot object.

Usage

```
stratiflevels(x, ...)
```

```
## S4 method for signature 'COBRAPerformance'
```

```
stratiflevels(x)
```

Arguments

x	An COBRAPerformance or COBRAPlot object
...	Additional arguments

Value

A character vector of all stratification levels represented in the object

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
cobrapperf <- calculate_performance(cobradata_example,
                                   binary_truth = "status",
                                   aspects = "fdrtpr", splv = "expr_cat",
                                   maxsplit = 4)
stratiflevels(cobrapperf)
```

tpr	<i>Accessor and replacement functions for tpr slot</i>
-----	--

Description

Accessor and replacement functions for the tpr slot in an COBRAPerformance or COBRAPlot object.

Usage

```
tpr(x, ...)
```

```
tpr(x, ...) <- value
```

```
## S4 method for signature 'COBRAPerformance'
```

```
tpr(x)
```

```
## S4 replacement method for signature 'COBRAPerformance,data.frame'
```

```
tpr(x) <- value
```

```
## S4 replacement method for signature 'COBRAPlot,data.frame'
```

```
tpr(x) <- value
```

Arguments

x	An COBRAPerformance or COBRAPlot object.
...	Additional arguments.
value	A data frame giving information about the observed TPR for each method and each stratification level, at various adjusted p-value thresholds.

Value

The accessor function returns a data frame giving information about the observed TPR for each method and each stratification level, at various adjusted p-value thresholds.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)
```

```
cobraperf <- calculate_performance(cobradata_example,
```

```
                                binary_truth = "status", aspects = "tpr")
```

```
head(tpr(cobraperf))
```

truth

Accessor and replacement functions for truth slot

Description

Accessor and replacement functions for the truth slot in an COBRADData object.

Usage

```
truth(x, ...)  
  
truth(x, ...) <- value  
  
## S4 method for signature 'COBRADData'  
truth(x)  
  
## S4 replacement method for signature 'COBRADData,data.frame'  
truth(x) <- value
```

Arguments

x	An COBRADData object.
...	Additional arguments.
value	A data frame containing true assignments and/or scores for features, together with other feature annotations to use for stratification of performance calculations.

Value

The accessor function returns a data frame containing true assignments and/or scores for features, together with other feature annotations to use for stratification of performance calculations.

Author(s)

Charlotte Soneson

Examples

```
data(cobradata_example)  
head(truth(cobradata_example))
```


Index

*Topic **datasets**

- cobradata_example, 8
- .COBRADData (COBRADData-class), 7
- .COBRAPerformance
 - (COBRAPerformance-class), 9
- .COBRAPlot (COBRAPlot-class), 11
- [(Extract), 15
- [, COBRADData-method (Extract), 15
- [, COBRAPerformance-method (Extract), 15
- [, COBRAPlot-method (Extract), 15

- basemethods, 3
- basemethods, COBRAPerformance-method
 - (basemethods), 3
- basemethods, COBRAPlot-method
 - (basemethods), 3

- calculate_adj, 3, 8
- calculate_performance, 4, 9, 38
- COBRAapp, 6
- COBRADData (COBRADData-class), 7
- COBRADData-class, 7
- cobradata_example, 8
- COBRADData_from_text (COBRADData-class), 7
- COBRADData_to_text, 6
- COBRADData_to_text (COBRADData-class), 7
- COBRAPerformance
 - (COBRAPerformance-class), 9
- COBRAPerformance-class, 9
- COBRAPlot (COBRAPlot-class), 11
- COBRAPlot, COBRAPerformance-method
 - (coerce), 12
- COBRAPlot-class, 11
- coerce, 12
- coerce, (coerce), 12
- coerce, COBRAPerformance, COBRAPlot-method
 - (coerce), 12
- coerce, COBRAPlot, COBRAPerformance-method
 - (coerce), 12
- corr, 13

- corr, COBRAPerformance-method (corr), 13
- corr, COBRAPlot-method (corr), 13
- corr<- (corr), 13
- corr<-, COBRAPerformance, data.frame-method
 - (corr), 13
- corr<-, COBRAPlot, data.frame-method
 - (corr), 13

- deviation, 14
- deviation, COBRAPerformance-method
 - (deviation), 14
- deviation, COBRAPlot-method (deviation),
14
- deviation<- (deviation), 14
- deviation<-, COBRAPerformance, data.frame-method
 - (deviation), 14
- deviation<-, COBRAPlot, data.frame-method
 - (deviation), 14

- Extract, 15

- facetted, 16
- facetted, COBRAPlot-method (facetted), 16
- facetted<- (facetted), 16
- facetted<-, COBRAPlot, logical-method
 - (facetted), 16

- fdrnbr, 17
- fdrnbr, COBRAPerformance-method
 - (fdrnbr), 17
- fdrnbr, COBRAPlot-method (fdrnbr), 17
- fdrnbr<- (fdrnbr), 17
- fdrnbr<-, COBRAPerformance, data.frame-method
 - (fdrnbr), 17
- fdrnbr<-, COBRAPlot, data.frame-method
 - (fdrnbr), 17

- fdrnbrcurve, 18
- fdrnbrcurve, COBRAPerformance-method
 - (fdrnbrcurve), 18
- fdrnbrcurve, COBRAPlot-method
 - (fdrnbrcurve), 18

- fdrnbrcurve<- (fdrnbrcurve), 18
- fdrnbrcurve<- ,COBRAPerformance, data.frame-method (fdrnbrcurve), 18
- fdrnbrcurve<- ,COBRAPlot, data.frame-method (fdrnbrcurve), 18
- fdrtptr, 19
- fdrtptr, COBRAPerformance-method (fdrtptr), 19
- fdrtptr, COBRAPlot-method (fdrtptr), 19
- fdrtptr<- (fdrtptr), 19
- fdrtptr<- ,COBRAPerformance, data.frame-method (fdrtptr), 19
- fdrtptr<- ,COBRAPlot, data.frame-method (fdrtptr), 19
- fdrtptrcurve, 20
- fdrtptrcurve, COBRAPerformance-method (fdrtptrcurve), 20
- fdrtptrcurve, COBRAPlot-method (fdrtptrcurve), 20
- fdrtptrcurve<- (fdrtptrcurve), 20
- fdrtptrcurve<- ,COBRAPerformance, data.frame-method (fdrtptrcurve), 20
- fdrtptrcurve<- ,COBRAPlot, data.frame-method (fdrtptrcurve), 20
- fpc, 21
- fpc, COBRAPerformance-method (fpc), 21
- fpc, COBRAPlot-method (fpc), 21
- fpc<- (fpc), 21
- fpc<- ,COBRAPerformance, data.frame-method (fpc), 21
- fpc<- ,COBRAPlot, data.frame-method (fpc), 21
- fpr, 22
- fpr, COBRAPerformance-method (fpr), 22
- fpr, COBRAPlot-method (fpr), 22
- fpr<- (fpr), 22
- fpr<- ,COBRAPerformance, data.frame-method (fpr), 22
- fpr<- ,COBRAPlot, data.frame-method (fpr), 22
- maxsplit, 23
- maxsplit, COBRAPerformance-method (maxsplit), 23
- maxsplit, COBRAPlot-method (maxsplit), 23
- maxsplit<- (maxsplit), 23
- maxsplit<- ,COBRAPerformance, numeric-method (maxsplit), 23
- maxsplit<- ,COBRAPlot, numeric-method (maxsplit), 23
- onlyshared, 24
- onlyshared, COBRAPerformance-method (onlyshared), 24
- onlyshared, COBRAPlot-method (onlyshared), 24
- onlyshared<- (onlyshared), 24
- onlyshared<- ,COBRAPerformance, logical-method (onlyshared), 24
- onlyshared<- ,COBRAPlot, logical-method (onlyshared), 24
- overlap, 25
- overlap, COBRAPerformance-method (overlap), 25
- overlap, COBRAPlot-method (overlap), 25
- overlap<- (overlap), 25
- overlap<- ,COBRAPerformance, list_df-method (overlap), 25
- overlap<- ,COBRAPlot, list_df-method (overlap), 25
- padj, 26
- padj, COBRADData-method (padj), 26
- padj<- (padj), 26
- padj<- ,COBRADData, data.frame-method (padj), 26
- plot_corr, 28
- plot_deviation, 29
- plot_fdrnbrcurve, 30
- plot_fdrtptrcurve, 31
- plot_fpc, 32
- plot_fpr, 33
- plot_overlap, 34
- plot_roc, 34
- plot_scatter, 35
- plot_tpr, 36
- plot_upset, 37
- plotcolors, 27
- plotcolors, COBRAPlot-method (plotcolors), 27
- plotcolors<- (plotcolors), 27
- plotcolors<- ,COBRAPlot, character-method (plotcolors), 27
- prepare_data_for_plot, 11, 38
- pval, 40
- pval, COBRADData-method (pval), 40
- pval<- (pval), 40

`pval<-`, COBRADData, data.frame-method
(pval), 40

`reorder_levels`, 41

`roc`, 42

`roc`, COBRAPerformance-method (roc), 42

`roc`, COBRAPlot-method (roc), 42

`roc<-` (roc), 42

`roc<-`, COBRAPerformance, data.frame-method
(roc), 42

`roc<-`, COBRAPlot, data.frame-method
(roc), 42

`scatter`, 43

`scatter`, COBRAPerformance-method
(scatter), 43

`scatter`, COBRAPlot-method (scatter), 43

`scatter<-` (scatter), 43

`scatter<-`, COBRAPerformance, data.frame-method
(scatter), 43

`scatter<-`, COBRAPlot, data.frame-method
(scatter), 43

`score`, 44

`score`, COBRADData-method (score), 44

`score<-` (score), 44

`score<-`, COBRADData, data.frame-method
(score), 44

`splv`, 45

`splv`, COBRAPerformance-method (splv), 45

`splv`, COBRAPlot-method (splv), 45

`splv<-` (splv), 45

`splv<-`, COBRAPerformance, character-method
(splv), 45

`splv<-`, COBRAPlot, character-method
(splv), 45

`stratiflevels`, 46

`stratiflevels`, COBRAPerformance-method
(stratiflevels), 46

`stratiflevels`, COBRAPlot-method
(stratiflevels), 46

`tpr`, 46

`tpr`, COBRAPerformance-method (tpr), 46

`tpr`, COBRAPlot-method (tpr), 46

`tpr<-` (tpr), 46

`tpr<-`, COBRAPerformance, data.frame-method
(tpr), 46

`tpr<-`, COBRAPlot, data.frame-method
(tpr), 46

`truth`, 47

`truth`, COBRADData-method (truth), 47

`truth<-` (truth), 47

`truth<-`, COBRADData, data.frame-method
(truth), 47