

Package ‘DiffLogo’

September 21, 2024

Type Package

Title DiffLogo: A comparative visualisation of biooligomer motifs

Version 2.29.0

Date 2015-02-12

Author c(
 person(`` Martin", `` Nettling", role = c(`` aut", `` cre"), email = `` martin.nettling@informatik.uni-halle.de"),
 person(`` Hendrik", `` Treutler", role = c(`` aut", `` cre"), email = `` hendrik.treutler@ipb-halle.de"),
 person(`` Jan", `` Grau", role = c(`` aut", `` ctb"), email = `` grau@informatik.uni-halle.de"),
 person(`` Andrey", `` Lando", role = c(`` aut", `` ctb"), email = `` dronte@autosome.ru"),
 person(`` Jens", `` Keilwagen", role = c(`` aut", `` ctb"), email = `` jens.keilwagen@julius-kuehn.de"),
 person(`` Stefan", `` Posch", role = `` aut", email = `` posch@informatik.uni-halle.de"),
 person(`` Ivo", `` Grosse", role = `` aut", email = `` grosse@informatik.uni-halle.de"))

Depends R (>= 3.4), stats, cba

Imports grDevices, graphics, utils, tools

Suggests knitr, testthat, seqLogo, MotifDb

Maintainer Hendrik Treutler<hendrik.treutler@gmail.com>

Description DiffLogo is an easy-to-use tool to visualize motif differences.

License GPL (>= 2)

URL <https://github.com/mgledi/DiffLogo/>

BugReports <https://github.com/mgledi/DiffLogo/issues>

biocViews Software, SequenceMatching, MultipleComparison,
MotifAnnotation, Visualization, Alignment

Collate 'alphabet.R' 'baseDistrs.R' 'diffSeqLogo.R' 'preconditions.R'
 'seqLogo.R' 'stackHeights.R' 'utilities.R'
 'diffSeqLogoSupport.R' 'pwmAlignment.R'

RoxygenNote 6.1.1

git_url <https://git.bioconductor.org/packages/DiffLogo>

git_branch devel

git_last_commit bff5c6a

git_last_commit_date 2024-04-30

Repository Bioconductor 3.20

Date/Publication 2024-09-20

Contents

alignPwmSets	3
Alphabet	3
ASN	4
baseDistributionPwm	4
calculatePvalue	5
createDiffLogoObject	6
differenceOfICs	7
diffLogo	8
diffLogoFromPwm	9
diffLogoTable	10
diffLogoTableConfiguration	11
DNA	13
drawDiffLogoTable	13
enrichDiffLogoObjectWithPvalues	14
enrichDiffLogoTableWithPvalues	15
extendPwmsFromAlignmentVector	16
FULL_ALPHABET	17
getAlphabetFromCharacters	17
getAlphabetFromSequences	18
getPwmFromAlignment	18
getPwmFromAlignmentFile	19
getPwmFromFastaFile	19
getPwmFromFile	20
getPwmFromHomerFile	20
getPwmFromPfmOrJasparFile	21
getPwmFromPwmFile	21
getSequencesFromAlignmentFile	22
getSequencesFromFastaFile	22
informationContent	23
localPwmAlignment	24
lossOfAbsICDifferences	25
multipleLocalPwmsAlignment	25
normalizedDifferenceOfProbabilities	26
normalizePWM	27
prepareDiffLogoTable	28
probabilities	29
pwmDivergence	29
pwmsDistanceMatrix	30
reverseAlignmentVector	31
RNA	31
seqLogo	32
shannonDivergence	33
sumOfAbsICDifferences	33
sumOfAbsProbabilityDifferences	34
sumProbabilities	35
switchDirection	36
twoSetsAveragePwmDivergenceFromAlignmentVector	36

alignPwmSets	<i>Multiple PWMs alignment</i>
--------------	--------------------------------

Description

Align two sets of pwms

Usage

```
alignPwmSets(left_pwms_set, left_alignment, right_pwms_set,
             right_alignment, try_reverse_complement)
```

Arguments

left_pwms_set list of pwms(matrixes)
left_alignment alignment of left_pwms_set.
right_pwms_set list of pwms;
right_alignment alignment of right_pwms_set.
try_reverse_complement
 if true(default), also try reverse complement.

Value

list - alignment of concatenation of left_pwms_set and right_pwms_set

Author(s)

Lando Andrey

Alphabet	<i>built alphabet</i>
----------	-----------------------

Description

builds an object of class Alphabet from the given set of symbols and colors

Usage

```
Alphabet(chars, cols, supportReverseComplement)
```

Arguments

chars set of symbols
cols set of colors; one for each symbol
supportReverseComplement
 boolean whether the alphabet supports reverse complementation (like DNA/RNA)
 or not (like ASN)

Value

the Alphabet object

Author(s)

Martin Nettling

Examples

```
DNA = Alphabet(c("A", "C", "G", "T"), c("green4", "blue", "orange", "red"), TRUE)
```

ASN

ASN alphabet

Description

the amino acid alphabet (20 symbols), i.e. A, C, D, E, F, G, H, I, K, L, M, N, P, Q, R, S, T, V, W, Y

Usage

ASN

Format

An object of class Alphabet of length 4.

Author(s)

Martin Nettling

Examples

```
ASN
```

baseDistributionPwm

Generates a PWM

Description

Generates a PWM consisting of only the uniform distribution or the given base_distribution (if defined).

Usage

```
baseDistributionPwm(pwm_length, alphabet_length,
  base_distribution = NULL)
```

Arguments

pwm_length the number of positions
alphabet_length the alphabet size
base_distribution optional base distribution for each PWM position

Value

a PWM

calculatePvalue	<i>p-value that two PWM-positions are from the same distribution</i>
-----------------	--

Description

Calculates the p-value for the null-hypothesis that two given probability vectors p1, p2 calculated from n1/n2 observations arise from the same distribution

Usage

```
calculatePvalue(p1, p2, n1, n2, stackHeight = shannonDivergence,  
                numberOfPermutations = 100, plotGammaDistributionFit = FALSE)
```

Arguments

p1 first probability vector with one probability for each symbol of the alphabet
p2 second probability vector with one probability for each symbol of the alphabet
n1 number of observations for the calculation of p1
n2 number of observations for the calculation of p2
stackHeight function for the calculation of a divergence measure for two probability vectors
numberOfPermutations the number of permutations to perform for the calculation of stackHeights
plotGammaDistributionFit if TRUE the fit of a gamma distribution to the sampled stackHeights is plotted

Value

a numeric p-value

Author(s)

Hendrik Treutler

Examples

```

p1 <- c(0.2, 0.3, 0.1, 0.4)
p2 <- c(0.2, 0.1, 0.3, 0.4)
n1 <- 100
n2 <- 200
numberOfPermutations = 100
plotGammaDistributionFit = TRUE

pValue <- calculatePvalue(p1 = p1, p2 = p2, n1 = n1, n2 = n2, stackHeight = shannonDivergence, numberOfPermutati

```

createDiffLogoObject *DiffLogo object*

Description

Creates a DiffLogo object

Usage

```

createDiffLogoObject(pwm1, pwm2, stackHeight = shannonDivergence,
  baseDistribution = normalizedDifferenceOfProbabilities,
  alphabet = DNA, align_pwms = FALSE,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, base_distribution = NULL,
  length_normalization = FALSE, unaligned_from_left = 0,
  unaligned_from_right = 0)

```

Arguments

pwm1	representation of the first position weight matrix (PWM) of type pwm, data.frame, or matrix
pwm2	representation of the second position weight matrix (PWM) of type pwm, data.frame, or matrix
stackHeight	function for the height of a stack at position i
baseDistribution	function for the heights of the individual bases
alphabet	of type Alphabet
align_pwms	if True, will align and extend pwms.
unaligned_penalty	is a function for localPwmAlignment.
try_reverse_complement	if True, alignment will try reverse complement pwms
base_distribution	is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used
length_normalization	If true, will minimize the average divergence between PWMs. Otherwise will minimize the sum of divergences between positions. In both cases unaligned positions are compared to base_distribution and are counted when computing the alignment length.

unaligned_from_left
 the number of unaligned positions on the left
 unaligned_from_right
 the number of unaligned positions on the right

Value

DiffLogo object

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoObj = createDiffLogoObject(pwm1 = pwm1, pwm2 = pwm2)
diffLogo(diffLogoObj)
```

differenceOfICs

normalized information content differences

Description

information content differences normalized by the sum of absolute information content differences for the given pair of probability vectors

Usage

```
differenceOfICs(p1, p2)
```

Arguments

p1 probability vector representing the first symbol distribution
 p2 probability vector representing the second symbol distribution

Value

a vector with one result for each symbol

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, baseDistribution = differenceOfICs)

```

diffLogo	<i>Draw DiffLogo</i>
----------	----------------------

Description

Draws the difference of two sequence logos.

Usage

```

diffLogo(diffLogoObj, ymin = 0, ymax = 0, sparse = FALSE,
         diffLogoConfiguration = list())

```

Arguments

diffLogoObj	a DiffLogoObject created by the function createDiffLogoObject
ymin	minimum value on the y-axis
ymax	maximum value on the y-axis
sparse	if TRUE margins are reduced and tickmarks are removed from the logo
diffLogoConfiguration	list of configuration parameters (see function diffLogoTableConfiguration(...))

Value

none (draws difference logo)

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoObj = createDiffLogoObject(pwm1 = pwm1, pwm2 = pwm2)
diffLogo(diffLogoObj)

```

diffLogoFromPwm	<i>Draw DiffLogo from PWM</i>
-----------------	-------------------------------

Description

Draws the difference of two sequence logos.

Usage

```

diffLogoFromPwm(pwm1, pwm2, ymin = 0, ymax = 0,
  stackHeight = shannonDivergence,
  baseDistribution = normalizedDifferenceOfProbabilities,
  sparse = FALSE, alphabet = DNA, align_pwms = FALSE,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, base_distribution = NULL,
  length_normalization = FALSE)

```

Arguments

pwm1	representation of the first position weight matrix (PWM) of type pwm, data.frame, or matrix
pwm2	representation of the second position weight matrix (PWM) of type pwm, data.frame, or matrix
ymin	minimum value on the y-axis
ymax	maximum value on the y-axis
stackHeight	function for the height of a stack at position i
baseDistribution	function for the heights of the individual bases
sparse	if TRUE margins are reduced and tickmarks are removed from the logo
alphabet	of type Alphabet
align_pwms	if true, DiffLogo will align pwms before plotting
unaligned_penalty	is a function for localPwmAlignment.

`try_reverse_complement`
 if True, alignment will try reverse complement pwms

`base_distribution`
 is a vector of length `nrow(pwm)` that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used

`length_normalization`
 If true, will minimize the average divergence between PWMs. Otherwise will minimize the sum of divergences between positions. In both cases unaligned positions are compared to `base_distribution` and are counted when computing the alignment length.

Value

none (draws difference logo)

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2)
```

diffLogoTable

Draw DiffLogo-table

Description

Draws a table of DiffLogos.

Usage

```
diffLogoTable(PWMs, sampleSizes = NULL, alphabet = DNA,
  configuration = list(), ...)
```

Arguments

PWMs	a list/vector of position weight matrices (PWMs) each of type pwm, data.frame, or matrix
sampleSizes	the number of sequences behind each PWM
alphabet	the alphabet of the given PWMs
configuration	list of (probably part of) of configuration options. See diffLogoTableConfiguration.
...	set of parameters passed to the function 'axis' for plotting

Value

none (draws table of difference logos)

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

diffLogoTable(motifs)

```

diffLogoTableConfiguration

Configuration object for diffLogoTable

Description

Default configuration list for diffLogoTable

Usage

```

diffLogoTableConfiguration(alphabet, stackHeight = shannonDivergence,
  baseDistribution = normalizedDifferenceOfProbabilities,
  uniformYaxis = TRUE, sparse = TRUE, showSequenceLogosTop = TRUE,
  enableClustering = TRUE, treeHeight = 0.5, margin = 0.02,
  ratio = 1, align_pwm = FALSE, multiple_align_pwm = TRUE,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, length_normalization = FALSE,
  numberOfPermutations = 100)

```

Arguments

alphabet	used alphabet of type Alphabet
stackHeight	function for the height of a stack at position i
baseDistribution	function for the heights of the individual bases
uniformYaxis	if TRUE each DiffLogo is plotted with the same scaling of the y-axis
sparse	if TRUE margins are reduced and tickmarks are removed from the logo
showSequenceLogosTop	if TRUE the classical sequence logos are drawn above each column of the table
enableClustering	if TRUE the motifs are reordered, so that similar motifs have a small vertical and horizontal distance in the table
treeHeight	the height of the plotted cluster tree above the columns of the table; set equal to zero to omit the cluster tree
margin	the space reserved for labels
ratio	the ratio of the plot; this is needed to determine the margin sizes correctly
align_pwm	if True, will align and extend pwms in each cell of diffLogoTable independently.
multiple_align_pwm	if True, will align and extend pwms in the diffLogoTable jointly.
unaligned_penalty	is a function for localPwmAlignment.
try_reverse_complement	if True, alignment will try reverse complement pwms
length_normalization	if True, divergence between pwms is divided by length of pwms.
numberOfPermutations	number of permutations for the permutation test for the calculation of p-values

Value

list of parameters

Author(s)

Lando Andrey

Examples

```
diffLogoTableConfiguration(DNA)
```

DNA	<i>DNA alphabet</i>
-----	---------------------

Description

the DNA alphabet, i.e. A, C, G, T

Usage

DNA

Format

An object of class Alphabet of length 4.

Author(s)

Martin Nettling

Examples

DNA

drawDiffLogoTable	<i>Draws a table of DiffLogos</i>
-------------------	-----------------------------------

Description

Draws a table of DiffLogos.

Usage

```
drawDiffLogoTable(diffLogoTableObj, ...)
```

Arguments

diffLogoTableObj	the diffLogoTable-Object created by function prepareDiffLogoTable(...)
...	optional parameters for function axis

Value

none (draws difference logo)

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

diffLogoTableObj = prepareDiffLogoTable(motifs)
drawDiffLogoTable(diffLogoTableObj)

```

enrichDiffLogoObjectWithPvalues

Enriches a difflogo object with p-values

Description

Enriches a difflogo object with p-values which quantifies the probability that two PWM-positions are from the same distribution

Usage

```

enrichDiffLogoObjectWithPvalues(diffLogoObj, n1, n2,
  stackHeight = shannonDivergence, numberOfPermutations = 100)

```

Arguments

diffLogoObj	matrix of difflogo objects
n1	the number of sequences behind the first pwm behind the given difflogo object
n2	the number of sequences behind the second pwm behind the given difflogo object
stackHeight	function for the calculation of a divergence measure for two probability vectors
numberOfPermutations	the number of permutations to perform for the calculation of stackHeights

Value

enriched difflogo object

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

```

```

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]
n1 <- 100
n2 <- 100
diffLogoObj = createDiffLogoObject(pwm1 = pwm1, pwm2 = pwm2)
diffLogoObj = enrichDiffLogoObjectWithPvalues(diffLogoObj, n1, n2)

```

enrichDiffLogoTableWithPvalues

Enriches a matrix of difflogo objects with p-values

Description

Enriches a matrix of difflogo objects with p-values which quantifies the probability that two PWM-positions are from the same distribution

Usage

```

enrichDiffLogoTableWithPvalues(diffLogoObjMatrix, sampleSizes,
  stackHeight = shannonDivergence, numberOfPermutations = 100)

```

Arguments

diffLogoObjMatrix	matrix of difflogo objects
sampleSizes	number of sequences behind the pwms behind the given difflogo objects
stackHeight	function for the calculation of a divergence measure for two probability vectors
numberOfPermutations	the number of permutations to perform for the calculation of stackHeights

Value

matrix of difflogo objects enriched with p-values

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}
sampleSizes <- c(100, 150, 200, 250)
names(sampleSizes) <- motif_names

diffLogoTableObj = prepareDiffLogoTable(motifs);
diffLogoTableObj$diffLogoObjMatrix = enrichDiffLogoTableWithPvalues(diffLogoTableObj$diffLogoObjMatrix, samp

```

`extendPwmsFromAlignmentVector`*Extend pwms with respect to alignment*

Description

Extends pwms by adding base_distribution to both sides, so that they keep aligned, but have equal length.

Usage

```
extendPwmsFromAlignmentVector(pwms, alignment_vector,  
  base_distribution = NULL)
```

Arguments

`pwms` is a list of matrixes

`alignment_vector`
is a list of shifts (`$shift`) and orientations (`$direction`)

`base_distribution`
is a vector of length `nrow(pwm)` that is added to unaligned columns of pwms for comparing. If `NULL`, uniform distribution is used

Value

extended pwms

Author(s)

Lando Andrey

Examples

```
file1 = system.file("extdata/homer/Max.motif", package = "DiffLogo")  
file2 = system.file("extdata/homer/c-Myc.motif", package = "DiffLogo")  
pwm1 = getPwmFromFile(file1)  
pwm2 = getPwmFromFile(file2)  
  
pwms <- list(pwm1, pwm2)  
multiple_pwms_alignment = multipleLocalPwmsAlignment(pwms)  
aligned_pwms = extendPwmsFromAlignmentVector(pwms, multiple_pwms_alignment$alignment$vector)
```

FULL_ALPHABET	<i>Complete character alphabet</i>
---------------	------------------------------------

Description

the alphabet of all 26 characters

Usage

FULL_ALPHABET

Format

An object of class Alphabet of length 4.

Author(s)

Hendrik Treutler

Examples

FULL_ALPHABET

getAlphabetFromCharacters	<i>returns the alphabet which fits to the given characters</i>
---------------------------	--

Description

returns the alphabet which fits to the given characters

Usage

getAlphabetFromCharacters(characters)

Arguments

characters a character vector of characters

Value

an alphabet of type Alphabet

Examples

alphabet = getAlphabetFromSequences(c("A","A","C","C","G","G","T","T"))

`getAlphabetFromSequences`*returns the alphabet which fits to the given sequences*

Description

returns the alphabet which fits to the given sequences

Usage

```
getAlphabetFromSequences(sequences)
```

Arguments

`sequences` a character vector of sequences

Value

an alphabet of type `Alphabet`

Examples

```
alphabet = getAlphabetFromSequences("AACCGGTT")
```

`getPwmFromAlignment`*Create PWM from alignment*

Description

Creates a matrix-representation of a PWM from a set of sequences

Usage

```
getPwmFromAlignment(alignment, alphabet = NULL, pseudoCount = 0)
```

Arguments

`alignment` a vector or list of sequences each with equal length
`alphabet` of type `Alphabet`
`pseudoCount` the number of pseudo-observations for each character in the alphabet

Value

PWM as matrix

Author(s)

Hendrik Treutler

Examples

```
motif_folder= "extdata/alignments"
motif_name = "calamodulin_1"
fileName = paste(motif_folder,"/",motif_name,".txt",sep="")
file = system.file(fileName, package = "DiffLogo")
motif = getPwmFromAlignment(readLines(file), ASN, 1)
seqLogo(pwm = motif, alphabet=ASN)
```

`getPwmFromAlignmentFile`*generates a pwm from an alignment file*

Description

generates a pwm from an alignment file

Usage

```
getPwmFromAlignmentFile(filename, alphabet = NULL)
```

Arguments

filename	the alignment file
alphabet	the desired alphabet of type Alphabet

Value

a pwm

Examples

```
fileName = "extdata/alignments/calamodulin_1.txt"
file = system.file(fileName, package = "DiffLogo")
pwm = getPwmFromAlignmentFile(file)
```

`getPwmFromFastaFile`*generates a pwm from a FASTA file*

Description

generates a pwm from a FASTA file

Usage

```
getPwmFromFastaFile(filename, alphabet = NULL)
```

Arguments

filename	the FASTA file
alphabet	the desired alphabet of type Alphabet

Value

a pwm

Examples

```
fileName = "extdata/alignments/F-box_bacteria.seq.fa"
file = system.file(fileName, package = "DiffLogo")
pwm = getPwmFromFastaFile(file)
```

getPwmFromFile	<i>generates a pwm from a file of different formats</i>
----------------	---

Description

Generates a pwm from a file of different formats. Supported formats are FASTA files (.fa, .fasta), alignment files (.txt, .text, .al, .alignment), PWM files (.pwm), JASPAR / Position Frequency Matrix files (.pfm), and homer files (.motif).

Usage

```
getPwmFromFile(filename)
```

Arguments

filename	the file
----------	----------

Value

a pwm

Examples

```
fileName = "extdata/pwm/H1-hESC.pwm"
file = system.file(fileName, package = "DiffLogo")
pwm = getPwmFromFile(file)
```

getPwmFromHomerFile	<i>generates a pwm from a homer file</i>
---------------------	--

Description

generates a pwm from a homer file

Usage

```
getPwmFromHomerFile(filename)
```

Arguments

filename	the homer file
----------	----------------

Value

a pwm

Examples

```
fileName = "extdata/homer/CTCF_Zf_CD4.motif"  
file = system.file(fileName, package = "DiffLogo")  
pwm = getPwmFromHomerFile(file)
```

getPwmFromPfmOrJasparFile

generates a pwm from a jaspar file

Description

generates a pwm from a jaspar file

Usage

```
getPwmFromPfmOrJasparFile(filename)
```

Arguments

filename the jaspar file

Value

a pwm

Examples

```
fileName = "extdata/pfm/ctcf_jaspar.pfm"  
file = system.file(fileName, package = "DiffLogo")  
pwm = getPwmFromPfmOrJasparFile(file)
```

getPwmFromPwmFile

generates a pwm from a pwm file

Description

generates a pwm from a pwm file

Usage

```
getPwmFromPwmFile(filename)
```

Arguments

filename the pwm file

Value

a pwm

Examples

```
fileName = "extdata/pwm/H1-hESC.pwm"  
file = system.file(fileName, package = "DiffLogo")  
pwm = getPwmFromPwmFile(file)
```

getSequencesFromAlignmentFile

extracts the sequences from an alignment file

Description

extracts the sequences from an alignment file

Usage

```
getSequencesFromAlignmentFile(filename)
```

Arguments

filename the alignment file

Value

a vector of sequences

Examples

```
fileName = "extdata/alignments/calamodulin_1.txt"  
file = system.file(fileName, package = "DiffLogo")  
sequences = getSequencesFromAlignmentFile(file)
```

getSequencesFromFastaFile

extracts the sequences from a FASTA file

Description

extracts the sequences from a FASTA file

Usage

```
getSequencesFromFastaFile(filename)
```

Arguments

filename the FASTA file

Value

a vector of sequences

Examples

```
fileName = "extdata/alignments/F-box_bacteria.seq.fa"
file = system.file(fileName, package = "DiffLogo")
sequences = getSequencesFromFastaFile(file)
```

informationContent	<i>information content</i>
--------------------	----------------------------

Description

the information content for the given probability vector

Usage

```
informationContent(p)
```

Arguments

p	probability vector representing the symbol distribution
---	---

Value

an object consisting of height a ylab

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_name = "HepG2"
fileName = paste(motif_folder,"/",motif_name,".pwm",sep="")
file = system.file(fileName, package = "DiffLogo")
motif = getPwmFromPwmFile(file)
seqLogo(pwm = motif, stackHeight = informationContent)
```

localPwmAlignment	<i>Align pwms</i>
-------------------	-------------------

Description

Finds best local alignment for two PWMs.

Usage

```
localPwmAlignment(pwm_left, pwm_right, divergence = shannonDivergence,  
  unaligned_penalty = divergencePenaltyForUnaligned,  
  try_reverse_complement = TRUE, base_distribution = NULL,  
  length_normalization = FALSE)
```

Arguments

pwm_left	first PWM, a matrix of type matrix
pwm_right	first PWM, a matrix of type matrix
divergence	is a measure of difference between two pwm columns. Smaller is more similar. If you want to use non-uniform background distribution, provide your own function.
unaligned_penalty	distance for unaligned columns at edges of matrixes. See divergencePenaltyForUnaligned as an example for providing your own function
try_reverse_complement	If false the alignment will not be performed on reverse complements. If true, the input pwms should have column order of ACTG/ACGU.
base_distribution	is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used
length_normalization	If true, will minimize the average divergence between PWMs. Otherwise will minimize the sum of divergences between positions. In both cases unalignes positions are compared to base_distribution and are counted when computing the alignment length.

Value

list of length two containing the alignment and the divergence

Author(s)

Lando Andrey

lossOfAbsICDifferences

the change of information content

Description

the change of information content for the given probability vectors

Usage

```
lossOfAbsICDifferences(p1, p2)
```

Arguments

p1	probability vector representing the first symbol distribution
p2	probability vector representing the second symbol distribution

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, stackHeight = lossOfAbsICDifferences)
```

multipleLocalPwmsAlignment

Multiple PWMs alignment

Description

Creates a multiple alignment of pwms

Usage

```
multipleLocalPwmsAlignment(pwms, divergence = shannonDivergence,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, base_distribution = NULL,
  length_normalization = FALSE)
```

Arguments

pwms list of pwms

divergence Divergence measure.

unaligned_penalty is a function for localPwmAlignment.

try_reverse_complement if True, alignment will try reverse complement pwms

base_distribution is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used

length_normalization If true, will minimize the average divergence between PWMs. Otherwise will minimize the sum of divergences between positions. In both cases unaligned positions are compared to base_distribution and are counted when computing the alignment length.

Value

list

Author(s)

Lando Andrey

Examples

```
file1 = system.file("extdata/homer/Max.motif", package = "DiffLogo")
file2 = system.file("extdata/homer/c-Myc.motif", package = "DiffLogo")
pwm1 = getPwmFromFile(file1)
pwm2 = getPwmFromFile(file2)

multiple_pwms_alignment = multipleLocalPwmsAlignment(list(pwm1, pwm2))
```

normalizedDifferenceOfProbabilities

normalized probability differences

Description

probability differences normalized by the sum of absolute probability differences for the given pair of probability vectors

Usage

```
normalizedDifferenceOfProbabilities(p1, p2)
```

Arguments

p1 probability vector representing the first symbol distribution
 p2 probability vector representing the second symbol distribution

Value

a vector with one result for each symbol

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, baseDistribution = normalizedDifferenceOfProbabilities)
```

normalizePWM	<i>normalizes the given pwm</i>
--------------	---------------------------------

Description

normalizes the given pwm to column-sums of 1.0

Usage

```
normalizePWM(pwm)
```

Arguments

pwm a pwm

Value

a normalized pwm

Examples

```
pwm = matrix(1:40, nrow = 4, dimnames = list(c("A","C","G","T"), 1:10))
pwm = normalizePWM(pwm)
```

```
prepareDiffLogoTable    Prepare a table of difflogo objects
```

Description

Prepares a DiffLogoTable and generates an object that contains the hierarchical clustering and a matrix of prepared difference logos.

Usage

```
prepareDiffLogoTable(PWMs, alphabet = DNA, configuration = list())
```

Arguments

PWMs	a list/vector of position weight matrices (PWMs) each of type pwm, data.frame, or matrix
alphabet	the alphabet of the given PWMs
configuration	list of (probably part of) of configuration options. See diffLogoTableConfiguration.

Value

matrix of difference logos

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}
sampleSizes <- c(100, 150, 200, 250)

diffLogoTableObj = prepareDiffLogoTable(motifs);
```

probabilities	<i>probabilities</i>
---------------	----------------------

Description

the given probabilities

Usage

```
probabilities(p)
```

Arguments

p probability vector representing the symbol distribution

Value

the given vector

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_name = "HepG2"
fileName = paste(motif_folder, "/", motif_name, ".pwm", sep="")
file = system.file(fileName, package = "DiffLogo")
motif = getPwmFromPwmFile(file)
seqLogo(pwm = motif, baseDistribution = probabilities)
```

pwmDivergence	<i>PWM divergence</i>
---------------	-----------------------

Description

Counts PWM divergence as sum of divergencies of their columns.

Usage

```
pwmDivergence(pwm_left, pwm_right, divergence = shannonDivergence)
```

Arguments

pwm_left	is a PWM representation in type of matrix
pwm_right	is a PWM representation in type of matrix. The result is symmetric on pwm_left and pwm_right
divergence	is a Divergence function on columns.

Value

float - sum of divergences

pwmsDistanceMatrix	<i>Multiple PWMs alignment</i>
--------------------	--------------------------------

Description

Creates a distance matrix for pwms

Usage

```
pwmsDistanceMatrix(pwms, diagonal_value = 0,
  bottom_default_value = NULL, divergence = shannonDivergence,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, base_distribution = NULL,
  length_normalization = FALSE)
```

Arguments

pwms	list of pwms
diagonal_value	value to put on diagonal.
bottom_default_value	value to put on bottom triangle. Set to NULL to get symmetric distance matrix.
divergence	divergence measure.
unaligned_penalty	is a function for localPwmAlignment.
try_reverse_complement	if True, alignment will try reverse complement pwms
base_distribution	is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used
length_normalization	is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used

Value

list

Author(s)

Lando Andrey

`reverseAlignmentVector`*Reverse for alignment vector*

Description

Returns alignment vector as if all pwm were reverted.

Usage

```
reverseAlignmentVector(alignment_vector, pwms)
```

Arguments

`alignment_vector`

list of list which \$shift and \$orientation

`pwms`

list of matrixes.

Value

list - reversed alignment vector

Author(s)

Lando Andrey

`RNA`*RNA alphabet*

Description

the RNA alphabet, i.e. A, C, G, U

Usage

```
RNA
```

Format

An object of class Alphabet of length 4.

Author(s)

Martin Nettling

Examples

```
RNA
```

`seqLogo`*Draw sequence logo*

Description

Draws the classic sequence logo.

Usage

```
seqLogo(pwm, sparse = FALSE, drawLines = 0.5,  
        stackHeight = informationContent, baseDistribution = probabilities,  
        alphabet = DNA, main = NULL)
```

Arguments

<code>pwm</code>	representation of a position weight matrix (PWM) of type <code>pwm</code> , <code>data.frame</code> , or <code>matrix</code>
<code>sparse</code>	if <code>TRUE</code> margins are reduced and tickmarks are removed from the logo
<code>drawLines</code>	distance between background lines
<code>stackHeight</code>	function for the height of a stack at position <code>i</code>
<code>baseDistribution</code>	function for the heights of the individual bases
<code>alphabet</code>	of type <code>Alphabet</code>
<code>main</code>	the main title for the plot

Value

`none` (draws sequence logo)

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"  
motif_name = "HepG2"  
fileName = paste(motif_folder, "/", motif_name, ".pwm", sep="")  
file = system.file(fileName, package = "DiffLogo")  
motif = getPwmFromPwmFile(file)  
seqLogo(pwm = motif)
```

shannonDivergence	<i>shannon divergence</i>
-------------------	---------------------------

Description

the shannon divergence for the given pair of probability vectors

Usage

```
shannonDivergence(p1, p2)
```

Arguments

p1	probability vector representing the first symbol distribution
p2	probability vector representing the second symbol distribution

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, stackHeight = shannonDivergence)
```

sumOfAbsICDifferences	<i>sum of absolute information content differences</i>
-----------------------	--

Description

the sum of absolute information content differences for the given pair of probability vectors

Usage

```
sumOfAbsICDifferences(p1, p2)
```

Arguments

p1 probability vector representing the first symbol distribution
 p2 probability vector representing the second symbol distribution

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, stackHeight = sumOfAbsICDifferences)
```

sumOfAbsProbabilityDifferences

sum of absolute probability differences

Description

the sum of absolute probability differences for the given pair of probability vectors

Usage

sumOfAbsProbabilityDifferences(p1, p2)

Arguments

p1 probability vector representing the first symbol distribution
 p2 probability vector representing the second symbol distribution

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, stackHeight = sumOfAbsProbabilityDifferences)

```

sumProbabilities	<i>sum of probabilities, i.e. 1.0</i>
------------------	---------------------------------------

Description

the sum of probabilities for the given probability vector, i.e. 1.0

Usage

```
sumProbabilities(p)
```

Arguments

p probability vector representing the symbol distribution

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_name = "HepG2"
fileName = paste(motif_folder,"/",motif_name,".pwm",sep="")
file = system.file(fileName, package = "DiffLogo")
motif = getPwmFromPwmFile(file)
seqLogo(pwm = motif, stackHeight = sumProbabilities)

```

switchDirection	<i>Switches between 'forward' and 'reverse'</i>
-----------------	---

Description

Switches between 'forward' and 'reverse'

Usage

```
switchDirection(direction)
```

Arguments

direction	either 'forward' or 'reverse'
-----------	-------------------------------

Value

either 'reverse' or 'forward'

twoSetsAveragePwmDivergenceFromAlignmentVector	<i>Average divergence between two sets.</i>
--	---

Description

Computes average pwm divergence from alignment vector for two datasets. This equals to average divergence between all pairs where one pwm comes from left set, and other comes from right

Usage

```
twoSetsAveragePwmDivergenceFromAlignmentVector(left_pwm_list,
  left_pwm_alignment, right_pwm_list, right_pwm_alignment,
  divergence = shannonDivergence)
```

Arguments

left_pwm_list	is a list of matrixes
left_pwm_alignment	
	is a list of shifts (\$shift) and orientations (\$direction)
right_pwm_list	
	is a list of matrixes
right_pwm_alignment	
	is a list of shifts (\$shift) and orientations (\$direction)
divergence	divergence measure.

Value

float

Author(s)

Lando Andrey

Index

* datasets

- ASN, [4](#)
- DNA, [13](#)
- FULL_ALPHABET, [17](#)
- RNA, [31](#)

alignPwmSets, [3](#)

Alphabet, [3](#)

ASN, [4](#)

baseDistributionPwm, [4](#)

calculatePvalue, [5](#)

createDiffLogoObject, [6](#)

differenceOfICs, [7](#)

diffLogo, [8](#)

diffLogoFromPwm, [9](#)

diffLogoTable, [10](#)

diffLogoTableConfiguration, [11](#)

DNA, [13](#)

drawDiffLogoTable, [13](#)

enrichDiffLogoObjectWithPvalues, [14](#)

enrichDiffLogoTableWithPvalues, [15](#)

extendPwmsFromAlignmentVector, [16](#)

FULL_ALPHABET, [17](#)

getAlphabetFromCharacters, [17](#)

getAlphabetFromSequences, [18](#)

getPwmFromAlignment, [18](#)

getPwmFromAlignmentFile, [19](#)

getPwmFromFastaFile, [19](#)

getPwmFromFile, [20](#)

getPwmFromHomerFile, [20](#)

getPwmFromPfmOrJasparFile, [21](#)

getPwmFromPwmFile, [21](#)

getSequencesFromAlignmentFile, [22](#)

getSequencesFromFastaFile, [22](#)

informationContent, [23](#)

localPwmAlignment, [24](#)

lossOfAbsICDifferences, [25](#)

multipleLocalPwmsAlignment, [25](#)

normalizedDifferenceOfProbabilities,

[26](#)

normalizePWM, [27](#)

prepareDiffLogoTable, [28](#)

probabilities, [29](#)

pwmDivergence, [29](#)

pwmsDistanceMatrix, [30](#)

reverseAlignmentVector, [31](#)

RNA, [31](#)

seqLogo, [32](#)

shannonDivergence, [33](#)

sumOfAbsICDifferences, [33](#)

sumOfAbsProbabilityDifferences, [34](#)

sumProbabilities, [35](#)

switchDirection, [36](#)

twoSetsAveragePwmDivergenceFromAlignmentVector,

[36](#)