

Package ‘GEOfastq’

May 20, 2024

Type Package

Title Downloads ENA Fastqs With GEO Accessions

Version 1.13.0

Description GEOfastq is used to download fastq files from the European Nucleotide Archive (ENA) starting with an accession from the Gene Expression Omnibus (GEO). To do this, sample metadata is retrieved from GEO and the Sequence Read Archive (SRA). SRA run accessions are then used to construct FTP and aspera download links for fastq files generated by the ENA.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

BugReports <https://github.com/alexvpickering/GEOfastq/issues>

Imports xml2, rvest, stringr, RCurl, doParallel, foreach, plyr

Suggests BiocCheck, roxygen2, knitr, rmarkdown, testthat

biocViews RNASeq, DataImport

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/GEOfastq>

git_branch devel

git_last_commit 2d075d0

git_last_commit_date 2024-04-30

Repository Bioconductor 3.20

Date/Publication 2024-05-20

Author Alex Pickering [cre, aut] (<<https://orcid.org/0000-0002-0002-6759>>)

Maintainer Alex Pickering <alexvpickering@gmail.com>

Contents

| | |
|--------------------------|----------|
| ascpR | 2 |
| crawl_gse | 2 |
| crawl_gsms | 3 |
| extract_gsms | 4 |
| get_dldir | 4 |
| get_ebi_fastqs | 5 |
| get_fastqs | 5 |
| Index | 7 |

| | |
|-------|---------------------------------------|
| ascpR | <i>Utility function to run aspera</i> |
|-------|---------------------------------------|

Description

Utility function to run aspera

Usage

```
ascpR(ascp_args, file, destDir = getwd())
```

Arguments

| | |
|-----------|---|
| ascp_args | Character vector of arguments to ascp. |
| file | Url to aspera file to download. |
| destDir | Path to directory to download files into. |

Value

return code from call to ascp

| | |
|-----------|------------------------------|
| crawl_gse | <i>Get GSE text from GEO</i> |
|-----------|------------------------------|

Description

Get GSE text from GEO

Usage

```
crawl_gse(gse_name)
```

Arguments

| | |
|----------|------------------------------------|
| gse_name | GEO study name to get metadata for |
|----------|------------------------------------|

Value

Character vector of lines on GSE record.

Examples

```
gse_text <- crawl_gse('GSE111459')
```

| | |
|------------|---|
| crawl_gsms | <i>Crawls SRX pages for each GSM to get metadata.</i> |
|------------|---|

Description

Goes to each GSM page to get SRX then to each SRX page to get some more metadata.

Usage

```
crawl_gsms(gsm_names, max.workers = 50)
```

Arguments

| | |
|-------------|--|
| gsm_names | Character vector of GSMs. |
| max.workers | Maximum number of parallel workers to split task between |

Value

data.frame

Examples

```
srp_meta <- crawl_gsms("GSM3031462")

# returns NULL because records on dbGAP for privacy reasons
srp_meta <- crawl_gsms("GSM2439650")

# example with empty values
srp_meta <- crawl_gsms('GSM4043025')
```

| | |
|--------------|--|
| extract_gsms | <i>Extract GSMS needed to download RNA-seq data for a series</i> |
|--------------|--|

Description

Extract GSMS needed to download RNA-seq data for a series

Usage

```
extract_gsms(gse_text)
```

Arguments

gse_text GSE text returned from [crawl_gse](#)

Value

Character vector of sample GSMS for the series gse_name

Examples

```
gse_text <- crawl_gse('GSE111459')
gsm_names <- extract_gsms(gse_text)
```

| | |
|-----------|--|
| get_dldir | <i>Gets part of path to download bulk RNAseq sample from EBI or NCBI</i> |
|-----------|--|

Description

Gets part of path to download bulk RNAseq sample from EBI or NCBI

Usage

```
get_dldir(srr, type = c("ebi", "ncbi"))
```

Arguments

srr SRR/ERR run name
type Either 'ebi' or 'ncbi'

Value

String path used by [get_fastqs](#).

Examples

```
get_dldir('SRR014242')
```

| | |
|----------------|---------------------------------|
| get_ebi_fastqs | <i>Download fastqs from EBI</i> |
|----------------|---------------------------------|

Description

Much faster to use aspera than ftp

Usage

```
get_ebi_fastqs(
  srp_meta,
  srr_name,
  data_dir,
  method = c("ftp", "aspera"),
  max_rate = "300m"
)
```

Arguments

| | |
|----------|---|
| srp_meta | data.frame with SRP meta info. Returned from crawl_gsms . |
| srr_name | Run accession as string. |
| data_dir | Path to folder that fastq files will be downloaded to. Will be created if doesn't exist. |
| method | One of 'aspera' or 'ftp'. 'aspera' is generally faster but requires the ascp command line utility to be on your path and in the authors experience frequently stalls. |
| max_rate | Used when method = 'aspera' only. Sets the target transfer rate. The default is '300m'. |

Value

Integer return code from ascp or download.file.

| | |
|------------|---|
| get_fastqs | <i>Download and RNA-seq fastq data from EBI</i> |
|------------|---|

Description

First tries to get RNA-Seq fastq files from EBI.

Usage

```
get_fastqs(srp_meta, data_dir, method = c("ftp", "aspera"), max_rate = "1g")
```

Arguments

| | |
|-----------------------|---|
| <code>srp_meta</code> | data.frame with SRP meta info. Returned from crawl_gsms . |
| <code>data_dir</code> | Path to folder that fastq files will be downloaded to. Will be created if doesn't exist. |
| <code>method</code> | One of 'aspera' or 'ftp'. 'aspera' is generally faster but requires the ascp command line utility to be on your path and in the authors experience frequently stalls. |
| <code>max_rate</code> | Used when method = 'aspera' only. Sets the target transfer rate. The default is '300m'. |

Value

Named vector of integer return codes from ascp or `download.file`. Names are SRR runs.

Examples

```
gsm_name <- 'GSM3926903'  
srp_meta <- crawl_gsms(gsm_name)  
data_dir <- tempdir()  
res <- get_fastqs(srp_meta, data_dir)
```

Index

* **internal**

ascpR, 2

get_ebi_fastqs, 5

ascpR, 2

crawl_gse, 2, 4

crawl_gsms, 3, 5, 6

extract_gsms, 4

get_dldir, 4

get_ebi_fastqs, 5

get_fastqs, 4, 5