Package 'ORFik'

September 20, 2024

Type Package

Title Open Reading Frames in Genomics

Version 1.25.4

Encoding UTF-8

Description

R package for analysis of transcript and translation features through manipulation of sequence data and NGS data like Ribo-Seq, RNA-Seq, TCP-Seq and CAGE. It is generalized in the sense that any transcript region can be analysed, as the name hints to it was made with investigation of ribosomal patterns over Open Reading Frames (ORFs) as it's primary use case. ORFik is extremely fast through use of C++, data.table and GenomicRanges. Package allows to reassign starts of the transcripts with the use of CAGE-Seq data, automatic shifting of RiboSeq reads, finding of Open Reading Frames for whole genomes and much more.

biocViews ImmunoOncology, Software, Sequencing, RiboSeq, RNASeq, FunctionalGenomics, Coverage, Alignment, DataImport

License MIT + file LICENSE

LazyData TRUE

BugReports https://github.com/Roleren/ORFik/issues

URL https://github.com/Roleren/ORFik

- **Depends** R (>= 4.1.0), IRanges (>= 2.17.1), GenomicRanges (>= 1.35.1), GenomicAlignments (>= 1.19.0)
- Imports AnnotationDbi (>= 1.45.0), Biostrings (>= 2.51.1), biomaRt, biomartr (>= 1.0.7), BiocFileCache, BiocGenerics (>= 0.29.1), BiocParallel (>= 1.19.0), BSgenome, cowplot (>= 1.0.0), data.table (>= 1.11.8), DESeq2 (>= 1.24.0), fst (>= 0.9.2), GenomeInfoDb (>= 1.15.5), GenomicFeatures (>= 1.31.10), ggplot2 (>= 2.2.1), gridExtra (>= 2.3), httr (>= 1.30), jsonlite, methods (>= 3.6.0), R.utils, Rcpp (>= 1.0.0), Rsamtools (>= 1.35.0), rtracklayer (>= 1.43.0), stats, SummarizedExperiment (>= 1.14.0), S4Vectors (>= 0.21.3), tools, txdbmaker, utils, XML, xml2 (>= 1.2.0), withr

RoxygenNote 7.3.1

Suggests testthat, rmarkdown, knitr, BiocStyle, BSgenome.Hsapiens.UCSC.hg19

Contents

LinkingTo Rcpp

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/ORFik

git_branch devel

git_last_commit a2c5168

git_last_commit_date 2024-09-03

Repository Bioconductor 3.20

Date/Publication 2024-09-19

Author Haakon Tjeldnes [aut, cre, dtc], Kornel Labun [aut, cph], Michal Swirski [ctb], Katarzyna Chyzynska [ctb, dtc], Yamila Torres Cleuren [ctb, ths], Eivind Valen [ths, fnd]

Maintainer Haakon Tjeldnes <hauken_heyken@hotmail.com>

Contents

ORFik-package
addCdsOnLeaderEnds 10
addNewTSSOnLeaders
alignmentFeatureStatistics
allFeaturesHelper
appendZeroes
artificial.orfs
assignAnnotations
assignFirstExonsStartSite
assignLastExonsStopSite
assignTSSByCage
asTX
bamVarName
bamVarNamePicker
batchNames
bedToGR
browseSRA
cellLineNames
cellTypeNames
changePointAnalysis
checkRFP
checkRNA
codonSumsPerGroup
codon_usage
codon_usage_exp
codon_usage_plot
collapse.by.scores
collapse.fastq
collapseDuplicatedReads
collapseDuplicatedReads,data.table-method
collapseDuplicatedReads,GAlignmentPairs-method

collapseDuplicatedReads,GAlignments-method	6
comapseDuplicatedReads, GRanges-method	0
	0
	.9 11
computereaturesCage	1
conditionNames	:3 4
config	4
config.exper	ۍ ا
config.save	.5
config_file	-6
convertLibs	-7
convertToOneBasedRanges	.9
convert_bam_to_ofst	1
convert_to_bigWig	2
convert_to_covRle	3
convert_to_covRleList	4
convert_to_fstWig	5
correlation.plots	6
cor_plot	7
cor_table	8
countOverlapsW	9
countTable	0
countTable_regions	51
coverageByTranscriptC	53
coverageByTranscriptW	53
coverageGroupings	j 4
coverageHeatMap	j 4
coveragePerTiling	6
coverageScorings	8
coverage to dt	0
covRle	1
covRle-class	1
covRleFromGR	2
covRleList 7	13
covRleList-class 7	13
create.experiment	4
defineIsoform 7	7
defineTrailer 7	8
DEG analysis 7	9
DEG nlot static	0
DEG model 8	22
DEG_model_results 8	3
DEG_model_testins	24
design experiment method	25
detactPibecomeShifte	15
detect ribe orfe	
diagramment Source 0	19
distraCda	'Z
uisilous	'5 M
(1)(1)(1)(5)(5)(5)(5)(5)(5)(5)(5)(5)(5)(5)(5)(5)	'4 \5
aownioaa.edi	C
download.SKA	6
download.SKA.metadata	18

downstreamFromPerGroup	. 99
downstreamN	. 100
downstreamOfPerGroup	. 101
DTEG.analysis	. 101
DTEG.plot	. 104
entropy	. 106
envExp	. 107
envExp,experiment-method	. 107
envExp<	. 108
envExp <experiment-method< td=""><td>. 108</td></experiment-method<>	. 108
exists.ftp.dir.fast	. 109
exists.ftp.file.fast	. 109
experiment-class	. 110
experiment.colors	. 112
export.bed12	. 113
export.bedo	. 114
export bedoc	. 114
export bigWig	115
export fstwig	116
export ofst	117
export of st GA lignment Pairs_method	118
export of st GAlignments method	110
export of st CD angas method	120
export.vis.,OKanges-method	120
export.wiggle	121
extendeTS covers	122
	123
	. 124
extract_run_id	. 125
I	. 125
f,covRle-method	. 126
	. 126
filterCage	. 128
filterExtremePeakGenes	. 129
filterTranscripts	. 130
filterUORFs	. 131
fimport	. 132
findFa	. 133
findFromPath	. 134
findLibrariesInFolder	. 134
findMapORFs	. 135
findMaxPeaks	. 137
findNewTSS	. 137
findNGSPairs	. 138
findORFs	. 138
findORFsFasta	. 140
findPeaksPerGene	. 141
findUORFs	. 143
findUORFs_exp	. 145
find_url_ebi	. 147
find_url_ebi_safe	. 148
firstEndPerGroup	. 148
firstExonPerGroup	. 149
1	-

firstStartPerGroup
fix_malformed_gff
flankPerGroup
floss
footprints.analysis
fpkm
fpkm_calc
fractionLength
fractionNames
fread.bed
gcContent
geneToSymbol
getGAlignments
getGAlignmentsPairs
getGenomeAndAnnotation
getGRanges
getGtfPathFromTxdb
getNGenesCoverage
getWeights
get_bioproject_candidates
get_genome_fasta
get_genome_gtf
get_noncoding_rna
get_phix_genome
get_silva_rRNA
groupGRangesBy
groupings
gSort
hasHits
heatMapL
heatMapRegion
heatMap_single
import.bedo
import.bedoc
import.fstwig
import.ofst
importGtfFromTxdb
inhibitorNames
initiationScore
insideOutsideORF
install.fastp
install.sratoolkit
is.grl
is.gr_or_grl
is.ORF
is.range
isInFrame
isOverlapping
isPeriodic
kozakHeatmap
kozakSequenceScore
kozak_IR_ranking

lastExonEndPerGroup	202
lastExonPerGroup	203
lastExonStartPerGroup	203
length,covRle-method	204
length,covRleList-method	204
lengths,covRle-method	205
lengths,covRleList-method	205
libFolder	206
libFolder, experiment-method	206
libNames	207
libraryTypes	207
list.experiments	208
list.genomes	209
loadRegion	210
loadRegions	211
loadTranscriptType	212
loadTxdb	213
longestORFs	213
mainNames	214
makeExonRanks	215
makeORFNames	215
makeSummarizedExperimentFromBam	216
makeTxdbFromGenome	218
manToGRanges	219
matchColors	220
matchNaming	220
matchSeqStyle	220
matchSeqStyle	221
mergel ibs	221
	222
metauata.aumanning	223
metawindow	224
	223
name	226
name, experiment-method	227
nrow, experiment-method	227
numCodons	228
numExonsPerGroup	228
ofst_merge	229
optimizedTranscriptLengths	229
optimized_txdb_path	230
optimizeReads	231
orfFrameDistributions	231
orfID	232
ORFik.template.experiment	233
ORFik.template.experiment.zf	233
ORFikQC	234
orfScore	236
organism, experiment-method	238
outputLibs	239
pasteDir	241
pcaExperiment	242
percentage_to_ratio	243

plotHelper	. 243
pmapFromTranscriptF	. 244
pmapToTranscriptF	245
pretty Scoring	246
preudo transform	240
	. 247
	. 247
Quiolder	. 249
QCfolder, experiment-method	. 249
QCplots	. 250
QCreport	. 251
QCstats	. 253
QCstats.plot	. 253
QC_count_tables	. 254
r	. 255
r.covRle-method	. 256
rankOrder	256
read experiment	257
readBam	258
	250
	. 239
	. 260
readWidths	. 261
readWig	. 262
reassignTSSbyCage	. 263
reassignTxDbByCage	. 264
reduceKeepAttr	. 266
regionPerReadLength	. 267
remakeTxdbExonIds	. 269
remove.experiments	. 269
remove.file ext	. 270
removeMetaCols	. 270
removeORFsWithinCDS	271
removeOREsWithSameStartAsCDS	271
removeOREsWithSameStonAsCDS	271
removeORFsWithStartIngideCDS	. 272
	. 212
	. 213
	. 273
rename.SRA.files	. 274
repNames	. 274
resFolder	. 275
resFolder,experiment-method	. 275
restrictTSSByUpstreamLeader	. 276
revElementsF	. 276
reverseMinusStrandPerGroup	. 277
riboORFs	. 277
riboORFsFolder	. 278
RiboOC nlot	278
ribosomeReleaseScore	270
ribosomeStallingScore	· 219
ribo fft	· 201
1100_111	. 202
	. 282
rnaNormalize	. 283
runIDs	. 284

runDs experiment-method	284
	207
save.experiment	. 205
	. 205
	. 280
	. 287
sequifo,covRle-method	. 288
seqinfo,covRleList-method	. 289
seqinfo, experiment-method	. 289
seqlevels,covRle-method	. 290
seqlevels, covRleList-method	. 290
seqlevels, experiment-method	. 291
seqnamesPerGroup	. 291
shiftFootprints	. 292
shiftFootprintsByExperiment	. 293
shiftPlots	. 296
shifts load	297
shifts load	298
shifts cave	200
show could method	200
	. 500
show,covKleList-method	. 300
show, experiment-method	. 301
simpleLibs	. 301
sortPerGroup	. 303
splitIn3Tx	. 304
stageNames	. 305
STAR.align.folder	. 306
STAR.align.single	. 310
STAR.allsteps.multiQC	. 314
STAR.index	. 315
STAR install	. 317
STAR multiOC	318
STAR remove crashed genome	318
startCodone	310
startDefinition	220
	. 520
	. 320
startRegionCoverage	. 321
startRegionString	. 323
startSites	. 323
stopCodons	. 324
stopDefinition	. 325
stopRegion	. 326
stopSites	. 327
strandBool	. 327
strandMode,covRle-method	. 328
strandMode.covRleList-method	. 328
strandPerGroup	. 329
subsetCoverage	329
subsetToFrame	330
symbols	331
symbols experiment_method	221
symools, caperinient-memou	
	. 552
te.table	. 333

Index

ORFik-package

ORFik for analysis of open reading frames.

Description

Main goals:

- 1. Finding Open Reading Frames (very fast) in the genome of interest or on the set of transcripts/sequences.
- 2. Utilities for metaplots of RiboSeq coverage over gene START and STOP codons allowing to spot the shift.
- 3. Shifting functions for the RiboSeq data.
- 4. Finding new Transcription Start Sites with the use of CageSeq data.
- 5. Various measurements of gene identity e.g. FLOSS, coverage, ORFscore, entropy that are recreated based on many scientific publications.
- 6. Utility functions to extend GenomicRanges for faster grouping, splitting, tiling etc.

Author(s)

Maintainer: Haakon Tjeldnes <hauken_heyken@hotmail.com> [data contributor] Authors:

• Kornel Labun <kornellabun@gmail.com> [copyright holder]

Other contributors:

- Michal Swirski <michal.swirski@uw.edu.pl>[contributor]
- Katarzyna Chyzynska <katchyz@gmail.com> [contributor, data contributor]
- Yamila Torres Cleuren <yamilatorrescleuren@gmail.com> [contributor, thesis advisor]
- Eivind Valen <eivind.valen@gmail.com> [thesis advisor, funder]

See Also

Useful links:

- https://github.com/Roleren/ORFik
- Report bugs at https://github.com/Roleren/ORFik/issues

addCdsOnLeaderEnds Extends leaders downstream

Description

When finding uORFs, often you want to allow them to end inside the cds.

Usage

```
addCdsOnLeaderEnds(fiveUTRs, cds, onlyFirstExon = FALSE)
```

Arguments

fiveUTRs	The 5' leader sequences as GRangesList
cds	If you want to extend 5' leaders downstream, to catch uorfs going into cds, include it.
onlyFirstExon	logical (F), include whole cds or only first exons.

Details

This is a simple way to do that

Value

a GRangesList of cds exons added to ends

See Also

Other uorfs: filterUORFs(), removeORFsWithSameStartAsCDS(), removeORFsWithSameStopAsCDS(), removeORFsWithStartInsideCDS(), removeORFsWithinCDS(), uORFSearchSpace()

addNewTSSOnLeaders Add cage max peaks as new transcript start sites for each 5' leader (*) strands are not supported, since direction must be known.

Description

Add cage max peaks as new transcript start sites for each 5' leader (*) strands are not supported, since direction must be known.

Usage

```
addNewTSSOnLeaders(fiveUTRs, maxPeakPosition, removeUnused, cageMcol)
```

Arguments

fiveUTRs	(GRangesList) The 5' leaders or full transcript sequences
maxPeakPosition	
	The max peak for each 5' leader found by cage
removeUnused	logical (FALSE), if False: (standard is to set them to original annotation), If TRUE: remove leaders that did not have any cage support.
cageMcol	a logical (FALSE), if TRUE, add a meta column to the returned object with the raw CAGE counts in support for new TSS.

Value

a GRanges object of first exons

alignmentFeatureStatistics

Create alignment feature statistcs

Description

Among others how much reads are in mRNA, introns, intergenic, and check of reads from rRNA and other ncRNAs. The better the annotation / gtf used, the more results you get.

```
alignmentFeatureStatistics(
  df,
  type = "ofst",
  force = TRUE,
  library.names = bamVarName(df),
  BPPARAM = bpparam()
)
```

Arguments

df	an ORFik experiment
type	a character(default: "default"), load files in experiment or some precomputed variant, like "ofst" or "pshifted". These are made with ORFik:::convertLibs(), shiftFootprintsByExperiment(), etc. Can also be custom user made folders inside the experiments bam folder. It acts in a recursive manner with priority: If you state "pshifted", but it does not exist, it checks "ofst". If no .ofst files, it uses "default", which always must exists. Presets are (folder is relative to default lib folder, some types fall back to other formats if folder does not exist):
	 "default": load the original files for experiment, usually bam. "ofst": loads ofst files from the ofst folder, relative to lib folder (falls back to
	default)- "pshifted": loads ofst, wig or bigwig from pshifted folder (falls back to ofst, then default)
	 "cov": Load covRle objects from cov_RLE folder (fail if not found) "covl": Load covRleList objects, from cov_RLE_List folder (fail if not found) "bed": Load bed files, from bed folder (falls back to default) Other formats must be loaded directly with fimport
force	logical, default TRUE If TRUE, reload library files even if matching named variables are found in environment used by experiment (see envExp) A simple way to make sure correct libraries are always loaded. FALSE is faster if data is loaded correctly already.
library.names	character vector, names of libraries, default: name_decider(df, naming)
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.

Value

a data.table of the statistcs

allFeaturesHelper Calculate the features in computeFeatures function

Description

Not used directly, calculates all features internally for computeFeatures.

```
allFeaturesHelper(
grl,
RFP,
RNA,
tx,
fiveUTRs,
cds,
threeUTRs,
```

allFeaturesHelper

```
faFile,
riboStart,
riboStop,
sequenceFeatures,
uorfFeatures,
grl.is.sorted,
weight.RFP = 1L,
weight.RNA = 1L,
st = NULL
)
```

Arguments

grl	a GRangesList object with usually ORFs, but can also be either leaders, cds', 3' utrs, etc. This is the regions you want to score.
RFP	RiboSeq reads as GAlignments, GRanges or GRangesList object
RNA	RnaSeq reads as GAlignments, GRanges or GRangesList object
tx	a GRangesList of transcripts, normally called from: exonsBy(Gtf, by = "tx", use.names = T) only add this if you are not including Gtf file If you are using CAGE, you do not need to reassign these to the cage peaks, it will do it for you.
fiveUTRs	fiveUTRs as GRangesList, if you used cage-data to extend 5' utrs, remember to input CAGE assigned version and not original!
cds	a GRangesList of coding sequences
threeUTRs	a GRangesList of transcript 3' utrs, normally called from: threeUTRsByTran- script(Gtf, use.names = T)
faFile	a path to fasta indexed genome, an open FaFile, a BSgenome, or path to ORFik experiment with valid genome.
riboStart	usually 26, the start of the floss interval, see ?floss
riboStop	usually 34, the end of the floss interval
sequenceFeature	2S
	a logical, default TRUE, include all sequence features, that is: Kozak, fraction- Lengths, distORFCDS, isInFrame, isOverlapping and rankInTx. uorfFeatures = FALSE will remove the 4 last.
uorfFeatures	a logical, default TRUE, include all uORF sequence features, that is: distOR-FCDS, isInFrame, isOverlapping and rankInTx
grl.is.sorted	logical (F), a speed up if you know argument grl is sorted, set this to TRUE.
weight.RFP	a vector (default: 1L). Can also be character name of column in RFP. As in translationalEff(weight = "score") for: GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times.
weight.RNA	Same as weightRFP but for RNA weights. (default: 1L)
st	(NULL), if defined must be: st = startRegion(grl, tx, T, -3, 9)

Value

a data.table with features

```
appendZeroes
```

Description

For every position in width max.pos - min.pos + 1, append 0 values in data.table. Needed when coveragePerTiling was run on coverage window with drop.zero.dt as TRUE and you need to plot 0 positions after a transformation by coverageScorings.

Usage

```
appendZeroes(dt, max.pos, min.pos = 1L, fractions = unique(dt$fraction))
```

Arguments

dt	a data.table from coverageByTiling that is normalized by coverageScorings.
max.pos	integer, max position of dt
min.pos	integer, default 1L. Minimum position of dt
fractions	default unique(dt\$fraction), will repeat each fraction max.pos - min.pos + 1 times.

Value

a data.table with appended 0 values

artificial.orfs Create small artificial orfs from cds

Description

Usefull to see if short ORFs prediction is dependent on length. Split cds first in two, a start part and stop part. Then say how large the two parts can be and merge them together. It will sample a value in range give. Parts will be forced to not overlap and can not extend outside original cds

```
artificial.orfs(
   cds,
   start5 = 1,
   end5 = 4,
   start3 = -4,
   end3 = 0,
   bin.if.few = TRUE
)
```

Arguments

cds	a GRangesList of orfs, must have width $\%\%$ 3 == 0 and length >= 6
start5	integer, default: 1 (start of orf)
end5	integer, default: 4 (max 4 codons from start codon)
start3	integer, default -4 (max 4 codons from stop codon)
end3	integer, default: 0 (end of orf)
bin.if.few	logical, default TRUE, instead of per codon, do per 2, 3, 4 codons if you have few samples compared to lengths wanted, If you have 4 cds' and you want 7 different lengths, which is the standard, it will give you possible nt length: $6-12-18-24$ instead of original $6-9-12-15-18-21-24$. If you have more than 30x cds than lengths wanted this is skipped. (for default arguments this is: $7*30 = 210$ cds)

Details

If artificial cds length is not divisible by 2, like 3 codons, the second codon will always be from the start region etc.

Also If there are many very short original cds, the distribution will be skewed towards more smaller artificial cds.

Value

GRangesList of new ORFs (sorted: + strand increasing start, - strand decreasing start)

Examples

```
txdb <- ORFik.template.experiment()
#cds <- loadRegion(txdb, "cds")
## To get enough CDSs, just replicate them
# cds <- rep(cds, 100)
#artificial.orfs(cds)</pre>
```

assignAnnotations Overlaps GRanges object with provided annotations.

Description

It will return same list of GRanges, but with metdata columns: trainscript_id - id of transcripts that overlap with each ORF gene_id - id of gene that this transcript belongs to isoform - for coding protein alignment in relation to cds on coresponding transcript, for non-coding transcripts alignment in relation to the transcript.

Usage

assignAnnotations(ORFs, con)

Arguments

ORFs	- GRanges or GRangesList object of your ORFs.
con	- Path to gtf file with annotations.

Value

A GRanges object of your ORFs with metadata columns 'gene', 'transcript', isoform' and 'biotype'.

assignFirstExonsStartSite

Reassign the start positions of the first exons per group in grl

Description

Per group in GRangesList, assign the most upstream site.

Usage

```
assignFirstExonsStartSite(
  grl,
  newStarts,
  is.circular = all(isCircular(grl) %in% TRUE)
)
```

Arguments

grl	a GRangesList object
newStarts	an integer vector of same length as grl, with new start values (absolute coordinates, not relative)
is.circular	logical, default FALSE if not any is: all(isCircular(grl) Where grl is the ranges checked. If TRUE, allow ranges to extend below position 1 on chromosome. Since circular genomes can have negative coordinates.

Details

make sure your grl is sorted, since start of "-" strand objects should be the max end in group, use ORFik:::sortPerGroup(grl) to get sorted grl.

Value

the same GRangesList with new start sites

See Also

Other GRanges: assignLastExonsStopSite(), downstreamFromPerGroup(), downstreamOfPerGroup(), upstreamFromPerGroup(), upstreamOfPerGroup() assignLastExonsStopSite

Reassign the stop positions of the last exons per group

Description

Per group in GRangesList, assign the most downstream site.

Usage

```
assignLastExonsStopSite(
  grl,
  newStops,
  is.circular = all(isCircular(grl) %in% TRUE)
)
```

Arguments

grl	a GRangesList object
newStops	an integer vector of same length as grl, with new start values (absolute coordinates, not relative)
is.circular	logical, default FALSE if not any is: all(isCircular(grl) Where grl is the ranges checked. If TRUE, allow ranges to extend below position 1 on chromosome. Since circular genomes can have negative coordinates.

Details

make sure your grl is sorted, since stop of "-" strand objects should be the min start in group, use ORFik:::sortPerGroup(grl) to get sorted grl.

Value

the same GRangesList with new stop sites

See Also

```
Other GRanges: assignFirstExonsStartSite(), downstreamFromPerGroup(), downstreamOfPerGroup(),
upstreamFromPerGroup(), upstreamOfPerGroup()
```

assignTSSByCage	Input a txdb and add a 5' leader for each transcript, that does not have
	one.

Description

For all cds in txdb, that does not have a 5' leader: Start at 1 base upstream of cds and use CAGE, to assign leader start. All these leaders will be 1 exon based, if you really want exon splicings, you can use exon prediction tools, or run sequencing experiments.

Usage

```
assignTSSByCage(
  txdb,
  cage,
  extension = 1000,
  filterValue = 1,
  restrictUpstreamToTx = FALSE,
  removeUnused = FALSE,
  preCleanup = TRUE,
  pseudoLength = 1
)
```

Arguments

txdb	a TxDb file, a path to one of: (.gtf ,.gff, .gff2, .gff2, .db or .sqlite) or an ORFik experiment
cage	Either a filePath for the CageSeq file as .bed .bam or .wig, with possible com- pressions (".gzip", ".gz", ".bgz"), or already loaded CageSeq peak data as GRanges or GAlignment. NOTE: If it is a .bam file, it will add a score column by run- ning: convertToOneBasedRanges(cage, method = "5prime", addScoreColumn = TRUE) The score column is then number of replicates of read, if score column is something else, like read length, set the score column to NULL first.
extension	The maximum number of basses upstream of the TSS to search for CageSeq peak.
filterValue	The minimum number of reads on cage position, for it to be counted as possible new tss. (represented in score column in CageSeq data) If you already filtered, set it to 0.
restrictUpstrea	mToTx
	a logical (FALSE). If TRUE: restrict leaders to not extend closer than 5 bases from closest upstream leader, set this to TRUE.
removeUnused	logical (FALSE), if False: (standard is to set them to original annotation), If TRUE: remove leaders that did not have any cage support.
preCleanup	logical (TRUE), if TRUE, remove all reads in region (-5:-1, 1:5) of all original tss in leaders. This is to keep original TSS if it is only +/- 5 bases from the original.
pseudoLength	a numeric, default 1. Either if no CAGE supports the leader, or if CAGE is set to NULL, add a pseudo length for all the UTRs. Will not extend a leader if it would make it go outside the defined seqlengths of the genome. So this length is not guaranteed for all!

Details

Given a TxDb object, reassign the start site per transcript using max peaks from CageSeq data. A max peak is defined as new TSS if it is within boundary of 5' leader range, specified by 'extension' in bp. A max peak must also be higher than minimum CageSeq peak cutoff specified in 'filter-Value'. The new TSS will then be the positioned where the cage read (with highest read count in the interval). If no CAGE supports a leader, the width will be set to 1 base.

Value

a TxDb obect of reassigned transcripts

asTX

See Also

```
Other CAGE: reassignTSSbyCage(), reassignTxDbByCage()
```

Examples

```
txdbFile <- system.file("extdata", "hg19_knownGene_sample.sqlite",
package = "GenomicFeatures")
cagePath <- system.file("extdata", "cage-seq-heart.bed.bgz",
package = "ORFik")
## Not run:
   assignTSSByCage(txdbFile, cagePath)
   #Minimum 20 cage tags for new TSS
   assignTSSByCage(txdbFile, cagePath, filterValue = 20)
   # Create pseudo leaders for the ones without hits
   assignTSSByCage(txdbFile, cagePath, pseudoLength = 100)
   # Create only pseudo leaders (in example 2 leaders are added)
   assignTSSByCage(txdbFile, cage = NULL, pseudoLength = 100)
```

End(Not run)

asTX

Map genomic to transcript coordinates by reference

Description

Map range coordinates between features in the genome and transcriptome (reference) space.

Usage

```
asTX(
  grl,
  reference,
  ignore.strand = FALSE,
  x.is.sorted = TRUE,
  tx.is.sorted = TRUE
)
```

Arguments

grl	a GRangesList of ranges within the reference, grl must either have names match- ing, or a meta column called 'names' that gives grouping names. i.e. grl named uORF_1_ENST00001, must then have a names meta column with ENST00001.
reference	a GRangesList of ranges that include grl as a subset of ranges. Example: cds is grl and mrna can be reference
ignore.strand	When ignore.strand is TRUE, strand is ignored in overlaps operations (i.e., all strands are considered "+") and the strand in the output is '*'. When ignore.strand is FALSE (default) strand in the output is taken from the transcripts argument. When transcripts is a GRangesList, all inner list elements of a common list element must have the same strand or an error is thrown. Mapped position is computed by counting from the transcription start site (TSS) and is not affected by the value of ignore.strand.

bamVarName

x.is.sorted	if x is a GRangesList object, are "-" strand groups pre-sorted in decreasing order within group, default: TRUE
tx.is.sorted	if transcripts is a GRangesList object, are "-" strand groups pre-sorted in decreasing order within group, default: TRUE

Details

Similar to GenomicFeatures' pmapToTranscripts, but in this version the grl ranges are compared to reference ranges with same name, not by index. This gives a large speedup, but also requires all objects must be named.

Value

a GRangesList in transcript coordinates

See Also

Other ExtendGenomicRanges: coveragePerTiling(), extendLeaders(), extendTrailers(), reduceKeepAttr(), tile1(), txSeqsFromFa(), windowPerGroup()

Examples

```
seqname <- c("tx1", "tx2", "tx3")</pre>
seqs <- c("ATGGGTATTTATA", "AAAAAA", "ATGGGTAATA")</pre>
grIn1 <- GRanges(seqnames = "1",</pre>
                  ranges = IRanges(start = c(21, 10), end = c(23, 19)),
                  strand = "-")
grIn2 <- GRanges(seqnames = "1",</pre>
                  ranges = IRanges(start = c(1), end = c(5)),
                  strand = "-")
grIn3 <- GRanges(seqnames = "1",</pre>
                  ranges = IRanges(start = c(1010), end = c(1019)),
                  strand = "-")
grl <- GRangesList(grIn1, grIn2, grIn3)</pre>
names(grl) <- seqname</pre>
# Find ORFs
test_ranges <- findMapORFs(grl, seqs,</pre>
                  "ATG|TGG|GGG",
                  "TAA|AAT|ATA",
                  longestORF = FALSE,
                  minimumLength = 0)
# Genomic coordinates ORFs
test_ranges
# Transcript coordinate ORFs
asTX(test_ranges, reference = grl)
# seqnames will here be index of transcript it came from
```

bamVarName

Get library variable names from ORFik experiment

bamVarName

Description

What will each sample be called given the columns of the experiment? A column is included if more than 1 unique element value exist in that column.

Usage

```
bamVarName(
    df,
    skip.replicate = length(unique(df$rep)) == 1,
    skip.condition = length(unique(df$condition)) == 1,
    skip.stage = length(unique(df$stage)) == 1,
    skip.fraction = length(unique(df$fraction)) == 1,
    skip.experiment = !df@expInVarName,
    skip.libtype = FALSE,
    fraction_prepend_f = TRUE
)
```

Arguments

df	an ORFik experiment	
<pre>skip.replicate</pre>	a logical (FALSE), don't include replicate in variable name.	
skip.condition	a logical (FALSE), don't include condition in variable name.	
skip.stage	a logical (FALSE), don't include stage in variable name.	
skip.fraction	a logical (FALSE), don't include fraction	
skip.experiment		
	a logical (FALSE), don't include experiment	
skip.libtype	a logical (FALSE), don't include libtype	
fraction_prepend_f		
	a logical (TRUE), include "f" in front of fraction, useful for knowing what fraction is.	

Value

variable names of libraries (character vector)

See Also

```
Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(),
create.experiment(), experiment-class, filepath(), libraryTypes(), organism, experiment-method,
outputLibs(), read.experiment(), save.experiment(), validateExperiments()
```

Examples

```
df <- ORFik.template.experiment()
bamVarName(df)</pre>
```

```
## without libtype
bamVarName(df, skip.libtype = TRUE)
## Without experiment name
bamVarName(df, skip.experiment = TRUE)
```

bamVarNamePicker

Description

Get variable name per filepath in experiment

Usage

```
bamVarNamePicker(
    df,
    skip.replicate = FALSE,
    skip.condition = FALSE,
    skip.stage = FALSE,
    skip.fraction = FALSE,
    skip.experiment = FALSE,
    skip.libtype = FALSE,
    fraction_prepend_f = TRUE
)
```

Arguments

```
dfan ORFik experimentskip.replicatea logical (FALSE), don't include replicate in variable name.skip.conditiona logical (FALSE), don't include condition in variable name.skip.stagea logical (FALSE), don't include stage in variable name.skip.fractiona logical (FALSE), don't include fractionskip.experimenta logical (FALSE), don't include experimentskip.libtypea logical (FALSE), don't include libtypefraction_prepend_fa logical (TRUE), include "f" in front of fraction, useful for knowing what fraction is.
```

Value

variable name of library (character vector)

batchNames	Get batch name variants	
------------	-------------------------	--

Description

Used to standardize nomeclature for experiments. Example: Biological samples (batches) batch will become b1

Usage

batchNames()

bedToGR

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

```
Other experiment_naming: cellLineNames(), cellTypeNames(), conditionNames(), fractionNames(),
inhibitorNames(), libNames(), mainNames(), repNames(), stageNames(), tissueNames()
```

bedToGR

Converts bed style data.frame to GRanges

Description

For info on columns, see: https://www.ensembl.org/info/website/upload/bed.html

Usage

```
bedToGR(x, skip.name = TRUE)
```

Arguments

х	A data.frame from imported bed-file, to convert to GRanges
skip.name	default (TRUE), skip name column (column 4)

Value

a GRanges object from bed

See Also

```
Other utils: convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.fstwig(),
export.wiggle(), fimport(), findFa(), fread.bed(), optimizeReads(), readBam(), readBigWig(),
readWig()
```

browseSRA

Open SRA in browser for specific bioproject

Description

Open SRA in browser for specific bioproject

```
browseSRA(x, browser = getOption("browser"))
```

Arguments

х	character, bioproject ID.
browser	a non-empty character string giving the name of the program to be used as the HTML browser. It should be in the PATH, or a full path specified. Alternatively, an R function to be called to invoke the browser.
	Under Windows NULL is also allowed (and is the default), and implies that the file association mechanism will be used.

Value

invisible(NULL), opens webpage only

See Also

Other sra: download.SRA(), download.SRA.metadata(), download.ebi(), get_bioproject_candidates(),
install.sratoolkit(), rename.SRA.files()

Examples

#browseSRA("PRJNA336542")

```
#' # For windows make sure a valid browser is defined:
browser <- getOption("browser")
#browseSRA("PRJNA336542", browser)
```

cellLineNames Get cell-line name variants

Description

Used to standardize nomeclature for experiments. Example: THP1 is main naming, but a variant is THP-1 THP-1 will then be renamed to THP1 (variables in R, can not have - in them)

Usage

cellLineNames(convertToTissue = FALSE)

Arguments

convertToTissue

logical, FALSE. If TRUE, return tissue type. NONE is returned for general non-differentiated cell lines like 3T3.

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

```
Other experiment_naming: batchNames(), cellTypeNames(), conditionNames(), fractionNames(),
inhibitorNames(), libNames(), mainNames(), repNames(), stageNames(), tissueNames()
```

cellTypeNames

Description

Used to standardize nomeclature for experiments. Example: 1 is main naming, but a variant is rep1 rep1 will then be renamed to 1

Usage

```
cellTypeNames()
```

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

Other experiment_naming: batchNames(), cellLineNames(), conditionNames(), fractionNames(), inhibitorNames(), libNames(), mainNames(), repNames(), stageNames(), tissueNames()

changePointAnalysis Get the offset for specific RiboSeq read width

Description

Creates sliding windows of transcript normalized counts per position and check which window has most in upstream window vs downstream window. Pick the position with highest absolute value maximum of the window difference. Checks windows with split sites between positions -17 to -7, where 0 is TIS. Normally you expect the shift around -12 for Ribo-seq, in TCP-seq / RCP-seq it is usually a bit higher, usually because of cross-linking variations.

```
changePointAnalysis(
    x,
    feature = "start",
    max.pos = 40L,
    interval = seq.int(14L, 24L),
    center.pos = 12,
    info = NULL,
    verbose = FALSE
)
```

Arguments

X	a vector with count per position to analyse, assumes the zero position (TIS) is in the middle + 1 (position 0). Default it is size 60, from -30 to 29 in p-shifting
feature	(character) either "start" or "stop"
max.pos	integer, default 40L, subset x to go from index 1 to max.pos, if tail is not relevant.
interval	integer vector , default seq.int(14L, 24L). The possible shift locations, default Seperation points for upstream and downstream windows. That is $(+/-5 \text{ from } -12)$ position.
center.pos	integer, default 12. Centering position for likely p-site. A first qualified guess to save time. 12 means 12 bases before TIS.
info	specify read length if wanted for verbose output.
verbose	logical, default FALSE. Report details of change point analysis.

Details

For visual explanation, see the supl. data of ORFik paper: Transcript normalized means per CDS TIS region, count reads per position, divide that number per position by the total of that transcript, then sum up these numbers per position for all transcripts.

Value

a single numeric offset, -12 would mean p-site is 12 bases upstream

See Also

Other pshifting: detectRibosomeShifts(), shiftFootprints(), shiftFootprintsByExperiment(), shiftPlots(), shifts_load(), shifts_save()

checkRFP

Helper Function to check valid RFP input

Description

Helper Function to check valid RFP input

Usage

checkRFP(class)

Arguments

class the given class of RFP object

Value

NULL, stop if invalid object

See Also

```
Other validity: checkRNA(), is.ORF(), is.gr_or_grl(), is.grl(), is.range(), validGRL(),
validSeqlevels()
```

checkRNA

Description

Helper Function to check valid RNA input

Usage

checkRNA(class)

Arguments

class the given class of RNA object

Value

NULL, stop if unvalid object

See Also

```
Other validity: checkRFP(), is.ORF(), is.gr_or_grl(), is.grl(), is.range(), validGRL(),
validSeqlevels()
```

codonSumsPerGroup Get read hits per codon

Description

Helper for entropy function, normally not used directly Seperate each group into tuples (abstract codons) Gives sum for each tuple within each group

Usage

```
codonSumsPerGroup(grl, reads, weight = "score", is.sorted = FALSE)
```

Arguments

grl	a GRangesList of 5' utrs, CDS, transcripts, etc.
reads	a GAlignments, GRanges, or precomputed coverage as covRle (one for each strand) of RiboSeq, RnaSeq etc. Weigths for scoring is default the 'score' column in 'reads'. Can also be random access paths to bigWig or fstwig file. Do not use random access for more than a few genes, then loading the entire files is usually better. File streaming is still in
weight	beta, so use with care! (default: 'score'), if defined a character name of valid meta column in subject. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.
is.sorted	logical (FALSE), is grl sorted. That is + strand groups in increasing ranges $(1,2,3)$, and - strand groups in decreasing ranges $(3,2,1)$

Details

Example: counts c(1,0,0,1), with reg_len = 2, gives c(1,0) and c(0,1), these are summed and returned as data.table 10 bases, will give 3 codons, 1 base codons does not exist.

Value

a data.table with codon sums

codon_usage Codon usage

Description

Per AA / codon, analyse the coverage, get a multitude of features. For both A sites and P-sites (Input reads must be P-sites for now) This function takes inspiration from the codonDT paper, and among others returns the negative binomial estimates, but in addition many other features.

Usage

```
codon_usage(
  reads,
  cds,
  mrna,
  faFile,
  filter_table,
  filter_cds_mod3 = TRUE,
  min_counts_cds_filter = max(min(quantile(filter_table, 0.5), 1000), 1000),
  with_A_sites = TRUE,
  aligned_position = "center",
  code = GENETIC_CODE
)
```

Arguments

reads	either a single library (GRanges, GAlignment, GAlignmentPairs), or a list of libraries returned from outputLibs(df) with p-sites. If list, the list must have names corresponding to the library names.
cds	a GRangesList
mrna	a GRangesList
faFile	a FaFile from genome
filter_table	a matrix / vector of length equal to cds
filter_cds_mod3	
	logical, default TRUE. Remove all ORFs that are not mod3, this speeds up the computation a lot, and usually removes malformed ORFs you would not want anyway.
<pre>min_counts_cds_</pre>	filter
	<pre>numeric, default: max(min(quantile(filter_table, 0.50), 100), 100). Min- imum number of counts from the 'filter_table' argument.</pre>
with_A_sites	logical, default TRUE. Not used yet, will also return A site scores.

aligned_positio	n
	what positions should be taken to calculate per-codon coverage. By default: "center", meaning that positions $-1,0,1$ will be taken. Alternative: "left", then positions $0,1,2$ are taken.
code	a named character vector of size 64. Default: GENETIC_CODE. Change if organism does not use the standard code.

Details

The primary column to use is "mean_txNorm", this is the fair normalized score.

Value

a data.table of rows per codon / AA. All values are given per library, per site (A or P), sorted by the mean_txNorm_percentage column of the first library in the set, the columns are:

- variable (character)Library name
- seq (character)Amino acid:codon
- sum (integer)total counts per seq
- sum_txNorm (integer)total counts per seq normalized per tx
- var (numeric)variance of total counts per seq
- N (integer)total number of codons of that type
- mean_txNorm (numeric)Default use output, the fair codon usage, normalized both for gene and genome level for codon and read counts
- .
- alpha (numeric)dirichlet alpha MOM estimator (imagine mean and variance of probability in 1 value, the lower the value, the higher the variance, mean is decided by the relative value between samples)
- sum_txNorm (integer)total counts per seq normalized per tx
- relative_to_max_score (integer)Percentage use of codon
- type (factor(character))Either "P" or "A"

References

https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7196831/

See Also

Other codon: codon_usage_exp(), codon_usage_plot()

Examples

df <- ORFik.template.experiment()[9:10,] # Subset to 2 Ribo-seq libs</pre>

codon_usage_exp

Description

Per AA / codon, analyse the coverage, get a multitude of features. For both A sites and P-sites (Input reads must be P-sites for now) This function takes inspiration from the codonDT paper, and among others returns the negative binomial estimates, but in addition many other features.

Usage

```
codon_usage_exp(
    df,
    reads,
    cds = loadRegion(df, "cds", filterTranscripts(df)),
    mrna = loadRegion(df, "mrna", names(cds)),
    filter_cds_mod3 = TRUE,
    filter_table = assay(countTable(df, type = "summarized")[names(cds)]),
    faFile = df@fafile,
    min_counts_cds_filter = max(min(quantile(filter_table, 0.5), 1000), 1000),
    with_A_sites = TRUE,
    code = GENETIC_CODE,
    aligned_position = "center"
)
```

Arguments

df	an ORFik experiment	
reads	either a single library (GRanges, GAlignment, GAlignmentPairs), or a list of libraries returned from outputLibs(df) with p-sites. If list, the list must have names corresponding to the library names.	
cds	a GRangesList, the coding sequences, default: loadRegion(df, "cds", filterTranscripts(df)) longest isoform per gene.	
mrna	a GRangesList, the full mRNA sequences (matching by names the cds sequences), default: loadRegion(df, "mrna", names(cds)).	
filter_cds_mod3		
	logical, default TRUE. Remove all ORFs that are not mod3, this speeds up the computation a lot, and usually removes malformed ORFs you would not want anyway.	
filter_table	an numeric(integer) matrix, where rownames are the names of the full set of mRNA transcripts. This will be subsetted to the cds subset you use. Then CDSs are filtered from this table by the 'min_counts_cds_filter' argument.	
faFile	FaFile, BSgenome, fasta/index file path or an ORFik experiment. This file is usually used to find the transcript sequences from some GRangesList.	
<pre>min_counts_cds_filter</pre>		
	numeric, default: max(min(quantile(filter_table, 0.50), 100), 100). Min- imum number of counts from the 'filter_table' argument.	
with_A_sites	logical, default TRUE. Not used yet, will also return A site scores.	

code

31

a named	character	vector	of size	64.	Default:	GENETIC_	CODE.	Change	if
organism	does not u	use the	standard	d cod	le.				

aligned_position

what positions should be taken to calculate per-codon coverage. By default: "center", meaning that positions -1,0,1 will be taken. Alternative: "left", then positions 0,1,2 are taken.

Details

The primary column to use is "mean_txNorm", this is the fair normalized score.

Value

a data.table of rows per codon / AA. All values are given per library, per site (A or P), sorted by the mean_txNorm_percentage column of the first library in the set, the columns are:

- variable (character)Library name
- seq (character)Amino acid:codon
- sum (integer)total counts per seq
- sum_txNorm (integer)total counts per seq normalized per tx
- var (numeric)variance of total counts per seq
- N (integer)total number of codons of that type
- mean_txNorm (numeric)Default use output, the fair codon usage, normalized both for gene and genome level for codon and read counts
- ...
- alpha (numeric)dirichlet alpha MOM estimator (imagine mean and variance of probability in 1 value, the lower the value, the higher the variance, mean is decided by the relative value between samples)
- sum_txNorm (integer)total counts per seq normalized per tx
- relative_to_max_score (integer)Percentage use of codon
- type (factor(character))Either "P" or "A"

References

https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7196831/

See Also

Other codon: codon_usage(), codon_usage_plot()

Examples

codon_usage_plot Plot codon_usage

Description

Plot codon_usage

Usage

```
codon_usage_plot(
  res,
  score_column = res$relative_to_max_score,
  ylab = "Ribo-seq library",
  legend.position = "none",
  limit = c(0, max(score_column)),
  midpoint = limit/2,
  monospace_font = TRUE
)
```

Arguments

res	a data.table of output from a codon_usage function
score_column	numeric, default: res\$relative_to_max_score. Which parameter to use as score column.
ylab	character vector, names for libraries to show on Y axis
legend.position	
	character, default "none", do not display legend.
limit	numeric, 2 values for plot color limits. Default: c(0, max(score_column))
midpoint	numeric, default: limit/2. midpoint of color limit.
monospace_font	logical, default TRUE. Use monospace font, this does not work on systems (require specific font packages), set to FALSE if it crashes for you.

Value

a ggplot object

See Also

Other codon: codon_usage(), codon_usage_exp()

Examples

collapse.by.scores Merge reads by sum of existing scores

Description

If you have multiple reads a same location but different read lengths, specified in meta column "size", it will sum up the scores (number of replicates) for all reads at that position

Usage

collapse.by.scores(x)

Arguments ×

a GRanges object

Value

merged GRanges object

Examples

collapse.fastq Very fast fastq/fasta collapser

Description

For each unique read in the file, collapse into 1 and state in the fasta header how many reads existed of that type. This is done after trimming usually, works best for reads < 50 read length. Not so effective for 150 bp length mRNA-seq etc.

```
collapse.fastq(
  files,
  outdir = file.path(dirname(files[1]), "collapsed"),
  header.out.format = "ribotoolkit",
  compress = FALSE,
  prefix = "collapsed_"
)
```

Arguments

files	paths to fasta / fastq files to collapse. I tries to detect format per file, if file does not have .fastq, .fastq.gz, .fq or fq.gz extensions, it will be treated as a .fasta file format.
outdir	outdir to save files, default: file.path(dirname(files[1]), "collapsed"). Inside same folder as input files, then create subfolder "collapsed", and add a prefix of "collapsed_" to the output names in that folder.
header.out.for	mat
	character, default "ribotoolkit", else must be "fastx". How the read header of the output fasta should be formated: ribotoolkit: ">seq1_x55", sequence 1 has 55 duplicated reads collapsed. fastx: ">1-55", sequence 1 has 55 duplicated reads collapsed
compress	logical, default FALSE
prefix	character, default "collapsed_" Prefix to name of output file.

Value

invisible(NULL), files saved to disc in fasta format.

Examples

```
fastq.folder <- tempdir() # <- Your fastq files
infiles <- dir(fastq.folder, "*.fastq", full.names = TRUE)
# collapse.fastq(infiles)
```

collapseDuplicatedReads

Collapse duplicated reads

Description

For every GRanges, GAlignments read, with the same: seqname, start, (cigar) / width and strand, collapse and give a new meta column called "score", which contains the number of duplicates of that read. If score column already exists, will return input object!

Usage

```
collapseDuplicatedReads(x, addScoreColumn = TRUE, ...)
```

Arguments

Х	a GRanges, GAlignments or GAlignmentPairs object
addScoreColumn	logical, default: (TRUE), if FALSE, only collapse and not keep score column of
	counts for collapsed reads. Returns directly without collapsing if reuse.score.column is FALSE and score is already defined.
	$alternative \ arguments \ for \ class \ instances. \ For \ example, \ see: \ ?' \ collapseDuplicated \ Reads, \ GRanges \ and \ reads \ read$

Value

a GRanges, GAlignments, GAlignmentPairs or data.table object, same as input

collapseDuplicatedReads,data.table-method

Examples

```
gr <- rep(GRanges("chr1", 1:10,"+"), 2)
collapseDuplicatedReads(gr)</pre>
```

collapseDuplicatedReads,data.table-method Collapse duplicated reads

Description

For every GRanges, GAlignments read, with the same: seqname, start, (cigar) / width and strand, collapse and give a new meta column called "score", which contains the number of duplicates of that read. If score column already exists, will return input object!

Usage

```
## S4 method for signature 'data.table'
collapseDuplicatedReads(
    x,
    addScoreColumn = TRUE,
    addSizeColumn = FALSE,
    reuse.score.column = TRUE,
    keepCigar = FALSE
)
```

Arguments

х	a GRanges, GAlignments or GAlignmentPairs object
addScoreColumn	logical, default: (TRUE), if FALSE, only collapse and not keep score column of counts for collapsed reads. Returns directly without collapsing if reuse.score.column is FALSE and score is already defined.
addSizeColumn	logical (FALSE), if TRUE, add a size column that for each read, that gives orig- inal width of read. Useful if you need original read lengths. This takes care of soft clips etc. If collapsing reads, each unique range will be grouped also by size.
reuse.score.col	umn
	logical (TRUE), if addScoreColumn is TRUE, and a score column exists, will sum up the scores to create a new score. If FALSE, will skip old score column and create new according to number of replicated reads after conversion. If addScoreColumn is FALSE, this argument is ignored.
keepCigar	logical, default FALSE. Keep the cigar information

Value

a GRanges, GAlignments, GAlignmentPairs or data.table object, same as input

Examples

```
gr <- rep(GRanges("chr1", 1:10,"+"), 2)
collapseDuplicatedReads(gr)</pre>
```

collapseDuplicatedReads,GAlignmentPairs-method Collapse duplicated reads

Description

For every GRanges, GAlignments read, with the same: seqname, start, (cigar) / width and strand, collapse and give a new meta column called "score", which contains the number of duplicates of that read. If score column already exists, will return input object!

Usage

```
## S4 method for signature 'GAlignmentPairs'
collapseDuplicatedReads(x, addScoreColumn = TRUE)
```

Arguments

addScoreColumn logical, default: (TRUE), if FALSE, only collapse and not keep score column of counts for collapsed reads. Returns directly without collapsing if reuse.score.column is FALSE and score is already defined	Х	a GRanges, GAlignments or GAlignmentPairs object
is i ALSE and score is arready defined.	addScoreColumn	logical, default: (TRUE), if FALSE, only collapse and not keep score column of counts for collapsed reads. Returns directly without collapsing if reuse.score.column is FALSE and score is already defined.

Value

a GRanges, GAlignments, GAlignmentPairs or data.table object, same as input

Examples

```
gr <- rep(GRanges("chr1", 1:10,"+"), 2)
collapseDuplicatedReads(gr)</pre>
```

collapseDuplicatedReads,GAlignments-method Collapse duplicated reads

Description

For every GRanges, GAlignments read, with the same: seqname, start, (cigar) / width and strand, collapse and give a new meta column called "score", which contains the number of duplicates of that read. If score column already exists, will return input object!

```
## S4 method for signature 'GAlignments'
collapseDuplicatedReads(x, addScoreColumn = TRUE, reuse.score.column = TRUE)
```
Arguments

х	a GRanges, GAlignments or GAlignmentPairs object	
addScoreColumn	logical, default: (TRUE), if FALSE, only collapse and not keep score column of counts for collapsed reads. Returns directly without collapsing if reuse.score.column is FALSE and score is already defined.	
reuse.score.column		
	logical (TRUE), if addScoreColumn is TRUE, and a score column exists, will sum up the scores to create a new score. If FALSE, will skip old score column and create new according to number of replicated reads after conversion. If	

addScoreColumn is FALSE, this argument is ignored.

Value

a GRanges, GAlignments, GAlignmentPairs or data.table object, same as input

Examples

```
gr <- rep(GRanges("chr1", 1:10,"+"), 2)
collapseDuplicatedReads(gr)</pre>
```

collapseDuplicatedReads,GRanges-method Collapse duplicated reads

Description

For every GRanges, GAlignments read, with the same: seqname, start, (cigar) / width and strand, collapse and give a new meta column called "score", which contains the number of duplicates of that read. If score column already exists, will return input object!

Usage

```
## S4 method for signature 'GRanges'
collapseDuplicatedReads(
    x,
    addScoreColumn = TRUE,
    addSizeColumn = FALSE,
    reuse.score.column = TRUE
)
```

x	a GRanges, GAlignments or GAlignmentPairs object
addScoreColumn	logical, default: (TRUE), if FALSE, only collapse and not keep score column of counts for collapsed reads. Returns directly without collapsing if reuse.score.column is FALSE and score is already defined.
addSizeColumn	logical (FALSE), if TRUE, add a size column that for each read, that gives orig- inal width of read. Useful if you need original read lengths. This takes care of soft clips etc. If collapsing reads, each unique range will be grouped also by size.

reuse.score.column

logical (TRUE), if addScoreColumn is TRUE, and a score column exists, will sum up the scores to create a new score. If FALSE, will skip old score column and create new according to number of replicated reads after conversion. If addScoreColumn is FALSE, this argument is ignored.

Value

a GRanges, GAlignments, GAlignmentPairs or data.table object, same as input

Examples

```
gr <- rep(GRanges("chr1", 1:10,"+"), 2)
collapseDuplicatedReads(gr)</pre>
```

combn.pairs

Create all unique combinations pairs possible

Description

Given a character vector, get all unique combinations of 2.

Usage

combn.pairs(x)

Arguments

х

a character vector, will unique elements for you.

Value

a list of character vector pairs

Examples

```
df <- ORFik.template.experiment()
ORFik:::combn.pairs(df[, "libtype"])</pre>
```

computeFeatures

Description

If you want to get all the NGS and/or sequence features easily, you can use this function. Each feature have a link to an article describing its creation and idea behind it. Look at the functions in the feature family (in the "see also" section below) to see all of them. Example, if you want to know what the "te" column is, check out: ?translationalEff.

A short description of each feature is also shown here:

** NGS features ** If not stated otherwise stated, the feature apply to Ribo-seq.

- countRFP : raw counts of Ribo-seq
- fpkmRFP : FPKM
- fpkmRNA : FPKM of RNA-seq
- te : Translation efficiency Ribo-seq / RNA-seq FPKM
- floss : Fragment length similarity score
- entropyRFP : Positional entropy
- · disengagementScores : downstream coverage from ORF
- RRS: Ribosome release score
- RSS: Ribosome staling score
- ORFScores: Periodicity score, does frame 0 have more reads
- · ioScore: inside outside score: coverage ORF / coverage rest of transcript
- startCodonCoverage: Coverage over start codon + 2nt before start codon
- startRegionCoverage: Coverage over codon 2 & 3
- startRegionRelative: Peakness of TIS, startCodonCoverage / startRegionCoverage, 0-n
- ** Sequence features **
 - kozak : Similarity to kozak sequence for organism score, 0-1
 - gc : GC percentage, 0-1
 - StartCodons : Start codon as a string, "ATG"
 - StopCodons : stop codon as a string, "TAA"
 - fractionLengths : ORF length compared to transcript, 0-1

** uORF features **

- distORFCDS : Distance from ORF stop site to CDS, -n:n
- inFrameCDS : Is ORF in frame with downstream CDS, T/F
- isOverlappingCds : Is ORF overlapping with downstream CDS, T/F
- rankInTx : ORF with most upstream start codon is 1, 1-n

Usage

```
computeFeatures(
  grl,
  RFP,
  RNA = NULL,
  Gtf,
  faFile = NULL,
  riboStart = 26,
  riboStop = 34,
  sequenceFeatures = TRUE,
  uorfFeatures = TRUE,
  grl.is.sorted = FALSE,
  weight.RFP = 1L,
  weight.RNA = 1L
)
```

Arguments

grl	a GRangesList object with usually ORFs, but can also be either leaders, cds', 3' utrs, etc. This is the regions you want to score.	
RFP	RiboSeq reads as GAlignments, GRanges or GRangesList object	
RNA	RnaSeq reads as GAlignments, GRanges or GRangesList object	
Gtf	a TxDb object of a gtf file or path to gtf, gff .sqlite etc.	
faFile	a path to fasta indexed genome, an open FaFile, a BSgenome, or path to ORFik experiment with valid genome.	
riboStart	usually 26, the start of the floss interval, see ?floss	
riboStop	usually 34, the end of the floss interval	
sequenceFeatures		
	a logical, default TRUE, include all sequence features, that is: Kozak, fraction- Lengths, distORFCDS, isInFrame, isOverlapping and rankInTx. uorfFeatures = FALSE will remove the 4 last.	
uorfFeatures	a logical, default TRUE, include all uORF sequence features, that is: distOR-FCDS, isInFrame, isOverlapping and rankInTx	
grl.is.sorted	logical (F), a speed up if you know argument grl is sorted, set this to TRUE.	
weight.RFP	a vector (default: 1L). Can also be character name of column in RFP. As in translationalEff(weight = "score") for: GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times.	
weight.RNA	Same as weightRFP but for RNA weights. (default: 1L)	

Details

If you used CageSeq to reannotate your leaders, your txDB object must contain the reassigned leaders. Use [reassignTxDbByCage()] to get the txdb.

As a note the library is reduced to only reads overlapping 'tx', so the library size in fpkm calculation is done on this subset. This will help remove rRNA and other contaminants.

Also if you have only unique reads with a weight column, explaining the number of duplicated reads, set weights to make calculations correct. See getWeights

40

computeFeaturesCage

Value

a data.table with scores, each column is one score type, name of columns are the names of the scores, i.g [floss()] or [fpkm()]

See Also

```
Other features: computeFeaturesCage(), countOverlapsW(), disengagementScore(), distToCds(),
distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
# Here we make an example from scratch
# Usually the ORFs are found in orfik, which makes names for you etc.
gtf <- system.file("extdata/references/danio_rerio", "annotations.gtf",
package = "ORFik") ## location of the gtf file
suppressWarnings(txdb <- loadTxdb(gtf))
# use cds' as ORFs for this example
```

```
ORFs <- loadRegion(txdb, "cds")
ORFs <- makeORFNames(ORFs) # need ORF names
# make Ribo-seq data,
RFP <- unlistGrl(firstExonPerGroup(ORFs))
computeFeatures(ORFs, RFP, Gtf = txdb)
# For more details see vignettes.</pre>
```

computeFeaturesCage Get all main features in ORFik

Description

If you have a txdb with correctly reassigned transcripts, use: [computeFeatures()]

```
computeFeaturesCage(
  grl,
  RFP,
  RNA = NULL,
  Gtf = NULL,
  tx = NULL,
  tiveUTRs = NULL,
  cds = NULL,
  threeUTRs = NULL,
  faFile = NULL,
  riboStart = 26,
  riboStop = 34,
  sequenceFeatures = TRUE,
  uorfFeatures = TRUE,
```

```
grl.is.sorted = FALSE,
weight.RFP = 1L,
weight.RNA = 1L
```

Arguments

grl	a GRangesList object with usually ORFs, but can also be either leaders, cds', 3' utrs, etc. This is the regions you want to score.	
RFP	RiboSeq reads as GAlignments, GRanges or GRangesList object	
RNA	RnaSeq reads as GAlignments, GRanges or GRangesList object	
Gtf	a TxDb object of a gtf file or path to gtf, gff .sqlite etc.	
tx	a GRangesList of transcripts, normally called from: exonsBy(Gtf, by = "tx", use.names = T) only add this if you are not including Gtf file If you are using CAGE, you do not need to reassign these to the cage peaks, it will do it for you.	
fiveUTRs	fiveUTRs as GRangesList, if you used cage-data to extend 5' utrs, remember to input CAGE assigned version and not original!	
cds	a GRangesList of coding sequences	
threeUTRs	a GRangesList of transcript 3' utrs, normally called from: threeUTRsByTran- script(Gtf, use.names = T)	
faFile	a path to fasta indexed genome, an open FaFile, a BSgenome, or path to ORFik experiment with valid genome.	
riboStart	usually 26, the start of the floss interval, see ?floss	
riboStop	usually 34, the end of the floss interval	
sequenceFeatures		
	a logical, default TRUE, include all sequence features, that is: Kozak, fraction- Lengths, distORFCDS, isInFrame, isOverlapping and rankInTx. uorfFeatures = FALSE will remove the 4 last.	
uorfFeatures	a logical, default TRUE, include all uORF sequence features, that is: distOR-FCDS, isInFrame, isOverlapping and rankInTx	
grl.is.sorted	logical (F), a speed up if you know argument grl is sorted, set this to TRUE.	
weight.RFP	a vector (default: 1L). Can also be character name of column in RFP. As in translationalEff(weight = "score") for: GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times.	
weight.RNA	Same as weightRFP but for RNA weights. (default: 1L)	

Details

A specialized version if you don't have a correct txdb, for example with CAGE reassigned leaders while txdb is not updated. It is 2x faster for tested data. The point of this function is to give you the ability to input transcript etc directly into the function, and not load them from txdb. Each feature have a link to an article describing feature, try ?floss

Value

a data.table with scores, each column is one score type, name of columns are the names of the scores, i.g [floss()] or [fpkm()]

42

conditionNames

See Also

```
Other features: computeFeatures(), countOverlapsW(), disengagementScore(), distToCds(),
distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
# a small example without cage-seq data:
 # we will find ORFs in the 5' utrs
 # and then calculate features on them
 if (requireNamespace("BSgenome.Hsapiens.UCSC.hg19")) {
 library(GenomicFeatures)
  # Get the gtf txdb file
  txdbFile <- system.file("extdata", "hg19_knownGene_sample.sqlite",</pre>
  package = "GenomicFeatures")
  txdb <- loadDb(txdbFile)</pre>
  # Extract sequences of fiveUTRs.
  fiveUTRs <- fiveUTRsByTranscript(txdb, use.names = TRUE)[1:10]</pre>
  faFile <- BSgenome.Hsapiens.UCSC.hg19::Hsapiens</pre>
  tx_seqs <- extractTranscriptSeqs(faFile, fiveUTRs)</pre>
  # Find all ORFs on those transcripts and get their genomic coordinates
  fiveUTR_ORFs <- findMapORFs(fiveUTRs, tx_seqs)</pre>
  unlistedORFs <- unlistGrl(fiveUTR_ORFs)</pre>
  # group GRanges by ORFs instead of Transcripts
  fiveUTR_ORFs <- groupGRangesBy(unlistedORFs, unlistedORFs$names)</pre>
  # make some toy ribo seq and rna seq data
  starts <- unlistGrl(ORFik:::firstExonPerGroup(fiveUTR_ORFs))</pre>
  RFP <- promoters(starts, upstream = 0, downstream = 1)</pre>
  score(RFP) <- rep(29, length(RFP)) # the original read widths</pre>
  # set RNA seq to duplicate transcripts
  RNA <- unlistGrl(exonsBy(txdb, by = "tx", use.names = TRUE))</pre>
  #ORFik:::computeFeaturesCage(grl = fiveUTR_ORFs, RFP = RFP,
  # RNA = RNA, Gtf = txdb, faFile = faFile)
# See vignettes for more examples
```

conditionNames Get condition name variants

Description

Used to standardize nomeclature for experiments. Example: WT is main naming, but a variant is control control will then be renamed to WT

Usage

conditionNames()

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

```
Other experiment_naming: batchNames(), cellLineNames(), cellTypeNames(), fractionNames(),
inhibitorNames(), libNames(), mainNames(), repNames(), stageNames(), tissueNames()
```

config

Read directory config for ORFik experiments

Description

Defines a folder for: 1. fastq files (raw data)

2. bam files (processed data)

3. references (organism annotation and STAR index)

4. experiments (Location to store and load all experiment .csv files) Update or use another config using config.save() function.

Usage

```
config(
  file = config_file(old_config_location = old_config_location),
  old_config_location = "~/Bio_data/ORFik_config.csv"
)
```

Arguments

file location of config csv, default: config_file(old_config_location = old_config_location) old_config_location

path, old config location before BiocFileCache implementation. Will copy this to cache directory and delete old version. This is done to follow bioc rules on not writing to user home directory.

Value

a named character vector of length 3

Examples

Make with default config path
#config()

config.exper Set directories for experiment

Description

Defines a folder for: 1. fastq files (raw_data)

- 2. bam files (processed data)
- 3. references (organism annotation and STAR index)
- 4. Experiment (name of experiment)

Usage

```
config.exper(experiment, assembly, type, config = ORFik::config())
```

Arguments

experiment	short name of experiment (must be valid as a folder name)
assembly	name of organism and assembly (must be valid as a folder name)
type	name of sequencing type, Ribo-seq, RNA-seq, CAGE Can be more than one.
config	a named character vector of length 3, default: ORFik::config()

Value

named character vector of paths for experiment

Examples

```
# Where should files go in general?
ORFik::config()
# Paths for project: "Alexaki_Human" containing Ribo-seq and RNA-seq:
#config.exper("Alexaki_Human", "Homo_sapiens_GRCh38_101", c("Ribo-seq", "RNA-seq"))
```

config.save

Save/update directory config for ORFik experiments

Description

Defines a folder for fastq files (raw_data), bam files (processed data) and references (organism annotation and STAR index)

```
config.save(
  file = config_file(),
  fastq.dir = file.path(base.dir, "raw_data"),
  bam.dir = file.path(base.dir, "processed_data"),
  reference.dir = file.path(base.dir, "references"),
  exp.dir = file.path(base.dir, "ORFik_experiments/"),
  base.dir = "~/Bio_data",
  conf = data.frame(type = c("fastq", "bam", "ref", "exp"), directory = c(fastq.dir,
      bam.dir, reference.dir, exp.dir))
)
```

Arguments

file	location of config csv, default: config_file(old_config_location = old_config_location)
fastq.dir	directory where ORFik puts fastq file directories, default: file.path(base.dir, "raw_data"), which is retrieved with: config()["fastq"]
bam.dir	directory where ORFik puts bam file directories, default: file.path(base.dir, "pro- cessed_data"), which is retrieved with: config()["bam"]
reference.dir	directory where ORFik puts reference file directories, default: file.path(base.dir, "references"), which is retrieved with: config()["ref"]
exp.dir	directory where ORFik puts experiment csv files, default: file.path(base.dir, "ORFik_experiments/"), which is retrieved with: config()["exp"]
base.dir	base directory for all output directories, default: "~/Bio_data"
conf	data.frame of complete conf object, default: data.frame(type = c("fastq", "bam", "ref", "exp"), directory = c(fastq.dir, bam.dir, reference.dir, exp.dir))

Value

invisible(NULL), file saved to disc

Examples

```
# Overwrite default config, with new base directory for files
#config.save(base.dir = "/media/Bio_data/") # Output files go here instead
# of ~/Bio_data
## Dont do this, but for understanding here is how to make a second config
#new_config_path <- config_file(query = "ORFik_config_2")
#config.save(new_config_path, "/media/Bio_data/raw_data/",
# "/media/Bio_data/processed_data", /media/Bio_data/references/)
```

config_file

Get path for ORFik config in cache

Description

Get path for ORFik config in cache

```
config_file(
  cache = BiocFileCache::getBFCOption("CACHE"),
  query = "ORFik_config",
  ask = interactive(),
  old_config_location = "~/Bio_data/ORFik_config.csv"
)
```

convertLibs

Arguments

cache	path to bioc cache directory with rname from query argument. Default is:	
	BiocFileCache::getBFCOption("CACHE") For info, see: [BiocFileCache::BiocFileCache()]	
query	default: "ORFik_config". Exact rname of the file in cache.	
ask	logical, default interactive().	
old_config_location		
	path, old config location before BiocFileCache implementation. Will copy this	
	to cache directory and delete old version. This is done to follow bioc rules on	
	not writing to user home directory.	

Value

a file path in cache

Examples

config_file()
Another config path
config_file(query = "ORFik_config_2")

convertLibs

Converted format of NGS libraries

Description

Export as either .ofst, .wig, .bigWig,.bedo (legacy format) or .bedoc (legacy format) files: Export files as .ofst for fastest load speed into R. Export files as .wig / bigWig for use in IGV or other genome browsers. The input files are checked if they exist from: envExp(df).

```
convertLibs(
  df,
  out.dir = libFolder(df),
  addScoreColumn = TRUE,
  addSizeColumn = TRUE,
  must.overlap = NULL,
  method = "None",
  type = "ofst",
  input.type = "ofst",
  reassign.when.saving = FALSE,
  envir = envExp(df),
  force = TRUE,
  library.names = bamVarName(df),
 libs = outputLibs(df, type = input.type, chrStyle = must.overlap, library.names =
    library.names, output.mode = "list", force = force, BPPARAM = BPPARAM),
  BPPARAM = bpparam()
)
```

Arguments

an ORFik experiment
optional output directory, default: libFolder(df), if it is NULL, it will just reas- sign R objects to simplified libraries. Will then create a final folder specfied as: paste0(out.dir, "/", type, "/"). Here the files will be saved in format given by the type argument.
logical, default TRUE, if FALSE will not add replicate numbers as score col- umn, see ORFik::convertToOneBasedRanges.
logical, default TRUE, if FALSE will not add size (width) as size column, see ORFik::convertToOneBasedRanges. Does not apply for (GAlignment version of.ofst) or .bedoc. Since they contain the original cigar.
default (NULL), else a GRanges / GRangesList object, so only reads that over- lap (must.overlap) are kept. This is useful when you only need the reads over transcript annotation or subset etc.
character, default "None", the method to reduce ranges, for more info see convertToOneBasedRanges
character, output format, default "ofst". Alternatives: "ofst", "bigWig", "wig", "bedo" or "bedoc". Which format you want. Will make a folder within out.dir with this name containing the files.
character, input type "ofst". Remember this function uses the loaded libraries if existing, so this argument is usually ignored. Only used if files do not already exist.
aving
logical, default FALSE. If TRUE, will reassign library to converted form after saving. Ignored when out.dir = NULL.
environment to save to, default envExp(df), which defaults to .GlobalEnv, but can be set with envExp(df) <- new.env() etc.
logical, default TRUE If TRUE, reload library files even if matching named variables are found in environment used by experiment (see envExp) A simple way to make sure correct libraries are always loaded. FALSE is faster if data is loaded correctly already.
character vector, names of libraries, default: name_decider(df, naming)
list, output of outputLibs as list of GRanges/GAlignments/GAlignmentPairs objects. Set input.type and force arguments to define parameters.
how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.

Details

We advice you to not use this directly, as other function are more safe for library type conversions. See family description below. This is mostly used internally in ORFik. It is only adviced to use if large bam files are already loaded in R and conversions are wanted from those.

See export.ofst, export.wiggle, export.bedo and export.bedoc for information on file formats.

If libraries of the experiment are already loaded into environment (default: .globalEnv) is will export using those files as templates. If they are not in environment the .ofst files from the bam files are loaded (unless you are converting to .ofst then the .bam files are loaded).

Value

invisible NULL (saves files to disc or R .GlobalEnv)

See Also

```
Other lib_converters: convert_bam_to_ofst(), convert_to_bigWig(), convert_to_covRle(),
convert_to_covRleList()
```

Examples

```
df <- ORFik.template.experiment()
#convertLibs(df, out.dir = NULL)
# Keep only 5' ends of reads
#convertLibs(df, out.dir = NULL, method = "5prime")</pre>
```

convertToOneBasedRanges

Convert a GRanges Object to 1 width reads

Description

There are 5 ways of doing this

- 1. Take 5' ends, reduce away rest (5prime)
- 2. Take 3' ends, reduce away rest (3prime)
- 3. Tile to 1-mers and include all (tileAll)
- 4. Take middle point per GRanges (middle)
- 5. Get original with metacolumns (None)

You can also do multiple at a time, then output is GRangesList, where each list group is the operation (5prime is [1], 3prime is [2] etc)

Many other ways to do this have their own functions, like startSites and stopSites etc. To retain information on original width, set addSizeColumn to TRUE. To compress data, 1 GRanges object per unique read, set addScoreColumn to TRUE. This will give you a score column with how many duplicated reads there were in the specified region.

Usage

```
convertToOneBasedRanges(
  gr,
  method = "5prime",
  addScoreColumn = FALSE,
  addSizeColumn = FALSE,
  after.softclips = TRUE,
  along.reference = FALSE,
  reuse.score.column = TRUE
)
```

method character, default "5prime", the method to reduce ranges, see NOTE for mo	gr	GRanges, GAlignment or GAlignmentPairs object to reduce.
IIIO.	method	character, default "5prime", the method to reduce ranges, see NOTE for more info.

- addScoreColumn logical (FALSE), if TRUE, add a score column that sums up the hits per unique range. This will make each read unique, so that each read is 1 time, and score column gives the number of collapsed hits. A useful compression. If add-SizeColumn is FALSE, it will not differentiate between reads with same start and stop, but different length. If addSizeColumn is FALSE, it will remove it. Collapses after conversion.
- addSizeColumn logical (FALSE), if TRUE, add a size column that for each read, that gives original width of read. Useful if you need original read lengths. This takes care of soft clips etc. If collapsing reads, each unique range will be grouped also by size.
- after.softclips
 - logical (TRUE), include softclips in width. Does not apply if along.reference is TRUE.
- along.reference

logical (FALSE), example: The cigar "26MI2" is by default width 28, but if along.reference is TRUE, it will be 26. The length of the read along the reference. Also "1D20M" will be 21 if by along.reference is TRUE. Intronic regions (cigar: N) will be removed. So: "1M200N19M" is 20, not 220.

reuse.score.column

logical (TRUE), if addScoreColumn is TRUE, and a score column exists, will sum up the scores to create a new score. If FALSE, will skip old score column and create new according to number of replicated reads after conversion. If addScoreColumn is FALSE, this argument is ignored.

Details

NOTE: Note: For cigar based ranges (GAlignments), the 5' end is the first non clipped base (neither soft clipped or hard clipped from 5'). This is following the default of bioconductor. For special case of GAlignmentPairs, 5prime will only use left (first) 5' end and read and 3prime will use only right (last) 3' end of read in pair. tileAll and middle can possibly find poinst that are not in the reads since: lets say pair is 1-5 and 10-15, middle is 7, which is not in the read.

Value

Converted GRanges object

See Also

Other utils: bedToGR(), export.bed12(), export.bigWig(), export.fstwig(), export.wiggle(), fimport(), findFa(), fread.bed(), optimizeReads(), readBam(), readBigWig(), readWig()

Examples

```
gr <- GRanges("chr1", 1:10,"+")
# 5 prime ends
convertToOneBasedRanges(gr)
# is equal to convertToOneBasedRanges(gr, method = "5prime")
# 3 prime ends
convertToOneBasedRanges(gr, method = "3prime")
# With lengths
convertToOneBasedRanges(gr, addSizeColumn = TRUE)
# With score (# of replicates)
gr <- rep(gr, 2)
convertToOneBasedRanges(gr, addSizeColumn = TRUE, addScoreColumn = TRUE)</pre>
```

Description

Saved by default in folder "ofst" relative to default libraries of experiment. Speeds up loading of full files compared to bam by large margins.

Usage

```
convert_bam_to_ofst(
    df,
    in_files = filepath(df, "default"),
    out_dir = file.path(libFolder(df), "ofst"),
    verbose = TRUE,
    strandMode = rep(0, length(in_files))
)
```

Arguments

df	an ORFik experiment, or NULL is allowed if both in_files and out_dir is spec- ified manually.
in_files	paths to input files, default: filepath(df, "default") with bam format files.
out_dir	<pre>paths to output files, default file.path(libFolder(df), "cov_RLE").</pre>
verbose	logical, default TRUE, message about library output status.
strandMode	numeric, default 0. Only used for paired end bam files. One of (0: strand $=$ *, 1: first read of pair is +, 2: first read of pair is -). See ?strandMode. Note: Sets default to 0 instead of 1, as readGAlignmentPairs uses 1. This is to guarantee hits, but will also make mismatches of overlapping transcripts in opposite directions.

Details

If you want to keep bam files loaded or faster conversion if you already have them loaded, use ORFik::convertLibs instead

Value

invisible(NULL), files saved to disc

See Also

Other lib_converters: convertLibs(), convert_to_bigWig(), convert_to_covRle(), convert_to_covRleList()

Examples

```
df <- ORFik.template.experiment.zf()
## Usually do default folder, here we use tmpdir
folder_to_save <- file.path(tempdir(), "ofst")
convert_bam_to_ofst(df, out_dir = folder_to_save)
fimport(file.path(folder_to_save, "ribo-seq.ofst"))</pre>
```

convert_to_bigWig Convert to BigWig

Description

Convert to BigWig

Usage

```
convert_to_bigWig(
    df,
    in_files = filepath(df, "pshifted"),
    out_dir = file.path(libFolder(df), "bigwig"),
    split.by.strand = TRUE,
    split.by.readlength = FALSE,
    seq_info = seqinfo(df),
    weight = "score",
    is_pre_collapsed = FALSE,
    verbose = TRUE
)
```

Arguments

df	an ORFik experiment, or NULL is allowed if both in_files and out_dir is spec- ified manually.	
in_files	paths to input files, default pshifted files: filepath(df, "pshifted") in ofst format	
out_dir	paths to output files, default file.path(libFolder(df), "bigwig").	
<pre>split.by.strand</pre>		
	logical, default TRUE, split into forward and reverse strand RleList inside cov- Rle object.	
split.by.readlength		
	logical, default FALSE, split into files for each readlength, defined by read-Widths (x) for each file.	
seq_info	SeqInfo object, default seqinfo(findFa(df))	
weight	integer, numeric or single length character. Default "score". Use score column in loaded in_files.	
is_pre_collapsed		
	logical, default FALSE. Have you already collapsed reads with collapse.by.scores, so each positions is only in 1 GRanges object with a score column per readlength? Set to TRUE, only if you are sure, will give a speedup.	
verbose	logical, default TRUE, message about library output status.	

Value

invisible(NULL), files saved to disc

See Also

Other lib_converters: convertLibs(), convert_bam_to_ofst(), convert_to_covRle(), convert_to_covRleList()

convert_to_covRle

Examples

```
df <- ORFik.template.experiment()[10,]
## Usually do default folder, here we use tmpdir
folder_to_save <- file.path(tempdir(), "bigwig")
convert_to_bigWig(df, out_dir = folder_to_save)
fimport(file.path(folder_to_save, c("RFP_Mutant_rep2_forward.bigWig",
    "RFP_Mutant_rep2_reverse.bigWig")))</pre>
```

convert_to_covRle Convert libraries to covRle

Description

Saved by default in folder "cov_RLE" relative to default libraries of experiment

Usage

```
convert_to_covRle(
    df,
    in_files = filepath(df, "pshifted"),
    out_dir = file.path(libFolder(df), "cov_RLE"),
    split.by.strand = TRUE,
    split.by.readlength = FALSE,
    seq_info = seqinfo(df),
    weight = "score",
    verbose = TRUE
)
```

Arguments

df	an ORFik experiment, or NULL is allowed if both in_files and out_dir is specified manually.	
in_files	paths to input files, default pshifted files: filepath(df, "pshifted") in ofst format	
out_dir	<pre>paths to output files, default file.path(libFolder(df), "cov_RLE").</pre>	
<pre>split.by.strand</pre>		
	logical, default TRUE, split into forward and reverse strand RleList inside cov-	
	Rle object.	
split.by.readlength		
	logical, default FALSE, split into files for each readlength, defined by read-Widths(x) for each file.	
seq_info	SeqInfo object, default seqinfo(findFa(df))	
weight	integer, numeric or single length character. Default "score". Use score column in loaded in_files.	
verbose	logical, default TRUE, message about library output status.	

Value

invisible(NULL), files saved to disc

See Also

Other lib_converters: convertLibs(), convert_bam_to_ofst(), convert_to_bigWig(), convert_to_covRleList()

Examples

```
df <- ORFik.template.experiment()[10,]
## Usually do default folder, here we use tmpdir
folder_to_save <- file.path(tempdir(), "cov_RLE")
convert_to_covRle(df, out_dir = folder_to_save)
fimport(file.path(folder_to_save, "RFP_Mutant_rep2.covrds"))</pre>
```

convert_to_covRleList Convert libraries to covRleList objects

Description

Useful to store reads separated by readlength, for much faster coverage calculation. Saved by default in folder "cov_RLE_List" relative to default libraries of experiment

Usage

```
convert_to_covRleList(
    df,
    in_files = filepath(df, "pshifted"),
    out_dir = file.path(libFolder(df), "cov_RLE_List"),
    out_dir_merged = file.path(libFolder(df), "cov_RLE"),
    split.by.strand = TRUE,
    seq_info = seqinfo(df),
    weight = "score",
    verbose = TRUE
)
```

Arguments

df	an ORFik experiment, or NULL is allowed if both in_files and out_dir is spec- ified manually.	
in_files	paths to input files, default pshifted files: filepath(df, "pshifted") in ofst format	
out_dir	<pre>paths to output files, default file.path(libFolder(df), "cov_RLE_List").</pre>	
out_dir_merged	character vector of paths, default: file.path(libFolder(df), "cov_RLE"). Paths to merged output files, Set to NULL to skip making merged covRle.	
split.by.strand		
	logical, default TRUE, split into forward and reverse strand RleList inside cov-Rle object.	
seq_info	SeqInfo object, default seqinfo(findFa(df))	
weight	integer, numeric or single length character. Default "score". Use score column in loaded in_files.	
verbose	logical, default TRUE, message about library output status.	

54

Value

invisible(NULL), files saved to disc

See Also

Other lib_converters: convertLibs(), convert_bam_to_ofst(), convert_to_bigWig(), convert_to_covRle()

Examples

```
df <- ORFik.template.experiment()[10,]
## Usually do default folder, here we use tmpdir
folder_to_save <- file.path(tempdir(), "cov_RLE_List")
folder_to_save_merged <- file.path(tempdir(), "cov_RLE")
ORFik:::convert_to_covRleList(df, out_dir = folder_to_save,
out_dir_merged = folder_to_save_merged)
fimport(file.path(folder_to_save, "RFP_Mutant_rep2.covrds"))</pre>
```

convert_to_fstWig Convert to fstwig

Description

Will split files by chromosome for faster loading for now. This feature might change in the future!

Usage

```
convert_to_fstWig(
    df,
    in_files = filepath(df, "pshifted"),
    out_dir = file.path(libFolder(df), "fstwig"),
    split.by.strand = TRUE,
    split.by.readlength = FALSE,
    seq_info = seqinfo(df),
    weight = "score",
    is_pre_collapsed = FALSE,
    verbose = TRUE
)
```

df	an ORFik experiment, or NULL is allowed if both in_files and out_dir is spec- ified manually.
in_files	paths to input files, default pshifted files: filepath(df, "pshifted") in ofst format
out_dir	paths to output files, default file.path(libFolder(df), "bigwig").
split.by.strand	
	logical, default TRUE, split into forward and reverse strand RleList inside cov-Rle object.
<pre>split.by.readle</pre>	ngth
	logical, default FALSE, split into files for each readlength, defined by read-Widths (x) for each file.

seq_info	SeqInfo object, default seqinfo(findFa(df))
weight	integer, numeric or single length character. Default "score". Use score column in loaded in_files.
is_pre_collapse	d
	logical, default FALSE. Have you already collapsed reads with collapse.by.scores so each positions is only in 1 GRanges object with a score column per readlength? Set to TRUE, only if you are sure, will give a speedup.
verbose	logical, default TRUE, message about library output status.

Value

invisible(NULL), files saved to disc

correlation.plots Correlation plots between all samples

Description

Get correlation plot of raw counts and/or log2(count + 1) over selected region in: c("mrna", "leaders", "cds", "trailers")

Note on correlation: Pearson correlation, using pairwise observations to fill in NA values for the covariance matrix.

Usage

```
correlation.plots(
    df,
    output.dir,
    region = "mrna",
    type = "fpkm",
    height = 400,
    width = 400,
    size = 0.15,
    plot.ext = ".pdf",
    complex.correlation.plots = TRUE,
    data_for_pairs = countTable(df, region, type = type),
    as_gg_list = FALSE,
    text_size = 4,
    method = c("pearson", "spearman")[1]
)
```

df	an ORFik experiment
output.dir	directory to save to, named : cor_plot, cor_plot_log2 and/or cor_plot_simple with either .pdf or .png
region	a character (default: mrna), make raw count matrices of whole mrnas or one of (leaders, cds, trailers)
type	which value to use, "fpkm", alternative "counts".

cor_plot

height	numeric, default 400 (in mm)
width	numeric, default 400 (in mm)
size	numeric, size of dots, default 0.15. Deprecated.
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".
complex.correla	ition.plots
	logical, default TRUE. Add in addition to simple correlation plot two compu- tationally heavy dots + correlation plots. Useful for deeper analysis, but takes longer time to run, especially on low-quality gpu computers. Set to FALSE to skip these.
data_for_pairs	a data.table from ORFik::countTable of counts wanted. Default is fpkm of all mRNA counts over all libraries.
as_gg_list	logical, default FALSE. Return as a list of ggplot objects instead of as a grob. Gives you the ability to modify plots more directly.
text_size	size of correlation numbers
method	c("pearson", "spearman")[1]

Value

invisible(NULL) / if as_gg_list is TRUE, return a list of raw plots.

cor_plot

Get correlation between columns

Description

Get correlation between columns

Usage

```
cor_plot(
    dt_cor,
    col = c(low = "blue", high = "red", mid = "white", na.value = "white"),
    limit = c(ifelse(min(dt_cor$Cor, na.rm = TRUE) < 0, -1, 0), 1),
    midpoint = mean(limit),
    label_name = "Pearson\nCorrelation",
    text_size = 4,
    legend.position = c(0.4, 0.7),
    legend.direction = "horizontal"
)</pre>
```

dt_cor	a data.table, with column Cor
col	colors c(low = "blue", high = "red", mid = "white", na.value = "white")
limit	<pre>default (-1, 1), defined by: c(ifelse(min(dt_cor\$Cor, na.rm = TRUE) < 0, -1, 0), 1)</pre>
midpoint	midpoint of correlation values in label coloring.

label_name	name of correlation method, default "Pearson Correlation" with newline after Pearson.	
text_size	size of correlation numbers	
legend.position		
	default c(0.4, 0.7), other: "top", "right",	
legend.directic	n	
	default "horizontal", or "vertical"	

Value

a ggplot (heatmap)

cor_table

Get correlation between columns

Description

Get correlation between columns

Usage

```
cor_table(
    dt,
    method = c("pearson", "spearman")[1],
    upper_triangle = TRUE,
    decimals = 2,
    melt = TRUE,
    na.rm.melt = TRUE
)
```

Arguments

dt	a data.table
method	c("pearson", "spearman")[1]
upper_triangle	logical, default TRUE. Make lower triangle values NA.
decimals	numeric, default 2. How many decimals for correlation
melt	logical, default TRUE.
na.rm.melt	logical, default TRUE. Remove NA values from melted table.

Value

a data.table with 3 columns, Var1, Var2 and Cor

countOverlapsW

Description

Similar to countOverlaps, but takes an optional weight column. This is usually the score column

Usage

countOverlapsW(query, subject, weight = NULL, ...)

Arguments

query	IRanges, IRangesList, GRanges, GRangesList object. Usually transcript a transcript region.
subject	GRanges, GRangesList, GAlignment or covRle, usually reads.
weight	(default: NULL), if defined either numeric or character name of valid meta col- umn in subject. If weight is single numeric, it is used for all. A normall weight is the score column given as weight = "score". GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. Ignored if subject is covRle.
	additional arguments passed to countOverlaps/findOverlaps

Value

a named vector of number of overlaps to subject weighted by 'weight' column.

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), disengagementScore(), distToCds(),
distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
countTable
```

Description

Used to quickly load pre-created read count tables to R.

If df is experiment: Extracts by getting /QC_STATS directory, and searching for region Requires ORFikQC to have been run on experiment, to get default count tables!

Usage

```
countTable(
  df,
  region = "mrna",
  type = "count",
  collapse = FALSE,
  count.folder = "default"
)
```

Arguments

df	an ORFik experiment or path to folder with countTable, use path if not same folder as experiment libraries. Will subset to the count tables specified if df is experiment. If experiment has 4 rows and you subset it to only 2, then only those 2 count tables will be outputted.
region	a character vector (default: "mrna"), make raw count matrices of whole mrnas or one of (leaders, cds, trailers).
type	character, default: "count" (raw counts matrix). Which object type and normal- ization do you want ? "summarized" (SummarizedExperiment object), "deseq" (Deseq2 experiment, design will be all valid non-unique columns except repli- cates, change by using DESeq2::design, normalization alternatives are: "fpkm", "log2fpkm" or "log10fpkm".
collapse	a logical/character (default FALSE), if TRUE all samples within the group SAM- PLE will be collapsed to one. If "all", all groups will be merged into 1 col- umn called merged_all. Collapse is defined as rowSum(elements_per_group) / ncol(elements_per_group)
count.folder	character, default "auto" (Use count tables from original bam files stored in "QC_STATS", these are like HTseq count tables). To load your custome count tables from pshifted reads, set to "pshifted" (remember to create the pshifted tables first!). If you have custom ranges, like reads over uORFs stored in a folder called "/uORFs" relative to the bam files, set to "uORFs". Always create these custom count tables with makeSummarizedExperimentFromBam. Always make the location of the folder directly inside the bam file directory!

Details

If df is path to folder: Loads the file in that directory with the regex region.rds, where region is what is defined by argument, if multiple exist, see if any start with "countTable_", if so, subset. If loaded as SummarizedExperiment or deseq, the colData will be made from ORFik.experiment information.

countTable_regions

Value

a data.table/SummarizedExperiment/DESeq object of columns as counts / normalized counts per library, column name is name of library. Rownames must be unique for now. Might change.

See Also

Other countTable: countTable_regions()

Examples

```
# Make experiment
df <- ORFik.template.experiment()</pre>
# Make QC report to get counts ++ (not needed for this template)
# ORFikQC(df)
# Get count Table of mrnas
# countTable(df, "mrna")
# Get count Table of cds
# countTable(df, "cds")
# Get count Table of mrnas as fpkm values
# countTable(df, "mrna", type = "count")
# Get count Table of mrnas with collapsed replicates
# countTable(df, "mrna", collapse = TRUE)
# Get count Table of mrnas as summarizedExperiment
# countTable(df, "mrna", type = "summarized")
# Get count Table of mrnas as DESeg2 object,
# for differential expression analysis
# countTable(df, "mrna", type = "deseq")
```

countTable_regions Make a list of count matrices from experiment

Description

By default will make count tables over mRNA, leaders, cds and trailers for all libraries in experiment. region

```
countTable_regions(
    df,
    out.dir = libFolder(df),
    longestPerGene = FALSE,
    geneOrTxNames = "tx",
    regions = c("mrna", "leaders", "cds", "trailers"),
    type = "count",
    lib.type = "ofst",
    weight = "score",
    rel.dir = "QC_STATS",
    forceRemake = FALSE,
    library.names = bamVarName(df),
    BPPARAM = bpparam()
)
```

Arguments

df	an ORFik experiment
out.dir	character, output directory, default: resFolder(df). Will make a folder within this called "QC_STATS" with all results in this directory. Warning: If you assign not default path, you will have a hazzle to load files later. Much easier to load count tables, statistics, ++ later with default. Update resFolder of df instead if needed.
longestPerGene	a logical (default FALSE), if FALSE all transcript isoforms per gene. Ignored if "region" is not a character of either: "mRNA", "tx", "cds", "leaders" or "trailers".
geneOrTxNames	a character vector (default "tx"), should row names keep trancript names ("tx") or change to gene names ("gene")
regions	a character vector, default: c("mrna", "leaders", "cds", "trailers"), make raw count matrices of whole regions specified. Can also be a custom GRangesList of for example uORFs or a subset of cds etc.
type	default: "count" (raw counts matrix), alternative is "fpkm", "log2fpkm" or "log10fpkm"
lib.type	a character(default: "default"), load files in experiment or some precomputed variant, either "ofst", "bedo", "bedoc" or "pshifted". These are made with OR-Fik:::convertLibs() or shiftFootprintsByExperiment(). Can also be custom user made folders inside the experiments bam folder.
weight	numeric or character, a column to score overlaps by. Default "score", will check for a metacolumn called "score" in libraries. If not found, will not use weights.
rel.dir	relative output directory for out.dir, default: "QC_STATS". For pshifted, write "pshifted".
forceRemake	logical, default FALSE. If TRUE, will not look for existing file count table files.
library.names	character, default: bamVarName(df). Names to load libraries as to environment and names to display in plots.
BPPARAM	how many cores/threads to use? default: bpparam()
type lib.type weight rel.dir forceRemake library.names BPPARAM	of for example uORFs or a subset of cds etc. default: "count" (raw counts matrix), alternative is "fpkm", "log2fpkm" or "log10fpkn a character(default: "default"), load files in experiment or some precomputed variant, either "ofst", "bedo", "bedoc" or "pshifted". These are made with OR- Fik:::convertLibs() or shiftFootprintsByExperiment(). Can also be custom user made folders inside the experiments bam folder. numeric or character, a column to score overlaps by. Default "score", will check for a metacolumn called "score" in libraries. If not found, will not use weights. relative output directory for out.dir, default: "QC_STATS". For pshifted, write "pshifted". logical, default FALSE. If TRUE, will not look for existing file count table files. character, default: bamVarName(df). Names to load libraries as to environment and names to display in plots. how many cores/threads to use? default: bpparam()

Value

a list of data.table, 1 data.table per region. The regions will be the names the list elements.

See Also

Other countTable: countTable()

Examples

```
##Make experiment
df <- ORFik.template.experiment()
## Create count tables for all default regions
# countTable_regions(df)
## Pshifted reads (first create pshiftead libs)
# countTable_regions(df, lib.type = "pshifted", rel.dir = "pshifted")</pre>
```

coverageByTranscriptC coverageByTranscript with coverage input

Description

Extends the function with direct genome coverage input, see coverageByTranscript for original function.

Usage

```
coverageByTranscriptC(x, transcripts, ignore.strand = !strandMode(x))
```

Arguments

x	a covRle (one RleList for each strand in object), must have defined and correct seqlengths in its SeqInfo object.
transcripts	GRangesList
ignore.strand	a logical (default: $length(x) == 1$)

Value

Integer Rle of coverage, 1 per transcript

coverageByTranscriptW coverageByTranscript with weights

Description

Extends the function with weights, see coverageByTranscript for original function.

Usage

```
coverageByTranscriptW(
    x,
    transcripts,
    ignore.strand = FALSE,
    weight = 1L,
    seqinfo.x.is.correct = FALSE
)
```

х	reads (GRanges, GAlignments)
transcripts	GRangesList
ignore.strand	a logical (default: FALSE)
weight	a vector (default: 1L), if single number applies for all, else it must be the string name of a defined meta column in "x", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment was found 5 times.

coverageHeatMap

seqinfo.x.is.correct

logical, default FALSE. If you know x, has correct sequinfo, then you can save some computation time by setting this to TRUE.

Value

Integer Rle of coverage, 1 per transcript

coverageGroupings Get grouping for a coverage table in ORFik

Description

Either of two groupings: GF: Gene, fraction FGF: Fraction, position, feature It finds which of these exists, and auto groups

Usage

```
coverageGroupings(logicals, grouping = "GF")
```

Arguments

logicals	size 2 logical vector, the is.null checks for each column,
grouping	which grouping to perform, default "GF" Gene & Fraction grouping. Alternative "FGF", Fraction & position & feature.

Details

Normally not used directly!

Value

a quote of the grouping to pass to data.table

coverageHeatMap Create a heatmap of coverage

Description

Creates a ggplot representing a heatmap of coverage:

- Rows : Position in region
- · Columns : Read length
- Index intensity : (color) coverage scoring per index.

Coverage rows in heat map is fraction, usually fractions is divided into unique read lengths (standard Illumina is 76 unique widths, with some minimum cutoff like 15.) Coverage column in heat map is score, default zscore of counts. These are the relative positions you are plotting to. Like +/- relative to TIS or TSS.

64

coverageHeatMap

Usage

```
coverageHeatMap(
  coverage,
  output = NULL,
  scoring = "zscore",
  legendPos = "right",
  addFracPlot = FALSE,
  xlab = "Position relative to start site",
  ylab = "Protected fragment length",
  colors = "default",
  title = NULL,
  increments.y = "auto",
  gradient.max = max(coverage$score)
)
```

Arguments

coverage	a data.table, e.g. output of scaledWindowCoverage
output	character string (NULL), if set, saves the plot as pdf or png to path given. If no format is given, is save as pdf.
scoring	character vector, default "zscore", Which scoring did you use to create? either of zscore, transcriptNormalized, sum, mean, median, see ?coverageScorings for info and more alternatives.
legendPos	a character, Default "right". Where should the fill legend be ? ("top", "bottom", "right", "left")
addFracPlot	Add margin histogram plot on top of heatmap with fractions per positions
xlab	the x-axis label, default "Position relative to start site"
ylab	the y-axis label, default "Protected fragment length"
colors	character vector, default: "default", this gives you: c("white", "yellow2", "yellow3", "lightblue", "blue", "navy"), do "high" for more high contrasts, or specify your own colors.
title	a character, default NULL (no title), what is the top title of plot?
increments.y	increments of y axis, default "auto". Or a numeric value < max position & > min position.
gradient.max	numeric, defualt: max(coverage\$score). What data value should the top color be ? Good to use if you want to compare 2 samples, with the same color intensity, in that case set this value to the max score of the 2 coverage tables.

Details

Colors: Remember if you want to change anything like colors, just return the ggplot object, and reassign like: obj + scale_color_brewer() etc. Standard colors are:

- 0 reads in whole readlength :gray
- few reads in position :white
- medium reads in position :yellow
- many reads in position :dark blue

Value

a ggplot object of the coverage plot, NULL if output is set, then the plot will only be saved to location.

See Also

```
Other heatmaps: heatMapL(), heatMapRegion(), heatMap_single()
Other coveragePlot: pSitePlot(), savePlot(), windowCoveragePlot()
```

Examples

```
# With top sum bar
coverageHeatMap(coverage, addFracPlot = TRUE)
# See vignette for more examples
```

coveragePerTiling Get coverage per group

Description

It tiles each GRangesList group to width 1, and finds hits per position.

A range from 1:5 will split into c(1,2,3,4,5) and count hits on each. This is a safer speedup of coverageByTranscript from GenomicFeatures. It also gives the possibility to return as data.table, for faster computations.

Usage

```
coveragePerTiling(
  grl,
  reads,
  is.sorted = FALSE,
  keep.names = TRUE,
  as.data.table = FALSE,
  withFrames = FALSE,
  weight = "score",
  drop.zero.dt = FALSE,
  fraction = NULL
)
```

66

Arguments

grl	a GRangesList of 5' utrs, CDS, transcripts, etc.
reads	a GAlignments, GRanges, or precomputed coverage as covRle (one for each strand) of RiboSeq, RnaSeq etc. Weigths for scoring is default the 'score' column in 'reads'. Can also be random access paths to bigWig or fstwig file. Do not use random access for more than a few genes, then loading the entire files is usually better. File streaming is still in beta, so use with care!
is.sorted	logical (FALSE), is grl sorted. That is + strand groups in increasing ranges $(1,2,3)$, and - strand groups in decreasing ranges $(3,2,1)$
keep.names	logical (TRUE), keep names or not. If as.data.table is TRUE, names (genes column) will be a factor column, if FALSE it will be an integer column (index of gene), so first input grl element is 1. Dropping names gives ~ 20 % speedup. If drop.zero.dt is FALSE, data.table will not return names, will use index (to avoid memory explosion).
as.data.table	a logical (FALSE), return as data.table with 2 columns, position and count.
withFrames	a logical (FALSE), only available if as.data.table is TRUE, return the ORF frame, 1,2,3, where position 1 is 1, 2 is 2 and 4 is 1 etc.
weight	(default: 'score'), if defined a character name of valid meta column in subject. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count posi- tions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)
fraction	integer or character, a description column. Useful for grouping multiple outputs together. If returned as Rle, this is added as: metadata(coverage) <- list(fraction = fraction). If as.data.table it will be added as an additional column.

Details

NOTE: If reads contains a \$score column, it will presume that this is the number of replicates per reads, weights for the coverage() function. So delete the score column or set weight to something else if this is not wanted.

Value

a numeric RleList, one numeric-Rle per group with # of hits per position. Or data.table if as.data.table is TRUE, with column names c("count" [numeric or integer], "genes" [integer], "position" [integer])

See Also

Other ExtendGenomicRanges: asTX(), extendLeaders(), extendTrailers(), reduceKeepAttr(), tile1(), txSeqsFromFa(), windowPerGroup()

Examples

```
ORF <- GRanges(seqnames = "1",</pre>
               ranges = IRanges(start = c(1, 10, 20),
                                 end = c(5, 15, 25)),
               strand = "+")
grl <- GRangesList(tx1_1 = ORF)</pre>
RFP <- GRanges("1", IRanges(25, 25), "+")</pre>
coveragePerTiling(grl, RFP, is.sorted = TRUE)
# now as data.table with frames
coveragePerTiling(grl, RFP, is.sorted = TRUE, as.data.table = TRUE,
                  withFrames = TRUE)
# With score column (usually replicated reads on that position)
RFP <- GRanges("1", IRanges(25, 25), "+", score = 5)</pre>
dt <- coveragePerTiling(grl, RFP, is.sorted = TRUE,</pre>
                         as.data.table = TRUE, withFrames = TRUE)
class(dt$count) # numeric
# With integer score column (faster and less space usage)
RFP <- GRanges("1", IRanges(25, 25), "+", score = 5L)</pre>
dt <- coveragePerTiling(grl, RFP, is.sorted = TRUE,</pre>
                         as.data.table = TRUE, withFrames = TRUE)
class(dt$count) # integer
```

coverageScorings Add a coverage scoring scheme

Description

Different scorings and groupings of a coverage representation.

Usage

```
coverageScorings(coverage, scoring = "zscore", copy.dt = TRUE)
```

Arguments

coverage	a data.table containing at least columns (count, position), it is possible to have additionals: (genes, fraction, feature)
scoring	a character, one of (zscore, transcriptNormalized, mean, median, sum, log2sum, log10sum, sumLength, meanPos and frameSum, periodic, NULL). More info in details
copy.dt	logical TRUE, copy object, to avoid overwriting original object. Set to false to run function using reference to object, a speed up if original object is not needed.

Details

Usually output of metaWindow or scaledWindowPositions is input in this function.

Content of coverage data.table: It must contain the count and position columns.

genes column: If you have multiple windows, the genes column must define which gene/transcript grouping the different counts belong to. If there is only a meta window or only 1 gene/transcript, then this column is not needed.

68

coverageScorings

fraction column: If you have coverage of i.e RNA-seq and Ribo-seq, or TCP -seq of large and small subunite, divide into fractions. Like factor(RNA, RFP)

feature column: If gene group is subdivided into parts, like gene is transcripts, and feature column can be c(leader, cds, trailer) etc.

Given a data.table coverage of counts, add a scoring scheme. per: the grouping given, if genes is defined, group by per gene in default scoring. Scorings:

- zscore (count-windowMean)/windowSD per)
- transcriptNormalized (sum(count / sum of counts per))
- mean (mean(count per))
- median (median(count per))
- sum (count per)
- log2sum (count per)
- log10sum (count per)
- sumLength (count per) / number of windows
- meanPos (mean per position per gene) used in scaledWindowPositions
- sumPos (sum per position per gene) used in scaledWindowPositions
- frameSum (sum per frame per gene) used in ORFScore
- frameSumPerL (sum per frame per read length)
- frameSumPerLG (sum per frame per read length per gene)
- fracPos (fraction of counts per position per gene)
- periodic (Fourier transform periodicity of meta coverage per fraction)
- NULL (no grouping, return input directly)

Value

a data.table with new scores (size dependent on score used)

See Also

Other coverage: metaWindow(), regionPerReadLength(), scaledWindowPositions(), windowPerReadLength()

Examples

coverage_to_dt

Description

Convert coverage RleList to data.table

Usage

```
coverage_to_dt(
  coverage,
  keep.names = TRUE,
  withFrames = FALSE,
  weight = "score",
  drop.zero.dt = FALSE,
  fraction = NULL
)
```

Arguments

coverage	RleList with names
keep.names	logical (TRUE), keep names or not. If as.data.table is TRUE, names (genes column) will be a factor column, if FALSE it will be an integer column (index of gene), so first input grl element is 1. Dropping names gives ~ 20 % speedup. If drop.zero.dt is FALSE, data.table will not return names, will use index (to avoid memory explosion).
withFrames	a logical (FALSE), only available if as.data.table is TRUE, return the ORF frame, 1,2,3, where position 1 is 1, 2 is 2 and 4 is 1 etc.
weight	(default: 'score'), if defined a character name of valid meta column in subject. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count posi- tions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)
fraction	integer or character, a description column. Useful for grouping multiple outputs together. If returned as Rle, this is added as: metadata(coverage) <- list(fraction = fraction). If as.data.table it will be added as an additional column.

Value

a data.table with column names c("count" [numeric or integer], "genes" [integer], "position" [integer])

covRle

Description

Coverage Rlelist for both strands

Usage

```
covRle(forward = RleList(), reverse = RleList())
```

Arguments

forward	a RleList with defined seqinfo for forward strand counts
reverse	a RleList with defined seqinfo for reverse strand counts

Value

a covRle object

See Also

Other covRLE: covRle-class, covRleFromGR(), covRleList, covRleList-class

Examples

```
covRle()
covRle(RleList(), RleList())
chr_rle <- RleList(chr1 = Rle(c(1,2,3), c(1,2,3)))
covRle(chr_rle, chr_rle)</pre>
```

covRle-class Coverage Rle for both strands or single

Description

Given a run of coverage(x) where x are reads, this class combines the 2 strands into 1 object

Value

a covRLE object

See Also

Other covRLE: covRle, covRleFromGR(), covRleList, covRleList-class

covRleFromGR

Description

Convert GRanges to covRle

Usage

```
covRleFromGR(x, weight = "AUTO", ignore.strand = FALSE)
```

Arguments

x	a GRanges, GAlignment or GAlignmentPairs object. Note that coverage cal- culation for GAlignment is slower, so usually best to call convertToOneBase- dRanges on GAlignment object to speed it up.
weight	default "AUTO", pick 'score' column if exist, else all are 1L. Can also be a manually assigned meta column like 'score2' etc.
ignore.strand	logical, default FALSE.

Value

covRle object

See Also

Other covRLE: covRle, covRle-class, covRleList, covRleList-class

Examples
covRleList

Description

Coverage Rlelist for both strands

Usage

```
covRleList(list, fraction = names(list))
```

Arguments

list	a list or List of covRle objects of equal length and lengths
fraction	character, default names(list). Names to elements of list, can be integers, as readlengths etc.

Value

a covRleList object

See Also

Other covRLE: covRle, covRle-class, covRleFromGR(), covRleList-class

Examples

```
covRleList(List(covRle()))
```

covRleList-class List of covRle

Description

Given a run of coverage(x) where x are reads, this covRle combines the 2 strands into 1 object This list can again combine these into 1 object, with accession functions and generalizations.

Value

a covRleList object

See Also

Other covRLE: covRle, covRle-class, covRleFromGR(), covRleList

create.experiment Create an ORFik experiment

Description

Create a single R object that stores and controls all results relevant to a specific Next generation sequencing experiment. Click the experiment link above in the title if you are not sure what an ORFik experiment is.

By using files in a folder / folders. It will make an experiment table with information per sample, this object allows you to use the extensive API in ORFik that works on experiments.

Information Auto-detection:

There will be several columns you can fill in, when creating the object, if the files have logical names like (RNA-seq_WT_rep1.bam) it will try to auto-detect the most likely values for the columns. Like if it is RNA-seq or Ribo-seq, Wild type or mutant, is this replicate 1 or 2 etc.

You will have to fill in the details that were not auto detected. Easiest way to fill in the blanks are in a csv editor like libre Office or excel. You can also remake the experiment and specify the specific column manually. Remember that each row (sample) must have a unique combination of values. An extra column called "reverse" is made if there are paired data, like +/- strand wig files.

Usage

```
create.experiment(
  dir,
  exper,
  saveDir = ORFik::config()["exp"],
  txdb = "",
  fa = "",
  organism = ""
  assembly = ""
  pairedEndBam = FALSE,
  viewTemplate = FALSE,
  types = c("bam", "bed", "wig", "ofst"),
  libtype = "auto",
  stage = "auto",
  rep = "auto",
  condition = "auto",
  fraction = "auto",
  author = "",
  files = findLibrariesInFolder(dir, types, pairedEndBam),
  result_folder = NULL,
  runIDs = extract_run_id(files)
)
```

Arguments

```
dir
```

Which directory / directories to create experiment from, must be a directory with NGS data from your experiment. Will include all files of file type specified by "types" argument. So do not mix files from other experiments in the same folder!

exper	Short name of experiment. Will be name used to load experiment, and name shown when running list.experiments
saveDir	Directory to save experiment csv file, default: ORFik::config()["exp"], which has default: "~/Bio_data/ORFik_experiments/". Set to NULL if you don't want to save it to disc.
txdb	A path to TxDb (prefered) or gff/gtf (not adviced, slower) file with transcriptome annotation for the organism.
fa	A path to fasta genome/sequences used for libraries, remember the file must have a fasta index too.
organism	character, default: "" (no organism set), scientific name of organism. Homo sapiens, Danio rerio, Rattus norvegicus etc. If you have a SRA metadata csv file, you can set this argument to study\$ScientificName[1], where study is the SRA metadata for all files that was aligned.
assembly	character, default: "" (no assembly set). The genome assembly name, like GRCh38 etc. Useful to add if you want detailed metadata of experiment analysis.
pairedEndBam	logical FALSE, else TRUE, or a logical list of TRUE/FALSE per library you see will be included (run first without and check what order the files will come in) 1 paired end file, then two single will be $c(T, F, F)$. If you have a SRA metadata csv file, you can set this argument to study\$LibraryLayout == "PAIRED", where study is the SRA metadata for all files that was aligned.
viewTemplate	run View() on template when finished, default (FALSE). Usually gives you a better view of result than using print().
types	Default c("bam", "bed", "wig", "ofst"), which types of libraries to allow as NGS data.
libtype	character, default "auto". Library types, must be length 1 or equal length of number of libraries. "auto" means ORFik will try to guess from file names. Example: RFP (Ribo-seq), RNA (RNA-seq), CAGE, SSU (TCP-seq 40S), LSU (TCP-seq 80S).
stage	character, default "auto". Developmental stage, tissue or cell line, must be length 1 or equal length of number of libraries. "auto" means ORFik will try to guess from file names. Example: HEK293 (Cell line), Sphere (zebrafish stage), ovary (Tissue).
rep	character, default "auto". Replicate numbering, must be length 1 or equal length of number of libraries. "auto" means ORFik will try to guess from file names. Example: 1 (rep 1), 2 rep(2). Insert only numbers here!
condition	character, default "auto". Library conditions, must be length 1 or equal length of number of libraries. "auto" means ORFik will try to guess from file names. Example: WT (wild type), mutant, etc.
fraction	character, default "auto". Fractionation of library, must be length 1 or equal length of number of libraries. "auto" means ORFik will try to guess from file names. This columns is used to make experiment unique, if the other columns are not sufficient. Example: cyto (cytosolic fraction), dmso (dmso treated frac- tion), etc.
author	character, default "". Main author of experiment, usually last name is enough. When printing will state "author et al" in info.
files	character vector or data.table of library paths in dir. Default: findLibrariesInFolder(dir, types, pairedEndBam). Do not touch unless you want to do some subsetting,

	it will automatically remove files that are not of file format defined by 'type' argument. Note that sorting on number that: 10 is before 2, so 1, 2, 10, is sorted as: 1, 10, 2. If you want to fix this, you could update this argument with: ORFik:::findLibrariesInFolder()[1,3,2] to get order back to 1,2,10 etc.
result_folder	character, default NULL. The folder to output analysis results like QC, count tables etc. By default the libFolder(df) folder is used, the folder of first library in experiment. If you are making a new experiment which is a collection of other experiments, set this to a new folder, to not contaminate your other experiment directories.
runIDs	character ids, usually SRR, ERR, or DRR identifiers, default is to search for any of these 3 in the filename by: extract_run_id(files). They are optional.

a data.frame, NOTE: this is not a ORFik experiment, only a template for it!

See Also

Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(), bamVarName(), experiment-class, filepath(), libraryTypes(), organism, experiment-method, outputLibs(), read.experiment(), save.experiment(), validateExperiments()

Examples

```
# 1. Pick directory
dir <- system.file("extdata/Homo_sapiens_sample", "", package = "ORFik")</pre>
# 2. Pick an experiment name
exper <- "ORFik"</pre>
# 3. Pick .gff/.gtf location
txdb <- system.file("extdata/references/homo_sapiens",</pre>
                     "Homo_sapiens_dummy.gtf.db", package = "ORFik")
# 4. Pick fasta genome of organism
fa <- system.file("extdata/references/homo_sapiens",</pre>
                   "Homo_sapiens_dummy.fasta", package = "ORFik")
# 5. Set organism (optional)
org <- "Homo sapiens"</pre>
# Create temple not saved on disc yet:
template <- create.experiment(dir = dir, exper, txdb = txdb,</pre>
                               saveDir = NULL,
                               fa = fa, organism = org,
                               viewTemplate = FALSE)
## Now fix non-unique rows: either is libre office, microsoft excel, or in R
template$X5[6] <- "heart"</pre>
# read experiment (if you set correctly)
df <- read.experiment(template)</pre>
# Save with: save.experiment(df, file = "path/to/save/experiment.csv")
## Create and save experiment directly:
## Default location of experiments is ORFik::config()["exp"]
#template <- create.experiment(dir = dir, exper, txdb = txdb,</pre>
#
                                 fa = fa, organism = org,
#
                                 viewTemplate = FALSE)
## Custom location (If you work in a team, use a shared folder)
#template <- create.experiment(dir = dir, exper, txdb = txdb,</pre>
```

defineIsoform

#	<pre>saveDir = "~/MY/CUSTOME/LOCATION",</pre>
#	fa = fa, organism = org,
#	viewTemplate = FALSE)

```
defineIsoform
```

Overlaps GRanges object with provided annotations.

Description

Overlaps GRanges object with provided annotations.

Usage

```
defineIsoform(
  rel_orf,
  tran,
  isoform_names = c("perfect_match", "elong_START_match", "trunc_START_match",
      "elong_STOP_match", "trunc_STOP_match", "overlap_inside", "overlap_both",
      "overlap_upstream", "overlap_downstream", "upstream", "downstram", "none")
)
```

Arguments

rel_orf	- GRanges object of your ORF.
tran	- GRanges object of annotation (transcript or cds) that overlapped in some way rel_orf.
isoform_names	- A vector of strings that will be used instead of these defaults: 'perfect_match' - start and stop matches the tran object strand wise 'elong_START_match' - rel_orf is extension from the STOP side of the tran 'trunc_START_match' - rel_orf is truncation from the STOP side of the tran 'elong_STOP_match' - rel_orf is extension from the START side of the tran 'trunc_STOP_match' - rel_orf is truncation from the START side of the tran 'overlap_inside' - rel_orf is inside tran object 'overlap_both' - rel_orf contains tran object inside 'over- lap_upstream' - rel_orf is overlaping upstream part of the tran 'overlap_downstream' - rel_orf is overlaping downstream part of the tran 'upstream' - rel_orf is up- stream towards the tran 'downstream' - rel_orf is downstream towards the tran 'none' - when none of the above options is true

Value

A string object of defined isoform towards transcript.

```
defineTrailer
```

Description

Creates GRanges object as a trailer for ORFranges representing ORF, maintaining restrictions of transcriptRanges. Assumes that ORFranges is on the transcriptRanges, strands and seqlevels are in agreement. When lengthOFtrailer is smaller than space left on the transcript than all available space is returned as trailer.

Usage

```
defineTrailer(ORFranges, transcriptRanges, lengthOftrailer = 200)
```

Arguments

ORFranges GRanges object of your Open Reading Frame.

transcriptRanges

GRanges object of transtript.

lengthOftrailer

Numeric. Default is 10.

Details

It assumes that ORFranges and transcriptRanges are not sorted when on minus strand. Should be like: (200, 600) (50, 100)

Value

A GRanges object of trailer.

See Also

```
Other ORFHelpers: longestORFs(), mapToGRanges(), orfID(), startCodons(), startSites(),
stopCodons(), stopSites(), txNames(), uniqueGroups(), uniqueOrder()
```

Examples

DEG.analysis

Description

Expression analysis of 1 dimension, usually between conditions of RNA-seq. Using the standardized DESeq2 pipeline flow. Creates a DESeq model (given x is the target.contrast argument) (usually 'condition' column) 1. RNA-seq model: design = ~ x (differences between the x groups in RNA-seq)

Usage

```
DEG.analysis(
    df,
    target.contrast = design[1],
    design = ORFik::design(df),
    p.value = 0.05,
    counts = countTable(df, "mrna", type = "summarized"),
    batch.effect = TRUE,
    pairs = combn.pairs(unlist(df[, target.contrast]))
)
```

Arguments

df	an experiment of usually RNA-seq.	
target.contrast		
	a character vector, default design[1]. The column in the ORFik experiment that represent the comparison contrasts. By default: the first design factor of the full experimental design. This is the factor you will do the comparison on. DESeq will normalize the counts based on the full design, but the log fold change values will be based on this contrast only. It is usually the 'condition' column.	
design	a character vector, default design(df.rfp). The full experiment design. Which factors have more than 1 level. Example: stage column are all HEK293, so it can not be a design factor. The condition column has 2 possible values, WT and mutant, so it is a factor of the experiment. Replicates column is not part of design, that is inserted later with setting batch.effect = TRUE. Library type 'libtype' column, can also no be part of initial design, it is always added inside the function, after initial setup.	
p.value	a numeric, default 0.05 in interval (0,1). Defines adjusted p-value to be used as significance threshold for the result groups. I.e. for exclusive translation group significant subset for p.value = 0.05 means: TE\$padj < 0.05 & Ribo\$padj < 0.05 & RNA\$padj > 0.05.	
counts	a SummarizedExperiment, default: countTable(df, "mrna", type = "summa- rized"), all transcripts. Assign a subset if you don't want to analyze all genes. It is recommended to not subset, to give DESeq2 data for variance analysis.	
batch.effect	logical, default TRUE. Makes replicate column of the experiment part of the design. If you believe you might have batch effects, keep as TRUE. Batch effect usually means that you have a strong variance between biological replicates. Check	

DEC nl	lat a	ta	tic
DLO.pi	01.5	na	uc

	out pcaExperiment and see if replicates cluster together more than the design factor, to verify if you need to set it to TRUE.
pairs	<pre>list of character pairs, the experiment contrasts. Default: combn.pairs(unlist(df.rfp[, target.contrast])</pre>

Details

#' Analysis is done between each possible combination of levels in the target contrast If target contrast is the condition column, with factor levels: WT, mut1 and mut2 with 3 replicates each. You get comparison of WT vs mut1, WT vs mut2 and mut1 vs mut2.

The respective result categories are defined as: (given a user defined p value, shown here as 0.05): Significant - p-value adjusted < 0.05 (p-value cutoff decided by 'p.value argument)

The LFC values are shrunken by lfcShrink(type = "normal").

Remember that DESeq by default can not do global change analysis, it can only find subsets with changes in LFC!

Value

a data.table with columns: (contrast variable, gene id, regulation status, log fold changes, p.adjust values, mean counts)

References

doi: 10.1002/cpmb.108

See Also

Other DifferentialExpression: DEG.plot.static(), DEG_model(), DTEG.plot(), te.table(), te_rna.plot()

Examples

```
## Simple example (use ORFik template, then use only RNA-seq)
df <- ORFik.template.experiment()
df.rna <- df[df$libtype == "RNA",]
design(df.rna) # The full experimental design
design(df.rna)[1] # Default target contrast
#dt <- DEG.analysis(df.rna)</pre>
```

DEG.plot.static Plot DEG result

Description

Plot setup:

X-axis: mean counts Y-axis: Log2 fold changes For explanation of plot, see DEG. analysis

DEG.plot.static

Usage

```
DEG.plot.static(
    dt,
    output.dir = NULL,
    p.value.label = 0.05,
    plot.title = "",
    plot.ext = ".pdf",
    width = 6,
    height = 6,
    dot.size = 0.4,
    xlim = "auto",
    ylim = "bidir.max",
    relative.name = paste0("DEG_plot", plot.ext)
)
```

Arguments

dt	a data.table with the results from DEG.analysis
output.dir	a character path, default NULL(no save), or a directory to save to a file. Relative name of file, specified by 'relative.name' argument.
p.value.label	a numeric, default 0.05 in interval (0,1) or "" to not show. What p-value used for the analysis? Will be shown as a caption.
plot.title	title for plots, usually name of experiment etc
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".
width	numeric, default 6 (in inches)
height	numeric, default 6 (in inches)
dot.size	numeric, default 0.4, size of point dots in plot.
xlim	numeric vector or character preset, default: "bidir.max" (Equal in both + / - direction, using max value + 0.5 of meanCounts column in dt). If you want ggplot to decide limit, set to "auto". For numeric vector, specify min and max x limit: like $c(-5, 5)$
ylim	numeric vector or character preset, default: "bidir.max" (Equal in both + / - direction, using max value + 0.5 of LFC column in dt). If you want ggplot to decide limit, set to "auto". For numeric vector, specify min and max y limit: like $c(-10, 10)$
relative.name	character, Default: paste0("DEG_plot", plot.ext) Relative name of file to be saved in folder specified in output.dir. Change to .pdf if you want pdf file instead of png.

Value

a ggplot object

See Also

Other DifferentialExpression: DEG_model(), DTEG.analysis(), DTEG.plot(), te.table(), te_rna.plot()

Examples

```
df <- ORFik.template.experiment()
df.rna <- df[df$libtype == "RNA",]
#dt <- DEG.analysis(df.rna)
#Default scaling
#DEG.plot.static(dt)
#Manual scaling
#DEG.plot.static(dt, xlim = c(-2, 2), ylim = c(-2, 2))</pre>
```

DEG_model

Get DESeq2 model without running results

Description

This is the preparation step of DESeq2 analysis using ORFik::DEG.analysis. It is exported so that you can do this step in standalone, usually you want to use DEG.analysis directly.

Usage

```
DEG_model(
    df,
    target.contrast = design[1],
    design = ORFik::design(df),
    p.value = 0.05,
    counts = countTable(df, "mrna", type = "summarized"),
    batch.effect = TRUE
)
```

Arguments

df	an experiment of usually RNA-seq.
target.contrast	
	a character vector, default design[1]. The column in the ORFik experiment that represent the comparison contrasts. By default: the first design factor of the full experimental design. This is the factor you will do the comparison on. DESeq will normalize the counts based on the full design, but the log fold change values will be based on this contrast only. It is usually the 'condition' column.
design	a character vector, default design(df.rfp). The full experiment design. Which factors have more than 1 level. Example: stage column are all HEK293, so it can not be a design factor. The condition column has 2 possible values, WT and mutant, so it is a factor of the experiment. Replicates column is not part of design, that is inserted later with setting batch.effect = TRUE. Library type 'libtype' column, can also no be part of initial design, it is always added inside the function, after initial setup.
p.value	a numeric, default 0.05 in interval (0,1). Defines adjusted p-value to be used as significance threshold for the result groups. I.e. for exclusive translation group significant subset for p.value = 0.05 means: TE\$padj < 0.05 & Ribo\$padj < 0.05 & RNA\$padj > 0.05 .
counts	a SummarizedExperiment, default: countTable(df, "mrna", type = "summa- rized"), all transcripts. Assign a subset if you don't want to analyze all genes. It is recommended to not subset, to give DESeq2 data for variance analysis.

batch.effect logical, default TRUE. Makes replicate column of the experiment part of the design.
If you believe you might have batch effects, keep as TRUE. Batch effect usually means that you have a strong variance between biological replicates. Check out pcaExperiment and see if replicates cluster together more than the design factor, to verify if you need to set it to TRUE.

Value

a DESeqDataSet object with results stored as metadata columns.

See Also

```
Other DifferentialExpression: DEG.plot.static(), DTEG.analysis(), DTEG.plot(), te.table(),
te_rna.plot()
```

Examples

```
## Simple example (use ORFik template, then use only RNA-seq)
df <- ORFik.template.experiment()
df.rna <- df[df$libtype == "RNA",]
design(df.rna) # The full experimental design
target.contrast <- design(df.rna)[1] # Default target contrast
#ddsMat_rna <- DEG_model(df.rna, target.contrast)</pre>
```

DEG_model_results Get DESeq2 model results from DESeqDataSet

Description

Get DESeq2 model results from DESeqDataSet

Usage

```
DEG_model_results(ddsMat_rna, target.contrast, pairs, p.value = 0.05)
```

Arguments

ddsMat_rna	a DESeqDataSet object with results stored as metadata columns.
target.contrast	
	a character vector, default design[1]. The column in the ORFik experiment that represent the comparison contrasts. By default: the first design factor of the full experimental design. This is the factor you will do the comparison on. DESeq will normalize the counts based on the full design, but the log fold change values will be based on this contrast only. It is usually the 'condition' column.
pairs	<pre>list of character pairs, the experiment contrasts. Default: combn.pairs(unlist(df.rfp[target.contrast])</pre>
p.value	a numeric, default 0.05 in interval (0,1). Defines adjusted p-value to be used as significance threshold for the result groups. I.e. for exclusive translation group significant subset for p.value = 0.05 means: TE\$padj < 0.05 & Ribo\$padj < 0.05 & RNA\$padj > 0.05.

a data.table

Examples

```
## Simple example (use ORFik template, then use only RNA-seq)
df <- ORFik.template.experiment()
df.rna <- df[df$libtype == "RNA",]
design(df.rna) # The full experimental design
target.contrast <- design(df.rna)[1] # Default target contrast
#ddsMat_rna <- DEG_model(df.rna, target.contrast)
#pairs <- combn.pairs(unlist(df[, target.contrast]))
#dt <- DEG_model_results(ddsMat_rna, target.contrast, pairs)</pre>
```

DEG_model_simple Simple Fpkm ratio test DEG

Description

If you do not have a valid DESEQ2 experimental setup (contrast), you can use this simplified test

Usage

```
DEG_model_simple(
    df,
    target.contrast = design[1],
    design = ORFik::design(df),
    p.value = 0.05,
    counts = countTable(df, "mrna", type = "summarized"),
    batch.effect = FALSE
)
```

Arguments

df	an experiment of usually RNA-seq.
target.contrast	
	a character vector, default design[1]. The column in the ORFik experiment that represent the comparison contrasts. By default: the first design factor of the full experimental design. This is the factor you will do the comparison on. DESeq will normalize the counts based on the full design, but the log fold change values will be based on this contrast only. It is usually the 'condition' column.
design	a character vector, default design(df.rfp). The full experiment design. Which factors have more than 1 level. Example: stage column are all HEK293, so it can not be a design factor. The condition column has 2 possible values, WT and mutant, so it is a factor of the experiment. Replicates column is not part of design, that is inserted later with setting batch.effect = TRUE. Library type 'libtype' column, can also no be part of initial design, it is always added inside the function, after initial setup.
p.value	a numeric, default 0.05 in interval (0,1). Defines adjusted p-value to be used as significance threshold for the result groups. I.e. for exclusive translation group significant subset for p.value = 0.05 means: TE\$padj < 0.05 & Ribo\$padj < 0.05 & RNA\$padj > 0.05 .

counts	a SummarizedExperiment, default: countTable(df, "mrna", type = "summa- rized"), all transcripts. Assign a subset if you don't want to analyze all genes. It is recommended to not subset, to give DESeq2 data for variance analysis.
batch.effect	logical, default TRUE. Makes replicate column of the experiment part of the design. If you believe you might have batch effects, keep as TRUE. Batch effect usually means that you have a strong variance between biological replicates. Check out pcaExperiment and see if replicates cluster together more than the design factor, to verify if you need to set it to TRUE.

a data.table of fpkm ratios

Examples

```
## Simple example (use ORFik template, then use only RNA-seq)
df <- ORFik.template.experiment()
df <- df[df$libtype == "RNA",]
#dt <- DEG_model_simple(df)</pre>
```

```
design, experiment-method
```

Get experimental design Find the column/columns that create a separation between samples, by default skips replicate and choose first that is from either: libtype, condition, stage and fraction.

Description

Get experimental design Find the column/columns that create a separation between samples, by default skips replicate and choose first that is from either: libtype, condition, stage and fraction.

Usage

```
## S4 method for signature 'experiment'
design(
   object,
   batch.correction.design = FALSE,
   as.formula = FALSE,
   multi.factor = TRUE
)
```

Arguments

object	an ORFik experiment
batch.correcti	on.design
	logical, default FALSE. If true, add replicate as a second design factor (only if >= 2 replicates exists).
as.formula	logical, default FALSE. If TRUE, return as formula
multi.factor	logical, default TRUE If FALSE, return first factor only (+ rep, if batch.correction.design is true). Order of picking is: libtype, if not then: stage, if not then: condition, if not then: fraction.

a character (name of column) or a formula

Examples

```
df <- ORFik.template.experiment()
design(df) # The 2 columns that decides the design here
# If we subset it changes
design(df[df$libtype == "RFP",])
# Only single factor design, it picks first
design(df, multi.factor = FALSE)</pre>
```

detectRibosomeShifts Detect ribosome shifts

Description

Utilizes periodicity measurement (Fourier transform), and change point analysis to detect ribosomal footprint shifts for each of the ribosomal read lengths. Returns subset of read lengths and their shifts for which top covered transcripts follow periodicity measure. Each shift value assumes 5' anchoring of the reads, so that output offsets values will shift 5' anchored footprints to be on the p-site of the ribosome. The E-site will be shift + 3 and A site will be shift - 3. So update to these, if you rather want those.

Usage

```
detectRibosomeShifts(
  footprints,
  txdb,
  start = TRUE,
  stop = FALSE,
  top_tx = 10L,
 minFiveUTR = 30L,
 minCDS = 150L,
 minThreeUTR = if (stop) {
     30
 } else NULL,
  txNames = filterTranscripts(txdb, minFiveUTR, minCDS, minThreeUTR),
  firstN = 150L,
  tx = NULL,
 min_reads = 1000,
 min_reads_TIS = 50,
 accepted.lengths = 26:34,
 heatmap = FALSE,
 must.be.periodic = TRUE,
  strict.fft = TRUE,
  verbose = FALSE
)
```

Arguments

footprints	GAlignments object of RiboSeq reads - footprints, can also be path to the .bam /.ofst file. If GAlignment object has a meta column called "score", this will be used as replicate numbering for that read. So be careful if you have custom files with score columns, with another meaning.
txdb	a TxDb file, a path to one of: (.gtf ,.gff, .gff2, .gff2, .db or .sqlite) or an ORFik experiment
start	(logical) Whether to include predictions based on the start codons. Default TRUE.
stop	(logical) Whether to include predictions based on the stop codons. Default FASLE. Only use if there exists 3' UTRs for the annotation. If peridicity around stop codon is stronger than at the start codon, use stop instead of start region for p-shifting.
top_tx	(integer), default 10. Specify which % of the top TIS coverage transcripts to use for estimation of the shifts. By default we take top 10 top covered transcripts as they represent less noisy data-set. This is only applicable when there are more than 1000 transcripts.
minFiveUTR	(integer) minimum bp for 5' UTR during filtering for the transcripts. Set to NULL if no 5' UTRs exists for annotation.
minCDS	(integer) minimum bp for CDS during filtering for the transcripts
minThreeUTR	(integer) minimum bp for 3' UTR during filtering for the transcripts. Set to NULL if no 3' UTRs exists for annotation.
txNames	a character vector of subset of CDS to use. Default: txNames = filterTran- scripts(txdb, minFiveUTR, minCDS, minThreeUTR) Example: c("ENST1000005"), will use only that transcript (You should use at least 100!). Remember that top_tx argument, will by default specify to use top 10 % of those CDSs. Set that to 100, to use all these specified transcripts.
firstN	(integer) Represents how many bases of the transcripts downstream of start codons to use for initial estimation of the periodicity.
tx	a GRangesList, if you do not have 5' UTRs in annotation, send your own version. Example: extendLeaders(tx, 30) Where 30 bases will be new "leaders". Since each original transcript was either only CDS or non-coding (filtered out).
min_reads	default (1000), how many reads must a read-length have in total to be considered for periodicity.
min_reads_TIS	default (50), how many reads must a read-length have in the TIS region to be considered for periodicity.
accepted.length	ns
	accepted read lengths, default 26:34, usually ribo-seq is strongest between 27:32.
heatmap	a logical or character string, default FALSE. If TRUE, will plot heatmap of raw reads before p-shifting to console, to see if shifts given make sense. You can also set a filepath to save the file there.
must.be.periodi	ic
	logical TRUE, if FALSE will not filter on periodic read lengths. (The Fourier transform filter will be skipped). This is useful if you are not going to do periodicity analysis, that is for you more coverage donth (more read lengths) is useful.

icity analysis, that is: for you more coverage depth (more read lengths) is more important than only keeping the high quality periodic read lengths.

strict.fft	logical, TRUE. Use a FFT without noise filter. This means keep only reads lengths that are "periodic for the human eye". If you want more coverage, set to FALSE, to also get read lengths that are "messy", but the noise filter detects the periodicity of 3. This should only be done when you do not need high quality periodic reads! Example would be differential translation analysis by counts over each ORF.
verbose	logical, default FALSE. Report details of analysis/periodogram. Good if you are not sure if the analysis was correct.

Details

Check out vignette for the examples of plotting RiboSeq metaplots over start and stop codons, so that you can verify visually whether this function detects correct shifts.

For how the Fourier transform works, see: isPeriodic For how the changepoint analysis works, see: changePointAnalysis

NOTE: It will remove softclips from valid width, the CIGAR 3S30M is qwidth 33, but will remove 3S so final read width is 30 in ORFik. This is standard for ribo-seq.

Value

a data.table with lengths of footprints and their predicted coresponding offsets

References

https://bmcgenomics.biomedcentral.com/articles/10.1186/s12864-018-4912-6

See Also

Other pshifting: changePointAnalysis(), shiftFootprints(), shiftFootprintsByExperiment(), shiftPlots(), shifts_load(), shifts_save()

Examples

```
## Basic run
# Transcriptome annotation ->
gtf_file <- system.file("extdata/references/danio_rerio", "annotations.gtf", package = "ORFik")</pre>
# Ribo seq data ->
riboSeq_file <- system.file("extdata/Danio_rerio_sample", "ribo-seq.bam", package = "ORFik")</pre>
## Not run:
footprints <- readBam(riboSeq_file)</pre>
## Using CDS start site as reference point:
detectRibosomeShifts(footprints, gtf_file)
## Using CDS start site and stop site as 2 reference points:
#detectRibosomeShifts(footprints, gtf_file, stop = TRUE)
## Debug and detailed information for accepted reads lengths and p-site:
detectRibosomeShifts(footprints, gtf_file, heatmap = TRUE, verbose = TRUE)
## Debug why read length 31 was not accepted or wrong p-site:
#detectRibosomeShifts(footprints, gtf_file, must.be.periodic = FALSE,
#
               accepted.lengths = 31, heatmap = TRUE, verbose = TRUE)
## Subset bam file
param = ScanBamParam(flag = scanBamFlag(
                       isDuplicate = FALSE,
```

detect_ribo_orfs

```
## End(Not run)
```

detect_ribo_orfs Detect

Detect ORFs by Ribosome profiling data

Description

Finding all ORFs: 1. Find all ORFs in mRNA using ORFik findORFs, with defined parameters. To create the candidate ORFs (all ORFs returned): Steps (candidate set):

Define a candidate search set by these 3 rules: 1.a Allowed ORF type: uORF, NTE, etc (only keep these in candidate list)

1.b Must have at least x reads over whole orf (default 10 reads)

1.c Must have at least x reads over start site (default 3 reads)

The total list is defined by these names, and saved according to allowed ORF type/types.

To create the prediction status (TRUE/FALSE) per candidate

Steps (prediction status)

(UP_NT is a 20nt window upstream of ORF, that stops 2NT before ORF starts) :

1. ORF mean reads per NT > (UP_NT mean reads per NT * 1.3)

2. ORFScore > 2.5

3. TIS total reads + 3 > ORF median reads per NT

4. Given expression above, a TRUE prediction is defined with the AND operation: 1. & 2. & 3.

```
In code that is:
```

```
predicted <- (orfs_cov_stats$mean > upstream_cov_stats$mean*1.3) & orfs_cov_stats$ORFScores
> 2.5 & ((reads_start[candidates] + 3) > orfs_cov_stats$median)
```

Usage

```
mrna = loadRegion(df, "mrna"),
cds = loadRegion(df, "cds"),
libraries = outputLibs(df, type = "pshifted", output = "envirlist"),
orf_candidate_ranges = findORFs(seqs = txSeqsFromFa(mrna, df, TRUE), longestORF =
longestORF, startCodon = startCodon, stopCodon = stopCodon, minimumLength =
minimumLength),
export_metrics_table = TRUE,
longestORF = FALSE,
startCodon = startDefinition(1),
stopCodon = stopDefinition(1),
minimumLength = 0,
minimum_reads_ORF = 10,
minimum_reads_start = 3
)
```

Arguments

df	an ORFik experiment	
out_folder	Directory to save files	
ORF_categories_	_to_keep	
	<pre>options, any subset of: c("uORF", "uoORF", "annotated", "NTE", "NTT", "internal", "doORF", "dORF", "a_error").</pre>	
	• uORF: Upstream ORFs (Starting in 5' UTR), not overlapping CDS	
	• uoORF: Upstream ORFs (Starting in 5' UTR), overlapping CDS	
	• annotated: The defined CDS for that transcript	
	NTE: 5' Start codon extension of annotated CDS	
	NTT: 5' Start codon truncation of annotated CDS	
	 internal: Starting inside CDS, ending before CDS ends 	
	 doORF: Downstream ORFs (Ending in 3' UTR), overlapping CDS 	
	 dORF: Downstream ORFs (Ending in 3' UTR), not overlapping CDS 	
	• a_error: Any ORF detect not in the above categories	
prefix_result	<pre>the prefix name of output files to out_folder. Default: paste(c(ORF_categories_to_keep, gsub(" ", "_", organism(df))), collapse = "_")</pre>	
mrna	=loadRegion(df, "mrna")	
cds	=loadRegion(df, "cds")	
libraries	<pre>the ribo-seq libraries loaded into R as list, default: outputLibs(df, type = "pshifted", output = "envirlist")</pre>	
orf_candidate_r	ranges	
	<pre>IRangesList, = findORFs(seqs = txSeqsFromFa(mrna, df, TRUE),longestORF = longestORF, startCodon = startCodon, stopCodon = stopCodon,minimumLength = minimumLength)</pre>	
export_metrics_table		
	logical, default TRUE. Export table of statistics to file with suffix: "_predic- tion_table.rds"	
longestORF	(logical) Default TRUE. Keep only the longest ORF per unique stopcodon: (se- qname, strand, stopcodon) combination, Note: Not longest per transcript! You can also use function longestORFs after creation of ORFs for same result.	

startCodon	(character vector) Possible START codons to search for. Check startDefinition for helper function. Note that it is case sensitive, so "atg" would give 0 hits for a sequence with only capital "ATG" ORFs.
stopCodon	(character vector) Possible STOP codons to search for. Check stopDefinition for helper function. Note that it is case sensitive, so "tga" would give 0 hits for a sequence with only capital "TGA" ORFs.
minimumLength	(integer) Default is 0. Which is START + STOP = 6 bp. Minimum length of ORF, without counting 3bps for START and STOP codons. For example minimumLength = 8 will result in size of ORFs to be at least START + $8*3$ (bp) + STOP = 30 bases. Use this param to restrict search.
minimum_reads_ORF	
	numeric, default 10, orf removed if less reads overlap whole orf

minimum_reads_start

numeric, default 3, orf removed if less reads overlap start

Value

invisible(NULL), all ORF results saved to disc

Examples

```
# Pre requisites
# 1. Create ORFik experiment
# ORFik::create.experiment(...)
# 2. Create ORFik optimized annotation:
# makeTxdbFromGenome(gtf = ORFik:::getGtfPathFromTxdb(df), genome = df@fafile,
                        organism = organism(df), optimize = TRUE)
# 3. There must exist pshifted reads, either as default files, or in a relative folder called
# "./pshifted/". See ?shiftFootprintsByExperiment
# EXAMPLE:
df <- ORFik.template.experiment()</pre>
df <- df[df$libtype == "RFP",][c(1,2),]</pre>
result_folder <- riboORFsFolder(df, tempdir())</pre>
results <- detect_ribo_orfs(df, result_folder, c("uORF", "uoORF", "annotated", "NTE"))</pre>
# Load results of annotated ORFs
table <- riboORFs(df[1,], type = "table", result_folder)</pre>
table # See all statistics
sum(table$predicted) # How many were predicted as Ribo-seq ORFs
# Load 2 results
table <- riboORFs(df[1:2,], type = "table", result_folder)</pre>
table # See all statistics
sum(table$predicted) # How many were predicted as Ribo-seq ORFs
# Load GRangesList
candidates_gr <- riboORFs(df[1,], type = "ranges_candidates", result_folder)</pre>
prediction <- riboORFs(df[1,], type = "predictions", result_folder)</pre>
predicted_gr <- riboORFs(df[1:2,], type = "ranges_predictions", result_folder)</pre>
identical(predicted_gr[[1]], candidates_gr[[1]][prediction[[1]]])
## Inspect predictions in RiboCrypt
# library(RiboCrypt)
# Inspect Predicted
view <- predicted_gr[[1]][1]</pre>
#multiOmicsPlot_ORFikExp(view, df, view, leader_extension = 100, trailer_extension = 100)
```

```
# Inspect not predicted
view <- candidates_gr[[1]][!prediction[[1]]][1]
#multiOmicsPlot_ORFikExp(view, df, view, leader_extension = 100, trailer_extension = 100)</pre>
```

disengagementScore Disengagement score (DS)

Description

Disengagement score is defined as

(RPFs over ORF)/(RPFs downstream to transcript end)

A pseudo-count of one is added to both the ORF and downstream sums.

Usage

```
disengagementScore(
  grl,
  RFP,
  GtfOrTx,
  RFP.sorted = FALSE,
  weight = 1L,
  overlapGrl = NULL
)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs.
RFP	RiboSeq reads as GAlignments, GRanges or GRangesList object
GtfOrTx	If it is TxDb object transcripts will be extracted using exonsBy(Gtf, by = "tx", use.names = TRUE). Else it must be GRangesList
RFP.sorted	<pre>logical (FALSE), an optimizer, have you ran this line: RFP <- sort(RFP[countOverlaps(RFP, tx, type = "within") > 0]) Normally not touched, for internal optimization purposes.</pre>
weight	a vector (default: 1L, if 1L it is identical to countOverlaps()), if single number (!= 1), it applies for all, if more than one must be equal size of 'reads'. else it must be the string name of a defined meta column in subject "reads", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean "score" column tells that this alignment region was found 5 times.
overlapGrl	an integer, (default: NULL), if defined must be countOverlaps(grl, RFP), added for speed if you already have it

Value

a named vector of numeric values of scores

References

doi: 10.1242/dev.098344

distToCds

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), distToCds(),
distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

distToCds

Get distances between ORF ends and starts of their transcripts cds.

Description

Will calculate distance between each ORF end and begining of the corresponding cds (main ORF). Matching is done by transcript names. This is applicable practically to the upstream (fiveUTRs) ORFs only. The cds start site, will be presumed to be on + 1 of end of fiveUTRs.

Usage

distToCds(ORFs, fiveUTRs, cds = NULL)

Arguments

ORFs	orfs as GRangesList, names of orfs must be transcript names
fiveUTRs	fiveUTRs as GRangesList, remember to use CAGE version of 5' if you did CAGE reassignment!
cds	cds' as GRangesList, only add if you have ORFs going into CDS.

Value

an integer vector, +1 means one base upstream of cds, -1 means 2nd base in cds, 0 means orf stops at cds start.

References

doi: 10.1074/jbc.R116.733899

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
grl <- GRangesList(tx1_1 = GRanges("1", IRanges(1, 10), "+"))
fiveUTRs <- GRangesList(tx1 = GRanges("1", IRanges(1, 20), "+"))
distToCds(grl, fiveUTRs)</pre>
```

distToTSS Get distances between ORF Start and TSS of its transcript

Description

Matching is done by transcript names. This is applicable practically to any region in Transcript If ORF is not within specified search space in tx, this function will crash.

Usage

distToTSS(ORFs, tx)

Arguments

ORFs	orfs as GRangesList, names of orfs must be txname_[rank]
tx	transcripts as GRangesList.

Value

an integer vector, 1 means on TSS, 2 means second base of Tx.

References

doi: 10.1074/jbc.R116.733899

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
grl <- GRangesList(tx1_1 = GRanges("1", IRanges(5, 10), "+"))
tx <- GRangesList(tx1 = GRanges("1", IRanges(2, 20), "+"))
distToTSS(grl, tx)</pre>
```

download.ebi

Description

Uses ftp download from vol1 drive on EBI ftp server, for faster download of ERR, SRR or DRR files. But does not support subsetting or custom settings of files!

Usage

```
download.ebi(
    info,
    outdir,
    rename = TRUE,
    ebiDLMethod = "auto",
    timeout = 5000,
    BPPARAM = bpparam()
)
```

Arguments

info	character vector of only SRR numbers or a data.frame with SRA metadata information including the SRR numbers in a column called "Run" or "SRR". Can be SRR, ERR or DRR numbers. If only SRR numbers can not rename, since no additional information is given.
outdir	directory to store runs, files are named by default (rename = TRUE) by informa- tion from SRA metadata table, if (rename = FALSE) named according to SRR numbers.
rename	logical or character, default TRUE (Auto guess new names). False: Skip renam- ing. A character vector of equal size as files wanted can also be given. Priority of renaming from the metadata is to check for unique names in the Library- Name column, then the sample_title column if no valid names in LibraryName. If new names found and still duplicates, will add "_rep1", "_rep2" to make them unique. If no valid names, will not rename, that is keep the SRR numbers, you then can manually rename files to something more meaningful.
ebiDLMethod	character, default "auto". Which download protocol to use in download.file when using ebi ftp download. Sometimes "curl" is might not work (the default auto usually), in those cases use wget. See "method" argument of ?download.file, for more info.
timeout	5000, how many seconds before killing download if still active? Will overwrite global option until R session is closed. Increase value if you are on a very slow connection or downloading a large dataset.
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers

Value

character, full filepath of downloaded files

See Also

Other sra: browseSRA(), download.SRA(), download.SRA.metadata(), get_bioproject_candidates(),
install.sratoolkit(), rename.SRA.files()

download.SRA Download read libraries from SRA

Description

Multicore version download, see documentation for SRA toolkit for more information.

Usage

```
download.SRA(
    info,
    outdir,
    rename = TRUE,
    fastq.dump.path = install.sratoolkit(),
    settings = paste("--skip-technical", "--split-files"),
    subset = NULL,
    compress = TRUE,
    use.ebi.ftp = is.null(subset),
    ebiDLMethod = "auto",
    timeout = 5000,
    BPPARAM = bpparam()
)
```

Arguments

info	character vector of only SRR numbers or a data.frame with SRA metadata in- formation including the SRR numbers in a column called "Run" or "SRR". Can be SRR, ERR or DRR numbers. If only SRR numbers can not rename, since no additional information is given.
outdir	directory to store runs, files are named by default (rename = TRUE) by informa- tion from SRA metadata table, if (rename = FALSE) named according to SRR numbers.
rename	logical or character, default TRUE (Auto guess new names). False: Skip renam- ing. A character vector of equal size as files wanted can also be given. Priority of renaming from the metadata is to check for unique names in the Library- Name column, then the sample_title column if no valid names in LibraryName. If new names found and still duplicates, will add "_rep1", "_rep2" to make them unique. If no valid names, will not rename, that is keep the SRR numbers, you then can manually rename files to something more meaningful.
fastq.dump.path	1
	path to fastq-dump binary, default: path returned from install.sratoolkit()
settings	a string of arguments for fastq-dump, default: paste("-gzip", "-skip-technical", "-split-files")
subset	an integer or NULL, default NULL (no subset). If defined as a integer will download only the first n reads specified by subset. If subset is defined, will force to use fastq-dump which is slower than ebi download.

compress	logical, default TRUE. Download compressed files ".gz".
use.ebi.ftp	logical, default: is.null(subset). Use ORFiks much faster download function that only works when subset is null, if subset is defined, it uses fastqdump, it is slower but supports subsetting. Force it to use fastqdump by setting this to FALSE.
ebiDLMethod	character, default "auto". Which download protocol to use in download.file when using ebi ftp download. Sometimes "curl" is might not work (the default auto usually), in those cases use wget. See "method" argument of ?download.file, for more info.
timeout	5000, how many seconds before killing download if still active? Will overwrite global option until R session is closed. Increase value if you are on a very slow connection or downloading a large dataset.
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers

a character vector of download files filepaths

References

https://ncbi.github.io/sra-tools/fastq-dump.html

See Also

Other sra: browseSRA(), download.SRA.metadata(), download.ebi(), get_bioproject_candidates(),
install.sratoolkit(), rename.SRA.files()

Examples

SRR <- c("SRR453566") # Can be more than one

```
## Simple single SRR run of YEAST
outdir <- tempdir() # Specify output directory
# Download, get 5 first reads
#download.SRA(SRR, outdir, rename = FALSE, subset = 5)</pre>
```

```
## Using metadata column to get SRR numbers and to be able to rename samples
outdir <- tempdir() # Specify output directory
info <- download.SRA.metadata("SRP226389", outdir) # By study id
## Download, 5 first reads of each library and rename
#files <- download.SRA(info, outdir, subset = 5)
#Biostrings::readDNAStringSet(files[1], format = "fastq")
```

```
## Download full libraries of experiment
## (note, this will take some time to download!)
#download.SRA(info, outdir)
```

download.SRA.metadata Downloads metadata from SRA

Description

Given a experiment identifier, query information from different locations of SRA to get a complete metadata table of the experiment. It first finds Runinfo for each library, then sample info, if pubmed id is not found searches for that and searches for author through pubmed.

Usage

```
download.SRA.metadata(
   SRP,
   outdir = tempdir(),
   remove.invalid = TRUE,
   auto.detect = FALSE,
   abstract = "printsave",
   force = FALSE,
   rich.format = FALSE
)
```

Arguments

SRP	a string, a study ID as either the PRJ, SRP, ERP, DRPor GSE of the study, examples would be "SRP226389" or "ERP116106". If GSE it will try to convert to the SRP to find the files. The call works as long the runs are registered on the efetch server, as their is a linked SRP link from bioproject or GSE. Example which fails is "PRJNA449388", which does not have a linking like this.
outdir	directory to save file, default: tempdir(). The file will be called "SraRunInfo_SRP.csv", where SRP is the SRP argument. We advice to use bioproject IDs "PRJNA". The directory will be created if not existing.
remove.invalid	logical, default TRUE. Remove Runs with 0 reads (spots)
auto.detect	logical, default FALSE. If TRUE, ORFik will add additional columns:
	LIBRARYTYPE: (is this Ribo-seq or mRNA-seq, CAGE etc),
	REPLICATE: (is this replicate 1, 2 etc),
	STAGE: (Which time point, cell line or tissue is this, HEK293, TCP-1, 24hpf
	etc),
	CONDITION: (is this Wild type control or a mutant etc).
	These values are only qualified guesses from the metadata, so always double check!
abstract	character, default "printsave". If abstract for project exists, print and save it (save the file to same directory as runinfo). Alternatives: "print", Only print first time downloaded, will not be able to print later. save" save it, no print
	"no" skip download of abstract
force	logical, default FALSE. If TRUE, will redownload all files needed even though they exists. Useuful if you wanted auto.detection, but already downloaded without it.
rich.format	logical, default FALSE. If TRUE, will fetch all Experiment and Sample at- tributes. It means, that different studies can have different set of columns if set to TRUE.

Details

A common problem is that the project is not linked to an article, you will then not get a pubmed id.

The algorithm works like this:

If GEO identifier, find the SRP.

Then search Entrez for project and get sample identifier.

From that extract the run information and collect into a final table.

Value

a data.table of the metadata, 1 row per sample, SRR run number defined in 'Run' column.

References

doi: 10.1093/nar/gkq1019

See Also

```
Other sra: browseSRA(), download.SRA(), download.ebi(), get_bioproject_candidates(),
install.sratoolkit(), rename.SRA.files()
```

Examples

```
## Originally on SRA
download.SRA.metadata("SRP226389")
## Now try with auto detection (guessing additional library info)
## Need to specify output dir as tempfile() to re-download
#download.SRA.metadata("SRP226389", tempfile(), auto.detect = TRUE)
## Originally on ENA (RCP-seq data)
# download.SRA.metadata("ERP116106")
## Originally on GEO (GSE) (save to directory to keep info with fastq files)
# download.SRA.metadata("GSE61011")
## Bioproject ID
# download.SRA.metadata("PRJNA231536")
```

downstreamFromPerGroup

Get rest of objects downstream (inclusive)

Description

Per group get the part downstream of position. downstreamFromPerGroup(tx, startSites(threeUTRs, asGR = TRUE)) will return the 3' utrs per transcript as GRangesList, usually used for interesting parts of the transcripts.

Usage

```
downstreamFromPerGroup(
  tx,
   downstreamFrom,
   is.circular = all(isCircular(tx) %in% TRUE)
)
```

Arguments

tx	a GRangesList, usually of Transcripts to be changed
downstreamFrom	a vector of integers, for each group in tx, where is the new start point of first valid exon.
is.circular	logical, default FALSE if not any is: all(isCircular(grl) Where grl is the ranges checked. If TRUE, allow ranges to extend below position 1 on chromosome. Since circular genomes can have negative coordinates.

Details

If you don't want to include the points given in the region, use downstreamOfPerGroup

Value

a GRangesList of downstream part

See Also

Other GRanges: assignFirstExonsStartSite(), assignLastExonsStopSite(), downstreamOfPerGroup(),
upstreamFromPerGroup(), upstreamOfPerGroup()

downstreamN Restrict GRangesList

Description

Will restrict GRangesList to 'N' bp downstream from the first base.

Usage

```
downstreamN(grl, firstN = 150L)
```

Arguments

grl	(GRangesList)
firstN	(integer) Allow only this many bp downstream, maximum,

Value

a GRangesList of reads restricted to firstN and tiled by 1

downstreamOfPerGroup Get rest of objects downstream (exclusive)

Description

Per group get the part downstream of position. downstreamOfPerGroup(tx, stopSites(cds, asGR = TRUE)) will return the 3' utrs per transcript as GRangesList, usually used for interesting parts of the transcripts.

Usage

downstreamOfPerGroup(tx, downstreamOf)

Arguments

tx	a GRangesList, usually of Transcripts to be changed
downstreamOf	a vector of integers, for each group in tx, where is the new start point of first
	valid exon. Can also be a GRangesList, then stopsites will be used.

Details

If you want to include the points given in the region, use downstreamFromPerGroup

Value

a GRangesList of downstream part

See Also

Other GRanges: assignFirstExonsStartSite(), assignLastExonsStopSite(), downstreamFromPerGroup(), upstreamFromPerGroup(), upstreamOfPerGroup()

DTEG.analysis

Run differential TE analysis

Description

Expression analysis of 2 dimensions, usually Ribo-seq vs RNA-seq.

Using an equal reimplementation of the deltaTE algorithm (see reference).

Creates a total of 3 DESeq models (given x is the target.contrast argument) (usually 'condition' column) and libraryType is RNA-seq and Ribo-seq):

1. Ribo-seq model: design = $\sim x$ (differences between the x groups in Ribo-seq)

2. RNA-seq model: design = $\sim x$ (differences between the x groups in RNA-seq)

3. TE model: design = $\sim x + \text{libraryType} + \text{libraryType:x}$ (differences between the x and libraryType groups and the interaction between them)

You need at least 2 groups and 2 replicates per group. By default, the Ribo-seq counts will be over CDS and RNA-seq counts over whole mRNAs, per transcript.

Usage

```
DTEG.analysis(
  df.rfp,
  df.rna,
  output.dir = QCfolder(df.rfp),
  target.contrast = design[1],
  design = ORFik::design(df.rfp),
  p.value = 0.05,
  RFP_counts = countTable(df.rfp, "cds", type = "summarized"),
  RNA_counts = countTable(df.rna, "mrna", type = "summarized"),
  batch.effect = FALSE,
  pairs = combn.pairs(unlist(df.rfp[, design])),
  plot.title = "",
  plot.ext = ".pdf",
  width = 6,
  height = 6,
  dot.size = 0.4,
  relative.name = paste0("DTEG_plot", plot.ext),
  complex.categories = FALSE
)
```

Arguments

df.rfp	a experiment of usually Ribo-seq or 80S from TCP-seq. (the numerator of the experiment, usually having a primary role)
df.rna	a experiment of usually RNA-seq. (the denominator of the experiment, usually having a normalizing function)
output.dir	character, default QCfolder(df.rfp). output.dir directory to save plots, plot will be named "TE_between". If NULL, will not save.
target.contrast	
	a character vector, default design[1]. The column in the ORFik experiment that represent the comparison contrasts. By default: the first design factor of the full experimental design. This is the factor you will do the comparison on. DESeq will normalize the counts based on the full design, but the log fold change values will be based on this contrast only. It is usually the 'condition' column.
design	a character vector, default design(df.rfp). The full experiment design. Which factors have more than 1 level. Example: stage column are all HEK293, so it can not be a design factor. The condition column has 2 possible values, WT and mutant, so it is a factor of the experiment. Replicates column is not part of design, that is inserted later with setting batch.effect = TRUE. Library type 'libtype' column, can also no be part of initial design, it is always added inside the function, after initial setup.
p.value	a numeric, default 0.05 in interval (0,1). Defines adjusted p-value to be used as significance threshold for the result groups. I.e. for exclusive translation group significant subset for p.value = 0.05 means: TE\$padj < 0.05 & Ribo\$padj < 0.05 & RNA\$padj > 0.05.
RFP_counts	a SummarizedExperiment, default: countTable(df.rfp, "cds", type = "summarized") unshifted libraries, all transcript CDSs. If you have pshifted reads and countTa- bles, do: countTable(df.rfp, "cds", type = "summarized", count.folder = "pshifted") Assign a subset if you don't want to analyze all genes. It is rec- ommended to not subset, to give DESeq2 data for variance analysis.

RNA_counts	a SummarizedExperiment, default: countTable(df.rna, "mrna", type = "summa- rized"), all transcripts. Assign a subset if you don't want to analyze all genes. It is recommended to not subset, to give DESeq2 data for variance analysis.
batch.effect	logical, default TRUE. Makes replicate column of the experiment part of the design. If you believe you might have batch effects, keep as TRUE. Batch effect usually means that you have a strong variance between biological replicates. Check out pcaExperiment and see if replicates cluster together more than the design factor, to verify if you need to set it to TRUE.
pairs	<pre>list of character pairs, the experiment contrasts. Default: combn.pairs(unlist(df.rfp[, target.contrast])</pre>
plot.title	title for plots, usually name of experiment etc
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".
width	numeric, default 6 (in inches)
height	numeric, default 6 (in inches)
dot.size	numeric, default 0.4, size of point dots in plot.
relative.name	character, Default: paste0("DTEG_plot", plot.ext) Relative name of file to be saved in folder specified in output.dir. Change to .pdf if you want pdf file instead of png.
complex.categories	
	logical, default FALSE. Seperate into more groups, will add Inverse (opposite diagonal of mRNA abundance) and Expression (only significant mRNA-seq)

Details

Log fold changes and p-values are created from a Walds test on the comparison contrast described bellow. The RNA-seq and Ribo-seq LFC values are shrunken using DESeq2::lfcShrink(type = "normal"). Note that the TE LFC values are not shrunken (as following specifications from deltaTE paper)

Analysis is done between each possible combination of levels in the target contrast If target contrast is condition column, with factor levels: WT, mut1 and mut2 with 3 replicates each. You get comparison of WT vs mut1, WT vs mut2 and mut1 vs mut2.

The respective result categories are defined as: (given a user defined p value, shown here as 0.05):

- 1. Translation te.p.adj < 0.05 & rfp.p.adj < 0.05 & rna.p.adj > 0.05
- 2. mRNA abundance te.p.adj > 0.05 & rfp.p.adj < 0.05 & rna.p.adj > 0.05
- 3. Buffering te.p.adj < 0.05 & rfp.p.adj > 0.05 & rna.p.adj > 0.05

Buffering will be broken down into sub-categories if you set complex.categories = TRUE See Figure 1 in the reference article for a clear definition of the groups!

If you do not need isoform variants, subset to longest isoform per gene either before or in the returned object (See examples). If you do not have RNA-seq controls, you can still use DESeq on Ribo-seq alone.

The LFC values are shrunken by lfcShrink(type = "normal").

Remember that DESeq by default can not do global change analysis, it can only find subsets with changes in LFC!

a data.table with columns: (contrast variable, gene id, regulation status, log fold changes, p.adjust values, mean counts)

References

doi: 10.1002/cpmb.108

See Also

```
Other DifferentialExpression: DEG.plot.static(), DEG_model(), DTEG.plot(), te.table(),
te_rna.plot()
```

Examples

```
## Simple example (use ORFik template, then split on Ribo and RNA)
df <- ORFik.template.experiment()</pre>
df.rfp <- df[df$libtype == "RFP",]</pre>
df.rna <- df[df$libtype == "RNA"
                                   . 1
design(df.rfp) # The experimental design, per libtype
design(df.rfp)[1] # Default target contrast
#dt <- DTEG.analysis(df.rfp, df.rna)</pre>
## If you want to use the pshifted libs for analysis:
#dt <- DTEG.analysis(df.rfp, df.rna,</pre>
                      RFP_counts = countTable(df.rfp, region = "cds",
#
                         type = "summarized", count.folder = "pshifted"))
#
## Restrict DTEGs by log fold change (LFC):
## subset to abs(LFC) < 1.5 for both rfp and rna
#dt[abs(rfp) < 1.5 & abs(rna) < 1.5, Regulation := "No change"]</pre>
## Only longest isoform per gene:
#tx_longest <- filterTranscripts(df.rfp, 0, 1, 0)</pre>
#dt <- dt[id %in% tx_longest,]</pre>
## Convert to gene id
#dt[, id := txNamesToGeneNames(id, df.rfp)]
## To get by gene symbol, use biomaRt conversion
## To flip directionality of contrast pair nr 2:
#design <- "condition"</pre>
#pairs <- combn.pairs(unlist(df.rfp[, design])</pre>
#pairs[[2]] <- rev(pars[[2]])</pre>
#dt <- DTEG.analysis(df.rfp, df.rna,</pre>
#
                      RFP_counts = countTable(df.rfp, region = "cds",
#
                         type = "summarized", count.folder = "pshifted"),
#
                         pairs = pairs)
```

DTEG.plot

Plot DTEG result

Description

For explanation of plot catagories, see DTEG.analysis

DTEG.plot

Usage

```
DTEG.plot(
    dt,
    output.dir = NULL,
    p.value.label = 0.05,
    plot.title = "",
    plot.ext = ".pdf",
    width = 6,
    height = 6,
    dot.size = 0.4,
    xlim = "bidir.max",
    ylim = "bidir.max",
    relative.name = paste0("DTEG_plot", plot.ext)
)
```

Arguments

dt	a data.table with the results from DTEG.analysis
output.dir	a character path, default NULL(no save), or a directory to save to a file. Relative name of file, specified by 'relative.name' argument.
p.value.label	a numeric, default 0.05 in interval $(0,1)$ or "" to not show. What p-value used for the analysis? Will be shown as a caption.
plot.title	title for plots, usually name of experiment etc
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".
width	numeric, default 6 (in inches)
height	numeric, default 6 (in inches)
dot.size	numeric, default 0.4, size of point dots in plot.
xlim	numeric vector or character preset, default: "bidir.max" (Equal in both + / - direction, using max value + 0.5 of rna column in dt). If you want ggplot to decide limit, set to "auto". For numeric vector, specify min and max x limit: like $c(-5, 5)$
ylim	numeric vector or character preset, default: "bidir.max" (Equal in both + / - direction, using max value + 0.5 of rfp column in dt). If you want ggplot to decide limit, set to "auto". For numeric vector, specify min and max y limit: like $c(-10, 10)$
relative.name	character, Default: paste0("DTEG_plot", plot.ext) Relative name of file to be saved in folder specified in output.dir. Change to .pdf if you want pdf file instead of png.

Value

a ggplot object

See Also

```
Other DifferentialExpression: DEG.plot.static(), DEG_model(), DTEG.analysis(), te.table(),
te_rna.plot()
```

Examples

```
df <- ORFik.template.experiment()
df.rfp <- df[df$libtype == "RFP",]
df.rna <- df[df$libtype == "RNA",]
#dt <- DTEG.analysis(df.rfp, df.rna)
#Default scaling
#DTEG.plot(dt)
#Manual scaling
#DTEG.plot(dt, xlim = c(-2, 2), ylim = c(-2, 2))</pre>
```

entropy

Percentage of maximum entropy

Description

Calculates percentage of maximum entropy of the 'reads' coverage over each ORF in 'grl' group. The entropy value per group is a real number in the interval (0:1), where 0 indicates no variance in reads over all codons of group For example c(0,0,0,0) has 0 entropy, since no reads overlap. Interval: [0]: No reads or all reads in 1 place Interval: [0.01-0.99]: >= 2 positions covered Interval: [1]: all positions covered perfectly in frame

Usage

```
entropy(grl, reads, weight = 1L, is.sorted = FALSE, overlapGrl = NULL)
```

Arguments

grl	a GRangesList object can be either transcripts, 5' utrs, cds', 3' utrs or ORFs as a special case (uORFs, potential new cds' etc). If regions are not spliced you can send a GRanges object.
reads	a GAlignments, GRanges or GRangesList object, usually of RiboSeq, RnaSeq, CageSeq, etc.
weight	a vector (default: 1L, if 1L it is identical to countOverlaps()), if single number (!= 1), it applies for all, if more than one must be equal size of 'reads'. else it must be the string name of a defined meta column in subject "reads", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean "score" column tells that this alignment region was found 5 times.
is.sorted	logical (FALSE), is grl sorted. That is + strand groups in increasing ranges $(1,2,3)$, and - strand groups in decreasing ranges $(3,2,1)$
overlapGrl	an integer, (default: NULL), if defined must be countOverlaps(grl, RFP), added for speed if you already have it

Value

A numeric vector containing one entropy value per element in 'grl'

envExp

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
envExp
```

Get ORFik experiment environment

Description

More correctly, get the pointer reference, default is .GlobalEnv

Usage

envExp(x)

Arguments

x an ORFik experiment

Value

environment pointer, name of environment: pointer

envExp, experiment-method

Get ORFik experiment environment

Description

More correctly, get the pointer reference, default is .GlobalEnv

Usage

```
## S4 method for signature 'experiment'
envExp(x)
```

Arguments

x an ORFik experiment

Value

environment pointer, name of environment: pointer

envExp<-

Set ORFik experiment environment

Description

More correctly, set the pointer reference, default is .GlobalEnv

Usage

envExp(x) <- value</pre>

Arguments

Х	an ORFik experiment
value	environment pointer to assign to experiment

Value

an ORFik experiment with updated environment

Description

More correctly, set the pointer reference, default is .GlobalEnv

Usage

```
## S4 replacement method for signature 'experiment'
envExp(x) <- value</pre>
```

Arguments

х	an ORFik experiment
value	environment pointer to assign to experiment

Value

an ORFik experiment with updated environment
exists.ftp.dir.fast A fast ftp directory check

Description

Check if ftp directory exists

Usage

```
exists.ftp.dir.fast(url.dir, report.error = FALSE)
```

Arguments

url.dir	character, url to a ftp directory.
report.error	logical, FALSE. If TRUE, stop and report error.

Value

logical, TRUE if url directory exists

exists.ftp.file.fast A fast ftp file check

Description

Check if ftp file exists

Usage

```
exists.ftp.file.fast(url, report.error = FALSE)
```

Arguments

url	character, url to a ftp file
report.error	logical, FALSE. If TRUE, stop and report error.

Value

logical, TRUE if file exists

experiment-class experiment class definition

Description

It is an object that simplify and error correct your NGS workflow, creating a single R object that stores and controls all results relevant to a specific experiment. It contains following important parts:

- filepaths : and info for each library in the experiment (for multiple files formats: bam, bed, wig, ofst, ..)
- genome : annotation files of the experiment (fasta genome, index, gtf, txdb)
- organism : name (for automatic GO, sequence analysis..)
- description : and author information (list.experiments(), show all experiments you have made with ORFik, easy to find and load them later)
- API : ORFik supports a rich API for using the experiment, like outputLibs(experiment, type = "wig") will load all libraries converted to wig format into R, loadTxdb(experiment) will load the txdb (gtf) of experiment, transcriptWindow() will automatically plot metacoverage of all libraries in the experiment, countTable(experiment) will load count tables, etc..)
- Safety : It is also a safety in that it verifies your experiments contain no duplicate, empty or non-accessible files.

Act as a way of extension of SummarizedExperiment by allowing more ease to find not only counts, but rather information about libraries, and annotation, so that more tasks are possible. Like coverage per position in some transcript etc.

Constructor: Simplest way to make is to call:

create.experiment(dir)

On some folder with NGS libraries (usually bam files) and see what you get. Some of the fields might be needed to fill in manually. Each resulting row must be unique (not including filepath, they are always unique), that means if it has replicates then that must be said explicit. And all filepaths must be unique and have files with size > 0.

Here all the columns in the experiment will be described: name (column info): examples

libtype library type: rna-seq, ribo-seq, CAGE etc

stage stage or tissue: 64cell, Shield, HEK293

rep replicate: 1,2,3 etc

condition treatment or condition: : WT (wild-type), control, target, mzdicer, starved

fraction fraction of total: 18, 19 (TCP / RCP fractions), or other ways to split library.

filepath Full filepath to file

reverse optional: 2nd filepath or info, only used if paired files

experiment-class

Details

Special rules:

Supported:

Single/paired end bam, bed, wig, ofst + compressions of these

The reverse column of the experiments says "paired-end" if bam file. If a pair of wig files, forward and reverse strand, reverse is filepath to '-' strand wig file. Paired forward / reverse wig files, must have same name except _forward / _reverse in name

Paired end bam, when creating experiment, set pairedEndBam = c(T, T, T, F). For 3 paired end libraries, then one single end.

Naming: Will try to guess naming for tissues / stages, replicates etc. If it finds more than one hit for one file, it will not guess. Always check that it guessed correctly.

Value

a ORFik experiment

See Also

Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(), bamVarName(), create.experiment(), filepath(), libraryTypes(), organism, experiment-method, outputLibs(), read.experiment(), save.experiment(), validateExperiments()

Examples

```
## To see an internal ORFik example
df <- ORFik.template.experiment()</pre>
## See libraries in experiment
df
## See organism of experiment
organism(df)
## See file paths in experiment
filepath(df, "default")
## Output NGS libraries in R, to .GlobalEnv
#outputLibs(df)
## Output cds of experiment annotation
#loadRegion(df, "cds")
## This is how to make it:
## Not run:
library(ORFik)
# 1. Update path to experiment data directory (bam, bed, wig files etc)
exp_dir = "/data/processed_data/RNA-seq/Lee_zebrafish_2013/aligned/"
# 2. Set a short character name for experiment, (Lee et al 2013 -> Lee13, etc)
exper_name = "Lee13"
# 3. Create a template experiment (gtf and fasta genome)
temp <- create.experiment(exp_dir, exper_name, saveDir = NULL,</pre>
 txdb = "/data/references/Zv9_zebrafish/Danio_rerio.Zv9.79.gtf",
 fa = "/data/references/Zv9_zebrafish/Danio_rerio.Zv9.fa",
organism = "Homo sapiens")
# 4. Make sure each row(sample) is unique and correct
# You will get a view open now, check the data.frame that it is correct:
```

```
# library type (RNA-seq, Ribo-seq), stage, rep, condition, fraction.
# Let say it did not figure out it is RNA-seq, then we do:"
temp[5:6, 1] <- "RNA" # [row 5 and 6, col 1] are library types
# You can also do this in your spread sheet program (excel, libre office)
# Now save new version, if you did not use spread sheet.
saveName <- paste0("/data/processed_data/experiment_tables_for_R/",
exper_name,".csv")
save.experiment(temp, saveName)
# 5. Load experiment, this will validate that you actually made it correct
df <- read.experiment(saveName)
# Set experiment name not to be assigned in R variable names
df@expInVarName <- FALSE
df
## End(Not run)
```

experiment.colors Decide color for libraries by grouping

Description

Pick the grouping wanted for colors, by default only group by libtype. Like RNA-seq(skyblue4) and Ribo-seq(orange).

Usage

```
experiment.colors(
   df,
   color_list = "default",
   skip.libtype = FALSE,
   skip.stage = TRUE,
   skip.replicate = TRUE,
   skip.fraction = TRUE,
   skip.condition = TRUE
)
```

Arguments

df	an ORFik experiment
color_list	a character vector of colors, default "default". That is the vector c("skyblue4", 'orange', "green", "red", "gray", "yellow", "blue", "red2", "orange3"). Picks number of colors needed to make groupings have unique color
skip.libtype	a logical (FALSE), don't include libtype
skip.stage	a logical (FALSE), don't include stage in variable name.
<pre>skip.replicate</pre>	a logical (FALSE), don't include replicate in variable name.
skip.fraction	a logical (FALSE), don't include fraction
skip.condition	a logical (FALSE), don't include condition in variable name.

export.bed12

Value

a character vector of colors

export.bed12 Export as bed12 format

Description

bed format for multiple exons per group, as transcripts. Can be use as alternative as a sparse .gff format for ORFs. Can be direct input for ucsc browser or IGV

Usage

export.bed12(grl, file, rgb = 0)

Arguments

grl	A GRangesList
file	a character path to valid output file name
rgb	integer vector, default (0), either single integer or vector of same size as grl to specify groups. It is adviced to not use more than 8 different groups

Details

If grl has no names, groups will be named 1,2,3,4..

Value

NULL (File is saved as .bed)

See Also

```
Other utils: bedToGR(), convertToOneBasedRanges(), export.bigWig(), export.fstwig(),
export.wiggle(),fimport(),findFa(),fread.bed(),optimizeReads(),readBam(),readBigWig(),
readWig()
```

Examples

```
grl <- GRangesList(GRanges("1", c(1,3,5), "+"))
# export.bed12(grl, "output/path/orfs.bed")</pre>
```

export.bedo

Description

.bedo is .bed ORFik, an optimized bed format for coverage reads with read lengths .bedo is a text based format with columns (6 maximum):

- 1. chromosome
- 2. start
- 3. end
- 4. strand
- 5. ref width (cigar # M's, match/mismatch total)
- 6. duplicates of that read

Usage

export.bedo(object, out)

Arguments

object	a GRanges object
out	a character, location on disc (full path)

Details

Positions are 1-based, not 0-based as .bed. End will be removed if all ends equals all starts. Import with import.bedo

Value

NULL, object saved to disc

export.bedoc

Store GAlignments object as .bedoc

Description

A fast way to store, load and use bam files. (we now recommend using link{export.ofst} instead!)

.bedoc is .bed ORFik, an optimized bed format for coverage reads with cigar and replicate number. .bedoc is a text based format with columns (5 maximum):

- 1. chromosome
- 2. cigar: (cigar # M's, match/mismatch total)
- 3. start (left most position)
- 4. strand (+, -, *)
- 5. score: duplicates of that read

export.bigWig

Usage

export.bedoc(object, out)

Arguments

object	a GAlignments object
out	a character, location on disc (full path)

Details

Positions are 1-based, not 0-based as .bed. Import with import.bedoc

Value

NULL, object saved to disc

export.bigWig Export as bigWig format

Description

Will create 2 files, 1 for + strand (*_forward.bigWig) and 1 for - strand (*_reverse.bigWig). If all ranges are * stranded, will output 1 file. Can be direct input for ucsc browser or IGV

Usage

```
export.bigWig(
    x,
    file,
    split.by.strand = TRUE,
    is_pre_collapsed = FALSE,
    seq_info = seqinfo(x)
)
```

Arguments

x	A GRangesList, GAlignment GAlignmentPairs with score column. Will be converted to 5' end position of original range. If score column does not exist, will group ranges and give replicates as score column. Since bigWig needs a score column to represent counts!	
file	a character path to valid output file name	
split.by.strand		
	logical, default TRUE. Split bigWig into 2 files, one for each strand.	
<pre>is_pre_collapse</pre>	d	
	logical, default FALSE. Have you already collapsed reads with collapse.by.scores, so each positions is only in 1 GRanges object with a score column per readlength? Set to TRUE, only if you are sure, will give a speedup.	
seq_info	a Seqinfo object, default seqinfo(x). Must have non NA seqlengths defined!	

Value

invisible(NULL) (File is saved as 2 .bigWig files)

References

https://genome.ucsc.edu/goldenPath/help/bigWig.html

See Also

```
Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.fstwig(), export.wiggle(),
fimport(), findFa(), fread.bed(), optimizeReads(), readBam(), readBigWig(), readWig()
```

Examples

```
x <- c(GRanges("1", c(1,3,5), "-"), GRanges("1", c(1,3,5), "+"))
seqlengths(x) <- 10
file <- file.path(tempdir(), "rna.bigWig")
# export.bigWig(x, file)
# export.bigWig(covRleFromGR(x), file)</pre>
```

export.fstwig *Export as fstwig (fastwig) format*

Description

Will create 2 files, 1 for + strand (*_forward.fstwig) and 1 for - strand (*_reverse.fstwig). If all ranges are * stranded, will output 1 file.

Usage

```
export.fstwig(
    x,
    file,
    by.readlength = TRUE,
    by.chromosome = TRUE,
    compress = 50
)
```

Arguments

x	A GRangesList, GAlignment GAlignmentPairs with score column or coverage RLElist Will be converted to 5' end position of original range. If score column does not exist, will group ranges and give replicates as score column.
file	a character path to valid output file name
by.readlength	logical, default TRUE
by.chromosome	logical, default TRUE
compress	value in the range 0 to 100, indicating the amount of compression to use. Lower values mean larger file sizes. The default compression is set to 50.

export.ofst

Value

invisible(NULL) (File is saved as 2 .fstwig files)

References

"TODO"

See Also

```
Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.wiggle(),
fimport(), findFa(), fread.bed(), optimizeReads(), readBam(), readBigWig(), readWig()
```

Examples

```
x <- c(GRanges("1", c(1,3,5), "-"), GRanges("1", c(1,3,5), "+"))
x$size <- rep(c(28, 29), length.out = length(x))
x$score <- c(5,1,2,5,1,6)
seqlengths(x) <- 5
# export.fstwig(x, "~/Desktop/ribo")</pre>
```

```
export.ofst
```

Store GRanges / GAlignments object as .ofst

Description

A much faster way to store, load and use bam files.

.ofst is ORFik fast serialized object, an optimized format for coverage reads with cigar and replicate number. It uses the fst format as back-end: fst-package.

A .ofst ribo seq file can compress the information in a bam file from 5GB down to a few MB. This new files has super fast reading time, only a few seconds, instead of minutes. It also has random index access possibility of the file.

.ofst is represented as a data.frane format with minimum 4 columns:

- 1. chromosome
- 2. start (left most position)
- 3. strand (+, -, *)
- 4. width (not added if cigar exists)
- 5. cigar (not needed if width exists): (cigar # M's, match/mismatch total)
- 5. score: duplicates of that read
- 6. size: qwidth according to reference of read

If file is from GAlignmentPairs, it will contain a cigar1, cigar2 instead of cigar and start1 and start2 instead of start

Usage

export.ofst(x, file, ...)

Arguments

х	a GRanges, GAlignments or GAlignmentPairs object
file	a character, location on disc (full path)
	additional arguments for write_fst

Other columns can be named whatever you want and added to meta columns. Positions are 1-based, not 0-based as .bed. Import with import.ofst

Value

NULL, object saved to disc

Examples

```
## GRanges
gr <- GRanges("1:1-3:-")
# export.ofst(gr, file = "path.ofst")
## GAlignment
# Make input data.frame
df <- data.frame(seqnames = "1", cigar = "3M", start = 1L, strand = "+")
ga <- ORFik:::getGAlignments(df)
# export.ofst(ga, file = "path.ofst")</pre>
```

 $\verb+export.ofst, GAlignmentPairs-method+$

Store GRanges / GAlignments object as .ofst

Description

A much faster way to store, load and use bam files.

.ofst is ORFik fast serialized object, an optimized format for coverage reads with cigar and replicate number. It uses the fst format as back-end: fst-package.

A .ofst ribo seq file can compress the information in a bam file from 5GB down to a few MB. This new files has super fast reading time, only a few seconds, instead of minutes. It also has random index access possibility of the file.

.ofst is represented as a data.frane format with minimum 4 columns:

- 1. chromosome
- 2. start (left most position)
- 3. strand (+, -, *)
- 4. width (not added if cigar exists)
- 5. cigar (not needed if width exists): (cigar # M's, match/mismatch total)
- 5. score: duplicates of that read
- 6. size: qwidth according to reference of read

If file is from GAlignmentPairs, it will contain a cigar1, cigar2 instead of cigar and start1 and start2 instead of start

Usage

```
## S4 method for signature 'GAlignmentPairs'
export.ofst(x, file, ...)
```

Arguments

Х	a GRanges, GAlignments or GAlignmentPairs object
file	a character, location on disc (full path)
	additional arguments for write_fst

Other columns can be named whatever you want and added to meta columns. Positions are 1-based, not 0-based as .bed. Import with import.ofst

Value

NULL, object saved to disc

Examples

```
## GRanges
gr <- GRanges("1:1-3:-")
# export.ofst(gr, file = "path.ofst")
## GAlignment
# Make input data.frame
df <- data.frame(seqnames = "1", cigar = "3M", start = 1L, strand = "+")
ga <- ORFik:::getGAlignments(df)
# export.ofst(ga, file = "path.ofst")</pre>
```

export.ofst,GAlignments-method

Store GRanges / GAlignments object as .ofst

Description

A much faster way to store, load and use bam files.

.ofst is ORFik fast serialized object, an optimized format for coverage reads with cigar and replicate number. It uses the fst format as back-end: fst-package.

A .ofst ribo seq file can compress the information in a bam file from 5GB down to a few MB. This new files has super fast reading time, only a few seconds, instead of minutes. It also has random index access possibility of the file.

.ofst is represented as a data.frane format with minimum 4 columns:

- 1. chromosome
- 2. start (left most position)
- 3. strand (+, -, *)
- 4. width (not added if cigar exists)
- 5. cigar (not needed if width exists): (cigar # M's, match/mismatch total)
- 5. score: duplicates of that read
- 6. size: qwidth according to reference of read

If file is from GAlignmentPairs, it will contain a cigar1, cigar2 instead of cigar and start1 and start2 instead of start

Usage

```
## S4 method for signature 'GAlignments'
export.ofst(x, file, ...)
```

Arguments

х	a GRanges, GAlignments or GAlignmentPairs object
file	a character, location on disc (full path)
	additional arguments for write_fst

Other columns can be named whatever you want and added to meta columns. Positions are 1-based, not 0-based as .bed. Import with import.ofst

Value

NULL, object saved to disc

Examples

```
## GRanges
gr <- GRanges("1:1-3:-")
# export.ofst(gr, file = "path.ofst")
## GAlignment
# Make input data.frame
df <- data.frame(seqnames = "1", cigar = "3M", start = 1L, strand = "+")
ga <- ORFik:::getGAlignments(df)
# export.ofst(ga, file = "path.ofst")</pre>
```

export.ofst,GRanges-method

Store GRanges / GAlignments object as .ofst

Description

A much faster way to store, load and use bam files.

.ofst is ORFik fast serialized object, an optimized format for coverage reads with cigar and replicate number. It uses the fst format as back-end: fst-package.

A .ofst ribo seq file can compress the information in a bam file from 5GB down to a few MB. This new files has super fast reading time, only a few seconds, instead of minutes. It also has random index access possibility of the file.

.ofst is represented as a data.frane format with minimum 4 columns:

- 1. chromosome
- 2. start (left most position)
- 3. strand (+, -, *)
- 4. width (not added if cigar exists)
- 5. cigar (not needed if width exists): (cigar # M's, match/mismatch total)
- 5. score: duplicates of that read
- 6. size: qwidth according to reference of read

If file is from GAlignmentPairs, it will contain a cigar1, cigar2 instead of cigar and start1 and start2 instead of start

Usage

```
## S4 method for signature 'GRanges'
export.ofst(x, file, ...)
```

Arguments

х	a GRanges, GAlignments or GAlignmentPairs object
file	a character, location on disc (full path)
	additional arguments for write_fst

export.wiggle

Details

Other columns can be named whatever you want and added to meta columns. Positions are 1-based, not 0-based as .bed. Import with import.ofst

Value

NULL, object saved to disc

Examples

```
## GRanges
gr <- GRanges("1:1-3:-")
# export.ofst(gr, file = "path.ofst")
## GAlignment
# Make input data.frame
df <- data.frame(seqnames = "1", cigar = "3M", start = 1L, strand = "+")
ga <- ORFik:::getGAlignments(df)
# export.ofst(ga, file = "path.ofst")</pre>
```

export.wiggle Export as wiggle format

Description

Will create 2 files, 1 for + strand (*_forward.wig) and 1 for - strand (*_reverse.wig). If all ranges are * stranded, will output 1 file. Can be direct input for ucsc browser or IGV

Usage

export.wiggle(x, file)

Arguments

х	A GRangesList, GAlignment GAlignmentPairs with score column. Will be con-
	verted to 5' end position of original range. If score column does not exist, will
	group ranges and give replicates as score column.
file	a character path to valid output file name

Value

invisible(NULL) (File is saved as 2 .wig files)

References

https://genome.ucsc.edu/goldenPath/help/wiggle.html

See Also

```
Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.fstwig(),
fimport(), findFa(), fread.bed(), optimizeReads(), readBam(), readBigWig(), readWig()
```

Examples

```
x <- c(GRanges("1", c(1,3,5), "-"), GRanges("1", c(1,3,5), "+"))
# export.wiggle(x, "output/path/rna.wig")</pre>
```

extendLeaders

Extend the leaders transcription start sites.

Description

Will extend the leaders or transcripts upstream (5' end) by extension. The extension is general not relative, that means splicing will not be taken into account. Requires the grl to be sorted beforehand, use sortPerGroup to get sorted grl.

Usage

```
extendLeaders(
  grl,
  extension = 1000L,
  cds = NULL,
  is.circular = all(isCircular(grl) %in% TRUE)
)
```

Arguments

grl	usually a GRangesList of 5' utrs or transcripts. Can be used for any extension of groups.
extension	an integer, how much to extend upstream (5' end). Eiter single value that will apply for all, or same as length of grl which will give 1 update value per grl object. Or a GRangesList where start / stops by strand are the positions to use as new starts.
cds	a GRangesList of coding sequences, If you want to extend 5' leaders down- stream, to catch upstream ORFs going into cds, include it. It will add first cds exon to grl matched by names. Do not add for transcripts, as they are already included.
is.circular	logical, default FALSE if not any is: all(isCircular(grl) Where grl is the ranges checked. If TRUE, allow ranges to extend below position 1 on chromosome. Since circular genomes can have negative coordinates.

Value

an extended GRangeslist

See Also

```
Other ExtendGenomicRanges: asTX(), coveragePerTiling(), extendTrailers(), reduceKeepAttr(),
tile1(), txSeqsFromFa(), windowPerGroup()
```

extendsTSSexons

Examples

```
library(GenomicFeatures)
samplefile <- system.file("extdata", "hg19_knownGene_sample.sqlite",</pre>
                           package = "GenomicFeatures")
txdb <- loadDb(samplefile)</pre>
fiveUTRs <- fiveUTRsByTranscript(txdb, use.names = TRUE) # <- extract only 5' leaders</pre>
tx \le exonsBy(txdb, by = "tx", use.names = TRUE)
cds <- cdsBy(txdb,"tx",use.names = TRUE)</pre>
## extend leaders upstream 1000
extendLeaders(fiveUTRs, extension = 1000)
## now try(extend upstream 1000, add all cds exons):
extendLeaders(fiveUTRs, extension = 1000, cds)
## when extending transcripts, don't include cds' of course,
## since they are already there
extendLeaders(tx, extension = 1000)
## Circular genome (allow negative coordinates)
circular_fives <- fiveUTRs</pre>
isCircular(circular_fives) <- rep(TRUE, length(isCircular(circular_fives)))</pre>
extendLeaders(circular_fives, extension = 32672841L)
```

extendsTSSexons Extend first exon of each transcript with length specified

Description

Extend first exon of each transcript with length specified

Usage

extendsTSSexons(fiveUTRs, extension = 1000)

Arguments

fiveUTRs	The 5' leader sequences as GRangesList
extension	The number of basses to extend transcripts upstream

Value

GRangesList object of fiveUTRs

```
extendTrailers
```

Description

Will extend the trailers or transcripts downstream (3' end) by extension. The extension is general not relative, that means splicing will not be taken into account. Requires the grl to be sorted beforehand, use sortPerGroup to get sorted grl.

Usage

```
extendTrailers(
  grl,
  extension = 1000L,
  is.circular = all(isCircular(grl) %in% TRUE)
)
```

Arguments

grl	usually a ${\tt GRangesList}$ of 3' utrs or transcripts. Can be used for any extension of groups.
extension	an integer, how much to extend downstream (3' end). Eiter single value that will apply for all, or same as length of grl which will give 1 update value per grl object. Or a GRangesList where start / stops sites by strand are the positions to use as new starts.
is.circular	logical, default FALSE if not any is: all(isCircular(grl) Where grl is the ranges checked. If TRUE, allow ranges to extend below position 1 on chromosome. Since circular genomes can have negative coordinates.

Value

an extended GRangeslist

See Also

Other ExtendGenomicRanges: asTX(), coveragePerTiling(), extendLeaders(), reduceKeepAttr(), tile1(), txSeqsFromFa(), windowPerGroup()

Examples

```
isCircular(circular_three) <- rep(TRUE, length(isCircular(circular_three)))
extendTrailers(circular_three, extension = 126200008L)[41] # <- negative stop coordinate</pre>
```

extract_run_id Extract SRR/ERR/DRR run IDs from string

Description

Extract SRR/ERR/DRR run IDs from string

Usage

```
extract_run_id(
    x,
    search = "(SRR[0-9]+|DRR[0-9]+|ERR[0-9]+)",
    only_valid = FALSE
)
```

Arguments

х	character vector to search through.
search	the regex search, default: "(SRR[0-9]+ DRR[0-9]+ ERR[0-9]+)"
only_valid	logical, default FALSE. If TRUE, return only the hits.

Value

a character vector of run accepted run ids according to search, if only_valid named character vector for which indices are returned

Examples

```
search <- c("SRR1230123_absdb", "SRR1241204124_asdasd", "asd_ERR1231230213",
    "DRR12412412_asdqwe", "ASDASD_ASDASD", "SRRASDASD")
ORFik:::extract_run_id(search)
ORFik:::extract_run_id(search, only_valid = TRUE)
```

f

strandMode covRle

Description

```
strandMode covRle
```

Usage

f(x)

Arguments

x a covRle object

filepath

Value

the forward RleList

f, covRle-method *strandMode covRle*

Description

strandMode covRle

Usage

S4 method for signature 'covRle'
f(x)

Arguments

x a covRle object

Value

the forward RleList

filepath

Get filepaths to ORFik experiment

Description

If other type than "default" is given and that type is not found (and 'fallback' is TRUE), it will return you ofst files, if they do not exist, then default filepaths without warning.

Usage

```
filepath(
  df,
  type,
  basename = FALSE,
  fallback = type %in% c("pshifted", "bed", "ofst", "bedoc", "bedo"),
  suffix_stem = "AUTO",
  base_folders = libFolder(df)
)
```

filepath

Arguments

df	an ORFik experiment
type	a character(default: "default"), load files in experiment or some precomputed variant, like "ofst" or "pshifted". These are made with ORFik:::convertLibs(), shiftFootprintsByExperiment(), etc. Can also be custom user made folders in- side the experiments bam folder. It acts in a recursive manner with priority: If you state "pshifted", but it does not exist, it checks "ofst". If no .ofst files, it uses "default", which always must exists. Presets are (folder is relative to default lib folder, some types fall back to other formats if folder does not exist):
	- "default": load the original files for experiment, usually bam.
	default)
	- "pshifted": loads ofst, wig or bigwig from pshifted folder (falls back to ofst, then default)
	 - "cov": Load covRle objects from cov_RLE folder (fail if not found) - "covl": Load covRleList objects, from cov_RLE_List folder (fail if not found) - "bed": Load bed files, from bed folder (falls back to default) - Other formats must be loaded directly with fimport
basename	logical, default (FALSE). Get relative paths instead of full. Only use for inspection!
fallback	logical, default: type If TRUE, will use type fallback, see above for info.
suffix_stem	character, default "AUTO". Which is "" for all except type = "pshifted". Then it is "_pshifted" appended to end of names before format. Can be vector, then it searches suffixes in priority: so if you insert c("_pshifted", ""), it will look for suffix _pshifted, then the empty suffix.
base_folders	character vector, default libFolder(df), path to base folder to search for library variant directories. If single path (length == 1), it will apply to all libraries in df. If df is a collection, an experiment where libraries are put in different folders and library variants like pshifted are put inside those respective folders, set base_folders = libFolder(df, mode = "all")

Details

For pshifted libraries, if "pshifted" is specified as type: if if multiple formats exist it will use a priority: ofst -> bigwig -> wig -> bed. For formats outside default, all files must be stored in the directory of the first file: base_folder <- libFolder(df)

Value

a character vector of paths, or a list of character with 2 paths per, if paired libraries exists

See Also

Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(), bamVarName(), create.experiment(), experiment-class, libraryTypes(), organism, experiment-method, outputLibs(), read.experiment(), save.experiment(), validateExperiments()

Examples

df <- ORFik.template.experiment()</pre>

filterCage

```
filepath(df, "default")
# Subset
filepath(df[9,], "default")
# Other format path
filepath(df[9,], "ofst")
## If you have pshifted files, see shiftFootprintsByExperiment()
filepath(df[9,], "pshifted") # <- falls back to ofst</pre>
```

filterCage

Filter peak of cage-data by value

Description

Filter peak of cage-data by value

Usage

```
filterCage(cage, filterValue = 1, fiveUTRs = NULL, preCleanup = TRUE)
```

Arguments

cage	Either a filePath for the CageSeq file as .bed .bam or .wig, with possible com- pressions (".gzip", ".gz", ".bgz"), or already loaded CageSeq peak data as GRanges or GAlignment. NOTE: If it is a .bam file, it will add a score column by run- ning: convertToOneBasedRanges(cage, method = "5prime", addScoreColumn = TRUE) The score column is then number of replicates of read, if score column is something else, like read length, set the score column to NULL first.
filterValue	The minimum number of reads on cage position, for it to be counted as possible new tss. (represented in score column in CageSeq data) If you already filtered, set it to 0.
fiveUTRs	a GRangesList (NULL), if added will filter out cage reads by these following rules: all reads in region (-5:-1, 1:5) for each tss will be removed, removes noise.
preCleanup	logical (TRUE), if TRUE, remove all reads in region (-5:-1, 1:5) of all original tss in leaders. This is to keep original TSS if it is only +/- 5 bases from the original.

Value

the filtered GRanges object

filterExtremePeakGenes

Filter out transcript by a median filter

Description

For removing very extreme peaks in coverage plots, use high quantiles, like 99. Used to make your plots look better, by removing extreme peaks.

Usage

```
filterExtremePeakGenes(
    tx,
    reads,
    upstream = NULL,
    downstream = NULL,
    multiplier = "0.99",
    min_cutoff = "0.999",
    pre_filter_minimum = 0,
    average = "median"
)
```

Arguments

tx	a GRangesList	
reads	a GAlignments or GRanges	
upstream	numeric or NULL, default NULL. if you want window of tx, instead of whole, specify how much upstream from start of tx, 10 is include 10 bases before start	
downstream	numeric or NULL, default NULL. if you want window of tx, instead of whole, specify how much downstream from start of tx, 10 is go 10 bases into tx from start.	
multiplier	a character or numeric, default "0.99", either a quantile if input is string[0-1], like "0.99", or numeric value if input is numeric. How much bigger than median / mean counts per gene, must a value be to be defined as extreme ?	
min_cutoff	a character or numeric, default "0.999", either a quantile if input is string[0-1], like "0.999", or numeric value if input is numeric. Lowest allowed value	
pre_filter_minimum		
	numeric, default 0. If value is x, will remove all positions in all genes with coverage $< x$, before median filter is applied. Set to 1 to remove all 0 positions.	
average	character, default "median". Alternative: "mean". How to scale the multiplier argument, from median or mean of gene coverage.	

Value

GRangesList (filtered)

filterTranscripts Filter transcripts by lengths

Description

Filter transcripts to those who have leaders, CDS, trailers of some lengths, you can also pick the longest per gene.

Usage

```
filterTranscripts(
   txdb,
   minFiveUTR = 30L,
   minCDS = 150L,
   minThreeUTR = 30L,
   longestPerGene = TRUE,
   stopOnEmpty = TRUE,
   by = "tx",
   create.fst.version = FALSE
)
```

Arguments

txdb	a TxDb file or a path to one of: (.gtf ,.gff, .gff2, .gff2, .db or .sqlite), if it is a GRangesList, it will return it self.	
minFiveUTR	(integer) minimum bp for 5' UTR during filtering for the transcripts. Set to NULL if no 5' UTRs exists for annotation.	
minCDS	(integer) minimum bp for CDS during filtering for the transcripts	
minThreeUTR	(integer) minimum bp for 3' UTR during filtering for the transcripts. Set to NULL if no 3' UTRs exists for annotation.	
longestPerGene	logical (TRUE), return only longest valid transcript per gene. NOTE: This is by priority longest cds isoform, if equal then pick longest total transcript. So if transcript is shorter but cds is longer, it will still be the one returned.	
stopOnEmpty	logical TRUE, stop if no valid transcripts are found ?	
by	a character, default "tx" Either "tx" or "gene". What names to output region by, the transcript name "tx" or gene names "gene". NOTE: this is not the same as cdsBy(txdb, by = "gene"), cdsBy would then only give 1 cds per Gene, loadRe- gion gives all isoforms, but with gene names.	
create.fst.version		
	<pre>logical, FALSE. If TRUE, creates a .fst version of the transcript length table (if it not already exists), reducing load time from ~ 15 seconds to ~ 0.01 second next time you run filterTranscripts with this txdb object. The file is stored in the same folder as the genome this txdb is created from, with the name: paste0(ORFik:::remove.file_ext(metadata(txdb)[3,2]), "_", gsub(" \(.* :", "", metadata(txdb)[metadata(txdb)[,1] == "Creation time",2]), "_txLengths.fst" Some error checks are done to see this is a valid location, if the txdb data source is a repository like UCSC and not a local folder, it will not be made.</pre>	

filterUORFs

Details

If a transcript does not have a trailer, then the length is 0, so they will be filtered out if you set minThreeUTR to 1. So only transcripts with leaders, cds and trailers will be returned. You can set the integer to 0, that will return all within that group.

If your annotation does not have leaders or trailers, set them to NULL, since 0 means there must exist a column called utr3_len etc. Genes with gene_id = NA will be be removed.

Value

a character vector of valid transcript names

Examples

filterUORFs

Remove uORFs that are false CDS hits

Description

This is a strong filtering, so that even if the cds is on another transcript, the uORF is filtered out, this is because there is no way of knowing by current ribo-seq, rna-seq experiments.

Usage

```
filterUORFs(uorfs, cds)
```

Arguments

uorfs	(GRangesList), the uORFs to filter
cds	(GRangesList), the coding sequences (main ORFs on transcripts), to filter against.

Value

(GRangesList) of filtered uORFs

See Also

Other uorfs: addCdsOnLeaderEnds(), removeORFsWithSameStartAsCDS(), removeORFsWithSameStopAsCDS(), removeORFsWithStartInsideCDS(), removeORFsWithinCDS(), uORFSearchSpace()

fimport

Description

Wraps around ORFik file format loaders and rtracklayer::import and tries to speed up loading with the use of data.table. Supports gzip, gz, bgz compression formats. Also safer chromosome naming with the argument chrStyle

Usage

fimport(path, chrStyle = NULL, param = NULL, strandMode = 0)

Arguments

a character path to file (1 or 2 files), or data.table with 2 colums(forward&reverse) or a GRanges/Galignment/GAlignmentPairs object etc. If it is ranged object it will presume to be already loaded, so will return the object as it is, updating the seqlevelsStyle if given.
a GRanges object, TxDb, FaFile, , a seqlevelsStyle or Seqinfo. (Default: NULL) to get seqlevelsStyle from. In addition if it is a Seqinfo object, seqinfo will be updated. Example of seqlevelsStyle update: Is chromosome 1 called chr1 or 1, is mitocondrial chromosome called MT or chrM etc. Will use 1st seqlevel-style if more are present. Like: c("NCBI", "UCSC") -> pick "NCBI"
NULL or a ScanBamParam object. Like for scanBam, this influences what fields and which records are imported. However, note that the fields specified thru this ScanBamParam object will be loaded <i>in addition</i> to any field required for gen- erating the returned object (GAlignments, GAlignmentPairs, or GappedReads object), but only the fields requested by the user will actually be kept as meta- data columns of the object.
By default (i.e. param=NULL or param=ScanBamParam()), no additional field is loaded. The flag used is scanBamFlag(isUnmappedQuery=FALSE) for readGAlignments readGAlignmentsList, and readGappedReads. (i.e. only records correspond- ing to mapped reads are loaded), and scanBamFlag(isUnmappedQuery=FALSE, isPaired=TRUE, hasUnmappedMate=FALSE) for readGAlignmentPairs (i.e. only records corresponding to paired-end reads with both ends mapped are loaded).
numeric, default 0. Only used for paired end bam files. One of (0: strand = *, 1: first read of pair is +, 2: first read of pair is -). See ?strandMode. Note: Sets default to 0 instead of 1, as readGAlignmentPairs uses 1. This is to guarantee hits, but will also make mismatches of overlapping transcripts in opposite directions.

Details

NOTE: For wig/bigWig files you can send in 2 files, so that it automatically merges forward and reverse stranded objects. You can also just send 1 wig/bigWig file, it will then have "*" as strand.

Value

a GAlignments/GRanges object, depending on input.

findFa

See Also

```
Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.fstwig(), export.wiggle(), findFa(), fread.bed(), optimizeReads(), readBam(), readBigWig(), readWig()
```

Examples

```
bam_file <- system.file("extdata/Danio_rerio_sample", "ribo-seq.bam", package = "ORFik")
fimport(bam_file)
# Certain chromosome naming
fimport(bam_file, "NCBI")
# Paired end bam strandMode 1:
fimport(bam_file, strandMode = 1)
# (will have no effect in this case, since it is not paired end)</pre>
```

findFa

Convenience wrapper for Rsamtools FaFile

Description

Get fasta file object, to find sequences in file. Will load and import file if necessarry.

Usage

```
findFa(faFile)
```

Arguments

faFile FaFile, BSgenome, fasta/index file path or an ORFik experiment. This file is usually used to find the transcript sequences from some GRangesList.

Value

a FaFile or BSgenome

See Also

Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.fstwig(), export.wiggle(), fimport(), fread.bed(), optimizeReads(), readBam(), readBigWig(), readWig()

Examples

```
# Some fasta genome with existing fasta index in same folder
path <- system.file("extdata/references/danio_rerio", "genome_dummy.fasta", package = "ORFik")
findFa(path)</pre>
```

findFromPath

Description

From the given experiment

Usage

```
findFromPath(filepaths, candidates, slot = "auto")
```

Arguments

filepaths	path to all files
candidates	a data.table with 2 columns, Possible names to search for, see experiment_naming family for candidates.
slot	character, default "auto". If auto, use auto guessing of slot, else must be a character vector of length 1 or equal length as filepaths.

Value

a candidate library types (character vector)

findLibrariesInFolder Get all library files in folder/folders of given types

Description

Will try to guess paired / unpaired wig, bed, bam files.

Usage

```
findLibrariesInFolder(dir, types, pairedEndBam = FALSE)
```

Arguments

dir	Which directory / directories to create experiment from, must be a directory with NGS data from your experiment. Will include all files of file type specified by "types" argument. So do not mix files from other experiments in the same folder!
types	Default c("bam", "bed", "wig", "ofst"), which types of libraries to allow as NGS data.
pairedEndBam	logical FALSE, else TRUE, or a logical list of TRUE/FALSE per library you see will be included (run first without and check what order the files will come in) 1 paired end file, then two single will be c(T, F, F). If you have a SRA metadata csv file, you can set this argument to study\$LibraryLayout == "PAIRED", where study is the SRA metadata for all files that was aligned.

findMapORFs

Details

Set pairedEndBam if you have paired end reads as a single bam file.

Value

(data.table) All files found from types parameter. With 2 extra column (logical), is it wig pairs, and paired bam files.

findMapORFs

Find ORFs and immediately map them to their genomic positions.

Description

This function can map spliced ORFs. It finds ORFs on the sequences of interest, but returns relative positions to the positions of 'grl' argument. For example, 'grl' can be exons of known transcripts (with genomic coordinates), and 'seq' sequences of those transcripts, in that case, this function will return genomic coordinates of ORFs found on transcript sequences.

Usage

```
findMapORFs(
  grl,
  seqs,
  startCodon = startDefinition(1),
  stopCodon = stopDefinition(1),
  longestORF = TRUE,
  minimumLength = 0,
  groupByTx = FALSE,
  grl_is_sorted = FALSE
)
```

Arguments

grl	A GRangesList of the original sequences that gave the orfs in Genomic coor- dinates. If grl_is_sorted = TRUE (default), negative exon ranges per grl object must be sorted in descending orders.
seqs	(DNAStringSet or character vector) - DNA/RNA sequences to search for Open Reading Frames. Can be both uppercase or lowercase. Easiest call to get seqs if you want only regions from a fasta/fasta index pair is: seqs = OR- Fik:::txSeqsFromFa(grl, faFile), where grl is a GRanges/List of search regions and faFile is a FaFile. Note: Remember that if you extracted through a GRanges object, that must have been sorted with negative strand exons descending.
startCodon	(character vector) Possible START codons to search for. Check startDefinition for helper function. Note that it is case sensitive, so "atg" would give 0 hits for a sequence with only capital "ATG" ORFs.
stopCodon	(character vector) Possible STOP codons to search for. Check stopDefinition for helper function. Note that it is case sensitive, so "tga" would give 0 hits for a sequence with only capital "TGA" ORFs.

longestORF	(logical) Default TRUE. Keep only the longest ORF per unique stopcodon: (se- qname, strand, stopcodon) combination, Note: Not longest per transcript! You can also use function longestORFs after creation of ORFs for same result.
minimumLength	(integer) Default is 0. Which is START + STOP = 6 bp. Minimum length of ORF, without counting 3bps for START and STOP codons. For example minimumLength = 8 will result in size of ORFs to be at least START + $8*3$ (bp) + STOP = 30 bases. Use this param to restrict search.
groupByTx	logical (default: FALSE), should output GRangesList be grouped by exons per ORF (TRUE) or by orfs per transcript (FALSE)?
grl_is_sorted	logical, default FALSE If FALSE will sort negative transcript in descending order for you. If you loaded ranges with default methods this is already the case, so you can set to TRUE to save some time.

Details

This function assumes that 'seq' is in widths relative to 'grl', and that their orders match. 1st seq is 1st grl object, etc.

See vignette for real life example.

Value

A GRangesList of ORFs.

See Also

Other findORFs: findORFs(), findORFsFasta(), findUORFs(), startDefinition(), stopDefinition()

Examples

```
# First show simple example using findORFs
# This sequence has ORFs at 1-9 and 4-9
seqs <- DNAStringSet("ATGATGTAA") # the dna transcript sequence</pre>
findORFs(seqs)
# lets assume that this sequence comes from two exons as follows
# Then we need to use findMapORFs instead of findORFs,
# for splicing information
gr <- GRanges(seqnames = "1", # chromosome 1</pre>
              ranges = IRanges(start = c(21, 10), end = c(23, 15)),
              strand = "-". #
              names = "tx1") #From transcript 1 on chr 1
grl <- GRangesList(tx1 = gr) # 1 transcript with 2 exons</pre>
findMapORFs(grl, seqs) # ORFs are properly mapped to its genomic coordinates
grl <- c(grl, grl)</pre>
names(grl) <- c("tx1", "tx2")</pre>
findMapORFs(grl, c(seqs, seqs))
# More advanced example and how to save sequences found in vignette
```

findMaxPeaks	Find max peak for each transcript, returns as data.table, without
	names, but with index

Description

Find max peak for each transcript, returns as data.table, without names, but with index

Usage

```
findMaxPeaks(cageOverlaps, filteredCage)
```

Arguments

cageOverlaps	The cageOverlaps between cage and extended 5' leaders
filteredCage	The filtered raw cage-data used to reassign 5' leaders

Value

a data.table of max peaks

findNewTSS	Finds max peaks per	trancsript from	reads in the cagefile
------------	---------------------	-----------------	-----------------------

Description

Finds max peaks per trancsript from reads in the cagefile

Usage

```
findNewTSS(fiveUTRs, cageData, extension, restrictUpstreamToTx)
```

Arguments

cageDataThe CAGE as GRanges objectextensionThe number of basses to extends transcripts upstream.restrictUpstreamToTxa logical (FALSE), if you want to restrict leaders to not extend closer than a bases from closest upstream leader, set this to TRUE.	fiveUTRs	The 5' leader sequences as GRangesList
extension The number of basses to extends transcripts upstream. restrictUpstreamToTx a logical (FALSE), if you want to restrict leaders to not extend closer than a bases from closest upstream leader, set this to TRUE.	cageData	The CAGE as GRanges object
restrictUpstreamToTx a logical (FALSE), if you want to restrict leaders to not extend closer than a bases from closest upstream leader, set this to TRUE.	extension	The number of basses to extends transcripts upstream.
a logical (FALSE), if you want to restrict leaders to not extend closer than bases from closest upstream leader, set this to TRUE.	restrictUpstrea	amToTx
		a logical (FALSE), if you want to restrict leaders to not extend closer than 5 bases from closest upstream leader, set this to TRUE.

Value

a Hits object

findNGSPairs

Description

Find pair of forward and reverse strand wig / bed files and paired end bam files split in two

Usage

```
findNGSPairs(
   paths,
   f = c("forward", "fwd"),
   r = c("reverse", "rev"),
   format = "wig"
)
```

Arguments

paths	a character path at least one .wig / .bed file
f	Default (c("forward", "fwd") a character vector for forward direction regex.
r	Default (c("reverse", "rev") a character vector for reverse direction regex.
format	default "wig", for bed do "bed". Also searches compressions of these variants.

Value

if not all are paired, return original list, if they are all paired, return a data.table with matches as 2 columns

findORFs

Find Open Reading Frames.

Description

Find all Open Reading Frames (ORFs) on the simple input sequences in ONLY 5'- 3' direction (+), but within all three possible reading frames. Do not use findORFs for mapping to full chromosomes, then use findMapORFs! For each sequence of the input vector IRanges with START and STOP positions (inclusive) will be returned as IRangesList. Returned coordinates are relative to the input sequences.

Usage

```
findORFs(
   seqs,
   startCodon = startDefinition(1),
   stopCodon = stopDefinition(1),
   longestORF = TRUE,
   minimumLength = 0
)
```

findORFs

Arguments

seqs	(DNAStringSet or character vector) - DNA/RNA sequences to search for Open Reading Frames. Can be both uppercase or lowercase. Easiest call to get seqs if you want only regions from a fasta/fasta index pair is: seqs = OR- Fik:::txSeqsFromFa(grl, faFile), where grl is a GRanges/List of search regions and faFile is a FaFile. Note: Remember that if you extracted through a GRanges object, that must have been sorted with negative strand exons descending.
startCodon	(character vector) Possible START codons to search for. Check startDefinition for helper function. Note that it is case sensitive, so "atg" would give 0 hits for a sequence with only capital "ATG" ORFs.
stopCodon	(character vector) Possible STOP codons to search for. Check stopDefinition for helper function. Note that it is case sensitive, so "tga" would give 0 hits for a sequence with only capital "TGA" ORFs.
longestORF	(logical) Default TRUE. Keep only the longest ORF per unique stopcodon: (se- qname, strand, stopcodon) combination, Note: Not longest per transcript! You can also use function longestORFs after creation of ORFs for same result.
minimumLength	(integer) Default is 0. Which is START + STOP = 6 bp. Minimum length of ORF, without counting 3bps for START and STOP codons. For example minimumLength = 8 will result in size of ORFs to be at least START + $8*3$ (bp) + STOP = 30 bases. Use this param to restrict search.

Details

If you want antisence strand too, do: #positive strands pos <- findORFs(seqs) #negative
strands (DNAStringSet only if character) neg <- findORFs(reverseComplement(DNAStringSet(seqs)))
relist(c(GRanges(pos, strand = "+"), GRanges(neg, strand = "-")), skeleton = merge(pos,
neg))</pre>

Value

(IRangesList) of ORFs locations by START and STOP sites grouped by input sequences. In a list of sequences, only the indices of the sequences that had ORFs will be returned, e.g. 3 sequences where only 1 and 3 has ORFs, will return size 2 IRangesList with names c("1", "3"). If there are a total of 0 ORFs, an empty IRangesList will be returned.

See Also

Other findORFs: findMapORFs(), findORFsFasta(), findUORFs(), startDefinition(), stopDefinition()

Examples

```
## Simple examples
findORFs("ATGTAA")
findORFs("ATGTTAA") # not in frame anymore
findORFs("ATGATGTAA") # only longest of two above
findORFs("ATGATGTAA", longestORF = FALSE) # two ORFs
findORFs(c("ATGTAA", "ATGATGTAA")) # 1 ORF per transcript
## Get DNA sequences from ORFs
seq <- DNAStringSet(c("ATGTAA", "AAA", "ATGATGTAA"))
names(seq) <- c("tx1", "tx2", "tx3")</pre>
```

```
orfs <- findORFs(seq, longestORF = FALSE)
# you can get sequences like this:
gr <- unlist(orfs, use.names = TRUE)
gr <- GRanges(seqnames = names(seq)[as.integer(names(gr))],
ranges = gr, strand = "+")
# Give them some proper names:
names(gr) <- paste0("ORF_", seq.int(length(gr)), "_", seqnames(gr))
orf_seqs <- getSeq(seq, gr)
orf_seqs
# Save as .fasta (orf_seqs must be of type DNAStringSet)
# writeXStringSet(orf_seqs, "orfs.fasta")
## Reading from file and find ORFs
#findORFs(readDNAStringSet("path/to/transcripts.fasta"))</pre>
```

findORFsFasta Finds Open Reading Frames in fasta files.

Description

Should be used for procaryote genomes or transcript sequences as fasta. Makes no sence for eukaryote whole genomes, since those contains splicing (use findMapORFs for spliced ranges). Searches through each fasta header and reports all ORFs found for BOTH sense (+) and antisense strand (-) in all frames. Name of the header will be used as seqnames of reported ORFs. Each fasta header is treated separately, and name of the sequence will be used as seqname in returned GRanges object. This supports circular genomes.

Usage

```
findORFsFasta(
   filePath,
   startCodon = startDefinition(1),
   stopCodon = stopDefinition(1),
   longestORF = TRUE,
   minimumLength = 0,
   is.circular = FALSE
)
```

Arguments

filePath	(character) Path to the fasta file. Can be both uppercase or lowercase. Or a already loaded R object of either types: "BSgenome" or "DNAStringSet" with named sequences
startCodon	(character vector) Possible START codons to search for. Check startDefinition for helper function. Note that it is case sensitive, so "atg" would give 0 hits for a sequence with only capital "ATG" ORFs.
stopCodon	(character vector) Possible STOP codons to search for. Check stopDefinition for helper function. Note that it is case sensitive, so "tga" would give 0 hits for a sequence with only capital "TGA" ORFs.
longestORF	(logical) Default TRUE. Keep only the longest ORF per unique stopcodon: (sequame, strand, stopcodon) combination, Note: Not longest per transcript! You can also use function longestORFs after creation of ORFs for same result.

minimumLength	(integer) Default is 0. Which is $START + STOP = 6$ bp. Minimum length
	of ORF, without counting 3bps for START and STOP codons. For example minimumLength = 8 will result in size of ORFs to be at least START + $8*3$ (bp) + STOP = 30 bases. Use this param to restrict search.
is.circular	(logical) Whether the genome in filePath is circular. Prokaryotic genomes are usually circular. Be carefull if you want to extract sequences, remember that seqlengths must be set, else it does not know what last base in sequence is before loop ends!

Remember if you have a fasta file of transcripts (transcript coordinates), delete all negative stranded ORFs afterwards by: orfs <- orfs[strandBool(orfs)] # negative strand orfs make no sense then. Seqnames are created from header by format: >name info, so name must be first after "biggern than" and space between name and info. Also make sure your fasta file is valid (no hidden spaces etc), as this might break the coordinate system!

Value

(GRanges) object of ORFs mapped from fasta file. Positions are relative to the fasta file.

See Also

Other findORFs: findMapORFs(), findORFs(), findUORFs(), startDefinition(), stopDefinition()

Examples

```
# location of the example fasta file
example_genome <- system.file("extdata/references/danio_rerio", "genome_dummy.fasta",
package = "ORFik")
orfs <- findORFsFasta(example_genome)
# To store ORF sequences (you need indexed genome .fai file):
fa <- FaFile(example_genome)
names(orfs) <- paste0("ORF_", seq.int(length(orfs)), "_", seqnames(orfs))
orf_seqs <- getSeq(fa, orfs)
# You sequences (fa), needs to have isCircular(fa) == TRUE for it to work
# on circular wrapping ranges!
# writeXStringSet(DNAStringSet(orf_seqs), "orfs.fasta")
```

findPeaksPerGene Find peaks per gene

Description

For finding the peaks (stall sites) per gene, with some default filters. A peak is basically a position of very high coverage compared to its surrounding area, as measured using zscore.

Usage

```
findPeaksPerGene(
   tx,
   reads,
   top_tx = 0.5,
   min_reads_per_tx = 20,
   min_reads_per_peak = 10,
   type = "max"
)
```

Arguments

tx	a GRangesList	
reads	a GAlignments or GRanges, must be 1 width reads like p-shifts, or other reads that is single positioned. It will work with non 1 width bases, but you then get larger areas for peaks.	
top_tx	numeric, default 0.50 (only use 50% top transcripts by read counts).	
min_reads_per_tx		
	numeric, default 20. Gene must have at least 20 reads, applied before type filter.	
min_reads_per_peak		
	numeric, default 10. Peak must have at least 10 reads.	
type	character, default "max". Get only max peak per gene. Alternatives: "all", all peaks passing the input filter will be returned. "median", only peaks that is higher than the median of all peaks. "maxmedian": get first "max", then median of those.	

Details

For more details see reference, which uses a slightly different method by zscore of a sliding window instead of over the whole tx.

Value

a data.table of gene_id, position, counts of the peak, zscore and standard deviation of the peak compared to rest of gene area.

References

doi: 10.1261/rna.065235.117

Examples

```
df <- ORFik.template.experiment()
cds <- loadRegion(df, "cds")
# Load ribo seq from ORFik
rfp <- fimport(df[3,]$filepath)
# All transcripts passing filter
findPeaksPerGene(cds, rfp, top_tx = 0)
# Top 50% of genes
findPeaksPerGene(cds, rfp)</pre>
```

findUORFs

Description

Procedure: 1. Create a new search space starting with the 5' UTRs. 2. Redefine TSS with CAGE if wanted. 3. Add the whole of CDS to search space to allow uORFs going into cds. 4. find ORFs on that search space. 5. Filter out wrongly found uORFs, if CDS is included. The CDS, alternative CDS, uORFs starting within the CDS etc.

Usage

```
findUORFs(
   fiveUTRs,
   fa,
   startCodon = startDefinition(1),
   stopCodon = stopDefinition(1),
   longestORF = TRUE,
   minimumLength = 0,
   cds = NULL,
   cage = NULL,
   extension = 1000,
   filterValue = 1,
   restrictUpstreamToTx = FALSE,
   removeUnused = FALSE
)
```

Arguments

fiveUTRs	(GRangesList) The 5' leaders or full transcript sequences
fa	a FaFile. With fasta sequences corresponding to fiveUTR annotation. Usually loaded from the genome of an organism with fa = ORFik:::findFa("path/to/fasta/genome")
startCodon	(character vector) Possible START codons to search for. Check startDefinition for helper function. Note that it is case sensitive, so "atg" would give 0 hits for a sequence with only capital "ATG" ORFs.
stopCodon	(character vector) Possible STOP codons to search for. Check stopDefinition for helper function. Note that it is case sensitive, so "tga" would give 0 hits for a sequence with only capital "TGA" ORFs.
longestORF	(logical) Default TRUE. Keep only the longest ORF per unique stopcodon: (se- qname, strand, stopcodon) combination, Note: Not longest per transcript! You can also use function longestORFs after creation of ORFs for same result.
minimumLength	(integer) Default is 0. Which is START + STOP = 6 bp. Minimum length of ORF, without counting 3bps for START and STOP codons. For example minimumLength = 8 will result in size of ORFs to be at least START + $8*3$ (bp) + STOP = 30 bases. Use this param to restrict search.
cds	(GRangesList) CDS of relative fiveUTRs, applicable only if you want to extend 5' leaders downstream of CDS's, to allow upstream ORFs that can overlap into CDS's.

cage	Either a filePath for the CageSeq file as .bed .bam or .wig, with possible com- pressions (".gzip", ".gz", ".bgz"), or already loaded CageSeq peak data as GRanges or GAlignment. NOTE: If it is a .bam file, it will add a score column by run- ning: convertToOneBasedRanges(cage, method = "5prime", addScoreColumn = TRUE) The score column is then number of replicates of read, if score column is something else, like read length, set the score column to NULL first.	
extension	The maximum number of basses upstream of the TSS to search for CageSeq peak.	
filterValue	The minimum number of reads on cage position, for it to be counted as possible new tss. (represented in score column in CageSeq data) If you already filtered, set it to 0.	
restrictUpstreamToTx		
	a logical (FALSE). If TRUE: restrict leaders to not extend closer than 5 bases from closest upstream leader, set this to TRUE.	
removeUnused	logical (FALSE), if False: (standard is to set them to original annotation), If TRUE: remove leaders that did not have any cage support.	

Details

From default a filtering process is done to remove "fake" uORFs, but only if cds is included, since uORFs that stop on the stop codon on the CDS is not a uORF, but an alternative cds by definition, etc.

Value

A GRangesList of uORFs, 1 granges list element per uORF.

See Also

Other findORFs: findMapORFs(), findORFs(), findORFsFasta(), startDefinition(), stopDefinition()

Examples

```
# Load annotation
txdbFile <- system.file("extdata", "hg19_knownGene_sample.sqlite",</pre>
                          package = "GenomicFeatures")
## Not run:
 txdb <- loadTxdb(txdbFile)</pre>
 fiveUTRs <- loadRegion(txdb, "leaders")</pre>
cds <- loadRegion(txdb, "cds")</pre>
 if (requireNamespace("BSgenome.Hsapiens.UCSC.hg19")) {
   # Normally you would not use a BSgenome, but some custom fasta-
   # annotation you have for your species
   findUORFs(fiveUTRs, BSgenome.Hsapiens.UCSC.hg19::Hsapiens, "ATG",
             cds = cds)
 }
```
findUORFs_exp

Description

Procedure: 1. Create a new search space starting with the 5' UTRs. 2. Redefine TSS with CAGE if wanted. 3. Add the whole of CDS to search space to allow uORFs going into cds. 4. find ORFs on that search space. 5. Filter out wrongly found uORFs, if CDS is included. The CDS, alternative CDS, uORFs starting within the CDS etc.

Usage

```
findUORFs_exp(
 df,
 faFile = findFa(df),
 leaders = loadRegion(txdb, "leaders"),
 startCodon = startDefinition(1),
 stopCodon = stopDefinition(1),
 longestORF = TRUE,
 minimumLength = 0,
 overlappingCDS = FALSE,
  cage = NULL,
 extension = 1000,
 filterValue = 1,
 restrictUpstreamToTx = FALSE,
 removeUnused = FALSE,
  save_optimized = FALSE
)
```

df	a txdb or experiment
faFile	FaFile of genome, default findFa(df). Default only works for ORFik experi- ments, if TxDb, input manually like: findFa(genome_path)
leaders	<pre>GRangesList, default: loadRegion(txdb, "leaders"). If you do not have any good leader annotation, a hack is to use ORFik:::groupGRangesBy(startSites(loadRegion(txdb, "cds"), asGR = TRUE, keep.names = TRUE, is.sorted = TRUE))</pre>
startCodon	(character vector) Possible START codons to search for. Check startDefinition for helper function. Note that it is case sensitive, so "atg" would give 0 hits for a sequence with only capital "ATG" ORFs.
stopCodon	(character vector) Possible STOP codons to search for. Check stopDefinition for helper function. Note that it is case sensitive, so "tga" would give 0 hits for a sequence with only capital "TGA" ORFs.
longestORF	(logical) Default TRUE. Keep only the longest ORF per unique stopcodon: (se- qname, strand, stopcodon) combination, Note: Not longest per transcript! You can also use function longestORFs after creation of ORFs for same result.
minimumLength	(integer) Default is 0. Which is START + STOP = 6 bp. Minimum length of ORF, without counting 3bps for START and STOP codons. For example minimumLength = 8 will result in size of ORFs to be at least START + 8*3 (bp) + STOP = 30 bases. Use this param to restrict search.

overlappingCDS	logical, default FALSE. Include uORFs that overlap CDS.	
cage	Either a filePath for the CageSeq file as .bed .bam or .wig, with possible com- pressions (".gzip", ".gz", ".bgz"), or already loaded CageSeq peak data as GRanges or GAlignment. NOTE: If it is a .bam file, it will add a score column by run- ning: convertToOneBasedRanges(cage, method = "5prime", addScoreColumn = TRUE) The score column is then number of replicates of read, if score column is something else, like read length, set the score column to NULL first.	
extension	The maximum number of basses upstream of the TSS to search for CageSeq peak.	
filterValue	The minimum number of reads on cage position, for it to be counted as possible new tss. (represented in score column in CageSeq data) If you already filtered, set it to 0.	
restrictUpstreamToTx		
	a logical (FALSE). If TRUE: restrict leaders to not extend closer than 5 bases from closest upstream leader, set this to TRUE.	
removeUnused	logical (FALSE), if False: (standard is to set them to original annotation), If TRUE: remove leaders that did not have any cage support.	
save_optimized	logical, default FALSE. If TRUE, save in the optimized folder for the exper- iment. You must have made this directory before running this function (call makeTxdbFromGenome first if not).	

Details

From default a filtering process is done to remove "fake" uORFs, but only if cds is included, since uORFs that stop on the stop codon on the CDS is not a uORF, but an alternative cds by definition, etc.

Value

A GRangesList of uORFs, 1 granges list element per uORF.

See Also

Other findORFs: findMapORFs(), findORFs(), findORFsFasta(), startDefinition(), stopDefinition()

Examples

```
df <- ORFik.template.experiment()
# Without cds overlapping, no 5' leader extension
findUORFs_exp(df, extension = 0)
# Without cds overlapping, extends 5' leaders by 1000 (good for yeast etc)
findUORFs_exp(df)
# Include cds overlapping uorfs
findUORFs_exp(df, overlappingCDS = TRUE)</pre>
```

find_url_ebi

Description

Look for files in ebi following url: ftp://ftp.sra.ebi.ac.uk/vol1/fastq Paired end and single end fastq files.

EBI uses 3 ways to organize data inside vol1/fastq:

- 1: Most common: SRR(3 first)/0(2 last)/whole

- 2: less common: SRR(3 first)/00(1 last)/whole
- 3: least common SRR(3 first)/whole

Usage

```
find_url_ebi(SRR, stop.on.error = FALSE, study = NULL)
```

Arguments

SRR	character, SRR, ERR or DRR numbers.
stop.on.error	logical FALSE, if TRUE will stop if all files are not found. If FALSE returns empty character vector if error is catched.
study	default NULL, optional PRJ (study id) to speed up search for URLs.

Value

full url to fastq files, same length as input (2 urls for paired end data). Returns empty character() if all files not found.

Examples

```
# Test the 3 ways to get fastq files from EBI
# Both single end and paired end data
# Most common: SRR(3 first)/0(2 last)/whole
# Single
ORFik:::find_url_ebi("SRR10503056")
# Paired
ORFik:::find_url_ebi("SRR10500056")
# less common: SRR(3 first)/00(1 last)/whole
# Single
#ORFik:::find_url_ebi("SRR1562873")
# Paired
#ORFik:::find_url_ebi("SRR1560083")
# least common SRR(3 first)/whole
# Single
#ORFik:::find_url_ebi("SRR105687")
# Paired
#ORFik:::find_url_ebi("SRR105788")
```

find_url_ebi_safe Find URL for EBI fastq files

Description

Safer version

Usage

```
find_url_ebi_safe(accession, SRR = NULL, stop.on.error = FALSE)
```

Arguments

accession	character: (PRJ, SRP, ERP, DRP, SRX, SRR, ERR,). For studies or samples, it returns all runs per study or sample.
SRR	character, which SRR numbers to subset by (can also be ERR or DRR numbers)
stop.on.error	logical FALSE, if TRUE will stop if all files are not found. If FALSE returns empty character vector if error is catched.

Value

character (1 element per SRR number)

firstEndPerGroup Get first end per granges group

Description

grl must be sorted, call ORFik:::sortPerGroup if needed

Usage

```
firstEndPerGroup(grl, keep.names = TRUE)
```

Arguments

grl	a GRangesList
keep.names	a boolean, keep names or not, default: (TRUE)

Value

a Rle(keep.names = T), or integer vector(F)

firstExonPerGroup

Examples

firstExonPerGroup Get first exon per GRangesList group

Description

grl must be sorted, call ORFik:::sortPerGroup if needed

Usage

firstExonPerGroup(grl)

Arguments

grl a GRangesList

Value

a GRangesList of the first exon per group

Examples

firstStartPerGroup Get first start per granges group

Description

grl must be sorted, call ORFik:::sortPerGroup if needed

Usage

```
firstStartPerGroup(grl, keep.names = TRUE)
```

Arguments

grl	a GRangesList
keep.names	a boolean, keep names or not, default: (TRUE)

Value

a Rle(keep.names = TRUE), or integer vector(FALSE)

Examples

fix_malformed_gff Fix a malformed gff file

Description

Basically removes all info lines with character length > 32768 and save that new file.

Usage

```
fix_malformed_gff(gff)
```

Arguments

gff character, path to gtf, can not be gzipped!

Value

path of fixed gtf

Examples

fix_malformed_gff("my_bad_gff.gff")

150

flankPerGroup *Get flanks per group*

Description

For a GRangesList, get start and end site, return back as GRL.

Usage

flankPerGroup(grl)

Arguments

grl a GRangesList

Value

a GRangesList, 1 GRanges per group with: start as minimum start of group and end as maximum per group.

Examples

floss

Fragment Length Organization Similarity Score

Description

This feature is usually calcualted only for RiboSeq reads. For reads of width between 'start' and 'end', sum the fraction of RiboSeq reads (per read widths) that overlap ORFs and normalize by CDS read width fractions. So if all read length are width 34 in ORFs and CDS, value is 1. If width is 33 in ORFs and 34 in CDS, value is 0. If width is 33 in ORFs and 50/50 (33 and 34) in CDS, values will be 0.5 (for 33).

Usage

```
floss(grl, RFP, cds, start = 26, end = 34, weight = 1L)
```

grl	a GRangesList object can be either transcripts, 5' utrs, cds', 3' utrs or ORFs as a special case (uORFs, potential new cds' etc). If regions are not spliced you can send a GRanges object.
RFP	ribosomal footprints, given as GAlignments or GRanges object, must be already shifted and resized to the p-site. Requires a \$size column with original read lengths.

cds	a GRangesList of coding sequences, cds has to have names as grl so that they can be matched
start	usually 26, the start of the floss interval (inclusive)
end	usually 34, the end of the floss interval (inclusive)
weight	a vector (default: 1L, if 1L it is identical to countOverlaps()), if single number (!= 1), it applies for all, if more than one must be equal size of 'reads'. else it must be the string name of a defined meta column in subject "reads", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean "score" column tells that this alignment region was found 5 times.

Details

Pseudo explanation of the function:

```
SUM[start to stop]((grl[start:end][name]/grl) / (cds[start:end][name]/cds))
```

Where 'name' is transcript names. Please read more in the article.

Value

a vector of FLOSS of length same as grl, 0 means no RFP reads in range, 1 is perfect match.

References

doi: 10.1016/j.celrep.2014.07.045

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
ORF1 <- GRanges(seqnames = "1",</pre>
               ranges = IRanges(start = c(1, 12, 22),
               end = c(10, 20, 32)),
               strand = "+")
grl <- GRangesList(tx1_1 = ORF1)</pre>
# RFP is 1 width position based GRanges
RFP <- GRanges("1", IRanges(c(1, 25, 35, 38), width = 1), "+")</pre>
RFP$size <- c(28, 28, 28, 29) # original width in size col
cds <- GRangesList(tx1 = GRanges("1", IRanges(35, 44), "+"))</pre>
\# grl must have same names as cds + _1 etc, so that they can be matched.
floss(grl, RFP, cds)
# or change ribosome start/stop, more strict
floss(grl, RFP, cds, 28, 28)
# With repeated alignments in score column
ORF2 <- GRanges(seqnames = "1",</pre>
               ranges = IRanges(start = c(12, 22, 36),
```

footprints.analysis

footprints.analysis Pre shifting plot analysis

Description

For internal use only!

Usage

```
footprints.analysis(rw, heatmap, region = "start of CDS")
```

Arguments

rw	a data.table of position, score and fraction (read length) of either TIS or TES (translation end site, around 3' UTR)
heatmap	a logical or character string, default FALSE. If TRUE, will plot heatmap of raw reads before p-shifting to console, to see if shifts given make sense. You can also set a filepath to save the file there.
region	a character string, default "start of CDS"

Value

invisible(NULL)

```
fpkm
```

Create normalizations of overlapping read counts.

Description

FPKM is short for "Fragments Per Kilobase of transcript per Million fragments in library". When calculating RiboSeq data FPKM over ORFs, use ORFs as 'grl'. When calculating RNASeq data FPKM, use full transcripts as 'grl'. It is equal to RPKM given that you do not have paired end reads.

Usage

```
fpkm(grl, reads, pseudoCount = 0, librarySize = "full", weight = 1L)
```

Arguments

grl	a GRangesList object can be either transcripts, 5' utrs, cds', 3' utrs or ORFs as a special case (uORFs, potential new cds' etc). If regions are not spliced you can send a GRanges object.
reads	a GAlignments, GRanges or GRangesList object, usually of RiboSeq, RnaSeq, CageSeq, etc.
pseudoCount	an integer, by default is 0, set it to 1 if you want to avoid NA and inf values.
librarySize	either numeric value or character vector. Default ("full"), number of alignments in library (reads). If you just have a subset, you can give the value by library- Size = length(wholeLib), if you want lib size to be only number of reads over- lapping grl, do: librarySize = "overlapping" sum(countOverlaps(reads, grl) > 0), if reads[1] has 3 hits in grl, and reads[2] has 2 hits, librarySize will be 2, not 5. You can also get the inverse overlap, if you want lib size to be total number of overlaps, do: librarySize = "DESeq" This is standard fpkm way of DESeq2::fpkm(robust = FALSE) sum(countOverlaps(grl, reads)) if grl[1] has 3 reads and grl[2] has 2 reads, librarySize is 5, not 2.
weight	a vector (default: 1L, if 1L it is identical to countOverlaps()), if single number (!= 1), it applies for all, if more than one must be equal size of 'reads'. else it must be the string name of a defined meta column in subject "reads", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean "score" column tells that this alignment region was found 5 times.

Details

Note also that you must consider if you will use the whole read library or just the reads overlapping 'grl' for library size. A normal question here is, does it make sense to include rRNA in library size ? If you only want overlapping grl, do: librarySize = "overlapping"

Value

a numeric vector with the fpkm values

References

doi: 10.1038/nbt.1621

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm_calc(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

fpkm_calc

```
fpkm(grl, RFP)
# With weights (10 reads at position 25)
RFP <- GRanges("1", IRanges(25, 25),"+", score = 10)
fpkm(grl, RFP, weight = "score")</pre>
```

fpkm_calc

Create normalizations of read counts

Description

A helper for [fpkm()] Normally use function [fpkm()], if you want unusual normalization, you can use this. Short for: Fragments per kilobase of transcript per million fragments Normally used in Translations efficiency calculations

Usage

fpkm_calc(counts, lengthSize, librarySize)

Arguments

counts	a list, # of read hits per group
lengthSize	a list of lengths per group
librarySize	a numeric of size 1, the # of reads in library

Value

a numeric vector

References

doi: 10.1038/nbt.1621

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fractionLength(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

fractionLength

Description

Fraction Length is defined as

(widths of grl)/tx_len

so that each group in the grl is divided by the corresponding transcript.

Usage

```
fractionLength(grl, tx_len = widthPerGroup(tx, TRUE), tx = NULL)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs. ORFs are a special case, see argument tx_len
tx_len	the transcript lengths of the transcripts, a named (tx names) vector of integers. If you have the transcripts as GRangesList, call 'ORFik:::widthPerGroup(tx, TRUE)'.
	If you used CageSeq to reannotate leaders, then the tss for the the leaders have changed, therefore the tx lengths have changed. To account for that call: 'tx_len <- widthPerGroup(extendLeaders(tx, cageFiveUTRs))' and calculate fraction length using 'fractionLength(grl, tx_len)'.
tx	default NULL, a GRangesList object of transcript to get lengths from. Pass in for wrapping to widths inside the function.

Value

a numeric vector of ratios

References

doi: 10.1242/dev.098343

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), initiationScore(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

fractionNames

Examples

fractionNames

Get cell fraction name variants

Description

Used to standardize nomeclature for experiments. Example: cytosolic, mitochondrial, specific gene knock down

Usage

fractionNames()

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

Other experiment_naming: batchNames(), cellLineNames(), cellTypeNames(), conditionNames(), inhibitorNames(), libNames(), mainNames(), repNames(), stageNames(), tissueNames()

fread.bed

Load bed file as GRanges

Description

Wraps around import.bed and tries to speed up loading with the use of data.table. Supports gzip, gz, bgz and bed formats. Also safer chromosome naming with the argument chrStyle

Usage

```
fread.bed(filePath, chrStyle = NULL)
```

filePath	The location of the bed file
chrStyle	a GRanges object, TxDb, FaFile, , a seqlevelsStyle or Seqinfo. (Default: NULL) to get seqlevelsStyle from. In addition if it is a Seqinfo object, seqinfo will be updated. Example of seqlevelsStyle update: Is chromosome 1 called chr1 or 1, is mitocondrial chromosome called MT or chrM etc. Will use 1st
	seqlevel-style if more are present. Like: c("NCBI", "UCSC") -> pick "NCBI"

Value

a GRanges object

See Also

```
Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.fstwig(), export.wiggle(), fimport(), findFa(), optimizeReads(), readBam(), readBigWig(), readWig()
```

Examples

gcContent

Get GC content

Description

0.5 means 50

Usage

gcContent(seqs, fa = NULL)

Arguments

seqs	a character vector of sequences, or ranges as GRangesList
fa	fasta index file .fai file, either path to it, or the loaded FaFile, default (NULL),
	only set if you give ranges as GRangesList

Value

a numeric vector of gc content scores

Examples

158

Description

If your organism is not in this list of supported organisms, manually assign the input arguments. There are 2 main fetch modes:

By gene ids (Single accession per gene)

By tx ids (Multiple accessions per gene)

Run the mode you need depending on your required attributes.

Will check for already existing table of all genes, and use that instead of re-downloading every time (If you input valid experiment or txdb and have run makeTxdbFromGenome with symbols = TRUE, you have a file called gene_symbol_tx_table.fst) will load instantly. If df = NULL, it can still search cache to load a bit slower.

Usage

```
geneToSymbol(
    df,
    organism_name = organism(df),
    gene_ids = filterTranscripts(df, by = "gene", 0, 0, 0),
    org.dataset = paste0(tolower(substr(organism_name, 1, 1)), gsub(".* ", replacement =
        "", organism_name), "_gene_ensembl"),
    ensembl = biomaRt::useEnsembl("ensembl", dataset = org.dataset),
    attribute = "external_gene_name",
    include_tx_ids = FALSE,
    uniprot_id = FALSE,
    force = FALSE,
    verbose = TRUE
)
```

df	an ORFik experiment or TxDb object with defined organism slot. If set will look for file at path of txdb / experiment reference path named: 'gene_symbol_tx_table.fst' relative to the txdb/genome directory. Can be set to NULL if gene_ids and organism is defined manually.
organism_name	default, organism(df). Scientific name of organism, like ("Homo sapiens"), remember capital letter for first name only!
gene_ids	default, filterTranscripts(df, by = "gene", 0, 0, 0). Ensembl gene IDs to search for (default all transcripts coding and noncoding) To only get coding do: filterTranscripts(df, by = "gene", 0, 1, 0)
org.dataset	<pre>default, paste0(tolower(substr(organism_name, 1, 1)), gsub(".*", replacement = "", organism_name), "_gene_ensembl") the ensembl dataset to use. For Homo sapiens, this converts to default as: hsapiens_gene_ensembl</pre>
ensembl	<pre>default, useEnsembl("ensembl",dataset=org.dataset) .The mart connec- tion.</pre>

attribute	default, "external_gene_name", the biomaRt column / columns default(primary gene symbol names). These are always from specific database, like hgnc symbol for human, and mgi symbol for mouse and rat, sgd for yeast etc.
include_tx_ids	logical, default FALSE, also match tx ids, which then returns as the 3rd column. Only allowed when 'df' is defined. If
uniprot_id	logical, default FALSE. Include uniprotsptrembl and/or uniprotswissprot. If in- clude_tx_ids you will get per isoform if available, else you get canonical uniprot id per gene. If both uniprotsptrembl and uniprotswissprot exists, it will make a merged uniprot id column with rule: if id exists in uniprotswissprot, keep. If not, use uniprotsptrembl column id.
force	logical FALSE, if TRUE will not look for existing file made through makeTxdbFromGenome corresponding to this txdb / ORFik experiment stored with name "gene_symbol_tx_table.fst".
verbose	logical TRUE, if FALSE, do not output messages.

Value

data.table with 2, 3 or 4 columns: gene_id, gene_symbol, tx_id and uniprot_id named after attribute, sorted in order of gene_ids input. (example: returns 3 columns if include_tx_ids is TRUE), and more if additional columns are specified in 'attribute' argument.

Examples

```
## Without ORFik experiment input
gene_id_ATF4 <- "ENSG00000128272"
#geneToSymbol(NULL, organism_name = "Homo sapiens", gene_ids = gene_id_ATF4)
# With uniprot canonical isoform id:
#geneToSymbol(NULL, organism_name = "Homo sapiens", gene_ids = gene_id_ATF4, uniprot_id = TRUE)
## All genes from Organism using ORFik experiment
# df <- read.experiment("some_experiment)
# geneToSymbol(df)
## Non vertebrate species (the ones not in ensembl, but in ensemblGenomes mart)
#txdb_ylipolytica <- loadTxdb("txdb_path")
#dt2 <- geneToSymbol(txdb_ylipolytica, include_tx_ids = TRUE,
# ensembl = useEnsemblGenomes(biomart = "fungi_mart", dataset = "ylipolytica_eg_gene"))
```

getGAlignments	Internal GAlignments	loader from fst data.frame
0 0	0	<i>y y y</i>

Description

Internal GAlignments loader from fst data.frame

Usage

```
getGAlignments(df, seqinfo = NULL)
```

Arguments

df	a data.frame with columns minimum 4 columns: seqnames, start ("pos" in final GA object), cigar and strand. Additional columns will be assigned as meta columns
seqinfo	Seqinfo object, defaul NULL (created from ranges). Add to avoid warnings later on differences in seqinfo.

Value

GAlignments object

getGAlignmentsPairs Internal GAlignmentPairs loader from fst data.frame

Description

Internal GAlignmentPairs loader from fst data.frame

Usage

```
getGAlignmentsPairs(df, strandMode = 0, seqinfo = NULL)
```

Arguments

df	a data.frame with columns minimum 6 columns: seqnames, start1/start2 (inte- gers), cigar1/cigar2 and strand Additional columns will be assigned as meta columns
strandMode	numeric, default 0. Only used for paired end bam files. One of (0: strand $= *, 1$: first read of pair is +, 2: first read of pair is -). See ?strandMode. Note: Sets default to 0 instead of 1, as readGAlignmentPairs uses 1. This is to guarantee hits, but will also make mismatches of overlapping transcripts in opposite directions.
seqinfo	Seqinfo object, defaul NULL (created from ranges). Add to avoid warnings later on differences in seqinfo.

Value

GAlignmentPairs object

getGenomeAndAnnotation

Download genome (fasta), annotation (GTF) and contaminants

Description

This function automatically downloads (if files not already exists) genomes and contaminants specified for genome alignment. By default, it will use ensembl reference, upon completion, the function will store a file called file.path(output.dir, "outputs.rds") with the output paths of your completed genome/annotation downloads. For most non-model nonvertebrate organisms, you need my fork of biomartr for it to work: remotes::install_github("Roleren/biomartr) If you misspelled something or crashed, delete wrong files and run again. Do remake = TRUE, to do it all over again.

Usage

```
getGenomeAndAnnotation(
 organism,
 output.dir,
 db = "ensembl",
 GTF = TRUE,
  genome = TRUE,
 merge_contaminants = TRUE,
 phix = FALSE,
 ncRNA = FALSE,
  tRNA = FALSE,
  rRNA = FALSE,
  gunzip = TRUE,
  remake = FALSE,
  assembly_type = c("primary_assembly", "toplevel"),
 optimize = FALSE,
  gene_symbols = FALSE,
  uniprot_id = FALSE,
 pseudo_5UTRS_if_needed = NULL,
 remove_annotation_outliers = TRUE,
 notify_load_existing = TRUE,
  assembly = organism
)
```

Arguments

organismscientific name of organism, Homo sapiens, Danio rerio, Mus musculus, etc.
See biomartr::get.ensembl.info() for full list of supported organisms.output.dirdirectory to save downloaded datadbdatabase to use for genome and GTF, default adviced: "ensembl" (remember to
set assembly_type to "primary_assembly", else it will contain haplotypes, very
large file!). Alternatives: "refseq" (reference assemblies) and "genbank" (all
assemblies)

GTF	logical, default: TRUE, download gtf of organism specified in "organism" argu- ment. If FALSE, check if the downloaded file already exist. If you want to use a custom gtf from you hard drive, set GTF = FALSE, and assign: annotation <- getGenomeAndAnnotation(gtf = FALSE) annotation["gtf"] = "path/to/gtf.gtf". If db is not "ensembl", you will instead get a gff file.
genome	<pre>logical, default: TRUE, download genome of organism specified in "organism" argument. If FALSE, check if the downloaded file already exist. If you want to use a custom gtf from you hard drive, set GTF = FALSE, and assign: annotation <- getGenomeAndAnnotation(genome = FALSE) annotation["genome"] = "path/to/genome.fasta". Will download the primary assembly from Ensembl.</pre>
merge_contamina	nts
	logical, default TRUE. Will merge the contaminants specified into one fasta file, this considerably saves space and is much quicker to align with STAR than each contaminant on it's own. If no contaminants are specified, this is ignored.
phix	logical, default FALSE, download phiX sequence to filter out Illumina control reads. ORFik defines Phix as a contaminant genome. Phix is used in Illumina sequencers for sequencing quality control. Genome is: refseq, Escherichia phage phiX174. If sequencing facility created fastq files with the command bcl2fastq, then there should be very few phix reads left in the fastq files recieved.
ncRNA	logical or character, default FALSE (not used, no download), if TRUE or defned path, ncRNA is used as a contaminant reference. If TRUE, will try to find ncRNA sequences from the gtf file, usually represented as lncRNA (long non- coding RNA's). Will let you know if no ncRNA sequences were found in gtf. If not found try character input: Alternatives; "auto": Will try to find ncRNA file on NONCODE from organ- ism, Homo sapiens -> human etc. "auto" will not work for all, then you must specify the name used by NONCODE, go to the link below and find it. If not "auto" / "" it must be a character vector of species common name (not scientific name) Homo sapiens is human, Rattus norwegicus is rat etc, download ncRNA sequence to filter out with. From NONCODE online server, if you cant find common name see: http://www.noncode.org/download.php/
tRNA	logical or character, default FALSE (not used, no download), tRNA is used as a contaminant genome. If TRUE, will try to find tRNA sequences from the gtf file, usually represented as Mt_tRNA (mature tRNA's). Will let you know if no tRNA sequences were found in gtf. If not found try character input: if not "" it must be a character vector to valid path of mature tRNAs fasta file to remove as contaminants on your disc. Find and download your wanted mtRNA at: http://gtrnadb.ucsc.edu/, or run trna-scan on you genome.
rRNA	logical or character, default FALSE (not used, no download), rRNA is used as a contaminant reference If TRUE, will try to find rRNA sequences from the gtf file, usually represented as rRNA (ribosomal RNA's). Will let you know if no rRNA sequences were found in gtf. If not found you can try character input: If "silva" will download silva SSU & LSU sequences for all species (250MB file) and use that. If you want a smaller file go to https://www.arb-silva.de/ If not "" or "silva" it must be a character vector to valid path of mature rRNA fasta file to remove as contaminants on your disc.
gunzip	logical, default TRUE, uncompress downloaded files that are zipped when downloaded, should be TRUE!

remake	logical, default: FALSE, if TRUE remake everything specified
assembly_type	character, default c("primary_assembly", "toplevel"). Used for ensembl only, specifies the genome assembly type. Searches for both primary and toplevel, and if both are found, uses the first by order (so primary is prioritized by default). The Primary assembly should usually be used if it exists. The "primary assembly" contains all the top-level sequence regions, excluding alternative haplotypes and patches. If the primary assembly file is not present for a species (only defined for standard model organisms), that indicates that there were no haplotype/patch regions, and in such cases, the 'toplevel file is used. For more details see: ensembl tutorial
optimize	logical, default FALSE. Create a folder within the folder of the gtf, that in- cludes optimized objects to speed up loading of annotation regions from up to 15 seconds on human genome down to 0.1 second. ORFik will then load these optimized objects instead. Currently optimizes filterTranscript() function and loadRegion() function for 5' UTRs, 3' UTRs, CDS, mRNA (all transcript with CDS) and tx (all transcripts).
gene_symbols	logical default FALSE. If TRUE, will download and store all gene symbols for all transcripts (coding and noncoding)- In a file called: "gene_symbol_tx_table.fst" in same folder as txdb. hgcn for human, mouse symbols for mouse and rat, more to be added.
uniprot_id	logical default FALSE. If TRUE, will download and store all uniprot id for all transcripts (coding and noncoding)- In a file called: "gene_symbol_tx_table.fst" in same folder as txdb.
pseudo_5UTRS_if	`_needed
	integer, default NULL. If defined > 0, will add pseudo 5' UTRs if 30 a leader.
remove_annotati	on_outliers
	logical, default TRUE. Only for refseq. shall outlier lines be removed from the input annotation_file? If yes, then the initial annotation_file will be overwritten and the removed outlier lines will be stored at tempdir for further exploration. Among others Aridopsis refseq contains malformed lines, where this is needed
notify_load_exi	sting
	logical, default TRUE. If annotation exists (defined as: locally (a file called outputs.rds) exists in outputdir), print a small message notifying the user it is not redownloading. Set to FALSE, if this is not wanted
assembly	character, default is assembly = organism, which means getting the first assembly in list, otherwise the name of the assembly wanted, like "GCA_000005845" will get ecoli substrain k12, which is the most used ones for references. Usually ignore this for non bacterial species.
ails	

Details

Some files that are made after download:

- A fasta index for the genome
- A TxDb to speed up GTF/GFF reading
- Seperat of merged contaminant files

Files that can be made:

- Gene symbols (hgnc, etc)
- Uniprot ids (For name of protein structures)

If you want custom genome or gtf from you hard drive, assign existing paths like this:

annotation <- getGenomeAndAnnotation(GTF = "path/to/gtf.gtf", genome = "path/to/genome.fasta")

getGRanges

Value

a named character vector of path to genomes and gtf downloaded, and additional contaminants if used. If merge_contaminants is TRUE, will not give individual fasta files to contaminants, but only the merged one.

See Also

```
Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(),
STAR.install(), STAR.multiQC(), STAR.remove.crashed.genome(), install.fastp()
```

Examples

```
## Get Saccharomyces cerevisiae genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel")
## Download and add pseudo 5' UTRs
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel",
# pseudo_5UTRS_if_needed = 100)
## Get Danio rerio genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Danio rerio", tempdir())
output.dir <- "/Bio_data/references/zebrafish"</pre>
## Get Danio rerio and Phix contamints to deplete during alignment
#getGenomeAndAnnotation("Danio rerio", output.dir, phix = TRUE)
## Optimize for ORFik (speed up for large annotations like human or zebrafish)
#getGenomeAndAnnotation("Danio rerio", tempdir(), optimize = TRUE)
# Drosophila melanogaster (toplevel exists only)
#getGenomeAndAnnotation("drosophila melanogaster", output.dir = file.path(config["ref"],
# "Drosophila_melanogaster_BDGP6"), assembly_type = "toplevel")
## How to save malformed refseq gffs:
## First run function and let it crash:
#annotation <- getGenomeAndAnnotation(organism = "Arabidopsis thaliana",</pre>
# output.dir = "~/Desktop/test_plant/",
# assembly_type = "primary_assembly", db = "refseq")
## Then apply a fix (example for linux, too long rows):
# fixed_gff <- fix_malformed_gff("~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.gff")</pre>
## Then updated arguments:
# annotation <- c(fixed_gff, "~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.fna")</pre>
# names(annotation) <- c("gtf", "genome")</pre>
# Then make the txdb (for faster R use)
# makeTxdbFromGenome(annotation["gtf"], annotation["genome"], organism = "Arabidopsis thaliana")
```

getGRanges

Internal GRanges loader from fst data.frame

Description

Internal GRanges loader from fst data.frame

Usage

getGRanges(df, seqinfo = NULL)

Arguments

df	a data.frame with columns minimum 4 columns: seqnames, start, strand Additional specific columns are:
	- width (if not set, width is set to 1 for all reads) Additional columns will be assigned as meta columns
seqinfo	Seqinfo object, defaul NULL (created from ranges). Add to avoid warnings later on differences in seqinfo.

Value

GRanges object

getGtfPathFromTxdb Get path of GTF that created txdb

Description

Will crash and report proper error if no gtf is found

Usage

```
getGtfPathFromTxdb(txdb, stop.error = TRUE)
```

Arguments

txdb	a loaded TxDb object
stop.error	logical TRUE, stop if Txdb does not have a gtf. If FALSE, return NULL.

Value

a character file path, returns NULL if not valid and stop.error is FALSE.

getNGenesCoverage Get number of genes per coverage table

Description

Used to count genes in ORFik meta plots

Usage

getNGenesCoverage(coverage)

Arguments

coverage a data.table with coverage

Value

number of genes in coverage

getWeights

Description

Get weights from a subject GenomicRanges object

Usage

```
getWeights(subject, weight = 1L)
```

Arguments

subject	a GRanges, IRanges or GAlignment object
weight	a vector (default: 1L, if 1L it is identical to countOverlaps()), if single number (!= 1), it applies for all, if more than one must be equal size of 'reads'. else it must be the string name of a defined meta column in subject "reads", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean "score" column tells that this alignment region was found 5 times.

Value

a numeric vector of weights of equal size to subject

get_bioproject_candidates

Query eutils for bioproject IDs

Description

The default query of Ribosome Profiling human, will result in internal entrez search of: Ribosome[All Fields] AND Profiling[All Fields] AND ("Homo sapiens"[Organism] OR human[All Fields])

Usage

```
get_bioproject_candidates(
  term = "Ribosome Profiling human",
  as_accession = TRUE,
  add_study_title = FALSE,
  RetMax = 10000
)
```

Arguments

term	character, default "Ribosome Profiling human". A space is translated into AND, that means "Ribosome AND Profiling AND human", will give same as above. To do OR operation, do: "Ribosome OR profiling OR human".
as_accession	logical, default TRUE. Get bioproject accessions: PRJNA, PRJEB, PRJDB values, or IDs (FALSE), numbers only. Accessions are usually the thing needed for most tools.
add_study_title	
	logical, default FALSE. If TRUE, return as data table with 2 columns: id: ID or accessions. title: The title of the study.
RetMax	integer, default 10000. How many IDs to return maximum

Value

character vector of Accessions or IDs. If add_study_title is TRUE, returns a data.table.

References

https://www.ncbi.nlm.nih.gov/books/NBK25501/

See Also

Other sra: browseSRA(), download.SRA(), download.SRA.metadata(), download.ebi(), install.sratoolkit(), rename.SRA.files()

Examples

```
term <- "Ribosome Profiling Saccharomyces cerevisiae"
# get_bioproject_candidates(term)</pre>
```

get_genome_fasta Download genome (fasta), annotation (GTF) and contaminants

Description

This function automatically downloads (if files not already exists) genomes and contaminants specified for genome alignment. By default, it will use ensembl reference, upon completion, the function will store a file called file.path(output.dir, "outputs.rds") with the output paths of your completed genome/annotation downloads. For most non-model nonvertebrate organisms, you need my fork of biomartr for it to work: remotes::install_github("Roleren/biomartr) If you misspelled something or crashed, delete wrong files and run again. Do remake = TRUE, to do it all over again.

get_genome_fasta

Usage

```
get_genome_fasta(
   genome,
   output.dir,
   organism,
   assembly,
   assembly_type,
   db,
   gunzip
```

```
)
```

Arguments

genome	<pre>logical, default: TRUE, download genome of organism specified in "organism" argument. If FALSE, check if the downloaded file already exist. If you want to use a custom gtf from you hard drive, set GTF = FALSE, and assign: annotation <- getGenomeAndAnnotation(genome = FALSE) annotation["genome"] = "path/to/genome.fasta". Will download the primary assembly from Ensembl.</pre>
output.dir	directory to save downloaded data
organism	scientific name of organism, Homo sapiens, Danio rerio, Mus musculus, etc. See biomartr:::get.ensembl.info() for full list of supported organisms.
assembly	character, default is assembly = organism, which means getting the first assembly in list, otherwise the name of the assembly wanted, like " $GCA_000005845$ " will get ecoli substrain k12, which is the most used ones for references. Usually ignore this for non bacterial species.
assembly_type	character, default c("primary_assembly", "toplevel"). Used for ensembl only, specifies the genome assembly type. Searches for both primary and toplevel, and if both are found, uses the first by order (so primary is prioritized by default). The Primary assembly should usually be used if it exists. The "primary assembly" contains all the top-level sequence regions, excluding alternative haplotypes and patches. If the primary assembly file is not present for a species (only defined for standard model organisms), that indicates that there were no haplotype/patch regions, and in such cases, the 'toplevel file is used. For more details see: ensembl tutorial
db	database to use for genome and GTF, default adviced: "ensembl" (remember to set assembly_type to "primary_assembly", else it will contain haplotypes, very large file!). Alternatives: "refseq" (reference assemblies) and "genbank" (all assemblies)
gunzip	logical, default TRUE, uncompress downloaded files that are zipped when down-loaded, should be TRUE!

Details

Some files that are made after download:

- A fasta index for the genome
- A TxDb to speed up GTF/GFF reading
- Seperat of merged contaminant files

Files that can be made:

- Gene symbols (hgnc, etc)
- Uniprot ids (For name of protein structures)

If you want custom genome or gtf from you hard drive, assign existing paths like this: annotation <- getGenomeAndAnnotation(GTF = "path/to/gtf.gtf", genome = "path/to/genome.fasta")

Value

a named character vector of path to genomes and gtf downloaded, and additional contaminants if used. If merge_contaminants is TRUE, will not give individual fasta files to contaminants, but only the merged one.

See Also

```
Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(),
STAR.install(), STAR.multiQC(), STAR.remove.crashed.genome(), install.fastp()
```

Examples

```
## Get Saccharomyces cerevisiae genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel")
## Download and add pseudo 5' UTRs
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel",
# pseudo_5UTRS_if_needed = 100)
## Get Danio rerio genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Danio rerio", tempdir())
output.dir <- "/Bio_data/references/zebrafish"</pre>
## Get Danio rerio and Phix contamints to deplete during alignment
#getGenomeAndAnnotation("Danio rerio", output.dir, phix = TRUE)
## Optimize for ORFik (speed up for large annotations like human or zebrafish)
#getGenomeAndAnnotation("Danio rerio", tempdir(), optimize = TRUE)
# Drosophila melanogaster (toplevel exists only)
#getGenomeAndAnnotation("drosophila melanogaster", output.dir = file.path(config["ref"],
# "Drosophila_melanogaster_BDGP6"), assembly_type = "toplevel")
## How to save malformed refseq gffs:
## First run function and let it crash:
#annotation <- getGenomeAndAnnotation(organism = "Arabidopsis thaliana",</pre>
# output.dir = "~/Desktop/test_plant/",
# assembly_type = "primary_assembly", db = "refseq")
## Then apply a fix (example for linux, too long rows):
# fixed_gff <- fix_malformed_gff("~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.gff")</pre>
## Then updated arguments:
# annotation <- c(fixed_gff, "~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.fna")</pre>
# names(annotation) <- c("gtf", "genome")</pre>
# Then make the txdb (for faster R use)
# makeTxdbFromGenome(annotation["gtf"], annotation["genome"], organism = "Arabidopsis thaliana")
```

get_genome_gtf

Download genome (fasta), annotation (GTF) and contaminants

Description

This function automatically downloads (if files not already exists) genomes and contaminants specified for genome alignment. By default, it will use ensembl reference, upon completion, the function will store a file called file.path(output.dir, "outputs.rds") with the output paths of your completed genome/annotation downloads. For most non-model nonvertebrate organisms, you need my fork of biomartr for it to work: remotes::install_github("Roleren/biomartr) If you misspelled something or crashed, delete wrong files and run again. Do remake = TRUE, to do it all over again.

Usage

```
get_genome_gtf(
GTF,
output.dir,
organism,
assembly,
db,
gunzip,
genome,
optimize = FALSE,
uniprot_id = FALSE,
gene_symbols = FALSE,
pseudo_5UTRS_if_needed = NULL,
remove_annotation_outliers = TRUE
)
```

GTF	logical, default: TRUE, download gtf of organism specified in "organism" argu- ment. If FALSE, check if the downloaded file already exist. If you want to use a custom gtf from you hard drive, set GTF = FALSE, and assign: annotation <- getGenomeAndAnnotation(gtf = FALSE) annotation["gtf"] = "path/to/gtf.gtf". If db is not "ensembl", you will instead get a gff file.
output.dir	directory to save downloaded data
organism	scientific name of organism, Homo sapiens, Danio rerio, Mus musculus, etc. See biomartr:::get.ensembl.info() for full list of supported organisms.
assembly	character, default is assembly = organism, which means getting the first assembly in list, otherwise the name of the assembly wanted, like "GCA_000005845" will get ecoli substrain k12, which is the most used ones for references. Usually ignore this for non bacterial species.
db	database to use for genome and GTF, default adviced: "ensembl" (remember to set assembly_type to "primary_assembly", else it will contain haplotypes, very large file!). Alternatives: "refseq" (reference assemblies) and "genbank" (all assemblies)
gunzip	logical, default TRUE, uncompress downloaded files that are zipped when downloaded, should be TRUE!
genome	character path, default NULL. Path to fasta genome, corresponding to the gtf. must be indexed (.fai file must exist there). If you want to make sure chromo-

		some naming of the GTF matches the genome and correct seqlengths. If value is NULL or FALSE, it will be ignored.
	optimize	logical, default FALSE. Create a folder within the folder of the gtf, that includes optimized objects to speed up loading of annotation regions from up to 15 seconds on human genome down to 0.1 second. ORFik will then load these optimized objects instead. Currently optimizes filterTranscript() function and loadRegion() function for 5' UTRs, 3' UTRs, CDS, mRNA (all transcript with CDS) and tx (all transcripts).
	uniprot_id	logical default FALSE. If TRUE, will download and store all uniprot id for all transcripts (coding and noncoding)- In a file called: "gene_symbol_tx_table.fst" in same folder as txdb.
	gene_symbols	logical default FALSE. If TRUE, will download and store all gene symbols for all transcripts (coding and noncoding)- In a file called: "gene_symbol_tx_table.fst in same folder as txdb. hgcn for human, mouse symbols for mouse and rat, more to be added.
pseudo_5UTRS_if_needed		
		integer, default NULL. If defined > 0, will add pseudo 5' UTRs if 30 a leader.
remove_annotation_outliers		
		logical, default TRUE. Only for refseq. shall outlier lines be removed from the input annotation_file? If yes, then the initial annotation_file will be overwritten and the removed outlier lines will be stored at tempdir for further exploration. Among others Aridopsis refseq contains malformed lines, where this is needed

Details

Some files that are made after download:

- A fasta index for the genome

- A TxDb to speed up GTF/GFF reading

- Seperat of merged contaminant files

Files that can be made:

- Gene symbols (hgnc, etc)

- Uniprot ids (For name of protein structures)

If you want custom genome or gtf from you hard drive, assign existing paths like this:

annotation <- getGenomeAndAnnotation (GTF = "path/to/gtf.gtf", genome = "path/to/genome.fasta")

Value

a named character vector of path to genomes and gtf downloaded, and additional contaminants if used. If merge_contaminants is TRUE, will not give individual fasta files to contaminants, but only the merged one.

See Also

```
Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(),
STAR.install(), STAR.multiQC(), STAR.remove.crashed.genome(), install.fastp()
```

Examples

Get Saccharomyces cerevisiae genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel")
Download and add pseudo 5' UTRs
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel",

get_noncoding_rna

```
# pseudo_5UTRS_if_needed = 100)
## Get Danio rerio genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Danio rerio", tempdir())
output.dir <- "/Bio_data/references/zebrafish"</pre>
## Get Danio rerio and Phix contamints to deplete during alignment
#getGenomeAndAnnotation("Danio rerio", output.dir, phix = TRUE)
## Optimize for ORFik (speed up for large annotations like human or zebrafish)
#getGenomeAndAnnotation("Danio rerio", tempdir(), optimize = TRUE)
# Drosophila melanogaster (toplevel exists only)
#getGenomeAndAnnotation("drosophila melanogaster", output.dir = file.path(config["ref"],
# "Drosophila_melanogaster_BDGP6"), assembly_type = "toplevel")
## How to save malformed refseq gffs:
## First run function and let it crash:
#annotation <- getGenomeAndAnnotation(organism = "Arabidopsis thaliana",</pre>
# output.dir = "~/Desktop/test_plant/",
# assembly_type = "primary_assembly", db = "refseq")
## Then apply a fix (example for linux, too long rows):
# fixed_gff <- fix_malformed_gff("~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.gff")</pre>
## Then updated arguments:
# annotation <- c(fixed_gff, "~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.fna")</pre>
# names(annotation) <- c("gtf", "genome")</pre>
# Then make the txdb (for faster R use)
# makeTxdbFromGenome(annotation["gtf"], annotation["genome"], organism = "Arabidopsis thaliana")
```

get_noncoding_rna Download genome (fasta), annotation (GTF) and contaminants

Description

This function automatically downloads (if files not already exists) genomes and contaminants specified for genome alignment. By default, it will use ensembl reference, upon completion, the function will store a file called file.path(output.dir, "outputs.rds") with the output paths of your completed genome/annotation downloads. For most non-model nonvertebrate organisms, you need my fork of biomartr for it to work: remotes::install_github("Roleren/biomartr) If you misspelled something or crashed, delete wrong files and run again. Do remake = TRUE, to do it all over again.

Usage

```
get_noncoding_rna(ncRNA, output.dir, organism, gunzip)
```

ncRNA	logical or character, default FALSE (not used, no download), if TRUE or defned
	path, ncRNA is used as a contaminant reference. If TRUE, will try to find
	ncRNA sequences from the gtf file, usually represented as lncRNA (long non-
	coding RNA's). Will let you know if no ncRNA sequences were found in gtf.
	If not found try character input:
	Alternatives; "auto": Will try to find ncRNA file on NONCODE from organ-
	ism, Homo sapiens -> human etc. "auto" will not work for all, then you must

	specify the name used by NONCODE, go to the link below and find it. If not "auto" / "" it must be a character vector of species common name (not scientific name) Homo sapiens is human, Rattus norwegicus is rat etc, download ncRNA sequence to filter out with. From NONCODE online server, if you cant find common name see: http://www.noncode.org/download.php/
output.dir	directory to save downloaded data
organism	scientific name of organism, Homo sapiens, Danio rerio, Mus musculus, etc. See biomartr:::get.ensembl.info() for full list of supported organisms.
gunzip	logical, default TRUE, uncompress downloaded files that are zipped when downloaded, should be TRUE!

Details

Some files that are made after download:

- A fasta index for the genome
- A TxDb to speed up GTF/GFF reading
- Seperat of merged contaminant files
- Files that can be made:
- Gene symbols (hgnc, etc)
- Uniprot ids (For name of protein structures)

If you want custom genome or gtf from you hard drive, assign existing paths like this:

annotation <- getGenomeAndAnnotation(GTF = "path/to/gtf.gtf", genome = "path/to/genome.fasta")

Value

a named character vector of path to genomes and gtf downloaded, and additional contaminants if used. If merge_contaminants is TRUE, will not give individual fasta files to contaminants, but only the merged one.

See Also

```
Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(),
STAR.install(), STAR.multiQC(), STAR.remove.crashed.genome(), install.fastp()
```

Examples

```
## Get Saccharomyces cerevisiae genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel")
## Download and add pseudo 5' UTRs
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel",
# pseudo_5UTRS_if_needed = 100)
## Get Danio rerio genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Danio rerio", tempdir())
output.dir <- "/Bio_data/references/zebrafish"
## Get Danio rerio and Phix contamints to deplete during alignment
#getGenomeAndAnnotation("Danio rerio", output.dir, phix = TRUE)
## Optimize for ORFik (speed up for large annotations like human or zebrafish)
#getGenomeAndAnnotation("Danio rerio", tempdir(), optimize = TRUE)</pre>
```

```
# Drosophila melanogaster (toplevel exists only)
#getGenomeAndAnnotation("drosophila melanogaster", output.dir = file.path(config["ref"],
```

```
# "Drosophila_melanogaster_BDGP6"), assembly_type = "toplevel")
## How to save malformed refseq gffs:
## First run function and let it crash:
#annotation <- getGenomeAndAnnotation(organism = "Arabidopsis thaliana",
# output.dir = "~/Desktop/test_plant/",
# assembly_type = "primary_assembly", db = "refseq")
## Then apply a fix (example for linux, too long rows):
# fixed_gff <- fix_malformed_gff("~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.gff")
## Then updated arguments:
# annotation <- c(fixed_gff, "~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.fna")
# names(annotation) <- c("gtf", "genome")
# Then make the txdb (for faster R use)
# makeTxdbFromGenome(annotation["gtf"], annotation["genome"], organism = "Arabidopsis thaliana")</pre>
```

get_phix_genome Download genome (fasta), annotation (GTF) and contaminants

Description

This function automatically downloads (if files not already exists) genomes and contaminants specified for genome alignment. By default, it will use ensembl reference, upon completion, the function will store a file called file.path(output.dir, "outputs.rds") with the output paths of your completed genome/annotation downloads. For most non-model nonvertebrate organisms, you need my fork of biomartr for it to work: remotes::install_github("Roleren/biomartr) If you misspelled something or crashed, delete wrong files and run again. Do remake = TRUE, to do it all over again.

Usage

get_phix_genome(phix, output.dir, gunzip)

Arguments

phix	logical, default FALSE, download phiX sequence to filter out Illumina control
	reads. ORFik defines Phix as a contaminant genome. Phix is used in Illu-
	mina sequencers for sequencing quality control. Genome is: refseq, Escherichia
	phage phiX174. If sequencing facility created fastq files with the command
	bcl2fastq, then there should be very few phix reads left in the fastq files re-
	cieved.
output.dir	directory to save downloaded data
gunzip	logical, default TRUE, uncompress downloaded files that are zipped when down-
	loaded, should be TRUE!

Details

Some files that are made after download:

- A fasta index for the genome
- A TxDb to speed up GTF/GFF reading
- Seperat of merged contaminant files
- Files that can be made:
- Gene symbols (hgnc, etc)

Uniprot ids (For name of protein structures)
 If you want custom genome or gtf from you hard drive, assign existing paths like this:
 annotation <- getGenomeAndAnnotation(GTF = "path/to/gtf.gtf", genome = "path/to/genome.fasta")

Value

a named character vector of path to genomes and gtf downloaded, and additional contaminants if used. If merge_contaminants is TRUE, will not give individual fasta files to contaminants, but only the merged one.

See Also

```
Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(),
STAR.install(), STAR.multiQC(), STAR.remove.crashed.genome(), install.fastp()
```

Examples

```
## Get Saccharomyces cerevisiae genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel")
## Download and add pseudo 5' UTRs
#getGenomeAndAnnotation("Saccharomyces cerevisiae", tempdir(), assembly_type = "toplevel",
# pseudo_5UTRS_if_needed = 100)
## Get Danio rerio genome and gtf (create txdb for R)
#getGenomeAndAnnotation("Danio rerio", tempdir())
output.dir <- "/Bio_data/references/zebrafish"</pre>
## Get Danio rerio and Phix contamints to deplete during alignment
#getGenomeAndAnnotation("Danio rerio", output.dir, phix = TRUE)
## Optimize for ORFik (speed up for large annotations like human or zebrafish)
#getGenomeAndAnnotation("Danio rerio", tempdir(), optimize = TRUE)
# Drosophila melanogaster (toplevel exists only)
#getGenomeAndAnnotation("drosophila melanogaster", output.dir = file.path(config["ref"],
# "Drosophila_melanogaster_BDGP6"), assembly_type = "toplevel")
## How to save malformed refseq gffs:
## First run function and let it crash:
#annotation <- getGenomeAndAnnotation(organism = "Arabidopsis thaliana",</pre>
# output.dir = "~/Desktop/test_plant/",
# assembly_type = "primary_assembly", db = "refseq")
## Then apply a fix (example for linux, too long rows):
# fixed_gff <- fix_malformed_gff("~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.gff")</pre>
## Then updated arguments:
# annotation <- c(fixed_gff, "~/Desktop/test_plant/Arabidopsis_thaliana_genomic_refseq.fna")</pre>
# names(annotation) <- c("gtf", "genome")</pre>
# Then make the txdb (for faster R use)
# makeTxdbFromGenome(annotation["gtf"], annotation["genome"], organism = "Arabidopsis thaliana")
```

get_silva_rRNA Download Silva SSU & LSU sequences

Description

Version downloaded is 138.1. NR99_tax (non redundant)

groupGRangesBy

Usage

get_silva_rRNA(output.dir)

Arguments

```
output.dir directory to save downloaded data
```

Details

If it fails from timeout, set higher timeout: options(timeout = 200)

Value

filepath to downloaded file

Examples

```
output.dir <- tempdir()
# get_silva_rRNA(output.dir)</pre>
```

groupGRangesBy Group GRanges

Description

It will group / split the GRanges object by the argument 'other'. For example if you would like to to group GRanges object by gene, set other to gene names.

If 'other' is not specified function will try to use the names of the GRanges object. It will then be similar to 'split(gr, names(gr))'.

Usage

groupGRangesBy(gr, other = NULL)

Arguments

gr	a GRanges object
other	a vector of unique names to group by (default: NULL)

Details

It is important that all intended groups in 'other' are uniquely named, otherwise duplicated group names will be grouped together.

Value

a GRangesList named after names(GRanges) if other is NULL, else names are from unique(other)

Examples

```
ORFranges <- GRanges(seqnames = Rle(rep("1", 3)),</pre>
                      ranges = IRanges(start = c(1, 10, 20),
                                        end = c(5, 15, 25)),
                      strand = "+")
ORFranges2 <- GRanges("1",</pre>
                       ranges = IRanges(start = c(20, 30, 40),
                                         end = c(25, 35, 45)),
                       strand = "+")
names(ORFranges) = rep("tx1_1", 3)
names(ORFranges2) = rep("tx1_2", 3)
grl <- GRangesList(tx1_1 = ORFranges, tx1_2 = ORFranges2)</pre>
gr <- unlist(grl, use.names = FALSE)</pre>
## now recreate the grl
## group by orf
grltest <- groupGRangesBy(gr) # using the names to group</pre>
identical(grl, grltest) ## they are identical
## group by transcript
names(gr) <- txNames(gr)</pre>
grltest <- groupGRangesBy(gr)</pre>
identical(grl, grltest) ## they are not identical
```

groupings

```
Get number of ranges per group as an iteration
```

Description

Get number of ranges per group as an iteration

Usage

groupings(grl)

Arguments

grl GRangesList

Value

an integer vector

Examples

178

gSort

Description

A helper for [sortPerGroup()]. A faster, more versatile reimplementation of GenomicRanges::sort() Normally not used directly. Groups first each group, then either decreasing or increasing (on starts if byStarts == T, on ends if byStarts == F)

Usage

gSort(grl, decreasing = FALSE, byStarts = TRUE)

Arguments

grl	a GRangesList
decreasing	should the first in each group have $max(start(group)) \rightarrow T$ or $min \rightarrow default(F)$?
byStarts	a logical T, should it order by starts or ends F.

Value

an equally named GRangesList, where each group is sorted within group.

|--|

Description

Finding GRanges groups that have overlap hits with reads Similar to

Usage

```
hasHits(grl, reads, keep.names = FALSE, overlaps = NULL)
```

Arguments

grl	a GRangesList or GRanges object
reads	a GRanges, GAlignment or GAlignmentPairs object
keep.names	logical (F), keep names or not
overlaps	default NULL, if not null must be countOverlaps(grl, reads), input if you have it already.

Value

a list of logicals, T == hit, F == no hit

heatMapL

Description

Coverage heatmap of multiple libraries

Usage

```
heatMapL(
  region,
  tx,
  df,
  outdir,
  scores = "sum",
  upstream,
  downstream,
  zeroPosition = upstream,
  acceptedLengths = NULL,
  type = "ofst",
  legendPos = "right",
  colors = "default",
  addFracPlot = TRUE,
  location = "TIS",
  shifting = NULL,
  skip.last = FALSE,
  plot.ext = ".pdf",
  plot.together = TRUE,
  title = TRUE,
  scale_x = 5.5,
  scale_y = 15.5,
  gradient.max = "default",
  BPPARAM = BiocParallel::SerialParam()
)
```

region	#' a GRangesList object of region, usually either leaders, cds', 3' utrs or ORFs, start region, stop regions etc. This is the region that will be mapped in heatmap	
tx	default NULL, a GRangesList of transcripts or (container region), names of tx must contain all grl names. The names of grl can also be the ORFik orf names. that is "txName_id"	
df	an ORFik experiment	
outdir	a character path to directory to save plot, will be named from ORFik experiment columns	
scores	character vector, default c("transcriptNormalized", "sum"), either of zs- core, transcriptNormalized, sum, mean, median, see ?coverageScorings for info and more alternatives.	
upstream	1 or 2 integers, default $c(50, 30)$, how long upstream from 0 should window extend (first index is 5' end extension, second is 3' end extension). If only 1 shifting, only 1 value should be given, if two are given will use first.	
-----------------	---	--
downstream	1 or 2 integers, default $c(29, 69)$, how long upstream from 0 should window extend (first index is 5' end extension, second is 3' end extension). If only 1 shifting, only 1 value should be given, if two are given will use first.	
zeroPosition	an integer DEFAULT (upstream), what is the center point? Like leaders and cds combination, then 0 is the TIS and -1 is last base in leader. NOTE!: if windows have different widths, this will be ignored.	
acceptedLengths		
	an integer vector (NULL), the read lengths accepted. Default NULL, means all lengths accepted.	
type	character, default: "ofst". Type of library: either "default", usually bam format (the one you gave to experiment), "pshifted" pshifted reads, "ofst", "bed", "bedo" optimized bed, or "wig"	
legendPos	a character, Default "right". Where should the fill legend be ? ("top", "bottom", "right", "left")	
colors	character vector, default: "default", this gives you: c("white", "yellow2", "yellow3", "lightblue", "blue", "navy"), do "high" for more high contrasts, or specify your own colors.	
addFracPlot	Add margin histogram plot on top of heatmap with fractions per positions	
location	a character, default "start site", will make xlabel of heatmap be Position relative to "start site" or alternative given.	
shifting	a character, default c("5prime", "3prime"), can also be NULL (no shifting of reads). If NULL, will use first index of 'upstream' and 'downstream' argument.	
skip.last	skip top(highest) read length, default FALSE	
plot.ext	a character, default ".pdf", alternative ".png"	
plot.together	logical (default: FALSE), plot all in 1 plot (if TRUE)	
title	a character, default NULL (no title), what is the top title of plot?	
scale_x	numeric, how should the width of the single plots be scaled, bigger the number, the bigger the plot	
scale_y	numeric, how should the height of the plots be scaled, bigger the number, the bigger the plot	
gradient.max	numeric or character, default: "default", which is: max(coverage\$score), the max coverage over all readlengths. If you want all plots to use same reference point for max scaling, then first detect this point, look at max in plot etc, and use that value, to get all plots to have same max point.	
BPPARAM	a core param, default: single thread: BiocParallel::SerialParam(). Set to BiocParallel::bpparam() to use multicore. Be aware, this uses a lot of extra ram (40GB+) for larger human samples!	

Value

invisible(NULL), plots are saved

See Also

Other heatmaps: coverageHeatMap(), heatMapRegion(), heatMap_single()

heatMapRegion

Description

Simplified input space for easier abstraction of coverage heatmaps Pick your transcript region and plot directly Input CAGE file if you use TSS and want improved 5' annotation.

Usage

```
heatMapRegion(
  df,
  region = "TIS",
  outdir = "default",
  scores = c("transcriptNormalized", "sum"),
  type = "ofst",
  cage = NULL,
  plot.ext = ".pdf",
  acceptedLengths = 21:75,
  upstream = c(50, 30),
  downstream = c(29, 69),
  shifting = c("5prime", "3prime"),
  longestPerGene = TRUE,
  colors = "default",
  scale_x = 5.5,
  scale_y = 15.5,
  gradient.max = "default",
  BPPARAM = BiocParallel::SerialParam()
)
```

Arguments

df	an ORFik experiment	
region	 a character, default "TIS". The centering point for the heatmap (what is position 0, beween -50 and 50 etc), can be any combination of the set: c("TSS", "TIS", "TTS", "TES"), which are: - Transcription start site (5' end of mrna) - Translation initation site (5' end of CDS) - Translation termination site (5' end of 3' UTRs) - Transcription end site (3' end of 3' UTRs) 	
outdir	a character path, default: "default", saves to: file.path(QCfolder(df), "heatmaps/"), a created folder within the ORFik experiment data folder for plots. Change if you want custom location.	
scores	character vector, default c("transcriptNormalized", "sum"), either of zs- core, transcriptNormalized, sum, mean, median, see ?coverageScorings for info and more alternatives.	
type	character, default: "ofst". Type of library: either "default", usually bam format (the one you gave to experiment), "pshifted" pshifted reads, "ofst", "bed", "bedo" optimized bed, or "wig"	

cage	a character path to library file or a GRanges, GAlignments preloaded file of CAGE data. Only used if "TSS" is defined as region, to redefine 5' leaders.	
<pre>plot.ext acceptedLengths</pre>	a character, default ".pdf", alternative ".png"	
	an integer vector (NULL), the read lengths accepted. Default NULL, means all lengths accepted.	
upstream	1 or 2 integers, default $c(50, 30)$, how long upstream from 0 should window extend (first index is 5' end extension, second is 3' end extension). If only 1 shifting, only 1 value should be given, if two are given will use first.	
downstream	1 or 2 integers, default $c(29, 69)$, how long upstream from 0 should window extend (first index is 5' end extension, second is 3' end extension). If only 1 shifting, only 1 value should be given, if two are given will use first.	
shifting	a character, default c("5prime", "3prime"), can also be NULL (no shifting of reads). If NULL, will use first index of 'upstream' and 'downstream' argument.	
longestPerGene	logical, default TRUE. Use only longest transcript isoform per gene. This will speed up your computation.	
colors	character vector, default: "default", this gives you: c("white", "yellow2", "yellow3", "lightblue", "blue", "navy"), do "high" for more high contrasts, or specify your own colors.	
scale_x	numeric, how should the width of the single plots be scaled, bigger the number, the bigger the plot	
scale_y	numeric, how should the height of the plots be scaled, bigger the number, the bigger the plot	
gradient.max	numeric or character, default: "default", which is: max(coverage\$score), the max coverage over all readlengths. If you want all plots to use same reference point for max scaling, then first detect this point, look at max in plot etc, and use that value, to get all plots to have same max point.	
BPPARAM	a core param, default: single thread: BiocParallel::SerialParam(). Set to BiocParallel::bpparam() to use multicore. Be aware, this uses a lot of extra ram (40GB+) for larger human samples!	

Value

invisible(NULL), plots are saved

See Also

Other heatmaps: coverageHeatMap(), heatMapL(), heatMap_single()

Examples

```
# Toy example, will not give logical output, but shows how it works
df <- ORFik.template.experiment()[9:10,] # Subset to 2 Ribo-seq libs
#heatMapRegion(df, "TIS", outdir = "default")
#
# Do also TSS, add cage for specific TSS
# heatMapRegion(df, c("TSS", "TIS"), cage = "path/to/cage.bed")
# Do on pshifted reads instead of original files
remove.experiments(df) # Remove loaded experiment first
# heatMapRegion(df, "TIS", type = "pshifted")
```

heatMap_single

Description

Coverage heatmap of single libraries

Usage

```
heatMap_single(
  region,
  tx,
  reads,
  outdir,
  scores = "sum",
  upstream,
  downstream,
  zeroPosition = upstream,
  returnCoverage = FALSE,
  acceptedLengths = NULL,
  legendPos = "right",
  colors = "default",
  addFracPlot = TRUE,
  location = "start site",
  shifting = NULL,
  skip.last = FALSE,
  title = NULL,
  gradient.max = "default"
)
```

Arguments

region	#' a GRangesList object of region, usually either leaders, cds', 3' utrs or ORFs, start region, stop regions etc. This is the region that will be mapped in heatmap
tx	default NULL, a GRangesList of transcripts or (container region), names of tx must contain all grl names. The names of grl can also be the ORFik orf names. that is "txName_id"
reads	a GAlignments, GRanges, or precomputed coverage as covRleList (where names of covRle objects are readlengths) of RiboSeq, RnaSeq etc. Weigths for scoring is default the 'score' column in 'reads'. Can also be random access paths to bigWig or fstwig file. Do not use random access for more than a few genes, then loading the entire files is usually better.
outdir	a character path to save file as: not just directory, but full name.
scores	character vector, default "sum", either of zscore, transcriptNormalized, sum, mean, median, see ?coverageScorings for info and more alternatives.
upstream	an integer, relative region to get upstream from.
downstream	an integer, relative region to get downstream from
zeroPosition	an integer DEFAULT (upstream), what is the center point? Like leaders and cds combination, then 0 is the TIS and -1 is last base in leader. NOTE!: if windows have different widths, this will be ignored.

import.bedo

logical, default: FALSE, return coverage, if FALSE returns plot instead.	
an integer vector (NULL), the read lengths accepted. Default NULL, means all lengths accepted.	
a character, Default "right". Where should the fill legend be ? ("top", "bottom", "right", "left")	
character vector, default: "default", this gives you: c("white", "yellow2", "yellow3", "lightblue", "blue", "navy"), do "high" for more high contrasts, or specify your own colors.	
Add margin histogram plot on top of heatmap with fractions per positions	
a character, default "start site", will make xlabel of heatmap be Position relative to "start site" or alternative given.	
a character, default NULL (no shifting), can also be either of c("5prime", "3prime")	
skip top(highest) read length, default FALSE	
a character, default NULL (no title), what is the top title of plot?	
numeric or character, default: "default", which is: max(coverage\$score), the max coverage over all readlengths. If you want all plots to use same reference point for max scaling, then first detect this point, look at max in plot etc, and use that value, to get all plots to have same max point.	

Value

ggplot2 grob (default), data.table (if returnCoverage is TRUE)

See Also

Other heatmaps: coverageHeatMap(), heatMapL(), heatMapRegion()

import.bedo

Load GRanges object from .bedo

Description

.bedo is .bed ORFik, an optimized bed format for coverage reads with read lengths .bedo is a text based format with columns (6 maximum):

- 1. chromosome
- 2. start
- 3. end
- 4. strand
- 5. ref width (cigar # M's, match/mismatch total)
- 6. duplicates of that read

Usage

import.bedo(path)

Arguments

path

a character, location on disc (full path)

Details

Positions are 1-based, not 0-based as .bed. export with export.bedo

Value

GRanges object

import.bedoc

Load GAlignments object from .bedoc

Description

A much faster way to store, load and use bam files. .bedoc is .bed ORFik, an optimized bed format for coverage reads with cigar and replicate number. .bedoc is a text based format with columns (5 maximum):

1. chromosome

2. cigar: (cigar # M's, match/mismatch total)

- 3. start (left most position)
- 4. strand (+, -, *)
- 5. score: duplicates of that read

Usage

import.bedoc(path)

Arguments

path

a character, location on disc (full path)

Details

Positions are 1-based, not 0-based as .bed. export with export.bedo

Value

GAlignments object

import.fstwig Import region from fastwig

Description

Import region from fastwig

Usage

```
import.fstwig(gr, dir, id = "", readlengths = "all")
```

import.ofst

Arguments

gr	a GRanges object of exons
dir	prefix to filepath for file strand and chromosome will be added
id	id to column type, not used currently!
readlengths	integer / character vector, default "all". Or a subset of readlengths.

Value

a data.table with columns specified by readlengths

import.ofst

Load GRanges / GAlignments object from .ofst

Description

A much faster way to store, load and use bam files.

.ofst is ORFik fast serialized object, an optimized format for coverage reads with cigar and replicate number. It uses the fst format as back-end: fst-package.

A .ofst ribo seq file can compress the information in a bam file from 5GB down to a few MB. This new files has super fast reading time, only a few seconds, instead of minutes. It also has random index access possibility of the file.

.ofst is represented as a data.frane format with minimum 4 columns:

- 1. chromosome
- 2. start (left most position)
- 3. strand (+, -, *)
- 4. width (not added if cigar exists)
- 5. cigar (not needed if width exists): (cigar # M's, match/mismatch total)
- 5. score: duplicates of that read
- 6. size: qwidth according to reference of read

If file is from GAlignmentPairs, it will contain a cigar1, cigar2 instead of cigar and start1 and start2 instead of start

Usage

```
import.ofst(file, strandMode = 0, seqinfo = NULL)
```

Arguments

file	a path to a .ofst file
strandMode	numeric, default 0. Only used for paired end bam files. One of (0: strand = $*$, 1: first read of pair is +, 2: first read of pair is -). See ?strandMode. Note: Sets default to 0 instead of 1, as readGAlignmentPairs uses 1. This is to guarantee hits, but will also make mismatches of overlapping transcripts in opposite directions.
seqinfo	Seqinfo object, defaul NULL (created from ranges). Add to avoid warnings later on differences in seqinfo.

Details

Other columns can be named whatever you want and added to meta columns. Positions are 1-based, not 0-based as .bed. Import with import.ofst

Value

a GAlignment, GAlignmentPairs or GRanges object, dependent of if cigar/cigar1 is defined in .ofst file.

Examples

```
## GRanges
gr <- GRanges("1:1-3:-")
tmp <- file.path(tempdir(), "path.ofst")
# export.ofst(gr, file = tmp)
# import.ofst(tmp)
## GAlignment
# Make input data.frame
df <- data.frame(seqnames = "1", cigar = "3M", start = 1L, strand = "+")
ga <- ORFik:::getGAlignments(df)
# export.ofst(ga, file = tmp)
# import.ofst(tmp)</pre>
```

importGtfFromTxdb Import the GTF / GFF that made the txdb

Description

Import the GTF / GFF that made the txdb

Usage

```
importGtfFromTxdb(txdb, stop.error = TRUE)
```

Arguments

txdb	a TxDb, path to txdb / gff or ORFik experiment object
stop.error	logical TRUE, stop if Txdb does not have a gtf. If FALSE, return NULL.

Value

data.frame, the gtf/gff object imported with rtracklayer::import. Or NULL, if stop.error is FALSE, and no GTF file found.

inhibitorNames

Description

Used to standardize nomeclature for experiments. Example: cycloheximide, lactimidomycin, harringtonine

Usage

```
inhibitorNames()
```

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

```
Other experiment_naming: batchNames(), cellLineNames(), cellTypeNames(), conditionNames(),
fractionNames(), libNames(), mainNames(), repNames(), stageNames(), tissueNames()
```

initiationScore Get initiation score for a GRangesList of ORFs

Description

initiationScore tries to check how much each TIS region resembles, the average of the CDS TIS regions.

Usage

initiationScore(grl, cds, tx, reads, pShifted = TRUE, weight = "score")

Arguments

grl	a GRangesList object with ORFs
cds	a GRangesList object with coding sequences
tx	a GRangesList of transcripts covering grl.
reads	ribo seq reads as GAlignments, GRanges or GRangesList object
pShifted	a logical (TRUE), are riboseq reads p-shifted?
weight	a vector (default: 1L, if 1L it is identical to countOverlaps()), if single number (!= 1), it applies for all, if more than one must be equal size of 'reads'. else it must be the string name of a defined meta column in subject "reads", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean "score" column tells that this alignment region was found 5 times.

Details

Since this features uses a distance matrix for scoring, values are distributed like this:

As result there is one value per ORF:

0.000: means that ORF had no reads

-1.000: means that ORF is identical to average of CDS

1.000: means that orf is maximum different than average of CDS

If a score column is defined, it will use it as weights, see getWeights

Value

an integer vector, 1 score per ORF, with names of grl

References

doi: 10.1186/s12915-017-0416-0

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(),
insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
# Good hiting ORF
ORF <- GRanges(seqnames = "1",</pre>
                ranges = IRanges(21, 40),
                strand = "+")
names(ORF) <- c("tx1")</pre>
grl <- GRangesList(tx1 = ORF)</pre>
# 1 width p-shifted reads
reads <- GRanges("1", IRanges(c(21, 23, 50, 50, 50, 53, 53, 56, 59),</pre>
                               width = 1), "+")
score(reads) <- 28 # original width</pre>
cds <- GRanges(seqnames = "1",</pre>
                ranges = IRanges(50, 80),
                strand = "+")
cds <- GRangesList(tx1 = cds)</pre>
tx <- GRanges(seqnames = "1",</pre>
                ranges = IRanges(1, 85),
                strand = "+")
tx <- GRangesList(tx1 = tx)</pre>
initiationScore(grl, cds, tx, reads, pShifted = TRUE)
```

insideOutsideORF Inside/Outside score (IO)

Description

Inside/Outside score is defined as

(reads over ORF)/(reads outside ORF and within transcript)

A pseudo-count of one is added to both the ORF and outside sums.

Usage

```
insideOutsideORF(
  grl,
  RFP,
  GtfOrTx,
  ds = NULL,
  RFP.sorted = FALSE,
  weight = 1L,
  overlapGrl = NULL
)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs.	
RFP	RiboSeq reads as GAlignments, GRanges or GRangesList object	
GtfOrTx	If it is TxDb object transcripts will be extracted using exonsBy(Gtf, by = "tx", use.names = TRUE). Else it must be GRangesList	
ds	numeric vector (NULL), disengagement score. If you have already calculated disengagementScore, input here to save time.	
RFP.sorted	<pre>logical (FALSE), an optimizer, have you ran this line: RFP <- sort(RFP[countOverlaps(RFP, tx, type = "within") > 0]) Normally not touched, for internal optimization purposes.</pre>	
weight	a vector (default: 1L, if 1L it is identical to countOverlaps()), if single number (!= 1), it applies for all, if more than one must be equal size of 'reads'. else it must be the string name of a defined meta column in subject "reads", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean "score" column tells that this alignment region was found 5 times.	
overlapGrl	an integer, (default: NULL), if defined must be countOverlaps(grl, RFP), added for speed if you already have it	

Value

a named vector of numeric values of scores

References

doi: 10.1242/dev.098345

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(),
initiationScore(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
# Check inside outside score of a ORF within a transcript
ORF <- GRanges("1",
                ranges = IRanges(start = c(20, 30, 40),
                                    end = c(25, 35, 45)),
                strand = "+")
grl <- GRangesList(tx1_1 = ORF)</pre>
tx1 <- GRanges(seqnames = "1",</pre>
                ranges = IRanges(start = c(1, 10, 20, 30, 40, 50),
                                  end = c(5, 15, 25, 35, 45, 200)),
               strand = "+")
tx <- GRangesList(tx1 = tx1)</pre>
RFP <- GRanges(seqnames = "1",</pre>
                   ranges = IRanges(start = c(1, 4, 30, 60, 80, 90),
                                     end = c(30, 33, 63, 90, 110, 120)),
                   strand = "+")
insideOutsideORF(grl, RFP, tx)
```

install.fastp Download and prepare fastp trimmer

Description

On Linux, will not run "make", only use precompiled fastp file. On Mac OS it will use precompiled binaries. For windows must be installed through WSL (Windows Subsystem Linux)

Usage

```
install.fastp(folder = "~/bin")
```

Arguments

folder path to folder for download, file will be named "fastp", this should be most recent version. On mac it will search for a folder called fastp-master inside folder given. Since there is no precompiled version of fastp for Mac OS.

Value

path to runnable fastp

install.sratoolkit

References

https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6129281/

See Also

```
Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(),
STAR.install(), STAR.multiQC(), STAR.remove.crashed.genome(), getGenomeAndAnnotation()
```

Examples

```
## With default folder:
#install.fastp()
## Or set manual folder:
```

```
folder <- "~/I/WANT/IT/HERE/"
#install.fastp(folder)</pre>
```

install.sratoolkit Download sra toolkit

Description

Currently supported for Linux (64 bit centos and ubunutu is tested to work) and Mac-OS(64 bit). If other linux distro, centos binaries will be used.

Usage

```
install.sratoolkit(folder = "~/bin", version = "2.11.3")
```

Arguments

folder	default folder, "~/bin"
version	a string, default "2.11.3"

Value

path to fastq-dump in sratoolkit

References

https://ncbi.github.io/sra-tools/fastq-dump.html

See Also

Other sra: browseSRA(), download.SRA(), download.SRA.metadata(), download.ebi(), get_bioproject_candida rename.SRA.files()

Examples

```
# install.sratoolkit()
## Custom folder and version (not adviced)
folder <- "/I/WANT/IT/HERE/"
# install.sratoolkit(folder, version = "2.10.9")</pre>
```

is.grl

Description

Helper function to check for GRangesList

Usage

is.grl(class)

Arguments

class the class you want to check if is GRL, either a character from class or the object itself.

Value

a boolean

See Also

Other validity: checkRFP(), checkRNA(), is.ORF(), is.gr_or_grl(), is.range(), validGRL(), validSeqlevels()

is.gr_or_grl Helper function to check for GRangesList or GRanges class

Description

Helper function to check for GRangesList or GRanges class

Usage

```
is.gr_or_grl(class)
```

Arguments

class the class you want to check if is GRL or GR, either a character from class or the object itself.

Value

a boolean

See Also

Other validity: checkRFP(), checkRNA(), is.ORF(), is.grl(), is.range(), validGRL(), validSeqlevels()

is.ORF

Description

Check if all requirements for an ORFik ORF is accepted.

Usage

is.ORF(grl)

Arguments

grl a GRangesList or GRanges to check

Value

a logical (TRUE/FALSE)

See Also

```
Other validity: checkRFP(), checkRNA(), is.gr_or_grl(), is.grl(), is.range(), validGRL(),
validSeqlevels()
```

is.range

Helper function to check for ranged object

Description

Helper function to check for ranged object

Usage

is.range(x)

Arguments

Х

the object to check is a ranged object. Either GRangesList, GRanges, IRangesList, IRanges.

Value

a boolean

See Also

```
Other validity: checkRFP(), checkRNA(), is.ORF(), is.gr_or_grl(), is.grl(), validGRL(),
validSeqlevels()
```

isInFrame

Description

Input of this function, is the output of the function [distToCds()], or any other relative ORF frame.

Usage

```
isInFrame(dists)
```

Arguments

dists

a vector of integer distances between ORF and cds. 0 distance means equal frame

Details

possible outputs: 0: orf is in frame with cds 1: 1 shifted from cds 2: 2 shifted from cds

Value

a logical vector

References

doi: 10.1074/jbc.R116.733899

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(),
initiationScore(), insideOutsideORF(), isOverlapping(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
# simple example
isInFrame(c(3,6,8,11,15))
# GRangesList example
grl <- GRangesList(tx1_1 = GRanges("1", IRanges(1,10), "+"))
fiveUTRs <- GRangesList(tx1 = GRanges("1", IRanges(1,20), "+"))
dist <- distToCds(grl, fiveUTRs)
isInFrame <- isInFrame(dist)</pre>
```

isOverlapping

Description

Input of this function, is the output of the function [distToCds()]

Usage

```
isOverlapping(dists)
```

Arguments

dists a vector of distances between ORF and cds

Value

a logical vector

References

doi: 10.1074/jbc.R116.733899

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(),
initiationScore(), insideOutsideORF(), isInFrame(), kozakSequenceScore(), orfScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
# simple example
isOverlapping(c(-3,-6,8,11,15))
```

```
# GRangesList example
grl <- GRangesList(tx1_1 = GRanges("1", IRanges(1,10), "+"))
fiveUTRs <- GRangesList(tx1 = GRanges("1", IRanges(1,20), "+"))
dist <- distToCds(grl, fiveUTRs)
isOverlapping <- isOverlapping(dist)</pre>
```

isPeriodic

Description

It uses Fourier transform + periodogram for finding periodic vectors on the transcript normalized counts over all CDS regions from position 0 (TIS) to 149 (or other max position if increased by the user.

Checks if there is a periodicity and if the periodicity is 3, more precisely between 2.9 and 3.1.

Usage

isPeriodic(x, info = NULL, verbose = FALSE, strict.fft = TRUE)

Arguments

х	(numeric) Vector of values to detect periodicity of 3 like in RiboSeq data.	
info	specify read length if wanted for verbose output.	
verbose	logical, default FALSE. Report details of analysis/periodogram. Good if you are not sure if the analysis was correct.	
strict.fft	logical, TRUE. Use a FFT without noise filter. This means keep only reads lengths that are "periodic for the human eye". If you want more coverage, set to FALSE, to also get read lengths that are "messy", but the noise filter detects the periodicity of 3. This should only be done when you do not need high quality periodic reads! Example would be differential translation analysis by counts over each ORF.	

Details

Input data:

Transcript normalized means per CDS TIS region, count reads per position, divide that number per position by the total of that transcript, then sum up these numbers per position for all transcripts. Detection method:

The maximum dominant Fourier frequencies is found by finding which period has the highest spectrum density (using a 10

Value

a logical, if it is periodic.

kozakHeatmap

Description

Given sequences, DNA or RNA. And some score, ribo-seq fpkm, TE etc. Create a heatmap divided per letter in seqs, by how strong the score is.

Usage

```
kozakHeatmap(
  seqs,
  rate,
  start = 1,
  stop = max(nchar(seqs)),
  center = ceiling((stop - start + 1)/2),
  min.observations = ">q1",
  skip.startCodon = FALSE,
  xlab = "TIS",
  type = "ribo-seq"
)
```

Arguments

seqs	the sequences (character vector, DNAStringSet)	
rate	a scoring vector (equal size to seqs)	
start	position in seqs to start at (first is 1), default 1.	
stop	position in seqs to stop at (first is 1), default max(nchar(seqs)), that is the longest sequence length	
center	position in seqs to center at (first is 1), center will be +1 in heatmap	
min.observations		
	How many observations per position per letter to accept? numeric or quantile, default (">q1", bigger than quartile 1 (25 percentile)). You can do (10), to get all with more than 10 observations.	
<pre>skip.startCodon</pre>		
	startCodon is defined as after centering (position 1, 2 and 3). Should they be skipped ? default (FALSE). Not relevant if you are not doing Translation initiation sites (TIS).	
xlab	Region you are checking, default (TIS)	
type	What type is the rate scoring ? default (ribo-seq)	

Details

It will create blocks around the highest rate per position

Value

a ggplot of the heatmap

Examples

```
## Not run:
if (requireNamespace("BSgenome.Hsapiens.UCSC.hg19")) {
  txdbFile <- system.file("extdata", "hg19_knownGene_sample.sqlite",</pre>
                           package = "GenomicFeatures")
  #Extract sequences of Coding sequences.
  cds <- loadRegion(txdbFile, "cds")</pre>
  tx <- loadRegion(txdbFile, "mrna")</pre>
  # Get region to check
  kozakRegions <- startRegionString(cds, tx, BSgenome.Hsapiens.UCSC.hg19::Hsapiens</pre>
                                      , upstream = 4, 5)
  # Some toy ribo-seq fpkm scores on cds
  set.seed(3)
  fpkm <- sample(1:115, length(cds), replace = TRUE)</pre>
  kozakHeatmap(kozakRegions, fpkm, 1, 9, skip.startCodon = F)
}
## End(Not run)
```

kozakSequenceScore Make a score for each ORFs start region by proximity to Kozak

Description

The closer the sequence is to the Kozak sequence the higher the score, based on the experimental pwms from article referenced. Minimum score is 0 (worst correlation), max is 1 (the best base per column was chosen).

Usage

```
kozakSequenceScore(grl, tx, faFile, species = "human", include.N = FALSE)
```

Arguments

grl	a GRangesList grouped by ORF
tx	a ${\tt GRangesList},$ the reference area for ORFs, each ORF must have a coresponding tx.
faFile	FaFile, BSgenome, fasta/index file path or an ORFik experiment. This file is usually used to find the transcript sequences from some GRangesList.
species	("human"), which species to use, currently supports human (Homo sapiens), zebrafish (Danio rerio) and mouse (Mus musculus). Both scientific or common name for these species will work. You can also specify a pfm for your own species. Syntax of pfm is an rectangular integer matrix, where all columns must sum to the same value, normally 100. See example for more information. Rows are in order: c("A", "C", "G", "T")
include.N	logical (F), if TRUE, allow N bases to be counted as hits, score will be average of the other bases. If True, N bases will be added to pfm, automaticly, so dont include them if you make your own pfm.

Details

Ranges that does not have minimum 15 length (the kozak requirement as a sliding window of size 15 around grl start), will be set to score 0. Since they should not have the posibility to make an efficient ribosome binding.

Value

a numeric vector with values between 0 and 1

an integer vector, one score per orf

References

doi: https://doi.org/10.1371/journal.pone.0108475

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(), distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), orfScore(), rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(), stopRegion(), subsetCoverage(), translationalEff()
```

Examples

```
# Usually the ORFs are found in orfik, which makes names for you etc.
# Here we make an example from scratch
seqName <- "Chromosome"</pre>
ORF1 <- GRanges(seqnames = seqName,</pre>
                    ranges = IRanges(c(1007, 1096), width = 60),
                    strand = c("+", "+"))
ORF2 <- GRanges(seqnames = seqName,</pre>
                     ranges = IRanges(c(400, 100), width = 30),
                     strand = c("-", "-"))
ORFs <- GRangesList(tx1 = ORF1, tx2 = ORF2)</pre>
ORFs <- makeORFNames(ORFs) # need ORF names
tx <- extendLeaders(ORFs, 100)</pre>
# get faFile for sequences
faFile <- FaFile(system.file("extdata/references/danio_rerio", "genome_dummy.fasta",</pre>
package = "ORFik"))
kozakSequenceScore(ORFs, tx, faFile)
# For more details see vignettes.
```

kozak_IR_ranking Rank kozak initiation sequences

Description

Defined as region (-4, -1) relative to TIS

Usage

kozak_IR_ranking(cds_k, mrna, dt.ir, faFile, group.min = 10, species = "human")

Arguments

cds_k	cds ranges (GRangesList)
mrna	mrna ranges (GRangesList)
dt.ir	data.table with a column called IR, initiation rate
faFile	FaFile, BSgenome, fasta/index file path or an ORFik experiment. This file is usually used to find the transcript sequences from some GRangesList.
group.min	numeric, default 10. Minimum transcripts per initation group to be included
species	("human"), which species to use, currently supports human (Homo sapiens), zebrafish (Danio rerio) and mouse (Mus musculus). Both scientific or common name for these species will work. You can also specify a pfm for your own species. Syntax of pfm is an rectangular integer matrix, where all columns must sum to the same value, normally 100. See example for more information. Rows are in order: c("A", "C", "G", "T")

Value

a ggplot grid object

lastExonEndPerGroup Get last end per granges group

Description

Get last end per granges group

Usage

```
lastExonEndPerGroup(grl, keep.names = TRUE)
```

Arguments

grl	a GRangesList
keep.names	a boolean, keep names or not, default: (TRUE)

Value

a Rle(keep.names = T), or integer vector(F)

Examples

lastExonPerGroup Get last exon per GRangesList group

Description

grl must be sorted, call ORFik:::sortPerGroup if needed

Usage

```
lastExonPerGroup(grl)
```

Arguments

grl a GRangesList

Value

a GRangesList of the last exon per group

Examples

lastExonStartPerGroup Get last start per granges group

Description

Get last start per granges group

Usage

```
lastExonStartPerGroup(grl, keep.names = TRUE)
```

Arguments

grl	a GRangesList
keep.names	a boolean, keep names or not, default: (TRUE)

Value

a Rle(keep.names = T), or integer vector(F)

Examples

length,covRle-method length covRle

Description

Number of chromosomes

Usage

S4 method for signature 'covRle'
length(x)

Arguments

х

a covRle object

Value

an integer, number of chromosomes in covRle object

length,covRleList-method

length covRleList

Description

Number of covRle objects

Usage

```
## S4 method for signature 'covRleList'
length(x)
```

Arguments

x a covRleList object

Value

an integer, number of covRle objects

lengths,covRle-method lengths covRle

Description

Lengths of each chromosome

Usage

S4 method for signature 'covRle'
lengths(x)

Arguments

x a covRle object

Value

a named integer vector of chromosome lengths

Description

Lengths of each chromosome

Usage

```
## S4 method for signature 'covRleList'
lengths(x)
```

Arguments

x a covRle object

Value

a named integer vector of chromosome lengths

libFolder

Description

Get ORFik experiment library folder

Usage

libFolder(x, mode = "first")

Arguments

х	an ORFik experiment
mode	character, default "first". Alternatives: "unique", "all".

Value

a character path

libFolder,experiment-method

```
Get ORFik experiment library folder
```

Description

Get ORFik experiment library folder

Usage

```
## S4 method for signature 'experiment'
libFolder(x, mode = "first")
```

Arguments

х	an ORFik experiment
mode	character, default "first". Alternatives: "unique", "all".

Value

a character path

libNames

Description

Used to standardize nomeclature for experiments. Example: RFP is main naming, but a variant is ribo-seq ribo-seq will then be renamed to RFP

Usage

libNames()

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

```
Other experiment_naming: batchNames(), cellLineNames(), cellTypeNames(), conditionNames(),
fractionNames(), inhibitorNames(), mainNames(), repNames(), stageNames(), tissueNames()
```

libraryTypes Which type of library type in experiment?

Description

Which type of library type in experiment?

Usage

```
libraryTypes(df, uniqueTypes = TRUE)
```

Arguments

df	an ORFik experiment
uniqueTypes	logical, default TRUE. Only return unique lib types.

Value

library types (character vector)

See Also

```
Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(),
bamVarName(), create.experiment(), experiment-class, filepath(), organism, experiment-method,
outputLibs(), read.experiment(), save.experiment(), validateExperiments()
```

Examples

```
df <- ORFik.template.experiment()
libraryTypes(df)
libraryTypes(df, uniqueTypes = FALSE)</pre>
```

list.experiments List current experiment available

Description

Will only search .csv extension, also exclude any experiment with the word template.

Usage

```
list.experiments(
  dir = ORFik::config()["exp"],
  pattern = "*",
  libtypeExclusive = NULL,
  validate = TRUE,
  BPPARAM = bpparam()
)
```

Arguments

dir	directory for ORFik experiments: default: ORFik::config()["exp"], which by default is: "~/Bio_data/ORFik_experiments/"	
pattern	allowed patterns in experiment file name: default ("*", all experiments)	
libtypeExclusive		
	search for experiments with exclusivly this libtype, default (NULL, all)	
validate	logical, default TRUE. Abort if any library files does not exist. Do not set this to FALSE, unless you know what you are doing!	
BPPARAM	how many cores/threads to use? default: bpparam()	

Value

a data.table, 1 row per experiment with columns:

- experiment (name),
- organism
- author
- libtypes
- number of samples

Examples

```
## Make your experiments
df <- ORFik.template.experiment(TRUE)
df2 <- df[1:6,] # Only first 2 libs
## Save them
# save.experiment(df, "~/Bio_data/ORFik_experiments/exp1.csv")
# save.experiment(df2, "~/Bio_data/ORFik_experiments/exp1_subset.csv")
## List all experiment you have:</pre>
```

list.genomes

```
## Path above is default path, so no dir argument needed
#list.experiments()
#list.experiments(pattern = "subset")
## For non default directory experiments
#list.experiments(dir = "MY/CUSTOM/PATH)
```

list.genomes

List genomes created with ORFik

Description

Given the reference.folder, list all valid references. An ORFik genome is defined as a folder with a file called output.rds that is a named R vector with names gtf and genome, where the values are character paths to those files inside that folder. This makes sure that this reference was made by ORFik and not some other program.

Usage

list.genomes(reference.folder = ORFik::config()["ref"])

Arguments

reference.folder

character path, default: ORFik::config()["ref"].

Value

a data.table with 5 columns:

- character (name of folder)

- logical (does it have a gtf)

- logical (does it have a fasta genome)

- logical (does it have a STAR index)

- logical (only displayed if some are TRUE, does it have protein structure predictions of ORFs from alphafold etc, in folder called 'protein_structure_predictions')

- logical (only displayed if some are TRUE, does it have gene symbol fst file from bioMart etc, in file called 'gene_symbol_tx_table.fst')

Examples

```
## Run with default config path
#list.genomes()
## Run with custom config path
list.genomes(tempdir())
## Get the path to fasta genome of first organism in list
#readRDS(file.path(config()["ref"], list.genomes()$name, "outputs.rds")[1])["genome"]
```

loadRegion

Description

Usefull to simplify loading of standard regions, like cds' and leaders. Adds another safety in that seqlevels will be set

Usage

```
loadRegion(
   txdb,
   part = "tx",
   names.keep = NULL,
   by = "tx",
   skip.optimized = FALSE
)
```

Arguments

txdb	a TxDb file or a path to one of: (.gtf ,.gff, .gff2, .gff2, .db or .sqlite), if it is a GRangesList, it will return it self.
part	a character, one of: tx, ncRNA, mrna, leader, cds, trailer, intron, NOTE: dif- ference between tx and mrna is that tx are all transcripts, while mrna are all transcripts with a cds, respectivly ncRNA are all tx without a cds.
names.keep	a character vector of subset of names to keep. Example: loadRegions(txdb, names = "ENST1000005"), will return only that transcript. Remember if you set by to "gene", then this list must be with gene names.
by	a character, default "tx" Either "tx" or "gene". What names to output region by, the transcript name "tx" or gene names "gene". NOTE: this is not the same as cdsBy(txdb, by = "gene"), cdsBy would then only give 1 cds per Gene, loadRegion gives all isoforms, but with gene names.
skip.optimized	logical, default FALSE. If TRUE, will not search for optimized rds files to load created from ORFik::makeTxdbFromGenome(, optimize = TRUE). The optimized files are ~ 100x faster to load for human genome.

Details

Load as GRangesList if input is not already GRangesList.

Value

a GRangesList of region

Examples

loadRegions

```
loadRegion(txdb, "intron")
# Use txdb from experiment
df <- ORFik.template.experiment()
txdb <- loadTxdb(df)
loadRegion(txdb, "leaders")
# Use ORFik experiment directly
loadRegion(df, "mrna")</pre>
```

```
loadRegions
```

Get all regions of transcripts specified to environment

Description

By default loads all parts to .GlobalEnv (global environemnt) Useful to not spend time on finding the functions to load regions.

Usage

```
loadRegions(
   txdb,
   parts = c("mrna", "leaders", "cds", "trailers"),
   extension = "",
   names.keep = NULL,
   by = "tx",
   skip.optimized = FALSE,
   envir = .GlobalEnv
)
```

Arguments

txdb	a TxDb file, a path to one of: (.gtf ,.gff, .gff2, .gff2, .db or .sqlite) or an ORFik experiment
parts	the transcript parts you want, default: c("mrna", "leaders", "cds", "trailers"). See ?loadRegion for more info on this argument.
extension	What to add on the name after leader, like: B -> leadersB
names.keep	a character vector of subset of names to keep. Example: loadRegions(txdb, names = "ENST1000005"), will return only that transcript. Remember if you set by to "gene", then this list must be with gene names.
by	a character, default "tx" Either "tx" or "gene". What names to output region by, the transcript name "tx" or gene names "gene". NOTE: this is not the same as cdsBy(txdb, by = "gene"), cdsBy would then only give 1 cds per Gene, loadRegion gives all isoforms, but with gene names.
skip.optimized	logical, default FALSE. If TRUE, will not search for optimized rds files to load created from ORFik::makeTxdbFromGenome(, optimize = TRUE). The optimized files are ~ 100x faster to load for human genome.
envir	Which environment to save to, default: .GlobalEnv

Value

invisible(NULL) (regions saved in envir)

Examples

loadTranscriptType Load transcripts of given biotype

Description

Like rRNA, snoRNA etc. NOTE: Only works on gtf/gff, not .db object for now. Also note that these anotations are not perfect, some rRNA annotations only contain 5S rRNA etc. If your gtf does not contain evertyhing you need, use a resource like repeatmasker and download a gtf: https://genome.ucsc.edu/cgi-bin/hgTables

Usage

```
loadTranscriptType(object, part = "rRNA", tx = NULL)
```

Arguments

object	a TxDb, ORFik experiment or path to gtf/gff,
part	a character, default rRNA. Can also be: snoRNA, tRNA etc. As long as that biotype is defined in the gtf.
tx	a GRangesList of transcripts (Optional, default NULL, all transcript of that type), else it must be names a list to subset on.

Value

a GRangesList of transcript of that type

References

doi: 10.1002/0471250953.bi0410s25

Examples

```
gtf <- "path/to.gtf"
#loadTranscriptType(gtf, part = "rRNA")
#loadTranscriptType(gtf, part = "miRNA")</pre>
```

loadTxdb

Description

Useful to allow fast TxDb loader like .db

Usage

```
loadTxdb(txdb, chrStyle = NULL, organism = NA, chrominfo = NULL)
```

Arguments

txdb	a TxDb file, a path to one of: (.gtf ,.gff, .gff2, .gff2, .db or .sqlite) or an ORFik experiment
chrStyle	a GRanges object, TxDb, FaFile, , a seqlevelsStyle or Seqinfo. (Default: NULL) to get seqlevelsStyle from. In addition if it is a Seqinfo object, seqinfo will be updated. Example of seqlevelsStyle update: Is chromosome 1 called chr1 or 1, is mitocondrial chromosome called MT or chrM etc. Will use 1st seqlevel-style if more are present. Like: c("NCBI", "UCSC") -> pick "NCBI"
organism	character, default NA. Scientific name of organism. Only used if input is path to gff.
chrominfo	Seqinfo object, default NULL. Only used if input is path to gff.

Value

a TxDb object

Examples

longestORFs

Get longest ORF per stop site

Description

Rule: if seqname, strand and stop site is equal, take longest one. Else keep. If IRangesList or IRanges, seqnames are groups, if GRanges or GRangesList seqnames are the seqlevels (e.g. chromosomes/transcripts)

Usage

longestORFs(grl)

Arguments

grl a GRangesList/IRangesList, GRanges/IRanges of ORFs

Value

a GRangesList/IRangesList, GRanges/IRanges (same as input)

See Also

```
Other ORFHelpers: defineTrailer(), mapToGRanges(), orfID(), startCodons(), startSites(),
stopCodons(), stopSites(), txNames(), uniqueGroups(), uniqueOrder()
```

Examples

```
ORF1 = GRanges("1", IRanges(10,21), "+")
ORF2 = GRanges("1", IRanges(1,21), "+") # <- longest
grl <- GRangesList(ORF1 = ORF1, ORF2 = ORF2)
longestORFs(grl) # get only longest</pre>
```

```
mainNames
```

Get main name from variant name

Description

Used to standardize nomeclature for experiments. Example: RFP is main naming, but a variant is ribo-seq ribo-seq will then be renamed to RFP

Usage

```
mainNames(names, dt)
```

Arguments

names	a character vector of names that must exist in dt\$allNames
dt	a data.table with 2 columns (mainName, allNames)

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

```
Other experiment_naming: batchNames(), cellLineNames(), cellTypeNames(), conditionNames(),
fractionNames(), inhibitorNames(), libNames(), repNames(), stageNames(), tissueNames()
```

makeExonRanks

Description

There are two ways to make vector of exon ranking: 1. Iterate per exon in ORF, byTranscript = FALSE 2. Iterate per ORF in transcript, byTranscript = TRUE.

Usage

```
makeExonRanks(grl, byTranscript = FALSE)
```

Arguments

grl	a GRangesList
byTranscript	logical (default: FALSE), groups orfs by transcript name or ORF name, if ORfs are by transcript, check duplicates.

Details

Either by transcript or by original groupings. Must be ordered, so that same transcripts are ordered together.

Value

an integer vector of indices for exon ranks

makeORFNames

Make ORF names per orf

Description

grl must be grouped by transcript If a list of orfs are grouped by transcripts, but does not have ORF names, then create them and return the new GRangesList

Usage

```
makeORFNames(grl, groupByTx = TRUE)
```

Arguments

grl	a GRangesList
groupByTx	logical (T), should output GRangesList be grouped by transcripts (T) or by ORFs (F)?

Value

(GRangesList) with ORF names, grouped by transcripts, sorted.

Examples

makeSummarizedExperimentFromBam

Make a count matrix from a library or experiment

Description

Make a summerizedExperiment / matrix object from bam files or other library formats sepcified by lib.type argument. Works like HTSeq, to give you count tables per library.

Usage

```
makeSummarizedExperimentFromBam(
    df,
    saveName = NULL,
    longestPerGene = FALSE,
    geneOrTxNames = "tx",
    region = "mrna",
    type = "count",
    lib.type = "ofst",
    weight = "score",
    forceRemake = FALSE,
    force = TRUE,
    library.names = bamVarName(df),
    BPPARAM = BiocParallel::SerialParam()
)
```

Arguments

df	an ORFik experiment
saveName	a character (default NULL), if set save experiment to path given. Always saved as .rds., it is optional to add .rds, it will be added for you if not present. Also used to load existing file with that name.
longestPerGene	a logical (default FALSE), if FALSE all transcript isoforms per gene. Ignored if "region" is not a character of either: "mRNA","tx", "cds", "leaders" or "trailers".
geneOrTxNames	a character vector (default "tx"), should row names keep trancript names ("tx") or change to gene names ("gene")
region	a character vector (default: "mrna"), make raw count matrices of whole mrnas or one of (leaders, cds, trailers). Can also be a GRangesList, then it uses this region directly. Can then be uORFs or a subset of CDS etc.
makeSummarizedExperimentFromBam

type	default: "count" (raw counts matrix), alternative is "fpkm", "log2fpkm" or "log10fpkm"
lib.type	a character(default: "default"), load files in experiment or some precomputed variant, either "ofst", "bedo", "bedoc" or "pshifted". These are made with OR-Fik:::convertLibs() or shiftFootprintsByExperiment(). Can also be custom user made folders inside the experiments bam folder.
weight	numeric or character, a column to score overlaps by. Default "score", will check for a metacolumn called "score" in libraries. If not found, will not use weights.
forceRemake	logical, default FALSE. If TRUE, will not look for existing file count table files.
force	logical, default TRUE If TRUE, reload library files even if matching named variables are found in environment used by experiment (see envExp) A simple way to make sure correct libraries are always loaded. FALSE is faster if data is loaded correctly already.
library.names	character, default: bamVarName(df). Names to load libraries as to environment and names to display in plots.
BPPARAM	how many cores/threads to use? default: BiocParallel::SerialParam()

Details

If txdb or gtf path is added, it is a rangedSummerizedExperiment NOTE: If the file called saveName exists, it will then load file, not remake it!

There are different ways of counting hits on transcripts, ORFik does it as pure coverage (if a single read aligns to a region with 2 genes, both gets a count of 1 from that read). This is the safest way to avoid false negatives (genes with no assigned hits that actually have true hits).

Value

a SummarizedExperiment object or data.table if "type" is not "count, with rownames as transcript / gene names.

Examples

```
##Make experiment
df <- ORFik.template.experiment()
# makeSummarizedExperimentFromBam(df)
## Only cds (coding sequences):
# makeSummarizedExperimentFromBam(df, region = "cds")
## FPKM instead of raw counts on whole mrna regions
# makeSummarizedExperimentFromBam(df, type = "fpkm")
## Make count tables of pshifted libraries over uORFs
uorfs <- GRangesList(uorf1 = GRanges("chr23", 17599129:17599156, "-"))
#saveName <- file.path(dirname(df$filepath[1]), "uORFs", "countTable_uORFs")
#makeSummarizedExperimentFromBam(df, saveName, region = uorfs)
## To load the uORFs later
# countTable(df, region = "uORFs", count.folder = "uORFs")
```

makeTxdbFromGenome Make txdb from genome

Description

Make a Txdb with defined seqlevels and seqlevelsstyle from the fasta genome. This makes it more fail safe than standard Txdb creation. Example is that you can not create a coverage window outside the chromosome boundary, this is only possible if you have set the seqlengths.

Usage

```
makeTxdbFromGenome(
  gtf,
  genome = NULL,
  organism,
  optimize = FALSE,
  gene_symbols = FALSE,
  uniprot_id = FALSE,
  pseudo_5UTRS_if_needed = NULL,
  return = FALSE
)
```

Arguments

gtf	path to gtf file
genome	character, default NULL. Path to fasta genome corresponding to the gtf. If NULL, can not set seqlevels. If value is NULL or FALSE, it will be ignored.
organism	Scientific name of organism, first letter must be capital! Example: Homo sapiens. Will force first letter to capital and convert any "_" (underscore) to " " (space)
optimize	logical, default FALSE. Create a folder within the folder of the gtf, that includes optimized objects to speed up loading of annotation regions from up to 15 seconds on human genome down to 0.1 second. ORFik will then load these optimized objects instead. Currently optimizes filterTranscript() function and loadRegion() function for 5' UTRs, 3' UTRs, CDS, mRNA (all transcript with CDS) and tx (all transcripts).
gene_symbols	logical default FALSE. If TRUE, will download and store all gene symbols for all transcripts (coding and noncoding)- In a file called: "gene_symbol_tx_table.fst" in same folder as txdb. hgcn for human, mouse symbols for mouse and rat, more to be added.
uniprot_id	logical default FALSE. If TRUE, will download and store all uniprot id for all transcripts (coding and noncoding)- In a file called: "gene_symbol_tx_table.fst" in same folder as txdb.
pseudo_5UTRS_if	_needed
	integer, default NULL. If defined > 0, will add pseudo 5' UTRs if 30 a leader.
return	logical, default FALSE. If TRUE, return TXDB object, else NULL.

Value

NULL, Txdb saved to disc named paste0(gtf, ".db"). Set 'return' argument to TRUE, to get txdb back

mapToGRanges

Examples

```
gtf <- "/path/to/local/annotation.gtf"
genome <- "/path/to/local/genome.fasta"
#makeTxdbFromGenome(gtf, genome, organism = "Saccharomyces cerevisiae")
## Add pseudo UTRs if needed (< 30% of cds have a defined 5'UTR)</pre>
```

mapToGRanges

Map orfs to genomic coordinates

Description

Creates GRangesList from the results of ORFs_as_List and the GRangesList used to find the ORFs

Usage

```
mapToGRanges(grl, result, groupByTx = TRUE, grl_is_sorted = FALSE)
```

Arguments

grl	A GRangesList of the original sequences that gave the orfs in Genomic coor- dinates. If grl_is_sorted = TRUE (default), negative exon ranges per grl object must be sorted in descending orders.
result	IRangesList A list of the results of finding uorfs list syntax is: Per list group in IRangesList is per grl index. In transcript coordinates. The names are grl index as character.
groupByTx	logical (T), should output GRangesList be grouped by transcripts (T) or by ORFs (F)?
grl_is_sorted	logical, default FALSE If FALSE will sort negative transcript in descending order for you. If you loaded ranges with default methods this is already the case, so you can set to TRUE to save some time.

Details

There is no check on invalid matches, so be carefull if you use this function directly.

Value

A GRangesList of ORFs.

See Also

```
Other ORFHelpers: defineTrailer(), longestORFs(), orfID(), startCodons(), startSites(),
stopCodons(), stopSites(), txNames(), uniqueGroups(), uniqueOrder()
```

matchColors

Description

Check that colors match with the number of fractions.

Usage

```
matchColors(coverage, colors)
```

Arguments

coverage	a data.table with coverage
colors	a character vector of colors

Value

number of genes in coverage

matchNaming Match naming of GRangesList

Description

Given a GRangesList and a reference, make the naming convention and the number of metacolumns equal to reference

Usage

```
matchNaming(gr, reference)
```

Arguments

gr	a GRangesList or GRanges object
reference	a GRangesList of a reference

Value

a GRangesList

matchSeqStyle

Description

To make sure chromosome naming is correct (chr1 vs 1 vs I etc)

Usage

```
matchSeqStyle(range, chrStyle = NULL)
```

Arguments

range	a ranged object, (GRanges, GAlignment etc)
chrStyle	a GRanges object, TxDb, FaFile, , a seqlevelsStyle or Seqinfo. (Default: NULL) to get seqlevelsStyle from. In addition if it is a Seqinfo object, seqinfo will be updated. Example of seqlevelsStyle update: Is chromosome 1 called chr1 or 1, is mitocondrial chromosome called MT or chrM etc. Will use 1st seqlevel-style if more are present. Like: c("NCBI", "UCSC") -> pick "NCBI"
	· · · ·

Value

a GAlignment/GRanges object depending on input.

mergeFastq	Merge groups of	Fastq /Fasta files
		····· · · · · · · · · · · · · · · · ·

Description

Will use multithreading to speed up process. Only works for Unix OS (Linux and Mac)

Usage

```
mergeFastq(in_files, out_files, BPPARAM = bpparam())
```

Arguments

in_files	character specify the full path to the individual fastq.gz files. Seperated by space per file in group: For 2 output files from 4 input files: in_files <- c("file1.fastq file2.fastq". "file3.fastq file4.fastq")
out_files	character specify the path to the FASTQ directory For 2 output files: out_files <- c("/merged/file1&2.fastq", "/merged/file3&4.fastq")
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers

Value

invisible(NULL).

Examples

```
fastq.folder <- tempdir() # <- Your fastq files</pre>
infiles <- dir(fastq.folder, "*.fastq", full.names = TRUE)</pre>
## Not run:
# Seperate files into groups (here it is 4 output files from 12 input files)
in_files <- c(paste0(grep(infiles, pattern = paste0("ribopool-"</pre>
               seq(11, 14), collapse = "|"), value = TRUE), collapse = " "),
              paste0(grep(infiles, pattern = paste0("ribopool-"
               seq(18, 19), collapse = "|"), value = TRUE), collapse = " "),
              paste0(grep(infiles, pattern = paste0("C11-",
               seq(11, 14), collapse = "|"), value = TRUE), collapse = " "),
              paste0(grep(infiles, pattern = paste0("C11-",
               seq(18, 19), collapse = "|"), value = TRUE), collapse = ""))
out_files <- paste0(c("SSU_ribopool", "LSU_ribopool", "SSU_WT", "LSU_WT"), ".fastq.gz")</pre>
merged.fastq.folder <- file.path(fastq.folder, "merged/")</pre>
out_files <- file.path(merged.fastq.folder, out_files)</pre>
mergeFastq(in_files, out_files)
## End(Not run)
```

```
mergeLibs
```

Merge and save libraries of experiment

Description

Aggregate count of reads (from the "score" column) by making a merged library. Only allowed for .ofst files!

Usage

```
mergeLibs(
    df,
    out_dir = file.path(libFolder(df), "ofst_merged"),
    mode = "all",
    type = "ofst",
    keep_all_scores = TRUE
)
```

Arguments

df	an ORFik experiment
out_dir	Ouput directory, default file.path(dirname(df\$filepath[1]), "ofst_merged"), saved as "all.ofst" in this folder if mode is "all". Use a folder called pshifted_merged, for default Ribo-seq ofst files.
mode	character, default "all". Merge all or "rep" for collapsing replicates only, or "lib" for collapsing all per library type.
type	a character(default: "default"), load files in experiment or some precomputed variant, like "ofst" or "pshifted". These are made with ORFik:::convertLibs(), shiftFootprintsByExperiment(), etc. Can also be custom user made folders inside the experiments bam folder. It acts in a recursive manner with priority: If

222

you state "pshifted", but it does not exist, it checks "ofst". If no .ofst files, it uses "default", which always must exists.

Presets are (folder is relative to default lib folder, some types fall back to other formats if folder does not exist):

- "default": load the original files for experiment, usually bam.

- "ofst": loads ofst files from the ofst folder, relative to lib folder (falls back to default)

- "pshifted": loads ofst, wig or bigwig from pshifted folder (falls back to ofst, then default)

- "cov": Load covRle objects from cov_RLE folder (fail if not found)

- "covl": Load covRleList objects, from cov_RLE_List folder (fail if not found)

- "bed": Load bed files, from bed folder (falls back to default)
- Other formats must be loaded directly with fimport

keep_all_scores

logical, default TRUE, keep all library scores in the merged file. These score columns are named the libraries full name from bamVarName(df).

Value

NULL, files saved to disc. A data.table with a score column that now contains the sum of scores per merge setting.

Examples

```
df2 <- ORFik.template.experiment()
df2 <- df2[df2$libtype == "RFP",]
# Merge all
#mergeLibs(df2, tempdir(), mode = "all", type = "default")
# Read as GRanges with mcols
#fimport(file.path(tempdir(), "all.ofst"))
# Read as direct fst data.table
#read_fst(file.path(tempdir(), "all.ofst"))
# Collapse replicates
#mergeLibs(df2, tempdir(), mode = "rep", type = "default")
# Collapse by lib types
#mergeLibs(df2, tempdir(), mode = "lib", type = "default")</pre>
```

metadata.autnaming Guess SRA metadata columns

Description

Guess SRA metadata columns

Usage

```
metadata.autnaming(file)
```

Arguments

file a data.table of SRA metadata

Value

a data.table of SRA metadata with additional columns: LIBRARYTYPE, REPLICATE, STAGE, CONDITION, INHIBITOR

Calculate meta-coverage of reads around input GRanges/List object.

Description

metaWindow

Sums up coverage over set of GRanges objects as a meta representation.

Usage

Arguments

x	GRanges/GAlignment object of your reads. Remember to resize them before- hand to width of 1 to focus on 5' ends of footprints etc, if that is wanted.
windows	GRangesList or GRanges of your ranges
scoring	a character, default: "sum", one of (zscore, transcriptNormalized, mean, median, sum, sumLength, NULL), see ?coverageScorings for info and more alternatives.
withFrames	a logical (TRUE), return positions with the 3 frames, relative to zeroPosition. zeroPosition is frame 0.
zeroPosition	an integer DEFAULT (NULL), the point if all windows are equal size, that should be set to position 0. Like leaders and cds combination, then 0 is the TIS and -1 is last base in leader. NOTE!: if not all windows have equal width, this will be ignored. If all have equal width and zeroPosition is NULL, it is set to as.integer(width / 2).
scaleTo	an integer (100), if windows have different size, a meta window can not directly be created, since a meta window must have equal size for all windows. Rescale (bin) all windows to scaleTo. i.e $c(1,2,3) \rightarrow size 2 \rightarrow coverage$ of position $c(1, mean(2,3))$ etc.
fraction	a character/integer (NULL), the fraction i.e (27) for read length 27, or ("LSU") for large sub-unit TCP-seq.

feature	a character string, info on region. Usually either gene name, transcript part like cds, leader, or CpG motifs etc.
forceUniqueEven	
	a logical (TRUE), if TRUE; require that all windows are of same width and even. To avoid bugs. FALSE if score is NULL.
forceRescale	logical, default TRUE. If TRUE, if unique(widthPerGroup(windows)) has length > 1, it will force all windows to width of the scaleTo argument, making a binned meta coverage.
weight	(default: 'score'), if defined a character name of valid meta column in subject. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count posi- tions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)
append.zeroes	logical, default FALSE. If TRUE and drop.zero.dt is TRUE and all windows have equal length, it will add back 0 values after transformation. Sometimes needed for correct plots, if TRUE, will call abort if not all windows are equal length!

Value

A data.table with scored counts (score) of reads mapped to positions (position) specified in windows along with frame (frame) per gene (genes) per library (fraction) per transcript region (feature). Column that does not apply is not given, but position and (score/count) is always returned.

See Also

Other coverage: coverageScorings(), regionPerReadLength(), scaledWindowPositions(),
windowPerReadLength()

Examples

```
model.matrix,experiment-method
```

Get experiment design model matrix

226

Description

The function extends stats::model.matrix.

Usage

```
## S4 method for signature 'experiment'
model.matrix(object, design_formula = design(object, as.formula = TRUE))
```

Arguments

object	an ORFik experiment
design_formula	the experiment design, as formula, subset columns, to change the model.matrix. default: design(object, as.formula = TRUE)

Value

a matrix with design and level attributes

Examples

df <- ORFik.template.experiment()
model.matrix(df)</pre>

name

Get name of ORFik experiment

Description

Get name of ORFik experiment

Usage

name(x)

Arguments

x an ORFik experiment

Value

character, name of experiment

name, experiment-method

Get name of ORFik experiment

Description

Get name of ORFik experiment

Usage

S4 method for signature 'experiment'
name(x)

Arguments

x an ORFik experiment

Value

character, name of experiment

```
nrow, experiment-method
```

Internal nrow function for ORFik experiment Number of runs in experiment

Description

Internal nrow function for ORFik experiment Number of runs in experiment

Usage

```
## S4 method for signature 'experiment'
nrow(x)
```

Arguments

x an ORFik experiment

Value

number of rows in experiment (integer)

numCodons

Description

Length of object / 3. Choose either only whole codons, or with stubs. ORF stubs are not relevant, since there are no correctly defined ORFs that are 17 bases long etc.

Usage

numCodons(grl, as.integer = TRUE, keep.names = FALSE)

Arguments

grl	a GRangesList object
as.integer	a logical (TRUE), remove stub codons
keep.names	a logical (FALSE)

Value

an integer vector

numExonsPerGroup Get list of the number of exons per group

Description

Can also be used generaly to get number of GRanges object per GRangesList group

Usage

numExonsPerGroup(grl, keep.names = TRUE)

Arguments

grl	a GRangesList
keep.names	a logical, keep names or not, default: (TRUE)

Value

an integer vector of counts

Examples

ofst_merge

Description

Collapses and sums the score column of each ofst file It is required that each file is of same ofst type. That is if one file has cigar information, all must have it.

Usage

```
ofst_merge(
  file_paths,
  lib_names = sub(pattern = "\\.ofst$", replacement = "", basename(file_paths)),
  keep_all_scores = TRUE,
  keepCigar = TRUE,
  sort = TRUE
)
```

Arguments

file_paths	Full path to .ofst files wanted to merge
lib_names	the name to give the resulting score columns
keep_all_scores	
	logical, default TRUE, keep all library scores in the merged file. These score columns are named the libraries full name from bamVarName(df).
keepCigar	logical, default TRUE. If CIGAR is defined, keep column. Setting to FALSE compresses the file much more usually.
sort	logical, default TRUE. Sort the ranges. Will make the file smaller and faster to load, but some additional merging time is added.

Value

a data.table of merged result, it is merged on all columns except "score". The returned file will contain the scores of each file + the aggregate sum score.

optimizedTranscriptLengths

Load length and names of all transcripts

Description

A speedup wrapper around transcriptLengths, default load time of lengths is ~ 15 seconds, if ORFik fst optimized lengths object has been made, load that file instead: load time reduced to ~ 0.1 second.

Usage

```
optimizedTranscriptLengths(
   txdb,
   with.utr5_len = TRUE,
   with.utr3_len = TRUE,
   create.fst.version = FALSE
)
```

Arguments

txdb	a TxDb file or a path to one of: (.gtf ,.gff, .gff2, .gff2, .db or .sqlite), if it is a GRangesList, it will return it self.	
with.utr5_len	logical TRUE, include length of 5' UTRs, ignored if .fst exists	
with.utr3_len	logical TRUE, include length of 3' UTRs, ignored if .fst exists	
create.fst.version		
	<pre>logical, FALSE. If TRUE, creates a .fst version of the transcript length table (if it not already exists), reducing load time from ~ 15 seconds to ~ 0.01 second next time you run filterTranscripts with this txdb object. The file is stored in the same folder as the genome this txdb is created from, with the name: paste@(ORFik:::remove.file_ext(metadata(txdb)[3,2]), "_", gsub(" \(.* :", "", metadata(txdb)[metadata(txdb)[,1] == "Creation time",2]), "_txLengths.fst" Some error checks are done to see this is a valid location, if the txdb data source is a repository like UCSC and not a local folder, it will not be made.</pre>	

Value

a data.table of loaded lengths 8 columns, 1 row per transcript isoform.

Examples

```
dt <- optimizedTranscriptLengths(ORFik.template.experiment())
dt
dt[cds_len > 0,] # All mRNA
```

optimized_txdb_path Get path for optimization files for txdb

Description

Get path for optimization files for txdb

Usage

```
optimized_txdb_path(txdb, create.dir = FALSE, stop.error = TRUE)
```

Arguments

txdb	a loaded TxDb object
create.dir	logical FALSE, if TRUE create the optimization directory, this should only be called first time used.
stop.error	logical TRUE

230

optimizeReads

Value

a character file path, returns NULL if not valid and stop.error is FALSE.

optimizeReads Find optimized subset of valid reads

Description

Keep only the ones that overlap within the grl ranges. Also sort them in the end

Usage

optimizeReads(grl, reads)

Arguments

grl	a GRangesList or GRanges object
reads	a GRanges, GAlignment or GAlignmentPairs object

Value

the reads as GRanges, GAlignment or GAlignmentPairs

See Also

```
Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.fstwig(),
export.wiggle(), fimport(), findFa(), fread.bed(), readBam(), readBigWig(), readWig()
```

orfFrameDistributions Find shifted Ribo-seq frame distributions

Description

Per library: get coverage over CDS per frame per readlength Return as data.datable with information and best frame found. Can be used to automize re-shifting of read lengths (find read lengths where frame 0 is not the best frame over the entire cds)

Usage

```
orfFrameDistributions(
    df,
    type = "pshifted",
    weight = "score",
    orfs = loadRegion(df, part = "cds"),
    BPPARAM = BiocParallel::bpparam()
)
```

Arguments

an ORFik experiment
type of library loaded, default pshifted, warning if not pshifted might crash if too many read lengths!
which column in reads describe duplicates, default "score".
GRangesList, default loadRegion(df, part = "cds")
how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.

Value

data.table with columns: fraction (library) frame (0, 1, 2) score (coverage) length (read length) percent (coverage percentage of library) percent_length (coverage percentage of library and length) best_frame (TRUE/FALSE, is this the best frame per length)

Examples

```
df <- ORFik.template.experiment()[3,]
dt <- orfFrameDistributions(df, BPPARAM = BiocParallel::SerialParam())
## Check that frame 0 is best frame for all
all(dt[frame == 0,]$best_frame)
```

orfID

Get id's for each orf

Description

These id's can be uniqued by isoform etc, this is not supported by GenomicRanges.

Usage

orfID(grl, with.tx = FALSE)

Arguments

grl	a GRangesList
with.tx	a boolean, include transcript names, if you want unique orfs, so that they dont
	have duplicates from different isoforms, set it to FALSE.

Value

a character vector of ids, 1 per orf

See Also

```
Other ORFHelpers: defineTrailer(), longestORFs(), mapToGRanges(), startCodons(), startSites(),
stopCodons(), stopSites(), txNames(), uniqueGroups(), uniqueOrder()
```

ORFik.template.experiment

An ORFik experiment to see how it looks

Description

Toy-data created to resemble human genes: Number of genes: 6 Genome size: 1161nt x 6 chromosomes = 6966 nt Experimental design (2 replicates, Wild type vs Mutant) CAGE: 4 libraries PAS (poly-A): 4 libraries Ribo-seq: 4 libraries RNA-seq: 4 libraries

Usage

ORFik.template.experiment(as.temp = FALSE)

Arguments

as.temp

logical, default FALSE, load as ORFik experiment. If TRUE, loads as data.frame template of the experiment.

Value

an ORFik experiment

See Also

```
Other ORFik_experiment: ORFik.template.experiment.zf(), bamVarName(), create.experiment(),
experiment-class, filepath(), libraryTypes(), organism, experiment-method, outputLibs(),
read.experiment(), save.experiment(), validateExperiments()
```

Examples

```
ORFik.template.experiment()
```

ORFik.template.experiment.zf

An ORFik experiment to see how it looks

Description

Toy-data created to resemble Zebrafish genes: Number of genes: 150 Ribo-seq: 1 library

Usage

```
ORFik.template.experiment.zf(as.temp = FALSE)
```

Arguments

as.temp logical, default FALSE, load as ORFik experiment. If TRUE, loads as data.frame template of the experiment.

Value

an ORFik experiment

See Also

```
Other ORFik_experiment: ORFik.template.experiment(), bamVarName(), create.experiment(),
experiment-class, filepath(), libraryTypes(), organism, experiment-method, outputLibs(),
read.experiment(), save.experiment(), validateExperiments()
```

Examples

ORFik.template.experiment.zf()

ORFikQC

A post Alignment quality control of reads

Description

The ORFik QC uses the aligned files (usually bam files), fastp and STAR log files combined with annotation to create relevant statistics.

This report consists of several steps:

1. Convert bam file / Input files to ".ofst" format, if not already done. This format is around 400x faster to use in R than the bam format. Files are also outputted to R environment specified by envExp(df)

2. From this report you will get a summary csv table, with distribution of aligned reads and overlap counts over transcript regions like: leader, cds, trailer, lincRNAs, tRNAs, rRNAs, snoRNAs etc. It will be called STATS.csv. And can be imported with QCstats function.

3. It will also make correlation plots and meta coverage plots, so you get a good understanding of how good the quality of your NGS data production + aligner step were.

4. Count tables are produced, similar to HTseq count tables. Over mrna, leader, cds and trailer separately. This tables are stored as SummarizedExperiment, for easy loading into DEseq, conversion to normalized fpkm values, or collapsing replicates in an experiment. And can be imported with countTable function.

Everything will be outputed in the directory of your NGS data, inside the folder ./QC_STATS/, relative to data location in 'df'. You can specify new out location with out.dir if you want. To make a ORFik experiment, see ?ORFik::experiment

To see some normal mrna coverage profiles of different RNA-seq protocols: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4310221/figure/F6/

234

ORFikQC

Usage

```
ORFikQC(
    df,
    out.dir = resFolder(df),
    plot.ext = ".pdf",
    create.ofst = TRUE,
    complex.correlation.plots = TRUE,
    library.names = bamVarName(df),
    use_simplified_reads = TRUE,
    BPPARAM = bpparam()
)
```

Arguments

df	an ORFik experiment	
out.dir	character, output directory, default: resFolder(df). Will make a folder within this called "QC_STATS" with all results in this directory. Warning: If you assign not default path, you will have a hazzle to load files later. Much easier to load count tables, statistics, ++ later with default. Update resFolder of df instead if needed.	
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg". Note that in pdf format the complex correlation plots become very slow to load!	
create.ofst	logical, default TRUE. Create ".ofst" files from the input libraries, ofst is much faster to load in R, for later use. Stored in ./ofst/ folder relative to experiment main folder.	
complex.correla	ation.plots	
	logical, default TRUE. Add in addition to simple correlation plot two compu- tationally heavy dots + correlation plots. Useful for deeper analysis, but takes longer time to run, especially on low-quality gpu computers. Set to FALSE to skip these.	
library.names	character, default: bamVarName(df). Names to load libraries as to environment and names to display in plots.	
use_simplified_reads		
	logical, default TRUE. For count tables and coverage plots a speed up for GAlign- ments is to use 5' ends only. This will lose some detail for splice sites, but is usually irrelevant. Note: If reads are precollapsed GRanges, set to FALSE to avoid recollapsing.	
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.	

Value

invisible(NULL) (objects are stored to disc)

See Also

Other QC report: QCplots(), QCstats()

orfScore

Examples

```
# Load an experiment
df <- ORFik.template.experiment()
# Run QC
#QCreport(df, tempdir())
# QC on subset
#QCreport(df[9,], tempdir())
```

orfScore

Get ORFscore for a GRangesList of ORFs

Description

ORFscore tries to check whether the first frame of the 3 possible frames in an ORF has more reads than second and third frame. IMPORTANT: Only use p-shifted libraries, see (detectRibosomeShifts). Else this score makes no sense.

Usage

```
orfScore(
  grl,
  RFP,
  is.sorted = FALSE,
  weight = "score",
  overlapGrl = NULL,
  coverage = NULL,
  stop3 = TRUE
```

)

Arguments

grl	a GRangesList of 5' utrs, CDS, transcripts, etc.
RFP	ribosomal footprints, given as GAlignments or GRanges object, must be already shifted and resized to the p-site. Requires a \$size column with original read lengths.
is.sorted	logical (FALSE), is grl sorted. That is + strand groups in increasing ranges $(1,2,3)$, and - strand groups in decreasing ranges $(3,2,1)$
weight	(default: 'score'), if defined a character name of valid meta column in subject. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.
overlapGrl	an integer, (default: NULL), if defined must be countOverlaps(grl, RFP), added for speed if you already have it
coverage	a data.table from coveragePerTiling of length same as 'grl' argument. Save time if you have already computed it.
stop3	logical, default TRUE. Stop if any input is of width < 3.

236

orfScore

Details

Pseudocode: assume rff - is reads fraction in specific frame

ORFScore = log(rff1 + rff2 + rff3)

If rff2 or rff3 is bigger than rff1, negate the resulting value.

ORFScore[rff1Smaller] <- ORFScore[rff1Smaller] * -1</pre>

As result there is one value per ORF: - Positive values say that the first frame have the most reads, - zero values means it is uniform: (ORFscore between -2.5 and 2.5 can be considered close to uniform), - negative values say that the first frame does not have the most reads. NOTE non-pshifted reads: If reads are not of width 1, then a read from 1-4 on range of 1-4, will get scores frame1 = 2, frame2 = 1, frame3 = 1. What could be logical is that only the 5' end is important, so that only frame1 = 1, to get this, you first resize reads to 5' end only.

General NOTES: 1. p shifting is not exact, so some functional ORFs will get a bad ORF score. 2. If a score column is defined, it will use it as weights, set to weight = 1L if you don't have weight, and score column is something else. 3. If needed a test for significance and critical values, use chi-squared. There are 3 degrees of freedom (3 frames), so critical 0.05 (3-1 degrees of freedm = 2), value is: log2(6) = 2.58 see getWeights

Value

a data.table with 4 columns, the orfscore (ORFScores) and score of each of the 3 tiles (frame_zero_RP, frame_one_RP, frame_two_RP)

References

doi: 10.1002/embj.201488411

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(),
initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(),
rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

organism, experiment-method

Get ORFik experiment organism

Description

If not defined directly, checks the txdb / gtf organism information, if existing.

Usage

```
## S4 method for signature 'experiment'
organism(object)
```

Arguments

object an ORFik experiment

Value

character, name of organism

See Also

```
Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(),
bamVarName(), create.experiment(), experiment-class, filepath(), libraryTypes(), outputLibs(),
read.experiment(), save.experiment(), validateExperiments()
```

Examples

```
# if you have set organism in txdb of ORFik experiment:
df <- ORFik.template.experiment()
organism(df)
#' If you have not set the organism you can do:
#gtf <- "pat/to/gff_or_gff"
#txdb_path <- paste0(gtf, ".db") # This file is created in next step
#txdb <- makeTxdbFromGenome(gtf, genome, organism = "Homo sapiens",</pre>
```

```
# optimize = TRUE, return = TRUE)
```

then use this txdb in you ORFik experiment and load:

```
# create.experiment(exper = "new_experiment",
```

```
# txdb = txdb_path) ...
```

```
# organism(read.experiment("new-experiment))
```

outputLibs

Description

By default loads the original files of the experiment into the global environment, named by the rows of the experiment required to make all libraries have unique names. Uses multiple cores to load, defined by multicoreParam

Usage

```
outputLibs(
    df,
    type = "default",
    paths = filepath(df, type),
    param = NULL,
    strandMode = 0,
    naming = "minimum",
    library.names = name_decider(df, naming),
    output.mode = "envir",
    chrStyle = NULL,
    envir = envExp(df),
    verbose = TRUE,
    force = TRUE,
    BPPARAM = bpparam()
)
```

Arguments

df	an ORFik experiment
type	a character(default: "default"), load files in experiment or some precomputed variant, like "ofst" or "pshifted". These are made with ORFik:::convertLibs(), shiftFootprintsByExperiment(), etc. Can also be custom user made folders in- side the experiments bam folder. It acts in a recursive manner with priority: If you state "pshifted", but it does not exist, it checks "ofst". If no .ofst files, it uses "default", which always must exists.
	 Presets are (folder is relative to default lib folder, some types fall back to other formats if folder does not exist): - "default": load the original files for experiment, usually bam. - "ofst": loads ofst files from the ofst folder, relative to lib folder (falls back to
	default) - "pshifted": loads ofst, wig or bigwig from pshifted folder (falls back to ofst, then default)
	 "cov": Load covRle objects from cov_RLE folder (fail if not found) "covl": Load covRleList objects, from cov_RLE_List folder (fail if not found) "bed": Load bed files, from bed folder (falls back to default) Other formats must be loaded directly with fimport
paths	character vector, the filpaths to use, default filepath(df, type). Change type argument if not correct. If that is not enough, then you can also update this argument. But be careful about using this directly.

param	NULL or a ScanBamParam object. Like for scanBam, this influences what fields and which records are imported. However, note that the fields specified thru this ScanBamParam object will be loaded <i>in addition</i> to any field required for gen- erating the returned object (GAlignments, GAlignmentPairs, or GappedReads object), but only the fields requested by the user will actually be kept as meta- data columns of the object.
	By default (i.e. param=NULL or param=ScanBamParam()), no additional field is loaded. The flag used is scanBamFlag(isUnmappedQuery=FALSE) for readGAlignments, readGAlignmentsList, and readGappedReads. (i.e. only records correspond- ing to mapped reads are loaded), and scanBamFlag(isUnmappedQuery=FALSE, isPaired=TRUE, hasUnmappedMate=FALSE) for readGAlignmentPairs (i.e. only records corresponding to paired-end reads with both ends mapped are loaded).
strandMode	numeric, default 0. Only used for paired end bam files. One of (0: strand = *, 1: first read of pair is +, 2: first read of pair is -). See ?strandMode. Note: Sets default to 0 instead of 1, as readGAlignmentPairs uses 1. This is to guarantee hits, but will also make mismatches of overlapping transcripts in opposite directions.
naming	a character (default: "minimum"). Name files as minimum information needed to make all files unique. Set to "full" to get full names. Set to "fullexp", to get full name with experiment name as prefix, the last one guarantees uniqueness.
library.names	character vector, names of libraries, default: name_decider(df, naming)
output.mode	character, default "envir". Output libraries to environment. Alternative: "list", return as list. "envirlist", output to envir and return as list. If output is list for- mat, the list elements are named from: bamVarName(df.rfp) (Full or minimum naming based on 'naming' argument)
chrStyle	a GRanges object, TxDb, FaFile, , a seqlevelsStyle or Seqinfo. (Default: NULL) to get seqlevelsStyle from. In addition if it is a Seqinfo object, seqinfo will be updated. Example of seqlevelsStyle update: Is chromosome 1 called chr1 or 1, is mitocondrial chromosome called MT or chrM etc. Will use 1st seqlevel-style if more are present. Like: c("NCBI", "UCSC") -> pick "NCBI"
envir	environment to save to, default envExp(df), which defaults to .GlobalEnv, but can be set with envExp(df) <- new.env() etc.
verbose	logical, default TRUE, message about library output status.
force	logical, default TRUE If TRUE, reload library files even if matching named variables are found in environment used by experiment (see envExp) A simple way to make sure correct libraries are always loaded. FALSE is faster if data is loaded correctly already.
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.

Details

The functions checks if the total set of libraries have already been loaded: i.e. Check if all names from 'library.names' exists as S4 objects in environment of experiment.

Value

NULL (libraries set by envir assignment), unless output.mode is "list" or "envirlist": Then you get a list of the libraries.

pasteDir

See Also

```
Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(),
bamVarName(), create.experiment(), experiment-class, filepath(), libraryTypes(), organism, experiment-
read.experiment(), save.experiment(), validateExperiments()
```

Examples

```
## Load a template ORFik experiment
df <- ORFik.template.experiment()</pre>
## Default library type load, usually bam files
# outputLibs(df, type = "default")
## .ofst file load, if ofst files does not exists
## it will load default
# outputLibs(df, type = "ofst")
## .wig file load, if wiggle files does not exists
## it will load default
# outputLibs(df, type = "wig")
## Load as list
outputLibs(df, output.mode = "list")
## Load libs to new environment (called ORFik in Global)
# outputLibs(df, envir = assign(name(df), new.env(parent = .GlobalEnv)))
## Load to hidden environment given by experiment
# envExp(df) <- new.env()</pre>
# outputLibs(df)
```

pasteDir	A paste function for directories Makes sure slashes are corrected, and not doubled.
----------	---

Description

A paste function for directories Makes sure slashes are corrected, and not doubled.

Usage

```
pasteDir(...)
```

Arguments

... any amount of arguments that are possible to convert to characters

Value

the pasted string

pcaExperiment

Description

Detect outlier libraries with PCA analysis. Will output PCA plot of PCA component 1 (x-axis) vs PCA component 2 (y-axis) for each library (colored by library), shape by replicate. Will be extended to allow batch correction in the future.

Usage

```
pcaExperiment(
    df,
    output.dir = NULL,
    table = countTable(df, "cds", type = "fpkm"),
    title = "PCA analysis by CDS fpkm",
    subtitle = paste("Numer of genes/regions:", nrow(table)),
    plot.ext = ".pdf",
    return.data = FALSE,
    color.by.group = TRUE
)
```

Arguments

df	an ORFik experiment
output.dir	default NULL, else character path to directory. File saved as "PCAplot_(experiment name)(plot.ext)"
table	data.table, default countTable(df, "cds", type = "fpkm"), a data.table of counts per column (default normalized fpkm values).
title	character, default "CDS fpkm".
subtitle	<pre>character, default: paste("Numer of genes:", nrow(table))</pre>
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg". Note that in pdf format the complex correlation plots become very slow to load!
return.data	logical, default FALSE. Return data instead of plot
color.by.group	logical, default TRUE. Colors in PCA plot represent unique library groups, if FALSE. Color each sample in seperate color (harder to distinguish for > 10 samples)

Value

ggplot or invisible(NULL) if output.dir is defined or < 3 samples. Returns data.table with PCA analysis if return.data is TRUE.

Examples

```
df <- ORFik.template.experiment()
# Select only Ribo-seq and RNA-seq
pcaExperiment(df[df$libtype %in% c("RNA", "RFP"),])</pre>
```

percentage_to_ratio Convert percentage to ratio of 1

Description

50 -> 0.5 etc, if length cds > minimum.cds

Usage

percentage_to_ratio(top_tx, cds, minimum.cds = 1000)

Arguments

top_tx	numeric
cds	GRangesList object
minimum.cds	numeric, default 1000

Value

numeric, as ratio of 1

plotHelper

Helper function for coverage plots

Description

Should only be used internally

Usage

```
plotHelper(
  coverage,
  df,
  outdir,
  scores,
  returnCoverage = FALSE,
  title = "coverage metaplot",
  plot.ext = ".pdf",
  colors = c("skyblue4", "orange"),
  plotFunction = "windowCoveragePlot"
)
```

Arguments

coverage	a data.table containing at least columns (count/score, position), it is possible to have additionals: (genes, fraction, feature)
df	an ORFik experiment
outdir	directory to save to (default: NULL, no saving)
scores	scoring function (default: c("sum", "transcriptNormalized")), see ?coverageScorings for possible scores.
returnCoverage	(defualt: FALSE), return the ggplot object (TRUE) or NULL (FALSE).
title	Title to give plot
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".
colors	Which colors to use, default auto color from function experiment.colors, new color per library type. Else assign colors yourself.
plotFunction	Which plot function, default: windowCoveragePlot

Value

NULL (or ggplot object if returnCoverage is TRUE)

pmapFromTranscriptF Faster pmapFromTranscript

Description

Map range coordinates between features in the transcriptome and genome (reference) space. The length of x must be the same as length of transcripts. Only exception is if x have integer names like (1, 3, 3, 5), so that x[1] maps to 1, x[2] maps to transcript 3 etc.

Usage

```
pmapFromTranscriptF(x, transcripts, removeEmpty = FALSE)
```

Arguments

х	IRangesList/IRanges/GRanges to map to genomic coordinates
transcripts	a GRangesList to map against (the genomic coordinates)
removeEmpty	a logical, remove non hit exons, else they are set to 0. That is all exons in the reference that the transcript coordinates do not span.

Details

This version tries to fix the short commings of GenomicFeature's version. Much faster and uses less memory. Implemented as dynamic program optimized c++ code.

Value

a GRangesList of mapped reads, names from ranges are kept.

244

pmapToTranscriptF

Examples

pmapToTranscriptF Faster pmapToTranscript

Description

Map range coordinates between features in the transcriptome and genome (reference) space. The length of x must be the same as length of transcripts. Only exception is if x have integer names like (1, 3, 3, 5), so that x[1] maps to 1, x[2] maps to transcript 3 etc.

Usage

```
pmapToTranscriptF(
    x,
    transcripts,
    ignore.strand = FALSE,
    x.is.sorted = TRUE,
    tx.is.sorted = TRUE
)
```

Arguments

Х	GRangesList/GRanges/IRangesList/IRanges to map to transcriptomic coordi- nates
transcripts	a GRangesList/GRanges/IRangesList/IRanges to map against (the genomic co- ordinates). Must be of lower abstraction level than x. So if x is GRanges, tran- scripts can not be IRanges etc.
ignore.strand	When ignore.strand is TRUE, strand is ignored in overlaps operations (i.e., all strands are considered "+") and the strand in the output is '*'. When ignore.strand is FALSE (default) strand in the output is taken from the transcripts argument. When transcripts is a GRangesList, all inner list elements of a common list element must have the same strand or an error is thrown. Mapped position is computed by counting from the transcription start site (TSS) and is not affected by the value of ignore.strand.
x.is.sorted	if x is a GRangesList object, are "-" strand groups pre-sorted in decreasing order within group, default: TRUE
tx.is.sorted	if transcripts is a GRangesList object, are "-" strand groups pre-sorted in de- creasing order within group, default: TRUE

Details

This version tries to fix the shortcommings of GenomicFeature's version. Much faster and uses less memory. Implemented as dynamic program optimized c++ code.

Value

object of same class as input x, names from ranges are kept.

Examples

```
library(GenomicFeatures)
# Need 2 ranges object, the target region and whole transcript
# x is target region
x <- GRanges("chr1", IRanges(start = c(26, 29), end = c(27, 29)), "+")</pre>
names(x) <- rep("tx1_ORF1", length(x))</pre>
x <- groupGRangesBy(x)</pre>
# tx is the whole region
tx_gr <- GRanges("chr1", IRanges(c(5, 29), c(27, 30)), "+")</pre>
names(tx_gr) <- rep("tx1", length(tx_gr))</pre>
tx <- groupGRangesBy(tx_gr)</pre>
pmapToTranscriptF(x, tx)
pmapToTranscripts(x, tx)
# Reuse names for matching
x <- GRanges("chr1", IRanges(start = c(26, 29, 5), end = c(27, 29, 18)), "+")
names(x) <- c(rep("tx1_1", 2), "tx1_2")</pre>
x <- groupGRangesBy(x)</pre>
tx1_2 <- GRanges("chr1", IRanges(c(4, 28), c(26, 31)), "+")</pre>
names(tx1_2) <- rep("tx1", 2)</pre>
tx <- c(tx, groupGRangesBy(tx1_2))</pre>
a <- pmapToTranscriptF(x, tx[txNames(x)])</pre>
b <- pmapToTranscripts(x, tx[txNames(x)])</pre>
identical(a, b)
seqinfo(a)
# A note here, a & b only have 1 seqlength, even though the 2 "tx1"
# are different in size. This is an artifact of using duplicated names.
```

Also look at the asTx for a similar useful function.

prettyScoring Prettify scoring name

Description

Prettify scoring name

Usage

prettyScoring(scoring)

Arguments

scoring a character (the scoring)

Value

a new scoring name or the same if pretty

246

pseudo.transform *Transform object*

Description

Similar to normal transform like log2 or log10. But keep 0 values as 0, to avoid Inf values and negtive values are made as -scale(abs(x)), to avoid NaN values.

Usage

pseudo.transform(x, scale = log2, by.reference = FALSE)

Arguments

х	a numeric vector or data.frame/data.table of numeric columns
scale	a function, default log2, which function to transform with.
by.reference	logical, FALSE. if TRUE, update object by reference if it is data.table

Value

same object class as x, with transformed values

pSitePlot	Plot area around TIS as histogram
-----------	-----------------------------------

Description

Usefull to validate p-shifting is correct Can be used for any coverage of region around a point, like TIS, TSS, stop site etc.

Usage

```
pSitePlot(
  hitMap,
  length = unique(hitMap$fraction),
  region = "start",
  output = NULL,
  type = "canonical CDS",
  scoring = "Averaged counts",
  forHeatmap = FALSE,
  title = "auto",
  facet = FALSE,
  frameSum = FALSE
)
```

Arguments

hitMap	a data.frame/data.table, given from metaWindow (must have columns: position, (score or count) and frame)
length	an integer (29), which read length is this for?
region	a character (start), either "start or "stop"
output	character (NULL), if set, saves the plot as pdf or png to path given. If no format is given, is save as pdf.
type	character (canonical CDS), type for plot
scoring	character, default: (Averaged counts), which scoring did you use ? see ?coverageScorings for info and more alternatives.
forHeatmap	a logical (FALSE), should the plot be part of a heatmap? It will scale it differently. Removing title, x and y labels, and truncate spaces between bars.
title	character, title of plot. Default "auto", will make it: paste("Length", length, "over", region, "of", type). Else set your own (set to NULL to remove all to-gether).
facet	logical, default FALSE. If you input multiple read lengths, specified by fraction column of hitMap, it will split the plots for each read length, putting them under each other. Ignored if forHeatmap is TRUE.
frameSum	logical default FALSE. If TRUE, add an addition plot to the right, sum per frame over all positions per length.

Details

The region is represented as a histogram with different colors for the 3 frames. To make it easy to see patterns in the reads. Remember if you want to change anything like colors, just return the ggplot object, and reassign like: obj + scale_color_brewer() etc.

Value

a ggplot object of the coverage plot, NULL if output is set, then the plot will only be saved to location.

See Also

Other coveragePlot: coverageHeatMap(), savePlot(), windowCoveragePlot()

Examples

See vignette for more examples

QCfolder

Description

Get ORFik experiment QC folder path

Usage

QCfolder(x)

Arguments

x an ORFik experiment

Value

a character path

QCfolder, experiment-method

Get ORFik experiment QC folder path

Description

Get ORFik experiment QC folder path

Usage

```
## S4 method for signature 'experiment'
QCfolder(x)
```

Arguments

x an ORFik experiment

Value

a character path

QCplots

Description

Correlation plots default to mRNA covering reads. Meta plots defaults to leader, cds, trailer. Output will be stored in same folder as the libraries in df.

Correlation plots will be fpkm correlation and log2(fpkm + 1) correlation between samples.

Usage

```
QCplots(
   df,
   region = "mrna",
   stats_folder = QCfolder(df),
   plot.ext = ".pdf",
   complex.correlation.plots = TRUE,
   library.names = bamVarName(df),
   force = TRUE,
   BPPARAM
)
```

Arguments

df	an ORFik experiment	
region	a character (default: mrna), make raw count matrices of whole mrnas or one of (leaders, cds, trailers)	
stats_folder	directory to save, default: QCfolder(df)	
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg". Note that in pdf format the complex correlation plots become very slow to load!	
complex.correlation.plots		
	logical, default TRUE. Add in addition to simple correlation plot two compu- tationally heavy dots + correlation plots. Useful for deeper analysis, but takes longer time to run, especially on low-quality gpu computers. Set to FALSE to skip these.	
library.names	character vector, names of libraries, default: name_decider(df, naming)	
force	logical, default TRUE If TRUE, reload library files even if matching named variables are found in environment used by experiment (see envExp) A simple way to make sure correct libraries are always loaded. FALSE is faster if data is loaded correctly already.	
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.	

Details

Is part of QCreport

QCreport

Value

invisible(NULL) (objects stored to disc)

See Also

Other QC report: QCreport(), QCstats()

QCreport

A post Alignment quality control of reads

Description

The ORFik QC uses the aligned files (usually bam files), fastp and STAR log files combined with annotation to create relevant statistics.

This report consists of several steps:

1. Convert bam file / Input files to ".ofst" format, if not already done. This format is around 400x faster to use in R than the bam format. Files are also outputted to R environment specified by envExp(df)

2. From this report you will get a summary csv table, with distribution of aligned reads and overlap counts over transcript regions like: leader, cds, trailer, lincRNAs, tRNAs, rRNAs, snoRNAs etc. It will be called STATS.csv. And can be imported with QCstats function.

3. It will also make correlation plots and meta coverage plots, so you get a good understanding of how good the quality of your NGS data production + aligner step were.

4. Count tables are produced, similar to HTseq count tables. Over mrna, leader, cds and trailer separately. This tables are stored as SummarizedExperiment, for easy loading into DEseq, conversion to normalized fpkm values, or collapsing replicates in an experiment. And can be imported with countTable function.

Everything will be outputed in the directory of your NGS data, inside the folder ./QC_STATS/, relative to data location in 'df'. You can specify new out location with out.dir if you want. To make a ORFik experiment, see ?ORFik::experiment

To see some normal mrna coverage profiles of different RNA-seq protocols: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4310221/figure/F6/

Usage

```
QCreport(
   df,
   out.dir = resFolder(df),
   plot.ext = ".pdf",
   create.ofst = TRUE,
   complex.correlation.plots = TRUE,
   library.names = bamVarName(df),
   use_simplified_reads = TRUE,
   BPPARAM = bpparam()
)
```

Arguments

df	an ORFik experiment	
out.dir	character, output directory, default: resFolder(df). Will make a folder within this called "QC_STATS" with all results in this directory. Warning: If you assign not default path, you will have a hazzle to load files later. Much easier to load count tables, statistics, ++ later with default. Update resFolder of df instead if needed.	
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg". Note that in pdf format the complex correlation plots become very slow to load!	
create.ofst	logical, default TRUE. Create ".ofst" files from the input libraries, ofst is much faster to load in R, for later use. Stored in ./ofst/ folder relative to experiment main folder.	
complex.correlation.plots		
	logical, default TRUE. Add in addition to simple correlation plot two compu- tationally heavy dots + correlation plots. Useful for deeper analysis, but takes longer time to run, especially on low-quality gpu computers. Set to FALSE to skip these.	
library.names	character, default: bamVarName(df). Names to load libraries as to environment and names to display in plots.	
use_simplified_	reads	
	logical, default TRUE. For count tables and coverage plots a speed up for GAlignments is to use 5' ends only. This will lose some detail for splice sites, but is usually irrelevant. Note: If reads are precollapsed GRanges, set to FALSE to avoid recollapsing.	
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.	

Value

invisible(NULL) (objects are stored to disc)

See Also

Other QC report: QCplots(), QCstats()

Examples

```
# Load an experiment
df <- ORFik.template.experiment()
# Run QC
#QCreport(df, tempdir())
# QC on subset
#QCreport(df[9,], tempdir())
```
QCstats

Description

Loads the pre / post alignment statistcs made in ORFik.

Usage

```
QCstats(df, path = file.path(QCfolder(df), "STATS.csv"))
```

Arguments

df	an ORFik experiment
path	$path \ to \ QC \ statistics \ report, \ default: \ file.path(dirname(df\ filepath[1]), \ "/QC_STATS/STATS.csv")$

Details

The ORFik QC uses the aligned files (usually bam files), fastp and STAR log files combined with annotation to create relevant statistics.

Value

data.table of QC report or NULL if not exists

See Also

Other QC report: QCplots(), QCreport()

Examples

```
df <- ORFik.template.experiment()
## First make QC report
# QCreport(df)
# stats <- QCstats(df)</pre>
```

QCstats.plot Make plot of ORFik QCreport

Description

From post-alignment QC relative to annotation, make a plot for all samples. Will contain among others read lengths, reads overlapping leaders, cds, trailers, mRNA / rRNA etc.

Usage

```
QCstats.plot(stats, output.dir = NULL, plot.ext = ".pdf", as_gg_list = FALSE)
```

Arguments

stats	the experiment object or path to custom ORFik QC folder where a file called "STATS.csv" is located.
output.dir	NULL or character path, default: NULL, plot not saved to disc. If defined saves plot to that directory with the name "/STATS_plot.pdf".
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".
as_gg_list	logical, default FALSE. Return as a list of ggplot objects instead of as a grob. Gives you the ability to modify plots more directly.

Value

the plot object, a grob of ggplot objects of the the statistics data

Examples

```
df <- ORFik.template.experiment()[3,]
## First make QC report
# QCreport(df)
## Now you can get plot
# QCstats.plot(df)</pre>
```

QC_count_tables Create count table info for QC report

Description

The better the annotation / gtf used, the more results you get.

Usage

```
QC_count_tables(
    df,
    out.dir,
    type = "ofst",
    use_simplified_reads = TRUE,
    force = TRUE,
    library.names = bamVarName(df),
    BPPARAM = bpparam()
)
```

Arguments

df	an ORFik experiment
out.dir	character, output directory, default: resFolder(df). Will make a folder within this called "QC_STATS" with all results in this directory. Warning: If you assign not default path, you will have a hazzle to load files later. Much easier to load count tables, statistics, ++ later with default. Update resFolder of df instead if needed.

type	 a character(default: "default"), load files in experiment or some precomputed variant, like "ofst" or "pshifted". These are made with ORFik:::convertLibs(), shiftFootprintsByExperiment(), etc. Can also be custom user made folders inside the experiments bam folder. It acts in a recursive manner with priority: If you state "pshifted", but it does not exist, it checks "ofst". If no .ofst files, it uses "default", which always must exists. Presets are (folder is relative to default lib folder, some types fall back to other formats if folder does not exist): - "default": load the original files for experiment, usually bam. - "ofst": loads ofst files from the ofst folder, relative to lib folder (falls back to default) - "pshifted": loads ofst, wig or bigwig from pshifted folder (falls back to ofst, then default) - "cov": Load covRle objects from cov_RLE folder (fail if not found) - "covl": Load bed files, from bed folder (falls back to default)
	- Other formats must be loaded directly with import
use_simplifie	d_reads logical, default TRUE. For count tables and coverage plots a speed up for GAlign- ments is to use 5' ends only. This will lose some detail for splice sites, but is usually irrelevant. Note: If reads are precollapsed GRanges, set to FALSE to avoid recollapsing.
force	logical, default TRUE If TRUE, reload library files even if matching named variables are found in environment used by experiment (see envExp) A simple way to make sure correct libraries are always loaded. FALSE is faster if data is loaded correctly already.
library.names	character vector, names of libraries, default: name_decider(df, naming)
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.

Value

a data.table of the count info

r

strandMode covRle

Description

strandMode covRle

Usage

r(x)

Arguments

x a covRle object

rankOrder

Value

the forward RleList

r, covRle-method *strandMode covRle*

Description

strandMode covRle

Usage

S4 method for signature 'covRle'
r(x)

Arguments

x a covRle object

Value

the forward RleList

rank0rder

ORF rank in transcripts

Description

Creates an ordering of ORFs per transcript, so that ORF with the most upstream start codon is 1, second most upstream start codon is 2, etc. Must input a grl made from ORFik, txNames_2 -> 2.

Usage

rankOrder(grl)

Arguments

grl a GRangesList object with ORFs

Value

a numeric vector of integers

References

doi: 10.1074/jbc.R116.733899

read.experiment

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(),
initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(),
orfScore(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

read.experiment Read ORFik experiment

Description

Read in runs / samples from an experiment as a single R object. To read an ORFik experiment, you must of course make one first. See create.experiment The file must be csv and be a valid ORFik experiment

Usage

```
read.experiment(
   file,
   in.dir = ORFik::config()["exp"],
   validate = TRUE,
   output.env = .GlobalEnv
)
```

Arguments

file	relative path to a ORFik experiment. That is a .csv file following ORFik experi- ment style ("," as seperator). , or a template data.frame from create.experiment Can also be full path to file, then in.dir argument is ignored.
in.dir	Directory to load experiment csv file from, default: ORFik::config()["exp"], which has default "~/Bio_data/ORFik_experiments/" Set to NULL if you don't want to save it to disc. Does not apply if file argument is not a path (can also be a data.frame). Also does not apply if file argument was given as full path.
validate	logical, default TRUE. Abort if any library files does not exist. Do not set this to FALSE, unless you know what you are doing!
output.env	an environment, default .GlobalEnv. Which environment should ORFik output libraries to (if this is done), can be updated later with envExp(df) <- new.env().

readBam

Value

an ORFik experiment

See Also

```
Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(),
bamVarName(), create.experiment(), experiment-class, filepath(), libraryTypes(), organism, experiment-
outputLibs(), save.experiment(), validateExperiments()
```

Examples

```
# From file
## Not run:
# Read from file
df <- read.experiment(filepath) # <- valid ORFik .csv file
## End(Not run)
## Read from (create.experiment() template)
df <- ORFik.template.experiment()
## To save it, do:
# save.experiment(df, file = "path/to/save/experiment")
## You can then do:
# read.experiment("path/to/save/experiment")
# or (identical):
# read.experiment("experiment", in.dir = "path/to/save/")</pre>
```

readBam

Custom bam reader

Description

Read in Bam file from either single end or paired end. Safer combined version of readGAlignments and readGAlignmentPairs that takes care of some common errors.

If QNAMES of the aligned reads are from collapsed fasta files (if the names are formated from collapsing in either (ORFik, ribotoolkit or fastx)), the bam file will contain a meta column called "score" with the counts of duplicates per read. Only works for single end reads, as perfect duplication events for paired end is more rare and therefor not supported!.

Usage

```
readBam(path, chrStyle = NULL, param = NULL, strandMode = 0)
```

Arguments

path

a character / data.table with path to .bam file. There are 3 input file possibilities.

- single end : a character path (length 1)
- paired end (1 file) : Either a character path (length of 2), where path[2] is "paired-end", or a data.table with 2 columns, forward = path & reverse = "paired-end"

	• paired end (2 files) : Either a character path (length of 2), where path[2] is path to R2, or a data.table with 2 columns, forward = path to R1 & reverse = path to R2. (This one is not used often)
chrStyle	a GRanges object, TxDb, FaFile, , a seqlevelsStyle or Seqinfo. (Default: NULL) to get seqlevelsStyle from. In addition if it is a Seqinfo object, seqinfo will be updated. Example of seqlevelsStyle update: Is chromosome 1 called chr1 or 1, is mitocondrial chromosome called MT or chrM etc. Will use 1st seqlevel-style if more are present. Like: c("NCBI", "UCSC") -> pick "NCBI"
param	NULL or a ScanBamParam object. Like for scanBam, this influences what fields and which records are imported. However, note that the fields specified thru this ScanBamParam object will be loaded <i>in addition</i> to any field required for gen- erating the returned object (GAlignments, GAlignmentPairs, or GappedReads object), but only the fields requested by the user will actually be kept as meta- data columns of the object.
	By default (i.e. param=NULL or param=ScanBamParam()), no additional field is loaded. The flag used is scanBamFlag(isUnmappedQuery=FALSE) for readGAlignments, readGAlignmentsList, and readGappedReads. (i.e. only records correspond- ing to mapped reads are loaded), and scanBamFlag(isUnmappedQuery=FALSE, isPaired=TRUE, hasUnmappedMate=FALSE) for readGAlignmentPairs (i.e. only records corresponding to paired-end reads with both ends mapped are loaded).
strandMode	numeric, default 0. Only used for paired end bam files. One of (0: strand = *, 1: first read of pair is +, 2: first read of pair is -). See ?strandMode. Note: Sets default to 0 instead of 1, as readGAlignmentPairs uses 1. This is to guarantee hits, but will also make mismatches of overlapping transcripts in opposite directions.

Details

In the future will use a faster .bam loader for big .bam files in R.

Value

a GAlignments or GAlignmentPairs object of bam file

See Also

```
Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.fstwig(), export.wiggle(), fimport(), findFa(), fread.bed(), optimizeReads(), readBigWig(), readWig()
```

Examples

bam_file <- system.file("extdata/Danio_rerio_sample", "ribo-seq.bam", package = "ORFik")
readBam(bam_file, "UCSC")</pre>

readBigWig

Custom bigWig reader

Description

Given 2 bigWig files (.bw, .bigWig), first is forward second is reverse. Merge them and return as GRanges object. If they contain name reverse and forward, first and second order does not matter, it will search for forward and reverse.

Usage

readBigWig(path, chrStyle = NULL, as = "GRanges")

Arguments

path	a character path to two .bigWig files, or a data.table with 2 columns, (forward, filepath) and reverse, only 1 row.
chrStyle	a GRanges object, TxDb, FaFile, , a seqlevelsStyle or Seqinfo. (Default: NULL) to get seqlevelsStyle from. In addition if it is a Seqinfo object, seqinfo will be updated. Example of seqlevelsStyle update: Is chromosome 1 called chr1 or 1, is mitocondrial chromosome called MT or chrM etc. Will use 1st seqlevel-style if more are present. Like: c("NCBI", "UCSC") -> pick "NCBI"
as	Specifies the class of the return object. Default is GRanges, which has one range per range in the file, and a score column holding the value for each range. For NumericList, one numeric vector is returned for each range in the selection argument. For RleList, there is one Rle per sequence, and that Rle spans the entire sequence.

Value

a GRanges object of the file/s

See Also

```
Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.fstwig(),
export.wiggle(), fimport(), findFa(), fread.bed(), optimizeReads(), readBam(), readWig()
```

readLengthTable Make table of readlengths

Description

Summarizing all libraries in experiment, make a table of proportion of read lengths.

Usage

```
readLengthTable(
    df,
    output.dir = NULL,
    type = "ofst",
    force = TRUE,
    library.names = bamVarName(df),
    BPPARAM = bpparam()
)
```

readWidths

Arguments

df	an ORFik experiment
output.dir	NULL or character path, default: NULL, plot not saved to disc. If defined saves plot to that directory with the name "./readLengths.csv".
type	character, default: "ofst". Type of library: either "default", usually bam format (the one you gave to experiment), "pshifted" pshifted reads, "ofst", "bed", "bedo" optimized bed, or "wig"
force	logical, default TRUE If TRUE, reload library files even if matching named variables are found in environment used by experiment (see envExp) A simple way to make sure correct libraries are always loaded. FALSE is faster if data is loaded correctly already.
library.names	character vector, names of libraries, default: name_decider(df, naming)
BPPARAM	a core param, default: single thread: BiocParallel::SerialParam(). Set to BiocParallel::bpparam() to use multicore. Be aware, this uses a lot of extra ram (40GB+) for larger human samples!

Value

a data.table object of the the read length data with columns: c("sample", "sample_id", "read length", "counts", "counts_per_sample", "perc_of_counts_per_sample")

|--|

Description

Input any reads, e.g. ribo-seq object and get width of reads, this is to avoid confusion between width, qwidth and meta column containing original read width.

Usage

```
readWidths(reads, after.softclips = TRUE, along.reference = FALSE)
```

Arguments

reads

a GRanges, GAlignment or GAlignmentPairs object.

after.softclips

logical (TRUE), include softclips in width. Does not apply if along.reference is TRUE.

along.reference

logical (FALSE), example: The cigar "26MI2" is by default width 28, but if along.reference is TRUE, it will be 26. The length of the read along the reference. Also "1D20M" will be 21 if by along.reference is TRUE. Intronic regions (cigar: N) will be removed. So: "1M200N19M" is 20, not 220.

Details

If input is p-shifted and GRanges, the "\$size" or "\$score" colum" must exist, and the column must contain the original read widths. In ORFik "\$size" have higher priority than "\$score" for defining length. ORFik P-shifting creates a \$size column, other softwares like shoelaces creates a score column.

Remember to think about how you define length. Like the question: is a Illumina error mismatch sufficient to reduce size of read and how do you know what is biological variance and what are Illumina errors?

Value

an integer vector of widths

Examples

```
gr <- GRanges("chr1", 1)
readWidths(gr)
# GAlignment with hit (1M) and soft clipped base (1S)
ga <- GAlignments(seqnames = "1", pos = as.integer(1), cigar = "1M1S",
strand = factor("+", levels = c("+", "-", "*")))
readWidths(ga) # Without soft-clip bases</pre>
```

readWidths(ga, after.softclips = FALSE) # With soft-clip bases

readWig Custom wig reader

Description

Given 2 wig files, first is forward second is reverse. Merge them and return as GRanges object. If they contain name reverse and forward, first and second order does not matter, it will search for forward and reverse.

Usage

```
readWig(path, chrStyle = NULL)
```

Arguments

path	a character path to two .wig files, or a data.table with 2 columns, (forward, filepath) and reverse, only 1 row.
chrStyle	a GRanges object, TxDb, FaFile, , a seqlevelsStyle or Seqinfo. (Default: NULL) to get seqlevelsStyle from. In addition if it is a Seqinfo object, seqinfo will be updated. Example of seqlevelsStyle update: Is chromosome 1 called chr1 or 1, is mitocondrial chromosome called MT or chrM etc. Will use 1st seqlevel-style if more are present. Like: c("NCBI", "UCSC") -> pick "NCBI"

Value

a GRanges object of the file/s

reassignTSSbyCage

See Also

Other utils: bedToGR(), convertToOneBasedRanges(), export.bed12(), export.bigWig(), export.fstwig(), export.wiggle(), fimport(), findFa(), fread.bed(), optimizeReads(), readBam(), readBigWig()

reassignTSSbyCage Reassign all Transcript Start Sites (TSS)

Description

Given a GRangesList of 5' UTRs or transcripts, reassign the start sites using max peaks from CageSeq data. A max peak is defined as new TSS if it is within boundary of 5' leader range, specified by 'extension' in bp. A max peak must also be higher than minimum CageSeq peak cutoff specified in 'filterValue'. The new TSS will then be the positioned where the cage read (with highest read count in the interval). If removeUnused is TRUE, leaders without cage hits, will be removed, if FALSE the original TSS will be used.

Usage

```
reassignTSSbyCage(
  fiveUTRs,
  cage,
  extension = 1000,
  filterValue = 1,
  restrictUpstreamToTx = FALSE,
  removeUnused = FALSE,
  preCleanup = TRUE,
  cageMcol = FALSE
```

```
)
```

Arguments

fiveUTRs	(GRangesList) The 5' leaders or full transcript sequences	
cage	Either a filePath for the CageSeq file as .bed .bam or .wig, with possible com- pressions (".gzip", ".gz", ".bgz"), or already loaded CageSeq peak data as GRanges or GAlignment. NOTE: If it is a .bam file, it will add a score column by run- ning: convertToOneBasedRanges(cage, method = "5prime", addScoreColumn = TRUE) The score column is then number of replicates of read, if score column is something else, like read length, set the score column to NULL first.	
extension	The maximum number of basses upstream of the TSS to search for CageSeq peak.	
filterValue	The minimum number of reads on cage position, for it to be counted as possible new tss. (represented in score column in CageSeq data) If you already filtered, set it to 0.	
restrictUpstreamToTx		
	a logical (FALSE). If TRUE: restrict leaders to not extend closer than 5 bases from closest upstream leader, set this to TRUE.	
removeUnused	logical (FALSE), if False: (standard is to set them to original annotation), If TRUE: remove leaders that did not have any cage support.	
extension filterValue restrictUpstrea removeUnused	The maximum number of basses upstream of the TSS to search for CageSe peak. The minimum number of reads on cage position, for it to be counted as possibl new tss. (represented in score column in CageSeq data) If you already filtered set it to 0. mToTx a logical (FALSE). If TRUE: restrict leaders to not extend closer than 5 base from closest upstream leader, set this to TRUE. logical (FALSE), if False: (standard is to set them to original annotation), TRUE: remove leaders that did not have any cage support.	

preCleanup	logical (TRUE), if TRUE, remove all reads in region (-5:-1, 1:5) of all original tss in leaders. This is to keep original TSS if it is only +/- 5 bases from the original.
cageMcol	a logical (FALSE), if TRUE, add a meta column to the returned object with the raw CAGE counts in support for new TSS.

Details

Note: If you used CAGEr, you will get reads of a probability region, with always score of 1. Remember then to set filterValue to 0. And you should use the 5' end of the read as input, use: ORFik:::convertToOneBasedRanges(cage) NOTE on filtervalue: To get high quality TSS, set filtervalue to median count of reads overlapping per leader. This will make you discard a lot of new TSS positions though. I usually use 10 as a good standard.

TIP: do summary(countOverlaps(fiveUTRs, cage)) so you can find a good cutoff value for noise.

Value

a GRangesList of newly assigned TSS for fiveUTRs, using CageSeq data.

See Also

Other CAGE: assignTSSByCage(), reassignTxDbByCage()

Examples

```
# example 5' leader, notice exon_rank column
fiveUTRs <- GenomicRanges::GRangesList(</pre>
  GenomicRanges::GRanges(seqnames = "chr1",
                          ranges = IRanges::IRanges(1000, 2000),
                          strand = "+",
                          exon_rank = 1))
names(fiveUTRs) <- "tx1"</pre>
# make fake CAGE data from promoter of 5' leaders, notice score column
cage <- GenomicRanges::GRanges(</pre>
  seqnames = "1",
  ranges = IRanges::IRanges(500, width = 1),
 strand = "+",
  score = 10) # <- Number of tags (reads) per position</pre>
# notice also that seqnames use different naming, this is fixed by ORFik
# finally reassign TSS for fiveUTRs
reassignTSSbyCage(fiveUTRs, cage)
# See vignette for example using gtf file and real CAGE data.
```

reassignTxDbByCage Input a txdb and reassign the TSS for each transcript by CAGE

reassignTxDbByCage

Description

Given a TxDb object, reassign the start site per transcript using max peaks from CageSeq data. A max peak is defined as new TSS if it is within boundary of 5' leader range, specified by 'extension' in bp. A max peak must also be higher than minimum CageSeq peak cutoff specified in 'filter-Value'. The new TSS will then be the positioned where the cage read (with highest read count in the interval).

Usage

```
reassignTxDbByCage(
   txdb,
   cage,
   extension = 1000,
   filterValue = 1,
   restrictUpstreamToTx = FALSE,
   removeUnused = FALSE,
   preCleanup = TRUE
)
```

Arguments

txdb	a TxDb file, a path to one of: (.gtf ,.gff, .gff2, .gff2, .db or .sqlite) or an ORFik experiment	
cage	Either a filePath for the CageSeq file as .bed .bam or .wig, with possible com- pressions (".gzip", ".gz", ".bgz"), or already loaded CageSeq peak data as GRanges or GAlignment. NOTE: If it is a .bam file, it will add a score column by run- ning: convertToOneBasedRanges(cage, method = "5prime", addScoreColumn = TRUE) The score column is then number of replicates of read, if score column is something else, like read length, set the score column to NULL first.	
extension	The maximum number of basses upstream of the TSS to search for CageSeq peak.	
filterValue	The minimum number of reads on cage position, for it to be counted as possible new tss. (represented in score column in CageSeq data) If you already filtered, set it to 0.	
restrictUpstrea	mToTx	
	a logical (FALSE). If TRUE: restrict leaders to not extend closer than 5 bases from closest upstream leader, set this to TRUE.	
removeUnused	logical (FALSE), if False: (standard is to set them to original annotation), If TRUE: remove leaders that did not have any cage support.	
preCleanup	logical (TRUE), if TRUE, remove all reads in region (-5:-1, 1:5) of all original tss in leaders. This is to keep original TSS if it is only +/- 5 bases from the original.	

Details

Note: If you used CAGEr, you will get reads of a probability region, with always score of 1. Remember then to set filterValue to 0. And you should use the 5' end of the read as input, use: ORFik:::convertToOneBasedRanges(cage)

Value

a TxDb obect of reassigned transcripts

See Also

Other CAGE: assignTSSByCage(), reassignTSSbyCage()

Examples

```
## Not run:
library(GenomicFeatures)
# Get the gtf txdb file
txdbFile <- system.file("extdata", "hg19_knownGene_sample.sqlite",
package = "GenomicFeatures")
cagePath <- system.file("extdata", "cage-seq-heart.bed.bgz",
package = "ORFik")
reassignTxDbByCage(txdbFile, cagePath)
```

```
## End(Not run)
```

reduceKeepAttr Reduce GRanges / GRangesList

Description

Reduce away all GRanges elements with 0-width.

Usage

```
reduceKeepAttr(
  grl,
  keep.names = FALSE,
  drop.empty.ranges = FALSE,
  min.gapwidth = 1L,
  with.revmap = FALSE,
  with.inframe.attrib = FALSE,
  ignore.strand = FALSE,
  min.strand.decreasing = TRUE
)
```

Arguments

grl	a GRangesList or GRanges object	
keep.names	(FALSE) keep the names and meta columns of the GRangesList	
drop.empty.ran	ges	
	(FALSE) if a group is empty (width 0), delete it.	
min.gapwidth	(1L) how long gap can it be between two ranges, to merge them.	
with.revmap	(FALSE) return info on which mapped to which	
with.inframe.a	ttrib	
	(FALSE) For internal use.	
ignore.strand	(FALSE), can different strands be reduced together.	
min.strand.dec	reasing	
	(TRUE), if GRangesList, return minus strand group ranges in decreasing order	
	(1-5, 30-50) -> (30-50, 1-5)	

Details

Extends function reduce by trying to keep names and meta columns, if it is a GRangesList. It also does not lose sorting for GRangesList, since original reduce sorts all by ascending position. If keep.names == FALSE, it's just the normal GenomicRanges::reduce with sorting negative strands descending for GRangesList.

Value

A reduced GRangesList

See Also

```
Other ExtendGenomicRanges: asTX(), coveragePerTiling(), extendLeaders(), extendTrailers(),
tile1(), txSeqsFromFa(), windowPerGroup()
```

Examples

regionPerReadLength Find proportion of reads per position per read length in region

Description

This is defined as: Given some transcript region (like CDS), get coverage per position. By default only returns positions that have hits, set drop.zero.dt to FALSE to get all 0 positions.

Usage

```
regionPerReadLength(
  grl,
  reads,
  acceptedLengths = NULL,
  withFrames = TRUE,
  scoring = "transcriptNormalized",
  weight = "score",
  exclude.zero.cov.grl = TRUE,
  drop.zero.dt = TRUE,
  BPPARAM = bpparam()
)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs	
reads	a GAlignments, GRanges, or precomputed coverage as covRleList (where names of covRle objects are readlengths) of RiboSeq, RnaSeq etc. Weigths for scoring is default the 'score' column in 'reads'. Can also be random access paths to bigWig or fstwig file. Do not use random access for more than a few genes, then loading the entire files is usually better.	
acceptedLengths		
	an integer vector (NULL), the read lengths accepted. Default NULL, means all lengths accepted.	
withFrames	logical TRUE, add ORF frame (frame 0, 1, 2), starting on first position of every grl.	
scoring	a character (transcriptNormalized), which meta coverage scoring ? one of (zs- core, transcriptNormalized, mean, median, sum, sumLength, fracPos), see ?cov- erageScorings for more info. Use to decide a scoring of hits per position for metacoverage etc. Set to NULL if you do not want meta coverage, but instead want per gene per position raw counts.	
weight	(default: 'score'), if defined a character name of valid meta column in subject. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.	
exclude.zero.cov.grl		
	logical, default TRUE. Do not include ranges that does not have any coverage (0 reads on them), this makes it faster to run.	
drop.zero.dt	logical, default TRUE. If TRUE and as.data.table is TRUE, remove all 0 count positions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 count positions are used in some sense.	
BPPARAM	how many cores/threads to use? default: bpparam()	

Value

a data.table with lengths by coverage.

See Also

Other coverage: coverageScorings(), metaWindow(), scaledWindowPositions(), windowPerReadLength()

Examples

```
# Raw counts per gene per position
cds <- GRangesList(tx1 = GRanges("1", 100:129, "+"))
reads <- GRanges("1", seq(79,129, 3), "+")
reads$size <- 28 # <- Set read length of reads
regionPerReadLength(cds, reads, scoring = NULL)
## Sum up reads in each frame per read length per gene
regionPerReadLength(cds, reads, scoring = "frameSumPerLG")
```

remakeTxdbExonIds Get new exon ids after update of txdb

Description

Get new exon ids after update of txdb

Usage

```
remakeTxdbExonIds(txList)
```

Arguments

txList a list, call of as.list(txdb)

Value

a new valid ordered list of exon ids (integer)

remove.experiments Remove ORFik experiment libraries load in R

Description

Variable names defined by df, in envir defined

Usage

```
remove.experiments(df, envir = envExp(df))
```

Arguments

df	an ORFik experiment
envir	environment to save to, default envExp(df), which defaults to .GlobalEnv, but can be set with envExp(df) <- new.env() etc.

Value

NULL (objects removed from envir specified)

Examples

```
df <- ORFik.template.experiment()
# Output to .GlobalEnv with:
# outputLibs(df)
# Then remove them with:
# remove.experiments(df)</pre>
```

remove.file_ext

Description

Allows removal of compression

Usage

remove.file_ext(path, basename = FALSE)

Arguments

path	character path (allows multiple paths)
basename	relative path (TRUE) or full path (FALSE)? (default: FALSE)

Value

character path without file extension

Temoverie cacors Removes meta commus	removeMetaCols	Removes meta columns
--------------------------------------	----------------	----------------------

Description

Removes meta columns

Usage

```
removeMetaCols(grl)
```

Arguments

grl a GRangesList or GRanges object

Value

same type and structure as input without meta columns

removeORFsWithinCDS Remove ORFs that are within cds

Description

Remove ORFs that are within cds

Usage

```
removeORFsWithinCDS(grl, cds)
```

Arguments

grl	(GRangesList), the ORFs to filter
cds	(GRangesList), the coding sequences (main ORFs on transcripts), to filter against.

Value

(GRangesList) of filtered uORFs

See Also

```
Other uorfs: addCdsOnLeaderEnds(), filterUORFs(), removeORFsWithSameStartAsCDS(), removeORFsWithSameSt removeORFsWithStartInsideCDS(), uORFSearchSpace()
```

removeORFsWithSameStartAsCDS

Remove ORFs that have same start site as the CDS

Description

Remove ORFs that have same start site as the CDS

Usage

```
removeORFsWithSameStartAsCDS(grl, cds)
```

Arguments

grl	(GRangesList), the ORFs to filter
cds	(GRangesList), the coding sequences (main ORFs on transcripts), to filter against.

Value

(GRangesList) of filtered uORFs

See Also

Other uorfs: addCdsOnLeaderEnds(), filterUORFs(), removeORFsWithSameStopAsCDS(), removeORFsWithStartIn removeORFsWithinCDS(), uORFSearchSpace()

removeORFsWithSameStopAsCDS

Remove ORFs that have same stop site as the CDS

Description

Remove ORFs that have same stop site as the CDS

Usage

removeORFsWithSameStopAsCDS(grl, cds)

Arguments

grl	(GRangesList), the ORFs to filter
cds	(GRangesList), the coding sequences (main ORFs on transcripts), to filter against

Value

(GRangesList) of filtered uORFs

See Also

Other uorfs: addCdsOnLeaderEnds(), filterUORFs(), removeORFsWithSameStartAsCDS(), removeORFsWithStartI removeORFsWithinCDS(), uORFSearchSpace()

removeORFsWithStartInsideCDS

Remove ORFs that have start site within the CDS

Description

Remove ORFs that have start site within the CDS

Usage

removeORFsWithStartInsideCDS(grl, cds)

Arguments

grl	(GRangesList), the ORFs to filter
cds	(GRangesList), the coding sequences (main ORFs on transcripts), to filter against.

Value

(GRangesList) of filtered uORFs

See Also

Other uorfs: addCdsOnLeaderEnds(), filterUORFs(), removeORFsWithSameStartAsCDS(), removeORFsWithSameSt removeORFsWithinCDS(), uORFSearchSpace()

removeTxdbExons Remove exons in txList that are not in fiveUTRs

Description

Remove exons in txList that are not in fiveUTRs

Usage

```
removeTxdbExons(txList, fiveUTRs)
```

Arguments

txList	a list, call of as.list(txdb)
fiveUTRs	a GRangesList of 5' leaders

Value

a list, modified call of as.list(txdb)

removeTxdbTranscripts Remove specific transcripts in txdb List

Description

Remove all transcripts, except the ones in fiveUTRs.

Usage

```
removeTxdbTranscripts(txList, fiveUTRs)
```

Arguments

txList	a list, call of as.list(txdb)
fiveUTRs	a GRangesList of 5' leaders

Value

a txList

rename.SRA.files Rename SRA files from metadata

Description

Rename SRA files from metadata

Usage

rename.SRA.files(files, new_names)

Arguments

files	a character vector, with full path to all the files	
new_names	a character vector of new names or a data.table with metadata to use to ren (usually from SRA metadata). Priority of renaming from the metadata is aback for unique names in the Library Name column, then the same is title	
	umn if no valid names in LibraryName. If found and still duplicates, will add "_rep1", "_rep2" to make them unique. Paired end data will get a extension of	
	_p1 and _p2. If no valid names, will not rename, that is keep the SKR numbers, you then can manually rename files to something more meaningful.	

Value

a character vector of new file names

See Also

Other sra: browseSRA(), download.SRA(), download.SRA.metadata(), download.ebi(), get_bioproject_candida install.sratoolkit()

repNames

Get replicate name variants

Description

Used to standardize nomeclature for experiments. Example: 1 is main naming, but a variant is rep1 rep1 will then be renamed to 1

Usage

repNames()

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

Other experiment_naming: batchNames(), cellLineNames(), cellTypeNames(), conditionNames(), fractionNames(), inhibitorNames(), libNames(), mainNames(), stageNames(), tissueNames() resFolder

Description

Get ORFik experiment main output directory

Usage

resFolder(x)

Arguments

x an ORFik experiment

Value

a character path

resFolder,experiment-method

Get ORFik experiment main output directory

Description

Get ORFik experiment main output directory

Usage

```
## S4 method for signature 'experiment'
resFolder(x)
```

Arguments

x an ORFik experiment

Value

a character path

restrictTSSByUpstreamLeader

Restrict extension of 5' UTRs to closest upstream leader end

Description

Basicly this function restricts all startSites, to the upstream GRangesList objects end. Usually leaders, for CAGE. Example: leader1: start on 10, leader2: stop on 8, extend leader1 to 5 -> this function will resize leader1 to 9, to be outside leader2, so that CAGE reads can not wrongly overlap.

Usage

```
restrictTSSByUpstreamLeader(fiveUTRs, shiftedfiveUTRs)
```

Arguments

fiveUTRs	The 5' leader sequences as GRangesList
shiftedfiveUTRs	
	The 5' leader sequences as GRangesList shifted by CAGE

Value

GRangesList object of restricted fiveUTRs

revElementsF Reverse elements within list

Description

A faster version of S4Vectors::revElements

Usage

```
revElementsF(x)
```

Arguments

х

RleList

Value

a RleList (reversed inside list elements)

 $reverse {\tt MinusStrandPerGroup}$

Reverse minus strand

Description

Reverse minus strand per group in a GRangesList Only reverse if minus strand is in increasing order

Usage

```
reverseMinusStrandPerGroup(grl, onlyIfIncreasing = TRUE)
```

Arguments

grl a GRangesList onlyIfIncreasing logical, default (TRUE), only reverse if decreasing

Value

 $a \; {\tt GRangesList}$

riboORFs

Load Predicted translons

Description

Load Predicted translons

Usage

```
riboORFs(df, type = "table", folder = riboORFsFolder(df))
```

Arguments

df	ORFik experiment
type	default "table", alternatives: c("table", "ranges_candidates", "ranges_predictions", "predictions")
folder	base folder to check for computed results, default: riboORFsFolder(df)

Value

a data.table, GRangesList or list of logical vector depending on input

Examples

```
df <- ORFik.template.experiment()
df <- df[df$libtype == "RFP",][c(1,2),]
# riboORFs(df) # Works when you have run prediction</pre>
```

riboORFsFolder

Description

Define folder for prediction output

Usage

```
riboORFsFolder(df, parrent_dir = resFolder(df))
```

Arguments

df	ORFik experiment	
parrent_dir	Parrent directory of computed study results, default: resFolder(df)	

Value

a file path (full path)

Examples

```
df <- ORFik.template.experiment()
df <- df[df$libtype == "RFP",][c(1,2),]
riboORFsFolder(df)
riboORFsFolder(df, tempdir())</pre>
```

RiboQC.plot

Quality control for pshifted Ribo-seq data

Description

Combines several statistics from the pshifted reads into a plot:

-1 Coding frame distribution per read length

-2 Alignment statistics

- -3 Biotype of non-exonic pshifted reads
- -4 mRNA localization of pshifted reads

Usage

```
RiboQC.plot(
   df,
   output.dir = QCfolder(df),
   width = 6.6,
   height = 4.5,
   plot.ext = ".pdf",
   type = "pshifted",
   weight = "score",
   bar.position = "dodge",
```

```
as_gg_list = FALSE,
BPPARAM = BiocParallel::SerialParam(progressbar = TRUE)
)
```

Arguments

df	an ORFik experiment	
output.dir	NULL or character path, default: NULL, plot not saved to disc. If defined saves plot to that directory with the name "/STATS_plot.pdf".	
width	width of plot, default 6.6 (in inches)	
height	height of plot, default 4.5 (in inches)	
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".	
type	type of library loaded, default pshifted, warning if not pshifted might crash if too many read lengths!	
weight	which column in reads describe duplicates, default "score".	
bar.position	character, default "dodge". Should Ribo-seq frames per read length be positioned as "dodge" or "stack" (on top of each other).	
as_gg_list	logical, default FALSE. Return as a list of ggplot objects instead of as a grob. Gives you the ability to modify plots more directly.	
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.	

Value

the plot object, a grob of ggplot objects of the the data

Examples

```
df <- ORFik.template.experiment()
df <- df[9,] #lets only p-shift RFP sample at index 9
#shiftFootprintsByExperiment(df)
#RiboQC.plot(df, tempdir())</pre>
```

ribosomeReleaseScore Ribosome Release Score (RRS)

Description

Ribosome Release Score is defined as

(RPFs over ORF)/(RPFs over 3' utrs)

and additionaly normalized by lengths. If RNA is added as argument, it will normalize by RNA counts to justify location of 3' utrs. It can be understood as a ribosome stalling feature. A pseudo-count of one was added to both the ORF and downstream sums.

Usage

```
ribosomeReleaseScore(
  grl,
  RFP,
  GtfOrThreeUtrs,
  RNA = NULL,
  weight.RFP = 1L,
  weight.RNA = 1L,
  overlapGrl = NULL
)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs.
RFP	RiboSeq reads as GAlignments, GRanges or GRangesList object
GtfOrThreeUtrs	if Gtf: a TxDb object of a gtf file transcripts is called from: 'threeUTRsByTran- script(Gtf, use.names = TRUE)', if object is GRangesList, it is presumed to be the 3' utrs
RNA	RnaSeq reads as GAlignments, GRanges or GRangesList object
weight.RFP	a vector (default: 1L). Can also be character name of column in RFP. As in translationalEff(weight = "score") for: GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times.
weight.RNA	Same as weightRFP but for RNA weights. (default: 1L)
overlapGrl	an integer, (default: NULL), if defined must be countOverlaps(grl, RFP), added for speed if you already have it

Value

a named vector of numeric values of scores, NA means that no 3' utr was found for that transcript.

References

doi: 10.1016/j.cell.2013.06.009

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(), distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(), rankOrder(), ribosomeStallingScore(), startRegion(), startRegionCoverage(), stopRegion(), subsetCoverage(), translationalEff()
```

Examples

ribosomeStallingScore Ribosome Stalling Score (RSS)

Description

Is defined as

(RPFs over ORF stop sites)/(RPFs over ORFs)

and normalized by lengths A pseudo-count of one was added to both the ORF and downstream sums.

Usage

```
ribosomeStallingScore(grl, RFP, weight = 1L, overlapGrl = NULL)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs.
RFP	RiboSeq reads as GAlignments, GRanges or GRangesList object
weight	a vector (default: 1L, if 1L it is identical to countOverlaps()), if single number (!= 1), it applies for all, if more than one must be equal size of 'reads'. else it must be the string name of a defined meta column in subject "reads", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean "score" column tells that this alignment region was found 5 times.
overlapGrl	an integer, (default: NULL), if defined must be countOverlaps(grl, RFP), added for speed if you already have it

Value

a named vector of numeric values of RSS scores

References

doi: 10.1016/j.cels.2017.08.004

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(), distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(), rankOrder(), ribosomeReleaseScore(), startRegion(), startRegionCoverage(), stopRegion(), subsetCoverage(), translationalEff()
```

Examples

ribo_fft

Description

A data.table of periods and amplitudes, great to detect ribosomal read lengths. Uses 5' end of reads to detect periodicity. Works both before and after p-shifting. Plot results with ribo_fft_plot.

Usage

```
ribo_fft(footprints, cds, read_lengths = 26:34, firstN = 150)
```

Arguments

footprints	Ribosome footprints in either GAlignments or GRanges	
cds	a GRangesList of coding sequences. Length must match length of argument mrna, and all must have length $>$ arugment firstN.	
read_lengths	integer vector, default: 26:34, which read length to check for. Will exclude all read_lengths that does not exist for footprints.	
firstN	(integer) Represents how many bases of the transcripts downstream of start codons to use for initial estimation of the periodicity.	

Value

a data.table with read_length, amplitude and periods

Examples

```
## Note, this sample data is not intended to be strongly periodic.
## Real data should have a cleaner peak for x = 3 (periodicity)
# Load sample data
df <- ORFik.template.experiment()
# Load annotation
loadRegions(df, "cds", names.keep = filterTranscripts(df))
# Select a riboseq library
df <- df[df$libtype == "RFP", ]
footprints <- fimport(filepath(df[1,], "default"))
fft_dt <-ribo_fft(footprints, cds)
ribo_fft_plot(fft_dt)
```

ribo_fft_plot Get periodogram plot per read length

Description

Get periodogram plot per read length

Usage

```
ribo_fft_plot(fft_dt, period_window = c(0, 6))
```

rnaNormalize

Arguments

fft_dt	a data.table with read_length, amplitude and periods
period_window	x axis limits, default $c(0,6)$

Value

a ggplot, geom_line plot facet by read length.

Examples

```
## Note, this sample data is not intended to be strongly periodic.
## Real data should have a cleaner peak for x = 3 (periodicity)
# Load sample data
df <- ORFik.template.experiment()
# Load annotation
cds <- loadRegion(df, "cds", names.keep = filterTranscripts(df))
# Select a riboseq library
df <- df[df$libtype == "RFP", ]
footprints <- fimport(filepath(df[1,], "default"))
fft_dt <-ribo_fft(footprints, cds)
ribo_fft_plot(fft_dt)
```

rnaNormalize	Normalize a data.table of coverage by RNA seq	per position
--------------	---	--------------

Description

Normalizes per position per gene by this function: (reads at position / min(librarysize, 1) * number of genes) / fpkm of that gene's RNA-seq

Usage

```
rnaNormalize(coverage, df, dfr = NULL, tx, normalizeMode = "position")
```

Arguments

coverage	a data.table containing at least columns (count/score, position), it is possible to have additionals: (genes, fraction, feature)
df	an ORFik experiment
dfr	an ORFik experiment of RNA-seq to normalize against. Will add RNA nor- malized to plot name if this is done.
tx	a GRangesList of mrna transcripts
normalizeMode	a character (default: "position"), how to normalize library against rna library. Either on "position", normalize by number of genes, sum of reads and RNA seq, on tx "region" or "feature": same as position but RNA is split into the feature groups to normalize. Useful if you have a list of targets and background genes.

Details

Good way to compare libraries

Value

a data.table of normalized transcripts by RNA.

runIDs

Get SRR/DRR/ERR run ids from ORFik experiment

Description

Get SRR/DRR/ERR run ids from ORFik experiment

Usage

runIDs(x)

Arguments

x an ORFik experiment

Value

a character vector of runIDs, "" if not existing.

runIDs, experiment-method

Get SRR/DRR/ERR run ids from ORFik experiment

Description

Get SRR/DRR/ERR run ids from ORFik experiment

Usage

S4 method for signature 'experiment'
runIDs(x)

Arguments

x an ORFik experiment

Value

a character vector of runIDs, "" if not existing.

save.experiment Save experiment to disc

Description

Save experiment to disc

Usage

```
save.experiment(df, file)
```

Arguments

df	an ORFik experiment
file	name of file to save df as

Value

NULL (experiment save only)

See Also

```
Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(),
bamVarName(), create.experiment(), experiment-class, filepath(), libraryTypes(), organism, experiment-n
outputLibs(), read.experiment(), validateExperiments()
```

Examples

```
df <- ORFik.template.experiment()
## Save with:
#save.experiment(df, file = "path/to/save/experiment.csv")
## Identical (.csv not needed, can be added):
#save.experiment(df, file = "path/to/save/experiment")</pre>
```

savePlot

Helper function for writing plots to disc

Description

Helper function for writing plots to disc

Usage

```
savePlot(
   plot,
   output = NULL,
   width = 200,
   height = 150,
   plot.ext = ".pdf",
   dpi = 300
)
```

Arguments

plot	the ggplot to save
output	character string (NULL), if set, saves the plot as pdf or png to path given. If no format is given, is save as specified by plot.ext argument.
width	width of output in mm
height	height of output in mm
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".
dpi	(300) dpi of plot

Value

a ggplot object of the coverage plot, NULL if output is set, then the plot will only be saved to location.

See Also

Other coveragePlot: coverageHeatMap(), pSitePlot(), windowCoveragePlot()

scaledWindowPositions Scale (bin) windows to a meta window of given size

Description

For example scale a coverage table of a all human CDS to width 100

Usage

```
scaledWindowPositions(
  grl,
  reads,
  scaleTo = 100,
  scoring = "meanPos",
  weight = "score",
  is.sorted = FALSE,
  drop.zero.dt = FALSE
)
```

Arguments

grl	a GRangesList of 5' utrs, CDS, transcripts, etc.
reads	 a GAlignments, GRanges, or precomputed coverage as covRle (one for each strand) of RiboSeq, RnaSeq etc. Weigths for scoring is default the 'score' column in 'reads'. Can also be random access paths to bigWig or fstwig file. Do not use random access for more than a few genes, then loading the entire files is usually better. File streaming is still in beta, so use with care!
scaleTo	an integer (100), if windows have different size, a meta window can not directly be created, since a meta window must have equal size for all windows. Rescale all windows to scaleTo. i.e $c(1,2,3) \rightarrow size 2 \rightarrow c(1, mean(2,3))$ etc. Can also be a vector, 1 number per grl group.

scoring	a character, one of (meanPos, sumPos,) Check the coverageScoring function for more options.
weight	(default: 'score'), if defined a character name of valid meta column in subject. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.
is.sorted	logical (FALSE), is grl sorted. That is + strand groups in increasing ranges $(1,2,3)$, and - strand groups in decreasing ranges $(3,2,1)$
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count positions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)

Details

Nice for making metaplots, the score will be mean of merged positions.

Value

A data.table with scored counts (counts) of reads mapped to positions (position) specified in windows along with frame (frame).

See Also

Other coverage: coverageScorings(), metaWindow(), regionPerReadLength(), windowPerReadLength()

Examples

```
library(GenomicRanges)
windows <- GRangesList(GRanges("chr1", IRanges(1, 200), "-"))
x <- GenomicRanges::GRanges(
    seqnames = "chr1",
    ranges = IRanges::IRanges(c(1, 100, 199), c(2, 101, 200)),
    strand = "-")
scaledWindowPositions(windows, x, scaleTo = 100)</pre>
```

scoreSummarizedExperiment

Helper function for makeSummarizedExperimentFromBam

Description

If txdb or gtf path is added, it is a rangedSummerizedExperiment For FPKM values, DESeq2::fpkm(robust = FALSE) is used

Usage

```
scoreSummarizedExperiment(
  final,
  score = "transcriptNormalized",
  collapse = FALSE
)
```

Arguments

final	ranged summarized experiment object
score	default: "transcriptNormalized" (row normalized raw counts matrix), alternative is "fpkm", "log2fpkm" or "log10fpkm"
collapse	a logical/character (default FALSE), if TRUE all samples within the group SAM- PLE will be collapsed to one. If "all", all groups will be merged into 1 col- umn called merged_all. Collapse is defined as rowSum(elements_per_group) / ncol(elements_per_group)

Value

a DEseq summerizedExperiment object (transcriptNormalized) or matrix (if fpkm input)

seqinfo,covRle-method Seqinfo covRle Extracted from forward RleList

Description

Seqinfo covRle Extracted from forward RleList

Usage

```
## S4 method for signature 'covRle'
seqinfo(x)
```

Arguments

x a covRle object

Value

integer vector with names
seqinfo,covRleList-method

Seqinfo covRle Extracted from forward RleList

Description

Seqinfo covRle Extracted from forward RleList

Usage

```
## S4 method for signature 'covRleList'
seqinfo(x)
```

Arguments

x a covRle object

Value

integer vector with names

seqinfo, experiment-method

Seqinfo ORFik experiment Extracted from fasta genome index

Description

Seqinfo ORFik experiment Extracted from fasta genome index

Usage

```
## S4 method for signature 'experiment'
seqinfo(x)
```

Arguments

x an ORFik experiment

Value

integer vector with names

```
seqlevels,covRle-method
```

Seqlevels covRle Extracted from forward RleList

Description

Seqlevels covRle Extracted from forward RleList

Usage

```
## S4 method for signature 'covRle'
seqlevels(x)
```

Arguments

x a covRle object

Value

integer vector with names

Seqlevels covRleList Extracted from forward RleList

Description

Seqlevels covRleList Extracted from forward RleList

Usage

```
## S4 method for signature 'covRleList'
seqlevels(x)
```

Arguments

x a covRle object

Value

integer vector with names

seqlevels, experiment-method

Seqlevels ORFik experiment Extracted from fasta genome index

Description

Seqlevels ORFik experiment Extracted from fasta genome index

Usage

```
## S4 method for signature 'experiment'
seqlevels(x)
```

Arguments

х

an ORFik experiment

Value

integer vector with names

seqnamesPerGroup Get list of seqnames per granges group

Description

Get list of seqnames per granges group

Usage

seqnamesPerGroup(grl, keep.names = TRUE)

Arguments

grl	a GRangesList
keep.names	a boolean, keep names or not, default: (TRUE)

Value

a character vector or Rle of seqnames(if seqnames = T)

Examples

```
shiftFootprints
```

Description

Function shifts footprints (GRanges) using specified offsets for every of the specified lengths. Reads that do not conform to the specified lengths are filtered out and rejected. Reads are resized to single base in 5' end fashion, treated as p site. This function takes account for junctions and soft clips in cigars of the reads. Length of the footprint is saved in size' parameter of GRanges output. Footprints are also sorted according to their genomic position, ready to be saved as a ofst, covRle, bed or wig file.

Usage

```
shiftFootprints(footprints, shifts, sort = TRUE)
```

Arguments

footprints	GAlignments object of RiboSeq reads - footprints, can also be path to the .bam /.ofst file. If GAlignment object has a meta column called "score", this will be used as replicate numbering for that read. So be careful if you have custom files with score columns, with another meaning.
shifts	a data.frame / data.table with minimum 2 columns, fraction (selected read lengths) and offsets_start (relative position in nt). Output from detectRibosomeShifts. Run ORFik::shifts.load(df)[[1]] for an example of input.
sort	logical, default TRUE. If False will keep original order of reads, and not sort output reads in increasing genomic location per chromosome and strand.

Details

The two columns in the shift data.frame/data.table argument are:

- fraction Numeric vector of lengths of footprints you select for shifting.

- offsets_start Numeric vector of shifts for corresponding selected_lengths. eg. c(-10, -10) with selected_lengths of c(31, 32) means length of 31 will be shifted left by 10. Footprints of length 32 will be shifted right by 10.

NOTE: It will remove softclips from valid width, the CIGAR 3S30M is qwidth 33, but will remove 3S so final read width is 30 in ORFik.

Value

A GRanges object of shifted footprints, sorted and resized to 1bp of p-site, with metacolumn "size" indicating footprint size before shifting and resizing, sorted in increasing order.

References

https://bmcgenomics.biomedcentral.com/articles/10.1186/s12864-018-4912-6

See Also

```
Other pshifting: changePointAnalysis(), detectRibosomeShifts(), shiftFootprintsByExperiment(),
shiftPlots(), shifts_load(), shifts_save()
```

shiftFootprintsByExperiment

Examples

```
## Basic run
# Transcriptome annotation ->
gtf_file <- system.file("extdata/references/danio_rerio", "annotations.gtf", package = "ORFik")
# Ribo seq data ->
riboSeq_file <- system.file("extdata/Danio_rerio_sample", "ribo-seq.bam", package = "ORFik")
## Not run:
footprints <- readBam(riboSeq_file)
# detect the shifts automagically
shifts <- detectRibosomeShifts(footprints, gtf_file)
# shift the RiboSeq footprints
shiftedReads <- shiftFootprints(footprints, shifts)</pre>
```

End(Not run)

shiftFootprintsByExperiment Shift footprints of each file in experiment

Description

A function that combines the steps of periodic read length detection, p-site shift detection and pshifting into 1 function. For more details, see: detectRibosomeShifts

Saves files to a specified location as .ofst and .wig, The .ofst file will include a score column containing read width.

The .wig files, will be saved in pairs of +/- strand, and score column will be replicates of reads starting at that position, score = 5 means 5 reads.

Remember that different species might have different default Ribosome read lengths, for human, mouse etc, normally around 27:30.

Usage

```
shiftFootprintsByExperiment(
 df,
  out.dir = pasteDir(libFolder(df), "/pshifted/"),
  start = TRUE,
  stop = FALSE,
  top_tx = 10L,
 minFiveUTR = 30L,
 minCDS = 150L,
 minThreeUTR = if (stop) {
     30
 } else NULL,
  firstN = 150L,
 min_reads = 1000,
 min_reads_TIS = 50,
 accepted.lengths = 26:34,
 output_format = c("ofst", "wig"),
 BPPARAM = bpparam(),
  tx = NULL,
```

```
shift.list = NULL,
log = TRUE,
heatmap = FALSE,
must.be.periodic = TRUE,
strict.fft = TRUE,
verbose = FALSE
)
```

Arguments

df	an ORFik experiment
out.dir	output directory for files, default: pasteDir(libFolder(df), "/pshifted/"), making a /pshifted folder inside default bam file location
start	(logical) Whether to include predictions based on the start codons. Default TRUE.
stop	(logical) Whether to include predictions based on the stop codons. Default FASLE. Only use if there exists 3' UTRs for the annotation. If peridicity around stop codon is stronger than at the start codon, use stop instead of start region for p-shifting.
top_tx	(integer), default 10. Specify which % of the top TIS coverage transcripts to use for estimation of the shifts. By default we take top 10 top covered transcripts as they represent less noisy data-set. This is only applicable when there are more than 1000 transcripts.
minFiveUTR	(integer) minimum bp for 5' UTR during filtering for the transcripts. Set to NULL if no 5' UTRs exists for annotation.
minCDS	(integer) minimum bp for CDS during filtering for the transcripts
minThreeUTR	(integer) minimum bp for 3' UTR during filtering for the transcripts. Set to NULL if no 3' UTRs exists for annotation.
firstN	(integer) Represents how many bases of the transcripts downstream of start codons to use for initial estimation of the periodicity.
min_reads	default (1000), how many reads must a read-length have in total to be considered for periodicity.
<pre>min_reads_TIS</pre>	default (50), how many reads must a read-length have in the TIS region to be considered for periodicity.
accepted.length	IS
	accepted read lengths, default 26:34, usually ribo-seq is strongest between 27:32.
output_format	default c("ofst", "wig"), use export.ofst or wiggle format (wig) using export.wiggle ? Default is both.
	Options are: c("ofst", "bigWig", "wig", "bed", "bedo") For future coverage per nucleotide, we advice to do here ofst and bigWig for other genome browsers, then call convert_to_covRleList to get much faster R objects. The wig format version can be used in IGV, the score column is counts of that read with that read length, the cigar reference width is lost, ofst is much faster to save and load in R, and retain cigar reference width, but can not be used in IGV. Also for larger tracks, you can use "bigWig".
BPPARAM	how many cores/threads to use? default: bpparam()
tx	a GRangesList, if you do not have 5' UTRs in annotation, send your own ver- sion. Example: extendLeaders(tx, 30) Where 30 bases will be new "leaders". Since each original transcript was either only CDS or non-coding (filtered out).

294

shift.list	default NULL, or a list containing named data.frames / data.tables with mini- mum 2 columns, fraction (selected read lengths) and offsets_start (relative posi- tion in nt). 1 named data.frame / data.table per library. Output from detectRibosomeShifts Run ORFik::shifts.load(df) for an example of input. The names of the list must be the file.paths of the Ribo-seq libraries. Use this to edit the shifts, if you suspect some of them are wrong in an experiment.	
log	logical, default (TRUE), output a log file with parameters used and a .rds file with all shifts per library (can be loaded with shifts.load)	
heatmap	a logical or character string, default FALSE. If TRUE, will plot heatmap of raw reads before p-shifting to console, to see if shifts given make sense. You can also set a filepath to save the file there.	
must.be.periodic		
	logical TRUE, if FALSE will not filter on periodic read lengths. (The Fourier transform filter will be skipped). This is useful if you are not going to do period- icity analysis, that is: for you more coverage depth (more read lengths) is more important than only keeping the high quality periodic read lengths.	
strict.fft	logical, TRUE. Use a FFT without noise filter. This means keep only reads lengths that are "periodic for the human eye". If you want more coverage, set to FALSE, to also get read lengths that are "messy", but the noise filter detects the periodicity of 3. This should only be done when you do not need high quality periodic reads! Example would be differential translation analysis by counts over each ORF.	
verbose	logical, default FALSE. Report details of analysis/periodogram. Good if you are not sure if the analysis was correct.	

Value

NULL (Objects are saved to out.dir/pshited/"name_pshifted.ofst", wig, bedo or .bedo)

References

https://bmcgenomics.biomedcentral.com/articles/10.1186/s12864-018-4912-6

See Also

```
Other pshifting: changePointAnalysis(), detectRibosomeShifts(), shiftFootprints(), shiftPlots(),
shifts_load(), shifts_save()
```

Examples

```
df <- ORFik.template.experiment.zf()
df <- df[1,] #lets only p-shift first RFP sample
## Output files as both .ofst and .wig(can be viewed in IGV/UCSC)
shiftFootprintsByExperiment(df)
# If you only need in R, do: (then you get no .wig files)
#shiftFootprintsByExperiment(df, output_format = "ofst")
## With debug info:
#shiftFootprintsByExperiment(df, verbose = TRUE)
## Re-shift, if you think some are wrong
## Here as an example we update library 1, third read length to shift 12
shift.list <- shifts_load(df)
shift.list[[1]]$offsets_start[3] <- -12
#shiftFootprintsByExperiment(df, shift.list = shift.list)</pre>
```

For additional speedup in R for nucleotide coverage (coveragePerTiling etc)

shiftPlots

Description

Around CDS TISs, plot coverage. A good validation for you p-shifting, to see shifts are corresponding and close to the CDS TIS.

Usage

```
shiftPlots(
    df,
    output = NULL,
    title = "Ribo-seq",
    scoring = "transcriptNormalized",
    pShifted = TRUE,
    upstream = if (pShifted) 5 else 20,
    downstream = if (pShifted) 20 else 5,
    type = "bar",
    addFracPlot = TRUE,
    plot.ext = ".pdf",
    BPPARAM = bpparam()
)
```

Arguments

df	an ORFik experiment
output	name to save file, full path. (Default NULL) No saving. Sett to "auto" to save to QC_STATS folder of experiment named: "pshifts_barplots.png" or "pshifts_heatmaps.png" depending on type argument. Folder must exist!
title	Title for top of plot, default "Ribo-seq". A more informative name could be "Ribo-seq zebrafish Chew et al. 2013"
scoring	which scoring scheme to use for heatmap, default "transcriptNormalized". Some alternatives: "sum", "zscore".
pShifted	a logical (TRUE), are Ribo-seq reads p-shifted to size 1 width reads? If upstream and downstream is set, this argument is irrelevant. So set to FALSE if this is not p-shifted Ribo-seq.
upstream	an integer (5), relative region to get upstream from. Default: ifelse(!is.null(tx), ifelse(pShifted, 5, 20), min(ifelse(pShifted, 5, 20), 0))
downstream	an integer (20), relative region to get downstream from. Default: ifelse(pShifted, 20, 5)
type	character, default "bar". Plot as faceted bars, gives more detailed information of read lengths, but harder to see patterns over multiple read lengths. Alternative: "heatmap", better overview of patterns over multiple read lengths.
addFracPlot	logical, default TRUE, add positional sum plot on top per heatmap.
plot.ext	default ".pdf". Alternative ".png". Only added if output is "auto".
BPPARAM	how many cores/threads to use? default: bpparam()

shifts.load

Value

a ggplot2 grob object

See Also

```
Other pshifting: changePointAnalysis(), detectRibosomeShifts(), shiftFootprints(), shiftFootprintsByExp
shifts_load(), shifts_save()
```

Examples

```
df <- ORFik.template.experiment.zf()
df <- df[df$libtype == "RFP",][1,] #lets only p-shift first RFP sample
#shiftFootprintsByExperiment(df, output_format = "bedo)
#grob <- shiftPlots(df, title = "Ribo-seq Human ORFik et al. 2020")
#plot(grob) #Only plot in RStudio for small amount of files!</pre>
```

shifts.load

Load the shifts from experiment

Description

When you p-shift using the function shiftFootprintsByExperiment, you will get a list of shifts per library. To automatically load them, you can use this function. Defaults to loading pshifts, if you made a-sites or e-sites, change the path argument to ashifted/eshifted folder instead.

Usage

```
shifts.load(
    df,
    path = file.path(libFolder(df), "pshifted", "shifting_table.rds")
)
```

Arguments

df	an ORFik experiment
path	path, default file.path(libFolder(df), "pshifted", "shifting_table.rds"). Path to
	. Tus me containing the sinits as a list, one list element per sinited bain me.

Value

a list of the shifts, one list element per shifted bam file.

See Also

```
Other pshifting: changePointAnalysis(), detectRibosomeShifts(), shiftFootprints(), shiftFootprintsByExp
shiftPlots(), shifts_save()
```

Examples

```
df <- ORFik.template.experiment()
# subset on Ribo-seq
df <- df[df$libtype == "RFP",]
#shiftFootprintsByExperiment(df)
#shifts_load(df)</pre>
```

shifts_load

Load the shifts from experiment

Description

When you p-shift using the function shiftFootprintsByExperiment, you will get a list of shifts per library. To automatically load them, you can use this function. Defaults to loading pshifts, if you made a-sites or e-sites, change the path argument to ashifted/eshifted folder instead.

Usage

```
shifts_load(
    df,
    path = file.path(libFolder(df), "pshifted", "shifting_table.rds")
)
```

Arguments

df	an ORFik experiment
path	path, default file.path(libFolder(df), "pshifted", "shifting_table.rds"). Path to .rds file containing the shifts as a list, one list element per shifted bam file.

Value

a list of the shifts, one list element per shifted bam file.

See Also

```
Other pshifting: changePointAnalysis(), detectRibosomeShifts(), shiftFootprints(), shiftFootprintsByExp
shiftPlots(), shifts_save()
```

Examples

```
df <- ORFik.template.experiment()
# subset on Ribo-seq
df <- df[df$libtype == "RFP",]
#shiftFootprintsByExperiment(df)
#shifts_load(df)</pre>
```

298

shifts_save

Description

Should be stored in pshifted folder relative to default files

Usage

shifts_save(shifts, folder)

Arguments

shifts	a list of data.table/data.frame objects. Must be named with the full path to ofst/bam files that defines the shifts.
folder	directory to save file, Usually: file.path(libFolder(df), "pshifted"), where df is the ORFik experiment / or your path of default file types. It will be named file.path(folder, "shifting_table.rds"). For ORFik to work optimally, the folder should be the /pshifted/ folder relative to default files.

Value

invisible(NULL), file saved to disc as "shifting_table.rds".

See Also

```
Other pshifting: changePointAnalysis(), detectRibosomeShifts(), shiftFootprints(), shiftFootprintsByExp
shiftPlots(), shifts_load()
```

Examples

```
df <- ORFik.template.experiment.zf()
shifts <- shifts_load(df)
original_shifts <- file.path(libFolder(df), "pshifted", "shifting_table.rds")
# Move to temp
new_shifts_path <- file.path(tempdir(), "shifting_table.rds")
new_shifts <- c(shifts, shifts)
names(new_shifts)[2] <- file.path(tempdir(), "RiboSeqTemp.ofst")
saveRDS(new_shifts, new_shifts_path)
new_shifts[[1]][1,2] <- -10
# Now update the new shifts, here we input only first
shifts_save(new_shifts[1], tempdir())
readRDS(new_shifts_path) # You still get 2 outputs</pre>
```

show, covRle-method covRle show definition

Description

Show a simplified version of the covRle

Usage

S4 method for signature 'covRle'
show(object)

Arguments

object acovRle

Value

print state of covRle

show, covRleList-method

covRleList show definition

Description

Show a simplified version of the covRleList.

Usage

```
## S4 method for signature 'covRleList'
show(object)
```

Arguments

object acovRleList

Value

print state of covRleList

show, experiment-method

experiment show definition

Description

Show a simplified version of the experiment. The show function simplifies the view so that any column of data (like replicate or stage) is not shown, if all values are identical in that column. Filepaths are also never shown.

Usage

```
## S4 method for signature 'experiment'
show(object)
```

Arguments

object an ORFik experiment

Value

print state of experiment

simpleLibs

Converted format of NGS libraries

Description

Export as either .ofst, .wig, .bigWig,.bedo (legacy format) or .bedoc (legacy format) files: Export files as .ofst for fastest load speed into R. Export files as .wig / bigWig for use in IGV or other genome browsers. The input files are checked if they exist from: envExp(df).

Usage

```
simpleLibs(
    df,
    out.dir = libFolder(df),
    addScoreColumn = TRUE,
    addSizeColumn = TRUE,
    must.overlap = NULL,
    method = "None",
    type = "ofst",
    input.type = "ofst",
    reassign.when.saving = FALSE,
    envir = envExp(df),
    force = TRUE,
    library.names = bamVarName(df),
```

```
libs = outputLibs(df, type = input.type, chrStyle = must.overlap, library.names =
    library.names, output.mode = "list", force = force, BPPARAM = BPPARAM),
BPPARAM = bpparam()
```

Arguments

)

df	an ORFik experiment	
out.dir	optional output directory, default: libFolder(df), if it is NULL, it will just reas- sign R objects to simplified libraries. Will then create a final folder specfied as: paste0(out.dir, "/", type, "/"). Here the files will be saved in format given by the type argument.	
addScoreColumn	logical, default TRUE, if FALSE will not add replicate numbers as score col- umn, see ORFik::convertToOneBasedRanges.	
addSizeColumn	logical, default TRUE, if FALSE will not add size (width) as size column, see ORFik::convertToOneBasedRanges. Does not apply for (GAlignment version of.ofst) or .bedoc. Since they contain the original cigar.	
must.overlap	default (NULL), else a GRanges / GRangesList object, so only reads that over- lap (must.overlap) are kept. This is useful when you only need the reads over transcript annotation or subset etc.	
method	character, default "None", the method to reduce ranges, for more info see convertToOneBasedRanges	
type	character, output format, default "ofst". Alternatives: "ofst", "bigWig", "wig", "bedo" or "bedoc". Which format you want. Will make a folder within out.dir with this name containing the files.	
input.type	character, input type "ofst". Remember this function uses the loaded libraries if existing, so this argument is usually ignored. Only used if files do not already exist.	
reassign.when.saving		
	logical, default FALSE. If TRUE, will reassign library to converted form after saving. Ignored when out.dir = NULL.	
envir	environment to save to, default envExp(df), which defaults to .GlobalEnv, but can be set with envExp(df) <- new.env() etc.	
force	logical, default TRUE If TRUE, reload library files even if matching named variables are found in environment used by experiment (see envExp) A simple way to make sure correct libraries are always loaded. FALSE is faster if data is loaded correctly already.	
library.names	character vector, names of libraries, default: name_decider(df, naming)	
libs	list, output of outputLibs as list of GRanges/GAlignments/GAlignmentPairs ob- jects. Set input.type and force arguments to define parameters.	
BPPARAM	how many cores/threads to use? default: bpparam(). To see number of threads used, do bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.	

Details

We advice you to not use this directly, as other function are more safe for library type conversions. See family description below. This is mostly used internally in ORFik. It is only adviced to use if large bam files are already loaded in R and conversions are wanted from those.

sortPerGroup

See export.ofst, export.wiggle, export.bedo and export.bedoc for information on file formats.

If libraries of the experiment are already loaded into environment (default: .globalEnv) is will export using those files as templates. If they are not in environment the .ofst files from the bam files are loaded (unless you are converting to .ofst then the .bam files are loaded).

Value

invisible NULL (saves files to disc or R .GlobalEnv)

See Also

```
Other lib_converters: convert_bam_to_ofst(), convert_to_bigWig(), convert_to_covRle(),
convert_to_covRleList()
```

Examples

```
df <- ORFik.template.experiment()
#convertLibs(df, out.dir = NULL)
# Keep only 5' ends of reads
#convertLibs(df, out.dir = NULL, method = "5prime")</pre>
```

sortPerGroup

Sort a GRangesList

Description

A faster, more versatile reimplementation of sort.GenomicRanges for GRangesList, needed since the original works poorly for more than 10k groups. This function sorts each group, where "+" strands are increasing by starts and "-" strands are decreasing by ends.

Usage

```
sortPerGroup(grl, ignore.strand = FALSE, quick.rev = FALSE)
```

Arguments

grl	a GRangesList
ignore.strand	a boolean, (default FALSE): should minus strands be sorted from highest to lowest ends. If TRUE: from lowest to highest ends.
quick.rev	default: FALSE, if TRUE, given that you know all ranges are sorted from min to max for both strands, it will only reverse coordinates for minus strand groups, and only if they are in increasing order. Much quicker

Details

Note: will not work if groups have equal names.

Value

an equally named GRangesList, where each group is sorted within group.

Examples

splitIn3Tx

Create binned coverage of transcripts, split into the 3 parts.

Description

The 3 parts of transcripts are the leaders, the cds' and trailers. Per transcript part, bin them all to windowSize (default 100), and make a data.table, rows are positions, useful for plotting with ORFik and ggplot2.

Usage

```
splitIn3Tx(
  leaders,
  cds,
  trailers,
  reads,
  windowSize = 100,
  fraction = "1",
  weight = "score",
  is.sorted = FALSE,
  drop.zero.dt = FALSE,
  BPPARAM = BiocParallel::SerialParam()
)
```

Arguments

leaders	a GRangesList of leaders (5' UTRs)
cds	a GRangesList of coding sequences
trailers	a GRangesList of trailers (3' UTRs)
reads	GRanges or GAlignment of reads
windowSize	an integer (100), size of windows (columns). All genes with region smaller than this size are filter out for metacoverage.
fraction	a character (1), info on reads (which read length, or which type (RNA seq)) (row names)
weight	(default: 'score'), if defined a character name of valid meta column in subject. $GRanges("chr1", 1, "+", score = 5)$, would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.

304

stageNames

is.sorted	logical (FALSE), is grl sorted. That is + strand groups in increasing ranges $(1,2,3)$, and - strand groups in decreasing ranges $(3,2,1)$
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count posi- tions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)
BPPARAM	how many cores/threads to use? default: bpparam()

Value

a data.table with columns position, score

stageNames

Get stage name variants

Description

Used to standardize nomeclature for experiments.

Example: Find timepoints 2 hours, 4 hours etc. Example: If using zebrafish stages as TRUE, 64Cell stage is same as 2 hours post fertilization, so all 2hpf will be converted to 64Cell etc.

Usage

stageNames(zebrafish.stages = FALSE)

Arguments

zebrafish.stages

logical, FALSE. If true, convert time points to stages.

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

References

https://www.mbl.edu/zebrafish/files/2013/03/Kimmel_stagingseries1.pdf

See Also

Other experiment_naming: batchNames(), cellLineNames(), cellTypeNames(), conditionNames(), fractionNames(), inhibitorNames(), libNames(), mainNames(), repNames(), tissueNames() STAR.align.folder *Align all libraries in folder with STAR*

Description

Does either all files as paired end or single end, so if you have mix, split them in two different folders.

If STAR halts at loading genome, it means the STAR index was aborted early, then you need to run: STAR.remove.crashed.genome(), with the genome that crashed, and rerun.

Usage

```
STAR.align.folder(
  input.dir,
 output.dir,
  index.dir,
  star.path = STAR.install(),
  fastp = install.fastp(),
 paired.end = FALSE,
 steps = "tr-ge",
  adapter.sequence = "auto",
  quality.filtering = FALSE,
 min.length = 20,
 mismatches = 3,
 trim.front = 0,
 max.multimap = 10,
 alignment.type = "Local",
 allow.introns = TRUE,
 max.cpus = min(90, BiocParallel::bpparam()$workers),
 wait = TRUE,
 include.subfolders = "n",
 resume = NULL,
 multiQC = TRUE,
 keep.contaminants = FALSE,
 keep.unaligned.genome = FALSE,
 script.folder = system.file("STAR_Aligner", "RNA_Align_pipeline_folder.sh", package =
    "ORFik"),
 script.single = system.file("STAR_Aligner", "RNA_Align_pipeline.sh", package = "ORFik")
)
```

Arguments

input.dir	path to fast files to align, the valid input files will be search for from formats: (".fasta", ".fastq", ".fq", or ".fa") with or without compression of .gz. Also either paired end or single end reads. Pairs will automatically be detected from similarity of naming, separated by something as .1 and .2 in the end. If files are renamed, where pairs are not similarily named, this process will fail to find correct pairs!
output.dir	directory to save indices, default: paste0(dirname(arguments[1]), "/STAR_index/") where arguments is the arguments input for this function.

index.dir	path to STAR index folder. Path returned from ORFik function STAR.index, when you created the index folders.
star.path	path to STAR, default: STAR.install(), if you don't have STAR installed at de- fault location, it will install it there, set path to a runnable star if you already have it.
fastp	path to fastp trimmer, default: install.fastp(), if you have it somewhere else al- ready installed, give the path. Only works for unix (linux or Mac OS), if not on unix, use your favorite trimmer and give the output files from that trimmer as input.dir here.
paired.end	a logical: default FALSE, alternative TRUE. If TRUE, will auto detect pairs by names. Can not be a combination of both TRUE and FALSE! If running in folder mode: The folder must then contain an even number of files and they must be named with the same prefix and sufix of either _1 and _2, 1 and 2, etc. If SRR numbers are used, it will start on lowest and match with second lowest etc.
steps	a character, default: "tr-ge", trimming then genome alignment steps of depletion and alignment wanted: The posible candidates you can use are:
	 tr : trim reads co : contamination merged depletion ph : phix depletion rR : rrna depletion nc : ncrna depletion tR : trna depletion (Mature tRNA, so no intron checks done) ge : genome alignment all: run steps: "tr-co-ge" or "tr-ph-rR-nc-tR-ge", depending on if you have merged contaminants or not If not "all", a subset of these ("tr-co-ph-rR-nc-tR-ge") If co (merged contaminants) is used, non of the specific contaminants can be specified, since they should be a subset of co. The step where you align to the genome is usually always included, unless you are doing pure contaminant analysis or only trimming. For Ribo-seq and TCP(RCP-seq) you should do rR (ribosomal RNA depletion), so when you made the STAR index you need the rRNA step, either use rRNA from .gtf or manual download. (usually just download a Silva rRNA database for SSU&LSU at: https://www ath-silva.de/) for your species
adapter.sequenc	ce
	character, default: "auto". Auto detect adapter using fastp adapter auto detec- tion, checking first 1.5M reads. (Auto detection of adapter will not work 100% of the time (if the library is of low quality), then you must rerun this function with specified adapter from fastp adapter analysis. , using FASTQC or other

adapter detection tools, else alignment will most likely fail!). If already trimmed or trimming not wanted: adapter.sequence = "disable" .You can manually assign adapter like: "ATCTCGTATGCCGTCTTCTGCTTG" or "AAAAAAAAAAAAA.". You can also specify one of the three presets:

- illumina (TrueSeq ~75/100 bp sequencing): AGATCGGAAGAGC
- small_RNA (standard for ~50 bp sequencing): TGGAATTCTCGG

• nextera: CTGTCTCTTATA

Paired end auto detection uses overlap sequence of pairs, to use the slower more secure paired end adapter detection, specify as: "autoPE".

quality.filtering

logical, default FALSE. Not needed for modern library prep of RNA-seq, Riboseq etc (usually < ~ 0.5 If you are aligning bad quality data, set this to TRUE. These filters will then be applied (default of fastp), filter if:

- Number of N bases in read: > 5
- Read quality: > 40% of bases in the read are <Q15

min.length 20, minimum length of aligned read without mismatches to pass filter. Anything under 20 is dangerous, as chance of random hits will become high!

- mismatches 3, max non matched bases. Excludes soft-clipping, this only filters reads that have defined mismatches in STAR. Only applies for genome alignment step.
- trim.front 0, default trim 0 bases 5'. For Ribo-seq use default 0. Ignored if tr (trim) is not one of the arguments in "steps"
- max.multimap numeric, default 10. If a read maps to more locations than specified, will skip the read. Set to 1 to only get unique mapping reads. Only applies for genome alignment step. The depletions are allowing for multimapping.
- alignment.type default: "Local": standard local alignment with soft-clipping allowed, "End-ToEnd" (global): force end-to-end read alignment, does not soft-clip.
- allow.introns logical, default TRUE. Allow large gaps of N in reads during genome alignment, if FALSE: sets –alignIntronMax to 1 (no introns). NOTE: You will still get some spliced reads if you assigned a gtf at the index step.
- max.cpus integer, default: min(90, BiocParallel:::bpparam()\$workers), number of threads to use. Default is minimum of 90 and maximum cores 2. So if you have 8 cores it will use 6. Note: FASTP will use maximum 16 threads as from testing I see performance actually degrades using anything higher. From testing I also see STAR gets no performance gain after ~50 threads. I do suspect this will change when hard drives gets better in the future.
- wait a logical (not NA) indicating whether the R interpreter should wait for the command to finish, or run it asynchronously. This will be ignored (and the interpreter will always wait) if intern = TRUE. When running the command asynchronously, no output will be displayed on the Rgui console in Windows (it will be dropped, instead).
- include.subfolders
 - "n" (no), do recursive search downwards for fast files if "y".
- resume default: NULL, continue from step, lets say steps are "tr-ph-ge": (trim, phix depletion, genome alignment) and resume is "ge", you will then use the assumed already trimmed and phix depleted data and start at genome alignment, useful if something crashed. Like if you specified wrong STAR version, but the trimming step was completed. Resume mode can only run 1 step at the time.
- multiQC logical, default TRUE. Do mutliQC comparison of STAR alignment between all the samples. Outputted in aligned/LOGS folder. See ?STAR.multiQC

keep.contaminants

logical, default FALSE. Create and keep contaminant aligning bam files, default is to only keep unaliged fastq reads, which will be further processed in "ge" genome alignment step. Useful if you want to do further processing on contaminants, like specific coverage of specific tRNAs etc.

keep.unaligned.	genome
	logical, default FALSE. Create and keep reads that did not align at the genome alignment step, default is to only keep the aliged bam file. Useful if you want to do further processing on plasmids/custom sequences.
script.folder	location of STAR index script, default internal ORFik file. You can change it and give your own if you need special alignments.
script.single	location of STAR single file alignment script, default internal ORFik file. You can change it and give your own if you need special alignments.

Details

Can only run on unix systems (Linux, Mac and WSL (Windows Subsystem Linux)), and requires a minimum of 30GB memory on genomes like human, rat, zebrafish etc.

If for some reason the internal STAR alignment bash script will not work for you, like if you want more customization of the STAR/fastp arguments. You can copy the internal alignment script, edit it and give that as the script used for this function.

The trimmer used is fastp (the fastest I could find), also works on (Linux, Mac and WSL (Windows Subsystem Linux)). If you want to use your own trimmer set file1/file2 to the location of the trimmed files from your program.

A note on trimming from creator of STAR about trimming: "adapter trimming it definitely needed for short RNA sequencing. For long RNA-seq, I would agree with Devon that in most cases adapter trimming is not advantageous, since, by default, STAR performs local (not end-to-end) alignment, i.e. it auto-trims." So trimming can be skipped for longer reads.

Value

output.dir, can be used as as input in ORFik::create.experiment

See Also

Other STAR: STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(), STAR.install(), STAR.multiQC(), STAR.remove.crashed.genome(), getGenomeAndAnnotation(), install.fastp()

Examples

```
# First specify directories wanted (temp directory here)
config_file <- tempfile()
#config.save(config_file, base.dir = tempdir())
#config <- ORFik::config(config_file)
## Yeast RNA-seq samples (small genome)
#project <- ORFik::config.exper("chalmers_2012", "Saccharomyces_cerevisiae", "RNA-seq", config)
#annotation.dir <- project["ref"]
#fastq.input.dir <- project["fastq RNA-seq"]
#bam.output.dir <- project["bam RNA-seq"]</pre>
```

```
## Download some SRA data and metadata (subset to 50k reads)
# info <- download.SRA.metadata("SRP012047", outdir = conf["fastq RNA-seq"])
# info <- info[1:2,] # Subset to 2 first libraries
# download.SRA(info, fastq.input.dir, rename = FALSE, subset = 50000)</pre>
```

```
## No contaminant depletion:
# annotation <- getGenomeAndAnnotation("Saccharomyces cerevisiae", annotation.dir)
# index <- STAR.index(annotation)
# STAR.align.folder(fastq.input.dir, bam.output.dir,
```

```
#
                     index, paired.end = FALSE) # Trim, then align to genome
## Human Ribo-seq sample (NB! very large genome and libraries!)
## Requires >= 32 GB memory
#project <- ORFik::config.exper("subtelny_2014", "Homo_sapiens", "Ribo-seq", config)</pre>
#annotation.dir <- project["ref"]</pre>
#fastq.input.dir <- project["fastq Ribo-seq"]</pre>
#bam.output.dir <- project["bam Ribo-seq"]</pre>
## Download some SRA data and metadata (full libraries)
# info <- download.SRA.metadata("DRR041459", fastq.input.dir)</pre>
# download.SRA(info, fastq.input.dir, rename = FALSE)
## Now align 2 different ways, without and with contaminant depletion
## No contaminant depletion:
# annotation <- getGenomeAndAnnotation("Homo sapiens", annotation.dir)</pre>
# index <- STAR.index(annotation)</pre>
# STAR.align.folder(fastq.input.dir, bam.output.dir,
                     index, paired.end = FALSE)
#
## All contaminants merged:
# annotation <- getGenomeAndAnnotation(</pre>
     organism = "Homo_sapiens",
#
     phix = TRUE, ncRNA = TRUE, tRNA = TRUE, rRNA = TRUE,
#
     output.dir = annotation.dir
#
#
     )
# index <- STAR.index(annotation)</pre>
# STAR.align.folder(fastq.input.dir, bam.output.dir,
                     index, paired.end = FALSE,
#
                     steps = "tr-ge")
#
```

STAR.align.single Align single or paired end pair with STAR

Description

Given a single NGS fastq/fasta library, or a paired setup of 2 mated libraries. Run either combination of fastq trimming, contamination removal and genome alignment. Works for (Linux, Mac and WSL (Windows Subsystem Linux))

Usage

```
STAR.align.single(
   file1,
   file2 = NULL,
   output.dir,
   index.dir,
   star.path = STAR.install(),
   fastp = install.fastp(),
   steps = "tr-ge",
   adapter.sequence = "auto",
   quality.filtering = FALSE,
   min.length = 20,
```

310

STAR.align.single

```
mismatches = 3,
trim.front = 0,
max.multimap = 10,
alignment.type = "Local",
allow.introns = TRUE,
max.cpus = min(90, BiocParallel::bpparam()$workers),
wait = TRUE,
resume = NULL,
keep.contaminants = FALSE,
keep.unaligned.genome = FALSE,
keep.index.in.memory = FALSE,
script.single = system.file("STAR_Aligner", "RNA_Align_pipeline.sh", package = "ORFik")
)
```

Arguments

file1	library file, if paired must be R1 file. Allowed formats are: (.fasta, .fastq, .fq, or.fa) with or without compression of .gz. This filename usually contains a suffix of .1
file2	default NULL, set if paired end to R2 file. Allowed formats are: (.fasta, .fastq, .fq, or.fa) with or without compression of .gz. This filename usually contains a suffix of .2
output.dir	directory to save indices, default: paste0(dirname(arguments[1]), "/STAR_index/"), where arguments is the arguments input for this function.
index.dir	path to STAR index folder. Path returned from ORFik function STAR.index, when you created the index folders.
star.path	path to STAR, default: STAR.install(), if you don't have STAR installed at de- fault location, it will install it there, set path to a runnable star if you already have it.
fastp	path to fastp trimmer, default: install.fastp(), if you have it somewhere else al- ready installed, give the path. Only works for unix (linux or Mac OS), if not on unix, use your favorite trimmer and give the output files from that trimmer as input.dir here.
steps	a character, default: "tr-ge", trimming then genome alignment steps of depletion and alignment wanted: The posible candidates you can use are:
	• tr : trim reads
	• co : contamination merged depletion
	• ph : phix depletion
	• rR : rrna depletion
	• nc : ncrna depletion
	• tR : trna depletion (Mature tRNA, so no intron checks done)
	• ge : genome alignment
	 all: run steps: "tr-co-ge" or "tr-ph-rR-nc-tR-ge", depending on if you have merged contaminants or not
	If not "all", a subset of these ("tr-co-ph-rR-nc-tR-ge") If co (merged contaminants) is used, non of the specific contaminants can be specified, since they should be a subset of co.

The step where you align to the genome is usually always included, unless you are doing pure contaminant analysis or only trimming. For Ribo-seq and TCP(RCP-seq) you should do rR (ribosomal RNA depletion), so when you made the STAR index you need the rRNA step, either use rRNA from .gtf or manual download. (usually just download a Silva rRNA database for SSU&LSU at: https://www.arb-silva.de/) for your species.

adapter.sequence

character, default: "auto". Auto detect adapter using fastp adapter auto detection, checking first 1.5M reads. (Auto detection of adapter will not work 100% of the time (if the library is of low quality), then you must rerun this function with specified adapter from fastp adapter analysis. , using FASTQC or other adapter detection tools, else alignment will most likely fail!). If already trimmed or trimming not wanted: adapter.sequence = "disable" .You can manually assign adapter like: "ATCTCGTATGCCGTCTTCTGCTTG" or "AAAAAAAAAAAAAA.". You can also specify one of the three presets:

- illumina (TrueSeq ~75/100 bp sequencing): AGATCGGAAGAGC
- small_RNA (standard for ~50 bp sequencing): TGGAATTCTCGG
- nextera: CTGTCTCTTATA

Paired end auto detection uses overlap sequence of pairs, to use the slower more secure paired end adapter detection, specify as: "autoPE".

quality.filtering

logical, default FALSE. Not needed for modern library prep of RNA-seq, Riboseq etc (usually $< \sim 0.5$ If you are aligning bad quality data, set this to TRUE. These filters will then be applied (default of fastp), filter if:

- Number of N bases in read: > 5
- Read quality: > 40% of bases in the read are < Q15
- min.length 20, minimum length of aligned read without mismatches to pass filter. Anything under 20 is dangerous, as chance of random hits will become high!
- mismatches 3, max non matched bases. Excludes soft-clipping, this only filters reads that have defined mismatches in STAR. Only applies for genome alignment step.
- trim.front 0, default trim 0 bases 5'. For Ribo-seq use default 0. Ignored if tr (trim) is not one of the arguments in "steps"
- max.multimap numeric, default 10. If a read maps to more locations than specified, will skip the read. Set to 1 to only get unique mapping reads. Only applies for genome alignment step. The depletions are allowing for multimapping.
- alignment.type default: "Local": standard local alignment with soft-clipping allowed, "End-ToEnd" (global): force end-to-end read alignment, does not soft-clip.
- allow.introns logical, default TRUE. Allow large gaps of N in reads during genome alignment, if FALSE: sets –alignIntronMax to 1 (no introns). NOTE: You will still get some spliced reads if you assigned a gtf at the index step.
- max.cpus integer, default: min(90, BiocParallel:::bpparam()\$workers), number of threads to use. Default is minimum of 90 and maximum cores 2. So if you have 8 cores it will use 6. Note: FASTP will use maximum 16 threads as from testing I see performance actually degrades using anything higher. From testing I also see STAR gets no performance gain after ~50 threads. I do suspect this will change when hard drives gets better in the future.

wait	a logical (not NA) indicating whether the R interpreter should wait for the com- mand to finish, or run it asynchronously. This will be ignored (and the inter- preter will always wait) if intern = TRUE. When running the command asyn- chronously, no output will be displayed on the Rgui console in Windows (it will be dropped, instead).	
resume	default: NULL, continue from step, lets say steps are "tr-ph-ge": (trim, phix depletion, genome alignment) and resume is "ge", you will then use the assumed already trimmed and phix depleted data and start at genome alignment, useful if something crashed. Like if you specified wrong STAR version, but the trimming step was completed. Resume mode can only run 1 step at the time.	
keep.contaminants		
	logical, default FALSE. Create and keep contaminant aligning bam files, de- fault is to only keep unaliged fastq reads, which will be further processed in "ge" genome alignment step. Useful if you want to do further processing on contaminants, like specific coverage of specific tRNAs etc.	
keep.unaligned.	genome	
	logical, default FALSE. Create and keep reads that did not align at the genome alignment step, default is to only keep the aliged bam file. Useful if you want to do further processing on plasmids/custom sequences.	
keep.index.in.m	nemory	
	logical or character, default FALSE (i.e. LoadAndRemove). If TRUE, will keep index in memory, useful if you need to loop over single calls, instead of using STAR.align.folder (remember last run should use FALSE, to remove index). Alternative useful for MAC machines especially is "noShared", for machines that do not support shared memory index, usually gives error: "abort trap 6".	
script.single	location of STAR single file alignment script, default internal ORFik file. You can change it and give your own if you need special alignments.	

Details

Can only run on unix systems (Linux, Mac and WSL (Windows Subsystem Linux)), and requires a minimum of 30GB memory on genomes like human, rat, zebrafish etc.

If for some reason the internal STAR alignment bash script will not work for you, like if you want more customization of the STAR/fastp arguments. You can copy the internal alignment script, edit it and give that as the script used for this function.

The trimmer used is fastp (the fastest I could find), also works on (Linux, Mac and WSL (Windows Subsystem Linux)). If you want to use your own trimmer set file1/file2 to the location of the trimmed files from your program.

A note on trimming from creator of STAR about trimming: "adapter trimming it definitely needed for short RNA sequencing. For long RNA-seq, I would agree with Devon that in most cases adapter trimming is not advantageous, since, by default, STAR performs local (not end-to-end) alignment, i.e. it auto-trims." So trimming can be skipped for longer reads.

Value

output.dir, can be used as as input in ORFik::create.experiment

See Also

Other STAR: STAR.align.folder(), STAR.allsteps.multiQC(), STAR.index(), STAR.install(), STAR.multiQC(), STAR.remove.crashed.genome(), getGenomeAndAnnotation(), install.fastp()

Examples

```
## Specify output libraries (using temp config)
config_file <- tempfile()</pre>
#config.save(config_file, base.dir = tempdir())
#config <- ORFik::config(config_file)</pre>
#project <- ORFik::config.exper("yeast_1", "Saccharomyces_cerevisiae", "RNA-seq", config)</pre>
# Get genome of yeast (quite small)
# arguments <- getGenomeAndAnnotation("Saccharomyces cerevisiae", project["ref"])</pre>
# index <- STAR.index(arguments)</pre>
## Make fake reads
#genome <- readDNAStringSet(arguments["genome"])</pre>
#which_chromosomes <- sample(seq_along(genome), 1000, TRUE, prob = width(genome))</pre>
#nt50_windows <- lapply(which_chromosomes, function(x)</pre>
# {window <- sample(width(genome[x]) - 51, 1); genome[[x]][seq(window, window+49)]})</pre>
#nt50_windows <- DNAStringSet(nt50_windows)</pre>
#names(nt50_windows) <- paste0("read_", seq_along(nt50_windows))</pre>
#dir.create(project["fastq RNA-seq"], recursive = TRUE)
#fake_fasta <- file.path(project["fastq RNA-seq"], "fake-RNA-seq.fasta")</pre>
#writeXStringSet(nt50_windows, fake_fasta, format = "fasta")
## Align the fake reads and import bam
# STAR.align.single(fake_fasta, NULL, project["bam RNA-seq"], index, steps = "ge")
#bam_file <- list.files(file.path(project["bam RNA-seq"], "aligned"),</pre>
# pattern = "\.bam$", full.names = TRUE)
#fimport(bam_file)
```

STAR.allsteps.multiQC Create STAR multiQC plot and table

Description

Takes a folder with multiple Log.final.out files from STAR, and create a multiQC report. This is automatically run with STAR.align.folder function.

Usage

```
STAR.allsteps.multiQC(folder, steps = "auto", plot.ext = ".pdf")
```

Arguments

folder	path to main output folder of STAR run. The folder that contains /aligned/, "/trim/, "contaminants_depletion" etc. To find the LOGS folders in, to use for summarized statistics.
steps	a character, default "auto". Find which steps you did. If manual, a combination of "tr-co-ge". See STAR alignment functions for description.
plot.ext	character, default ".pdf". Which format to save QC plot. Alternative: ".png".

Value

data.table of main statistics, plots and data saved to disc. Named: "/00_STAR_LOG_plot.pdf" and "/00_STAR_LOG_table.csv"

314

STAR.index

See Also

Other STAR: STAR.align.folder(), STAR.align.single(), STAR.index(), STAR.install(), STAR.multiQC(), STAR.remove.crashed.genome(), getGenomeAndAnnotation(), install.fastp()

STAR.index

Create STAR genome index

Description

Used as reference when aligning data Get genome and gtf by running getGenomeAndFasta()

Usage

```
STAR.index(
    arguments,
    output.dir = paste0(dirname(arguments[1]), "/STAR_index/"),
    star.path = STAR.install(),
    max.cpus = min(90, BiocParallel::bpparam()$workers),
    max.ram = 30,
    SAsparse = 1,
    tmpDirStar = "-",
    wait = TRUE,
    remake = FALSE,
    script = system.file("STAR_Aligner", "STAR_MAKE_INDEX.sh", package = "ORFik"),
    notify_load_existing = TRUE
)
```

Arguments

arguments	a named character vector containing paths wanted to use for index creation. They must be named correctly: names must be a subset of: c("gtf", "genome", "contaminants", "phix", "rRNA", "tRNA", "ncRNA")
output.dir	directory to save indices, default: paste0(dirname(arguments[1]), "/STAR_index/"), where arguments is the arguments input for this function.
star.path	path to STAR, default: STAR.install(), if you don't have STAR installed at de- fault location, it will install it there, set path to a runnable star if you already have it.
max.cpus	integer, default: min(90, BiocParallel:::bpparam()\$workers), number of threads to use. Default is minimum of 90 and maximum cores - 2. So if you have 8 cores it will use 6. Note: FASTP will use maximum 16 threads as from testing I see performance actually degrades using anything higher. From testing I also see STAR gets no performance gain after ~50 threads. I do suspect this will change when hard drives gets better in the future.
max.ram	integer, default 30, in Giga Bytes (GB). Maximum amount of RAM allowed for STAR limitGenomeGenerateRAM argument. RULE: idealy 10x genome size, but do not set too close to machine limit. Default fits well for human genome size (3 GB $*$ 10 = 30 GB)

SAsparse	int > 0, default 1. If you do not have at least 64GB RAM, you might need to set this to 2. suffux array sparsity, i.e. distance between indices: use bigger numbers to decrease needed RAM at the cost of mapping speed reduction. Only applies to genome, not conaminants.	
tmpDirStar	character, default "-". STAR automatic temp folder creation, deleted when done. The directory can not exists, as a safety STAR must make it!. If you are on a NFS file share drive, and you have a non NFS tmp dir, set this to tempfile() or the manually specified folder to get a considerable speedup!	
wait	a logical (not NA) indicating whether the R interpreter should wait for the command to finish, or run it asynchronously. This will be ignored (and the interpreter will always wait) if intern = TRUE. When running the command asynchronously, no output will be displayed on the Rgui console in Windows (it will be dropped, instead).	
remake	logical, default: FALSE, if TRUE remake everything specified	
script	location of STAR index script, default internal ORFik file. You can change it and give your own if you need special alignments.	
notify_load_existing		
	logical, default TRUE. If annotation exists (defined as: locally (a file called outputs.rds) exists in outputdir), print a small message notifying the user it is not redownloading. Set to FALSE, if this is not wanted	

Details

Can only run on unix systems (Linux and Mac), and requires minimum 30GB memory on genomes like human, rat, zebrafish etc.

If for some reason the internal STAR index bash script will not work for you, like if you have a very small genome. You can copy the internal index script, edit it and give that as the Index script used for this function. It is recommended to run through the RStudio local job tab, to give full info about the run. The system console will not stall, as can happen in happen in normal RStudio console.

Value

output.dir, can be used as as input for STAR.align..

See Also

```
Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.install(),
STAR.multiQC(), STAR.remove.crashed.genome(), getGenomeAndAnnotation(), install.fastp()
```

Examples

```
## Manual way, specify all paths yourself.
#arguments <- c(path.GTF, path.genome, path.phix, path.rrna, path.trna, path.ncrna)
#names(arguments) <- c("gtf", "genome", "phix", "rRNA", "tRNA","ncRNA")
#STAR.index(arguments, "output.dir")</pre>
```

```
## Or use ORFik way:
output.dir <- "/Bio_data/references/Human"
# arguments <- getGenomeAndAnnotation("Homo sapiens", output.dir)
# STAR.index(arguments, output.dir)
```

STAR.install

Description

Will not run "make", only use precompiled STAR file. Can only run on unix systems (Linux and Mac), and requires minimum 30GB memory on genomes like human, rat, zebrafish etc.

Usage

```
STAR.install(folder = "~/bin", version = "2.7.4a")
```

Arguments

folder	path to folder for download, fille will be named "STAR-version", where version is version wanted.
version	default "2.7.4a"

Details

ORFik for now only uses precompiled STAR binaries, so if you already have a STAR version it is adviced to redownload the same version, since STAR genome indices usually does not work between STAR versions.

Value

path to runnable STAR

References

https://www.ncbi.nlm.nih.gov/pubmed/23104886

See Also

```
Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(),
STAR.multiQC(), STAR.remove.crashed.genome(), getGenomeAndAnnotation(), install.fastp()
```

Examples

```
## Default folder install:
#STAR.install()
## Manual set folder:
folder <- "/I/WANT/IT/HERE"
#STAR.install(folder, version = "2.7.4a")
```

STAR.multiQC

Description

Takes a folder with multiple Log.final.out files from STAR, and create a multiQC report

Usage

```
STAR.multiQC(folder, type = "aligned", plot.ext = ".pdf")
```

Arguments

folder	path to LOGS folder of ORFik STAR runs. Can also be the path to the aligned/
	(parent directory of LOGS), then it will move into LOG from there. Only if no
	files with pattern Log.final.out are found in parent directory. If no LOGS folder
	is found it can check for a folder /aligned/LOGS/ so to go 2 folders down.
type	a character path, default "aligned". Which subfolder to check for. If you want log files for contamination do type = "contaminants_depletion"
plot.ext	character, default ".pdf". Which format to save QC plot. Alternative: ".png".

Value

a data.table with all information from STAR runs, plot and data saved to disc. Named: "/00_STAR_LOG_plot.pdf" and "/00_STAR_LOG_table.csv"

See Also

Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(), STAR.install(), STAR.remove.crashed.genome(), getGenomeAndAnnotation(), install.fastp()

STAR.remove.crashed.genome

Remove crashed STAR genome

Description

This happens if you abort STAR run early, and it halts at: loading genome

Usage

```
STAR.remove.crashed.genome(index.path, star.path = STAR.install())
```

Arguments

index.path	path to index folder of genome
star.path	path to STAR, default: STAR.install(), if you don't have STAR installed at de- fault location, it will install it there, set path to a runnable star if you already have it.

startCodons

Value

return value from system call, 0 if all good.

See Also

```
Other STAR: STAR.align.folder(), STAR.align.single(), STAR.allsteps.multiQC(), STAR.index(),
STAR.install(), STAR.multiQC(), getGenomeAndAnnotation(), install.fastp()
```

Examples

```
index.path = "/home/data/human_GRCh38/STAR_INDEX/genomeDir/"
# STAR.remove.crashed.genome(index.path = index.path)
## If you have the index argument from STAR.index function:
# index.path <- STAR.index()
# STAR.remove.crashed.genome(file.path(index.path, "genomeDir"))
# STAR.remove.crashed.genome(file.path(index.path, "contaminants_genomeDir"))</pre>
```

startCodons	Get the Start codons(3 bases) from a GRangesList of orfs grouped by
	orfs

Description

In ATGTTTTGA, get the positions ATG. It takes care of exons boundaries, with exons < 3 length.

Usage

```
startCodons(grl, is.sorted = FALSE)
```

Arguments

grl	a GRangesList object
is.sorted	a boolean, a speedup if you know the ranges are sorted

Value

a GRangesList of start codons, since they might be split on exons

See Also

```
Other ORFHelpers: defineTrailer(), longestORFs(), mapToGRanges(), orfID(), startSites(),
stopCodons(), stopSites(), txNames(), uniqueGroups(), uniqueOrder()
```

Examples

startDefinition

Description

According to: <http://www.ncbi.nlm.nih.gov/Taxonomy/taxonomyhome.html/index.cgi?chapter=tgencodes#SG1> ncbi genetic code number for translation. This version is a cleaned up version, unknown indices removed.

Usage

startDefinition(transl_table)

Arguments

transl_table numeric. NCBI genetic code number for translation.

Value

A string of START sites separatd with "I".

See Also

Other findORFs: findMapORFs(), findORFs(), findORFsFasta(), findUORFs(), stopDefinition()

Examples

```
startDefinition
startDefinition(1)
```

startRegion

Start region as GRangesList

Description

Get the start region of each ORF. If you want the start codon only, set upstream = 0 or just use startCodons. Standard is 2 upstream and 2 downstream, a width 5 window centered at start site. since p-shifting is not 100 usually the reads from the start site.

Usage

```
startRegion(grl, tx = NULL, is.sorted = TRUE, upstream = 2L, downstream = 2L)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs
tx	default NULL, a GRangesList of transcripts or (container region), names of tx must contain all grl names. The names of grl can also be the ORFik orf names. that is "txName_id"
is.sorted	logical (TRUE), is grl sorted.
upstream	an integer (2), relative region to get upstream from.
downstream	an integer (2), relative region to get downstream from

Details

If tx is null, then upstream will be forced to 0 and downstream to a maximum of grl width (3' UTR end for mRNAs). Since there is no reference for splicing.

Value

a GRanges, or GRangesList object if any group had > 1 exon.

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(),
initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(),
orfScore(), rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegionCoverage(),
stopRegion(), subsetCoverage(), translationalEff()
```

Examples

startRegionCoverage Start region coverage

Description

Get the number of reads in the start region of each ORF. If you want the start codon coverage only, set upstream = 0. Standard is 2 upstream and 2 downstream, a width 5 window centered at start site. since p-shifting is not 100 start site.

Usage

```
startRegionCoverage(
  grl,
  RFP,
  tx = NULL,
  is.sorted = TRUE,
  upstream = 2L,
  downstream = 2L,
  weight = 1L
)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs
RFP	ribo seq reads as GAlignments, GRanges or GRangesList object
tx	default NULL, a GRangesList of transcripts or (container region), names of tx must contain all grl names. The names of grl can also be the ORFik orf names. that is "txName_id"
is.sorted	logical (TRUE), is grl sorted.
upstream	an integer (2), relative region to get upstream from.
downstream	an integer (2), relative region to get downstream from
weight	a vector (default: 1L, if 1L it is identical to countOverlaps()), if single number (!= 1), it applies for all, if more than one must be equal size of 'reads'. else it must be the string name of a defined meta column in subject "reads", that gives number of times a read was found. GRanges("chr1", 1, "+", score = 5), would mean "score" column tells that this alignment region was found 5 times.

Details

If tx is null, then upstream will be force to 0 and downstream to a maximum of grl width. Since there is no reference for splicing.

Value

a numeric vector of counts

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(), distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(), rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), stopRegion(), subsetCoverage(), translationalEff()
```

Examples

322

startRegionString

startRegionString Get start region as DNA-strings per GRanges group

Description

One window per start site, if upstream and downstream are both 0, then only the startsite is returned.

Usage

```
startRegionString(grl, tx, faFile, upstream = 20, downstream = 20)
```

Arguments

grl	a GRangesList of ranges to find regions in.
tx	a GRangesList of transcripts or (container region), names of tx must contain all gr names. The names of gr can also be the ORFik orf names. that is "tx-Name_id".
faFile	FaFile, BSgenome, fasta/index file path or an ORFik experiment. This file is usually used to find the transcript sequences from some GRangesList.
upstream	an integer, default (0), relative region to get upstream from.
downstream	an integer, default (0), relative region to get downstream from

Value

a character vector of start regions

startSites Get the start sites from a GRangesList of orfs grouped by orfs

Description

In ATGTTTTGG, get the position of the A.

Usage

startSites(grl, asGR = FALSE, keep.names = FALSE, is.sorted = FALSE)

Arguments

grl	a GRangesList object
asGR	a boolean, return as GRanges object
keep.names	a logical (FALSE), keep names of input.
is.sorted	a speedup, if you know the ranges are sorted

Value

if asGR is False, a vector, if True a GRanges object

See Also

```
Other ORFHelpers: defineTrailer(), longestORFs(), mapToGRanges(), orfID(), startCodons(),
stopCodons(), stopSites(), txNames(), uniqueGroups(), uniqueOrder()
```

Examples

stopCodons	Get the Stop codons (3 bases) from a GRangesList of orfs grouped by
	orfs

Description

In ATGTTTTGA, get the positions TGA. It takes care of exons boundaries, with exons < 3 length.

Usage

stopCodons(grl, is.sorted = FALSE)

Arguments

grl	a GRangesList object
is.sorted	a boolean, a speedup if you know the ranges are sorted

Value

a GRangesList of stop codons, since they might be split on exons

See Also

```
Other ORFHelpers: defineTrailer(), longestORFs(), mapToGRanges(), orfID(), startCodons(),
startSites(), stopSites(), txNames(), uniqueGroups(), uniqueOrder()
```

324
stopDefinition

Examples

stopDefinition Returns stop codon definitions

Description

According to: <http://www.ncbi.nlm.nih.gov/Taxonomy/taxonomyhome.html/index.cgi?chapter=tgencodes#SG1> ncbi genetic code number for translation. This version is a cleaned up version, unknown indices removed.

Usage

```
stopDefinition(transl_table)
```

Arguments

transl_table numeric. NCBI genetic code number for translation.

Value

A string of STOP sites separatd with "I".

See Also

Other findORFs: findMapORFs(), findORFs(), findORFsFasta(), findUORFs(), startDefinition()

Examples

```
stopDefinition
stopDefinition(1)
```

stopRegion

Description

Get the stop region of each ORF / region. If you want the stop codon only, set downstream = 0 or just use stopCodons. Standard is 2 upstream and 2 downstream, a width 5 window centered at stop site.

Usage

```
stopRegion(grl, tx = NULL, is.sorted = TRUE, upstream = 2L, downstream = 2L)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs
tx	default NULL, a GRangesList of transcripts or (container region), names of tx must contain all grl names. The names of grl can also be the ORFik orf names. that is "txName_id"
is.sorted	logical (TRUE), is grl sorted.
upstream	an integer (2), relative region to get upstream from.
downstream	an integer (2), relative region to get downstream from

Details

If tx is null, then downstream will be forced to 0 and upstream to a minimum of -grl width (to the TSS). . Since there is no reference for splicing.

Value

a GRanges, or GRangesList object if any group had > 1 exon.

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(),
distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(),
initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(),
orfScore(), rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(),
startRegionCoverage(), subsetCoverage(), translationalEff()
```

Examples

stopSites

Description

In ATGTTTTGC, get the position of the C.

Usage

```
stopSites(grl, asGR = FALSE, keep.names = FALSE, is.sorted = FALSE)
```

Arguments

grl	a GRangesList object
asGR	a boolean, return as GRanges object
keep.names	a logical (FALSE), keep names of input.
is.sorted	a speedup, if you know the ranges are sorted

Value

if asGR is False, a vector, if True a GRanges object

See Also

```
Other ORFHelpers: defineTrailer(), longestORFs(), mapToGRanges(), orfID(), startCodons(),
startSites(), stopCodons(), txNames(), uniqueGroups(), uniqueOrder()
```

Examples

strandBool

Get logical list of strands

Description

Helper function to get a logical list of True/False, if GRangesList group have + strand = T, if - strand = F Also checks for * strands, so a good check for bugs

Usage

strandBool(grl)

Arguments

grl a GRangesList or GRanges object

Value

a logical vector

Examples

strandMode,covRle-method

strandMode covRle

Description

strandMode covRle

Usage

```
## S4 method for signature 'covRle'
strandMode(x)
```

Arguments

x a covRle object

Value

integer vector with names

strandMode.covRleList-method
 strandMode covRle

Description

strandMode covRle

Usage

```
## S4 method for signature 'covRleList'
strandMode(x)
```

strandPerGroup

Arguments

x a covRle object

Value

integer vector with names

strandPerGroup Get list of strands per granges group

Description

Get list of strands per granges group

Usage

```
strandPerGroup(grl, keep.names = TRUE)
```

Arguments

grl	a GRangesList
keep.names	a boolean, keep names or not, default: (TRUE)

Value

a vector named/unnamed of characters

Examples

subsetCoverage Subset GRanges to get coverage.

Description

GRanges object should be beforehand tiled to size of 1. This subsetting takes account for strand.

Usage

```
subsetCoverage(cov, y)
```

Arguments

COV	A coverage object from coverage()
У	GRanges object for which coverage should be extracted

Value

numeric vector of coverage of input GRanges object

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(), distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(), rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegion(), translationalEff()
```

```
subsetToFrame
```

Subset GRanges to get desired frame.

Description

Usually used for ORFs to get specific frame (0-2): frame 0, frame 1, frame 2

Usage

```
subsetToFrame(x, frame)
```

Arguments

х	A tiled to size of 1 GRanges object
frame	A numeric indicating which frame to extract

Details

GRanges object should be beforehand tiled to size of 1. This subsetting takes account for strand.

Value

GRanges object reduced to only first frame

Examples

```
subsetToFrame(GRanges("1", IRanges(1:10, width = 1), "+"), 2)
```

symbols

Description

Get ORFik experiment QC folder path

Usage

symbols(x)

Arguments

х

an ORFik experiment

Value

a data.table with gene id, gene symbols and tx ids (3 columns)

symbols,experiment-method

Get ORFik experiment QC folder path

Description

Get ORFik experiment QC folder path

Usage

```
## S4 method for signature 'experiment'
symbols(x)
```

Arguments

x an ORFik experiment

Value

a character path

te.plot

Description

Create 2 TE plots of:

- Within sample (TE log2 vs mRNA fpkm) ("default")
- Between all combinations of samples (x-axis: rna1fpkm rna2fpkm, y-axis rfp1fpkm rfp2fpkm)

Usage

```
te.plot(
  df.rfp,
  df.rna,
  output.dir = QCfolder(df.rfp),
  type = c("default", "between"),
  filter.rfp = 1,
  filter.rna = 1,
  collapse = FALSE,
  plot.title = "",
  plot.ext = ".pdf",
  width = 6,
  height = "auto"
)
```

Arguments

a experiment of Ribo-seq or 80S from TCP-seq.
a experiment of RNA-seq
directory to save plots, plots will be named "TE_between.pdf" and "TE_within.pdf"
which plots to make, default: c("default", "between"). Both plots.
numeric, default 1. minimum fpkm value to be included in plots
numeric, default 1. minimum fpkm value to be included in plots
a logical/character (default FALSE), if TRUE all samples within the group SAM- PLE will be collapsed to one. If "all", all groups will be merged into 1 col- umn called merged_all. Collapse is defined as rowSum(elements_per_group) / ncol(elements_per_group)
title for plots, usually name of experiment etc
character, default: ".pdf". Alternatives: ".png" or ".jpg".
numeric, default 6 (in inches)
numeric or character, default "auto", which is: 3 + (ncol(RFP_CDS_FPKM)-2). Else a numeric value of height (in inches)

Details

Ribo-seq and RNA-seq must have equal nrows, with matching samples. Only exception is if RNA-seq is 1 single sample. Then it will use that for each of the Ribo-seq samples. Same stages, conditions etc, with a unique pairing 1 to 1. If not you can run collapse = "all". It will then merge all and do combined of all RNA-seq vs all Ribo-seq

te.table

Value

a data.table with TE values, fpkm and log fpkm values, library samples melted into rows with split variable called "variable".

Examples

```
##
# df.rfp <- read.experiment("zf_baz14_RFP")
# df.rna <- read.experiment("zf_baz14_RNA")
# te.plot(df.rfp, df.rna)
## Collapse replicates:
# te.plot(df.rfp, df.rna, collapse = TRUE)</pre>
```

te.table

Create a TE table

Description

Creates a data.table with 6 columns, column names are: variable, rfp_log2, rna_log2, rna_log10, TE_log2, id

Usage

te.table(df.rfp, df.rna, filter.rfp = 1, filter.rna = 1, collapse = FALSE)

Arguments

df.rfp	a experiment of usually Ribo-seq or 80S from TCP-seq. (the numerator of the experiment, usually having a primary role)
df.rna	a experiment of usually RNA-seq. (the denominator of the experiment, usually having a normalizing function)
filter.rfp	numeric, default 1. What is the minimum fpkm value?
filter.rna	numeric, default 1. What is the minimum fpkm value?
collapse	a logical/character (default FALSE), if TRUE all samples within the group SAM- PLE will be collapsed to one. If "all", all groups will be merged into 1 col- umn called merged_all. Collapse is defined as rowSum(elements_per_group) / ncol(elements_per_group)

Value

a data.table with 6 columns

See Also

Other DifferentialExpression: DEG.plot.static(), DEG_model(), DTEG.analysis(), DTEG.plot(), te_rna.plot()

Examples

```
df <- ORFik.template.experiment()
df.rfp <- df[df$libtype == "RFP",]
df.rna <- df[df$libtype == "RNA",]
#te.table(df.rfp, df.rna)</pre>
```

te_rna.plot

Description

Create TE plot of: - Within sample (TE log2 vs mRNA fpkm)

Usage

```
te_rna.plot(
    dt,
    output.dir = NULL,
    filter.rfp = 1,
    filter.rna = 1,
    plot.title = "",
    plot.ext = ".pdf",
    width = 6,
    height = "auto",
    dot.size = 0.4,
    xlim = c(filter.rna, filter.rna + 2.5)
)
```

Arguments

dt	a data.table with the results from te.table
output.dir	a character path, default NULL(no save), or a directory to save to a file will be called "TE_within.pdf"
filter.rfp	numeric, default 1. What is the minimum fpkm value?
filter.rna	numeric, default 1. What is the minimum fpkm value?
plot.title	title for plots, usually name of experiment etc
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".
width	numeric, default 6 (in inches)
height	a numeric, width of plot in inches. Default "auto".
dot.size	numeric, default 0.4, size of point dots in plot.
xlim	<pre>numeric vector of length 2. X-axis limits. Default: c(filter.rna, filter.rna + 2.5)</pre>

Value

a ggplot object

See Also

Other DifferentialExpression: DEG.plot.static(), DEG_model(), DTEG.analysis(), DTEG.plot(), te.table() tile1

Examples

```
df <- ORFik.template.experiment()
df.rfp <- df[df$libtype == "RFP",]
df.rna <- df[df$libtype == "RNA",]
#dt <- te.table(df.rfp, df.rna)
#te_rna.plot(dt, filter.rfp = 0, filter.rna = 5, dot.size = 1)</pre>
```

tile1

```
Tile each GRangesList group to 1-base resolution.
```

Description

Will tile a GRangesList into single bp resolution, each group of the list will be splited by positions of 1. Returned values are sorted as the same groups as the original GRangesList, except they are in bp resolutions. This is not supported originally by GenomicRanges for GRangesList.

Usage

```
tile1(grl, sort.on.return = TRUE, matchNaming = TRUE, is.sorted = TRUE)
```

Arguments

grl	a GRangesList object with names.
sort.on.return	logical (TRUE), should the groups be sorted before return (Negative ranges should be in decreasing order). Makes it a bit slower, but much safer for downstream analysis.
matchNaming	logical (TRUE), should groups keep unlisted names and meta data. (This make the list very big, for $>100 {\rm K}$ groups)
is.sorted	logical (TRUE), grl is presorted (negative coordinates are decreasing). Set to FALSE if they are not, else output will most likely be wrong!

Value

a GRangesList grouped by original group, tiled to 1. Groups with identical names will be merged.

See Also

Other ExtendGenomicRanges: asTX(), coveragePerTiling(), extendLeaders(), extendTrailers(), reduceKeepAttr(), txSeqsFromFa(), windowPerGroup()

Examples

tissueNames

Description

Used to standardize nomeclature for experiments. Example: testis is main naming, but a variant is testicles. testicles will then be renamed to testis.

Usage

tissueNames()

Value

a data.table with 2 columns, the main name, and all name variants of the main name in second column as a list.

See Also

Other experiment_naming: batchNames(), cellLineNames(), cellTypeNames(), conditionNames(), fractionNames(), inhibitorNames(), libNames(), mainNames(), repNames(), stageNames()

TOP.Motif.ecdf TOP Motif ecdf plot

Description

Given sequences, DNA or RNA. And some score, scanning efficiency (SE), ribo-seq fpkm, TE etc.

Usage

```
TOP.Motif.ecdf(
    seqs,
    rate,
    start = 1,
    stop = max(nchar(seqs)),
    xlim = c("q10", "q99"),
    type = "Scanning efficiency",
    legend.position.1st = c(0.75, 0.28),
    legend.position.motif = c(0.75, 0.28)
)
```

Arguments

seqs	the sequences (character vector, DNAStringSet), of 5' UTRs (leaders). See example below for input.
rate	a scoring vector (equal size to seqs)
start	position in seqs to start at (first is 1), default 1.

stop	position in seqs to stop at (first is 1), default max(nchar(seqs)), that is the longest sequence length
xlim	What interval of rate values you want to show type: numeric or quantile of length 2, 1. default c("q10","q99"). bigger than 10 percentile and less than 99 percentile. 2. Set to numeric values, like c(5, 1000), 3. Set to NULL if you want all values. Backend uses coord_cartesian.
type	What type is the rate scoring ? default ("Scanning efficiency")
legend.positio	on.1st
	adjust left plot label position, default c(0.75, 0.28), ("none", "left", "right", "bottom", "top", or two-element numeric vector)
legend.positio	on.motif
	adjust right plot label position, default c(0.75, 0.28), ("none", "left", "right", "bottom", "top", or two-element numeric vector)

Details

Top motif defined as a TSS of C and 4 T's or C's (pyrimidins) downstream of TSS C.

The right plot groups: C nucleotide, TOP motif (C, then 4 pyrimidines) and OTHER (all other TSS variants).

Value

a ggplot gtable of the TOP motifs in 2 plots

Examples

```
## Not run:
if (requireNamespace("BSgenome.Hsapiens.UCSC.hg19")) {
  txdbFile <- system.file("extdata", "hg19_knownGene_sample.sqlite",</pre>
                           package = "GenomicFeatures")
  #Extract sequences of Coding sequences.
  leaders <- loadRegion(txdbFile, "leaders")</pre>
  # Should update by CAGE if not already done
  cageData <- system.file("extdata", "cage-seq-heart.bed.bgz",</pre>
                           package = "ORFik")
  leadersCage <- reassignTSSbyCage(leaders, cageData)</pre>
  # Get region to check
  seqs <- startRegionString(leadersCage, NULL,</pre>
        BSgenome.Hsapiens.UCSC.hg19::Hsapiens, 0, 4)
  # Some toy ribo-seq fpkm scores on cds
  set.seed(3)
  fpkm <- sample(1:115, length(leadersCage), replace = TRUE)</pre>
  # Standard arguments
  TOP.Motif.ecdf(seqs, fpkm, type = "ribo-seq FPKM",
                  legend.position.1st = "bottom",
                  legend.position.motif = "bottom")
  # with no zoom on x-axis:
  TOP.Motif.ecdf(seqs, fpkm, xlim = NULL,
                 legend.position.1st = "bottom",
                 legend.position.motif = "bottom")
}
```

End(Not run)

topMotif

Description

Per leader, detect if the leader has a TOP motif at TSS (5' end of leader) TOP motif defined as: (C, then 4 pyrimidines)

Usage

topMotif(seqs, start = 1, stop = max(nchar(seqs)), return.sequence = TRUE)

Arguments

seqs	the sequences (character vector, DNAStringSet), of 5' UTRs (leaders) start re- gion. seqs must be of minimum widths start - stop + 1 to be included. See example below for input.
start	position in seqs to start at (first is 1), default 1.
stop	position in seqs to stop at (first is 1), default max(nchar(seqs)), that is the longest sequence length
return.sequence	
	logical, default TRUE, return as data.table with sequence as columns in addition to TOP class. If FALSE, return character vector.

Value

default: return.sequence == FALSE, a character vector of either TOP, C or OTHER. C means leaders started on C, Other means not TOP and did not start on C. If return.sequence == TRUE, a data.table is returned with the base per position in the motif is included as additional columns (per position called seq1, seq2 etc) and a id column called X.gene_id (with names of seqs).

Examples

transcriptWindow Make 100 bases size meta window for all libraries in experiment

Description

Gives you binned meta coverage plots, either saved seperatly or all in one.

Usage

```
transcriptWindow(
 leaders,
 cds,
 trailers,
 df,
 outdir = NULL,
 scores = c("sum", "transcriptNormalized"),
 allTogether = TRUE,
 colors = experiment.colors(df),
 title = "Coverage metaplot",
 windowSize = min(100, min(widthPerGroup(leaders, FALSE)), min(widthPerGroup(cds,
   FALSE)), min(widthPerGroup(trailers, FALSE))),
 returnPlot = is.null(outdir),
 dfr = NULL,
 idName = ""
 plot.ext = ".pdf",
  type = "ofst",
  is.sorted = FALSE,
 drop.zero.dt = TRUE,
 verbose = TRUE,
 force = TRUE,
 library.names = bamVarName(df),
 BPPARAM = bpparam()
```

)

Arguments

leaders	a GRangesList of leaders (5' UTRs)
cds	a GRangesList of coding sequences
trailers	a GRangesList of trailers (3' UTRs)
df	an ORFik experiment
outdir	directory to save to (default: NULL, no saving)
scores	scoring function (default: c("sum", "transcriptNormalized")), see ?coverageScorings for possible scores.
allTogether	plot all coverage plots in 1 output? (defualt: TRUE)
colors	Which colors to use, default auto color from function experiment.colors, new color per library type. Else assign colors yourself.
title	title of ggplot
windowSize	size of binned windows, default: 100

returnPlot	return plot from function, default is.null(outdir), so TRUE if outdir is not defined.
dfr	an ORFik experiment of RNA-seq to normalize against. Will add RNA normalized to plot name if this is done.
idName	A character ID to add to saved name of plot, if you make several plots in the same folder, and same experiment, like splitting transcripts in two groups like targets / nontargets etc. (default: "")
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".
type	 a character(default: "default"), load files in experiment or some precomputed variant, like "ofst" or "pshifted". These are made with ORFik:::convertLibs(), shiftFootprintsByExperiment(), etc. Can also be custom user made folders inside the experiments bam folder. It acts in a recursive manner with priority: If you state "pshifted", but it does not exist, it checks "ofst". If no .ofst files, it uses "default", which always must exists. Presets are (folder is relative to default lib folder, some types fall back to other formats if folder does not exist): - "default": load the original files for experiment, usually bam. - "ofst": loads ofst files from the ofst folder, relative to lib folder (falls back to default) - "pshifted": loads ofst, wig or bigwig from pshifted folder (falls back to ofst, then default) - "cov": Load covRle objects from cov_RLE folder (fail if not found) - "covl": Load bed files, from bed folder (falls back to default) - Other formats must be loaded directly with fimport
is.sorted	logical (FALSE), is grl sorted. That is + strand groups in increasing ranges $(1,2,3)$, and - strand groups in decreasing ranges $(3,2,1)$
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count posi- tions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)
verbose	logical, default TRUE, message about library output status.
force	logical, default TRUE If TRUE, reload library files even if matching named variables are found in environment used by experiment (see envExp) A simple way to make sure correct libraries are always loaded. FALSE is faster if data is loaded correctly already.
library.names	character vector, names of libraries, default: name_decider(df, naming)
BPPARAM	how many cores/threads to use? default: bpparam()

Value

NULL, or ggplot object if returnPlot is TRUE

See Also

Other experiment plots: transcriptWindow1(), transcriptWindowPer()

transcriptWindow1

Examples

```
df <- ORFik.template.experiment()[3,] # Only third library
loadRegions(df) # Load leader, cds and trailers as GRangesList
#transcriptWindow(leaders, cds, trailers, df, outdir = "directory/to/save")</pre>
```

transcriptWindow1 *Meta coverage over all transcripts*

Description

Given as single window

Usage

```
transcriptWindow1(
    df,
    outdir = NULL,
    scores = c("sum", "zscore"),
    colors = experiment.colors(df),
    title = "Coverage metaplot",
    windowSize = 100,
    returnPlot = is.null(outdir),
    dfr = NULL,
    idName = "",
    plot.ext = ".pdf",
    type = "ofst",
    drop.zero.dt = drop.zero.dt,
    BPPARAM = bpparam()
)
```

Arguments

df	an ORFik experiment
outdir	directory to save to (default: NULL, no saving)
scores	scoring function (default: c("sum", "transcriptNormalized")), see ?coverageScorings for possible scores.
colors	Which colors to use, default auto color from function experiment.colors, new color per library type. Else assign colors yourself.
title	title of ggplot
windowSize	size of binned windows, default: 100
returnPlot	return plot from function, default is.null(outdir), so TRUE if outdir is not defined.
dfr	an ORFik experiment of RNA-seq to normalize against. Will add RNA normalized to plot name if this is done.
idName	A character ID to add to saved name of plot, if you make several plots in the same folder, and same experiment, like splitting transcripts in two groups like targets / nontargets etc. (default: "")
plot.ext	character, default: ".pdf". Alternatives: ".png" or ".jpg".

type	a character(default: "default"), load files in experiment or some precomputed variant, like "ofst" or "pshifted". These are made with ORFik:::convertLibs(), shiftFootprintsByExperiment(), etc. Can also be custom user made folders in- side the experiments bam folder. It acts in a recursive manner with priority: If you state "pshifted", but it does not exist, it checks "ofst". If no .ofst files, it uses "default", which always must exists. Presets are (folder is relative to default lib folder, some types fall back to other formats if folder does not exist): - "default": load the original files for experiment, usually bam.
	 "ofst": loads ofst files from the ofst folder, relative to lib folder (falls back to default) "pshifted": loads ofst, wig or bigwig from pshifted folder (falls back to ofst, then default) "cov": Load covRle objects from cov_RLE folder (fail if not found) "covl": Load covRleList objects, from cov_RLE_List folder (fail if not found) "bed": Load bed files, from bed folder (falls back to default) Other formats must be loaded directly with fimport
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count posi- tions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)
BPPARAM	how many cores/threads to use? default: bpparam()

Value

NULL, or ggplot object if returnPlot is TRUE

See Also

Other experiment plots: transcriptWindow(), transcriptWindowPer()

transcriptWindowPer Helper function for transcriptWindow

Description

Make 100 bases size meta window for one library in experiment

Usage

```
transcriptWindowPer(
  leaders,
  cds,
  trailers,
  df,
  outdir = NULL,
  scores = c("sum", "zscore"),
  reads,
  returnCoverage = FALSE,
  windowSize = 100,
  drop.zero.dt = TRUE,
```

translationalEff

BPPARAM = bpparam()
)

Arguments

leaders	a GRangesList of leaders (5' UTRs)			
cds	a GRangesList of coding sequences			
trailers	a GRangesList of trailers (3' UTRs)			
df	an ORFik experiment			
outdir	directory to save to (default: NULL, no saving)			
scores	scoring function (default: c("sum", "transcriptNormalized")), see ?coverageScorings for possible scores.			
reads	a GRanges / GAligment object of reads, can also be a list of those.			
returnCoverage	return data.table with coverage (default: FALSE)			
windowSize	size of binned windows, default: 100			
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count posi- tions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)			
BPPARAM	how many cores/threads to use? default: bpparam()			

Details

Gives you binned meta coverage plots, either saved seperatly or all in one.

Value

NULL, or ggplot object if returnPlot is TRUE

See Also

Other experiment plots: transcriptWindow(), transcriptWindow1()

translationalEff Translational efficiency

Description

Uses RnaSeq and RiboSeq to get translational efficiency of every element in 'grl'. Translational efficiency is defined as:

(density of RPF within ORF) / (RNA expression of ORFs transcript)

Usage

```
translationalEff(
  grl,
  RNA,
  RFP,
  tx,
  with.fpkm = FALSE,
  pseudoCount = 0,
  librarySize = "full",
  weight.RFP = 1L,
  weight.RNA = 1L
)
```

Arguments

grl	a GRangesList object can be either transcripts, 5' utrs, cds', 3' utrs or ORFs as a special case (uORFs, potential new cds' etc). If regions are not spliced you can send a GRanges object.
RNA	RnaSeq reads as GAlignments, GRanges or GRangesList object
RFP	RiboSeq reads as GAlignments, GRanges or GRangesList object
tx	a GRangesList of the transcripts. If you used cage data, then the tss for the the leaders have changed, therefor the tx lengths have changed. To account for that call: 'translationalEff(grl, RNA, RFP, tx = extendLeaders(tx, cageFiveUTRs)) 'where cageFiveUTRs are the reannotated by CageSeq data leaders.
with.fpkm	logical, default: FALSE, if true return the fpkm values together with translational efficiency as a data.table
pseudoCount	an integer, by default is 0, set it to 1 if you want to avoid NA and inf values.
librarySize	either numeric value or character vector. Default ("full"), number of alignments in library (reads). If you just have a subset, you can give the value by library- Size = length(wholeLib), if you want lib size to be only number of reads over- lapping grl, do: librarySize = "overlapping" sum(countOverlaps(reads, grl) > 0), if reads[1] has 3 hits in grl, and reads[2] has 2 hits, librarySize will be 2, not 5. You can also get the inverse overlap, if you want lib size to be total number of overlaps, do: librarySize = "DESeq" This is standard fpkm way of DESeq2::fpkm(robust = FALSE) sum(countOverlaps(grl, reads)) if grl[1] has 3 reads and grl[2] has 2 reads, librarySize is 5, not 2.
weight.RFP	a vector (default: 1L). Can also be character name of column in RFP. As in translationalEff(weight = "score") for: GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times.
weight.RNA	Same as weightRFP but for RNA weights. (default: 1L)

Value

a numeric vector of fpkm ratios, if with.fpkm is TRUE, return a data.table with te and fpkm values (total 3 columns then)

References

doi: 10.1126/science.1168978

trimming.table

See Also

```
Other features: computeFeatures(), computeFeaturesCage(), countOverlapsW(), disengagementScore(), distToCds(), distToTSS(), entropy(), floss(), fpkm(), fpkm_calc(), fractionLength(), initiationScore(), insideOutsideORF(), isInFrame(), isOverlapping(), kozakSequenceScore(), orfScore(), rankOrder(), ribosomeReleaseScore(), ribosomeStallingScore(), startRegion(), startRegion(), startRegion(), subsetCoverage()
```

Examples

trimming.table Create trimming table

Description

From fastp runs in ORFik alignment process

Usage

trimming.table(trim_folder)

Arguments

trim_folder folder of trimmed files, only reads fastp .json files

Value

a data.table with 6 columns, raw_library (names of library), raw_reads (numeric, number of raw reads), trim_reads (numeric, number of trimmed reads), raw_mean_length (numeric, raw mean read length), trim_mean_length (numeric, trim mean read length).

Examples

```
# Location of fastp trimmed .json files
trimmed_folder <- "path/to/libraries/trim/"
#trimming.table(trimmed_folder)
```

trim_detection

Description

Only works if alignment was done using ORFik with STAR.

Usage

```
trim_detection(df, finals, alignment_folder = libFolder(df, "unique"))
```

Arguments

df	an ORFik experiment
finals	a data.table with current output from QCreport
alignment_folde	r
	character, default: libFolder(df, "unique"). All unique folders. trim_folders
	should then be relative as: file.path(alignment_folder, "", "trim/")

Value

a data.table of the update finals object with trim info

txNames

Get transcript names from orf names

Description

```
Using the ORFik definition of orf name, which is: example ENSEMBL:
tx name: ENST0909090909090
orf id: _1 (the first of on that tx)
orf_name: ENST09090909090_1
So therefor txNames("ENST09090909090_1") = ENST0909090909090
```

Usage

txNames(grl, ref = NULL, unique = FALSE)

Arguments

grl	a GRangesList grouped by ORF, GRanges object or IRanges object.
ref	a reference GRangesList. The object you want grl to subset by names. Add to make sure naming is valid.
unique	a boolean, if true unique the names, used if several orfs map to same transcript and you only want the unique groups

Details

The names must be extracted from a column called names, or the names of the grl object. If it is already tx names, it returns the input

NOTE! Do not use _123 etc in end of transcript names if it is not ORFs. Else you will get errors. Just _ will work, but if transcripts are called ENST_123124124000 etc, it will crash, so substitute "_" with "." gsub("_", ".", names)

Value

a character vector of transcript names, without _* naming

See Also

```
Other ORFHelpers: defineTrailer(), longestORFs(), mapToGRanges(), orfID(), startCodons(),
startSites(), stopCodons(), stopSites(), uniqueGroups(), uniqueOrder()
```

Examples

txNamesToGeneNames Convert transcript names to gene names

Description

Works for ensembl, UCSC and other standard annotations.

Usage

```
txNamesToGeneNames(txNames, txdb)
```

Arguments

txNames	character vector, the transcript names to convert. Can also be a named	object
	with tx names (like a GRangesList), will then extract names.	
txdb	the transcript database to use or gtf/gff path to it.	

Value

character vector of gene names

Examples

```
df <- ORFik.template.experiment()
txdb <- loadTxdb(df)
loadRegions(txdb, "cds") # using tx names
txNamesToGeneNames(cds, txdb)
# Identical to:
loadRegions(txdb, "cds", by = "gene")</pre>
```

txSeqsFromFa

Get transcript sequence from a GRangesList and a faFile or BSgenome

Description

For each GRanges object, find the sequence of it from faFile or BSgenome.

Usage

```
txSeqsFromFa(grl, faFile, is.sorted = FALSE, keep.names = TRUE)
```

Arguments

grl	a GRangesList object
faFile	FaFile, BSgenome, fasta/index file path or an ORFik experiment. This file is usually used to find the transcript sequences from some GRangesList.
is.sorted	a speedup, if you know the grl ranges are sorted
keep.names	a logical, default (TRUE), if FALSE: return as character vector without names.

Details

A wrapper around extractTranscriptSeqs that works for DNAStringSet and ORFik experiment input. For debug of errors do: which(!(unique(seqnamesPerGroup(grl, FALSE)) This happens usually when the grl contains chromsomes that the fasta file does not have. A normal error is that mitocondrial chromosome is called MT vs chrM even though they have same seqlevelsStyle. The above line will give you which chromosome it is missing.

Value

a DNAStringSet of the transcript sequences

See Also

Other ExtendGenomicRanges: asTX(), coveragePerTiling(), extendLeaders(), extendTrailers(), reduceKeepAttr(), tile1(), windowPerGroup()

uniqueGroups

Description

Sometimes GRangesList groups might be identical, for example ORFs from different isoforms can have identical ranges. Use this function to reduce these groups to unique elements in GRangesList gr1, without names and metacolumns.

Usage

uniqueGroups(grl)

Arguments grl

a GRangesList

Value

a GRangesList of unique orfs

See Also

```
Other ORFHelpers: defineTrailer(), longestORFs(), mapToGRanges(), orfID(), startCodons(),
startSites(), stopCodons(), stopSites(), txNames(), uniqueOrder()
```

Examples

gr1 <- GRanges("1", IRanges(1,10), "+")
gr2 <- GRanges("1", IRanges(20, 30), "+")
make a grl with duplicated ORFs (gr1 twice)
grl <- GRangesList(tx1_1 = gr1, tx2_1 = gr2, tx3_1 = gr1)
uniqueGroups(grl)</pre>

uniqueOrder

Get unique ordering for GRangesList groups

Description

This function can be used to calculate unique numerical identifiers for each of the GRangesList elements. Elements of GRangesList are unique when the GRanges inside are not duplicated, so ranges differences matter as well as sorting of the ranges.

Usage

uniqueOrder(grl)

Arguments

grl a GRangesList

unlistGrl

Value

an integer vector of indices of unique groups

See Also

uniqueGroups

```
Other ORFHelpers: defineTrailer(), longestORFs(), mapToGRanges(), orfID(), startCodons(),
startSites(), stopCodons(), stopSites(), txNames(), uniqueGroups()
```

Examples

```
gr1 <- GRanges("1", IRanges(1,10), "+")
gr2 <- GRanges("1", IRanges(20, 30), "+")
# make a gr1 with duplicated ORFs (gr1 twice)
gr1 <- GRangesList(tx1_1 = gr1, tx2_1 = gr2, tx3_1 = gr1)
uniqueOrder(gr1) # remember ordering
# example on unique ORFs
uniqueORFs <- uniqueGroups(gr1)
# now the orfs are unique, let's map back to original set:
reMappedGr1 <- uniqueORFs[uniqueOrder(gr1)]</pre>
```

unlistGrl

Safe unlist

Description

Same as [AnnotationDbi::unlist2()], keeps names correctly. Two differences is that if grl have no names, it will not make integer names, but keep them as null. Also if the GRangesList has names, and also the GRanges groups, then the GRanges group names will be kept.

Usage

unlistGrl(grl)

Arguments

grl a GRangesList

Value

a GRanges object

Examples

uORFSearchSpace Create search space to look for uORFs

Description

Given a GRangesList of 5' UTRs or transcripts, reassign the start sites using max peaks from CageSeq data (if CAGE is given). A max peak is defined as new TSS if it is within boundary of 5' leader range, specified by 'extension' in bp. A max peak must also be higher than minimum CageSeq peak cutoff specified in 'filterValue'. The new TSS will then be the positioned where the cage read (with highest read count in the interval). If you want to include uORFs going into the CDS, add this argument too.

Usage

```
uORFSearchSpace(
   fiveUTRs,
   cage = NULL,
   extension = 1000,
   filterValue = 1,
   restrictUpstreamToTx = FALSE,
   removeUnused = FALSE,
   cds = NULL
)
```

Arguments

fiveUTRs	(GRangesList) The 5' leaders or full transcript sequences				
cage	Either a filePath for the CageSeq file as .bed .bam or .wig, with possible com- pressions (".gzip", ".gz", ".bgz"), or already loaded CageSeq peak data as GRanges or GAlignment. NOTE: If it is a .bam file, it will add a score column by run- ning: convertToOneBasedRanges(cage, method = "5prime", addScoreColumn = TRUE) The score column is then number of replicates of read, if score column is something else, like read length, set the score column to NULL first.				
extension	The maximum number of basses upstream of the TSS to search for CageSeq peak.				
filterValue	The minimum number of reads on cage position, for it to be counted as possible new tss. (represented in score column in CageSeq data) If you already filtered, set it to 0.				
restrictUpstreamToTx					
	a logical (FALSE). If TRUE: restrict leaders to not extend closer than 5 bases from closest upstream leader, set this to TRUE.				
removeUnused	logical (FALSE), if False: (standard is to set them to original annotation), If TRUE: remove leaders that did not have any cage support.				
cds	(GRangesList) CDS of relative fiveUTRs, applicable only if you want to extend 5' leaders downstream of CDS's, to allow upstream ORFs that can overlap into CDS's.				

Value

a GRangesList of newly assigned TSS for fiveUTRs, using CageSeq data.

See Also

```
Other uorfs: addCdsOnLeaderEnds(), filterUORFs(), removeORFsWithSameStartAsCDS(), removeORFsWithSameSt removeORFsWithStartInsideCDS(), removeORFsWithinCDS()
```

Examples

updateTxdbRanks	Update exon	ranks of exon	data.frame	inside txdł	o object
-----------------	-------------	---------------	------------	-------------	----------

Description

Update exon ranks of exon data.frame inside txdb object

Usage

```
updateTxdbRanks(exons)
```

Arguments

exons a data.frame, call of as.list(txdb)\$splicings

Value

a data.frame, modified call of as.list(txdb)

updateTxdbStartSites Update start sites of leaders

Description

Update start sites of leaders

Usage

updateTxdbStartSites(txList, fiveUTRs, removeUnused)

Arguments

txList	a list, call of as.list(txdb)
fiveUTRs	a GRangesList of 5' leaders
removeUnused	logical (FALSE), remove leaders that did not have any cage support. (standard is to set them to original annotation)

Value

a list, modified call of as.list(txdb)

upstreamFromPerGroup Get rest of objects upstream (inclusive)

Description

Per group get the part upstream of position. upstreamFromPerGroup(tx, stopSites(fiveUTRs, asGR = TRUE)) will return the 5' utrs per transcript as GRangesList, usually used for interesting parts of the transcripts.

Usage

upstreamFromPerGroup(tx, upstreamFrom)

Arguments

tx	a GRangesList, usually of Transcripts to be changed
upstreamFrom	a vector of integers, for each group in tx, where is the new start point of first valid exon.

Details

If you don't want to include the points given in the region, use upstreamOfPerGroup

Value

a GRangesList of upstream part

See Also

```
Other GRanges: assignFirstExonsStartSite(), assignLastExonsStopSite(), downstreamFromPerGroup(),
downstreamOfPerGroup(), upstreamOfPerGroup()
```

upstreamOfPerGroup Get rest of objects upstream (exclusive)

Description

Per group get the part upstream of position upstreamOfPerGroup(tx, startSites(cds, asGR = TRUE)) will return the 5' utrs per transcript, usually used for interesting parts of the transcripts.

Usage

```
upstreamOfPerGroup(
  tx,
  upstreamOf,
  allowOutside = TRUE,
  is.circular = all(isCircular(tx) %in% TRUE)
)
```

Arguments

tx	a GRangesList, usually of Transcripts to be changed
upstreamOf	a vector of integers, for each group in tx, where is the the base after the new stop point of last valid exon.
allowOutside	a logical (T), can upstreamOf extend outside range of tx, can set boundary as a false hit, so beware.
is.circular	logical, default FALSE if not any is: all(isCircular(grl) Where grl is the ranges checked. If TRUE, allow ranges to extend below position 1 on chromosome. Since circular genomes can have negative coordinates.

Value

a GRangesList of upstream part

See Also

Other GRanges: assignFirstExonsStartSite(), assignLastExonsStopSite(), downstreamFromPerGroup(), downstreamOfPerGroup(), upstreamFromPerGroup()

validateExperiments Validate ORFik experiment

Description

Check for valid existing, non-empty and all unique. A good way to see if your experiment is valid.

Usage

```
validateExperiments(df, library.names = bamVarName(df))
```

Arguments

dfan ORFik experimentlibrary.namescharacter vector, names of libraries, default: name_decider(df, naming)

Value

NULL (Stops if failed)

See Also

```
Other ORFik_experiment: ORFik.template.experiment(), ORFik.template.experiment.zf(),
bamVarName(), create.experiment(), experiment-class, filepath(), libraryTypes(), organism, experiment-
outputLibs(), read.experiment(), save.experiment()
```

validGRL Helper Function to check valid GRangesList input

Description

Helper Function to check valid GRangesList input

Usage

validGRL(class, type = "grl", checkNULL = FALSE)

Arguments

class	as character vector the given class of supposed GRangesList object
type	a character vector, is it gtf, cds, 5', 3', for messages.
checkNULL	should NULL classes be checked and return indeces of these?

Value

either NULL or indices (checkNULL == TRUE)

See Also

```
Other validity: checkRFP(), checkRNA(), is.ORF(), is.gr_or_grl(), is.grl(), is.range(),
validSeqlevels()
```

validSeqlevels

Description

Keep only seqnames in reads that are in grl Useful to avoid seqname warnings in bioC

Usage

```
validSeqlevels(grl, reads)
```

Arguments

grl	a GRangesList or GRanges object
reads	a GRanges, GAlignment or GAlignmentPairs object

Value

a character vector of valid seqlevels

See Also

```
Other validity: checkRFP(), checkRNA(), is.ORF(), is.gr_or_grl(), is.grl(), is.range(),
validGRL()
```

widthPerGroup Get list of widths per granges group

Description

Get list of widths per granges group

Usage

```
widthPerGroup(grl, keep.names = TRUE)
```

Arguments

grl	a GRangesList
keep.names	a boolean, keep names or not, default: (TRUE)

Value

an integer vector (named/unnamed) of widths

windowCoveragePlot

Examples

windowCoveragePlot Get meta coverage plot of reads

Description

Spanning a region like a transcripts, plot how the reads distribute.

Usage

```
windowCoveragePlot(
   coverage,
   output = NULL,
   scoring = "zscore",
   colors = c("skyblue4", "orange"),
   title = "Coverage metaplot",
   type = "transcripts",
   scaleEqual = FALSE,
   setMinToZero = FALSE
)
```

Arguments

coverage	a data.table, e.g. output of scaledWindowCoverage
output	character string (NULL), if set, saves the plot as pdf or png to path given. If no format is given, is save as pdf.
scoring	character vector, default "zscore", either of zscore, transcriptNormalized, sum, mean, median, or NULL. Set NULL if already scored. see ?coverageScorings for info and more alternatives.
colors	character vector colors to use in plot, will fix automaticly, using binary splits with colors c('skyblue4', 'orange').
title	a character (metaplot) (what is the title of plot?)
type	a character (transcripts), what should legends say is the whole region? Transcripts, genes, non coding rnas etc.
scaleEqual	a logical (FALSE), should all fractions (rows), have same max value, for easy comparison of max values if needed.
setMinToZero	a logical (FALSE), should minimum y-value be 0 (TRUE). With FALSE minimum value is minimum score at any position. This parameter overrides scaleE- qual.

Details

If coverage has a column called feature, this can be used to subdivide the meta coverage into parts as (5' UTRs, cds, 3' UTRs) These are the columns in the plot. The fraction column divide sequence libraries. Like ribo-seq and rna-seq. These are the rows of the plot. If you return this function without assigning it and output is NULL, it will automaticly plot the figure in your session. If output is assigned, no plot will be shown in session. NULL is returned and object is saved to output.

Colors: Remember if you want to change anything like colors, just return the ggplot object, and reassign like: obj + scale_color_brewer() etc.

Value

a ggplot object of the coverage plot, NULL if output is set, then the plot will only be saved to location.

See Also

Other coveragePlot: coverageHeatMap(), pSitePlot(), savePlot()

Examples

windowPerGroup

Get window region of GRanges object

Description

Per GRanges input (gr) of single position inputs (center point), create a GRangesList window output of specified upstream, downstream region relative to some transcript "tx".

If downstream is 20, it means the window will start 20 downstream of gr start site (-20 in relative transcript coordinates.) If upstream is 20, it means the window will start 20 upstream of gr start site (+20 in relative transcript coordinates.) It will keep exon structure of tx, so if -20 is on next exon, it jumps to next exon.

Usage

```
windowPerGroup(gr, tx, upstream = 0L, downstream = 0L)
```

Arguments

gr	a GRanges/IRanges object (startSites or others, must be single point per in ge- nomic coordinates)
tx	a GRangesList of transcripts or (container region), names of tx must contain all gr names. The names of gr can also be the ORFik orf names. that is "tx-Name_id".
upstream	an integer, default (0), relative region to get upstream from.
downstream	an integer, default (0), relative region to get downstream from

Details

If a region has a part that goes out of bounds, E.g if you try to get window around the CDS start site, goes longer than the 5' leader start site, it will set start to the edge boundary (the TSS of the transcript in this case). If region has no hit in bound, a width 0 GRanges object is returned. This is useful for things like countOverlaps, since 0 hits will then always be returned for the correct object index. If you don't want the 0 width windows, use reduce() to remove 0-width windows.

Value

a GRanges, or GRangesList object if any group had > 1 exon.

See Also

```
Other ExtendGenomicRanges: asTX(), coveragePerTiling(), extendLeaders(), extendTrailers(),
reduceKeepAttr(), tile1(), txSeqsFromFa()
```

Examples

```
# find 2nd codon of an ORF on a spliced transcript
ORF <- GRanges("1", c(3), "+") # start site
names(ORF) <- "tx1_1" # ORF 1 on tx1
tx <- GRangesList(tx1 = GRanges("1", c(1,3,5,7,9,11,13), "+"))
windowPerGroup(ORF, tx, upstream = -3, downstream = 5) # <- 2nd codon
# With multiple extensions downstream
ORF <- rep(ORF, 2)
names(ORF)[2] <- "tx1_2"
windowPerGroup(ORF, tx, upstream = 0, downstream = c(2, 5))
# The last one gives 2nd and (1st and 2nd) codon as two groups</pre>
```

windowPerReadLength Find proportion of reads per position per read length in window

Description

This is defined as: Fraction of reads per read length, per position in whole window (defined by upstream and downstream) If tx is not NULL, it gives a metaWindow, centered around startSite of grl from upstream and downstream. If tx is NULL, it will use only downstream, since it has no reference on how to find upstream region. The exception is when upstream is negative, that is, going into downstream region of the object.

Usage

```
windowPerReadLength(
  grl,
  tx = NULL,
  reads,
  pShifted = TRUE,
 upstream = ifelse(!is.null(tx), ifelse(pShifted, 5, 20), min(ifelse(pShifted, 5, 20),
    0)),
  downstream = ifelse(pShifted, 20, 5),
  acceptedLengths = NULL,
  zeroPosition = upstream,
  scoring = "transcriptNormalized",
  weight = "score",
  drop.zero.dt = FALSE,
  append.zeroes = FALSE,
  windows = startRegion(grl, tx, TRUE, upstream, downstream)
)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs
tx	default NULL, a GRangesList of transcripts or (container region), names of tx must contain all grl names. The names of grl can also be the ORFik orf names. that is "txName_id"
reads	a GAlignments, GRanges, or precomputed coverage as covRleList (where names of covRle objects are readlengths) of RiboSeq, RnaSeq etc. Weigths for scoring is default the 'score' column in 'reads'. Can also be random access paths to bigWig or fstwig file. Do not use random access for more than a few genes, then loading the entire files is usually better.
pShifted	a logical (TRUE), are Ribo-seq reads p-shifted to size 1 width reads? If upstream and downstream is set, this argument is irrelevant. So set to FALSE if this is not p-shifted Ribo-seq.
upstream	<pre>an integer(5), relative region to get upstream from. Default: ifelse(!is.null(tx), ifelse(pShifted, 5, 20), min(ifelse(pShifted, 5, 20), 0))</pre>
downstream	an integer (20), relative region to get downstream from. Default: ifelse(pShifted, 20, 5)
acceptedLengths	
	an integer vector (NULL), the read lengths accepted. Default NULL, means all lengths accepted.
zeroPosition	an integer DEFAULT (upstream), what is the center point? Like leaders and cds combination, then 0 is the TIS and -1 is last base in leader. NOTE!: if windows have different widths, this will be ignored.
scoring	a character (transcriptNormalized), which meta coverage scoring ? one of (zs- core, transcriptNormalized, mean, median, sum, sumLength, fracPos), see ?cov- erageScorings for more info. Use to decide a scoring of hits per position for metacoverage etc. Set to NULL if you do not want meta coverage, but instead want per gene per position raw counts.
weight	(default: 'score'), if defined a character name of valid meta column in subject. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains
	a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.
---------------	---
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count posi- tions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)
append.zeroes	logical, default FALSE. If TRUE and drop.zero.dt is TRUE and all windows have equal length, it will add back 0 values after transformation. Sometimes needed for correct plots, if TRUE, will call abort if not all windows are equal length!
windows	the GRangesList windows to actually check, default: startRegion(grl, tx, TRUE, upstream, downstream).

Details

Careful when you create windows where not all transcripts are long enough, this function usually is used first with filterTranscripts to make sure they are of all of valid length!

Value

a data.table with 4 columns: position (in window), score, fraction (read length). If score is NULL, will also return genes (index of grl). A note is that if no coverage is found, it returns an empty data.table.

See Also

Other coverage: coverageScorings(), metaWindow(), regionPerReadLength(), scaledWindowPositions()

Examples

```
cds <- GRangesList(tx1 = GRanges("1", 100:129, "+"))
tx <- GRangesList(tx1 = GRanges("1", 80:129, "+"))
reads <- GRanges("1", seq(79,129, 3), "+")
windowPerReadLength(cds, tx, reads, scoring = "sum")
windowPerReadLength(cds, tx, reads, scoring = "transcriptNormalized")</pre>
```

windowPerTranscript Get a binned coverage window per transcript

Description

Per transcript (or other regions), bin them all to windowSize (default 100), and make a data.table, rows are positions, useful for plotting with ORFik and ggplot2.

Usage

```
windowPerTranscript(
   txdb,
   reads,
   splitIn3 = TRUE,
   windowSize = 100,
```

```
fraction = "1",
weight = "score",
drop.zero.dt = FALSE,
BPPARAM = bpparam()
)
```

Arguments

txdb	a TxDb object or a path to gtf/gff/db file.
reads	GRanges or GAlignment of reads
splitIn3	a logical(TRUE), split window in 3 (leader, cds, trailer)
windowSize	an integer (100), size of windows (columns). All genes with region smaller than this size are filter out for metacoverage.
fraction	a character (1), info on reads (which read length, or which type (RNA seq)) (row names)
weight	(default: 'score'), if defined a character name of valid meta column in subject. GRanges("chr1", 1, "+", score = 5), would mean score column tells that this alignment region was found 5 times. ORFik ofst, bedoc and .bedo files contains a score column like this. As do CAGEr CAGE files and many other package formats. You can also assign a score column manually.
drop.zero.dt	logical FALSE, if TRUE and as.data.table is TRUE, remove all 0 count posi- tions. This greatly speeds up and most importantly, greatly reduces memory usage. Will not change any plots, unless 0 positions are used in some sense. (mean, median, zscore coverage will only scale differently)
BPPARAM	how many cores/threads to use? default: bpparam()

Details

NOTE: All ranges with smaller width than windowSize, will of course be removed. What is the 100th position on a 1 width object ?

Value

a data.table with columns position, score

xAxisScaler Scale x axis correctly

Description

Works for all coverage plots, that need 0 position aligning

Usage

```
xAxisScaler(covPos)
```

Arguments

covPos a numeric v

a numeric vector of positions in coverage

yAxisScaler

Details

It basicly bins the x axis on floor(length of x axis / 20) or 1 if x < 20

Value

a numeric vector from the seq() function, aligned to 0.

yAxisScaler Scale y axis correctly

Description

Works for all coverage plots.

Usage

```
yAxisScaler(covPos, increments.y = "auto")
```

Arguments

covPos	a levels object from a factor of y axis
increments.y	increments of y axis, default "auto". Or a numeric value < max position & > min position.

Value

a character vector from the seq() function, aligned to 0.

Index

* CAGE assignTSSByCage, 17 reassignTSSbyCage, 263 reassignTxDbByCage, 264 * DifferentialExpression DEG.plot.static, 80 DEG_model, 82 DTEG.analysis, 101 DTEG.plot, 104 te.table, 333 te_rna.plot, 334 * ExtendGenomicRanges asTX. 19 coveragePerTiling, 66 extendLeaders, 122 extendTrailers, 124 reduceKeepAttr, 266 tile1, 335 txSeqsFromFa, 348 windowPerGroup, 358 * GRanges assignFirstExonsStartSite, 16 assignLastExonsStopSite, 17 downstreamFromPerGroup, 99 downstreamOfPerGroup, 101 upstreamFromPerGroup, 353 upstreamOfPerGroup, 354 * **ORFHelpers** defineTrailer, 78 longestORFs, 213 mapToGRanges, 219 orfID, 232 startCodons, 319 startSites, 323 stopCodons, 324 stopSites, 327 txNames, 346 uniqueGroups, 349 uniqueOrder, 349 * ORFik_experiment bamVarName, 20 create.experiment, 74 experiment-class, 110

filepath, 126 libraryTypes, 207 ORFik.template.experiment, 233 ORFik.template.experiment.zf, 233 organism, experiment-method, 238 outputLibs, 239 read.experiment, 257 save.experiment, 285 validateExperiments, 355 * QC report QCplots, 250 QCreport, 251 QCstats, 253 * STAR getGenomeAndAnnotation, 162 install.fastp, 192 STAR.align.folder, 306 STAR.align.single, 310 STAR.allsteps.multiQC, 314 STAR.index, 315 STAR.install, 317 STAR.multiQC, 318 STAR.remove.crashed.genome, 318 * codon codon_usage, 28 codon_usage_exp, 30 codon_usage_plot, 32 * countTable countTable, 60 countTable_regions, 61 * covRLE covRle, 71 covRle-class, 71 covRleFromGR, 72 covRleList, 73 covRleList-class, 73 * coveragePlot coverageHeatMap, 64 pSitePlot, 247 savePlot, 285 windowCoveragePlot, 357 * coverage coverageScorings, 68

metaWindow, 224 regionPerReadLength, 267 scaledWindowPositions, 286 windowPerReadLength, 359 * experiment plots transcriptWindow, 339 transcriptWindow1, 341 transcriptWindowPer, 342 * experiment_naming batchNames, 22 cellLineNames, 24 cellTypeNames, 25 conditionNames, 43 fractionNames, 157 inhibitorNames, 189 libNames, 207 mainNames, 214 repNames, 274 stageNames, 305 tissueNames. 336 * features computeFeatures, 39 computeFeaturesCage, 41 countOverlapsW, 59 disengagementScore, 92 distToCds, 93 distToTSS, 94 entropy, 106 floss, 151 fpkm, 153 fpkm_calc, 155 fractionLength, 156 initiationScore, 189 insideOutsideORF, 191 isInFrame, 196 isOverlapping, 197 kozakSequenceScore, 200 orfScore, 236 rankOrder, 256 ribosomeReleaseScore, 279 ribosomeStallingScore, 281 startRegion, 320 startRegionCoverage, 321 stopRegion, 326 subsetCoverage, 329 translationalEff, 343 * findORFs findMapORFs, 135 findORFs, 138 findORFsFasta, 140 findUORFs, 143 startDefinition, 320

stopDefinition, 325 * heatmaps coverageHeatMap, 64 heatMap_single, 184 heatMapL, 180 heatMapRegion, 182 * internal addCdsOnLeaderEnds, 10 addNewTSSOnLeaders, 11 alignmentFeatureStatistics, 11 allFeaturesHelper, 12 appendZeroes, 14 assignAnnotations, 15 assignFirstExonsStartSite, 16 assignLastExonsStopSite, 17 bamVarNamePicker, 22 batchNames, 22 bedToGR, 23 cellLineNames, 24 cellTypeNames, 25 changePointAnalysis, 25 checkRFP, 26 checkRNA, 27 codonSumsPerGroup, 27 collapse.by.scores, 33 conditionNames, 43 coverageGroupings, 64 defineIsoform, 77 download.ebi, 95 downstreamFromPerGroup, 99 downstreamN, 100 downstreamOfPerGroup, 101 exists.ftp.dir.fast, 109 exists.ftp.file.fast, 109 extendsTSSexons, 123 filterCage, 128 filterUORFs, 131 find_url_ebi_safe, 148 findFromPath, 134 findLibrariesInFolder, 134 findMaxPeaks, 137 findNewTSS, 137 findNGSPairs, 138 footprints.analysis, 153 fpkm_calc, 155 fractionNames, 157 get_genome_fasta, 168 get_genome_gtf, 170 get_noncoding_rna, 173 get_phix_genome, 175 getGAlignments, 160 getGAlignmentsPairs, 161

getGRanges, 165 getGtfPathFromTxdb, 166 getNGenesCoverage, 166 getWeights, 167 gSort. 179 hasHits, 179 heatMapL, 180 inhibitorNames, 189 is.gr_or_grl, 194 is.grl, 194 is.ORF, 195 is.range, 195 isPeriodic, 198 libNames, 207 mainNames, 214 makeExonRanks, 215 mapToGRanges, 219 matchColors, 220 matchNaming, 220 matchSeqStyle, 221 numCodons, 228 optimized_txdb_path, 230 optimizeReads, 231 orfID, 232 pasteDir, 241 percentage_to_ratio, 243 plotHelper, 243 prettyScoring, 246 pseudo.transform, 247 QC_count_tables, 254 QCplots, 250 readLengthTable, 260 remakeTxdbExonIds, 269 remove.file_ext, 270 removeMetaCols, 270 removeORFsWithinCDS, 271 removeORFsWithSameStartAsCDS, 271 removeORFsWithSameStopAsCDS, 272 removeORFsWithStartInsideCDS, 272 removeTxdbExons, 273 removeTxdbTranscripts, 273 rename.SRA.files, 274 repNames, 274 restrictTSSByUpstreamLeader, 276 revElementsF, 276 reverseMinusStrandPerGroup, 277 savePlot, 285 splitIn3Tx, 304 stageNames, 305 subsetCoverage, 329 tissueNames, 336 transcriptWindow1, 341

transcriptWindowPer, 342 trim_detection, 346 updateTxdbRanks, 352 updateTxdbStartSites, 353 upstreamFromPerGroup, 353 upstreamOfPerGroup, 354 validateExperiments, 355 validGRL, 355 validSeqlevels, 356 windowPerTranscript, 361 xAxisScaler, 362 yAxisScaler, 363 * lib_converters convert_bam_to_ofst, 51 convert_to_bigWig, 52 convert_to_covRle, 53 convert_to_covRleList, 54 convertLibs, 47 * pshifting changePointAnalysis, 25 detectRibosomeShifts, 86 shiftFootprints, 292 shiftFootprintsByExperiment, 293 shiftPlots, 296 shifts_load, 298 shifts_save, 299 * sra browseSRA, 23 download.ebi, 95 download.SRA,96 download.SRA.metadata, 98 get_bioproject_candidates, 167 install.sratoolkit, 193 rename.SRA.files, 274 * uorfs addCdsOnLeaderEnds, 10 filterUORFs, 131 removeORFsWithinCDS, 271 removeORFsWithSameStartAsCDS, 271 removeORFsWithSameStopAsCDS, 272 removeORFsWithStartInsideCDS, 272 uORFSearchSpace, 351 * utils bedToGR, 23 convertToOneBasedRanges, 49 export.bed12,113 export.bigWig, 115 export.fstwig, 116 export.wiggle, 121 fimport, 132 findFa, 133 fread.bed, 157

optimizeReads, 231 readBam. 258 readBigWig, 259 readWig, 262 * validity checkRFP, 26 checkRNA, 27 is.gr_or_grl, 194 is.grl, 194 is.ORF, 195 is.range, 195 validGRL, 355 validSeqlevels, 356 addCdsOnLeaderEnds, 10, 131, 271, 272, 352 addNewTSSOnLeaders, 11 alignmentFeatureStatistics, 11 allFeaturesHelper, 12 appendZeroes, 14 artificial.orfs, 14 assignAnnotations, 15 assignFirstExonsStartSite, 16, 17, 100, 101, 354 assignLastExonsStopSite, 16, 17, 100, 101, 354 assignTSSByCage, 17, 264, 266 asTX, 19, 67, 122, 124, 267, 335, 348, 359 bamVarName, 20, 76, 111, 127, 207, 233, 234, 238, 241, 258, 285, 355 bamVarNamePicker, 22 batchNames, 22, 24, 25, 44, 157, 189, 207, 214, 274, 305, 336 bedToGR, 23, 50, 113, 116, 117, 121, 133, 158, 231, 259, 260, 263 browseSRA, 23, 96, 97, 99, 168, 193, 274 cellLineNames, 23, 24, 25, 44, 157, 189, 207, 214, 274, 305, 336 cellTypeNames, 23, 24, 25, 44, 157, 189, 207, 214, 274, 305, 336 changePointAnalysis, 25, 88, 292, 295, 297-299 checkRFP, 26, 27, 194, 195, 355, 356 checkRNA, 26, 27, 194, 195, 355, 356 codon_usage, 28, 31, 32 codon_usage_exp, 29, 30, 32 codon_usage_plot, 29, 31, 32 codonSumsPerGroup, 27 collapse.by.scores, 33 collapse.fastq, 33 collapseDuplicatedReads, 34

collapseDuplicatedReads,data.table-method, 35 collapseDuplicatedReads,GAlignmentPairs-method, 36 collapseDuplicatedReads,GAlignments-method, 36 collapseDuplicatedReads,GRanges-method, 37 combn.pairs, 38 computeFeatures, 39, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 computeFeaturesCage, *41*, *41*, *59*, *93*, *94*, 107, 152, 154–156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 conditionNames, 23-25, 43, 157, 189, 207, 214, 274, 305, 336 config, 44 config.exper, 45 config.save, 45 config_file, 46 convert_bam_to_ofst, 49, 51, 52, 54, 55, 303 convert_to_bigWig, 49, 51, 52, 54, 55, 303 convert_to_covRle, 49, 51, 52, 53, 55, 303 convert_to_covRleList, 49, 51, 52, 54, 54, 294.303 convert_to_fstWig, 55 convertLibs, 47, 51, 52, 54, 55 convertToOneBasedRanges, 23, 48, 49, 113, 116, 117, 121, 133, 158, 231, 259, 260, 263, 302 cor_plot, 57 cor_table, 58 correlation.plots, 56 countOverlapsW, 41, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 countTable, 60, 62, 234, 251 countTable_regions, 61, 61 coverage_to_dt, 70 coverageByTranscript, 63 coverageByTranscriptC, 63 coverageByTranscriptW, 63 coverageGroupings, 64 coverageHeatMap, 64, 181, 183, 185, 248, 286, 358 coveragePerTiling, 20, 66, 122, 124, 267, 335, 348, 359 coverageScorings, 68, 225, 268, 287, 361

covRle, 27, 67, 71, 71, 72, 73, 286, 300 covRle-class, 71 covRleFromGR, 71, 72, 73 covRleList, 71–73, 73, 184, 268, 300, 360 covRleList-class, 73 create.experiment, 21, 74, 111, 127, 207, 233, 234, 238, 241, 257, 258, 285, 355

data.frame, 23 defineIsoform, 77 defineTrailer, 78, 214, 219, 232, 319, 324, 327, 347, 349, 350 DEG.analysis, 79, 80, 81 DEG.plot.static, 80, 80, 83, 104, 105, 333, 334 DEG_model, 80, 81, 82, 104, 105, 333, 334 DEG_model_results, 83 DEG_model_simple, 84 design, experiment-method, 85 detect_ribo_orfs, 89 detectRibosomeShifts, 26, 86, 236, 292, 293, 295, 297-299 disengagementScore, 41, 43, 59, 92, 94, 107, 152, 154-156, 190-192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 distToCds, 41, 43, 59, 93, 93, 94, 107, 152, 154–156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 distToTSS, 41, 43, 59, 93, 94, 94, 107, 152, 154-156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 DNAStringSet, 348 download.ebi, 24, 95, 97, 99, 168, 193, 274 download.SRA, 24, 96, 96, 99, 168, 193, 274 download.SRA.metadata, 24, 96, 97, 98, 168, 193, 274 downstreamFromPerGroup, 16, 17, 99, 101, 354 downstreamN, 100 downstreamOfPerGroup, 16, 17, 100, 101, 354 DTEG.analysis, 81, 83, 101, 104, 105, 333, 334 DTEG.plot, 80, 81, 83, 104, 104, 333, 334 entropy, 41, 43, 59, 93, 94, 106, 152, 154-156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345

envExp, 12, 48, 107, 217, 240, 250, 255, 261, 302.340 envExp, experiment-method, 107 envExp<-, 108 envExp<-, experiment-method, 108 exists.ftp.dir.fast, 109 exists.ftp.file.fast, 109 experiment, 12, 13, 20-22, 30, 40, 42, 44, 48, 51-56, 60, 62, 74, 79, 82, 84, 85, 90, 102, 107, 108, 112, 127, 133, 134, 145, 159, 180, 182, 200, 202, 206, 207, 216, 222, 226, 227, 232–235, 238, 239, 242, 244, 249, 250, 252-254, 257, 258, 261, 269, 275, 279, 283–285, 289, 291, 294, 296–298, 301, 302, 323, 331–333, 339-341, 343, 346, 348, 355 experiment (experiment-class), 110 experiment-class, 110 experiment.colors, 112, 244, 339, 341 export.bed12, 23, 50, 113, 116, 117, 121, 133, 158, 231, 259, 260, 263 export.bedo, 48, 114, 303 export.bedoc, 48, 114, 303 export.bigWig, 23, 50, 113, 115, 117, 121, 133, 158, 231, 259, 260, 263 export.fstwig, 23, 50, 113, 116, 116, 121, 133, 158, 231, 259, 260, 263 export.ofst, 48, 117, 303 export.ofst,GAlignmentPairs-method, 118 export.ofst, GAlignments-method, 119 export.ofst, GRanges-method, 120 export.wiggle, 23, 48, 50, 113, 116, 117, 121, 133, 158, 231, 259, 260, 263, 294,303 extendLeaders, 20, 67, 122, 124, 267, 335, 348,359 extendsTSSexons, 123 extendTrailers, 20, 67, 122, 124, 267, 335, 348, 359 extract_run_id, 125 extractTranscriptSeqs, 348 f. 125

filterUORFs, 10, 131, 271, 272, 352 fimport, 23, 50, 113, 116, 117, 121, 132, 133, 158, 231, 259, 260, 263 find_url_ebi, 147 find_url_ebi_safe, 148 findFa, 23, 50, 113, 116, 117, 121, 133, 133, 158, 231, 259, 260, 263 findFromPath, 134 findLibrariesInFolder, 134 findMapORFs, 135, 138, 139, 141, 144, 146, 320, 325 findMaxPeaks, 137 findNewTSS, 137 findNGSPairs. 138 findORFs, 136, 138, 141, 144, 146, 320, 325 findORFsFasta, 136, 139, 140, 144, 146, 320, 325 findPeaksPerGene, 141 findUORFs, 136, 139, 141, 143, 320, 325 findUORFs_exp, 145 firstEndPerGroup, 148 firstExonPerGroup, 149 firstStartPerGroup, 149 fix_malformed_gff, 150 flankPerGroup, 151 floss, 41, 43, 59, 93, 94, 107, 151, 154-156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 footprints.analysis, 153 fpkm, 41, 43, 59, 93, 94, 107, 152, 153, 155, 156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 fpkm_calc, 41, 43, 59, 93, 94, 107, 152, 154, 155, 156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 fractionLength, 41, 43, 59, 93, 94, 107, 152, 154, 155, 156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 fractionNames, 23-25, 44, 157, 189, 207, 214, 274, 305, 336 fread.bed, 23, 50, 113, 116, 117, 121, 133, 157, 231, 259, 260, 263 GAlignmentPairs, 132, 187, 240, 259 GAlignments, 13, 27, 40, 42, 63, 67, 87, 106, 132, 151, 154, 183, 184, 189, 236, 240, 259, 268, 280, 282, 286, 292, 344, 360 GappedReads, 132, 240, 259 gcContent, 158

geneToSymbol, 159 get_bioproject_candidates, 24, 96, 97, 99, 167, 193, 274 get_genome_fasta, 168 get_genome_gtf, 170 get_noncoding_rna, 173 get_phix_genome, 175 get_silva_rRNA, 176 getGAlignments, 160 getGAlignmentsPairs, 161 getGenomeAndAnnotation, 162, 193, 309, 313, 315-319 getGRanges, 165 getGtfPathFromTxdb, 166 getNGenesCoverage, 166 getWeights, 40, 167, 190, 237 GRanges, 13, 23, 27, 40, 42, 63, 67, 106, 132, 151, 154, 158, 183, 184, 236, 260, 262, 268, 280, 282, 286, 292, 344, 349,360 GRangesList, 13, 16, 17, 19, 27, 40, 42, 63, 67, 92–94, 100, 101, 106, 122, 124, 135, 148–152, 154, 156, 179, 180, 184, 189, 191, 200, 202, 203, 214–216, 219, 220, 228, 231, 232, 236, 256, 266, 268, 277, 280–283, 286, 291, 303, 304, 319, 321–324, 326-329, 335, 339, 343, 344, 346, 348, 349, 353, 354, 356, 359, 360 groupGRangesBy, 177 groupings, 178 gSort, 179 hasHits, 179 heatMap_single, 66, 181, 183, 184 heatMapL, 66, 180, 183, 185 heatMapRegion, 66, 181, 182, 185 import.bed, 157 import.bedo, 185 import.bedoc, 186 import.fstwig, 186 import.ofst, 187 importGtfFromTxdb, 188 inhibitorNames, 23-25, 44, 157, 189, 207, 214, 274, 305, 336 initiationScore, 41, 43, 59, 93, 94, 107, 152, 154–156, 189, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 insideOutsideORF, 41, 43, 59, 93, 94, 107, 152, 154–156, 190, 191, 196, 197,

201, 237, 257, 280, 281, 321, 322, 326.330.345 install.fastp, 165, 170, 172, 174, 176, 192, 309, 313, 315-319 install.sratoolkit, 24, 96, 97, 99, 168, 193, 274 IRanges, 138 IRangesList, 138 is.gr_or_grl, 26, 27, 194, 194, 195, 355, 356 is.grl, 26, 27, 194, 194, 195, 355, 356 is.ORF, 26, 27, 194, 195, 195, 355, 356 is.range, 26, 27, 194, 195, 195, 355, 356 isInFrame, 41, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 isOverlapping, 41, 43, 59, 93, 94, 107, 152, 154–156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 isPeriodic, 88, 198 kozak_IR_ranking, 201 kozakHeatmap, 199 kozakSequenceScore, 41, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 200, 237, 257, 280, 281, 321, 322, 326, 330, 345 lastExonEndPerGroup, 202 lastExonPerGroup, 203 lastExonStartPerGroup, 203 length, covRle-method, 204 length.covRleList-method, 204 lengths, covRle-method, 205 lengths, covRleList-method, 205 libFolder, 206 libFolder, experiment-method, 206 libNames, 23-25, 44, 157, 189, 207, 214, 274, 305, 336 libraryTypes, 21, 76, 111, 127, 207, 233, 234, 238, 241, 258, 285, 355 list.experiments, 75, 208 list.genomes, 209 loadRegion, 210 loadRegions, 211 loadTranscriptType, 212 loadTxdb, 213 longestORFs, 78, 90, 136, 139, 140, 143, 145, 213, 219, 232, 319, 324, 327, 347, 349, 350 mainNames, 23-25, 44, 157, 189, 207, 214, 274, 305, 336

makeExonRanks, 215 makeORFNames, 215 makeSummarizedExperimentFromBam, 60, 216 makeTxdbFromGenome, 159, 160, 218 mapToGRanges, 78, 214, 219, 232, 319, 324, 327, 347, 349, 350 matchColors, 220 matchNaming, 220 matchSeqStyle, 221 mergeFastq, 221 mergeLibs, 222 metadata.autnaming, 223 metaWindow, 69, 224, 268, 287, 361 model.matrix, experiment-method, 225 name, 226 name, experiment-method, 227 nrow, experiment-method, 227 numCodons, 228 numExonsPerGroup, 228 ofst_merge, 229 optimized_txdb_path, 230 optimizedTranscriptLengths, 229 optimizeReads, 23, 50, 113, 116, 117, 121, 133, 158, 231, 259, 260, 263 orfFrameDistributions, 231 orfID, 78, 214, 219, 232, 319, 324, 327, 347, 349, 350 ORFik (ORFik-package), 9 ORFik-package, 9 ORFik.template.experiment, 21, 76, 111, 127, 207, 233, 234, 238, 241, 258, 285.355 ORFik.template.experiment.zf, 21, 76, 111, 127, 207, 233, 233, 238, 241, 258, 285, 355 ORFikQC, 60, 234 orfScore, 41, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 201, 236, 257, 280, 281, 321, 322, 326, 330, 345 organism, experiment-method, 238 outputLibs, 21, 76, 111, 127, 207, 233, 234, 238, 239, 258, 285, 355 pasteDir, 241 pcaExperiment, 80, 83, 85, 103, 242 percentage_to_ratio, 243 plotHelper, 243 pmapFromTranscriptF, 244 pmapToTranscriptF, 245

prettyScoring, 246

pseudo.transform, 247

pSitePlot, 66, 247, 286, 358

QC_count_tables, 254 QCfolder, 249 QCfolder, experiment-method, 249 QCplots, 235, 250, 252, 253 OCreport, 250, 251, 251, 253 QCstats, 234, 235, 251, 252, 253 QCstats.plot, 253 r, 255 r, covRle-method, 256 rankOrder, 41, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 201, 237, 256, 280, 281, 321, 322, 326, 330.345 read.experiment, 21, 76, 111, 127, 207, 233, 234, 238, 241, 257, 285, 355 readBam, 23, 50, 113, 116, 117, 121, 133, 158, 231, 258, 260, 263 readBigWig, 23, 50, 113, 116, 117, 121, 133, 158, 231, 259, 259, 263 readGAlignments, 258 readLengthTable, 260 readWidths, 261 readWig, 23, 50, 113, 116, 117, 121, 133, 158, 231, 259, 260, 262 reassignTSSbyCage, 19, 263, 266 reassignTxDbByCage, 19, 264, 264 reduce, 267 reduceKeepAttr, 20, 67, 122, 124, 266, 335, 348.359 regionPerReadLength, 69, 225, 267, 287, 361 remakeTxdbExonIds, 269 remove.experiments, 269 remove.file_ext, 270 removeMetaCols, 270 removeORFsWithinCDS, 10, 131, 271, 271, 272, 352 removeORFsWithSameStartAsCDS, 10, 131, 271, 271, 272, 352 removeORFsWithSameStopAsCDS, 10, 131, 271, 272, 272, 352 removeORFsWithStartInsideCDS, 10, 131, 271, 272, 272, 352 removeTxdbExons, 273 removeTxdbTranscripts, 273 rename.SRA.files, 24, 96, 97, 99, 168, 193, 274

repNames, 23-25, 44, 157, 189, 207, 214, 274, 305.336 resFolder, 275 resFolder, experiment-method, 275 restrictTSSByUpstreamLeader, 276 revElementsF, 276 reverse MinusStrandPerGroup, 277ribo_fft, 282 ribo_fft_plot, 282 riboORFs, 277 riboORFsFolder, 278 RiboOC.plot, 278 ribosomeReleaseScore, 41, 43, 59, 93, 94, 107, 152, 154–156, 190, 192, 196, 197, 201, 237, 257, 279, 281, 321, 322, 326, 330, 345 ribosomeStallingScore, 41, 43, 59, 93, 94, 107, 152, 154–156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 rnaNormalize, 283 runIDs. 284 runIDs, experiment-method, 284 save.experiment, 21, 76, 111, 127, 207, 233, 234, 238, 241, 258, 285, 355 savePlot, 66, 248, 285, 358 scaledWindowPositions, 69, 225, 268, 286, 361 scanBam, 132, 240, 259 ScanBamParam, 132, 240, 259 scoreSummarizedExperiment, 287 Seqinfo, 132, 157, 213, 221, 240, 259, 260, 262 seginfo.covRle-method, 288 seqinfo,covRleList-method, 289 seqinfo, experiment-method, 289 seqlevels, covRle-method, 290 seqlevels, covRleList-method, 290 seqlevels, experiment-method, 291 seqlevelsStyle, 132, 157, 213, 221, 240, 259, 260, 262 segnamesPerGroup, 291 shiftFootprints, 26, 88, 292, 295, 297-299 shiftFootprintsByExperiment, 26, 88, 292, 293.297-299 shiftPlots, 26, 88, 292, 295, 296, 297-299 shifts.load, 295, 297 shifts_load, 26, 88, 292, 295, 297, 298, 299 shifts_save, 26, 88, 292, 295, 297, 298, 299 show, covRle-method, 300 show, covRleList-method, 300 show, experiment-method, 301

simpleLibs, 301 sort.GenomicRanges, 303 sortPerGroup, 122, 124, 303 splitIn3Tx, 304 stageNames, 23-25, 44, 157, 189, 207, 214, 274, 305, 336 STAR.align.folder, 165, 170, 172, 174, 176, 193, 306, 313, 315-319 STAR.align.single, 165, 170, 172, 174, 176, 193, 309, 310, 315-319 STAR.allsteps.multiQC, 165, 170, 172, 174, 176, 193, 309, 313, 314, 316–319 STAR. index, 165, 170, 172, 174, 176, 193, 309, 313, 315, 315, 317-319 STAR. install, 165, 170, 172, 174, 176, 193, 309, 313, 315, 316, 317, 318, 319 STAR.multiQC, 165, 170, 172, 174, 176, 193, 309, 313, 315-317, 318, 319 STAR. remove. crashed.genome, 165, 170, 172, 174, 176, 193, 309, 313, 315-318, 318 startCodons, 78, 214, 219, 232, 319, 320, 324, 327, 347, 349, 350 startDefinition, 91, 135, 136, 139-141, 143-146, 320, 325 startRegion, 41, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 320, 322, 326, 330.345 startRegionCoverage, 41, 43, 59, 93, 94, 107, 152, 154–156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 321, 326, 330, 345 startRegionString, 323 startSites, 78, 214, 219, 232, 319, 323, 324, 327, 347, 349, 350 stopCodons, 78, 214, 219, 232, 319, 324, 324, 326, 327, 347, 349, 350 stopDefinition, 91, 135, 136, 139-141, 143–146, 320, 325 stopRegion, 41, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 345 stopSites, 78, 214, 219, 232, 319, 324, 327, 347, 349, 350 strandBool, 327 strandMode, covRle-method, 328 strandMode,covRleList-method, 328 strandPerGroup, 329 subsetCoverage, 41, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 201,

237, 257, 280, 281, 321, 322, 326, 329.345 subsetToFrame, 330 SummarizedExperiment, 102, 110, 217, 234, 251 symbols, 331 symbols, experiment-method, 331 te.plot, 332 te.table, 80, 81, 83, 104, 105, 333, 334 te_rna.plot, 80, 81, 83, 104, 105, 333, 334 tile1, 20, 67, 122, 124, 267, 335, 348, 359 tissueNames, 23-25, 44, 157, 189, 207, 214, 274, 305, 336 TOP.Motif.ecdf, 336 topMotif, 338 transcriptLengths, 229 transcriptWindow, 339, 342, 343 transcriptWindow1, 340, 341, 343 transcriptWindowPer, 340, 342, 342 translationalEff, 41, 43, 59, 93, 94, 107, 152, 154-156, 190, 192, 196, 197, 201, 237, 257, 280, 281, 321, 322, 326, 330, 343 trim_detection, 346 trimming.table, 345 TxDb, 92, 191 txNames, 78, 214, 219, 232, 319, 324, 327, 346, 349, 350 txNamesToGeneNames, 347 txSeqsFromFa, 20, 67, 122, 124, 267, 335, 348.359 uniqueGroups, 78, 214, 219, 232, 319, 324, 327, 347, 349, 350 uniqueOrder, 78, 214, 219, 232, 319, 324, 327, 347, 349, 349 unlistGrl, 350 uORFSearchSpace, 10, 131, 271, 272, 351 updateTxdbRanks, 352 updateTxdbStartSites, 353 upstreamFromPerGroup, 16, 17, 100, 101, 353.354 upstreamOfPerGroup, 16, 17, 100, 101, 353, 354.354 validateExperiments, 21, 76, 111, 127, 207, 233, 234, 238, 241, 258, 285, 355 validGRL, 26, 27, 194, 195, 355, 356 validSeqlevels, 26, 27, 194, 195, 355, 356 widthPerGroup, 356

windowCoveragePlot, 66, 248, 286, 357

windowPerGroup, 20, 67, 122, 124, 267, 335, 348, 358windowPerReadLength, 69, 225, 268, 287, 359windowPerTranscript, 361

xAxisScaler, 362

yAxisScaler, 363