

Package ‘RepViz’

May 21, 2024

Type Package

Title Replicate oriented Visualization of a genomic region

Version 1.21.0

Author Thomas Faux, Kalle Rytönen, Asta Laiho, Laura L. Elo

Maintainer Thomas Faux, Asta Laiho <faux.thomas1@gmail.com> <asta.laiho@utu.fi>

Description RepViz enables the view of a genomic region in a simple and efficient way. RepViz allows simultaneous viewing of both intra- and intergroup variation in sequencing counts of the studied conditions, as well as their comparison to the output features (e.g. identified peaks) from user selected data analysis methods. The RepViz tool is primarily designed for chromatin data such as ChIP-seq and ATAC-seq, but can also be used with other sequencing data such as RNA-seq, or combinations of different types of genomic data.

License GPL-3

Encoding UTF-8

RoxygenNote 6.1.1

VignetteBuilder knitr

Depends R (>= 3.5.1), GenomicRanges (>= 1.30.0), Rsamtools (>= 1.34.1), IRanges (>= 2.14.0), biomaRt (>= 2.36.0), S4Vectors (>= 0.18.0), graphics, grDevices, utils

Suggests rmarkdown, knitr, testthat

biocViews WorkflowStep, Visualization, Sequencing, ChIPSeq, ATACSeq, Software, Coverage, GenomicVariation

git_url <https://git.bioconductor.org/packages/RepViz>

git_branch devel

git_last_commit 325bf8e

git_last_commit_date 2024-04-30

Repository Bioconductor 3.20

Date/Publication 2024-05-20

Contents

| | |
|------------------|----------|
| RepViz | 2 |
| Index | 4 |

| | |
|--------|------------------------------|
| RepViz | <i>Plot a genomic region</i> |
|--------|------------------------------|

Description

Plot a genomic region

Usage

```
RepViz(region, genome = c("hg19", "hg38", "mm10"), BAM = NULL,
        BED = NULL, avgTrack = TRUE, geneTrack = TRUE, max = NULL,
        verbose = TRUE, cex = 1)
```

Arguments

| | |
|-----------|---|
| region | a GRange object with chr, start, end |
| genome | a character vector 'hg19','hg38' or 'mm10' |
| BAM | a path to the BAM related csv input file |
| BED | a path to the BED related csv input file |
| avgTrack | a logical indicating if the average track should be included or not |
| geneTrack | a logical indicating if the gene track should be included or not |
| max | a numerical vector containing the yaxis maximum value of each BAM track |
| verbose | a logical indicating whether the progress of the plotting is shown |
| cex | number indicating the amount by which plotting text and symbols should be scaled relative to the default. |
| col | vector of character user can set color of the different BED tracks. |

Value

displays the region specified by the user

Examples

```
region <- GRanges('chr12:110938000-110940000')
setwd(tempdir())
#Copying the files to the user working directory
file.copy(from = list.files(system.file('extdata', package = 'RepViz'), full.names = TRUE),
          to = tempdir())
#Generate the visualization of the given region
RepViz::RepViz(region = region,
               genome = 'hg19',
```

```
BAM = 'BAM_input.csv',  
BED = 'BED_input.csv',  
avgTrack = TRUE,  
geneTrack = TRUE)
```

Index

RepViz, [2](#)