

Package ‘SynMut’

September 23, 2024

Type Package

Title SynMut: Designing Synonymously Mutated Sequences with Different Genomic Signatures

Version 1.21.0

Description There are increasing demands on designing virus mutants with specific dinucleotide or codon composition.
This tool can take both dinucleotide preference and/or codon usage bias into account while designing mutants.
It is a powerful tool for in silico designs of DNA sequence mutants.

License GPL-2

Encoding UTF-8

Suggests BiocManager, knitr, rmarkdown, testthat, devtools, prettydoc, glue

VignetteBuilder knitr

Imports seqinr, methods, Biostrings, stringr, BiocGenerics

RoxygenNote 7.1.0

Collate 'regioned_dna_Class.R' 'codon_mimic.R' 'input_seq.R'
'codon_random.R' 'codon_to.R' 'dinu_to.R' 'distance_analysis.R'
'region_related.R' 'seq_random.R' 'zzz.R'

biocViews SequenceMatching, ExperimentalDesign, Preprocessing

BugReports <https://github.com/Koohoko/SynMut/issues>

URL <https://github.com/Koohoko/SynMut>

git_url <https://git.bioconductor.org/packages/SynMut>

git_branch devel

git_last_commit dc19ea3

git_last_commit_date 2024-04-30

Repository Bioconductor 3.20

Date/Publication 2024-09-22

Author Haogao Gu [aut, cre],
Leo L.M. Poon [led]

Maintainer Haogao Gu <hggu@connect.hku.hk>

Contents

| | |
|------------------------------|-----------|
| codon_dist | 2 |
| codon_mimic | 3 |
| codon_random | 4 |
| codon_to | 5 |
| dinu_dist | 6 |
| dinu_to | 7 |
| get_cu | 8 |
| get_dna | 8 |
| get_du | 9 |
| get_freq | 10 |
| get_nu | 11 |
| get_region | 11 |
| get_rscu | 12 |
| input_seq | 13 |
| regioned_dna-class | 14 |
| seq_random | 14 |
| Index | 16 |

| | |
|------------|---|
| codon_dist | <i>Calculating the codon usage difference between sequences</i> |
|------------|---|

Description

We use a least squares approach to estimate the codon usage difference between DNA sequences.

Usage

```
codon_dist(seq, ref)

## S4 method for signature 'ANY'
codon_dist(seq, ref)
```

Arguments

- seq the input DNA sequece of DNASTringSet or regioned_dna class.
- ref the reference DNA sequece of DNASTringSet or regioned_dna class.

Details

idea inspired by "Daniel Macedo de Melo Jorge, Ryan E. Mills, Adam S. Lauring, CodonShuffle: a tool for generating and analyzing synonymously mutated sequences, Virus Evolution, Volume 1, Issue 1, March 2015, vev012, <https://doi.org/10.1093/ve/vev012>"

Value

vector

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_cu(rgd.seq)

mut.seq <- codon_random(rgd.seq)
codon_dist(mut.seq, rgd.seq)
mut.seq2 <- codon_random(rgd.seq, keep = TRUE)
codon_dist(mut.seq2, rgd.seq)
```

| | |
|-------------|--|
| codon_mimic | <i>Mimic a target codon usage bias</i> |
|-------------|--|

Description

Mutating the current DNA sequences in the `regioned_dna` object to mimic a target codon usage pattern.

Usage

```
codon_mimic(object, alt, numcode = 1, ...)

## S4 method for signature 'regioned_dna,vector'
codon_mimic(object, alt, numcode)

## S4 method for signature 'regioned_dna,DNAStringSet'
codon_mimic(object, alt, numcode)

## S4 method for signature 'DNAStringSet,DNAStringSet'
codon_mimic(object, alt, numcode)
```

Arguments

| | |
|----------------------|--|
| <code>object</code> | <code>regioned_dna</code> object |
| <code>alt</code> | target codon usage vector or <code>DNAStringSet</code> object representing target codon usage |
| <code>numcode</code> | The ncbi genetic code number for translation. Default value: 1. Details please refer to <code>?seqinr::translate</code> (" https://rdr.io/cran/seqinr/man/translate.html "). |
| <code>...</code> | ... |

Details

The ideas for `codon_mimic` is similar to `codon_to`: first extract the mutable regions and then do the mutation. However the codons in the fixed (not mutable) regions will also alter the final codon usage, thus we have to adjust for the fixed codons when introducing synonymous codons. The ideal design for `codon_mimic` is not unique as the swap between positions of the synonymous codons will not change the codon usage bias.

Details please refer to: <https://koohoko.github.io/SynMut/algorithm.html>

Value

regioned_dna

See Also

[input_seq](#), [codon_to](#), [codon_random](#), [dinu_to](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
target <- get_cu(rgd.seq)[2,]
new <- codon_mimic(rgd.seq, alt = target)
get_cu(new) - get_cu(rgd.seq)

target <- Biostrings::DNAStringSet("TTGAAAA-CTC-N--AAG")
new <- codon_mimic(rgd.seq, alt = target)
get_cu(new) - get_cu(rgd.seq)
get_freq(new) - get_freq(rgd.seq)
get_rscu(new) - get_rscu(rgd.seq)
```

codon_random

Generate random synonymous mutations

Description

Generating random synonymous mutations (in user-defined region), with optionally keeping/not keeping the original codon usage bias.

Usage

```
codon_random(object, n = 1, keep = FALSE, numcode = 1, ...)
```

```
## S4 method for signature 'regioned_dna'
codon_random(object, n, keep, numcode)
```

```
## S4 method for signature 'DNAStringSet'
codon_random(object, n, keep, numcode)
```

Arguments

| | |
|---------|--|
| object | A regioned_dna object. |
| n | Optional n parameter specifying what proportion of the codons to be mutated. Default value: 1. |
| keep | Logical parameter controlling whether keeping the codon usage bias |
| numcode | The ncbi genetic code number for translation. Default value: 1. Details please refer to <code>?seqinr::translate</code> (" https://rdr.io/cran/seqinr/man/translate.html "). |
| ... | ... |

Details

This method randomly sample synonymous codons for n propotion of every mutable codons in the sequences. This process will be likely to alter the codon usage bias of the original sequences. However the `keep = TRUE` argument help to preserve the codon usage bias. It is done via the `synsequence` function in `seqinr` package. The `synsequence` function essentially swaps the position of the synonymous codons without introducing new codons into the original sequences.

Value

A `regioned_dna` object containing the mutants; Or a `DNAStrngSet` object if the input is a `DNAS-trngSet` object.

See Also

[input_seq](#), [dinu_to](#), [codon_to](#), [codon_mimic](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
set.seed(2019)
get_cu(codon_random(rgd.seq, n = 0.5))
get_cu(codon_random(rgd.seq))
```

codon_to

Maximize or minimize the usage of certain codon.

Description

Input string of a codon to either the `"max.codon = "` or `"min.codon = "` parameter to maximize or minimize the usage of certain codon in the sequence.

Usage

```
codon_to(object, max.codon = NA, min.codon = NA, ...)
```

```
## S4 method for signature 'regioned_dna'
codon_to(object, max.codon, min.codon)
```

Arguments

| | |
|------------------------|-------------------------------------|
| <code>object</code> | A <code>regioned_dna</code> object. |
| <code>max.codon</code> | A string of a codon. |
| <code>min.codon</code> | A string of a codon. |
| <code>...</code> | ... |

Details

The ideas for this function is simple. We first extract the mutable regions for every sequences, then mutated the synonymous codons of the input to the desired. There will be only one ideal design for the maximization problem, however there may be numerous comparable designs having the same minimal usage of certain codon, as we randomly sample synonymous codon for substitution when solving the minimization problem.

Value

A regioned_dna object.

See Also

[input_seq](#), [dinu_to](#), [codon_random](#), [codon_mimic](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_cu(codon_to(rgd.seq, max.codon = "AAC")) - get_cu(rgd.seq)
get_cu(codon_to(rgd.seq, min.codon = "AAC")) - get_cu(rgd.seq)
```

| | |
|-----------|--|
| dinu_dist | <i>Calculating the dinucleotide usage difference between sequences</i> |
|-----------|--|

Description

We use a least squares approach to estimate the dinucleotide usage difference between DNA sequences

Usage

```
dinu_dist(seq, ref)

## S4 method for signature 'ANY'
dinu_dist(seq, ref)
```

Arguments

| | |
|-----|---|
| seq | the input DNA sequence of DNASTringSet or regioned_dna class. |
| ref | the reference DNA sequence of DNASTringSet or regioned_dna class. |

Details

similar method that applied in "Daniel Macedo de Melo Jorge, Ryan E. Mills, Adam S. Luring, CodonShuffle: a tool for generating and analyzing synonymously mutated sequences, Virus Evolution, Volume 1, Issue 1, March 2015, vev012, <https://doi.org/10.1093/ve/vev012>"

Value

vector

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_cu(rgd.seq)

mut.seq <- codon_random(rgd.seq)
dinu_dist(mut.seq, rgd.seq)
```

dinu_to

*Maximize or minimize the usage of certain dinucleotide.***Description**

Input string of a dinucleotide to either the "max.dinu = " or "min.codon = " parameter to maximize or minimize the usage of certain codon in the sequence. Using a greedy algorithm with priority given to dinucleotide12 or dinucleotide23.

Usage

```
dinu_to(object, max.dinu = NA, min.dinu = NA, keep = FALSE, numcode = 1, ...)
```

```
## S4 method for signature 'regioned_dna'
dinu_to(object, max.dinu, min.dinu, keep, numcode)
```

Arguments

| | |
|----------|---|
| object | A regioned_dna object. |
| max.dinu | A string of a dinucleotide. |
| min.dinu | A string of a dinucleotide. |
| keep | A logical varibale stating if the codon usage of the original sequences should be keep. Default: False. |
| numcode | The ncbi genetic code number for translation. Default value: 1. Details please refer to ?seqinr::translate (" https://rdr.io/cran/seqinr/man/translate.html "). |
| ... | ... |

Details

The detail strategy for this function please refer to: <https://koohoko.github.io/SynMut/algorithm.html>

Value

regioned_dna

See Also

[input_seq](#), [codon_to](#), [codon_random](#), [codon_mimic](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_du(dinu_to(rgd.seq, max.dinu = "cg")) - get_du(rgd.seq)
get_du(dinu_to(rgd.seq, min.dinu = "AA")) - get_du(rgd.seq)
get_du(dinu_to(rgd.seq, max.dinu = "cg", keep = TRUE)) - get_du(rgd.seq)
get_cu(dinu_to(rgd.seq, max.dinu = "CG", keep = TRUE)) - get_cu(rgd.seq)
```

| | |
|--------|-------------------------------|
| get_cu | <i>Get codon usage matrix</i> |
|--------|-------------------------------|

Description

Access the codon usage matrix

Usage

```
get_cu(object, ...)
```

```
## S4 method for signature 'regioned_dna'
```

```
get_cu(object)
```

```
## S4 method for signature 'DNAStrngSet'
```

```
get_cu(object)
```

Arguments

| | |
|--------|----------------------------|
| object | regioned_dna / DNAStrngSet |
| ... | ... |

Value

matrix

See Also

[input_seq](#), [get_region](#), [get_nu](#), [get_du](#), [get_freq](#), [get_rscu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_cu(rgd.seq)
```

| | |
|---------|---------------------------------|
| get_dna | <i>Get the DNAStrngSet data</i> |
|---------|---------------------------------|

Description

Access the DNA sequence data in DNAStrngSet.

Usage

```
get_dna(object, ...)
```

```
## S4 method for signature 'regioned_dna'
```

```
get_dna(object)
```


Arguments

| | |
|--------|------------------------|
| object | A regioned_dna object. |
| ... | ... |

Value

DNASTringSet

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_dna(rgd.seq)
```

| | |
|--------|--------------------------------------|
| get_du | <i>Get dinucleotide usage matrix</i> |
|--------|--------------------------------------|

Description

Access the dinucleotide usage matrix

Usage

```
get_du(object, ...)
```

S4 method for signature 'regioned_dna'

```
get_du(object)
```

S4 method for signature 'DNASTringSet'

```
get_du(object)
```

Arguments

| | |
|--------|-----------------------------|
| object | regioned_dna / DNASTringSet |
| ... | ... |

Value

matrix

See Also

[input_seq](#), [get_region](#), [get_nu](#), [get_cu](#), [get_freq](#), [get_rscu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_du(rgd.seq)
```

get_freq

*Get codon usage frequency of synonymous codons***Description**

Access the synonymous codon usage frequency

Usage

```
get_freq(object, numcode = 1, ...)

## S4 method for signature 'regioned_dna'
get_freq(object, numcode)

## S4 method for signature 'DNAStrngSet'
get_freq(object, numcode)

## S4 method for signature 'matrix'
get_freq(object, numcode)

## S4 method for signature 'vector'
get_freq(object, numcode)
```

Arguments

| | |
|---------|---|
| object | regioned_dna / DNAStrngSet / codon usage matrix (vector) |
| numcode | The ncbi genetic code number for translation. Default value: 1. Details please refer to ?seqinr::translate (" https://rdr.io/cran/seqinr/man/translate.html "). |
| ... | ... |

Value

matrix

See Also

[input_seq](#), [get_region](#), [get_cu](#), [get_du](#), [get_rscu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_freq(rgd.seq)
```

| | |
|--------|------------------------------------|
| get_nu | <i>Get nucleotide usage matrix</i> |
|--------|------------------------------------|

Description

Access the nucleotide usage matrix

Usage

```
get_nu(object, ...)  
  
## S4 method for signature 'regioned_dna'  
get_nu(object)  
  
## S4 method for signature 'DNAStrngSet'  
get_nu(object)
```

Arguments

| | |
|--------|----------------------------|
| object | regioned_dna / DNAStrngSet |
| ... | ... |

Value

matrix

See Also

[input_seq](#), [get_region](#), [get_cu](#), [get_du](#), [get_rscu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")  
rgd.seq <- input_seq(filepath)  
get_nu(rgd.seq)
```

| | |
|------------|--------------------------------|
| get_region | <i>Get the variable region</i> |
|------------|--------------------------------|

Description

Access the variable regions

Usage

```
get_region(object, ...)  
  
## S4 method for signature 'regioned_dna'  
get_region(object)
```

Arguments

| | |
|--------|--------------|
| object | regioned_dna |
| ... | ... |

Value

list

See Also

[input_seq](#), [get_cu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_region(rgd.seq)
```

get_rscu

Get Relative Synonymous Codon Usage (rscu) of synonymous codons

Description

Access the Relative Synonymous Codon Usage rscu

Usage

```
get_rscu(object, numcode = 1, ...)

## S4 method for signature 'regioned_dna'
get_rscu(object, numcode)

## S4 method for signature 'DNAStrngSet'
get_rscu(object, numcode)
```

Arguments

| | |
|---------|---|
| object | regioned_dna / DNAStrngSet / codon usage matrix (vector) |
| numcode | The ncbi genetic code number for translation. Default value: 1. Details please refer to ?seqinr::translate (" https://rdr.io/cran/seqinr/man/translate.html "). |
| ... | ... |

Value

matrix

See Also

[input_seq](#), [get_region](#), [get_cu](#), [get_du](#), [get_freq](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_rscu(rgd.seq)
```

input_seq

*Import region / constructing regioned_dna object***Description**

Constructing regioned_dna from DNASTringSet. Optionally input a region data.frame to define restricted amino-acid region for mutation.

Usage

```
input_seq(object, region = NA, ...)

## S4 method for signature 'character'
input_seq(object, region)

## S4 method for signature 'DNASTringSet'
input_seq(object, region)

## S4 method for signature 'DNASTring'
input_seq(object, region)
```

Arguments

| | |
|--------|--|
| object | Filepath or DNASTringSet. The input sequences is suggested to be in open reading frame(ORF). |
| region | NA. A data.frame specifying particular regions (positions in amino acid sequence) that is allowed to be mutated in the sequences. Both 1 / 0 or TRUE / FALSE encoding is OK. Please refer to Examples below for reference. |
| ... | ... |

Value

A regioned_dna-class object

See Also

[get_cu](#), [get_du](#), [get_region](#), [get_dna](#)

Examples

```
# Creating a input_seq class directly from system file
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)

# Optionally input with region dataframe
filepath.fasta <- system.file("extdata", "example.fasta", package = "SynMut")
```

```
fp.csv <- system.file("extdata", "target_regions.csv", package = "SynMut")
region <- read.csv(fp.csv)
rgd.seq <- input_seq(filepath.fasta, region)

# Creating from exsisting DNASTringSet object
seq <- Biostrings::DNASTringSet("ATCGATCGA")
rgd.seq <- input_seq(seq)
```

| | |
|--------------------|---|
| regioned_dna-class | <i>An S4 class to record DNA sequences and variable regions for mutations</i> |
|--------------------|---|

Description

Recording codon DNA sequences and region.

Slots

dnaseq a DNASTringSet object recording the sequence(s)
 region a list specifying particular regions in the sequences allowed to be mutated

Author(s)

Haogao Gu

See Also

[input_seq](#), [get_cu](#), [get_region](#)

| | |
|------------|--|
| seq_random | <i>Generate n random DNA sequences of length m</i> |
|------------|--|

Description

Generate n random DNA sequences of length m, optional exclude stop codons.

Usage

```
seq_random(n = 1, m, no.stop.codon = FALSE, ...)
```

S4 method for signature 'numeric,numeric'

```
seq_random(n, m, no.stop.codon)
```

Arguments

| | |
|---------------|--|
| n | the number of the output sequence(s). |
| m | the length of the output sequence(s). Either a fixed number or a vector of different numbers. |
| no.stop.codon | Default FALSE. If TRUE, the stop codons in the frame 1 would be substituted to another random codon. |
| ... | ... |

Value

a DNASTringSet object

Examples

```
seq_random(n = 1, m = 99)
seq_random(n = 10, m = 30)
seq_random(n = 10, m = 1:10)
seq.nsc <- seq_random(n = 10, m = 100, no.stop.codon = TRUE)
get_cu(seq.nsc)
```

Index

codon_dist, [2](#)
codon_dist, ANY-method (codon_dist), [2](#)
codon_mimic, [3](#), [5–7](#)
codon_mimic, DNASTringSet, DNASTringSet-method (codon_mimic), [3](#)
codon_mimic, regioned_dna, DNASTringSet-method (codon_mimic), [3](#)
codon_mimic, regioned_dna, vector-method (codon_mimic), [3](#)
codon_random, [4](#), [4](#), [6](#), [7](#)
codon_random, DNASTringSet-method (codon_random), [4](#)
codon_random, regioned_dna-method (codon_random), [4](#)
codon_to, [3–5](#), [5](#), [7](#)
codon_to, regioned_dna-method (codon_to), [5](#)

dinu_dist, [6](#)
dinu_dist, ANY-method (dinu_dist), [6](#)
dinu_to, [4–6](#), [7](#)
dinu_to, regioned_dna-method (dinu_to), [7](#)

get_cu, [8](#), [9–14](#)
get_cu, DNASTringSet-method (get_cu), [8](#)
get_cu, regioned_dna-method (get_cu), [8](#)
get_dna, [8](#), [13](#)
get_dna, regioned_dna-method (get_dna), [8](#)
get_du, [8](#), [9](#), [10–13](#)
get_du, DNASTringSet-method (get_du), [9](#)
get_du, regioned_dna-method (get_du), [9](#)
get_freq, [8](#), [9](#), [10](#), [12](#)
get_freq, DNASTringSet-method (get_freq), [10](#)
get_freq, matrix-method (get_freq), [10](#)
get_freq, regioned_dna-method (get_freq), [10](#)
get_freq, vector-method (get_freq), [10](#)
get_nu, [8](#), [9](#), [11](#)
get_nu, DNASTringSet-method (get_nu), [11](#)
get_nu, regioned_dna-method (get_nu), [11](#)
get_region, [8–11](#), [11](#), [12–14](#)
get_region, regioned_dna-method (get_region), [11](#)

get_rscu, [8–11](#), [12](#)
get_rscu, DNASTringSet-method (get_rscu), [12](#)
get_rscu, regioned_dna-method (get_rscu), [12](#)

input_seq, [4–12](#), [13](#), [14](#)
input_seq, character-method (input_seq), [13](#)
input_seq, DNASTring-method (input_seq), [13](#)
input_seq, DNASTringSet-method (input_seq), [13](#)

regioned_dna-class, [14](#)

seq_random, [14](#)
seq_random, numeric, numeric-method (seq_random), [14](#)