

Package ‘autonomics’

May 15, 2024

Type Package

Title Unified statistal Modeling of Omics Data

Version 1.13.3

Description This package unifies access to Statistal Modeling of Omics Data.

Across linear modeling engines (lm, lme, lmer, limma, and wilcoxon).

Across coding systems (treatment, difference, deviation, etc).

Across model formulae (with/without intercept, random effect, interaction or nesting).

Across omics platforms (microarray, rnaseq, msproteomics, affinity proteomics, metabolomics).

Across projection methods (pca, pls, sma, lda, spls, opls).

It provides a fast enrichment analysis implementation.

And an intuitive contrastogram visualisation to summarize contrast effects in complex designs.

License GPL-3

Encoding UTF-8

LazyData true

VignetteBuilder knitr

biocViews Software, DataImport, Preprocessing, DimensionReduction,

PrincipalComponent, Regression, DifferentialExpression,

GeneSetEnrichment, Transcriptomics, Transcription,

GeneExpression, RNASeq, Microarray, Proteomics, Metabolomics,

MassSpectrometry,

BugReports <https://github.com/bhagwataditya/autonomics>

URL <https://github.com/bhagwataditya/autonomics>

RoxygenNote 7.3.1

Depends R (>= 4.0)

Imports abind, BiocFileCache, BiocGenerics, bit64, codingMatrices,

colorspace, data.table, dplyr, edgeR, ggforce, ggplot2,

ggrepel, graphics, grDevices, grid, gridExtra, limma, magrittr,

matrixStats, methods, MultiAssayExperiment, parallel,

RColorBrewer, rlang, R.utils, readxl, S4Vectors, scales, stats,

stringi, SummarizedExperiment, tidyverse, tidyselect, tools, utils,

vsn

Suggests affy, AnnotationDbi, AnnotationHub, apcluster, BiocManager, BiocStyle, Biostrings, diagram, DBI, ensemblDb, fpc, GenomicDataCommons, GenomicRanges, GEOquery, hgu95av2.db, ICSNP, jsonlite, knitr, lme4, lmerTest, MASS, mixOmics, mpm, nlme, OlinkAnalyze, org.Hs.eg.db, org.Mm.eg.db, pcaMethods, pheatmap, progeny, propagate, RCurl, RSQLite, remotes, rmarkdown, ropens, Rsubread, readODS, rtracklayer, statmod, survival, survminer, testthat, UniProt.ws, writexl, XML

git_url <https://git.bioconductor.org/packages/autonomics>

git_branch devel

git_last_commit 043b7c3

git_last_commit_date 2024-05-08

Repository Bioconductor 3.20

Date/Publication 2024-05-15

Author Aditya Bhagwat [aut, cre],

Richard Cotton [aut],
Shahina Hayat [aut],
Laure Cougnaud [ctb],
Witold Szymanski [ctb],
Vanessa Beutgen [ctb],
Willem Ligtenberg [sad],
Hinrich Goehlmann [sad],
Karsten Suhre [sad],
Johannes Graumann [aut, sad, rth]

Maintainer Aditya Bhagwat <aditya.bhagwat@uni-marburg.de>

Contents

.extract_p_features	6
.merge	9
.read_compounddiscoverer	9
.read_diann_precursors	10
.read_maxquant_proteingroups	12
.read_metabolon	13
.read_rectangles	15
.read_rnaseq_bams	17
.read_somascan	20
abstract_fit	22
add_adjusted_pvalues	23
add_assay_means	24
add_facetvars	25
add_opentargets_by_uniprot	25
add_psp	26
add_smiles	27
altenrich	28

analysis	29
analyze	30
annotate_maxquant	31
annotate_uniprot_rest	33
assert_is_valid_sumexp	33
AUTONOMICS_DATASETS	34
bin	34
biplot	35
biplot_corrections	37
biplot_covariates	38
block2lme	39
center	40
code	41
coefs	43
collapsed_entrezg_to_symbol	44
COMPOUNDDISCOVERER_PATTERNS	45
CONTAMINANTSURL	45
contrast_subgroup_cols	46
counts	46
counts2cpm	47
counts2tpm	48
count_in	49
cpm	50
create_design	51
DATADIR	52
default_geom	54
default_sfile	55
default_subgroupvar	55
demultiplex	56
dequantify	57
dequantify_compounddiscoverer	58
download_contaminants	58
download_gtf	59
download_mcclain21	60
download_tcga_example	60
dt2mat	61
enrichment	61
ens2org	63
entrezg_to_symbol	64
explore_transformations	64
extract_rectangle	65
fcluster	67
fcor	68
fdata	68
fdr2p	70
filter_exprs_replicated_in_some_subgroup	71
filter_features	72
filter_medoid	72

filter_samples	73
fit	74
fitcoefs	77
fits	78
FITSEP	78
fitvars	79
fit_lmx	79
fit_survival	82
fix_xlgenes	83
flevels	84
fnames	85
formula2str	85
fvalues	86
fvars	87
genome_to_orgdb	87
group_by_level	88
guess_compounddiscoverer_quantity	89
guess_fitsep	90
guess_maxquant_quantity	90
guess_sep	91
has_multiple_levels	92
hdlproteins	94
impute	94
invert_subgroups	96
is_collapsed_subset	97
is_correlation_matrix	97
is_diann_report	98
is_fastadt	100
is_file	100
is_fraction	101
is_imputed	101
is_positive_number	102
is_scalar_subset	103
is_sig	104
is_valid_formula	105
keep_connected_blocks	106
keep_connected_features	106
keep_replicated_features	107
label2index	107
LINMOD_ENGINES	108
list2mat	108
list_files	109
log2counts	109
log2cpm	110
log2diffs	111
log2proteins	112
log2sites	112
log2tpm	113

log2transform	114
logical2factor	115
make_alpha_palette	116
make_colors	117
make_volcano_dt	117
map_fvalues	118
matrix2sumexp	119
MAXQUANT_PATTERNS	119
merge_compounddiscoverer	120
merge_sample_excel	120
merge_sample_file	121
merge_sdata	122
message_df	124
modelvar	124
MSIGCOLLECTIONSHUMAN	129
MSIGDIR	129
nfactors	130
OPENTARGETSDIR	131
order_on_p	131
pca	132
percentiles	134
pg_to_canonical	135
plot_contrastogram	135
plot_contrast_venn	136
plot_data	137
plot_densities	138
plot_design	140
plot_detections	141
plot_exprs	142
plot_exprs_per_coef	146
plot_fit_summary	147
plot_heatmap	148
plot_matrix	149
plot_subgroup_points	149
plot_summary	151
plot_venn	152
plot_venn_heatmap	152
plot_violins	153
plot_volcano	155
PRECURSOR_QUANTITY	157
preprocess_rmaseq_counts	157
pull_columns	158
read_affymetrix	159
read_compounddiscoverer	159
read_contaminants	161
read_fragpipe	161
read_maxquant_phosphosites	162
read_maxquant_proteingroups	164

read_msigdt	166
read_olink	166
read_salmon	167
read_uniprot dt	168
reexports	169
reset_fit	169
rm_diann_contaminants	170
rm_missing_in_all_samples	170
rm_unmatched_samples	171
scaledlibsizes	172
scoremat	172
slevels	173
snames	174
split_samples	174
stri_any_regex	175
stri_detect_fixed_in_collapsed	176
subgroup_array	177
subtract_baseline	177
sumexplist_to_longdt	179
sumexp_to_tsv	180
sumexp_to_widedt	180
summarize_fit	181
svalues	182
svars	183
systematic_nas	184
tag_features	185
tag_hdproteins	186
TAXON_TO_ORGNAME	186
TESTS	187
tpm	187
uncollapse	188
values	189
varlevels_dont_clash	190
venn_detects	191
weights	191
write_xl	192
zero_to_na	193

.extract_p_features *Extract coefficient features*

Description

Extract coefficient features

Usage

```
.extract_p_features(  
    object,  
    coefs,  
    p = 0.05,  
    fit = fits(fdt(object)),  
    combiner = "|",  
    verbose = TRUE  
)  
  
.extract_fdr_features(  
    object,  
    coefs,  
    fdr = 0.05,  
    fit = fits(fdt(object)),  
    combiner = "|",  
    verbose = TRUE  
)  
  
.extract_effectsize_features(  
    object,  
    coefs,  
    effectsize = 1,  
    fit = fits(fdt(object)),  
    combiner = "|",  
    verbose = TRUE  
)  
  
.extract_sign_features(  
    object,  
    coefs,  
    sign,  
    fit = fits(fdt(object))[1],  
    combiner = "|",  
    verbose = TRUE  
)  
  
.extract_n_features(  
    object,  
    coefs,  
    combiner = "|",  
    n,  
    fit = fits(fdt(object))[1],  
    verbose = TRUE  
)  
  
extract_coef_features(  
    object,
```

```

fit = fits(fdt(object))[1],
coefs = default_coefs(fdt(object), fit = fit),
combiner = "|",
p = 1,
fdr = 1,
effectsize = 0,
sign = c(-1, +1),
n = 4,
verbose = TRUE
)

```

Arguments

object	SummarizedXExperiment
coefs	subset of coefs(object)
p	p threshold
fit	subset of fits(fdt(object))
combiner	' ' or '&': how to combine multiple fits/coefs
verbose	TRUE or FALSE
fdr	fdr threshold
effectsize	effectsize threshold
sign	effect sign
n	number of top features (Inf means all)

Value

SummarizedExperiment

Examples

```

# Read and Fit
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% fit_limma()
fdt(object) %>% add_adjusted_pvalues('fdr')

# Single coef
object0 <- object
object %>% .extract_p_features(coefs = 't1', p = 0.05)
object %>% .extract_fdr_features(coefs = 't1', fdr = 0.05)
object %>% .extract_effectsize_features(coefs = 't1', effectsize = 1)
object %>% .extract_sign_features(coefs = 't1', sign = -1)
object %>% .extract_n_features(coefs = 't1', n = 1)
object <- object0
object %>% extract_coef_features(
  coefs = 't1', p = 0.05, fdr = 0.05, effectsize = 1, sign = -1, n = 1)

# Multiple coeffs
object <- object0
object %>% .extract_p_features(coefs = c('t1', 't2'), p = 0.05)

```

.merge

9

```
object %<>% .extract_fdr_features(      coefs = c('t1', 't2'), fdr = 0.01)
object %<>% .extract_effectsize_features(coefs = c('t1', 't2'), effectsize = 1)
object %<>% .extract_sign_features(      coefs = c('t1', 't2'), sign = -1)
object %<>% .extract_n_features(        coefs = c('t1', 't2'), n = 1)
object <- object0
object %<>% extract_coef_features(
  coefs = c('t1', 't2'), p = 0.05, fdr = 0.01, effectsize = 1, sign = -1, n = 1)
```

.merge

Clean Merge

Description

Clean Merge

Usage

```
.merge(dt1, dt2, by)
```

Arguments

dt1	data.table
dt2	data.table
by	string

Examples

```
require(data.table)
dt1 <- data.table(feature_id = c('PG1', 'PG2'), gene    = c('G1', 'G2'))
dt2 <- data.table(feature_id = c('PG1', 'PG2'), protein = c('P1', 'P2'))
dt1 %<>% .merge(dt2, by = 'feature_id')
dt1
```

.read_compounddiscoverer

Read compound discoverer files as-is

Description

Read compound discoverer files as-is

Usage

```
.read_compounddiscoverer(
  file,
  quantity = guess_compounddiscoverer_quantity(file),
  verbose = TRUE
)
```

Arguments

file	compoumd discoverer file
quantity	string
verbose	TRUE / FALSE

Value

data.table

.read_diann_precursors

Read diann

Description

Read diann

Usage

```
.read_diann_precursors(file, Lib.PG.Q = 0.01, verbose = TRUE)

.read_diann_proteingroups(file, Lib.PG.Q = 0.01)

read_diann_proteingroups(
  file,
  Lib.PG.Q = 0.01,
  simplify_snames = TRUE,
  contaminants = character(0),
  impute = FALSE,
  plot = FALSE,
  pca = plot,
  pls = plot,
  fit = if (plot) "limma" else NULL,
  formula = ~subgroup,
  block = NULL,
  coefs = NULL,
  contrasts = NULL,
  palette = NULL,
  verbose = TRUE
)
read_diann(...)
```

Arguments

file	'report.tsv' file
Lib.PG.Q	Lib.PG.Q cutoff
verbose	TRUE or FALSE
simplify_snames	TRUE or FALSE: simplify (drop common parts in) samplenames ?
contaminants	character vector: contaminant uniprots
impute	TRUE or FALSE: impute group-specific NA values?
plot	TRUE or FALSE
pca	TRUE or FALSE: run pca ?
pls	TRUE or FALSE: run pls ?
fit	model engine: 'limma', 'lm', 'lme(r)', 'wilcoxon' or NULL
formula	model formula
block	model blockvar: string or NULL
coefs	model coefficients of interest: character vector or NULL
contrasts	coefficient contrasts of interest: character vector or NULL
palette	color palette: named string vector
...	used to maintain deprecated functions

Value

data.table or SummarizedExperiment

Examples

```
# Read
  file <- download_data('dilution.report.tsv')
  .read_diann_precursors(file)          #    precursors longdt
  .read_diann_proteingroups(file)       # proteingroups longdt
  fdt(read_diann_proteingroups(file))  # proteingroups sumexp
# Compare
  PR <- .read_diann_precursors(file)
  PG <- .read_diann_proteingroups(file)
  PG[intensity==top1] # matches      : 24975 (85%) proteingroups
  PG[intensity!=top1] # doesnt match : 4531 (15%) proteingroups
  RUN <- 'IPT_HeLa_1_DIAstd_Slot1-40_1_9997'
  PR[uniprot=='Q96JP5;Q96JP5-2' & run == RUN, 1:6] #    match: 8884 == 8884
  PR[uniprot=='P36578'           & run == RUN, 1:6] # no match: 650887 != 407978
  PR[intensity != top1][feature_id == unique(feature_id)[1]][run == unique(run)[1]][1:2, 1:6]
  PR[intensity != top1][feature_id == unique(feature_id)[2]][run == unique(run)[1]][1:2, 1:6]
  PR[intensity != top1][feature_id == unique(feature_id)[3]][run == unique(run)[1]][1:3, 1:6]
```

.read_maxquant_proteingroups
Read proteingroups/phosphosites as-is

Description

Read proteingroups/phosphosites as-is

Usage

```
.read_maxquant_proteingroups(
  file,
  quantity = guess_maxquant_quantity(file),
  verbose = TRUE
)

.read_maxquant_phosphosites(
  file,
  profile,
  quantity = guess_maxquant_quantity(file),
  verbose = TRUE
)
```

Arguments

file	proteingroups / phosphosites file
quantity	string
verbose	TRUE / FALSE
profile	proteingroups file

Value

data.table

Examples

```
profile <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
fosfile <- system.file('extdata/billing19.phosphosites.txt', package = 'autonomics')
prodt <- .read_maxquant_proteingroups(file = profile)
fosdt <- .read_maxquant_phosphosites( file = fosfile, profile = profile)
```

```
.read_metabolon      Read metabolon xlsxfile
```

Description

Read metabolon xlsxfile

Usage

```
.read_metabolon(  
  file,  
  sheet = "OrigScale",  
  fidvar = "BIOCHEMICAL",  
  sidvar = "(CLIENT_IDENTIFIER|Client ID)",  
  sfile = NULL,  
  by.x = "sample_id",  
  by.y = NULL,  
  subgroupvar = "Group",  
  verbose = TRUE  
)  
  
read_metabolon(  
  file,  
  sheet = "OrigScale",  
  fidvar = "BIOCHEMICAL",  
  sidvar = "(CLIENT_IDENTIFIER|Client ID)",  
  sfile = NULL,  
  by.x = "sample_id",  
  by.y = NULL,  
  subgroupvar = "Group",  
  fnamevar = "BIOCHEMICAL",  
  kegg_pathways = FALSE,  
  smiles = FALSE,  
  impute = TRUE,  
  plot = FALSE,  
  pca = plot,  
  pls = plot,  
  label = "feature_id",  
  fit = if (plot) "limma" else NULL,  
  formula = ~subgroup,  
  block = NULL,  
  coefs = NULL,  
  contrasts = NULL,  
  palette = NULL,  
  verbose = TRUE  
)
```

Arguments

file	metabolon xlsx file
sheet	excel sheet (number or string)
fidvar	featureid var
sidvar	samplid var
sfile	sample file
by.x	‘file’ mergeby column
by.y	‘sfile’ mergeby column
subgroupvar	subgroup var
verbose	TRUE or FALSE
fnamevar	featurename fvar
kegg_pathways	TRUE or FALSE: add kegg pathways?
smiles	TRUE or FALSE: add smiles?
impute	TRUE or FALSE: impute group-specific NA values?
plot	TRUE or FALSE
pca	TRUE or FALSE
pls	TRUE or FALSE
label	fvar
fit	model engine: ‘limma’, ‘lm’, ‘lme(r)’, ‘wilcoxon’ or NULL
formula	model formula
block	model blockvar: string or NULL
coefs	model coefficients of interest: character vector or NULL
contrasts	coefficient contrasts of interest: character vector or NULL
palette	NULL or colorvector

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
read_metabolon(file, plot = TRUE, block = 'Subject')
```

.read_rectangles *Read omics data from rectangular file*

Description

Read omics data from rectangular file

Usage

```
.read_rectangles(  
  file,  
  sheet = 1,  
  fid_rows,  
  fid_cols,  
  sid_rows,  
  sid_cols,  
  expr_rows,  
  expr_cols,  
  fvar_rows = NULL,  
  fvar_cols = NULL,  
  svar_rows = NULL,  
  svar_cols = NULL,  
  fdata_rows = NULL,  
  fdata_cols = NULL,  
  sdata_rows = NULL,  
  sdata_cols = NULL,  
  transpose = FALSE,  
  verbose = TRUE  
)  
  
read_rectangles(  
  file,  
  sheet = 1,  
  fid_rows,  
  fid_cols,  
  sid_rows,  
  sid_cols,  
  expr_rows,  
  expr_cols,  
  fvar_rows = NULL,  
  fvar_cols = NULL,  
  svar_rows = NULL,  
  svar_cols = NULL,  
  fdata_rows = NULL,  
  fdata_cols = NULL,  
  sdata_rows = NULL,  
  sdata_cols = NULL,
```

```

    transpose = FALSE,
    sfile = NULL,
    sfileby = NULL,
    subgroupvar = character(0),
    verbose = TRUE
)

```

Arguments

file	string: name of text (txt, csv, tsv, adat) or excel (xls, xlsx) file
sheet	integer/string: only relevant for excel files
fid_rows	numeric vector: featureid rows
fid_cols	numeric vector: featureid cols
sid_rows	numeric vector: sampleid rows
sid_cols	numeric vector: sampleid cols
expr_rows	numeric vector: expr rows
expr_cols	numeric vector: expr cols
fvar_rows	numeric vector: fvar rows
fvar_cols	numeric vector: fvar cols
svar_rows	numeric vector: svar rows
svar_cols	numeric vector: svar cols
fdata_rows	numeric vector: fdata rows
fdata_cols	numeric vector: fdata cols
sdata_rows	numeric vector: sdata rows
sdata_cols	numeric vector: sdata cols
transpose	TRUE or FALSE (default)
verbose	TRUE (default) or FALSE
sfile	sample file
sfileby	sample file mergeby column
subgroupvar	subgroupvar in sfile

Value

SummarizedExperiment

Examples

```
# RNASEQ
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
read_rectangles( file, fid_rows = 2:25,      fid_cols = 2,
                  sid_rows = 1,      sid_cols = 5:28,
                  expr_rows = 2:25 ,  expr_cols = 5:28,
                  fvar_rows = 1,      fvar_cols = 1:4,
                  fdata_rows = 2:25 , fdata_cols = 1:4,   transpose = FALSE)
```

```
# LCMSMS PROTEINGROUPS
  file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
  read_rectangles( file,
    fid_rows = 2:21,      fid_cols = 383,
    sid_rows = 1,         sid_cols = seq(124, 316, by = 6),
    expr_rows = 2:21,     expr_cols = seq(124, 316, by = 6),
    fvar_rows = 1,        fvar_cols = c(2, 6, 7, 383),
    fdata_rows = 2:21,    fdata_cols = c(2, 6, 7, 383),
    transpose = FALSE )

# SOMASCAN
  file <- system.file('extdata/atkin.somascan.adat', package = 'autonomics')
  read_rectangles(file, fid_rows = 30,           fid_cols = 23:42,
                 sid_rows = 42:108,      sid_cols = 4,
                 expr_rows = 42:108,     expr_cols = 23:42,
                 fvar_rows = 28:40,      fvar_cols = 22,
                 svar_rows = 41,         svar_cols = 1:21,
                 fdata_rows = 28:40,     fdata_cols = 23:42,
                 sdata_rows = 42:108,    sdata_cols = 1:21, transpose = TRUE)

# METABOLON
  file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
  read_rectangles(file, sheet = 2,
    fid_rows = 11:30,      fid_cols = 2,
    sid_rows = 4,           sid_cols = 15:81,
    expr_rows = 11:30,      expr_cols = 15:81,
    fvar_rows = 10,          fvar_cols = 1:14,
    svar_rows = 1:10,        svar_cols = 14,
    fdata_rows = 11:30,      fdata_cols = 1:14,
    sdata_rows = 1:10,        sdata_cols = 15:81,
    transpose = FALSE )
```

.read_rnaseq_bams Read rnaseq counts/bams

Description

Read rnaseq counts/bams

Usage

```
.read_rnaseq_bams(
  dir,
  paired,
  genome,
  nthreads = detectCores(),
  sfile = NULL,
  by.y = NULL,
  ensdb = NULL,
  verbose = TRUE
)
```

```
.read_rnaseq_counts(  
  file,  
  fid_col = 1,  
  sfile = NULL,  
  by.y = NULL,  
  ensdb = NULL,  
  verbose = TRUE  
)
```

```
read_rnaseq_bams(  
  dir,  
  paired,  
  genome,  
  nthreads = detectCores(),  
  sfile = NULL,  
  by.y = NULL,  
  block = NULL,  
  formula = ~subgroup,  
  min_count = 10,  
  pseudo = 0.5,  
  ensdb = NULL,  
  tpm = FALSE,  
  cpm = TRUE,  
  log2 = TRUE,  
  plot = FALSE,  
  label = "feature_id",  
  pca = plot,  
  pls = plot,  
  fit = if (plot) "limma" else NULL,  
  voom = cpm,  
  coefs = NULL,  
  contrasts = NULL,  
  palette = NULL,  
  verbose = TRUE  
)
```

```
read_rnaseq_counts(  
  file,  
  fid_col = 1,  
  sfile = NULL,  
  by.y = NULL,  
  formula = ~subgroup,  
  block = NULL,  
  min_count = 10,  
  pseudo = 0.5,  
  tpm = FALSE,  
  ensdb = NULL,
```

```
    cpm = !tpm,
    log2 = TRUE,
    plot = FALSE,
    label = "feature_id",
    pca = plot,
    pls = plot,
    fit = if (plot) "limma" else NULL,
    voom = cpm,
    coefs = NULL,
    contrasts = NULL,
    palette = NULL,
    verbose = TRUE
)
```

Arguments

dir	read_rnaseq_bams: bam/sam dir
paired	read_rnaseq_bams: TRUE/FALSE : paired end reads ?
genome	read_rnaseq_bams: 'mm10', 'hg38', etc. or GTF file
nthreads	read_rnaseq_bams: nthreads used by Rsubread::featureCounts()
sfile	sample file
by.y	sample file mergeby column
ensdb	EnsDb with genesizes : e.g. AnnotationHub::AnnotationHub[['AH64923']]
verbose	TRUE or FALSE: message?
file	count file
fid_col	featureid column (number or string)
block	model blockvar: string or NULL
formula	model formula
min_count	min feature count required in some samples
pseudo	pseudocount added to prevent -Inf log2 values
tpm	TRUE or FALSE : add tpm to assays (counts / libsize / genelength) ?
cpm	TRUE or FALSE: add cpm to assays (counts / effectivelibsize) ?
log2	TRUE or FALSE: log2 transform ?
plot	TRUE or FALSE: plot?
label	fvar
pca	TRUE or FALSE: perform and plot pca?
pls	TRUE or FALSE: run pls ?
fit	model engine: 'limma', 'lm', 'lme(r)', 'wilcoxon' or NULL
voom	model weights to be computed? TRUE/FALSE
coefs	model coefficients of interest: string vector or NULL
contrasts	model coefficient contrasts of interest: string vector or NULL
palette	color palette : named string vector

Value

```
SummarizedExperiment
```

Author(s)

Aditya Bhagwat, Shahina Hayat

Examples

```
# read_rnaseq_bams
if (requireNamespace('Rsubread')){
  dir <- download_data('billing16.bam.zip')
  object <- read_rnaseq_bams(dir, paired = TRUE, genome = 'hg38')
  object <- read_rnaseq_bams(dir, paired = TRUE, genome = 'hg38', plot = TRUE)
}
# read_rnaseq_counts
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnaseq_counts(file, fit = 'limma', coefs = 'E15')
object <- read_rnaseq_counts(file, fit = 'limma', coefs = 'E15', voom = FALSE)
object <- read_rnaseq_counts(file, fit = 'limma', coefs = 'E15', voom = FALSE, cpm = FALSE)
object <- read_rnaseq_counts(file, fit = 'limma', coefs = 'E15', voom = FALSE, cpm = FALSE,
                             log2 = FALSE)
object <- read_rnaseq_counts(file, plot = TRUE)

# read_rnaseq_counts(tpm = TRUE)
## Not run:
ah <- AnnotationHub::AnnotationHub()
ensdb <- ah[['AH64923']]
object <- read_rnaseq_counts(file, fit = 'limma', coefs = 'E02', tpm = TRUE, ensdb = ensdb)

## End(Not run)
```

.read_somascans

Read somascans adatfile

Description

Read somascans adatfile

Usage

```
.read_somascans(
  file,
  fidvar = "Target",
  sidvar = "SampleId",
  sfile = NULL,
  by.x = NULL,
  by.y = NULL,
  subgroupvar = "SampleGroup",
```

```
    verbose = TRUE
)

read_somascan(
  file,
  fidvar = "Target",
  sidvar = "SampleId",
  sfile = NULL,
  by.x = NULL,
  by.y = NULL,
  subgroupvar = "SampleGroup",
  fname_var = "EntrezGeneSymbol",
  sample_type = "Sample",
  feature_type = "Protein",
  sample_quality = c("FLAG", "PASS"),
  feature_quality = c("FLAG", "PASS"),
  rm_na_svars = FALSE,
  rm_single_value_svars = FALSE,
  plot = FALSE,
  label = "feature_id",
  pca = plot,
  pls = plot,
  fit = if (plot) "limma" else NULL,
  formula = ~subgroup,
  block = NULL,
  coefs = NULL,
  contrasts = NULL,
  palette = NULL,
  verbose = TRUE
)
```

Arguments

file	somascan (adat) file
fidvar	featureid var
sidvar	sampleid var
sfile	sample file
by.x	‘file’ mergeby column
by.y	‘sfile’ mergeby column
subgroupvar	subgroup var: string
verbose	TRUE or FALSE: message?
fname_var	featurename var: string
sample_type	subset of c('Sample','QC','Buffer','Calibrator')
feature_type	subset of c('Protein', 'Hybridization Control Elution','Rat Protein')
sample_quality	subset of c('PASS', 'FLAG', 'FAIL')

```

feature_quality
  subset of c('PASS', 'FLAG', 'FAIL')

rm_na_svars    TRUE or FALSE: rm NA svars?
rm_single_value_svars
  TRUE or FALSE: rm single value svars?

plot           TRUE or FALSE: plot ?
label          fvar

pca            TRUE or FALSE: run pca?

pls             TRUE or FALSE: run pls?

fit             model engine: 'limma', 'lm', 'lme(r)', 'wilcoxon' or NULL

formula        model formula

block           model blockvar

coefs           model coefficients of interest: character vector or NULL

contrasts      coefficient contrasts of interest: character vector or NULL

palette         character vector or NULL

```

Value

Summarizedexperiment

Examples

```

file <- system.file('extdata/atkin.somascan.adat', package = 'autonomics')
read_somascan(file, plot = TRUE, block = 'Subject')

```

abstract_fit	<i>Abstract model fit</i>
---------------------	---------------------------

Description

Abstract model fit

Usage

```

abstract_fit(
  object,
  sep = guess_fitsep(fdt(object)),
  fit = fits(fdt(object)),
  coef = coefs(fdt(object), fit = fit),
  significancevar = "p",
  significance = 0.05
)

```

Arguments

object	SummarizedExperiment
sep	string
fit	character vector
coef	character vector
significancevar	'p' or 'fdr'
significance	fraction : pvalue cutoff

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file, fit = 'limma', coef = 't3')
fdt(object)
fdt(abstract_fit(object))
```

add_adjusted_pvalues *Add adjusted pvalues***Description**

Add adjusted pvalues

Usage

```
add_adjusted_pvalues(
  featuredt,
  method,
  fit = fits(featuredt),
  coefs = default_coefs(featuredt, fit = fit),
  verbose = TRUE
)
```

Arguments

featuredt	fdt(object)
method	'fdr', 'bonferroni', ... (see 'p.adjust.methods')
fit	'limma', 'lm', 'lme', 'lmer'
coefs	coefficient (string)
verbose	TRUE or FALSE

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
fdt(object) %>% extract(, 1:2)
object %<>% fit_limma(coef = 'Adult')
object %<>% extract(order(fdt(.)$`p~Adult~limma`), )
fdt(object)
(fdta(object) %<>% add_adjusted_pvalues('fdr'))
(fdta(object) %<>% add_adjusted_pvalues('fdr'))      # smart enough not to add second column
(fdta(object) %>% add_adjusted_pvalues('bonferroni'))
```

add_assay_means *Add assay means*

Description

Add assay means

Usage

```
add_assay_means(object, assay = assayNames(object)[1], bin = TRUE)
```

Arguments

object	SummarizedExperiment or NULL
assay	string
bin	TRUE or FALSE

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
fdt(object) %>% extract(, 1:2)
fdt(object)
object %<>% add_assay_means(SummarizedExperiment::assayNames(.))
fdt(object)
```

add_facetvars *Add facetvars*

Description

Add facetvars

Usage

```
add_facetvars(  
  object,  
  fit = fits(fdt(object))[1],  
  coefs = default_coefs(fdt(object), fit = fit)  
)
```

Arguments

object	SummarizedExperiment
fit	string
coefs	string vector

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')  
object <- read_metabolon(file, fit = 'limma')  
fdt(object)  
fdt(add_facetvars(object))
```

add_opentargets_by_uniprot *Add opentargets annotations*

Description

Add opentargets annotations

Usage

```
add_opentargets_by_uniprot(  
  object,  
  cols = c("genesymbol", "genename", "function"),  
  verbose = TRUE  
)
```

Arguments

object	SummarizedExperiment
cols	character vector
verbose	TRUE or FALSE

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
object %>% add_opentargets_by_uniprot()
```

add_psp

*Add psp***Description**

Add PhosphoSitePlus literature counts

Usage

```
add_psp(
  object,
  pspfile = file.path(R_user_dir("autonomics", "cache"), "phosphositeplus",
    "Phosphorylation_site_dataset.gz")
)
```

Arguments

object	SummarizedExperiment
pspfile	phosphositeplus file

Details

Go to www.phosphosite.org
 Register and Login.
 Download Phosphorylation_site_dataset.gz'.
 Save into: file.path(R_user_dir('autonomics','cache'),'phosphositeplus')

Value

SummarizedExperiment

Examples

```
fosfile <- system.file('extdata/billing19.phosphosites.txt', package = 'autonomics')
profile <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_phosphosites(fosfile = fosfile, profile = profile)
fdt(object)
object %<>% add_psp()
fdt(object)
```

add_smiles

Add smiles

Description

Add smiles

Usage

```
add_smiles(object)
```

Arguments

object character/factor vector with pubchem ids

Value

character/factor vector

References

<https://pubchemdocs.ncbi.nlm.nih.gov/pug-rest-tutorial>

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
# add_smiles(object[1:10, ]) # seems down
```

altenrichAlternative Enrichment Analysis

Description

Alternative Enrichment Analysis

Usage

```
altenrich(
  object,
  pathwaydt,
  genevar = "gene",
  genesep = "[ ,;]",
  coef = default_coefs(fdt(object))[1],
  fit = fits(fdt(object))[1],
  significancevar = "p",
  significance = 0.05,
  effectsize = 0,
  n = 3,
  genes = FALSE,
  verbose = TRUE
)
```

Arguments

object	SummarizedExperiment
pathwaydt	data.table, e.g. read_msigdt
genevar	gene fvar
genesep	string or NULL
coef	string in coefs(fdt(object))
fit	'limma', 'lm', 'lme', 'lmer', 'wilcoxon'
significancevar	'p' or 'fdr'
significance	significance cutoff
effectsize	effectsize cutoff
n	no of detected genes required (for geneset to be examined)
genes	whether to record genes
verbose	whether to msg

Details

This is an alternative enrichment analysis implementation. It is more modular: uses four times `.enrichment(VERBOSE)?` as backend. But also four times slower than `enrichment`, so not recommended. It is retained for testing purposes.

This alternative enrichment implementation

See Also

[enrichment()]

analysis

Get/set analysis

Description

Get/set analysis

Usage

```
analysis(object)

## S4 method for signature 'SummarizedExperiment'
analysis(object)

analysis(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,list'
analysis(object) <- value
```

Arguments

object	SummarizedExperiment
value	list

Value

analysis details (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
analysis(object)
```

analyze	<i>Analyze</i>
---------	----------------

Description

Analyze

Usage

```
analyze(
  object,
  pca = TRUE,
  pls = TRUE,
  fit = "limma",
  formula = default_formula(object),
  drop = varlevels_dont_clash(object, all.vars(formula)),
  codingfun = contr.treatment,
  contrasts = NULL,
  coefs = colnames(create_design(object, formula = formula, drop = drop)),
  block = NULL,
  weightvar = if ("weights" %in% assayNames(object)) "weights" else NULL,
  plot = pca & !is.null(fit),
  label = "feature_id",
  palette = NULL,
  verbose = TRUE
)
```

Arguments

<code>object</code>	SummarizedExperiment
<code>pca</code>	TRUE / FALSE: perform pca ?
<code>pls</code>	TRUE / FALSE: perform pls ?
<code>fit</code>	linmod engine: 'limma', 'lm', 'lme(r)', 'lmer', 'wilcoxon'
<code>formula</code>	model formula
<code>drop</code>	TRUE / FALSE : drop varname in designmat ?
<code>codingfun</code>	factor coding function <ul style="list-style-type: none"> • <code>contr.treatment</code>: $\text{intercept} = y_0$, $\text{coef}_i = y_i - y_0$ • <code>contr.treatment.explicit</code>: $\text{intercept} = y_0$, $\text{coef}_i = y_i - y_0$ • <code>code_control</code>: $\text{intercept} = \text{ymean}$, $\text{coef}_i = y_i - \text{ymean}$ • <code>contr.diff</code>: $\text{intercept} = y_0$, $\text{coef}_i = y_i - y_{(i-1)}$ • <code>code_diff</code>: $\text{intercept} = \text{ymean}$, $\text{coef}_i = y_i - y_{(i-1)}$ • <code>code_diff_forward</code>: $\text{intercept} = \text{ymean}$, $\text{coef}_i = y_i - y_{(i+)}$ • <code>code_deviation</code>: $\text{intercept} = \text{ymean}$, $\text{coef}_i = y_i - \text{ymean}$ (drop last) • <code>code_deviation_first</code>: $\text{intercept} = \text{ymean}$, $\text{coef}_i = y_i - \text{ymean}$ (drop first)

	<ul style="list-style-type: none"> • code_helmert: intercept = ymean, coefi = yi - mean(y0:(yi-1)) • code_helmert_forward: intercept = ymean, coefi = yi - mean(y(i+1):yp)
contrasts	model coefficient contrasts of interest: string vector or NULL
coefs	model coefficients of interest: string vector or NULL
block	model blockvar
weightvar	NULL or name of weight matrix in assays(object)
plot	TRUE / FALSE
label	fvar
palette	NULL or colorvector
verbose	TRUE / FALSE: message?

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% analyze()
```

annotate_maxquant *Annotate maxquant*

Description

Annotate maxquant data.table

Usage

```
annotate_maxquant(
  dt,
  uniprothdrs,
  contaminanthdrs,
  maxquanthdrs,
  restapi = FALSE,
  verbose = TRUE
)
```

Arguments

```
dt          data.table : output of read_maxquant_(proteingroups|phosphosites)
uniprothdrs   data.table : output of read_uniprotdt
contaminanthdrs
              data.table : output of read_uniprotdt
maxquanthdrs   data.table : output of read_uniprotdt
restapi        logical(1) : use uniprot restapi to complete missing annotations ?
verbose        logical(1) : message ?
```

Details

Uncollapse, annotate, curate, recollapse, name

Value

data.table

Examples

```
# Fukuda 2020: contaminants + maxquanthdrs
#-----
  file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
  dt <- .read_maxquant_proteingroups(file)
  dt[, 1:2]
  uniprothdrs <- NULL
  contaminanthdrs <- read_contaminantdt()
  maxquanthdrs <- parse_maxquant_hdrs(dt$`Fasta headers`); dt$`Fasta headers` <- NULL
  dt %>% annotate_maxquant(uniprothdrs, contaminanthdrs, maxquanthdrs)
  dt[      , 1:9]
  dt[    reverse== '+', 1:9]
  dt[contaminant== '+', 1:9]

# Billing 2019: uniprothdrs + contaminants + maxquanthdrs
#-----
profile <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
fosfile <- system.file('extdata/billing19.phosphosites.txt', package = 'autonomics')
upfile <- system.file('extdata/uniprot_hsa_20140515.fasta', package = 'autonomics')
prodt <- .read_maxquant_proteingroups(profile);           prodt[, 1:2]
fosdt <- .read_maxquant_phosphosites(fosfile, profile); fosdt[, 1:3]
  uniprothdrs <- read_uniprotdt(upfile)
  contaminanthdrs <- read_contaminantdt()
  maxquanthdrs <- parse_maxquant_hdrs(prodt$`Fasta headers`)
  annotate_maxquant(prodt, uniprothdrs, contaminanthdrs, maxquanthdrs)[, 1:8]
  annotate_maxquant(fosdt, uniprothdrs, contaminanthdrs, maxquanthdrs)[, 1:8]
```

annotate_uniprot_rest *Annotate uniprot/ensp*

Description

Annotate uniprot/ensp

Usage

```
annotate_uniprot_rest(x, columns = UNIPROTCOLS, verbose = TRUE)
```

Arguments

x	character vector
columns	character vector
verbose	TRUE or FALSE

Value

data.table(dbid, uniprot, reviewed, protein, gene, canonical, isoform, fragment, existence, organism, full)

Examples

```
annotate_uniprot_rest( x = c('P00761', 'Q32MB2') )
annotate_uniprot_rest( x = c('ENSBTAP00000006074', 'ENSP00000377550') )
```

assert_is_valid_sumexp

Assert that x is a valid SummarizedExperiment

Description

Assert that x is a valid SummarizedExperiment

Usage

```
assert_is_valid_sumexp(x, .xname = get_name_in_parent(x))
```

Arguments

x	SummarizedExperiment
.xname	see get_name_in_parent

Value

TRUE or FALSE

Examples

```
# VALID
  file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
  x <- read_metabolon(file)
  assert_is_valid_sumexp(x)
# NOT VALID
  rownames(SummarizedExperiment::colData(x)) <- NULL
  # assert_is_valid_sumexp(x)
```

AUTONOMICS_DATASETS *Data used in examples/vignette/tests/longtests*

Description

Data used in examples/vignette/tests/longtests

Usage

AUTONOMICS_DATASETS

Format

An object of class character of length 19.

Examples

AUTONOMICS_DATASETS

bin *Bin continuous variable*

Description

Bin continuous variable

Usage

```
bin(object, ...)

## S3 method for class 'logical'
bin(object, ...)

## S3 method for class 'character'
bin(object, ...)

## S3 method for class 'factor'
bin(object, ...)

## S3 method for class 'numeric'
bin(object, probs = c(0, 0.33, 0.66, 1), ...)

## S3 method for class 'SummarizedExperiment'
bin(object, fvar, probs = c(0, 0.33, 0.66, 1), ...)
```

Arguments

object	numeric or SummarizedExperiment
...	(S3 dispatch)
probs	numeric
fvar	string or NULL

Value

factor vector

Examples

```
# Numeric vector
  object <- rnorm(10, 5, 1)
  bin(object)
# SummarizedExperiment
  file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
  fdt(object <- read_maxquant_proteingroups(file))
  fdt(bin(object, 'pepcounts'))
```

biplot

Biplot

Description

Biplot

Usage

```
biplot(
  object,
  method = biplot_methods(object)[1],
  by = biplot_by(object, method)[1],
  dims = biplot_dims(object, method, by)[1:2],
  color = "subgroup",
  shape = NULL,
  size = NULL,
  alpha = NULL,
  group = NULL,
  linetype = NULL,
  label = NULL,
  feature_label = "feature_id",
  fixed = list(shape = 15, size = 3),
  nx = 0,
  ny = 0,
  colorpalette = make_svar_palette(object, color),
  alphapalette = make_alpha_palette(object, alpha),
  title = paste0(method, guess_fitsep(fdt(object)), by),
  theme = ggplot2::theme(plot.title = element_text(hjust = 0.5), panel.grid =
    element_blank())
)
```

Arguments

object	SummarizedExperiment
method	'pca', 'pls', 'lda', 'spls', 'opls', 'sma'
by	svar
dims	numeric vector: e.g. 1:2
color	svar
shape	svar
size	svar
alpha	svar
group	svar
linetype	svar
label	svar
feature_label	fvar
fixed	fixed plot aesthetics
nx	number of x features to plot
ny	number of y features to plot
colorpalette	character vector
alphapalette	character vector
title	string
theme	ggplot2::theme output

Value

ggplot object

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% pca(ndim = 4)
object %>% pls(ndim = 4)
biplot(object)
biplot(object, nx = 1)
biplot(object, dims = 3:4, nx = 1)
biplot(object, method = 'pls')
biplot(object, method = 'pls', dims = 3:4)
biplot(object, method = 'pls', dims = 3:4, group = 'Subject')
```

biplot_corrections *Biplot batch corrections*

Description

Biplot batch corrections

Usage

```
biplot_corrections(
  object,
  method = "pca",
  by = "sample_id",
  color = "subgroup",
  covariates = character(0),
  varcols = ceiling(sqrt(1 + length(covariates))),
  plot = TRUE
)
```

Arguments

object	SummarizedExperiment
method	'pca', 'pls', 'lda', or 'sma'
by	svar
color	variable mapped to color (symbol)
covariates	covariates to be batch-corrected
varcols	number of covariate columns
plot	TRUE/FALSE: plot?

Value

grid object

See Also

`biplot_covariates`

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file, pca = TRUE, plot = FALSE)
biplot_corrections(object, color = 'subgroup', covariates = c('Sex', 'Diabetes', 'Subject', 'Time'))
```

`biplot_covariates` *Biplot covariates*

Description

Biplot covariates

Usage

```
biplot_covariates(
  object,
  method = "pca",
  by = "sample_id",
  block = NULL,
  covariates = "subgroup",
  ndim = 6,
  dimcols = 1,
  varcols = length(covariates),
  plot = TRUE
)
```

Arguments

<code>object</code>	SummarizedExperiment
<code>method</code>	'pca', 'pls', 'lda', or 'sma'
<code>by</code>	svar
<code>block</code>	svar
<code>covariates</code>	covariates: mapped to color or batch-corrected
<code>ndim</code>	number of dimensions to plot
<code>dimcols</code>	number of dimension columns
<code>varcols</code>	number of covariate columns
<code>plot</code>	TRUE or FALSE: whether to plot

Value

ggplot object

See Also

biplot_corrections

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file, pca = TRUE)
biplot_covariates(object, covariates = 'subgroup', ndim = 12, dimcols = 3)
biplot_covariates(object, covariates = c('Sex', 'Diabetes', 'Subject', 'Time'))
biplot_covariates(object, covariates = c('Sex', 'Diabetes', 'Subject', 'Time'), ndim = 2)
biplot_covariates(object, covariates = c('subgroup'), dimcols = 3)
```

block2lme

Put block in lme-compatible format

Description

Put block in lme-compatible format

Usage

```
block2lme(block, ...)

## S3 method for class 'list'
block2lme(block, verbose = TRUE, ...)

## S3 method for class 'formula'
block2lme(block, verbose = TRUE, ...)

## S3 method for class 'character'
block2lme(block, verbose = TRUE, ...)

formula2lmer(formula, block)

formula2lm(formula, block)

block_vars(formula)
```

Arguments

block	block: charactervector or formula
...	required for s3 dispatch
verbose	TRUE or FALSE
formula	formula

Examples

```
# lme: ensure lme-compatible block specification
block2lme( block = list(subject = ~1, batch = ~1))
block2lme( block = ~1|subject)
block2lme( block = c('subject', 'batch'))

# lm: integrate block into formula as random effect
formula2lm( formula = ~ subgroup, block = c('subject', 'batch') )

# lmer: integrate block into formula as fixed effect
formula2lmer( formula = ~ subgroup, block = c('subject', 'batch') )
formula2lmer( formula = ~ subgroup + (1|subject) + (1|batch) )
```

center

Center samples

Description

Center samples

Usage

```
center(
  object,
  selector = rep(TRUE, nrow(object)) == TRUE,
  fun = "median",
  verbose = TRUE
)
```

Arguments

object	SummarizedExperiment
selector	logical vector (length = nrow(object))
fun	aggregation function (string)
verbose	TRUE/FALSE

Value

SummarizedExperiment

Examples

```
require(matrixStats)
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
fdt(object)$housekeeping <- FALSE
fdt(object)$housekeeping[order(rowVars(values(object)))[1:5]] <- TRUE
```

```
values(object)[, object$subgroup=='Adult'] %>% magrittr::add(5)
plot_sample_densities(object)
plot_sample_densities(center(object))
plot_sample_densities(center(object, housekeeping))
```

code

*Contrast Code Factor***Description**

Contrast Code Factor for General Linear Model

Usage

```
code(object, ...)

## S3 method for class 'factor'
code(object, codingfun, verbose = TRUE, ...)

## S3 method for class 'data.table'
code(object, codingfun, vars = names(object), verbose = TRUE, ...)

contr.treatment.explicit(n)

code_control(n)

contr.diff(n)

code_diff(n)

code_diff_forward(n)

code_deviation(n)

code_deviation_first(n)

code_helmert(n)

code_helmert_forward(n)
```

Arguments

object	factor vector
...	used for s3 dispatch
codingfun	factor coding function <ul style="list-style-type: none"> • contr.treatment: intercept = y0, coefi = yi - y0 • contr.treatment.explicit: intercept = y0, coefi = yi - y0

		<ul style="list-style-type: none"> • code_control: intercept = ymean, coefi = yi - y0 • contr.diff: intercept = y0, coefi = yi - y(i-1) • code_diff: intercept = ymean, coefi = yi - y(i-1) • code_diff_forward: intercept = ymean, coefi = yi - y(i+) • code_deviation: intercept = ymean, coefi = yi - ymean (drop last) • code_deviation_first: intercept = ymean, coefi = yi - ymean (drop first) • code_helmert: intercept = ymean, coefi = yi - mean(y0:(yi-1)) • code_helmert_forward: intercept = ymean, coefi = yi - mean(y(i+1):yp)
verbose		TRUE or FALSE
vars		svars
n		character vector

Details

A General Linear Model contains:

- * An Intercept Coefficient: expressing some form of sample average
- * For each numeric variable: a slope coefficient
- * For each k-leveled factor: (k-1) Contrast Coefficients.

The interpretation of (intercept and contrast) coefficients depends on the contrast coding function used. Several contrast coding functions are available in 'stats' and 'codingMatrices'. But their (function and coefficient) namings are a bit confusing and unsystematic. Instead, the functions below offer an intuitive interface (to the otherwise powerful stats/codingMatrices packages). The names of these functions reflect the contrast coding used (treatment, backward, sum, or helmert contrasts). They also reflect the intercept interpretation (either first factor's first level or grand mean). They all produce intuitive coefficient names (e.g. 't1-t0' rather than just 't1'). They all have unit scaling (a coefficient of 1 means a backward of 1).

Value

(explicitly coded) factor vector

Examples

```
# Coding functions
x <- factor(paste0('t', 0:3))
xlevels <- levels(x)
contr.treatment(      xlevels)
contr.treatment.explicit(xlevels)
contr.diff(           xlevels)
code_control(         xlevels)
code_diff(            xlevels)
code_diff_forward(   xlevels)
code_deviation(       xlevels)
code_deviation_first( xlevels)
code_helmert(          xlevels)
code_helmert_forward( xlevels)

# Code
```

```

x %>% code(contr.treatment)
x %>% code(contr.treatment.explicit)
x %>% code(contr.diff)
x %>% code(code_control)
x %>% code(code_diff)
x %>% code(code_diff_forward)
x %>% code(code_deviation)
x %>% code(code_deviation_first)
x %>% code(code_helmert)
x %>% code(code_helmert_forward)

# Model
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% fit_limma(codingfun = contr.treatment) # default
object %>% fit_limma(codingfun = contr.treatment.explicit)
object %>% fit_limma(codingfun = contr.diff)
object %>% fit_limma(codingfun = code_control)
object %>% fit_limma(codingfun = code_diff)
object %>% fit_limma(codingfun = code_diff_forward)
object %>% fit_limma(codingfun = code_deviation)
object %>% fit_limma(codingfun = code_deviation_first)
object %>% fit_limma(codingfun = code_helmert)
object %>% fit_limma(codingfun = code_helmert_forward)

```

coefs

*Get coefs***Description**

Get coefs

Usage

```

coefs(featuredt, ...)

## S3 method for class 'factor'
coefs(featuredt, ...)

## S3 method for class 'data.table'
coefs(featuredt, fit = fits(featuredt), svars = NULL, ...)

```

Arguments

featuredt	data.table or factor
...	required for s3 dispatch
fit	string: 'limma', 'lm', 'lme', 'lmer'
svars	NULL or charactervector (svar for which to return coefs)

Value

character vector

Examples

```
# Factor
x <- factor(c('A', 'B', 'C'))
coefs(x)
coefs(code(x, contr.treatment.explicit))
coefs(code(x, code_control))

# SummarizedExperiment
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file, fit = 'limma')
coefs(fdt(object))
```

collapsed_entrezg_to_symbol

Collapsed entrezg to genesymbol

Description

Collapsed entrezg to genesymbol

Usage

```
collapsed_entrezg_to_symbol(x, sep, orgdb)
```

Arguments

x	charactervector
sep	string
orgdb	OrgDb

Value

character vector

Examples

```
if (requireNamespace('org.Hs.eg.db', quiet = TRUE)){
  x <- c('7448/3818/727', '5034/9601/64374')
  orgdb <- org.Hs.eg.db::org.Hs.eg.db
  collapsed_entrezg_to_symbol(x, sep = '/', orgdb = orgdb)
}
```

COMPOUNDDISCOVERER_PATTERNS

compound discoverer quantity patterns

Description

compound discoverer quantity patterns

Usage

COMPOUNDDISCOVERER_PATTERNS

Format

An object of class character of length 2.

Examples

COMPOUNDDISCOVERER_PATTERNS

CONTAMINANTSURL

Contaminants URL

Description

Contaminants URL

Usage

CONTAMINANTSURL

Format

An object of class character of length 1.

Examples

CONTAMINANTSURL

`contrast_subgroup_cols`

Row/Col contrasts

Description

Row/Col contrasts

Usage

```
contrast_subgroup_cols(object, subgroupvar)
contrast_subgroup_rows(object, subgroupvar)
```

Arguments

object	SummarizedExperiment
subgroupvar	svar

Value

matrix

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object$subgroup <- paste0(object$Diabetes, '.', object$Time)
subgroup_matrix(object, subgroupvar = 'subgroup')
contrast_subgroup_cols(object, subgroupvar = 'subgroup')
contrast_subgroup_rows(object, subgroupvar = 'subgroup')
```

`counts`

Get/Set counts

Description

Get / Set counts matrix

Usage

```
counts(object)

## S4 method for signature 'SummarizedExperiment'
counts(object)

counts(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
counts(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,numERIC'
counts(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,NULL'
counts(object) <- value
```

Arguments

object	SummarizedExperiment
value	count matrix (features x samples)

Value

count matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnased_counts(file)
counts(object)[1:3, 1:3]
counts(object) <- values(object)
```

counts2cpm

Convert between counts and cpm/tpm

Description

Convert between counts and cpm/tpm

Usage

```
counts2cpm(x, libsize = scaledlibsizes(x))

cpm2counts(x, libsize)
```

Arguments

x	count/cpm matrix
libsize	(scaled) libsize vector

Value

cpm/tpm/count matrix

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnased_counts(file)
libsize <- scaledlibsizes(counts(object))
tpm <- counts2tpm(counts(object), genesize = 1)
cpm <- counts2cpm(counts(object), libsize)
counts <- cpm2counts(cpm, libsize)
sum(counts(object) - counts)
```

counts2tpm

counts to tpm

Description

counts to tpm

Usage

```
counts2tpm(x, genesize)
```

Arguments

x	count matrix
genesize	genesize vector (kilobase)

Value

tpm matrix

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnased_counts(file)
counts(object)[1:3, 1:3]
counts2tpm(counts(object), genesize = 1)[1:3, 1:3]
```

`count_in`*Count/Collapse in/outside intersection*

Description

Count/Collapse in/outside intersection

Usage

```
count_in(x, ...)

## S3 method for class 'character'
count_in(x, y, ...)

## S3 method for class 'factor'
count_in(x, y, ...)

## S3 method for class 'list'
count_in(x, y, ...)

collapse_in(x, ...)

## S3 method for class 'character'
collapse_in(x, y, sep, ...)

## S3 method for class 'factor'
collapse_in(x, y, sep, ...)

## S3 method for class 'list'
collapse_in(x, y, sep, ...)

count_out(x, ...)

## S3 method for class 'character'
count_out(x, y, ...)

## S3 method for class 'factor'
count_out(x, y, ...)

## S3 method for class 'list'
count_out(x, y, ...)
```

Arguments

<code>x</code>	character OR list
<code>...</code>	used for S3 dispatch

y	character
sep	string

Value

number OR numeric

Examples

```
# Sets
contrast1 <- c('a', 'b', 'c', 'd')
pathway <- c('c', 'd', 'e', 'f')
contrast2 <- c('e', 'f', 'g', 'h')

# Count outside
count_out(contrast1, pathway)
count_out(list(contrast1 = contrast1, contrast2 = contrast2), pathway)

# Count inside
count_in(contrast1, pathway)
count_in(list(contrast1 = contrast1, contrast2 = contrast2), pathway)

# Collapse inside
collapse_in(contrast1, pathway, sep = ' ')
collapse_in(list(contrast1 = contrast1, contrast2 = contrast2), pathway, sep = ' ')
```

Description

Get / Set cpm matrix

Usage

```
cpm(object)

## S4 method for signature 'SummarizedExperiment'
cpm(object)

cpm(object) <- value

## S4 replacement method for signature 'SummarizedExperiment, matrix'
cpm(object) <- value

## S4 replacement method for signature 'SummarizedExperiment, numeric'
cpm(object) <- value
```

Arguments

object	SummarizedExperiment
value	cpm matrix (features x samples)

Value

cpm matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnased_counts(file)
cpm(object)[1:3, 1:3]
cpm(object) <- values(object)
```

create_design

Create design

Description

Create design matrix for statistical analysis

Usage

```
create_design(object, ...)

## S3 method for class 'SummarizedExperiment'
create_design(
  object,
  formula = default_formula(object),
  drop = varlevels_dont_clash(object, all.vars(formula)),
  codingfun = contr.treatment,
  verbose = TRUE,
  ...
)

## S3 method for class 'data.table'
create_design(
  object,
  formula = default_formula(object),
  drop = varlevels_dont_clash(object, all.vars(formula)),
  codingfun = contr.treatment,
  verbose = TRUE,
  ...
)
```

Arguments

object	SummarizedExperiment or data.frame
...	required to s3ify
formula	formula with svars
drop	whether to drop predictor names
codingfun	<p>factor coding function</p> <ul style="list-style-type: none"> • contr.treatment: intercept = y_0, coefi = $y_i - y_0$ • contr.treatment.explicit: intercept = y_0, coefi = $y_i - y_0$ • code_control: intercept = ymean, coefi = $y_i - y_0$ • contr.diff: intercept = y_0, coefi = $y_i - y_{(i-1)}$ • code_diff: intercept = ymean, coefi = $y_i - y_{(i-1)}$ • code_diff_forward: intercept = ymean, coefi = $y_i - y_{(i+)}$ • code_deviation: intercept = ymean, coefi = $y_i - y_{(i-1)}$ (drop last) • code_deviation_first: intercept = ymean, coefi = $y_i - y_{(i-1)}$ (drop first) • code_helmert: intercept = ymean, coefi = $y_i - \text{mean}(y_0:(y_{i-1}))$ • code_helmert_forward: intercept = ymean, coefi = $y_i - \text{mean}(y_{(i+1)}:y_p)$
verbose	whether to message

Value

design matrix

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
unique(create_design(object))
unique(create_design(object, ~ Time))
unique(create_design(object, ~ Time, codingfun = contr.treatment.explicit))
unique(create_design(object, ~ Time, codingfun = contr.diff))
unique(create_design(object, ~ Time + Diabetes))
unique(create_design(object, ~ Time / Diabetes))
unique(create_design(object, ~ Time * Diabetes))
```

Description

Download autonomics example data

Usage

```
DATADIR

download_data(
  filename = NULL,
  localdir = file.path(DATADIR, split_extract_fixed(filename, ".", 1)),
  verbose = TRUE,
  force = FALSE
)
```

Arguments

<code>filename</code>	file name		
'atkin.somascan.adat'	Halama, 2018	effects of hypoglycemia	
'atkin.metabolon.xlsx'			
'billing16.bam.zip'	Billing, 2016	stemcell comparison	
'billing16.rnacounts.txt'			
'billing16.somascan.adat'			
'billing16.proteingroups.txt'			
'billing19.rnacounts.txt'	Billing, 2016	stemcell differentiation	
'billing19.proteingroups.txt'			
'billing19.phosphosites.txt'			
'ddglucose.proteingroups.txt'	Omics Module	glycolysis inhibitor	
'fukuda20.proteingroups.txt'	Fukuda, 2020	zebrafish development	
'halama18.metabolon.xlsx'	Halama, 2018	glutaminase inhibitor	
<code>localdir</code>	local dir to save file to		
<code>verbose</code>	TRUE / FALSE		
<code>force</code>	TRUE / FALSE		

Format

An object of class character of length 1.

Value

local file path

Examples

```
# Show available datasets
download_data()

# atkin 2018 - hypoglycemia - pubmed 30525282
# download_data('atkin.somascan.adat')          # somascan intensities
# download_data('atkin.metabolon.xlsx')          # metabolon intensities

# billing16 - stemcell characterization - pubmed 26857143
```

```

# download_data('billing16.proteingroups.txt')      # proteingroup ratios
# download_data('billing16.somascan.adat')          # somascan intensities
# download_data('billing16.rnacounts.txt')           # rnaseq counts
# download_data('billing16.bam.zip')                 # rnaseq alignments

# billing19 - stemcell differentiation - pubmed 31332097
# download_data('billing19.proteingroups.txt')      # proteingroup ratios
# download_data('billing19.phosphosites.txt')        # phosphosite ratios
# download_data('billing19.rnacounts.txt')           # rnaseq counts

# fukuda20 - heart regeneration - pubmed PXD016235
# download_data('fukuda20.proteingroups.txt')        # proteingroup LFQ

# halama18 - glutaminase inhibition - pubmed 30525282
# download_data('halama18.metabolon.xlsx')           # metabolon intensities

```

default_geom*Default geom***Description**

Default geom

Usage

```
default_geom(object, x, block = NULL)
```

Arguments

object	SummarizedExperiment
x	svar
block	svar or NULL

Value

character vector

Examples

```

file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object$Age <- runif(min = 20, max = 60, n = ncol(object))
svars(object)
default_geom(object, x = 'Age')
default_geom(object, x = c('Age', 'Diabetes'))
default_geom(object, x = c('Age', 'Diabetes'), block = 'Subject')

```

default_sfile	<i>Default sfile</i>
---------------	----------------------

Description

Default sfile

Usage

```
default_sfile(file)
```

Arguments

file	data file
------	-----------

Value

sample file

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
default_sfile(file)
```

default_subgroupvar	<i>Create default formula</i>
---------------------	-------------------------------

Description

Create default formula

Usage

```
default_subgroupvar(object)
default_formula(object)
```

Arguments

object	SummarizedExperiment
--------	----------------------

Value

formula

Examples

```
# Abundances
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
default_formula(object)
file <- download_data('billing16.proteingroups.txt')
object <- read_maxquant_proteingroups(file)
default_formula(object)
```

demultiplex

Demultiplex snames

Description

Demultiplex maxquant sampenames

Usage

```
demultiplex(x, verbose = FALSE)
```

Arguments

x	character vector
verbose	TRUE or FALSE

Details

$$WT(L).KD(H).R1\{H/L\} \rightarrow KD_WT.R1 WT(1).KD(2).R1\{1\} \rightarrow WT.R1 WT.R1 \rightarrow WT.R1$$

Value

character

Examples

```
# uniplexed / intensity / ratio
demultiplex(c('KD.R1','OE.R1'))
demultiplex(c('WT(L).KD(M).OE(H).R1\{M\}', 'WT(L).KD(M).OE(H).R1\{H\}'))
demultiplex(c('WT(L).KD(M).OE(H).R1\{M/L\}', 'WT(L).KD(M).OE(H).R1\{H/L\}'))
# run / replicate
demultiplex(c('WT(L).OE(H).R1\{L\}', 'WT(L).OE(H).R1\{H\}') ) # run
demultiplex(c('WT.R1(L).OE.R1(H)\{L\}', 'WT.R1(L).OE.R1(H)\{H\}') ) # repl
# label / index
demultiplex(c('WT(L).OE(H).R1\{L\}', 'WT(L).OE(H).R1\{H\}') ) # label
demultiplex(c('WT(1).OE(2).R1\{1\}', 'WT(1).OE(2).R1\{2\}') ) # index
# with unused channels
demultiplex('WT(1).KD(2).OE(3).R1\{6\}')
```

dequantify	<i>Dequantify maxquant snames</i>
------------	-----------------------------------

Description

Drop quantity ('Reporter intensity').
Encode channel as suffix.

Usage

```
dequantify(x, quantity = guess_maxquant_quantity(x), verbose = FALSE)
```

Arguments

x	character
quantity	'ratio', 'normalizedratio', 'LFQ intensity', 'intensity', 'labeledintensity' 'reporterintensity', 'correctedreporterintensit
verbose	TRUE or FALSE

Details

Ratio H/L WT(L).KD(H).R1 → WT(L).KD(H).R1{H/L}	LFQ intensity WT.R1 → WT.R1
Reporter intensity 0 WT(126).KD(127).R1 → WT(1).KD(2).R1{1}	

Value

character

Examples

```
dequantify(c('Ratio H/L WT(L).KD(M).OE(H).R1',           # Ratios
            'Ratio M/L WT(L).KD(M).OE(H).R1'))
dequantify(c('Ratio H/L normalized WT(L).KD(M).OE(H).R1', # Norm. Ratios
            'Ratio M/L normalized WT(L).KD(M).OE(H).R1'))
dequantify(c('LFQ intensity WT.R1',                      # LFQ intensity
            'LFQ intensity KD.R1'))
dequantify(c('Reporter intensity 1 WT(126).KD(127).R1',   # Rep.intensities
            'Reporter intensity 2 WT(126).KD(127).R1'))
```

`dequantify_componddiscoverer`
dequantify_componddiscoverer compound discoverer snames

Description

Drop quantity.

Usage

```
dequantify_componddiscoverer(
  x,
  quantity = guess_componddiscoverer_quantity(x),
  verbose = FALSE
)
```

Arguments

x	character
quantity	'area', 'normalizedarea'
verbose	TRUE or FALSE

Details

Norm. Area: 20230908_F143_HILICNEG.raw (F11) -> 20230908_F143_HILICNEG.raw (F11)
 Area: 20230908_F143_HILICNEG.raw (F11) -> 20230908_F143_HILICNEG.raw (F11)

Value

character

Examples

```
dequantify_componddiscoverer("Norm. Area: 20230908_F143_HILICNEG.raw (F11)") # Norm. Area
dequantify_componddiscoverer("Area: 20230908_F143_HILICNEG.raw (F11)") # Area
```

`download_contaminants` *Downloads contaminants*

Description

Downloads contaminants

Usage

```
download_contaminants(url = CONTAMINANTSURL, overwrite = FALSE)
```

Arguments

url	contaminants file url (string)
overwrite	TRUE or FALSE: overwrite existing download?

Value

filename (string)

Examples

```
download_contaminants()           # download first time
download_contaminants(overwrite = TRUE) # download each time
```

download_gtf

Download GTF file

Description

Download GTF file with feature annotations

Usage

```
download_gtf(
  organism,
  release = 100,
  gtffile = sprintf("%s/gtf/%s", R_user_dir("autonomics", "cache"),
    basename(make_gtf_url(organism, release)) %>% substr(1, nchar(.) - 3)))
)
```

Arguments

organism	'Homo sapiens', 'Mus musculus' or 'Rattus norvegicus'
release	GTF release (number)
gtffile	string: path to local GTF file

Value

gtffile path

Examples

```
organism <- 'Homo sapiens'
# download_gtf(organism)
```

```
download_mcclain21      Download mcclain21 data
```

Description

Download mcclain21 data

Usage

```
download_mcclain21(  
  counts_or_samples = "counts",  
  localdir = file.path(DATADIR, "mcclain21"),  
  force = FALSE  
)
```

Arguments

counts_or_samples	'counts' or 'samples'
localdir	dirname
force	TRUE or FALSE

Details

Mc clain 2021: COVID19 transcriptomics:

Examples

```
download_mcclain21('counts')  
download_mcclain21('samples')
```

```
download_tcga_example  Download tcga example
```

Description

Download tcga example

Usage

```
download_tcga_example()
```

<code>dt2mat</code>	<i>'data.table' to 'matrix'</i>
---------------------	---------------------------------

Description

Convert between ‘`data.table`‘ and ‘`matrix`‘

Usage

```
dt2mat(x)

mat2dt(x, idvar)
```

Arguments

<code>x</code>	<code>data.table / matrix</code>
<code>idvar</code>	<code>idvar string</code>

Value

`matrix / data.table`

Examples

```
x <- data.table::data.table(
  gene      = c('ENSG001', 'ENSG002', 'ENSG003'),
  sampleA  = c(1787, 10, 432),
  sampleB  = c(1143, 3, 268))
dt2mat(x)
mat2dt(dt2mat(x), 'gene')
```

<code>enrichment</code>	<i>Enrichment analysis</i>
-------------------------	----------------------------

Description

Are selected genes enriched in pathway?

Usage

```
enrichment(
  object,
  pathwaydt,
  fit = fits(fdt(object))[1],
  coef = coefs(fdt(object), fit = fit)[1],
  var = abstractvar(fdt(object), fit = fit, coef = coef),
```

```

levels = fdt(object)[[var]] %>% base::levels() %>% extract(-1),
genevar = "gene",
genesep = "[ ,;]",
n = 3,
verbose = TRUE,
genes = FALSE
)

```

Arguments

object	SummarizedExperiment
pathwaydt	pathway data.table
fit	string
coef	string
var	selection fvar
levels	selection levels
genevar	gene fvar
genesep	gene separator (string)
n	number
verbose	whether to msg
genes	whether to report genes

Details

Four enrichment analyses per geneset using the Fisher Exact Test (see four pvalues). Results are returned in a data.table

in	: genes in pathway
in.det	: detected genes in pathway
in.sel	: up/downregulated genes in pathway
in.up(.genes)	: upregulated genes in pathway
in.down(.genes)	: downregulated genes in pathway
out	: genes outside pathway
det	: detected genes (in + out)
sel	: up/downregulated genes (in + out)
up	: upregulated genes (in + out)
down	: downregulated genes (in + out)
p.coef.upDET	: prob to randomly select this many (or more) upregulated genes (among detected genes)
p.coef.downDET	: prob to randomly select this many (or more) downregulated genes (among detected genes)
p.coef.selDET	: prob to randomly select this many (or more) up OR downregulated genes (among detected genes)
p.coef.selGEN	: prob to randomly select this many (or more) up OR downregulated genes (among genome genes)
p.detGEN	: prob to randomly select this many (or more) detected genes (among genome genes)

Examples

```
# Read
pathwaydt <- read_msigdt(collections = 'C5:GO:BP')
file <- system.file('extdata/atkin.somascan.adat', package = 'autonomics')
object <- read_somascan(file, fit = 'limma', coefs = 't1')
fvars(object) %<% gsub('EntrezGeneSymbol', 'gene', .)
object %>% abstract_fit()
var <- abstractvar(fdt(object))
varlevels <- c('flat', 'down', 'up')
enrichdt1 <- enrichment(object, pathwaydt, var = var) # 2:n factor
enrichdt2 <- enrichment(object, pathwaydt, var = var, levels = varlevels) # 1:n factor
enrichdt3 <- altenrich(object, pathwaydt) # alternative implementation
cols <- intersect(names(enrichdt1), names(enrichdt3))
all(enrichdt1[, cols, with = FALSE] == enrichdt3[, cols, with = FALSE]) # identical
```

ens2org

taxon/ens to organism

Description

taxon/ens to organism

Usage

```
ens2org(x)
```

```
taxon2org(x)
```

Arguments

x	character vector
---	------------------

Value

character vector

Examples

```
taxon2org( x = c('9606', '9913') )
ens2org( x = c('ENSP00000377550', 'ENSBTAP00000038329') )
```

`entrezg_to_symbol` *Entrezg to genesymbol*

Description

Entrezg to genesymbol

Usage

```
entrezg_to_symbol(x, orgdb)
```

Arguments

<code>x</code>	charactervector
<code>orgdb</code>	OrgDb

Value

character vector

Examples

```
if (requireNamespace('org.Hs.eg.db', quiet = TRUE)){
  orgdb <- org.Hs.eg.db::org.Hs.eg.db
  entrezg_to_symbol(x = c('7448', '3818', '727'), orgdb)
}
```

`explore_transformations` *Explore transformations*

Description

Explore transformations

Usage

```
explore_transformations(
  object,
  subgroupvar = "subgroup",
  transformations = c("quantnorm", "vsn", "zscore", "invnorm"),
  method = "pca",
  xdim = 1,
  ydim = 2,
  ...
)
```

Arguments

object	SummarizedExperiment
subgroupvar	string
transformations	
	vector
method	'pca', 'pls', 'sma', or 'lda'
xdim	number (default 1)
ydim	number (default 2)
...	passed to plot_data

Value

grid object

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
subgroups <- sprintf('%s_STD', c('E00','E01','E02','E05','E15','E30','M00'))
object <- read_maxquant_proteingroups(file, subgroups = subgroups)
explore_transformations(object, transformations = c('quantnorm', 'zscore', 'invnorm'))
```

extract_rectangle *Extract rectangle from omics file, data.table, or matrix*

Description

Extract rectangle from omics file, data.table, or matrix

Usage

```
extract_rectangle(x, ...)

## S3 method for class 'character'
extract_rectangle(
  x,
  rows = seq_len(nrows(x, sheet = sheet)),
  cols = seq_len(ncols(x, sheet = sheet)),
  verbose = FALSE,
  transpose = FALSE,
  drop = FALSE,
  sheet = 1,
  ...
)

## S3 method for class 'data.table'
```

```

extract_rectangle(  

  x,  

  rows = seq_len(nrow(x)),  

  cols = seq_len(ncol(x)),  

  transpose = FALSE,  

  drop = FALSE,  

  ...  

)  
  

## S3 method for class 'matrix'  

extract_rectangle(  

  x,  

  rows = seq_len(nrow(x)),  

  cols = seq_len(ncol(x)),  

  transpose = FALSE,  

  drop = FALSE,  

  ...  

)

```

Arguments

x	omics datafile or datatable
...	allow for S3 method dispatch
rows	numeric vector
cols	numeric vector
verbose	logical
transpose	logical
drop	logical
sheet	numeric or string

Value

matrix

Examples

```

# FROM FILE: extract_rectangle.character
#=====
x <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
extract_rectangle(x, rows = 11:30, cols = 15:81, sheet = 2)[ 1:3, 1:3 ] # exprs
extract_rectangle(x, rows = 11:30, cols = 2,      sheet = 2)[ 1:3,      ] # fids
extract_rectangle(x, rows = 4,      cols = 15:81, sheet = 2)[      , 1:3 ] # sids
extract_rectangle(x, rows = 10:30, cols = 1:14,   sheet = 2)[ 1:3, 1:3 ] # fdt
extract_rectangle(x, rows = 1:10,  cols = 14:81,  sheet = 2, transpose = TRUE)[1:3, 1:3] # sdt

# FROM MATRIX: extract_rectangle.matrix
#=====
x <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')

```

```

x %>% extract_rectangle(sheet = 2)
extract_rectangle(x, rows = 11:30, cols = 15:81, sheet = 2)[ 1:3, 1:3 ] # exprs
extract_rectangle(x, rows = 11:30, cols = 2, sheet = 2)[ 1:3, ] # fids
extract_rectangle(x, rows = 4, cols = 15:81, sheet = 2)[ , 1:3 ] # sids
extract_rectangle(x, rows = 10:30, cols = 1:14, sheet = 2)[ 1:3, 1:3 ] # fdt
extract_rectangle(x, rows = 1:10, cols = 14:81, sheet = 2, transpose = TRUE)[1:3, 1:3] # sdt

```

fcluster*Cluster features***Description**

Cluster features

Usage

```

fcluster(
  object,
  cormat,
  method = c("pamk", "hclust", "apcluster")[1],
  k = 3,
  verbose = TRUE
)

```

Arguments

object	SummarizedExperiment
cormat	correlation matrix
method	'pamk', 'hclust', 'apcluster'
k	number
verbose	TRUE or FALSE

Value

matrix

Examples

```

file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
fdt(object) %>% extract(, 1)
cormat <- fcov(object)
object %>% fcluster(cormat, method = c('pamk', 'apcluster', 'hclust'), k = 3)
fdt(object)

```

fcor	<i>Correlate features</i>
------	---------------------------

Description

Correlate features

Usage

```
fcor(object, verbose = TRUE)
```

Arguments

object	SummarizedExperiment
verbose	TRUE or FALSE

Value

matrix

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
fdt(object) %>% extract(, 1)
cormat <- fcor(object)
```

fdata	<i>Get/Set sample/feature data</i>
-------	------------------------------------

Description

Get/Set sample/feature data

Usage

```
fdata(object)

sdata(object)

fdt(object)

sdt(object)

## S4 method for signature 'SummarizedExperiment'
fdata(object)
```

```
## S4 method for signature 'SummarizedExperiment'
sdata(object)

## S4 method for signature 'SummarizedExperiment'
fdt(object)

## S4 method for signature 'SummarizedExperiment'
sdt(object)

fdata(object) <- value

sdata(object) <- value

fdt(object) <- value

sdt(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,data.frame'
fdata(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,data.frame'
sdata(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,DataFrame'
sdata(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,data.table'
fdt(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,data.table'
sdt(object) <- value
```

Arguments

object	SummarizedExperiment
value	data.frame/data.table

Value

data.frame/data.table (get) or updated object (set)

Examples

```
# Read data
  file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
  object <- read_maxquant_proteingroups(file)
# sdt/fdt
  sdt(object)[1:3, ]
```

```

fdt(object)[1:3, ]
sdt(object) %<>% cbind(b=1)
fdt(object) %<>% cbind(b=1)
sdt(object)
fdt(object)
# sdata/fdata
sdata(object)[1:3, ]
fdata(object)[1:3, ]
sdata(object) %<>% cbind(a=1)
fdata(object) %<>% cbind(a=1)
sdata(object)[1:3, ]
fdata(object)[1:3, ]

```

fdr2p*fdr to p***Description**

fdr to p

Usage`fdr2p(fdr)`**Arguments**

fdr	fdr values
-----	------------

Examples

```

# Read/Fit
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %<>% fit_limma()
pcol <- pvar(fdt(object), fit = 'limma', coef = 't3')
object %<>% extract(order(fdt(.)[[pcol]]), )
object %<>% extract(1:10, )
fdt(object) %<>% extract(, 1)
object %<>% fit_limma(coefs = 't3')
# fdr2p
fdt(object)[[pcol]]
fdt(object)[[pcol]] %>% p.adjust(method = 'fdr')
fdt(object)[[pcol]] %>% p.adjust(method = 'fdr') %>% fdr2p()

```

```
filter_exprs_replicated_in_some_subgroup
```

Filter features with replicated expression in some subgroup

Description

Filter features with replicated expression in some subgroup

Usage

```
filter_exprs_replicated_in_some_subgroup(  
  object,  
  subgroupvar = "subgroup",  
  assay = assayNames(object)[1],  
  comparator = if (contains_ratios(object)) "!=" else ">",  
  lod = 0,  
  nsample = 2,  
  nsubgroup = 1,  
  verbose = TRUE  
)
```

Arguments

object	SummarizedExperiment
subgroupvar	subgroup svar
assay	string
comparator	'>' or '!='
lod	number: limit of detection
nsample	number
nsubgroup	number
verbose	TRUE or FALSE

Value

Filtered SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')  
object <- read_metabolon(file)  
object %>% filter_exprs_replicated_in_some_subgroup()  
filter_exprs_replicated_in_some_subgroup(object, character(0))  
filter_exprs_replicated_in_some_subgroup(object, NULL)
```

<code>filter_features</code>	<i>Filter features on condition</i>
------------------------------	-------------------------------------

Description

Filter features on condition

Usage

```
filter_features(object, condition, verbose = TRUE)
```

Arguments

<code>object</code>	SummarizedExperiment
<code>condition</code>	filter condition
<code>verbose</code>	logical

Value

filtered eSet

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
filter_features(object, SUPER_PATHWAY == 'Lipid')
```

<code>filter_medoid</code>	<i>Filter medoid sample</i>
----------------------------	-----------------------------

Description

Filter medoid sample

Usage

```
filter_medoid(object, by = NULL, verbose = FALSE)
```

Arguments

<code>object</code>	SummarizedExperiment
<code>by</code>	svar
<code>verbose</code>	whether to message

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnaseq_counts(file, plot = FALSE)
object %>% filter_medoid(by = 'subgroup', verbose=TRUE)
```

filter_samples *Filter samples on condition*

Description

Filter samples on condition

Usage

```
filter_samples(object, condition, verbose = TRUE, record = TRUE)
```

Arguments

object	SummarizedExperiment
condition	filter condition
verbose	TRUE/FALSE
record	TRUE/FALSE

Value

filtered SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
filter_samples(object, subgroup != 't0', verbose = TRUE)
```

fit	<i>Fit model and test for differential expression</i>
------------	---

Description

Fit model and test for differential expression

Usage

```

fit(  

  object,  

  formula = default_formula(object),  

  engine = "limma",  

  drop = varlevels_dont_clash(object, all.vars(formula)),  

  codingfun = contr.treatment,  

  design = create_design(object, formula = formula, drop = drop, codingfun = codingfun),  

  contrasts = NULL,  

  coefs = if (is.null(contrasts)) colnames(design) else NULL,  

  block = NULL,  

  weightvar = if ("weights" %in% assayNames(object)) "weights" else NULL,  

  statvars = c("effect", "p", "se", "t")[1:2],  

  sep = FITSEP,  

  suffix = paste0(sep, "limma"),  

  verbose = TRUE,  

  plot = FALSE  

)  
  

fit_limma(  

  object,  

  formula = default_formula(object),  

  drop = varlevels_dont_clash(object, all.vars(formula)),  

  codingfun = contr.treatment,  

  design = create_design(object, formula = formula, drop = drop, codingfun = codingfun),  

  contrasts = NULL,  

  coefs = if (is.null(contrasts)) colnames(design) else NULL,  

  block = NULL,  

  weightvar = if ("weights" %in% assayNames(object)) "weights" else NULL,  

  statvars = c("effect", "p"),  

  sep = FITSEP,  

  suffix = paste0(sep, "limma"),  

  verbose = TRUE,  

  plot = FALSE  

)  
  

.fit_limma(  

  object,  

  formula = default_formula(object),

```

```

drop = varlevels_dont_clash(object, all.vars(formula)),
codingfun = "treatment",
design = create_design(object, formula = formula, drop = drop, codingfun = codingfun),
contrasts = NULL,
coefs = if (is.null(contrasts)) colnames(design) else NULL,
block = NULL,
weightvar = if ("weights" %in% assayNames(object)) "weights" else NULL,
statvars = c("effect", "p", "se", "t")[1:2],
sep = FITSEP,
suffix = paste0(sep, "limma"),
verbose = TRUE,
plot = FALSE
)

fit_wilcoxon(
  object,
  formula = default_formula(object),
  drop = NULL,
  codingfun = contr.treatment.explicit,
  contrasts = NULL,
  coefs = NULL,
  block = NULL,
  weightvar = NULL,
  statvars = c("effect", "p"),
  sep = FITSEP,
  verbose = TRUE,
  plot = FALSE
)

```

Arguments

object	SummarizedExperiment
formula	modeling formula
engine	'limma', 'lm', 'lme', 'lmer', or 'wilcoxon'
drop	TRUE or FALSE
codingfun	factor coding function <ul style="list-style-type: none"> • contr.treatment: intercept = y_0, coefi = $y_i - y_0$ • contr.treatment.explicit: intercept = y_0, coefi = $y_i - y_0$ • code_control: intercept = ymean, coefi = $y_i - y_0$ • contr.diff: intercept = y_0, coefi = $y_i - y_{(i-1)}$ • code_diff: intercept = ymean, coefi = $y_i - y_{(i-1)}$ • code_diff_forward: intercept = ymean, coefi = $y_i - y_{(i+)}$ • code_deviation: intercept = ymean, coefi = $y_i - y_{\text{mean}}$ (drop last) • code_deviation_first: intercept = ymean, coefi = $y_i - y_{\text{mean}}$ (drop first) • code_helmert: intercept = ymean, coefi = $y_i - \text{mean}(y_0:(y_{i-1}))$ • code_helmert_forward: intercept = ymean, coefi = $y_i - \text{mean}(y_{(i+1)}:y_p)$

design	design matrix
contrasts	NULL or character vector: coefficient contrasts to test
coefs	NULL or character vector: model coefs to test
block	block svar (or NULL)
weightvar	NULL or name of weight matrix in assays(object)
statvars	character vector: subset of c('effect', 'p', 'fdr', 't', 'se')
sep	string: pvar separator ("~" in "p~t2~limma")
suffix	string: pvar suffix ("limma" in "p~t2~limma")
verbose	whether to msg
plot	whether to plot

Value

Updated SummarizedExperiment

Examples

```
# Read
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)

# Standard
fdt(object) %>>% extract(, 'feature_id')
object %>>% fit_lm(      ~ subgroup)                      #      statistics default
object %>>% fit_limma( ~ subgroup)                      # bioinformatics default
summarize_fit(fdt(object))

# Blocked
fdt(object) %>>% extract(, 'feature_id')
object %>>% fit_limma( ~ subgroup, block = 'Subject') #      simple random effects
object %>>% fit_lme(   ~ subgroup, block = 'Subject') #      powerful random effects
object %>>% fit_lmer(  ~ subgroup, block = 'Subject') # more powerful random effects
summarize_fit(fdt(object))

# Alternative coding: e.g. grand mean intercept
fdt(object) %>>% extract(, 'feature_id')
object %>>% fit_limma( ~ subgroup, block = 'Subject', codingfun = code_control)
object %>>% fit_lme(   ~ subgroup, block = 'Subject', codingfun = code_control)
object %>>% fit_lmer(  ~ subgroup, block = 'Subject', codingfun = code_control)
summarize_fit(fdt(object))

# Posthoc contrasts (only limma!)
fdt(object) %>>% extract(, 'feature_id')
object %>>% fit_limma( ~ subgroup, block = 'Subject', codingfun = code_control, coefs ='t1-t0')
object %>>% fit_limma( ~ 0 + subgroup, block = 'Subject', contrasts = 't1-t0')
# flexible, but only approximate
# stat.ethz.ch/pipermail/bioconductor/2014-February/057682.html

# Non-parametric: wilcoxon
```

```
fdt(object) %<-%> extract(, 'feature_id')
object %<-%> fit_wilcoxon( ~ subgroup) # unpaired
object %<-%> fit_wilcoxon( ~ subgroup, block = 'Subject') # paired

# Custom separator
fdt(object) %<-%> extract(, 'feature_id')
fdt( fit_lm(      object, sep = '.')) 
fdt( fit_limma(   object, block = 'Subject', sep = '.') ) 
fdt( fit_lme(     object, block = 'Subject', sep = '.') ) 
fdt( fit_lmer(    object, block = 'Subject', sep = '.') ) 
fdt( fit_wilcoxon(object, block = 'Subject', sep = '.') ) 
fdt( fit_wilcoxon(object, sep = '.') )
```

fitcoefs*fitcoefs*

Description

fitcoefs

Usage

```
fitcoefs(object)
```

Arguments

object	SummarizedExperiment
--------	----------------------

Value

string vector

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
fitcoefs(object)
fitcoefs(fit_limma(object))
```

fits	<i>Get fit models</i>
------	-----------------------

Description

Get fit models

Usage

```
fits(featuredt)
```

Arguments

featuredt	feature data.table
-----------	--------------------

Value

character vector

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file, fit = 'limma')
fits(fdt(object))
```

FITSEP	<i>Fit results separator</i>
--------	------------------------------

Description

Fit results separator

Usage

```
FITSEP
```

```
PPATTERN
```

Format

An object of class character of length 1.

An object of class character of length 1.

Examples

```
FITSEP
```

fitvars	<i>Get fit vars/dt</i>
---------	------------------------

Description

Get fit vars/dt

Usage

```
fitvars(object)  
fitdt(object)
```

Arguments

object	SummarizedExperiment
--------	----------------------

Value

string vector

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')  
object <- read_metabolon(file)  
fitvars(object)  
fitdt(object)  
fitvars(fit_limma(object))  
fitdt(fit_limma(object))
```

fit_lmx	<i>Fit lm, lme, or lmer</i>
---------	-----------------------------

Description

Fit lm, lme, or lmer

Usage

```
fit_lmx(  
  object,  
  fit,  
  formula = default_formula(object),  
  drop = varlevels_dont_clash(object, all.vars(formula)),  
  codingfun = contr.treatment,  
  coefs = colnames(create_design(object, formula = formula, drop = drop, codingfun =
```

```

    codingfun, verbose = FALSE)),
block = NULL,
opt = "optim",
weightvar = if ("weights" %in% assayNames(object)) "weights" else NULL,
statvars = c("effect", "p", "se", "t")[1:2],
sep = FITSEP,
verbose = TRUE,
plot = FALSE
)

fit_lm(
object,
formula = default_formula(object),
drop = varlevels_dont_clash(object, all.vars(formula)),
codingfun = contr.treatment,
block = NULL,
weightvar = if ("weights" %in% assayNames(object)) "weights" else NULL,
statvars = c("effect", "p", "se", "t")[1:2],
sep = FITSEP,
coefs = colnames(create_design(object, formula = formula, drop = drop, codingfun =
codingfun, verbose = FALSE)),
contrasts = NULL,
verbose = TRUE,
plot = FALSE
)

fit_lme(
object,
formula = default_formula(object),
drop = varlevels_dont_clash(object, all.vars(formula)),
codingfun = contr.treatment,
block = NULL,
weightvar = if ("weights" %in% assayNames(object)) "weights" else NULL,
opt = "optim",
statvars = c("effect", "p", "se", "t")[1:2],
sep = FITSEP,
coefs = colnames(create_design(object, formula = formula, drop = drop, codingfun =
codingfun, verbose = FALSE)),
contrasts = NULL,
verbose = TRUE,
plot = FALSE
)

fit_lmer(
object,
formula = default_formula(object),
drop = varlevels_dont_clash(object, all.vars(formula)),
codingfun = contr.treatment,

```

```

block = NULL,
weightvar = if ("weights" %in% assayNames(object)) "weights" else NULL,
statvars = c("effect", "p", "se", "t")[1:2],
sep = FITSEP,
coefs = colnames(create_design(object, formula = formula, drop = drop, codingfun =
  codingfun, verbose = FALSE)),
contrasts = NULL,
verbose = TRUE,
plot = FALSE
)

```

Arguments

object	SummarizedExperiment
fit	'lm', 'lme', or 'lmer'
formula	formula
drop	TRUE or FALSE
codingfun	coding function
coefs	NULL or stringvector
block	NULL or svar
opt	optimizer used in fit_lme: 'optim' (more robust) or 'nlminb'
weightvar	NULL or svar
statvars	character vector: subset of c('effect', 'p', 'fdr', 't')
sep	string
verbose	TRUE or FALSE
plot	TRUE or FALSE
contrasts	unused. only to allow generic get(fitfun)(contrasts)

Value

SummarizedExperiment

Examples

```

file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
fit_lm(    object, formula = ~subgroup)
fit_limma( object, formula = ~subgroup)
fit_limma( object, formula = ~subgroup, block = 'Subject' )
fit_lme(   object, formula = ~subgroup, block = 'Subject' )
fit_lmer(  object, formula = ~subgroup, block = 'Subject' )
# fit_lme( object, formula = ~subgroup, block = ~1|Subject) # needs fine-tuning
# fit_lmer( object, formula = ~subgroup + (1|Subject))      # needs fine-tuning

```

fit_survival	<i>Fit/Plot survival</i>
--------------	--------------------------

Description

Fit/Plot survival

Usage

```
fit_survival(
  object,
  assay = assayNames(object)[1],
  percentile = 25,
  sep = FITSEP,
  samples = if (ncol(object) < 50) TRUE else FALSE,
  verbose = TRUE
)

.plot_survival(
  object,
  assay = assayNames(object)[1],
  percentile = 25,
  title = paste0(assay, " ", percentile, "%"),
  subtitle = NULL,
  palette = c("#009999", "#ff5050")
)

plot_survival(
  object,
  assay = assayNames(object)[1],
  percentile = percentiles(object),
  title = paste0(assay, " ", percentile, "%"),
  subtitle = NULL,
  palette = c("#009999", "#ff5050"),
  n = 4,
  ncol = 4,
  nrow = length(percentile),
  file = NULL,
  width = 7 * ncol,
  height = 7 * nrow
)
```

Arguments

object	SummarizedExperiment
assay	string

percentile	percentage (not greater than 50)
sep	fvar string separator : e.g. '~' gives p~surv~LR50
samples	TRUE or FALSE : record which samples in which stratum ?
verbose	TRUE or FALSE
title	string
subtitle	string
palette	color vector
n	number
ncol	number
nrow	number
file	filepath
width	number
height	number

Value

ggsurvplot

Examples

```

file <- download_tcga_example()
if (!is.null(file) & requireNamespace('survminer')){
  # Read
  object <- readRDS(file)
  object %>>% extract(, .$sample_type == 'T')
  object %>>% extract(c('UGT3A2', 'NSUN3', 'XRCC4', 'WNT10A'), )
  # Fit
  fdt(object)
  fdt(fit_survival(object))
  fdt(fit_survival(object, percentile = 50))
  fdt(fit_survival(object, percentile = 50, sep = '.'))
  # Plot
  object %>>% fit_survival()
  plot_survival(object)
  p1 <- .plot_survival(object[1, ])
  p2 <- .plot_survival(object[2, ])
}

```

Description

Fix excel genes

Usage

```
fix_xlgenes(x)
```

Arguments

x	character
---	-----------

Value

character

Examples

```
x <- c('FAM46B', '15-Sep', '2-Mar', 'MARCHF6')
x
fix_xlgenes(x)
```

flevels	<i>Get fvar levels</i>
---------	------------------------

Description

Get fvar levels

Usage

```
flevels(object, fvar)
```

Arguments

object	SummarizedExperiment
fvar	feature variable

Value

fvar values

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
head(flevels(object, 'feature_id'))
```

fnames	<i>Get/Set fnames</i>
--------	-----------------------

Description

Get/Set feature names

Usage

```
fnames(object)

## S4 method for signature 'SummarizedExperiment'
fnames(object)

fnames(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,character'
fnames(object) <- value
```

Arguments

object	SummarizedExperiment, eSet, or EList
value	character vector with feature names

Value

feature name vector (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
fnames(object) %<-% paste0('protein_', .)
object
```

formula2str	<i>formula to string</i>
-------------	--------------------------

Description

formula to string

Usage

```
formula2str(formula)
```

Arguments

formula	formula
---------	---------

Value

string

Examples

```
formula2str(~0+subgroup)
```

fvalues	<i>Get fvalues</i>
---------	--------------------

Description

Get fvar values

Usage

```
fvalues(object, fvar)
```

Arguments

object	SummarizedExperiment
fvar	feature variable

Value

fvar values

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
head(fvalues(object, 'feature_id'))
fvalues(object, NULL)
```

fvars	<i>Get/Set fvars</i>
-------	----------------------

Description

Get/Set feature variables

Usage

```
fvars(object)

## S4 method for signature 'SummarizedExperiment'
fvars(object)

fvars(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,character'
fvars(object) <- value
```

Arguments

object	SummarizedExperiment
value	character vector with feature variables

Value

feature variables vector (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
fvars(object)[1] %>% paste0('1')
fvars(object)[1]
```

genome_to_orgdb	<i>Get corresponding orgdb</i>
-----------------	--------------------------------

Description

Get corresponding orgdb

Usage

```
genome_to_orgdb(genome)
```

Arguments

genome	'hg38', 'hg19', 'mm10', or 'mm9'
--------	----------------------------------

Value

OrgDb

Examples

```
if (requireNamespace('org.Hs.eg.db', quiet = TRUE)){
  class(genome_to_orgdb('hg38'))
}
```

group_by_level	<i>group by level</i>
----------------	-----------------------

Description

group by level

Usage

```
group_by_level(x, ...)

## S3 method for class 'character'
group_by_level(x, ...)

## S3 method for class 'factor'
group_by_level(x, ...)

## S3 method for class 'data.table'
group_by_level(x, var, idvar, ...)
```

Arguments

x	named logical/character/factor
...	S3 dispatch
var	string
idvar	string

Value

unnamed character

Examples

```
t1 <- c( KLF5 = 'up', F11 = 'up', RIG = 'flat', ABT1 = 'down')
dt <- data.table( gene = c( 'KLF5', 'F11', 'RIG', 'ABT1' ),
                  t1 = c( 'up', 'up', 'flat', 'down' ) )
group_by_level(t1)          # character
group_by_level(factor(t1))   # factor
group_by_level(dt, 't1', 'gene') # data.table
```

guess_compounddiscoverer_quantity

Guess compound discoverer quantity from snames

Description

Guess compound discoverer quantity from snames

Usage

```
guess_compounddiscoverer_quantity(x)
```

Arguments

x	character vector
---	------------------

Value

string: value from names(COMPOUNDDISCOVERER_PATTERNS)

Examples

```
## Not run:
# file
  file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
  guess_compounddiscoverer_quantity(file)

## End(Not run)

# character vector
  x <- "Area: 20230908_F143_HILICNEG.raw (F11)"
  guess_compounddiscoverer_quantity(x)

  x <- "Norm. Area: 20230908_F143_HILICNEG.raw (F11)"
  guess_compounddiscoverer_quantity(x)
```

guess_fitsep	<i>guess_fitsep</i>
--------------	---------------------

Description

guess fitsep

Usage

```
guess_fitsep(featuredt)
```

Arguments

featuredt	data.table
-----------	------------

Value

string

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
guess_fitsep(fdt(object))
guess_fitsep(fdt(fit_limma(object)))
```

guess_maxquant_quantity	<i>Guess maxquant quantity from snames</i>
-------------------------	--

Description

Guess maxquant quantity from snames

Usage

```
guess_maxquant_quantity(x)
```

Arguments

x	character vector
---	------------------

Value

string: value from names(MAXQUANT_PATTERNS)

Examples

```
# file
  file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
  guess_maxquant_quantity(file)

# character vector
  x <- "Ratio M/L normalized STD(L)_E00(M)_E01(H)_R1"
  guess_maxquant_quantity(x)

  x <- "Ratio M/L STD(L)_E00(M)_E01(H)_R1"
  guess_maxquant_quantity(x)

  x <- "LFQ intensity E00.R1"
  guess_maxquant_quantity(x)

  x <- "Reporter intensity corrected 0 STD(0)E00(1)E01(2)_R1"
  guess_maxquant_quantity(x)

  x <- "Reporter intensity 0 STD(0)E00(1)E01(2)_R1"
  guess_maxquant_quantity(x)

  x <- "Intensity H STD(L)_E00(M)_E01(H)_R1"
  guess_maxquant_quantity(x)
```

guess_sep

Guess separator

Description

Guess separator

Usage

```
guess_sep(x, ...)

## S3 method for class 'numeric'
guess_sep(x, ...)

## S3 method for class 'character'
guess_sep(x, separators = c(".", "_"), verbose = FALSE, ...)

## S3 method for class 'factor'
guess_sep(x, ...)

## S3 method for class 'SummarizedExperiment'
guess_sep(x, var = "sample_id", separators = c(".", "_"), verbose = FALSE, ...)
```

Arguments

x	character vector or SummarizedExperiment
...	used for proper S3 method dispatch
separators	character vector: possible separators to look for
verbose	TRUE or FALSE
var	svar or fvar

Value

separator (string) or NULL (if no separator could be identified)

Examples

```
# charactervector
guess_sep(c('PERM_NON.R1[H/L]', 'PERM_NON.R2[H/L]'))
guess_sep(c('WT_untreated_1', 'WT_untreated_2'))
guess_sep(c('group1', 'group2.R1'))
# SummarizedExperiment
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
guess_sep(object)
```

has_multiple_levels *Variable has multiple levels?*

Description

Variable has multiple levels?

Usage

```
has_multiple_levels(x, ...)

## S3 method for class 'character'
has_multiple_levels(x, .xname = get_name_in_parent(x), ...)

## S3 method for class 'factor'
has_multiple_levels(x, .xname = get_name_in_parent(x), ...)

## S3 method for class 'numeric'
has_multiple_levels(x, .xname = get_name_in_parent(x), ...)

## S3 method for class 'data.table'
has_multiple_levels(
  x,
  y,
```

```

  .xname = get_name_in_parent(x),
  .yname = get_name_in_parent(y),
  ...
)

## S3 method for class 'SummarizedExperiment'
has_multiple_levels(
  x,
  y,
  .xname = get_name_in_parent(x),
  .yname = get_name_in_parent(y),
  ...
)

```

Arguments

x	vector, data.table or SummarizedExperiment
...	required for s3 dispatch
.xname	string
y	string
.yname	string

Value

TRUE or false

Examples

```

# numeric
  a <- numeric();
  a <- c(1, 1);
  a <- c(1, 2);                                has_multiple_levels(a)
has_multiple_levels(a)
has_multiple_levels(a)

# character
  a <- character();
  a <- c('A', 'A');
  a <- c('A', 'B');                            has_multiple_levels(a)
has_multiple_levels(a)
has_multiple_levels(a)

# factor
  a <- factor();
  a <- factor(c('A', 'A'));
  a <- factor(c('A', 'B'));                  has_multiple_levels(a)
has_multiple_levels(a)
has_multiple_levels(a)

# data.table
  dt <- data.table(a = factor());
  dt <- data.table(a = factor());
  dt <- data.table(a = factor());
  dt <- data.table(a = factor(c('A', 'A')));   has_multiple_levels(dt, 'b')
  dt <- data.table(a = factor(c('A', 'B')));   has_multiple_levels(dt, 'a')
has_multiple_levels(dt, 'a')
has_multiple_levels(dt, 'a')

# sumexp
  object <- matrix(1:9, nrow = 3)
  rownames(object) <- sprintf('f%d', 1:3)
  colnames(object) <- sprintf('s%d', 1:3)

```

```

object <- list(exprs = object)
object %>% SummarizedExperiment::SummarizedExperiment()
object$subgroup <- c('A', 'A', 'A');           has_multiple_levels(object, 'group')
object$subgroup <- c('A', 'A', 'A');           has_multiple_levels(object, 'subgroup')
object$subgroup <- c('A', 'B', 'A');           has_multiple_levels(object, 'subgroup')

```

hdlproteins*hdl proteomewatch proteins***Description**

hdl proteomewatch proteins

Usage

```
hdlproteins()
```

Value

string vector: HDLProteomeWatch protein entries

Examples

```
hdlproteins()
```

impute*Impute***Description**

Impute NA values

Usage

```

impute(object, ...)

## S3 method for class 'numeric'
impute(object, shift = 2.5, width = 0.3, verbose = TRUE, plot = FALSE, ...)

## S3 method for class 'matrix'
impute(
  object,
  shift = 2.5,
  width = 0.3,
  verbose = TRUE,
  plot = FALSE,

```

```
n = min(9, ncol(object)),
palette = make_colors(colnames(object)),
...
)

## S3 method for class 'SummarizedExperiment'
impute(
  object,
  assay = assayNames(object)[1],
  by = "subgroup",
  shift = 2.5,
  width = 0.3,
  frac = 0.5,
  verbose = TRUE,
  plot = FALSE,
  palette = make_colors(colnames(object)),
  n = min(9, ncol(object)),
  ...
)
```

Arguments

object	numeric vector, SumExp
...	required for s3 dispatch
shift	number: sd units
width	number: sd units
verbose	TRUE or FALSE
plot	TRUE or FALSE
n	number of samples to plot
palette	color vector
assay	string
by	svar
frac	fraction: fraction of available samples should be greater than this value for a subgroup to be called available

Details

Imputes NA values from $N(\text{mean} - 2.5 \text{ sd}, 0.3 \text{ sd})$

Value

numeric vector, matrix or SumExp

Examples

```
# Simple Design
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
impute(values(object)[, 1], plot = TRUE)[1:3]                      # vector
impute(values(object),      plot = TRUE)[1:3, 1:3]                  # matrix
impute(object, plot = TRUE)                                         # sumexp

# Complex Design
subgroups <- sprintf('%s_STD', c('E00','E01','E02','E05','E15','E30','M00'))
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file, subgroups = subgroups)
impute(values(object)[1:3, 1    ])      # vector
impute(values(object)[1:3, 1:5 ])      # matrix
impute( object )                      # sumexp
```

invert_subgroups *Invert subgroups*

Description

Invert expressions , subgroups, and sample ids

Usage

```
invert_subgroups(
  object,
  subgroups = slevels(object, "subgroup"),
  sep = guess_sep(object, "subgroup")
)
```

Arguments

object	SummarizedExperiment
subgroups	character vector: subgroup levels to be inversed
sep	string: collapsed string separator

Value

character vector or SummarizedExperiment

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
invert_subgroups(object)
```

```
isCollapsedSubset    Is collapsed subset
```

Description

Is collapsed subset

Usage

```
isCollapsedSubset(x, y, sep = ";")
```

Arguments

x	character vector
y	character vector
sep	string

Value

character vector

Examples

```
x <- c('H3BNX8;H3BRM5', 'G5E9Y3')
y <- c('P20674;H3BNX8;H3BV69;H3BRM5', 'G5E9Y3;Q8WWN8;B4DIT1')
isCollapsedSubset(x, y)
```

```
isCorrelationMatrix  Assert correlation matrix
```

Description

Assert correlation matrix

Usage

```
isCorrelationMatrix(
  x,
  .xname = get_name_in_parent(x),
  severity = getOption("assertive.severity", "stop")
)
assertCorrelationMatrix(x, .xname = get_name_in_parent(x))
```

Arguments

x	correlation matrix
.xname	string
severity	'warning' or 'stop'

Value

TRUE or false

Examples

```
x <- matrix(c(1,0.7, 0.3, 1), nrow = 2)
rownames(x) <- c('gene1', 'gene2')
colnames(x) <- c('gene1', 'gene2')
is_correlation_matrix(x)
is_correlation_matrix({x[1,1] <- -2; x})
```

is_diann_report *Is diann, fragpipe, proteingroups, phosphosites file?*

Description

Is diann, fragpipe, proteingroups, phosphosites file?

Usage

```
is_diann_report(x, .xname = get_name_in_parent(x))

is_fragpipe_tsv(x, .xname = get_name_in_parent(x))

is_maxquant_proteingroups(x, .xname = get_name_in_parent(x))

is_maxquant_phosphosites(x, .xname = get_name_in_parent(x))

is_compounddiscoverer_output(x, .xname = get_name_in_parent(x))

assert_diann_report(x, .xname = get_name_in_parent(x))

assert_fragpipe_tsv(x, .xname = get_name_in_parent(x))

assert_maxquant_proteingroups(x, .xname = get_name_in_parent(x))

assert_maxquant_phosphosites(x, .xname = get_name_in_parent(x))

assert_compounddiscoverer_output(x, .xname = get_name_in_parent(x))
```

Arguments

x	file
.xname	name of x

Examples

```
file <- NULL
is_diann_report(file)
is_fragpipe_tsv(file)
is_maxquant_proteingroups(file)
is_maxquant_phosphosites(file)

file <- 3
is_diann_report(file)
is_fragpipe_tsv(file)
is_maxquant_proteingroups(file)
is_maxquant_phosphosites(file)

file <- 'blabla.tsv'
is_diann_report(file)
is_fragpipe_tsv(file)
is_maxquant_proteingroups(file)
is_maxquant_phosphosites(file)

file <- download_data('multiorganism.combined_protein.tsv')
is_diann_report(file)
is_fragpipe_tsv(file)
is_maxquant_proteingroups(file)
is_maxquant_phosphosites(file)

file <- download_data('dilution.report.tsv')
is_diann_report(file)
is_fragpipe_tsv(file)
is_maxquant_proteingroups(file)
is_maxquant_phosphosites(file)

file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
is_diann_report(file)
is_fragpipe_tsv(file)
is_maxquant_proteingroups(file)
is_maxquant_phosphosites(file)

file <- system.file('extdata/billing19.phosphosites.txt', package = 'autonomics')
is_diann_report(file)
is_fragpipe_tsv(file)
is_maxquant_proteingroups(file)
is_maxquant_phosphosites(file)
```

is_fastadt*Is fastadt***Description**

Is fastadt

Usage

```
is_fastadt(x, .xname = get_name_in_parent(x))

assert_fastadt(x, .xname = get_name_in_parent(x))
```

Arguments

x	fasta data.table
.xname	string

Examples

```
fastafastafile <- system.file('extdata/uniprot_hsa_20140515.fasta', package = 'autonomics')
x <- read_uniprotdt(fastafastafile)
# is_fastadt(x) # slow
```

is_file*Is a file?***Description**

Is a file (and not a dir)

Usage

```
is_file(file)
```

Arguments

file	filepath
------	----------

Details

This function distinguishes between dir and file. Others dont: is.file, fs::file_exists, assertive::is_existing_file

Examples

```
dir <- tempdir(); dir.create(dir, showWarnings = FALSE)
file <- tempfile(); invisible(file.create(file))
is_file(dir)
is_file(file)
```

is_fraction*Is fraction*

Description

Is fraction

Usage

```
is_fraction(x, .xname = get_name_in_parent(x))

assert_is_fraction(x, .xname = get_name_in_parent(x))
```

Arguments

x	number
.xname	string

Value

TRUE or false

Examples

```
is_fraction(0.1)      # YES
is_fraction(1)        # YES
is_fraction(1.2)      # NO - more than 1
is_fraction(c(0.1, 0.2)) # NO - vector
```

is_imputed*Get/set is_imputed*

Description

Get/Set is_imputed

Usage

```
is_imputed(object)

## S4 method for signature 'SummarizedExperiment'
is_imputed(object)

is_imputed(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
is_imputed(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,NULL'
is_imputed(object) <- value
```

Arguments

object	SummarizedExperiment
value	matrix

Value

matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file, impute = TRUE)
sum(is_imputed(object))
```

is_positive_number *Is positive number*

Description

Is positive number

Usage

```
is_positive_number(x, .xname = get_name_in_parent(x))

assert_positive_number(x, .xname = get_name_in_parent(x))

is_weakly_positive_number(x, .xname = get_name_in_parent(x))

assert_weakly_positive_number(x, .xname = get_name_in_parent(x))
```

Arguments

x	number
.xname	name of x

Value

TRUE or false

Examples

```
is_positive_number( 3)
is_positive_number(-3)
is_positive_number( 0)
is_weakly_positive_number(0)
assert_positive_number(3)
```

is_scalar_subset *Is scalar subset*

Description

Is scalar subset

Usage

```
is_scalar_subset(
    x,
    y,
    .xname = get_name_in_parent(x),
    .yname = get_name_in_parent(y)
)

assert_scalar_subset(
    x,
    y,
    .xname = get_name_in_parent(x),
    .yname = get_name_in_parent(y)
)
```

Arguments

x	scalar
y	SummarizedExperiment
.xname	name of x
.yname	name of y

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
is_scalar_subset('subgroup', svars(object))
is_scalar_subset('subject', svars(object))
assert_scalar_subset('subgroup', svars(object))
```

is_sig

Is significant?

Description

Is significant?

Usage

```
is_sig(
  object,
  fit = fits(fdt(object))[1],
  contrast = coefs(fdt(object)),
  quantity = "fdr"
)
```

Arguments

object	SummarizedExperiment
fit	subset of <code>autonomics::TESTS</code>
contrast	subset of <code>colnames(metadata(object)[[fit]]</code>)
quantity	value in <code>dimnames(metadata(object)[[fit]][3]</code>

Value

matrix: -1 (downregulated), +1 (upregulated), 0 (not fdr significant)

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
object %>% fit_lm()
object %>% fit_limma()
issig <- is_sig(object, fit = c('lm','limma'), contrast = 'Adult')
plot_contrast_venn(issig)
```

<code>is_valid_formula</code>	<i>Is valid formula</i>
-------------------------------	-------------------------

Description

Is valid formula

Usage

```
is_valid_formula(
  x,
  y,
  .xname = get_name_in_parent(x),
  .yname = get_name_in_parent(y)
)

assert_valid_formula(
  x,
  y,
  .xname = get_name_in_parent(x),
  .yname = get_name_in_parent(y)
)
```

Arguments

x	formula
y	SummarizedExperiment
.xname	string
.yname	string

Value

TRUE or false

Examples

```
object <- matrix(1:9, nrow = 3)
rownames(object) <- sprintf('f%d', 1:3)
colnames(object) <- sprintf('s%d', 1:3)
object <- list(exprs = object)
object %>% SummarizedExperiment::SummarizedExperiment()
object$group    <- 'group0'
object$subgroup <- c('A', 'B', 'C')
svars(object)
  is_valid_formula( 'condition',   object)  # not formula
  is_valid_formula( ~condition,    object)  # not svar
  is_valid_formula( ~group,       object)  # not multilevel
```

```

is_valid_formula(~subgroup,      object) # TRUE
is_valid_formula(~0+subgroup,    object) # TRUE
is_valid_formula(~1,            object) # TRUE
assert_valid_formula(~subgroup,  object)

```

keep_connected_blocks *Keep fully connected blocks*

Description

Keep fully connected blocks

Usage

```
keep_connected_blocks(object, block, verbose = TRUE)
```

Arguments

object	SummarizedExperiment
block	svar
verbose	TRUE or FALSE

Examples

```

file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% keep_connected_blocks( block = 'Subject')

```

keep_connected_features

Keep features with n+ connected blocks

Description

Keep features with n+ connected blocks

Usage

```
keep_connected_features(object, block, n = 2, verbose = TRUE)
```

Arguments

object	SummarizedExperiment
block	svar
n	number
verbose	TRUE or FALSE

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% keep_connected_blocks( block = 'Subject')
object %>% keep_connected_features(block = 'Subject')
```

keep_replicated_features

Keep replicated features

Description

Keep features replicated for each slevel

Usage

```
keep_replicated_features(object, formula = ~1, n = 3, verbose = TRUE)
```

Arguments

object	SummarizedExperiment
formula	formula
n	min replications required
verbose	TRUE or FALSE

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% keep_replicated_features()
object %>% keep_replicated_features(~ subgroup)
```

label2index

Convert labels into indices

Description

Convert labels into indices

Usage

```
label2index(x)
```

Arguments

x	'character'
---	-------------

Examples

```
label2index(x = 'Reporter intensity 0 WT(0).KD(1).OE(2).R1')
label2index(x = 'Reporter intensity 1 WT(1).KD(2).OE(3).R1')
label2index(x = 'Reporter intensity 0 WT(126).KD(127).OE(128).R1')
label2index(x = 'Reporter intensity 1 WT(126).KD(127).OE(128).R1')
label2index(x = 'Reporter intensity 1 Mix1')
```

LINMOD_ENGINES

*Linear Modeling Engines***Description**

Linear Modeling Engines

Usage

LINMOD_ENGINES

Format

An object of class character of length 5.

Examples

LINMOD_ENGINES

list2mat

*list to matrix***Description**

list to matrix

Usage

list2mat(x)

Arguments

x list

Value

matrix

Examples

```
x <- list(roundfruit = c('apple', 'orange'), redfruit = c('apple', 'strawberry'))
list2mat(x)
```

list_files	<i>list files</i>
------------	-------------------

Description

list.files for programming

Usage

```
list_files(dir, full.names)
```

Arguments

dir	directory
full.names	TRUE or FALSE

Details

Adds a small layer on list.files. Returning NULL rather than character(0) when no files. Making it better suited for programming.

log2counts	<i>Get/Set log2counts</i>
------------	---------------------------

Description

Get / Set log2counts matrix

Usage

```
log2counts(object)

## S4 method for signature 'SummarizedExperiment'
log2counts(object)

log2counts(object) <- value

## S4 replacement method for signature 'SummarizedExperiment, matrix'
log2counts(object) <- value

## S4 replacement method for signature 'SummarizedExperiment, numeric'
log2counts(object) <- value
```

Arguments

object	SummarizedExperiment
value	log2count matrix (features x samples)

Value

log2count matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnasedq_counts(file)
log2counts(object)[1:3, 1:3]
log2counts(object) <- values(object)
```

log2cpm

Get/Set log2cpm

Description

Get / Set log2cpm matrix

Usage

```
log2cpm(object)

## S4 method for signature 'SummarizedExperiment'
log2cpm(object)

log2cpm(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
log2cpm(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,numERIC'
log2cpm(object) <- value
```

Arguments

object	SummarizedExperiment
value	log2cpm matrix (features x samples)

Value

log2cpm matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnaseq_counts(file)
log2cpm(object)[1:3, 1:3]
log2cpm(object) <- values(object)
```

log2diffs*Get/Set log2diffs*

Description

Get/Set log2diffs

Usage

```
log2diffs(object)

## S4 method for signature 'SummarizedExperiment'
log2diffs(object)

log2diffs(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
log2diffs(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,numeric'
log2diffs(object) <- value
```

Arguments

object	SummarizedExperiment
value	occupancy matrix (features x samples)

Value

occupancy matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
log2diffs(object)[1:3, 1:3]
```

log2proteins*Get/Set log2proteins***Description**

Get/Set log2proteins

Usage

```
log2proteins(object)

## S4 method for signature 'SummarizedExperiment'
log2proteins(object)

log2proteins(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
log2proteins(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,numERIC'
log2proteins(object) <- value
```

Arguments

object	SummarizedExperiment
value	occupancy matrix (features x samples)

Value

occupancy matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
log2proteins(object)[1:3, 1:3]
```

log2sites*Get/Set log2sites***Description**

Get/Set log2sites

Usage

```
log2sites(object)

## S4 method for signature 'SummarizedExperiment'
log2sites(object)

log2sites(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
log2sites(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,numeric'
log2sites(object) <- value
```

Arguments

object	SummarizedExperiment
value	occupancy matrix (features x samples)

Value

occupancy matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
log2sites(object)[1:3, 1:3]
```

log2tpm

Get/Set log2tpm

Description

Get / Set log2tpm matrix

Usage

```
log2tpm(object)

## S4 method for signature 'SummarizedExperiment'
log2tpm(object)

log2tpm(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
log2tpm(object) <- value
```

```
## S4 replacement method for signature 'SummarizedExperiment,numeric'
log2tpm(object) <- value
```

Arguments

object	SummarizedExperiment
value	log2tpm matrix (features x samples)

Value

log2tpm matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnaseq_counts(file)
log2tpm(object) <- values(object)
log2tpm(object)[1:3, 1:3]
```

log2transform *Transform values*

Description

Transform values

Usage

```
log2transform(
  object,
  assay = assayNames(object)[1],
  pseudo = 0,
  verbose = FALSE
)

exp2(object, verbose = FALSE)

zscore(object, verbose = FALSE)

quantnorm(object, verbose = FALSE)

invnorm(object, verbose = FALSE)

vsn(object, verbose = FALSE, delog = TRUE)
```

Arguments

object	SummarizedExperiment
assay	character vector : assays for which to perform transformation
pseudo	number : pseudo value to be added prior to transformation
verbose	TRUE or FALSE : whether to msg
delog	TRUE or FALSE (vsn)

Value

Transformed sumexp

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)

object %>% plot_sample_densities()
invnorm(object) %>% plot_sample_densities()

object %>% plot_sample_densities()
quantnorm(object) %>% plot_sample_densities()

object %>% plot_sample_densities()
#vsn(object) %>% plot_sample_densities() # dataset too small

object %>% plot_sample_densities()
zscore(object) %>% plot_sample_densities()

object %>% plot_sample_densities()
exp2(object) %>% plot_sample_densities()
log2transform(exp2(object)) %>% plot_sample_densities()
```

logical2factor	<i>logical to factor</i>
----------------	--------------------------

Description

logical to factor

Usage

```
logical2factor(x, true = get_name_in_parent(x), false = paste0("not", true))

factor2logical(x)
```

Arguments

<code>x</code>	logical vector
<code>true</code>	string : truelevel
<code>false</code>	string : falselevel

Value

factor

Examples

```
t1up <- c( TRUE, FALSE, TRUE)
t1   <- c('flat', 'down', 'up' ) %>% factor(., .)
t1up
logical2factor(t1up)
factor2logical(t1)
```

make_alpha_palette *Make alpha palette*

Description

Make alpha palette

Usage

```
make_alpha_palette(object, alpha)
```

Arguments

<code>object</code>	SummarizedExperiment
<code>alpha</code>	string

Value

character vector

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
make_alpha_palette(object, 'Time')
```

make_colors *Make colors*

Description

Make colors

Usage

```
make_colors(  
  varlevels,  
  sep = guess_sep(varlevels),  
  show = FALSE,  
  verbose = FALSE  
)
```

Arguments

varlevels	character vector
sep	string
show	TRUE or FALSE: whether to plot
verbose	TRUE or FALSE: whether to msg

Examples

```
make_colors(c('A', 'B', 'C', 'D'), show = TRUE)  
make_colors(c('A.1', 'B.1', 'A.2', 'B.2'), show = TRUE)
```

make_volcano_dt *Create volcano datatable*

Description

Create volcano datatable

Usage

```
make_volcano_dt(  
  object,  
  fit = fits(fdt(object))[1],  
  coefs = default_coefs(fdt(object), fit = fit)[1],  
  shape = "imputed",  
  size = NULL,  
  alpha = NULL,  
  label = "feature_id"  
)
```

Arguments

<code>object</code>	SummarizedExperiment
<code>fit</code>	'limma', 'lme', 'lm', 'wilcoxon'
<code>coefs</code>	character vector: coefs for which to plot volcanoes
<code>shape</code>	fvar or NULL
<code>size</code>	fvar or NULL
<code>alpha</code>	fvar or NULL
<code>label</code>	fvar or NULL

Value

`data.table`

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file, impute = TRUE, fit = 'limma')
make_volcano_dt(object, fit = 'limma', coefs = 'Adult')
```

map_fvalues

Map fvalues

Description

Map fvalues

Usage

```
map_fvalues(object, fvalues, from = "uniprot", to = "feature_id", sep = ";")
```

Arguments

<code>object</code>	SummarizedExperiment
<code>fvalues</code>	uncollapsed string vector
<code>from</code>	string (fvar)
<code>to</code>	string (svar)
<code>sep</code>	collapse separator

Value

string vector

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
fdt(object)
map_fvalues(object, c('Q6DHL5', 'Q6PFS7'), from = 'uniprot', to = 'feature_id', sep = ';')
```

matrix2sumexp

*Convert matrix into SummarizedExperiment***Description**

Convert matrix into SummarizedExperiment

Usage

```
matrix2sumexp(x, verbose = TRUE)
```

Arguments

x	matrix
verbose	TRUE/FALSE

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
x <- values(read_metabolon(file))
object <- matrix2sumexp(x)
object %<-%> pca()
biplot(object, color = 'subgroup')
```

MAXQUANT_PATTERNS

*maxquant quantity patterns***Description**

maxquant quantity patterns

Usage

```
MAXQUANT_PATTERNS
```

Format

An object of class character of length 7.

Examples

```
MAXQUANT_PATTERNS
```

```
merge_compounddiscoverer  
merge compound discoverer files
```

Description

merge compound discoverer files

Usage

```
merge_compounddiscoverer(x, quantity = NULL, verbose = TRUE)
```

Arguments

x	'list'
quantity	'area', 'normalizedarea'
verbose	'TRUE' or 'FALSE'

Value

'data.table'

```
merge_sample_excel      Merge sample excel
```

Description

Merge sample excel

Usage

```
merge_sample_excel(  
  object,  
  sfile,  
  range = NULL,  
  by.x = "sample_id",  
  by.y = "sample_id"  
)
```

Arguments

object	SummarizedExperiment
sfile	sample file
range	string
by.x	string
by.y	string

Value

SummarizedExperiment

merge_sample_file *Merge sample / feature file*

Description

Merge sample / feature file

Usage

```
merge_sample_file(  
  object,  
  sfile = NULL,  
  by.x = "sample_id",  
  by.y = "sample_id",  
  all.x = TRUE,  
  select = NULL,  
  stringsAsFactors = FALSE,  
  verbose = TRUE  
)  
  
merge_ffile(  
  object,  
  ffile = NULL,  
  by.x = "feature_id",  
  by.y = "feature_id",  
  all.x = TRUE,  
  select = NULL,  
  stringsAsFactors = FALSE,  
  verbose = TRUE  
)
```

Arguments

object	SummarizedExperiment
sfile	string : sample file path
by.x	string : object mergevar
by.y	string : file mergevar
all.x	TRUE / FALSE : whether to keep samples / feature without annotation
select	character : [sf]file columns to select
stringsAsFactors	TRUE / FALSE
verbose	TRUE / FALSE
ffile	string : ffile path

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
subgroups <- c('E00', 'E01', 'E02', 'E05', 'E15', 'E30', 'M00')
subgroups %>% paste0('_STD')
object <- read_maxquant_proteingroups(file, subgroups = subgroups)
sfile <- paste0(tempdir(), '/', basename(tools::file_path_sans_ext(file)))
sfile %>% paste0('.samples.txt')
dt <- data.table(sample_id = object$sample_id,
                  day = split_extract_fixed(object$subgroup, '_', 1))
data.table::fwrite(dt, sfile)
sdt(object)
sdt(merge_sample_file(object, sfile))
```

merge_sdata

Merge sample/feature dt

Description

Merge sample/feature dt

Usage

```
merge_sdata(
  object,
  dt,
  by.x = "sample_id",
  by.y = names(dt)[1],
  all.x = TRUE,
```

```
    verbose = TRUE
)

merge_sdt(
  object,
  dt,
  by.x = "sample_id",
  by.y = "sample_id",
  all.x = TRUE,
  verbose = TRUE
)

merge_fdata(
  object,
  dt,
  by.x = "feature_id",
  by.y = names(dt)[1],
  all.x = TRUE,
  verbose = TRUE
)

merge_fdt(
  object,
  dt,
  by.x = "feature_id",
  by.y = "feature_id",
  all.x = TRUE,
  verbose = TRUE
)
```

Arguments

object	SummarizedExperiment
dt	data.frame, data.table, DataFrame
by.x	string : object mergevar
by.y	string : df mergevar
all.x	TRUE / FALSE : whether to keep samples / features without annotation
verbose	TRUE / FALSE : whether to msg

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
sdt(object)
```

```
sdt(merge_sdt(object, data.table(sample_id = object$sample_id,
                                number = seq_along(object$sample_id))))
```

message_df

message dataframe

Description

message dataframe using sprintf syntax. Use place holder ‘

Usage

```
message_df(format_string, x)
```

Arguments

format_string	sprintf style format string
x	data.frame

Value

nothing returned

Examples

```
x <- data.frame(feature_id = c('F001', 'F002'), symbol = c('FEAT1', 'FEAT2'))
message_df('\t%s', x)

x <- c(rep('PASS', 25), rep('FAIL', 25))
message_df(format_string = '%s', table(x))
```

modelvar

Get model variable

Description

Get model variable

Usage

```
modelvar(  
    featuredt,  
    quantity,  
    fit = fits(featuredt),  
    coef = default_coefs(featuredt, fit = fit)  
)  
  
effectvar(  
    featuredt,  
    fit = fits(featuredt),  
    coef = default_coefs(featuredt, fit = fit)  
)  
  
tvar(  
    featuredt,  
    fit = fits(featuredt),  
    coef = default_coefs(featuredt, fit = fit)  
)  
  
pvar(  
    featuredt,  
    fit = fits(featuredt),  
    coef = default_coefs(featuredt, fit = fit)  
)  
  
fdrvar(  
    featuredt,  
    fit = fits(featuredt),  
    coef = default_coefs(featuredt, fit = fit)  
)  
  
abstractvar(  
    featuredt,  
    fit = fits(featuredt),  
    coef = default_coefs(featuredt, fit = fit)  
)  
  
modelvec(  
    featuredt,  
    quantity,  
    fit = fits(featuredt)[1],  
    coef = default_coefs(featuredt, fit = fit)[1],  
    fvar = "feature_id"  
)  
  
effectvec(  
    featuredt,
```

```
fit = fits(featuredt)[1],
coef = default_coefs(featuredt, fit = fit)[1],
fvar = "feature_id"
)

tvec(
  featuredt,
  fit = fits(featuredt)[1],
  coef = default_coefs(featuredt, fit = fit)[1],
  fvar = "feature_id"
)

pvec(
  featuredt,
  fit = fits(featuredt)[1],
  coef = default_coefs(featuredt, fit = fit)[1],
  fvar = "feature_id"
)

fdrvec(
  featuredt,
  fit = fits(featuredt)[1],
  coef = default_coefs(featuredt, fit = fit)[1],
  fvar = "feature_id"
)

modeldt(
  featuredt,
  quantity,
  fit = fits(featuredt),
  coef = default_coefs(featuredt, fit = fit)
)

effectdt(
  featuredt,
  fit = fits(featuredt),
  coef = default_coefs(featuredt, fit = fit)
)

tdt(
  featuredt,
  fit = fits(featuredt),
  coef = default_coefs(featuredt, fit = fit)
)

pdt(
  featuredt,
  fit = fits(featuredt),
```

```
coef = default_coefs(featuredt, fit = fit)
)

modelmat(
    featuredt,
    quantity,
    fit = fits(featuredt),
    coef = default_coefs(featuredt, fit = fit)
)

effectmat(
    featuredt,
    fit = fits(featuredt),
    coef = default_coefs(featuredt, fit = fit)
)

effectsizemat(
    featuredt,
    fit = fits(featuredt),
    coef = default_coefs(featuredt, fit = fit)
)

tmat(
    featuredt,
    fit = fits(featuredt),
    coef = default_coefs(featuredt, fit = fit)
)

pmat(
    featuredt,
    fit = fits(featuredt),
    coef = default_coefs(featuredt, fit = fit)
)

fdrmat(
    featuredt,
    fit = fits(featuredt),
    coef = default_coefs(featuredt, fit = fit)
)

modelfeatures(
    featuredt,
    fit = fits(featuredt)[1],
    coef = default_coefs(featuredt, fit = fit)[1],
    fvar = "feature_id",
    significancevar = "p",
    significance = 0.05,
    effectdirection = "<>,"
```

```

    effectsize = 0
  )

  upfeatures(
    featuredt,
    fit = fits(featuredt)[1],
    coef = default_coefs(featuredt, fit = fit)[1],
    fvar = "feature_id",
    significancevar = "p",
    significance = 0.05,
    effectsize = 0
  )

  downfeatures(
    featuredt,
    fit = fits(featuredt)[1],
    coef = default_coefs(featuredt, fit = fit)[1],
    fvar = "feature_id",
    significancevar = "p",
    significance = 0.05,
    effectsize = 0
  )
)

```

Arguments

<code>featured</code>	<code>data.table</code>
<code>quantity</code>	'p', 'effect', 'fdr', 't', or 'se'
<code>fit</code>	string (vector)
<code>coef</code>	string (vector)
<code>fvar</code>	'feature_id' or other fvar for values (pvec) or names (upfeatures)
<code>significancevar</code>	'p' or 'fdr'
<code>significance</code>	p or fdr cutoff (fractional number)
<code>effectdirection</code>	'<>', '<' or '>'
<code>effectsize</code>	effectsize cutoff (positive number)

Value

string (tvar), matrix (tmat), numeric vector (tvec), character vector (tfeatures)

Examples

```

# Read
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %<%>% fit_limma()

```

```

object %<>% fit_lm()
featuredt <- fdt(object)
featuredt %<>% add_adjusted_pvalues('fdr')
# modelvar
  modelvar(featuredt, 'p');                                pvar(featuredt)
  modelvar(featuredt, 'effect');                            effectvar(featuredt)
  modelvar(featuredt, 'fdr');                               fdrvar(featuredt)
# modelvec
  modelvec(featuredt, 'p'      )[1:3];                     pvec(featuredt)[1:3]
  modelvec(featuredt, 'effect')[1:3];                     effectvec(featuredt)[1:3]
  modelvec(featuredt, 'fdr'   )[1:3];                     fdrcvec(featuredt)[1:3]
# modelmatrix
  modelmat(featuredt, 'p'     )[1:3, 1:3];                pmat(featuredt)[1:3, 1:3]
  modelmat(featuredt, 'effect')[1:3, 1:3];                effectmat(featuredt)[1:3, 1:3]
  modelmat(featuredt, 'fdr'   )[1:3, 1:3];                fdrmat(featuredt)[1:3, 1:3]
# modelfeatures
  modelfeatures(featuredt      )[1:3]                      downfeatures(featuredt)[1:3]
  modelfeatures(featuredt, effectdirection = '<' )[1:3];  upfeatures(featuredt)[1:3]
  modelfeatures(featuredt, effectdirection = '>' )[1:3];

```

MSIGCOLLECTIONSHUMAN *Human/Mouse Msigdb Collections*

Description

Human/Mouse Msigdb Collections

Usage

MSIGCOLLECTIONSHUMAN

MSIGCOLLECTIONSMOUSE

Format

An object of class character of length 25.

An object of class character of length 13.

MSIGDIR *local msigdb dir*

Description

local msigdb dir

Usage

MSIGDIR

Format

An object of class character of length 1.

nfactors	<i>stri_split and extract</i>
----------	-------------------------------

Description

stri_split and extract

Usage

```
nfactors(x, sep = guess_sep(x))

split_extract_fixed(x, sep, i)

split_extract_regex(x, sep, i)

split_extract(x, i, sep = guess_sep(x))
```

Arguments

x	character vector
sep	string
i	integer

Value

character vector

Examples

```
# Read
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
x <- object$sample_id[1:5]
nfactors(x)

# Split
split_extract_fixed(x, '.', 1:2)
split_extract_fixed(x, '.', seq_len(nfactors(x)-1))
split_extract_fixed(x, '.', nfactors(x))
split_extract_fixed(fdt(object)$PUBCHEM, ';', 1) # with NA values
```

OPENTARGETSDIR	<i>opentargets dir</i>
----------------	------------------------

Description

`opentargets dir`

Usage

`OPENTARGETSDIR`

Format

An object of class character of length 1.

order_on_p	<i>Order on p</i>
------------	-------------------

Description

`Order on p`

Usage

```
order_on_p(
  object,
  fit = autonomics::fits(fdt(object)),
  coefs = autonomics::coefs(fdt(object), fit = fit),
  combiner = "|",
  verbose = TRUE
)

order_on_effect(
  object,
  fit = autonomics::fits(fdt(object)),
  coefs = autonomics::coefs(fdt(object), fit = fit),
  combiner = "|",
  verbose = TRUE
)
```

Arguments

object	SummarizedExperiment
fit	string vector: subset of ‘fits(fdt(object))’
coefs	string vector: subset of ‘coefs(fdt(object))’
combiner	‘ ’ or ‘&’
verbose	TRUE or FALSE

Value

`SummarizedExperiment`

Examples

```
# Read
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
order_on_p(object)
order_on_p(fit_limma(object), coefs = c('t1', 't2', 't3'))
```

`pca`

PCA, SMA, LDA, PLS, SPLS, OPLS

Description

Perform a dimension reduction. Store sample scores, feature loadings, and dimension variances.

Usage

```
pca(
  object,
  by = "sample_id",
  assay = assayNames(object)[1],
  ndim = 2,
  sep = FITSEP,
  minvar = 0,
  center_samples = TRUE,
  verbose = TRUE,
  plot = FALSE,
  ...
)

pls(
  object,
  by = "subgroup",
  assay = assayNames(object)[1],
  ndim = 2,
  sep = FITSEP,
  minvar = 0,
  verbose = FALSE,
  plot = FALSE,
  ...
)

sma(
  object,
```

```
    by = "sample_id",
    assay = assayNames(object)[1],
    ndim = 2,
    sep = FITSEP,
    minvar = 0,
    verbose = TRUE,
    plot = FALSE,
    ...
)

lda(
  object,
  assay = assayNames(object)[1],
  by = "subgroup",
  ndim = 2,
  sep = FITSEP,
  minvar = 0,
  verbose = TRUE,
  plot = FALSE,
  ...
)

spls(
  object,
  assay = assayNames(object)[1],
  by = "subgroup",
  ndim = 2,
  sep = FITSEP,
  minvar = 0,
  plot = FALSE,
  ...
)

opls(
  object,
  by = "subgroup",
  assay = assayNames(object)[1],
  ndim = 2,
  sep = FITSEP,
  minvar = 0,
  verbose = FALSE,
  plot = FALSE,
  ...
)
```

Arguments

object SummarizedExperiment

by	svar or NULL
assay	string
ndim	number
sep	string
minvar	number
center_samples	TRUE/FALSE: center samples prior to pca ?
verbose	TRUE/FALSE: message ?
plot	TRUE/FALSE: plot ?
...	passed to biplot

Value

SummarizedExperiment

Author(s)

Aditya Bhagwat, Laure Cougnaud (LDA)

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
pca(object, plot = TRUE)      # Principal Component Analysis
pls(object, plot = TRUE)     # Partial Least Squares
lda(object, plot = TRUE)      # Linear Discriminant Analysis
sma(object, plot = TRUE)      # Spectral Map Analysis
spls(object, plot = TRUE)     # Sparse PLS
# opls(object, plot = TRUE)   # OPLS # outcommented because it produces a file named FALSE
```

percentiles *survival percentiles***Description**

survival percentiles

Usage

percentiles(object)

Arguments

object SummarizedExperiment

Value

numeric vector

pg_to_canonical *proteingroup to isoforms*

Description

proteingroup to isoforms

Usage

```
pg_to_canonical(x, unique = TRUE)  
pg_to_isoforms(x, unique = TRUE)
```

Arguments

x	proteingroups string vector
unique	whether to remove duplicates

Value

string vector

Examples

```
(x <- c('Q96JP5;Q96JP5-2', 'Q96JP5', 'Q96JP5-2;P86791'))  
pg_to_isoforms(x)  
pg_to_canonical(x)  
pg_to_isoforms( x, unique = FALSE)  
pg_to_canonical(x, unique = FALSE)  
# .pg_to_isoforms(x[1]) # unexported dot functions  
# .pg_to_canonical(x[1]) # operate on scalars
```

plot_contrastogram *Plot contrastogram*

Description

Plot contrastogram

Usage

```
plot_contrastogram(  
  object,  
  subgroupvar,  
  formula = as.formula(paste0("~ 0 +", subgroupvar)),  
  colors = make_colors(slevels(object, subgroupvar), guess_sep(object)),  
  curve = 0.1  
)
```

Arguments

object	SummarizedExperiment
subgroupvar	subgroup svar
formula	formula
colors	named color vector (names = subgroups)
curve	arrow curvature

Value

list returned by [plotmat](#)

Examples

```
if (requireNamespace('diagram', quietly = TRUE)){
  file <- download_data('halama18.metabolon.xlsx')
  object <- read_metabolon(file)
  plot_contrastogram(object, subgroupvar = 'subgroup')
}
```

plot_contrast_venn *Plot contrast venn*

Description

Plot contrast venn

Usage

```
plot_contrast_venn(issig, colors = NULL)
```

Arguments

issig	matrix(nrow, ncontrast): -1 (down), +1 (up)
colors	NULL or colorvector

Value

nothing returned

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% fit_wilcoxon(~ subgroup, block = 'Subject')
object %>% fit_limma( ~ subgroup, block = 'Subject', codingfun = contr.treatment.explicit)
isfdr <- is_sig(object, contrast = 't3-t0', quantity = 'p', fit = fits(fdt(object)))
plot_contrast_venn(isfdr)
```

plot_data	<i>Plot data</i>
-----------	------------------

Description

Plot data

Usage

```
plot_data(  
  data,  
  geom = geom_point,  
  color = NULL,  
  fill = NULL,  
  linetype = NULL,  
  ...,  
  palette = NULL,  
  fixed = list(),  
  theme = list()  
)
```

Arguments

data	data.frame'
geom	geom_point, etc.
color	variable mapped to color (symbol)
fill	variable mapped to fill (symbol)
linetype	variable mapped to linetype (symbol)
...	mapped aesthetics
palette	color palette (named character vector)
fixed	fixed aesthetics (list)
theme	list with ggplot theme specifications

Value

ggplot object

Author(s)

Aditya Bhagwat, Johannes Graumann

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% pca()
data <- sdt(object)
plot_data(data, x = `effect~sample_id~pca1`, y = `effect~sample_id~pca2`)
plot_data(data, x = `effect~sample_id~pca1`, y = `effect~sample_id~pca2`, color = subgroup)
plot_data(data, x = `effect~sample_id~pca1`, y = `effect~sample_id~pca2`, color = NULL)
fixed <- list(shape = 15, size = 3)
plot_data(data, x = `effect~sample_id~pca1`, y = `effect~sample_id~pca2`, fixed = fixed)
```

plot_densities*Plot sample/feature distributions***Description**

Plot sample/feature distributions

Usage

```
plot_densities(
  object,
  assay = assayNames(object)[1],
  group,
  fill,
  color = NULL,
  linetype = NULL,
  facet = NULL,
  nrow = NULL,
  ncol = NULL,
  dir = "h",
  scales = "free_y",
  labeller = label_value,
  palette = NULL,
  fixed = list(alpha = 0.8, na.rm = TRUE)
)

plot_sample_densities(
  object,
  assay = assayNames(object)[1],
  group = "sample_id",
  fill = if ("subgroup" %in% svars(object)) "subgroup" else "sample_id",
  color = NULL,
  linetype = NULL,
  n = 100,
  facet = NULL,
  nrow = NULL,
```

```
  ncol = NULL,  
  dir = "h",  
  scales = "free_y",  
  labeller = label_value,  
  palette = NULL,  
  fixed = list(alpha = 0.8, na.rm = TRUE)  
)  
  
  plot_feature_densities(  
    object,  
    assay = assayNames(object)[1],  
    fill = "feature_id",  
    group = fill,  
    color = NULL,  
    linetype = NULL,  
    n = 9,  
    facet = NULL,  
    nrow = NULL,  
    ncol = NULL,  
    dir = "h",  
    scales = "free",  
    labeller = label_value,  
    palette = NULL,  
    fixed = list(alpha = 0.8, na.rm = TRUE)  
)
```

Arguments

object	SummarizedExperiment
assay	string
group	svar (string)
fill	svar (string)
color	svar (string)
linetype	svar (string)
facet	svar (character vector)
nrow	number of facet rows
ncol	number of facet cols
dir	'h' (horizontal) or 'v' (vertical)
scales	'free', 'fixed', 'free_y'
labeller	e.g. label_value
palette	named character vector
fixed	fixed aesthetics
n	number

Value

ggplot object

See Also

[plot_sample_violins](#), [plot_sample_boxplots](#)

Examples

```
# Data
  file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
  object <- read_metabolon(file)
  object %>% extract(, order(.\$subgroup))

# Sample distributions
  plot_sample_densities(object)
  plot_sample_violins( object, facet = 'Time')
  plot_sample_boxplots(object)
  plot_exprs(object)
  plot_exprs(object, dim = 'samples', x = 'subgroup', facet = 'Time')

# Feature distributions
  plot_feature_densities(object)
  plot_feature_violins( object)
  plot_feature_boxplots( object)
```

[plot_design](#)

Plot model

Description

Plot model

Usage

```
plot_design(object, codingfun = contr.treatment)
```

Arguments

object	'SummarizedExperiment'
codingfun	factor coding function <ul style="list-style-type: none"> • contr.treatment: intercept = y0, coefi = yi - y0 • contr.treatment.explicit: intercept = y0, coefi = yi - y0 • code_control: intercept = ymean, coefi = yi - y0 • contr.diff: intercept = y0, coefi = yi - y(i-1) • code_diff: intercept = ymean, coefi = yi - y(i-1) • code_diff_forward: intercept = ymean, coefi = yi - y(i+)

- code_deviation: intercept = ymean, coefi = yi - ymean (drop last)
- code_deviation_first: intercept = ymean, coefi = yi - ymean (drop first)
- code_helmert: intercept = ymean, coefi = yi - mean(y0:(yi-1))
- code_helmert_forward: intercept = ymean, coefi = yi - mean(y(i+1):yp)

Value

ggplot

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
subgroups <- paste0(c('E00', 'E01', 'E02', 'E05', 'E15', 'E30', 'M00'), '_STD')
object <- read_maxquant_proteingroups(file, subgroups = subgroups)
object$subgroup %<-% substr(1,3)
plot_design(object)
```

plot_detections

*Plot missingness per sample / subgroup***Description**

plot_sample_nas shows systematic and random missingness (white), and full detection (bright color) at sample resolution. Imputations are also shown (light color).

Usage

```
plot_detections(...)

plot_summarized_detections(...)

plot_sample_nas(
  object,
  by = "subgroup",
  fill = by,
  palette = make_svar_palette(object, fill),
  axis.text.y = element_blank()
)

plot_subgroup_nas(
  object,
  by = "subgroup",
  fill = by,
  palette = NULL,
  na_imputes = TRUE
)
```

Arguments

...	used to maintain deprecated functions
object	SummarizedExperiment
by	svar (string)
fill	svar (string)
palette	color vector (names = levels, values = colors)
axis.text.y	passed to ggplot2::theme
na_imputes	TRUE or FALSE

Details

`plot_subgroup_nas` shows systematic missingness at subgroup resolution. Random missingness and full detection are shown together (bright color). Imputations are also shown (light color).

Value

ggplot object

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
plot_sample_nas(object)
plot_sample_nas(impute(object))
plot_subgroup_nas(object)
plot_subgroup_nas(impute(object))

subgroups <- sprintf('%s_STD', c('E00','E01','E02','E05','E15','E30','M00'))
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file, subgroups = subgroups)
plot_subgroup_nas(object)
plot_subgroup_nas(object, 'subgroup')
plot_sample_nas(object)
plot_sample_nas(object, 'subgroup')
```

Description

Plot exprs for coef

Usage

```
plot_exprs(
  object,
  dim = "both",
  assay = assayNames(object)[1],
  fit = fits(fdt(object))[1],
  coefs = default_coefs(fdt(object), fit = fit),
  block = NULL,
  x = default_x(object, dim),
  geom = default_geom(object, x = x, block = block),
  color = x,
  fill = x,
  shape = NULL,
  size = NULL,
  alpha = NULL,
  linetype = NULL,
  highlight = NULL,
  combiner = "|",
  p = 1,
  fdr = 1,
  facet = if (dim == "both") "feature_id" else NULL,
  n = 4,
  ncol = NULL,
  nrow = NULL,
  scales = "free_y",
  labeller = "label_value",
  pointsize = if (is.null(block)) 0 else 0.5,
  jitter = if (is.null(block)) 0.1 else 0,
  fillpalette = make_var_palette(object, fill),
  colorpalette = make_var_palette(object, color),
  hlevels = NULL,
  title = switch(dim, both = x, features = "Feature Boxplots", samples =
    "Sample Boxplots"),
  subtitle = if (!is.null(fit)) coefs else "",
  xlab = NULL,
  ylab = "value",
  theme = ggplot2::theme(plot.title = element_text(hjust = 0.5)),
  file = NULL,
  width = 7,
  height = 7,
  verbose = TRUE
)

plot_sample_boxplots(
  object,
  fill = if ("subgroup" %in% svars(object)) "subgroup" else "sample_id",
  n = min(ncol(object), 16),
  ...
```

```
)
  plot_feature_boxplots(object, ...)
```

Arguments

<code>object</code>	SummarizedExperiment
<code>dim</code>	'samples' (per-sample distribution across features), 'features' (per-feature distribution across samples) or 'both' (subgroup distribution faceted per feature)
<code>assay</code>	string: value in assayNames(object)
<code>fit</code>	'limma', 'lme', 'lmer', 'wilcoxon'
<code>coefs</code>	subset of coefs(fdt(object)) to consider in selecting top
<code>block</code>	group svar
<code>x</code>	x svar
<code>geom</code>	'boxplot' or 'point'
<code>color</code>	color svar: points, lines
<code>fill</code>	fill svar: boxplots
<code>shape</code>	shape svar
<code>size</code>	size svar
<code>alpha</code>	alpha svar
<code>linetype</code>	linetype svar
<code>highlight</code>	highlight svar
<code>combiner</code>	'&' or 'l'
<code>p</code>	fraction: p cutoff
<code>fdr</code>	fraction: fdr cutoff
<code>facet</code>	string: fvar mapped to facet
<code>n</code>	number of samples (dim = 'samples') or features (dim = 'features' or 'both') to plot
<code>ncol</code>	number of cols in faceted plot (if dim = 'both')
<code>nrow</code>	number of rows in faceted plot (if dim = 'both')
<code>scales</code>	'free_y', 'free_x', 'fixed'
<code>labeller</code>	string or function
<code>pointsize</code>	number
<code>jitter</code>	jitter width (number)
<code>fillpalette</code>	named character vector: fill palette
<code>colorpalette</code>	named character vector: color palette
<code>hlevels</code>	xlevels for which to plot hlines
<code>title</code>	string

subtitle	string
xlab	string
ylab	string
theme	ggplot2::theme(...) or NULL
file	NULL or filepath
width	inches
height	inches
verbose	TRUE or FALSE
...	used to maintain deprecated functions

Value

ggplot object

See Also

[plot_sample_densities](#), [plot_sample_violins](#)

Examples

```
# Without limma
  file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
  object <- read_metabolon(file)
  plot_exprs(object, block = 'Subject', title = 'Subgroup Boxplots')
  plot_exprs(object, dim = 'samples')
  plot_exprs(object, dim = 'features', block = 'sample_id')
# With limma
  object %>% fit_limma(block = 'Subject')
  plot_exprs(object, block = 'Subject')
  plot_exprs(object, block = 'Subject', coefs = c('t1', 't2', 't3'))
  plot_exprs_per_coef(object, x = 'Time', block = 'Subject')
# Points
  plot_exprs(object, geom = 'point', block = 'Subject')
# Add highlights
  controlfeatures <- c('biotin', 'phosphate')
  fdt(object) %>% cbind(control = .$feature_name %in% controlfeatures)
  plot_exprs(object, dim = 'samples', highlight = 'control')
# Multiple pages
  plot_exprs(object, block = 'Subject', n = 4, nrow = 1, ncol = 2)
```

plot_exprs_per_coef *Plot exprs per coef*

Description

Plot exprs per coef

Usage

```
plot_exprs_per_coef(
  object,
  fit = fits(fdt(object))[1],
  coefs = default_coefs(fdt(object), fit = fit),
  x = default_x(object),
  geom = default_geom(object, x),
  block = NULL,
  orderbyp = FALSE,
  title = x,
  subtitle = default_subtitle(fit, x, coefs),
  n = 1,
  nrow = 1,
  ncol = NULL,
  theme = ggplot2::theme(legend.position = "bottom", legend.title = element_blank(),
  plot.title = element_text(hjust = 0.5), plot.subtitle = element_text(hjust = 0.5))
)
```

Arguments

object	SummarizedExperiment
fit	'limma', 'lm', 'lme', 'lmer', 'wilcoxon'
coefs	subset of coefs(fdt(object)) to consider in selecting top
x	x svar
geom	'boxplot' or 'point'
block	group svar
orderbyp	TRUE or FALSE
title	string
subtitle	string
n	number
nrow	number of rows in faceted plot
ncol	number of cols in faceted plot
theme	ggplot2::theme(...) or NULL

Value

ggplot object

See Also

[plot_sample_densities](#), [plot_sample_violins](#)

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% fit_limma()
object %>% pls(by = 'subgroup')
object %>% pls(by = 'Diabetes')
object %>% pls(by = 'Subject')
plot_exprs_per_coef(object)
plot_exprs_per_coef(object, orderbyp = TRUE)
plot_exprs_per_coef(object, fit = 'pls1', block = 'Subject')
```

plot_fit_summary *Plot fit summary*

Description

Plot fit summary

Usage

```
plot_fit_summary(sumdt, nrow = NULL, ncol = NULL, order = FALSE)
```

Arguments

sumdt	data.table
nrow	number
ncol	number
order	TRUE or FALSE

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% fit_lm()
object %>% fit_limma(block = 'Subject')
sumdt <- summarize_fit(fdt(object), coefs = c('t1', 't2', 't3'))
plot_fit_summary(sumdt)
```

plot_heatmap*Plot heatmap***Description**

Plot heatmap

Usage

```
plot_heatmap(
  object,
  fit = fits(fdt(object))[1],
  coef = default_coefs(fdt(object), fit = fit)[1],
  effectsize = 0,
  p = 1,
  fdr = 0.05,
  n = 100,
  assay = assayNames(object)[1],
  cluster_features = FALSE,
  cluster_samples = FALSE,
  flabel = intersect(c("gene", "feature_id"), fvars(object))[1],
  group = "subgroup",
  verbose = TRUE
)
```

Arguments

object	SummarizedExperiment
fit	'limma', 'lm', 'lme(r)', 'wilcoxon'
coef	string: one of coefs(fdt(object))
effectsize	number: effectsize filter
p	number: p filter
fdr	number: fdr filter
n	number: n filter
assay	string: one of assayNames(object)
cluster_features	TRUE or FALSE
cluster_samples	TRUE or FALSE
flabel	string: feature label
group	sample groupvar
verbose	TRUE or FALSE

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file, fit = 'limma')
plot_heatmap(object)
```

plot_matrix*Plot binary matrix*

Description

Plot binary matrix

Usage

```
plot_matrix(mat)
```

Arguments

mat matrix

Value

no return (base R plot)

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
mat <- sdt(object)[, .(replicate, subgroup)]
mat$present <- 1
mat %>% data.table::dcast(replicate ~ subgroup, value.var = 'present', fill = 0)
mat %>% dt2mat()
plot_matrix(mat)
```

plot_subgroup_points *Plot features*

Description

Plot features

Usage

```
plot_subgroup_points(
  object,
  subgroup = "subgroup",
  block = NULL,
  x = subgroup,
  color = subgroup,
  group = block,
  facet = "feature_id",
  nrow = NULL,
  scales = "free_y",
  ...,
  palette = NULL,
  fixed = list(na.rm = TRUE),
  theme = list(axis.text.x = element_text(angle = 90, vjust = 0.5, hjust = 1))
)
```

Arguments

object	SummarizedExperiment
subgroup	subgroup svar
block	block svar
x	svar mapped to x
color	svar mapped to color
group	svar mapped to group
facet	svar mapped to facets
nrow	number of rows
scales	'free_y' etc.
...	mapped aesthetics
palette	color palette (named character vector)
fixed	fixed aesthetics
theme	ggplot theme specifications

Value

ggplot object

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file, fit = 'limma')
idx <- order(fdata(object)$`p~t1~limma`)[1:9]
object %>% extract(idx, )
plot_sample_boxplots( object)
plot_feature_boxplots( object)
```

```
plot_sample_boxplots(object, x = 'Time')
plot_subgroup_points( object, subgroup = 'Time')
plot_subgroup_points( object, subgroup = 'Time', block = 'Subject')
```

plot_summary

Plot summary

Description

Plot summary

Usage

```
plot_summary(
  object,
  fit = "limma",
  formula = default_formula(object),
  block = NULL,
  label = "feature_id",
  palette = make_svar_palette(object, svar = svar)
)
```

Arguments

object	SummarizedExperiment
fit	linmod engine : 'limma', 'lm', 'lme', 'lmer' or 'wilcoxon'
formula	model formula
block	NULL or svar
label	fvar
palette	NULL or colorvector

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %>% pca()
object %>% pls(by = 'subgroup')
object %>% fit_limma()
plot_summary(object, block = 'Subject')
```

plot_venn

Plot venn

Description

Plot venn

Usage

```
plot_venn(x)
```

Arguments

x	list
---	------

Examples

```
x <- list(roundfruit = c('apple', 'orange'), redfruit = c('apple', 'strawberry'))  
plot_venn(x)
```

plot_venn_heatmap

Plot venn heatmap

Description

Plot venn heatmap

Usage

```
plot_venn_heatmap(x)
```

Arguments

x	list
---	------

Examples

```
x <- list(roundfruit = c('apple', 'orange'), redfruit = c('apple', 'strawberry'))  
plot_venn_heatmap(x)
```

plot_violins *Plot sample/feature violins*

Description

Plot sample/feature violins

Usage

```
plot_violins(  
  object,  
  assay = assayNames(object)[1],  
  x,  
  fill,  
  color = NULL,  
  group = NULL,  
  facet = NULL,  
  nrow = NULL,  
  ncol = NULL,  
  dir = "h",  
  scales = "free",  
  labeller = label_value,  
  highlight = NULL,  
  palette = NULL,  
  fixed = list(na.rm = TRUE)  
)  
  
plot_feature_violins(  
  object,  
  assay = assayNames(object)[1],  
  x = "feature_id",  
  fill = "feature_id",  
  color = NULL,  
  n = 9,  
  facet = NULL,  
  nrow = NULL,  
  ncol = NULL,  
  dir = "h",  
  scales = "free",  
  labeller = label_value,  
  highlight = NULL,  
  fixed = list(na.rm = TRUE)  
)  
  
plot_sample_violins(  
  object,  
  assay = assayNames(object)[1],
```

```

x = "sample_id",
fill = if ("subgroup" %in% svars(object)) "subgroup" else "sample_id",
color = NULL,
n = 100,
facet = NULL,
nrow = NULL,
ncol = NULL,
dir = "h",
scales = "free",
labeller = label_both,
highlight = NULL,
fixed = list(na.rm = TRUE)
)

plot_subgroup_violins(
  object,
  assay = assayNames(object)[1],
  subgroup,
  x = "subgroup",
  fill = "subgroup",
  color = NULL,
  highlight = NULL,
  facet = "feature_id",
  fixed = list(na.rm = TRUE)
)

```

Arguments

object	SummarizedExperiment
assay	string
x	svar (string)
fill	svar (string)
color	svar (string)
group	svar (string)
facet	svar (character vector)
nrow	NULL or number
ncol	NULL or number
dir	'h' or 'v' : are facets filled horizontally or vertically ?
scales	'free', 'free_x', 'free_y', or 'fixed'
labeller	label_both or label_value
highlight	fvar expressing which feature should be highlighted (string)
palette	named color vector (character vector)
fixed	fixed aesthetics
n	number
subgroup	subgroup svar

Value

ggplot object

See Also

[plot_exprs](#), [plot_densities](#)

Examples

```
# data
  file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
  object <- read_metabolon(file)
  object %>% extract(, order(.subgroup))
  control_features <- c('biotin','phosphate')
  fdata(object) %>% cbind(control = .$feature_name %in% control_features)
# plot
  plot_violins(object[1:12, ], x = 'feature_id', fill = 'feature_id')
  plot_feature_violins(object[1:12, ])
  plot_sample_violins(object[, 1:12], highlight = 'control')
  plot_subgroup_violins(object[1:4, ], subgroup = 'subgroup')
```

plot_volcano

Plot volcano

Description

Plot volcano

Usage

```
plot_volcano(
  object,
  fit = fits(fdt(object))[1],
  coefs = default_coefs(fdt(object), fit = fit)[1],
  facet = if (is_scalar(fit)) "coef" else c("fit", "coef"),
  shape = if ("imputed" %in% fvars(object)) "imputed" else NULL,
  size = NULL,
  alpha = NULL,
  label = "feature_id",
  max.overlaps = 10,
  features = NULL,
  nrow = length(fit),
  p = 0.05,
  fdr = 0.05,
  xndown = NULL,
  xnup = NULL,
  title = NULL
)
```

Arguments

object	SummarizedExperiment
fit	'limma', 'lme', 'lm', 'wilcoxon'
coefs	character vector
facet	character vector
shape	fvar (string)
size	fvar (string)
alpha	fvar (string)
label	fvar (string)
max.overlaps	number: passed to ggrepel
features	feature ids (character vector): features to encircle
nrow	number: no of rows in plot
p	number: p cutoff for labeling
fdr	number: fdr cutoff for labeling
xndown	x position of ndown labels
xnup	x position of nup labels
title	string or NULL

Value

ggplot object

Examples

```
# Regular Usage
  file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
  object <- read_metabolon(file)
  object %>% fit_limma()
  object %>% fit_lm()
  plot_volcano(object, coefs = 't3', fit = 'limma')           # single contrast
  plot_volcano(object, coefs = c('t2', 't3'), fit = 'limma')    # multip contrasts
  plot_volcano(object, coefs = c('t2', 't3'), fit = c('limma', 'lm')) # multip contrs & methods

# When nothing passes FDR
  fdt(object) %>% add_adjusted_pvalues('fdr', fit = 'limma', coefs = 't3')
  object %>% extract( fdrvec(fdt(object)), fit = 'limma', coef = 't3') > 0.05, )
  plot_volcano(object, coefs = 't3', fit = 'limma')

# Additional mappings
  file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
  object <- read_maxquant_proteingroups(file, impute = TRUE)
  object %>% fit_limma()
  plot_volcano(object)
  plot_volcano(object, label = 'gene')
  plot_volcano(object, label = 'gene', size = 'log2maxlfq')
  plot_volcano(object, label = 'gene', size = 'log2maxlfq', alpha = 'pepcounts')
  plot_volcano(object, label = 'gene', features = c('hmbsb'))
```

PRECURSOR_QUANTITY *dian precursor quantity*

Description

dian precursor quantity

Usage

PRECURSOR_QUANTITY

Format

An object of class character of length 1.

preprocess_rnaseq_counts
Preprocess RNAseq counts

Description

Preprocess RNAseq counts

Usage

```
preprocess_rnaseq_counts(  
  object,  
  formula = ~subgroup,  
  block = NULL,  
  min_count = 10,  
  pseudo = 0.5,  
  tpm = FALSE,  
  cpm = TRUE,  
  voom = TRUE,  
  log2 = TRUE,  
  verbose = TRUE,  
  plot = TRUE  
)
```

Arguments

object	SummarizedExperiment
formula	designmat formula
block	blocK svar
min_count	min count required in some samples

pseudo	added pseudocount to avoid log(x)=-Inf
tpm	TRUE or FALSE : tpm normalize?
cpm	TRUE or FALSE : cpm normalize? (counts per million (scaled) reads)
voom	TRUE or FALSE : voom weight?
log2	TRUE or FALSE : log2 transform?
verbose	TRUE or FALSE : msg?
plot	TRUE or FALSE : plot?

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- .read_rnaseq_counts(file)
object$subgroup
object %>>% preprocess_rnaseq_counts()
```

pull_columns

Pull columns in a dataframe to the front

Description

Pull columns in a dataframe to the front

Usage

```
pull_columns(df, first_cols, verbose = TRUE)
```

Arguments

df	data.frame
first_cols	character vector: columns to be pulled to the front
verbose	TRUE (default) or FALSE

Value

dataframe with re-ordered columns

Examples

```
df <- data.frame(
  symbol = c('A1BG', 'A2M'),
  id     = c('1', '2'),
  name   = c('alpha-1-B glycoprotein', 'alpha-2-macroglobulin'),
  type   = c('proteinencoding', 'proteinencoding'))
first_cols <- c('id', 'symbol', 'location', 'uniprot')
pull_columns(df, first_cols)
```

read_affymetrix	<i>Read affymetrix microarray</i>
-----------------	-----------------------------------

Description

Read affymetrix microarray

Usage

```
read_affymetrix(celfiles)
```

Arguments

celfiles	string vector: CEL file paths
----------	-------------------------------

Value

RangedSummarizedExperiment

Examples

```
# Downloading example dataset fails 600s limit - example outcommented.  
# url <- paste0('http://www.bioconductor.org/help/publications/2003/Chiaretti/chiaretti2/T33.tgz')  
# localdir <- file.path(tools:::R_user_dir('autonomics', 'cache'), 'T33')  
# dir.create(localdir, showWarnings = FALSE)  
# localfile <- file.path(localdir, basename(url))  
# if (!file.exists(localfile)){ download.file(url, destfile = localfile)  
#                           untar(localfile, exdir = path.expand(localdir)) }  
# localfile %<>% substr(1, nchar(.)-4)  
# if (!requireNamespace("BiocManager", quietly = TRUE)) install.packages('BiocManager')  
# if (!requireNamespace("hgu95av2.db", quietly = TRUE)) BiocManager::install('hgu95av2.db')  
# read_affymetrix(celfiles = list.files(localfile, full.names = TRUE))
```

read_compounddiscoverer	<i>Read maxquant proteingroups</i>
-------------------------	------------------------------------

Description

Read maxquant proteingroups

Usage

```
read_compounddiscoverer(
  dir = getwd(),
  files = list.files(path = dir, pattern = ".*\\.csv$", full.names = TRUE),
  quantity = NULL,
  subgroups = NULL,
  impute = FALSE,
  plot = FALSE,
  label = "feature_id",
  pca = plot,
  pls = plot,
  fit = if (plot) "limma" else NULL,
  formula = ~subgroup,
  block = NULL,
  coefs = NULL,
  contrasts = NULL,
  palette = NULL,
  verbose = TRUE
)
```

Arguments

dir	compound discoverer output directory
files	compound discoverer output files
quantity	'area', 'normalizedarea' or NULL
subgroups	NULL or string vector : subgroups to retain
impute	TRUE or FALSE: impute group-specific NA values?
plot	TRUE or FALSE: plot ?
label	fvar
pca	TRUE or FALSE: run pca ?
pls	TRUE or FALSE: run pls ?
fit	model engine: 'limma', 'lm', 'lme(r)', 'wilcoxon' or NULL
formula	model formula
block	model blockvar: string or NULL
coefs	model coefficients of interest: character vector or NULL
contrasts	coefficient contrasts of interest: character vector or NULL
palette	color palette : named character vector
verbose	TRUE or FALSE : message ?

Value

SummarizedExperiment

read_contaminants *Read contaminants*

Description

Read contaminants

Usage

```
read_contaminants(file = download_contaminants())
```

Arguments

file	contaminant file
------	------------------

Value

data.table

Examples

```
file <- download_contaminants()
dt <- read_contaminants(file)
```

read_fragpipe *Read fragpipe*

Description

Read fragpipe

Usage

```
read_fragpipe(
  dir = getwd(),
  file = if (is_file(dir)) dir else file.path(dir, "combined_protein.tsv"),
  contaminants = FALSE,
  verbose = TRUE
)
```

Arguments

dir	directory with 'combined_protein.tsv'
file	'combined_protein.tsv' (full path)
contaminants	whether to include contaminants
verbose	whether to msg

Value

SummarizedExperiment

Examples

```
file <- download_data('multiorganism.combined_protein.tsv')
object <- read_fragpipe(file = file)
object
fdt(object)
sdt(object)
```

read_maxquant_phosphosites

Read maxquant phosphosites

Description

Read maxquant phosphosites

Usage

```
read_maxquant_phosphosites(
  dir = getwd(),
  fosfile = if (is_file(dir)) dir else file.path(dir, "phospho (STY)Sites.txt"),
  profile = file.path(dirname(fosfile), "proteinGroups.txt"),
  fastafile = NULL,
  restapi = FALSE,
  quantity = NULL,
  subgroups = NULL,
  invert = character(0),
  contaminants = FALSE,
  reverse = FALSE,
  rm_missing_in_all_samples = TRUE,
  localization = 0.75,
  impute = FALSE,
  plot = FALSE,
  label = "feature_id",
  pca = plot,
  pls = plot,
  fit = if (plot) "limma" else NULL,
  formula = ~subgroup,
  block = NULL,
  coefs = NULL,
  contrasts = NULL,
  palette = NULL,
  verbose = TRUE
)
```

```
read_phosphosites(...)
```

Arguments

dir	proteingroups directory
fosfile	phosphosites file
profile	proteingroups file
fastafilename	uniprot fastafilename
restapi	TRUE or FALSE : annotate non-fastaadt uniprots using uniprot restapi
quantity	'normalizedratio', 'ratio', 'correctedreporterintensity', 'reporterintensity', 'maxlfq', 'labeledintensity', 'intensity' or NULL
subgroups	NULL or string vector : subgroups to retain
invert	string vector: subgroups which require inversion
contaminants	TRUE or FALSE: retain contaminants ?
reverse	TRUE or FALSE: include reverse hits
rm_missing_in_all_samples	TRUE or FALSE
localization	number: min localization probability (for phosphosites)
impute	TRUE or FALSE: impute group-specific NA values?
plot	TRUE or FALSE
label	fvar
pca	TRUE or FALSE: run pca ?
pls	TRUE or FALSE: run pls ?
fit	model engine: 'limma', 'lm', 'lme(r)', 'wilcoxon' or NULL
formula	model formula
block	model blockvar: string or NULL
coefs	model coefficients of interest: string vector or NULL
contrasts	model coefficient contrasts of interest: string vector or NULL
palette	color palette: named string vector
verbose	TRUE or FALSE: message ?
...	maintain deprecated functions

Value

SummarizedExperiment

Examples

```

profile <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
fosfile <- system.file('extdata/billing19.phosphosites.txt', package = 'autonomics')
fastafile <- system.file('extdata/uniprot_hsa_20140515.fasta', package = 'autonomics')
subgroups <- sprintf('%s_STD', c('E00', 'E01', 'E02', 'E05', 'E15', 'E30', 'M00'))
pro <- read_maxquant_proteingroups(file = profile, subgroups = subgroups)
fos <- read_maxquant_phosphosites(
  fosfile = fosfile, profile = profile, subgroups = subgroups)
fos <- read_maxquant_phosphosites(
  fosfile = fosfile, profile = profile, fastafile = fastafile, subgroups = subgroups)

```

read_maxquant_proteingroups*Read maxquant proteingroups***Description**

Read maxquant proteingroups

Usage

```

read_maxquant_proteingroups(
  dir = getwd(),
  file = if (is_file(dir)) dir else file.path(dir, "proteinGroups.txt"),
  fastafile = NULL,
  restapi = FALSE,
  quantity = NULL,
  subgroups = NULL,
  invert = character(0),
  contaminants = FALSE,
  reverse = FALSE,
  rm_missing_in_all_samples = TRUE,
  impute = FALSE,
  plot = FALSE,
  label = "feature_id",
  pca = plot,
  pls = plot,
  fit = if (plot) "limma" else NULL,
  formula = ~subgroup,
  block = NULL,
  coefs = NULL,
  contrasts = NULL,
  palette = NULL,
  verbose = TRUE
)

```

`read_proteingroups(...)`

Arguments

dir	proteingroups directory
file	proteingroups file
fastafile	uniprot fastafile
restapi	TRUE or FALSE : use uniprot restapi to annotate uniprots not in fastadt ?
quantity	'normalizedratio', 'ratio', 'correctedreporterintensity', 'reporterintensity', 'maxlfq', 'labeledintensity', 'intensity' or NULL
subgroups	NULL or string vector : subgroups to retain
invert	string vector : subgroups which require inversion
contaminants	TRUE or FALSE : retain contaminants ?
reverse	TRUE or FALSE : include reverse hits ?
rm_missing_in_all_samples	TRUE or FALSE
impute	TRUE or FALSE: impute group-specific NA values?
plot	TRUE or FALSE: plot ?
label	fvar
pca	TRUE or FALSE: run pca ?
pls	TRUE or FALSE: run pls ?
fit	model engine: 'limma', 'lm', 'lme(r)', 'wilcoxon' or NULL
formula	model formula
block	model blockvar: string or NULL
coefs	model coefficients of interest: character vector or NULL
contrasts	coefficient contrasts of interest: character vector or NULL
palette	color palette : named character vector
verbose	TRUE or FALSE : message ?
...	maintain deprecated functions

Value

SummarizedExperiment

Examples

```
# fukuda20 - LFQ
  file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
  pro <- read_maxquant_proteingroups(file = file)

# billing19 - Normalized Ratios
  file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
  fastafile <- system.file('extdata/uniprot_hsa_20140515.fasta', package = 'autonomics')
  subgroups <- sprintf('%s_STD', c('E00', 'E01', 'E02', 'E05', 'E15', 'E30', 'M00'))
  pro <- read_maxquant_proteingroups(file = file, subgroups = subgroups)
  pro <- read_maxquant_proteingroups(file = file, fastafile = fastafile, subgroups = subgroups)
```

read_msigdt	<i>Read msigdb datatable</i>
-------------	------------------------------

Description

Read msigdb datatable

Usage

```
read_msigdt(
  file = list_files(MSIGDIR, full.names = TRUE)[1],
  collections = if (is.null(file)) NULL else switch(basename(file) %>% substr(nchar(.) - 4, nchar(.) - 3), Hs = c("C2:CP:REACTOME", "C5:GO:BP", "C5:GO:MF", "C5:GO:CC"), Mm = c("M2:CP:REACTOME", "M5:GO:BP", "M5:GO:MF", "M5:GO:CC"))
)
```

Arguments

file	msigdb file: one of the files in dir(MSIGDB).
collections	subset of names(MSIGCOLLECTIONS)

Examples

```
read_msigdt()
```

read_olink	<i>Read olink file</i>
------------	------------------------

Description

Read olink file

Usage

```
read_olink(file, sample_excel = NULL, sample_tsv = NULL, by.y = "SampleID")
```

Arguments

file	olinkfile
sample_excel	sample excel
sample_tsv	sample tsv
by.y	sample tsv mergeby column

Value

SummarizedExperiment

Examples

```
# Example data
  npxdt  <- data.table::data.table(OlinkAnalyze::npx_data1)[, c(1:11, 17)]
  sampledt <- data.table::data.table(OlinkAnalyze::npx_data1)[, c(1, 12:15)]
  sampledt %>% extract(!grepl('CONTROL', SampleID))
  sampledt %>% unique()
# Write to file
  file <- paste0(tempfile(), '.olink.csv')
  samplefile <- paste0(tempfile(), '.samples.xlsx')
  data.table::fwrite(npxdt, file)
  writexl::write_xlsx(sampledt, samplefile)
# Read
  object <- read_olink(file, sample_excel = samplefile)
  biplot(pca(object), color = 'Time', group = 'Subject', shape = 'Treatment')
```

read_salmon

Read salmon

Description

Read salmon

Usage

```
read_salmon(dir, sfile = NULL, by = NULL, ensdb = NULL)
```

Arguments

dir	salmon results rootdir
sfile	samplefile
by	samplefile column to merge by
ensdb	EnsDb object

Value

SummarizedExperiment

Examples

```
# dir <- '../bh/salmon_quants'
# sfile <- '../bh/samplesheet.csv'
# by <- 'salmonDir'
# ah <- AnnotationHub::AnnotationHub()
# ensdb <- ah[['AH98078']]
# read_salmon(dir, sfile = sfile, by = 'salmonDir', ensdb = ensdb)
```

read_uniprotdt *Read fasta hdrs*

Description

Read fasta hdrs

Usage

```
read_uniprotdt(fastafile, fastafields = FASTAFIELDS, verbose = TRUE)

parse_maxquant_hdrs(fastahdrs)

read_contaminantdt(force = FALSE, verbose = TRUE)
```

Arguments

fastafile	string (or charactervector)
fastafeilds	charactervector : which fastahdr fields to extract ?
verbose	bool
fastahdrs	character vector
force	whether to overwrite existing file

Value

`data.table(uniprot, protein, gene, uniprot, reviewed, existence)`

Note

existence values are always those of the canonical isoform (no isoform-level resolution for this field)

Examples

```
# uniprot hdrs
  fastafile <- system.file('extdata/uniprot_hsa_20140515.fasta', package = 'autonomics')
  read_uniprotdt(fastafile)

# maxquant hdrs
  file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
  dt <- .read_maxquant_proteingroups(file)
  parse_maxquant_hdrs(dt$`Fasta headers`)

  profile <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
  fosfile <- system.file('extdata/billing19.phosphosites.txt', package = 'autonomics' )
  prodt <- .read_maxquant_proteingroups(profile)
  fosdt <- .read_maxquant_phosphosites(fosfile, profile)
  parse_maxquant_hdrs(prodt$`Fasta headers`)
  parse_maxquant_hdrs(fosdt$`Fasta headers`)
```

```
# contaminant hdrs  
read_contaminantdt()
```

reexports*Objects exported from other packages*

Description

These objects are imported from other packages. Follow the links below to see their documentation.

data.table [data.table](#)
magrittr [%<>%](#), [%>%](#), [extract](#)

reset_fit*Reset fit*

Description

Reset fit

Usage

```
reset_fit(  
  object,  
  fit = fits(fdt(object)),  
  coefs = autonomics::coefs(fdt(object), fit = fit),  
  verbose = TRUE  
)
```

Arguments

object	SummarizedExperiment
fit	character vector
coefs	character vector
verbose	TRUE or FALSE

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')  
(object <- read_metabolon(file))  
object %<>% reset_fit()  
object %<>% fit_limma() %>% reset_fit()  
object %<>% fit_limma() %>% fit_lm() %>% reset_fit()  
object %<>% fit_limma() %>% fit_lm() %>% reset_fit('limma')
```

`rm_diann_contaminants` *Rm contaminants*

Description

Rm contaminants from DIA-NN SumExp

Usage

```
rm_diann_contaminants(
  object,
  contaminants = read_contaminants(),
  verbose = TRUE
)
```

Arguments

<code>object</code>	SummarizedExperiment
<code>contaminants</code>	uniprot (character vector)
<code>verbose</code>	TRUE or FALSE

Value

SummarizedExperiment

Examples

```
file <- download_data('dilution.report.tsv')
object <- read_diann_proteingroups(file)
object %>% rm_diann_contaminants()
```

`rm_missing_in_all_samples`

Rm features missing in some samples

Description

Rm features missing in some samples

Usage

```
rm_missing_in_all_samples(object, verbose = TRUE)

rm_missing_in_some_samples(object, verbose = TRUE)
```

Arguments

object	SummarizedExperiment
verbose	TRUE (default) or FALSE

Value

updated object

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
rm_missing_in_all_samples( object)
rm_missing_in_some_samples(object)
```

rm_unmatched_samples *rm unmatched singleton samples*

Description

rm unmatched singleton samples

Usage

```
rm_unmatched_samples(
  object,
  subgroupvar = "subgroup",
  subgroupctr = slevels(object, subgroupvar)[1],
  block,
  verbose = TRUE
)
rm_singleton_samples(object, subgroupvar = "subgroup", verbose = TRUE)
```

Arguments

object	SummarizedExperiment
subgroupvar	subgroup variable (string)
subgroupctr	control subgroup (string)
block	block variable (string)
verbose	TRUE/FALSE

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.somascan.adat', package = 'autonomics')
object <- read_somascan(file)
object %>% filter_samples(subgroup %in% c('t1', 't2'), verbose = TRUE)
rm_singleton_samples(object, subgroupvar = 'Subject')
rm_unmatched_samples(object, subgroupvar = 'subgroup', block = 'Subject')
```

scaledlibsizes *Get tmm-scaled libsizes*

Description

Get tmm-scaled libsizes

Usage

```
scaledlibsizes(counts)
```

Arguments

counts	counts matri
--------	--------------

Value

scaled libsize vector

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnaseq_counts(file)
scaledlibsizes(counts(object))
```

scoremat *Extract scores/loadings*

Description

Extract scores/loadings

Usage

```
scoremat(object, method = "pca", by = biplot_by(object, method), dim = 1:2)

scores(object, method = "pca", by = biplot_by(object, method), dim = 1)

loadingmat(object, method = "pca", by = biplot_by(object, method), dim = 1:2)

loadings(object, method = "pca", by = biplot_by(object, method), dim = 1)
```

Arguments

object	SummarizedExperiment
method	'pca', 'pls', etc.
by	svar (string)
dim	numeric vector

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
object %<>% pca()
  scores(object)[1:2]
  loadings(object)[1:2]
  scoremat(object)[1:2, ]
  loadingmat(object)[1:2, ]
```

slevels

Get slevels

Description

Get svar levels

Usage

```
slevels(object, svar)

subgroup_levels(object)
```

Arguments

object	SummarizedExperiment, eSet, or eList
svar	sample var (character)

Value

svar values (character)

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
slevels(object, 'subgroup')
subgroup_levels(object)
```

snames

*Get/Set snames***Description**

Get/Set sample names

Usage

```
snames(object)

## S4 method for signature 'SummarizedExperiment'
snames(object)

snames(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,character'
snames(object) <- value
```

Arguments

object	SummarizedExperiment
value	string vector with sample names

Value

sample names vector (get) or updated eSet (set)

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
head(snames(object))
head(snames(object) %<-% paste0('SAMPLE_', .))
```

split_samples

*Split samples***Description**

Split samples by svar

Usage

```
split_samples(object, by = "subgroup")
cbind_imputed(objlist)
split_features(object, by)
```

Arguments

object	SummarizedExperiment
by	svar to split by (string)
objlist	SummarizedExperiment list

Value

SummarizedExperiment list

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
objlist <- split_features(object, by = 'PLATFORM')
objlist <- split_samples(object, 'Diabetes')
objlist %>% Map(impute, .)
object <- cbind_imputed(objlist)
```

stri_any_regex	<i>Does any string have a regex</i>
----------------	-------------------------------------

Description

Does any string have a regex

Usage

```
stri_any_regex(str, pattern)
```

Arguments

str	string vector
pattern	string

Value

TRUE or FALSE

Examples

```
str <- c('s1 Spectral Count', 's1 Unique Spectral Count')
patterns <- c('Spectral Count', '(?<!Unique) Spectral Count', 'Intensity')
stringi::stri_detect_regex(str, pattern = patterns[1])
stringi::stri_detect_regex(str, pattern = patterns[2])
stringi::stri_detect_regex(str, pattern = patterns[3])
stri_any_regex( str, pattern = patterns)
```

stri_detect_fixed_in_collapsed

Detect fixed patterns in collapsed strings

Description

Detect fixed patterns in collapsed strings

Usage

```
stri_detect_fixed_in_collapsed(x, patterns, sep)
```

Arguments

x	vector with collapsed strings
patterns	vector with fixed patterns (strings)
sep	collapse separator (string) or NULL (if uncollapsed)

Value

boolean vector

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
x <- fdt(object)$uniprot
patterns <- c('A0A0R4IKT8', 'Q7T3G6')
table(stri_detect_fixed_in_collapsed(x = x, patterns = patterns, sep = ';'))
```

subgroup_array	<i>Get subgroup matrix</i>
----------------	----------------------------

Description

Arrange (subgroup)levels in matrix

Usage

```
subgroup_array(object, subgroupvar)  
subgroup_matrix(object, subgroupvar)
```

Arguments

object	SummarizedExperiment
subgroupvar	subgroup svar

Value

matrix

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')  
object <- read_metabolon(file)  
object$subgroup <- paste0(object$Diabetes, '.', object$subgroup)  
subgroup_matrix(object, 'subgroup')
```

subtract_baseline	<i>Subtract baseline</i>
-------------------	--------------------------

Description

Subtract baseline level within block

Usage

```
subtract_baseline(  
  object,  
  subgroupvar,  
  subgroupctr = slevels(object, subgroupvar)[1],  
  block = NULL,  
  assaynames = setdiff(assayNames(object), c("weights", "pepcounts")),  
  verbose = TRUE  
)
```

```

subtract_pairs(
  object,
  subgroupvar = "subgroup",
  subgroupctr = slevels(object, subgroupvar)[1],
  block,
  assaynames = assayNames(object)[1],
  verbose = TRUE
)

subtract_differences(object, block, subgroupvar, verbose = TRUE)

```

Arguments

object	SummarizedExperiment
subgroupvar	subgroup svar
subgroupctr	control subgroup
block	block svar (within which subtraction is performed)
assaynames	which assays to subtract for
verbose	TRUE/FALSE

Details

subtract_baseline subtracts baseline levels within block, using the medoid baseline sample if multiple exist.

subtract_pairs also subtracts baseline level within block. It cannot handle multiple baseline samples, but has instead been optimized for many blocks

subtract_differences subtracts differences between subsequent levels, again within block

Value

SummarizedExperiment

Examples

```

# read
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object0 <- read_metabolon(file)
pca(object0, plot = TRUE, color = 'Time')

# subtract_baseline: takes medoid of baseline samples if multiple
object <- subtract_baseline(object0, block = 'Subject', subgroupvar = 'Time')
pca(object, plot = TRUE, color = 'Time')

# subtract_pairs: optimized for many blocks
object <- subtract_pairs(object0, block = 'Subject', subgroupvar = 'Time')

```

```

pca(object, plot = TRUE, color = 'Time')

# subtract_differences
object <- subtract_differences(object0, block = 'Subject', subgroupvar = 'Time')
values(object) %>>% na_to_zero()
pca(object, plot = TRUE, color = 'Time')

```

sumexplist_to_longdt *SummarizedExperiment list to long data.table*

Description

SummarizedExperiment list to long data.table

Usage

```

sumexplist_to_longdt(
  sumexplist,
  svars = intersect("subgroup", autonomics::svars(sumexplist[[1]])),
  fvars = intersect("gene", autonomics::fvars(sumexplist[[1]])),
  setvarname = "set"
)

```

Arguments

sumexplist	list of SummarizedExperiments
svars	character vector
fvars	character vector
setvarname	string

Value

data.table

Examples

```

subgroups <- paste0(c('E00', 'E01', 'E02', 'E05', 'E15', 'E30', 'M00'), '_STD')
rnafile <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
profile <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
fosfile <- system.file('extdata/billing19.phosphosites.txt', package = 'autonomics')
rna <- read_rnaseq_counts(rnafile)
pro <- read_maxquant_proteingroups(file = profile, subgroups = subgroups)
fos <- read_maxquant_phosphosites(fosfile = fosfile, profile = profile, subgroups = subgroups)
pro$subgroup %>>% stringi::stri_replace_first_fixed('_STD', '')
fos$subgroup %>>% stringi::stri_replace_first_fixed('_STD', '')

sumexplist <- list(rna = rna, pro = pro, fos = fos)
dt <- sumexplist_to_longdt(sumexplist, setvarname = 'platform')
dt %>>% extract(gene %in% c('TNMD', 'TSPAN6'))

```

sumexp_to_tsv*Write sumexp to tsv***Description**

Write sumexp to tsv

Usage

```
sumexp_to_tsv(object, assay = assayNames(object)[1], file)
```

Arguments

object	SummarizedExperiment
assay	string
file	filename

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file, fit = 'limma')
tsv <- file.path(tempdir(), 'fukuda20.proteingroups.tsv')
sumexp_to_tsv(object, file = tsv)
```

sumexp_to_widedt*SummarizedExperiment to data.table***Description**

SummarizedExperiment to data.table

Usage

```
sumexp_to_widedt(
  object,
  fvars = autonomics::fvars(object),
  assay = assayNames(object)[1]
)

sumexp_to_longdt(
  object,
  fvars = intersect("feature_name", autonomics::fvars(object)),
  svrs = intersect("subgroup", autonomics::svrs(object)),
  assay = assayNames(object) %>% intersect(c(.[1], "is_imputed"))
)

sumexp_to_subrep_dt(object, subgroup = subgroup)
```

Arguments

object	sumexp
fvars	additional fvars to include in table
assay	matrix in assays(object) to be used
svars	additional svars to include in table
subgroup	subgroup (sym)

Details

- sumexp_to_widedt: feature x sample
- sumexp_to_subrep_dt: feature.subgroup x replicate
- sumexp_to_longdt: feature.sample

Value

data.table

Examples

```
# Atkin Hypoglycemia
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file)
sumexp_to_widedt(object)
sumexp_to_longdt(object)
sumexp_to_subrep_dt(object)

# Fukuda
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
values(object)
fdt(object)
object %>% impute()
table(fdt(object)$imputed)
sumexp_to_longdt(object)
sumexp_to_widedt(object)
sumexp_to_longdt(object)
```

Description

Summarize fit

Usage

```
summarize_fit(
  featuredt,
  fit = fits(featuredt),
  coefs = autometrics::coefs(featuredt, fit = fit)
)
```

Arguments

featured <code>t</code>	<code>fdt(object)</code>
<code>fit</code>	'limma', 'lme', 'lm', 'lme', 'wilcoxon' or <code>NULL</code>
<code>coefs</code>	string vector

Value

`data.table(contrast, nup, ndown)`

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autometrics')
object <- read_metabolon(file)
object %>>% fit_limma()
object %>>% fit_lm()
summarize_fit(fdt(object), coefs = c('t1', 't2', 't3'))
```

svalues

Get/Set svalues

Description

Get/Set svar values

Usage

```
svalues(object, svar)

subgroup_values(object)

sampleid_values(object)

svalues(object, svar) <- value

## S4 replacement method for signature 'SummarizedExperiment,character'
svalues(object, svar) <- value
```

Arguments

object	SummarizedExperiment
svar	sample var (character)
value	value vector

Value

character vector (get) or SummarizedExperiment (set)

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
svalues(object, 'subgroup')
subgroup_values(object)
```

svars

*Get/Set svars***Description**

Get/Set sample variables

Usage

```
svars(object)

## S4 method for signature 'SummarizedExperiment'
svars(object)

## S4 method for signature 'MultiAssayExperiment'
svars(object)

svars(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,character'
svars(object) <- value

## S4 replacement method for signature 'MultiAssayExperiment,character'
svars(object) <- value
```

Arguments

object	SummarizedExperiment
value	string factor with variable names

Value

sample variable names (get) or updated SummarizedExperiment

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
svars(object)[1]
(svarts(object)[1] %<-% paste0('1'))
```

systematic_nas	<i>Is systematic/random/full NA</i>
----------------	-------------------------------------

Description

Is systematic/random/full NA

Usage

```
systematic_nas(object, by = "subgroup", frac = 0.5)

random_nas(object, by = "subgroup")

no_nas(object)
```

Arguments

object	SummarizedExperiment
by	svar (string)
frac	fraction

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
table(systematic_nas(object)) # missing in some subgroups, present in others
table(random_nas(object)) # missing in some samples, independent of subgroup
table(no_nas(object)) # missing in no samples
```

tag_features	<i>Tag features</i>
--------------	---------------------

Description

Tag features

Usage

```
tag_features(  
  object,  
  keyvar,  
  sep,  
  features,  
  tagvar = get_name_in_parent(features),  
  verbose = TRUE  
)
```

Arguments

object	SummarizedExperiment
keyvar	string : intersection fvar
sep	string : keyvar collapse separator
features	character vector : intersection set
tagvar	string :
verbose	TRUE or FALSE

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/atkin.somascan.adat', package = 'autonomics')  
object <- read_somascan(file)  
features <- AnnotationDbi::keys(org.Hs.eg.db::org.Hs.eg.db, keytype = 'SYMBOL')  
object %>% tag_features(keyvar = 'EntrezGeneSymbol', sep = ' ', features)  
table(fdt(object)$features)
```

tag_hdlproteins *Tag hdlproteins*

Description

Tag hdlproteins

Usage

```
tag_hdlproteins(object, verbose = TRUE)
```

Arguments

object	SummarizedExperiment
verbose	TRUE or FALSE

Value

SummarizedExperiment

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
object %>% tag_hdlproteins()
fdt(object)
```

TAXON_TO_ORGNAME *Annotation Maps*

Description

Annotation Maps

Usage

```
TAXON_TO_ORGNAME
ABBREV_TO_ORGNAME
REVIEWED_TO_NUMBER
EXISTENCE_TO_NUMBER
```

Format

- An object of class character of length 7.
- An object of class character of length 4.
- An object of class character of length 2.
- An object of class numeric of length 4.

Examples

```
TAXON_TO_ORGNAME['9606']
ABBREV_TO_ORGNAME['HSA']
REVIEWED_TO_NUMBER['reviewed']
EXISTENCE_TO_NUMBER['Evidence at protein level']
```

TESTS

*Statistical models supported in autonomics***Description**

Statistical models supported in autonomics

Usage

TESTS

Format

- An object of class character of length 5.

Examples

TESTS

tpm

*Get/Set tpm***Description**

Get / Set tpm matrix

Usage

```
tpm(object)

## S4 method for signature 'SummarizedExperiment'
tpm(object)

tpm(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
tpm(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,numERIC'
tpm(object) <- value
```

Arguments

object	SummarizedExperiment
value	tpm matrix (features x samples)

Value

tpm matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnased_counts(file, plot=FALSE)
tpm(object) <- values(object)
tpm(object)[1:3, 1:3]
```

uncollapse	<i>Uncollapse/Recollapse</i>
------------	------------------------------

Description

Uncollapse data.table cols

Usage

```
uncollapse(dt, ..., sep = ";")
recollapse(dt, by, sep = ";")
```

Arguments

dt	data.table
...	cols
sep	string
by	string

Examples

```
(dt <- data.table::data.table(
    uniprot = 'Q9BQL6;Q96AC1;Q96AC1-3',
    protein = 'FERM1_HUMAN;FERM2_HUMAN',
    gene    = 'FERMT1;FERMT2'))
(dt %>% uncollapse(protein, gene, sep = ';'))
(dt %>% recollapse(by = 'uniprot'))
```

values

*Get/Set expr values***Description**

Get/Set value matrix

Usage

```
values(object)

## S4 method for signature 'SummarizedExperiment'
values(object)

values(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
values(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,numeric'
values(object) <- value
```

Arguments

object	SummarizedExperiment
value	ratio matrix (features x samples)

Value

value matrix (get) or updated object (set)

Examples

```
file <- system.file('extdata/billing19.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
values(object)[1:3, 1:3]
values(object) <- 0
values(object)[1:3, 1:3]
```

`varlevels_dont_clash` *Are varlevels unique*

Description

Are varlevels unique

Usage

```
varlevels_dont_clash(object, ...)

## S3 method for class 'data.table'
varlevels_dont_clash(object, vars = names(object), ...)

## S3 method for class 'SummarizedExperiment'
varlevels_dont_clash(object, vars = svars(object), ...)
```

Arguments

object	SummarizedExperiment or data.table
...	required for s3 dispatch
vars	character vector

Value

TRUE or FALSE

Examples

```
require(data.table)
object1 <- data.table(expand.grid(genome = c('WT', 'MUT'), treat = c('control', 'drug')))
object2 <- data.table(expand.grid(mutant = c('YES', 'NO'), treated = c('YES', 'NO')))
varlevels_dont_clash(object1)
varlevels_dont_clash(object2)
```

venn_detects

Venn detects

Description

Venn diagram full/consistent/random detects

Usage

```
venn_detects(object, by = "subgroup")
```

Arguments

object	SummarizedExperiment
by	svar (string)

Value

NULL

Examples

```
file <- system.file('extdata/fukuda20.proteingroups.txt', package = 'autonomics')
object <- read_maxquant_proteingroups(file)
venn_detects(object, 'subgroup')
```

weights

Get/Set weights

Description

Get/Set weight matrix

Usage

```
weights(object, ...)

## S4 method for signature 'SummarizedExperiment'
weights(object)

weights(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,matrix'
weights(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,numERIC'
```

```

weights(object) <- value

## S4 replacement method for signature 'SummarizedExperiment,NULL'
weights(object) <- value

```

Arguments

object	SummarizedExperiment
...	additional params
value	ratio matrix (features x samples)

Value

weight matrix (get) or updated object (set)

Examples

```

file <- system.file('extdata/billing19.rnacounts.txt', package = 'autonomics')
object <- read_rnased_counts(file)
weights(object)[1:3, 1:2]
weights(object) <- 1
weights(object)[1:3, 1:2]

```

write_xl

Write xl/ods

Description

Write xl/ods

Usage

```

write_xl(object, xlfie, fitcoefs = autonomics::fitcoefs(object))

write_ods(object, odsfile, fitcoefs = autonomics::fitcoefs(object))

```

Arguments

object	SummarizedExperiment
xlfie	file
fitcoefs	character vector
odsfile	file

Value

filepath

Examples

```
file <- system.file('extdata/atkin.metabolon.xlsx', package = 'autonomics')
object <- read_metabolon(file, fit = 'limma')
xlf file <- file.path(tempdir(), 'fukuda20.proteingroups.fdt.xlsx')
odsfile <- file.path(tempdir(), 'fukuda20.proteingroups.fdt.ods')
# write_xl(object, xlf file)
# write_ods(object, odsfile)
```

zero_to_na

*Change nondetect representation***Description**

Change nondetect representation

Usage

```
zero_to_na(x, verbose = FALSE)

nan_to_na(x, verbose = FALSE)

na_to_zero(x, verbose = FALSE)

inf_to_na(x, verbose = FALSE)

minusinf_to_na(x, verbose = FALSE)

na_to_string(x)
```

Arguments

x	matrix
verbose	logical(1)

Value

Updated matrix

Examples

```
matrix(c(0, 7), nrow=1)
matrix(c(0, 7), nrow=1)    %>% zero_to_na(verbose=TRUE)

matrix(c(NA, 7), nrow=1)
matrix(c(NA, 7), nrow=1)    %>% na_to_zero(verbose=TRUE)

matrix(c(NaN, 7), nrow=1)
matrix(c(NaN, 7), nrow=1)  %>% nan_to_na(verbose=TRUE)
```

```
matrix(c(Inf, 7), nrow=1)
matrix(c(Inf, 7), nrow=1) %>% inf_to_na(verbose=TRUE)

matrix(c(-Inf, 7), nrow=1)
matrix(c(-Inf, 7), nrow=1) %>% minusinf_to_na(verbose=TRUE)
```

Index

* **datasets**
AUTONOMICS_DATASETS, 34
COMPOUNDDISCOVERER_PATTERNS, 45
CONTAMINANTSURL, 45
DATADIR, 52
FITSEP, 78
LINMOD_ENGINES, 108
MAXQUANT_PATTERNS, 119
MSIGCOLLECTIONSHUMAN, 129
MSIGDIR, 129
OPENTARGETSDIR, 131
PRECURSOR_QUANTITY, 157
TAXON_TO_ORGNAME, 186
TESTS, 187

* **internal**
reexports, 169
.extract_effectsize_features
 (.extract_p_features), 6
.extract_fdr_features
 (.extract_p_features), 6
.extract_n_features
 (.extract_p_features), 6
.extract_p_features, 6
.extract_sign_features
 (.extract_p_features), 6
.fit_limma(fit), 74
.merge, 9
.plot_survival(fit_survival), 82
.read_compounddiscoverer, 9
.read_dianncprecursors, 10
.read_dianncproteingroups
 (.read_dianncprecursors), 10
.read_maxquant_phosphosites
 (.read_maxquant_proteingroups),
 12
.read_maxquant_proteingroups, 12
.read_metabolon, 13
.read_rectangles, 15
.read_rnaseq_bams, 17

.read_rnaseq_counts
 (.read_rnaseq_bams), 17
.read_somascans, 20
%<>% (reexports), 169
%>% (reexports), 169
%<>%, 169
%>%, 169

ABBREV_TO_ORGNAME (TAXON_TO_ORGNAME),
 186
abstract_fit, 22
abstractvar (modelvar), 124
add_adjusted_pvalues, 23
add_assay_means, 24
add_facetvars, 25
add_opentargets_by_uniprot, 25
add_psp, 26
add_smiles, 27
altenrich, 28
analysis, 29
analysis, SummarizedExperiment-method
 (analysis), 29
analysis<- (analysis), 29
analysis<-, SummarizedExperiment, list-method
 (analysis), 29
analyze, 30
annotate_maxquant, 31
annotate_uniprot_rest, 33
assert_compounddiscoverer_output
 (is_dianncreport), 98
assert_correlation_matrix
 (is_correlation_matrix), 97
assert_dianncreport (is_dianncreport),
 98
assert_fastadt (is_fastadt), 100
assert_fragpipe_tsv (is_dianncreport),
 98
assert_is_fraction (is_fraction), 101
assert_is_valid_sumexp, 33

assert_maxquant_phosphosites
 (is_diann_report), 98
assert_maxquant_proteingroups
 (is_diann_report), 98
assert_positive_number
 (is_positive_number), 102
assert_scalar_subset
 (is_scalar_subset), 103
assert_valid_formula
 (is_valid_formula), 105
assert_weakly_positive_number
 (is_positive_number), 102
AUTONOMICS_DATASETS, 34

bin, 34
biplot, 35
biplot_corrections, 37
biplot_covariates, 38
block2lme, 39
block_vars (block2lme), 39

cbind_imputed (split_samples), 174
center, 40
code, 41
code_control (code), 41
code_deviation (code), 41
code_deviation_first (code), 41
code_diff (code), 41
code_diff_forward (code), 41
code_helmert (code), 41
code_helmert_forward (code), 41
coefs, 43
collapse_in (count_in), 49
collapsed_entrezg_to_symbol, 44
COMPOUNDDISCOVERER_PATTERNS, 45
CONTAMINANTSURL, 45
contr.diff (code), 41
contr.treatment.explicit (code), 41
contrast_subgroup_cols, 46
contrast_subgroup_rows
 (contrast_subgroup_cols), 46
count_in, 49
count_out (count_in), 49
counts, 46
counts, SummarizedExperiment-method
 (counts), 46
counts2cpm, 47
counts2tpm, 48
counts<- (counts), 46

counts<-, SummarizedExperiment, matrix-method
 (counts), 46
counts<-, SummarizedExperiment, NULL-method
 (counts), 46
counts<-, SummarizedExperiment, numeric-method
 (counts), 46
cpm, 50
cpm, SummarizedExperiment-method (cpm),
 50
cpm2counts (counts2cpm), 47
cpm<- (cpm), 50
cpm<-, SummarizedExperiment, matrix-method
 (cpm), 50
cpm<-, SummarizedExperiment, numeric-method
 (cpm), 50
create_design, 51

data.table, 169
data.table (reexports), 169
DATADIR, 52
default_formula (default_subgroupvar),
 55
default_geom, 54
default_sfile, 55
default_subgroupvar, 55
demultiplex, 56
dequantify, 57
dequantify_compounddiscoverer, 58
downfeatures (modelvar), 124
download_contaminants, 58
download_data (DATADIR), 52
download_gtf, 59
download_mcclain21, 60
download_tcga_example, 60
dt2mat, 61

effectdt (modelvar), 124
effectmat (modelvar), 124
effectsizemat (modelvar), 124
effectvar (modelvar), 124
effectvec (modelvar), 124
enrichment, 61
ens2org, 63
entrezg_to_symbol, 64
EXISTENCE_TO_NUMBER (TAXON_TO_ORGNAME),
 186
exp2 (log2transform), 114
explore_transformations, 64
extract, 169

```

extract (reexports), 169
extract_coef_features
  (.extract_p_features), 6
extract_rectangle, 65

factor2logical (logical2factor), 115
fcluster, 67
fcor, 68
fdata, 68
fdata,SummarizedExperiment-method
  (fdata), 68
fdata<- (fdata), 68
fdata<-, SummarizedExperiment,data.frame-method
  (fdata), 68
fdp2p, 70
fdemat (modelvar), 124
fdvar (modelvar), 124
fdvec (modelvar), 124
fdt (fdata), 68
fdt,SummarizedExperiment-method
  (fdata), 68
fdt<- (fdata), 68
fdt<-, SummarizedExperiment,data.table-method
  (fdata), 68
filter_exprs_replicated_in_some_subgroup,
  71
filter_features, 72
filter_medoid, 72
filter_samples, 73
fit, 74
fit_limma (fit), 74
fit_lm (fit_lmx), 79
fit_lme (fit_lmx), 79
fit_lmer (fit_lmx), 79
fit_lmx, 79
fit_survival, 82
fit_wilcoxon (fit), 74
fitcoefs, 77
fitdt (fitvars), 79
fits, 78
FITSEP, 78
fitvars, 79
fix_xlgenes, 83
flevels, 84
fnames, 85
fnames,SummarizedExperiment-method
  (fnames), 85
fnames<- (fnames), 85

fnames<-, SummarizedExperiment,character-method
  (fnames), 85
formula2lm (block2lme), 39
formula2lmer (block2lme), 39
formula2str, 85
fvalues, 86
fvars, 87
fvars,SummarizedExperiment-method
  (fvars), 87
fvars<- (fvars), 87
fvars<-, SummarizedExperiment,character-method
  (fvars), 87
genome_to_orgdb, 87
group_by_level, 88
guess_compounddiscoverer_quantity, 89
guess_fitsep, 90
guess_maxquant_quantity, 90
guess_sep, 91

has_multiple_levels, 92
hdlproteins, 94
impute, 94
inf_to_na (zero_to_na), 193
invert_subgroups, 96
invnorm (log2transform), 114
is_collapsed_subset, 97
is_compounddiscoverer_output
  (is_diann_report), 98
is_correlation_matrix, 97
is_diann_report, 98
is_fastadt, 100
is_file, 100
is_fraction, 101
is_fragpipe_tsv (is_diann_report), 98
is_imputed, 101
is_imputed,SummarizedExperiment-method
  (is_imputed), 101
is_imputed<- (is_imputed), 101
is_imputed<-, SummarizedExperiment,matrix-method
  (is_imputed), 101
is_imputed<-, SummarizedExperiment,NULL-method
  (is_imputed), 101
is_maxquant_phosphosites
  (is_diann_report), 98
is_maxquant_proteingroups
  (is_diann_report), 98
is_positive_number, 102

```

is_scalar_subset, 103
 is_sig, 104
 is_valid_formula, 105
 is_weakly_positive_number
 (is_positive_number), 102

 keep_connected_blocks, 106
 keep_connected_features, 106
 keep_replicated_features, 107

 label2index, 107
 lda(pca), 132
 LINMOD_ENGINES, 108
 list2mat, 108
 list_files, 109
 loadingmat(scoremat), 172
 loadings(scoremat), 172
 log2counts, 109
 log2counts, SummarizedExperiment-method
 (log2counts), 109
 log2counts<- (log2counts), 109
 log2counts<-, SummarizedExperiment, matrix-method
 (log2counts), 109
 log2counts<-, SummarizedExperiment, numeric-method
 (log2counts), 109
 log2cpm, 110
 log2cpm, SummarizedExperiment-method
 (log2cpm), 110
 log2cpm<- (log2cpm), 110
 log2cpm<-, SummarizedExperiment, matrix-method
 (log2cpm), 110
 log2cpm<-, SummarizedExperiment, numeric-method
 (log2cpm), 110
 log2diffs, 111
 log2diffs, SummarizedExperiment-method
 (log2diffs), 111
 log2diffs<- (log2diffs), 111
 log2diffs<-, SummarizedExperiment, matrix-method
 (log2diffs), 111
 log2diffs<-, SummarizedExperiment, numeric-method
 (log2diffs), 111
 log2proteins, 112
 log2proteins, SummarizedExperiment-method
 (log2proteins), 112
 log2proteins<- (log2proteins), 112
 log2proteins<-, SummarizedExperiment, matrix-method
 (log2proteins), 112
 log2proteins<-, SummarizedExperiment, numeric-method
 (log2proteins), 112

log2sites, 112
 log2sites, SummarizedExperiment-method
 (log2sites), 112
 log2sites<- (log2sites), 112
 log2sites<-, SummarizedExperiment, matrix-method
 (log2sites), 112
 log2sites<-, SummarizedExperiment, numeric-method
 (log2sites), 112
 log2tpm, 113
 log2tpm, SummarizedExperiment-method
 (log2tpm), 113
 log2tpm<- (log2tpm), 113
 log2tpm<-, SummarizedExperiment, matrix-method
 (log2tpm), 113
 log2tpm<-, SummarizedExperiment, numeric-method
 (log2tpm), 113
 log2transform, 114
 logical2factor, 115

 make_alpha_palette, 116
 make_colors, 117
 make_volcano_dt, 117
 map_fvalues, 118
 mat2dt(dt2mat), 61
 matrix2sumexp, 119
 MAXQUANT_PATTERNS, 119
 merge_compounddiscoverer, 120
 merge_fdata(merge_sdata), 122
 merge_fdt(merge_sdata), 122
 merge_ffile(merge_sample_file), 121
 merge_sample_excel, 120
 merge_sample_file, 121
 merge_sdata, 122
 merge_sdt(merge_sdata), 122
 message_df, 124
 minusinf_to_na(zero_to_na), 193
 modeldt(modelvar), 124
 modelfeatures(modelvar), 124
 modelmat(modelvar), 124
 modelvar, 124
 modelvec(modelvar), 124
 MSIGCOLLECTIONSHUMAN, 129
 MSIGCOLLECTIONSMOUSE
 (MSIGCOLLECTIONSHUMAN), 129
 MSIGDIR, 129
 na_to_string(zero_to_na), 193
 mathbd_zero(zero_to_na), 193
 nan_to_na(zero_to_na), 193

nfactors, 130
no_nas (systematic_nas), 184

OPENTARGETSDIR, 131
opls (pca), 132
order_on_effect (order_on_p), 131
order_on_p, 131

parse_maxquant_hdrs (read_uniprotdt),
 168
pca, 132
pdt (modelvar), 124
percentiles, 134
pg_to_canonical, 135
pg_to_isoforms (pg_to_canonical), 135
plot_contrast_venn, 136
plot_contrastogram, 135
plot_data, 137
plot_densities, 138, 155
plot_design, 140
plot_detections, 141
plot_exprs, 142, 155
plot_exprs_per_coef, 146
plot_feature_boxplots (plot_exprs), 142
plot_feature_densities
 (plot_densities), 138
plot_feature_violins (plot_violins), 153
plot_fit_summary, 147
plot_heatmap, 148
plot_matrix, 149
plot_sample_boxplots, 140
plot_sample_boxplots (plot_exprs), 142
plot_sample_densities, 145, 147
plot_sample_densities (plot_densities),
 138
plot_sample_nas (plot_detections), 141
plot_sample_violins, 140, 145, 147
plot_sample_violins (plot_violins), 153
plot_subgroup_nas (plot_detections), 141
plot_subgroup_points, 149
plot_subgroup_violins (plot_violins),
 153
plot_summarized_detections
 (plot_detections), 141
plot_summary, 151
plot_survival (fit_survival), 82
plot_venn, 152
plot_venn_heatmap, 152
plot_violins, 153

plot_volcano, 155
plotmat, 136
pls (pca), 132
pmat (modelvar), 124
PPATTERN (FITSEP), 78
PRECURSOR_QUANTITY, 157
preprocess_rnaseq_counts, 157
pull_columns, 158
pvar (modelvar), 124
pvec (modelvar), 124

quantnorm (log2transform), 114

random_nas (systematic_nas), 184
read_affymetrix, 159
read_compounddiscoverer, 159
read_contaminantdt (read_uniprotdt), 168
read_contaminants, 161
read_diann (.read_diann_precursors), 10
read_diann_proteingroups
 (.read_diann_precursors), 10
read_fragpipe, 161
read_maxquant_phosphosites, 162
read_maxquant_proteingroups, 164
read_metabolon (.read_metabolon), 13
read_msigdt, 28, 166
read_olink, 166
read_phosphosites
 (read_maxquant_phosphosites),
 162
read_proteingroups
 (read_maxquant_proteingroups),
 164
read_rectangles (.read_rectangles), 15
read_rnaseq_bams (.read_rnaseq_bams), 17
read_rnaseq_counts (.read_rnaseq_bams),
 17
read_salmon, 167
read_somaskan (.read_somaskan), 20
read_uniprotdt, 168
recollapse (uncollapse), 188
reexports, 169
reset_fit, 169
REVIEWED_TO_NUMBER (TAXON_TO_ORGNAME),
 186
rm_diann_contaminants, 170
rm_missing_in_all_samples, 170
rm_missing_in_some_samples
 (rm_missing_in_all_samples),

170
`rm_singleton_samples`
`(rm_unmatched_samples)`, 171
`rm_unmatched_samples`, 171

`sampleid_values` (`svalues`), 182
`scaledlibsizes`, 172
`scoremat`, 172
`scores` (`scoremat`), 172
`sdata` (`fdata`), 68
`sdata`, `SummarizedExperiment`-method
`(fdata)`, 68
`sdata<-` (`fdata`), 68
`sdata<-`, `SummarizedExperiment`, `data.frame`-method
`(fdata)`, 68
`sdata<-`, `SummarizedExperiment`, `DataFrame`-method
`(fdata)`, 68
`sdt` (`fdata`), 68
`sdt`, `SummarizedExperiment`-method
`(fdata)`, 68
`sdt<-` (`fdata`), 68
`sdt<-`, `SummarizedExperiment`, `data.table`-method
`(fdata)`, 68
`slevels`, 173
`sma` (`pca`), 132
`snames`, 174
`snames`, `SummarizedExperiment`-method
`(snames)`, 174
`snames<-` (`snames`), 174
`snames<-`, `SummarizedExperiment`, `character`-method
`(snames)`, 174
`split_extract` (`nFactors`), 130
`split_extract_fixed` (`nFactors`), 130
`split_extract_regex` (`nFactors`), 130
`split_features` (`split_samples`), 174
`split_samples`, 174
`spls` (`pca`), 132
`stri_any_regex`, 175
`stri_detect_fixed_in_collapsed`, 176
`subgroup_array`, 177
`subgroup_levels` (`slevels`), 173
`subgroup_matrix` (`subgroup_array`), 177
`subgroup_values` (`svalues`), 182
`subtract_baseline`, 177
`subtract_differences`
`(subtract_baseline)`, 177
`subtract_pairs` (`subtract_baseline`), 177
`sumexp_to_longdt` (`sumexp_to_widedt`), 180

`sumexp_to_subrep_dt` (`sumexp_to_widedt`),
180
`sumexp_to_tsv`, 180
`sumexp_to_widedt`, 180
`sumexpList_to_longdt`, 179
`summarize_fit`, 181
`svalues`, 182
`svalues<-` (`svalues`), 182
`svalues<-`, `SummarizedExperiment`, `character`-method
`(svalues)`, 182
`svars`, 183
`svars`, `MultiAssayExperiment`-method
`(svars)`, 183
`svars`, `SummarizedExperiment`-method
`(svars)`, 183
`svars<-` (`svars`), 183
`svars<-`, `MultiAssayExperiment`, `character`-method
`(svars)`, 183
`svars<-`, `SummarizedExperiment`, `character`-method
`(svars)`, 183
`systematic_nas`, 184

`tag_features`, 185
`tag_hdlproteins`, 186
`taxon2org` (`ens2org`), 63
`TAXON_TO_ORGNAME`, 186
`tdt` (`modelvar`), 124
`TESTS`, 187
`tmat` (`modelvar`), 124
`tpm`, 187
`tpm`, `SummarizedExperiment`-method (`tpm`),
187
`tpm<-` (`tpm`), 187
`tpm<-`, `SummarizedExperiment`, `matrix`-method
`(tpm)`, 187
`tpm<-`, `SummarizedExperiment`, `numeric`-method
`(tpm)`, 187
`tvar` (`modelvar`), 124
`tvec` (`modelvar`), 124

`uncollapse`, 188
`upfeatures` (`modelvar`), 124

`values`, 189
`values`, `SummarizedExperiment`-method
`(values)`, 189
`values<-` (`values`), 189
`values<-`, `SummarizedExperiment`, `matrix`-method
`(values)`, 189

values<- ,SummarizedExperiment,numeric-method
 (values), 189
varlevels_dont_clash, 190
venn_detects, 191
vsn (log2transform), 114

weights, 191
weights,SummarizedExperiment-method
 (weights), 191
weights<- (weights), 191
weights<- ,SummarizedExperiment,matrix-method
 (weights), 191
weights<- ,SummarizedExperiment,NULL-method
 (weights), 191
weights<- ,SummarizedExperiment,numeric-method
 (weights), 191
write_ods (write_xl), 192
write_xl, 192

zero_to_na, 193
zscore (log2transform), 114