

Package ‘predictionet’

September 24, 2012

Type Package

Title Inference for predictive networks designed for (but not limited to) genomic data

Version 1.2.2

Date 2011-10-05

Author Benjamin Haibe-Kains, Catharina Olsen, Gianluca Bontempi, John Quackenbush

Maintainer Benjamin Haibe-Kains <bhaibeka@jimmy.harvard.edu>, Catharina Olsen <colsen@ulb.ac.be>

Description This package contains a set of functions related to network inference combining genomic data and prior information extracted from biomedical literature and structured biological databases. The main function is able to generate networks using Bayesian or regression-based inference methods; while the former is limited to < 100 of variables, the latter may infer networks with hundreds of variables. Several statistics at the edge and node levels have been implemented (edge stability, predictive ability of each node, ...) in order to help the user to focus on high quality subnetworks. Ultimately, this package is used in the ‘Predictive Networks’ web application developed by the Dana-Farber Cancer Institute in collaboration with Entagen.

Depends igraph0, catnet

Suggests network, minet, knitr

Imports penalized

License Artistic 2.0

URL <http://compbio.dfci.harvard.edu>, <http://www.ulb.ac.be/di/mlg>

LazyData yes

R topics documented:

predictionet-package	2
adj.descent	3
adj.remove.cycles	4
data.discretize	5
eval.network	6
expO.colon.ras	7

jorissen.colon.ras	8
mcc	9
net.stab	9
net2topo	10
netinf	11
netinf.cv	13
netinf.predict	16
netinf2gml	17
pred.score	18

Index	20
--------------	-----------

predictionet-package *Inference for predictive networks designed for (but not limited to) genomic data*

Description

This package contains a set of functions related to network inference combining genomic data and prior information extracted from biomedical literature and structured biological databases. The main function is able to generate networks using bayesian or regression-based inference methods; while the former is limited to < 100 of variables, the latter may infer network with hundreds of variables. Several statistics at the edge and node levels have been implemented (edge stability, predictive ability of each node, ...) in order to help the user to focus on high quality subnetworks. Ultimately, this package is used in the 'Predictive Networks' web application developed by the Dana-Farber Cancer Institute in collaboration with

Details

Package:	predictionet
Type:	Package
Version:	1.2.2
Date:	2011-10-05
License:	Artistic 2.0
LazyLoad:	yes

Author(s)

Benjamin Haibe-Kains, Catharina Olsen, Gianluca Bontempi, John Quackenbush
 - Computational Biology and Functional Genomics, Dana-Farber Cancer Institute, Boston, MA, USA

<http://compbio.dfci.harvard.edu/>

- Center for Cancer Computational Biology, Dana-Farber Cancer Institute, Boston, MA, USA

<http://cccb.dfci.harvard.edu/index.html>

- Machine Learning Group (MLG), Universite Libre de Bruxelles, Bruxelles, Belgium

<http://www.ulb.ac.be/di/mlg/>

Maintainer: Benjamin Haibe-Kains

<bhaibeka@jimmy.harvard.edu>

<bhaibeka@ulb.ac.be>

Catharina Olsen

<colsen@ulb.ac.be>

adj.descent

Function to identify all children of a parent

Description

This function uses a depth-first search algorithm to identify all the children (and their corresponding depth) of a node.

Usage

```
adj.descent(adjmat, from, depth)
```

Arguments

adjmat	adjacency matrix; parents in rows, children in columns
from	name or index of the parent node
depth	numeric representing the depth of the search for the children; if depth is missing or negative, all children are returned

Details

The algorithm is based on the depth-first search.

Value

two-column matrix containing the names of the children in the first column and their corresponding depth in the descent in the second column

Author(s)

Benjamin Haibe-Kains

Examples

```
## check whether a list of two nodes are children of another node
set.seed(54321)
mytopo <- matrix(sample(0:1, 100, replace=TRUE, prob=c(0.7,0.3)), nrow=10, dimnames=list(LETTERS[1:10], LETTERS[1:10]))
adj.descent(adjmat=mytopo, from="A")
```

adj.remove.cycles	<i>Function to remove cycles that may be present in a directed graph represented by an adjacency matrix</i>
-------------------	---

Description

This function removes cycles that may be present in a directed graph represented by an adjacency matrix,

Usage

```
adj.remove.cycles(adjmat)
```

Arguments

adjmat	adjacency matrix with positive entries represent evidence for the presence of an edge and entries less or equal than zero represent absence of an edge; parents in row, children in columns.
--------	--

Details

This function may be useful when it comes to generate a bayesian network using a topology identified from an source of information where cycles are allowed. When cycles are removed, the function tries to keep the most positive entries.

Value

A list of two items

adjmat.acyclic an adjacency matrix without cycles

adjmat.removed a matrix of booleans representing the edges that have been removed from the original adjacency matrix to make it acyclic

Author(s)

Benjamin Haibe-Kains

Examples

```
set.seed(54321)
xx <- matrix(sample(c(0,1), 100, replace=TRUE), nrow=10, ncol=10)
adj.remove.cycles(adjmat=xx)
```

data.discretize	<i>Function to discretize data based on user specified cutoffs</i>
-----------------	--

Description

This function enable discretization of data based on cutoffs specified by the users

Usage

```
data.discretize(data, cuts)
```

Arguments

data	matrix of continuous or categorical values (gene expressions for example); observations in rows, features in columns.
cuts	list of cutoffs for each variable.

Details

This function is discretizing the continuous value in data using the cutoffs specified in cuts to create categories represented by increasing integers in 1,2,...,n where n is the maximum number of categories in the dataset.

Value

a matrix of categorical values where categories are {1,2,...,n} depending on the list of cutoffs specified in cuts; observations in rows, features in columns.

Author(s)

Benjamin Haibe-Kains

See Also

[discretize](#)

Examples

```
## load gene expression data for colon cancer data, list of genes related to RAS signaling pathway and the
data(exp0.colon.ras)
## discretize the data in 3 categories
categories <- rep(3, ncol(data.ras))
## estimate the cutoffs (tertiles) for each gene
cuts.discr <- lapply(apply(rbind("nbcats"=categories, data.ras), 2, function(x) { y <- x[1]; x <- x[-1]; return(y)
data.ras.bin <- data.discretize(data=data.ras, cuts=cuts.discr)
```

eval.network	<i>Function computing the f1-score, comparing an inferred topology with a given topology</i>
--------------	--

Description

This function computes the f1-score for an inferred topology using a topology provided by the user.

Usage

```
eval.network(net, true.net)
```

Arguments

net	Inferred topology, an edge between to variables X and Y corresponds to $\text{net}[X,Y]=1$.
true.net	topology the user wants to compare the inferred topology with, e.g. the true network using generated datasets. An edge between to variables X and Y corresponds to $\text{net}[X,Y]=1$.

Value

The computed f1-score, defined as $2*TP/(2*TP+FN+FP)$

Author(s)

Benjamin Haibe-Kains, Catharina Olsen

Examples

```
## load gene expression data for colon cancer data, list of genes related to RAS signaling pathway and the
data(exp0.colon.ras)
## number of genes to select for the analysis
genen <- 10
## select only the top genes
goi <- dimnames(annot.ras)[[1]][order(abs(log2(annot.ras[ , "fold.change"])), decreasing=TRUE)[1:genen]]
mydata <- data.ras[ , goi, drop=FALSE]
myannot <- annot.ras[goi, , drop=FALSE]
mypriors <- priors.ras[goi, goi, drop=FALSE]
mydemo <- demo.ras
## regression-based network inference
res <- netinf(data=mydata, categories=3, priors=mypriors, priors.weight=0.5, method="regrnet", seed=54321)

## extract adjacency matrix from inferred network
net2topo(net=res)
## with coefficients
net2topo(net=res, coefficients=TRUE)
```

exp0.colon.ras	<i>Gene expression, annotations, clinical data and priors for the colon cancer tumors collected by the expression project for oncology (expO).</i>
----------------	--

Description

This dataset contains (part of) the gene expression, annotations and clinical data as published by the expO project (<http://www.intgen.org/expo/>). Genes related to KRAS mutations were retrieved from Bild et al, Nature, 2006. Only genes with known gene symbols were selected resulting in a dataset of 292 human colon tumors and 259 RAS-related genes.

Usage

```
data(exp0.colon.ras)
```

Format

[exp0.colon.ras](#) is a dataset containing four matrices:

demo.ras clinical information of the colon cancer patients whose tumors were hybridized.

data.ras matrix containing expression of genes related to RAS.

annot.ras matrix containing annotations of the genes related to RAS.

priors.ras matrix of priors counts for all the genes related to RAS. Each value represents the number of times an interaction was observed for a specific pair of genes (parents in rows, children in columns).

Details

The microarray platform used in the expO project is the Affymetrix HG-U133PLUS2 GeneChip.

Source

<https://expo.intgen.org/geo/>

<http://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE2109>

References

<http://www.intgen.org/expo/>

Bild AH, Yao G, Chang JT, Wang Q, Potti A, Chasse D, Joshi MB, Harpole D, Lancaster JM, Berchuck A, Olson JA Jr, Marks JR, Dressman HK, West M, Nevins JR. (2006) "Oncogenic pathway signatures in human cancers as a guide to targeted therapies", *Nature*, **439**(7074):274-275.

Examples

```
data(exp0.colon.ras)
```

jorissen.colon.ras *Gene expression, annotations, clinical data and priors for the colon cancer tumors collected by Jorissen and colleagues in 2009.*

Description

This dataset contains (part of) the gene expression, annotations and clinical data as published by Jorissen and colleagues in 2009. Genes related to KRAS mutations were retrieved from Bild et al, Nature, 2006. Only genes with known gene symbols were selected resulting in a dataset of 290 human colon tumors and 259 RAS-related genes.

Usage

```
data(jorissen.colon.ras)
```

Format

[jorissen.colon.ras](#) is a dataset containing four matrices:

demo2.ras clinical information of the colon cancer patients whose tumors were hybridized.

data2.ras matrix containing expression of genes related to RAS.

annot2.ras matrix containing annotations of the genes related to RAS.

priors2.ras matrix of priors counts for all the genes related to RAS. Each value represents the number of times an interaction was observed for a specific pair of genes (parents in rows, children in columns).

Details

The microarray platform used in Jorissen's dataset is the Affymetrix HG-U133PLUS2 GeneChip.

Source

<http://www.ncbi.nlm.nih.gov/projects/geo/query/acc.cgi?acc=GSE14333>

References

Jorissen RN, Gibbs P, Christie M, Prakash S, Lipton L, Desai J, Kerr D, Aaltonen LA, Arango D, Kruhoffer M, Orntoft TF, Andersen CL, Gruidl M, Kamath VP, Eschrich S, Yeatman TJ, Sieber OM. (2009) "Metastasis-Associated Gene Expression Changes Predict Poor Outcomes in Patients with Dukes Stage B and C Colorectal Cancer", *Clin Cancer Res* **15**(24):7642-7651.

Bild AH, Yao G, Chang JT, Wang Q, Potti A, Chasse D, Joshi MB, Harpole D, Lancaster JM, Berchuck A, Olson JA Jr, Marks JR, Dressman HK, West M, Nevins JR. (2006) "Oncogenic pathway signatures in human cancers as a guide to targeted therapies", *Nature*, **439**(7074):274-275.

Examples

```
data(jorissen.colon.ras)
```

mcc	<i>Function to compute the Matthews Correlation Coefficient (MCC) in a classification framework</i>
-----	---

Description

This function computes the Matthews Correlation Coefficient (MCC) in a classification framework.

Usage

```
mcc(ct, nbcats = nrow(ct))
```

Arguments

ct	contingency table
nbcats	number of categories

Value

MCC estimate

Author(s)

Benjamin Haibe-Kains

net.stab	<i>Function evaluating the stability of a network inferred from data with a specific method</i>
----------	---

Description

This function evaluates the stability of a network inferred from data with a specific method.

Usage

```
net.stab(data, categories, perturbations, priors, priors.count = TRUE, priors.weight = 0.5, maxp
```

Arguments

data
categories
perturbations
priors
priors.count
priors.weight
maxparents
subset
method

Author(s)

Benjamin Haibe-Kains

net2topo

*Function transforming a network model into an adjacency matrix:
parents in rows, children in columns*

Description

This function transforms a network model into an adjacency matrix: parents in rows, children in columns.

Usage

```
net2topo(net, coefficients=FALSE)
```

Arguments

net
coefficients

Value

Matrix of binary values (0=absence of an edge and 1=presence of an edge) or regression coefficients as estimated in the local regression models (input=parents nodes, output=target/child node)

Author(s)

Benjamin Haibe-Kains, Catharina Olsen

Examples

```
## load gene expression data for colon cancer data, list of genes related to RAS signaling pathway and the
data(exp0.colon.ras)
## number of genes to select for the analysis
genen <- 10
## select only the top genes
goi <- dimnames(annot.ras)[[1]][order(abs(log2(annot.ras[, "fold.change"])), decreasing=TRUE)[1:genen]]
mydata <- data.ras[, goi, drop=FALSE]
myannot <- annot.ras[goi, , drop=FALSE]
mypriors <- priors.ras[goi, goi, drop=FALSE]
mydemo <- demo.ras
## regression-based network inference
res <- netinf(data=mydata, categories=3, priors=mypriors, priors.weight=0.5, method="regrnet", seed=54321)

## extract adjacency matrix from inferred network
net2topo(net=res)
## with coefficients
net2topo(net=res, coefficients=TRUE)
```

netinf	<i>Function performing network inference by combining priors and genomic data</i>
--------	---

Description

Main function of the predictionet package, netinf infers a gene network by combining priors and genomic data. The two main network inference methodologies implemented so far are the bayesian and regression-based inferences.

Usage

```
netinf(data, categories, perturbations, priors, predn, priors.count = TRUE, priors.weight = 0.5,
```

Arguments

data	matrix of continuous or categorical values (gene expressions for example); observations in rows, features in columns.
categories	if this parameter missing, 'data' should be already discretized; otherwise either a single integer or a vector of integers specifying the number of categories used to discretize each variable (data are then discretized using equal-frequency bins) or a list of cutoffs to use to discretize each of the variables in 'data' matrix. If method='bayesnet' and categories is missing, data should contain categorical values and the number of categories will determine from the data.
perturbations	matrix of 0,1 specifying whether a gene has been perturbed (e.g., knockdown, overexpression) in some experiments. Dimensions should be the same than data.
priors	matrix of prior information available for gene-gene interaction (parents in rows, children in columns). Values may be probabilities or any other weights (citations count for instance). if priors counts are used the parameter priors.count should be TRUE so the priors are scaled accordingly.
predn	indices or names of variables to fit during network inference. If missing, all the variables will be used for network inference. Note that for bayesian network inference (method='bayesnet') this parameter is ignored and a network will be generated using all the variables.
priors.count	TRUE if priors specified by the user are number of citations (count) for each interaction, FALSE if probabilities or any other weight in [0,1] are reported instead.
priors.weight	real value in [0,1] specifying the weight to put on the priors (0=only the data are used, 1=only the priors are used to infer the topology of the network).
maxparents	maximum number of parents allowed for each gene.
maxparents.push	if TRUE it forces the method to select the maximum number of parents for each variable in the network, FALSE otherwise. For now, this parameters has little effect when method='regrnet' and causal=TRUE. For method='bayesnet', this parameter has an effect the the maximum number of parents is not always chosen, we will fix that in a future release.
subset	vector of indices to select only subset of the observations.
method	regrnet for regression-based network inference, bayesnet for bayesian network inference with the catnet package.

ensemble	TRUE if the ensemble approach should be used, FALSE otherwise.
regrmodel	type of regression model to fit when regrnet method is selected.
ensemble.model	Could be either full or best depending how the equivalent networks are selected to be included in the ensemble network: for full bootstrapping is used to identify all the statistically equivalent networks, it best only the top ensemble.maxnsol are considered at each step of the feature selection.
ensemble.maxnsol	maximum number of solutions to consider at each step of the feature selection for the method=ensemble.regrnet, default is 3.
causal	'TRUE' if the causality should be inferred from the data, 'FALSE' otherwise
seed	set the seed to make the network inference deterministic.
bayesnet.maxcomplexity	maximum complexity for bayesian network inference, see Details.
bayesnet.maxiter	maximum number of iterations for bayesian network inference, see Details.

Details

bayesnet.maxcomplexity and bayesnet.maxiter are parameters to be passed to the network inference method (see [cnSearchOrder](#) and [cnSearchSA](#) from the catnet package for more details). Relevance score is either MRMR scores if causal=FALSE or causality score if causal=TRUE.

Value

method	name of the method used for network inference.
topology	adjacency matrix representing the topology of the inferred network; parents in rows, children in columns.
topology.coeff	if method='regrnet' topology.coeff contains an adjacency matrix with the coefficients used in the local regression model; parents in rows, children in columns. Additionally the beta_0 values for each model in the first row of the matrix
edge.relevance	relevance score for each edge (see Details).

Author(s)

Benjamin Haibe-Kains, Catharina Olsen

Examples

```
## load gene expression data for colon cancer data, list of genes related to RAS signaling pathway and the
data(exp0.colon.ras)
## create matrix of perturbations (no perturbations in this dataset)
pert <- matrix(0, nrow=nrow(data.ras), ncol=ncol(data.ras), dimnames=dimnames(data.ras))

## number of genes to select for the analysis
genen <- 10
## select only the top genes
goi <- dimnames(annot.ras)[[1]][order(abs(log2(annot.ras[, "fold.change"])), decreasing=TRUE)[1:genen]]
mydata <- data.ras[, goi, drop=FALSE]
myannot <- annot.ras[goi, , drop=FALSE]
```

```

mypriors <- priors.ras[goi, goi, drop=FALSE]
mydemo <- demo.ras
mypert <- pert[ , goi, drop=FALSE]

#####
## regression-based network inference
#####
## infer global network from data and priors
mynet <- netinf(data=mydata, perturbations=mypert, priors=mypriors, priors.count=TRUE, priors.weight=0.5, n

## plot network topology
mytopo <- mynet$topology
library(network)
xnet <- network(x=mytopo, matrix.type="adjacency", directed=TRUE, loops=FALSE, vertex.attrnames=dimnames(my
plot.network(x=xnet, displayisolates=TRUE, displaylabels=TRUE, boxed.labels=FALSE, label.pos=0, arrowhead.

## export network as a 'gml' file that you can import into Cytoscape
rr <- netinf2gml(object=mynet, file=paste(tempdir(),"/predictionet_regrnet",sep=""))

## predictions
mypreds <- netinf.predict(net=mynet, data=mydata, perturbations=mypert)
print(pred.score(data=mydata, pred=mypreds, categories=3, method="mcc"))

#####
## bayesian network inference
#####
## discretize gene expression values in three categories
categories <- rep(3, ncol(mydata))
## estimate the cutoffs (tertiles) for each gene
cuts.discr <- lapply(apply(rbind("nbcats"=categories, mydata), 2, function(x) { y <- x[1]; x <- x[-1]; return
mydata <- data.discretize(data=mydata, cuts=cuts.discr)

## infer a bayesian network network from data and priors
mynet <- netinf(data=mydata, perturbations=mypert, priors=mypriors, priors.count=TRUE, priors.weight=0.5, n

## plot network topology
mytopo <- net2topo(net=mynet)
library(network)
xnet <- network(x=mytopo, matrix.type="adjacency", directed=TRUE, loops=FALSE, vertex.attrnames=dimnames(my
plot.network(x=xnet, displayisolates=TRUE, displaylabels=TRUE, boxed.labels=FALSE, label.pos=0, arrowhead.

## export network as a 'gml' file that you can import into Cytoscape
rr <- netinf2gml(object=mynet, file=paste(tempdir(),"/predictionet_bayesnet",sep=""))

## predictions
mypreds <- netinf.predict(net=mynet, data=mydata, perturbations=mypert)
print(pred.score(data=mydata, pred=mypreds, method="mcc"))

```

netinf.cv

Function performing network inference by combining priors and genomic data

Description

The function `netinf.cv` perform a cross-validation loop and infers a gene network by combining priors and genomic data in each fold. This allows to estimate the predictive ability of the inferred

network as well as edge stability.

Usage

```
netinf.cv(data, categories, perturbations, priors, predn, priors.count = TRUE, priors.weight = 0
```

Arguments

<code>data</code>	matrix of continuous or categorical values (gene expressions for example); observations in rows, features in columns.
<code>categories</code>	if this parameter missing, 'data' should be already discretize; otherwise either a single integer or a vector of integers specifying the number of categories used to discretize each variable (data are then discretized using equal-frequency bins) or a list of cutoffs to use to discretize each of the variables in 'data' matrix. If <code>method='bayesnet'</code> , this parameter should be specified by the user.
<code>perturbations</code>	matrix of 0, 1 specifying whether a gene has been perturbed (e.g., knockdown, overexpression) in some experiments. Dimensions should be the same than data.
<code>priors</code>	matrix of prior information available for gene-gene interaction (parents in rows, children in columns). Values may be probabilities or any other weights (citations count for instance). if priors counts are used the parameter <code>priors.count</code> should be TRUE so the priors are scaled accordingly.
<code>predn</code>	indices or names of variables to fit during network inference. If missing, all the variables will be used for network inference.
<code>priors.count</code>	TRUE if priors specified by the user are number of citations (count) for each interaction, FALSE if probabilities or any other weight in [0,1] are reported instead.
<code>priors.weight</code>	real value in [0,1] specifying the weight to put on the priors (0=only the data are used, 1=only the priors are used to infer the topology of the network).
<code>maxparents</code>	maximum number of parents allowed for each gene.
<code>maxparents.push</code>	if TRUE it forces the method to select the maximum number of parents for each variable in the network, FALSE otherwise. For now, this parameters has little effect when <code>method='regrnet'</code> and <code>causal=TRUE</code> . For <code>method='bayesnet'</code> , this parameter has an effect the the maximum number of parents is not always chosen, we will fix that in a future release.
<code>subset</code>	vector of indices to select only subset of the observations.
<code>method</code>	<code>regrnet</code> for regression-based network inference, <code>bayesnet</code> for bayesian network inference with the <code>catnet</code> package.
<code>ensemble</code>	TRUE if the ensemble approach should be used, FALSE otherwise.
<code>ensemble.maxnsol</code>	Number of equivalent solutions chosen at each step.
<code>regrmodel</code>	type of regression model to fit when <code>regrnet</code> method is selected.
<code>nfold</code>	number of folds for the cross-validation.
<code>causal</code>	'TRUE' if the causality should be inferred from the data, 'FALSE' otherwise
<code>seed</code>	set the seed to make the cross-validation and network inference deterministic.
<code>bayesnet.maxcomplexity</code>	maximum complexity for bayesian network inference, see Details.
<code>bayesnet.maxiter</code>	maximum number of iterations for bayesian network inference, see Details.

Details

bayesnet.maxcomplexity and bayesnet.maxiter are parameters to be passed to the network inference method (see [cnSearchOrder](#) and [cnSearchSA](#) from the catnet package for more details).

Value

method	name of the method used for network inference.
topology	topology of the model inferred using the entire dataset.
topology.coeff	if method='regrnet' topology.coeff contains an adjacency matrix with the coefficients used in the local regression model; parents in rows, children in columns. Additionally the beta_0 values for each model in the first row of the matrix
topology.cv	topology of the networks inferred at each fold of the cross-validation.
topology.coeff.cv	if method='regrnet' topology.coeff contains an adjacency matrix with the coefficients used in the local regression model; parents in rows, children in columns. Additionally the beta_0 values for each model in the first row of the matrix. Inferred at each fold of the cross-validation
prediction.score.cv	list of prediction scores (R2, NRMSE, MCC) computed at each fold of the cross-validation.
edge.stability	stability of the edges inferred during cross-validation; only the stability of the edges present in the network inferred using the entire dataset is reported.
edge.stability.cv	stability of the edges inferred during cross-validation.
edge.relevance	mean relevance score for each across folds in cross-validation.
edge.relevance.cv	relevance score for each across computed during cross-validation.

Author(s)

Benjamin Haibe-Kains, Catharina Olsen

Examples

```
## load gene expression data for colon cancer data, list of genes related to RAS signaling pathway and the
data(exp0.colon.ras)
## create matrix of perturbations (no perturbations in this dataset)
pert <- matrix(0, nrow=nrow(data.ras), ncol=ncol(data.ras), dimnames=dimnames(data.ras))

## number of genes to select for the analysis
genen <- 10
## select only the top genes
goi <- dimnames(annot.ras)[[1]][order(abs(log2(annot.ras[, "fold.change"])), decreasing=TRUE)[1:genen]]
mydata <- data.ras[, goi, drop=FALSE]
myannot <- annot.ras[goi, , drop=FALSE]
mypriors <- priors.ras[goi, goi, drop=FALSE]
mydemo <- demo.ras
mypert <- pert[, goi, drop=FALSE]
```

```
#####
## regression-based network inference
#####
## number of fold for cross-validation
res <- netinf.cv(data=mydata, categories=3, perturbations=mypert, priors=mypriors, priors.weight=0.5, meth

## MCC for predictions in cross-validation
print(res$prediction.score.cv)

## export network as a 'gml' file that you can import into Cytoscape
rr <- netinf2gml(object=res, file=paste(tempdir(),"predictionet_regrnet",sep=""))

#####
## bayesian network inference
#####
## infer a bayesian network network from data and priors
## number of fold for cross-validation
res <- netinf.cv(data=mydata, categories=3, perturbations=mypert, priors=mypriors, priors.count=TRUE, prior

## MCC for predictions in cross-validation
print(res$prediction.score.cv)

## export network as a 'gml' file that you can import into Cytoscape
rr <- netinf2gml(object=res, file=paste(tempdir(),"predictionet_bayesnet",sep=""))
```

netinf.predict	<i>Function to make prediction of a node values given its parents using an inferred network</i>
----------------	---

Description

This function predict the value of a node given its parents using an inferred network

Usage

```
netinf.predict(net, data, categories, perturbations, subset, predn, ensemble=FALSE)
```

Arguments

net	
data	
categories	
perturbations	
subset	
predn	indices or names of variables to fit during network inference. If missing, all the variables will be used for network inference.
ensemble	TRUE if the ensemble approach should be used, FALSE otherwise.

Value

matrix of predicted values

Author(s)

Benjamin Haibe-Kains, Catharina Olsen

Examples

```
## load gene expression data for colon cancer data, list of genes related to RAS signaling pathway and the
data(exp0.colon.ras)
## number of genes to select for the analysis
genen <- 10
## select only the top genes
goi <- dimnames(annot.ras)[[1]][order(abs(log2(annot.ras[, "fold.change"])), decreasing=TRUE)[1:genen]]
mydata <- data.ras[, goi, drop=FALSE]
myannot <- annot.ras[goi, , drop=FALSE]
mypriors <- priors.ras[goi, goi, drop=FALSE]
mydemo <- demo.ras
## infer global network from data and priors
mynet <- netinf(data=mydata, priors=mypriors, priors.count=TRUE, priors.weight=0.5, maxparents=3, method="r")

## predict gene expression of the first gene
mypreds <- netinf.predict(net=mynet, data=mydata, predn=goi[1])[ ,goi[1]]
## root mean squared error (RMSE)
sqrt(mean((mydata[, goi[1]] - mypreds)^2))
```

netinf2gml

Function to create an [igraph](#) object and export a network to a GML readable by Cytoscape

Description

This function creates, from a network inferred from [netinf](#) or [netinf.cv](#), an [igraph](#) object and export this network to a GML readable by Cytoscape.

Usage

```
netinf2gml(object, edge.info, node.info, file = "predictionet")
```

Arguments

object	object returns by netinf or netinf.cv
edge.info	matrix of values representing the statistics for each edge; parents in rows, children in columns. A list of matrices could be provided, names of the list will then be used to describe the statistics in Cytoscape
node.info	vector of values representing the statistics for each node; parents in rows, children in columns. A list of vectors could be provided, names of the list will then be used to describe the statistics in Cytoscape
file	name of the GML file to be saved.

Details

The GML file created by this function has been tested on Cytoscape 2.8.1; a Vizmap property file of the same name is also created and could be imported into Cytoscape ("predictionet_vizmap2") so the information for each node and edge are displayed correctly.

Value

an `igraph` object

Author(s)

Benjamin Haibe-Kains

See Also

`\codeRCytoscape`

Examples

```
## load gene expression data for colon cancer data, list of genes related to RAS signaling pathway and the
data(exp0.colon.ras)
## number of genes to select for the analysis
genen <- 10
## select only the top genes
goi <- dimnames(annot.ras)[[1]][order(abs(log2(annot.ras[, "fold.change"])), decreasing=TRUE)[1:genen]]
mydata <- data.ras[, goi, drop=FALSE]
myannot <- annot.ras[goi, , drop=FALSE]
mypriors <- priors.ras[goi, goi, drop=FALSE]
mydemo <- demo.ras
## infer global network from data and priors
mynet <- netinf.cv(data=mydata, categories=3, priors=mypriors, priors.count=TRUE, priors.weight=0.5, maxpar=10)

## create an igraph object and export it into a GML file
netinf2gml(object=mynet, file = "predictionet")
```

pred.score

Function computing performance of prediction; methods include r2, nrmse and mcc

Description

This function computes prediction performance; methods include r2, nrmse and mcc.

Usage

```
pred.score(data, pred, categories, method = c("r2", "nrmse", "mcc"), ensemble=FALSE)
```

Arguments

data

pred

categories if this parameter missing, 'data' should be already discretize; otherwise either a single integer or a vector of integers specifying the number of categories used to discretize each variable (data are then discretized using equal-frequency bins) or a list of cutoffs to use to discretize each of the variables in 'data' matrix. If method='bayesnet', this parameter should be specified by the user.

method

ensemble TRUE if the ensemble approach should be used, FALSE otherwise.

Value

A vector of performance scores, one for each node

Author(s)

Benjamin Haibe-Kains, Catharina Olsen

See Also

[netinf.predict](#)

Examples

```
set.seed(54321)
xx <- runif(100)
## R2
pred.score(data=xx, pred=xx+rnorm(100)/10, method="r2")
## NRMSE
pred.score(data=xx, pred=xx+rnorm(100)/10, method="nrmse")
## MCC
pred.score(data=xx, pred=xx+rnorm(100)/10, categories=3, method="mcc")
```

Index

- *Topic **classif**
 - mcc, 9
 - netinf.predict, 16
 - pred.score, 18
- *Topic **data**
 - exp0.colon.ras, 7
 - jorissen.colon.ras, 8
- *Topic **graphs**
 - adj.remove.cycles, 4
 - eval.network, 6
 - net.stab, 9
 - net2topo, 10
 - netinf, 11
 - netinf.cv, 13
- *Topic **graph**
 - netinf2gml, 17
- *Topic **package**
 - predictionet-package, 2
- *Topic **regression**
 - netinf.predict, 16
 - pred.score, 18
- *Topic **univar**
 - mcc, 9
 - net.stab, 9
 - pred.score, 18

adj.descent, 3

adj.remove.cycles, 4

annot.ras (exp0.colon.ras), 7

annot2.ras (jorissen.colon.ras), 8

cnSearchOrder, 12, 15

cnSearchSA, 12, 15

data.discretize, 5

data.ras (exp0.colon.ras), 7

data2.ras (jorissen.colon.ras), 8

demo.ras (exp0.colon.ras), 7

demo2.ras (jorissen.colon.ras), 8

discretize, 5

eval.network, 6

exp0.colon.ras, 7, 7

igraph, 17, 18

jorissen.colon.ras, 8, 8

mcc, 9

net.stab, 9

net2topo, 10

netinf, 11, 17

netinf.cv, 13, 17

netinf.predict, 16, 19

netinf2gml, 17

pred.score, 18

predictionet (predictionet-package), 2

predictionet-package, 2

priors.ras (exp0.colon.ras), 7

priors2.ras (jorissen.colon.ras), 8