

# Package ‘Biostrings’

April 5, 2014

**Title** String objects representing biological sequences, and matching algorithms

**Description** Memory efficient string containers, string matching algorithms, and other utilities, for fast manipulation of large biological sequences or sets of sequences.

**Version** 2.30.1

**Author** H. Pages, P. Aboyoun, R. Gentleman, and S. DebRoy

**Maintainer** H. Pages <hpages@fhcrc.org>

**biocViews** SequenceMatching, Genetics, Sequencing, Infrastructure,DataImport, DataRepresentation

**Depends** R (>= 2.8.0), methods, BiocGenerics (>= 0.5.4), IRanges (>= 1.19.34), XVector (>= 0.1.3)

**Imports** graphics, methods, stats, utils, BiocGenerics, IRanges,XVector

**LinkingTo** IRanges, XVector

**Enhances** Rmpi

**Suggests** BSgenome (>= 1.13.14), BSgenome.Celegans.UCSC.ce2 (>= 1.3.11), BSgenome.Dmelanogaster.UCSC.dm3 (>= 1.3.11),BSgenome.Hsapiens.UCSC.hg18, drosophila2probe, hgu95av2, nomicFeatures (>= 1.3.14), hgu95av2cdf, affy,affydata (>= 1.11.5), RUnit

**License** Artistic-2.0

**LazyLoad** yes

**Collate** 00datacache.R utils.R IUPAC\_CODE\_MAP.R AMINO\_ACID\_CODE.R GENETIC\_CODE.R XStringCodec-class.R seqtype.R XString-class.R XStringSet-class.R XStringSet-comparison.R XStringViews-class.R MaskedXString-class.R XStringSetList-class.R xscat.R XStringSet-io.R letter.R getSeq.R dinucleotideFrequencyTest.R chartr.R reverseComplement.R translate.R toComplex.R replaceAt.R replaceLetterAt.R injectHardMask.R padAndClip.R misc.R SparseList-class.R MIndex-class.R lowlevel-matching.R match-utils.R matchPattern.R maskMotif.R matchPattern.BOC.R matchPattern.BOC2.R matchLRPatterns.R trimLRPatterns.R

matchProbePair.R matchPWM.R findPalindromes.R PDict-class.R  
 matchPDict.R XStringPartialMatches-class.R  
 XStringQuality-class.R QualityScaledXStringSet.R  
 letterFrequency.R InDel-class.R AlignedXStringSet-class.R PairwiseAlignments-class.R  
 PairwiseAlignmentsSingleSubject-class.R PairwiseAlignments-io.R  
 align-utils.R pmatchPattern.R pairwiseAlignment.R stringDist.R  
 needwunsQS.R MultipleAlignment.R matchprobes.R debug.R test.R zzz.R

## R topics documented:

AAString-class	3
align-utils	4
AlignedXStringSet-class	6
AMINO_ACID_CODE	8
BOC_SubjectString-class	9
chartr	9
detail	10
dinucleotideFrequencyTest	11
DNAStrng-class	13
findPalindromes	14
GENETIC_CODE	16
getSeq	17
gregexpr2	18
HNF4alpha	19
InDel-class	19
injectHardMask	20
IUPAC_CODE_MAP	22
letter	23
letterFrequency	24
longestConsecutive	29
lowlevel-matching	30
MaskedXString-class	35
maskMotif	38
match-utils	40
matchLRPatterns	42
matchPattern	43
matchPDict	48
matchPDict-inexact	56
matchProbePair	59
matchprobes	61
matchPWM	62
MIndex-class	65
misc	66
MultipleAlignment-class	67
needwunsQS	72
nucleotideFrequency	73
padAndClip	78
pairwiseAlignment	80

PairwiseAlignments-class . . . . .	83
PairwiseAlignments-io . . . . .	87
PDict-class . . . . .	89
phiX174Phage . . . . .	93
pid . . . . .	94
pmatchPattern . . . . .	96
QualityScaledXStringSet-class . . . . .	96
replaceAt . . . . .	98
replaceLetterAt . . . . .	102
reverseComplement . . . . .	104
RNAString-class . . . . .	106
stringDist . . . . .	107
substitution.matrices . . . . .	109
toComplex . . . . .	112
translate . . . . .	113
trimLRPatterns . . . . .	115
xscat . . . . .	117
XString-class . . . . .	118
XStringPartialMatches-class . . . . .	121
XStringQuality-class . . . . .	122
XStringSet-class . . . . .	123
XStringSet-comparison . . . . .	129
XStringSet-io . . . . .	132
XStringSetList-class . . . . .	135
XStringViews-class . . . . .	137
yeastSEQCHR1 . . . . .	139

**Index****141**


---

AAString-class	<i>AAString objects</i>
----------------	-------------------------

---

**Description**

An AAString object allows efficient storage and manipulation of a long amino acid sequence.

**Details**

The AAString class is a direct [XString](#) subclass (with no additional slot). Therefore all functions and methods described in the [XString](#) man page also work with an AAString object (inheritance).

Unlike the [BString](#) container that allows storage of any single string (based on a single-byte character set) the AAString container can only store a string based on the Amino Acid alphabet (see below).

### The Amino Acid alphabet

This alphabet contains all letters from the Single-Letter Amino Acid Code (see [?AMINO\\_ACID\\_CODE](#)) + the stop ("\*"), the gap ("-") and the hard masking ("+") letters. It is stored in the AA\_ALPHABET constant (character vector). The alphabet method also returns AA\_ALPHABET when applied to an AAString object and is provided for convenience only.

### Constructor-like functions and generics

In the code snippet below, x can be a single string (character vector of length 1) or a [BString](#) object.

```
AAString(x="", start=1, nchar=NA): Tries to convert x into an AAString object by reading nchar letters starting at position start in x.
```

### Accessor methods

In the code snippet below, x is an [AAString](#) object.

```
alphabet(x): If x is an AAString object, then return the Amino Acid alphabet (see above). See the corresponding man pages when x is a BString, DNAStrng or RNAStrng object.
```

### Author(s)

H. Pages

### See Also

[AMINO\\_ACID\\_CODE](#), [letter](#), [XString-class](#), [alphabetFrequency](#)

### Examples

```
AA_ALPHABET
a <- AAString("MARKSLEMSIR*")
length(a)
alphabet(a)
```

---

align-utils

*Utility functions related to sequence alignment*

---

### Description

A variety of different functions used to deal with sequence alignments.

**Usage**

```

nedit(x) # also nmatch and nmismatch

mismatchTable(x, shiftLeft=0L, shiftRight=0L, ...)
mismatchSummary(x, ...)
## S4 method for signature AlignedXStringSet0
coverage(x, shift=0L, width=NULL, weight=1L)
## S4 method for signature PairwiseAlignmentsSingleSubject
coverage(x, shift=0L, width=NULL, weight=1L)
compareStrings(pattern, subject)

## S4 method for signature PairwiseAlignmentsSingleSubject
consensusMatrix(x,
                 as.prob=FALSE, shift=0L, width=NULL,
                 baseOnly=FALSE, gapCode="-", endgapCode="-")

```

**Arguments**

x	A character vector or matrix, XStringSet, XStringViews, PairwiseAlignments, or list of FASTA records containing the equal-length strings.
shiftLeft, shiftRight	Non-positive and non-negative integers respectively that specify how many preceding and succeeding characters to and from the mismatch position to include in the mismatch substrings.
...	Further arguments to be passed to or from other methods.
shift, width	See ?coverage.
weight	An integer vector specifying how much each element in x counts.
pattern, subject	The strings to compare. Can be of type character, XString, XStringSet, AlignedXStringSet, or, in the case of pattern, PairwiseAlignments. If pattern is a PairwiseAlignments object, then subject must be missing.
as.prob	If TRUE then probabilities are reported, otherwise counts (the default).
baseOnly	TRUE or FALSE. If TRUE, the returned vector only contains frequencies for the letters in the "base" alphabet i.e. "A", "C", "G", "T" if x is a "DNA input", and "A", "C", "G", "U" if x is "RNA input". When x is a BString object (or an XStringViews object with a BString subject, or a BStringSet object), then the baseOnly argument is ignored.
gapCode, endgapCode	The codes in the appropriate alphabet to use for the internal and end gaps.

**Details**

mismatchTable: a data.frame containing the positions and substrings of the mismatches for the AlignedXStringSet or PairwiseAlignments object.

mismatchSummary: a list of data.frame objects containing counts and frequencies of the mismatches for the AlignedXStringSet or PairwiseAlignmentsSingleSubject object.

compareStrings combines two equal-length strings that are assumed to be aligned into a single character string containing that replaces mismatches with "?", insertions with "+", and deletions with "-".

### See Also

[pairwiseAlignment](#), [consensusMatrix](#), [XString-class](#), [XStringSet-class](#), [XStringViews-class](#), [AlignedXStringSet-class](#), [PairwiseAlignments-class](#), [match-utils](#)

### Examples

```
## Compare two globally aligned strings
string1 <- "ACTTCACCAGCTCCCTGGCGGTAAGTTGATC---AAAGG---AAACGCAAAGTTTTCAAG"
string2 <- "GTTTCACTACTTCCTTCGGGTAAGTAAATATATAAATATATAAAAAATATAATTTTCATC"
compareStrings(string1, string2)

## Create a consensus matrix
nw1 <-
  pairwiseAlignment(AAStringSet(c("HLDNLKGTG", "HVDDMPNAL")), AAString("SMDDTEKMSMKL"),
    substitutionMatrix = "BLOSUM50", gapOpening = -3, gapExtension = -1)
consensusMatrix(nw1)

## Examine the consensus between the bacteriophage phi X174 genomes
data(phiX174Phage)
phageConsmat <- consensusMatrix(phiX174Phage, baseOnly = TRUE)
phageDiffs <- which(apply(phageConsmat, 2, max) < length(phiX174Phage))
phageDiffs
phageConsmat[,phageDiffs]
```

---

AlignedXStringSet-class

*AlignedXStringSet and QualityAlignedXStringSet objects*

---

### Description

The AlignedXStringSet and QualityAlignedXStringSet classes are containers for storing an aligned XStringSet.

### Details

Before we define the notion of alignment, we introduce the notion of "filled-with-gaps subsequence". A "filled-with-gaps subsequence" of a string string1 is obtained by inserting 0 or any number of gaps in a subsequence of s1. For example L-A-ND and A-N-D are "filled-with-gaps subsequences" of LAND. An alignment between two strings string1 and string2 results in two strings (align1 and align2) that have the same length and are "filled-with-gaps subsequences" of string1 and string2.

For example, this is an alignment between LAND and LEAVES:

```
L-A
LEA
```

An alignment can be seen as a compact representation of one set of basic operations that transforms string1 into align1. There are 3 different kinds of basic operations: "insertions" (gaps in align1), "deletions" (gaps in align2), "replacements". The above alignment represents the following basic operations:

```
insert E at pos 2
insert V at pos 4
insert E at pos 5
replace by S at pos 6 (N is replaced by S)
delete at pos 7 (D is deleted)
```

Note that "insert X at pos i" means that all letters at a position  $\geq i$  are moved 1 place to the right before X is actually inserted.

There are many possible alignments between two given strings string1 and string2 and a common problem is to find the one (or those ones) with the highest score, i.e. with the lower total cost in terms of basic operations.

### Accessor methods

In the code snippets below, x is a AlignedXStringSet or QualityAlignedXStringSet object.

unaligned(x): The original string.

aligned(x, degap = FALSE): If degap = FALSE, the "filled-with-gaps subsequence" representing the aligned substring. If degap = TRUE, the "gap-less subsequence" representing the aligned substring.

start(x): The start of the aligned substring.

end(x): The end of the aligned substring.

width(x): The width of the aligned substring, ignoring gaps.

indel(x): The positions, in the form of an IRanges object, of the insertions or deletions (depending on what x represents).

nindel(x): A two-column matrix containing the length and sum of the widths for each of the elements returned by indel.

length(x): The length of the aligned(x).

nchar(x): The nchar of the aligned(x).

alphabet(x): Equivalent to alphabet(unaligned(x)).

as.character(x): Converts aligned(x) to a character vector.

toString(x): Equivalent to toString(as.character(x)).

**Subsetting methods**

`x[i]`: Returns a new `AlignedXStringSet` or `QualityAlignedXStringSet` object made of the selected elements.

`rep(x, times)`: Returns a new `AlignedXStringSet` or `QualityAlignedXStringSet` object made of the repeated elements.

**Author(s)**

P. Aboyoun and H. Pages

**See Also**

[pairwiseAlignment](#), [PairwiseAlignments-class](#), [XStringSet-class](#)

**Examples**

```
pattern <- AAStrng("LAND")
subject <- AAStrng("LEAVES")
nw1 <- pairwiseAlignment(pattern, subject, substitutionMatrix = "BLOSUM50", gapOpening = -3, gapExtension = -1)
alignedPattern <- pattern(nw1)
unaligned(alignedPattern)
aligned(alignedPattern)
as.character(alignedPattern)
nchar(alignedPattern)
```

---

AMINO\_ACID\_CODE

*The Single-Letter Amino Acid Code*

---

**Description**

Named character vector mapping single-letter amino acid representations to 3-letter amino acid representations.

**See Also**

[AAStrng](#), [GENETIC\\_CODE](#)

**Examples**

```
## See all the 3-letter codes
AMINO_ACID_CODE

## Convert an AAStrng object to a vector of 3-letter amino acid codes
aa <- AAStrng("LANDEECQW")
AMINO_ACID_CODE[strsplit(as.character(aa), NULL)[[1]]]
```



---

 BOC\_SubjectString-class

*BOC\_SubjectString and BOC2\_SubjectString objects*


---

**Description**

The BOC\_SubjectString and BOC2\_SubjectString classes are experimental and might not work properly.

Please DO NOT TRY TO USE them for now. Thanks for your comprehension!

**Author(s)**

H. Pages

---

 chartr

*Translating letters of a sequence*


---

**Description**

Translate letters of a sequence.

**Usage**

```
## S4 method for signature ANY,ANY,XString
chartr(old, new, x)
```

**Arguments**

old	A character string specifying the characters to be translated.
new	A character string specifying the translations.
x	The sequence or set of sequences to translate. If x is an <a href="#">XString</a> , <a href="#">XStringSet</a> , <a href="#">XStringViews</a> or <a href="#">MaskedXString</a> object, then the appropriate chartr method is called, otherwise the standard <a href="#">chartr</a> R function is called.

**Details**

See [?chartr](#) for the details.

Note that, unlike the standard [chartr](#) R function, the methods for [XString](#), [XStringSet](#), [XStringViews](#) and [MaskedXString](#) objects do NOT support character ranges in the specifications.

**Value**

An object of the same class and length as the original object.

**See Also**

[chartr](#), [replaceLetterAt](#), [XString-class](#), [XStringSet-class](#), [XStringViews-class](#), [MaskedXString-class](#), [alphabetFrequency](#), [matchPattern](#), [reverseComplement](#)

**Examples**

```
x <- BString("MiXeD cAsE 123")
chartr("iXs", "why", x)

## -----
## TRANSFORMING DNA WITH BISULFITE (AND SEARCHING IT...)
## -----

library(BSgenome.Celegans.UCSC.ce2)
chrII <- Celegans[["chrII"]]
alphabetFrequency(chrII)
pattern <- DNASTring("TGGGTGATTTA")

## Transforming and searching the + strand
plus_strand <- chartr("C", "T", chrII)
alphabetFrequency(plus_strand)
matchPattern(pattern, plus_strand)
matchPattern(pattern, chrII)

## Transforming and searching the - strand
minus_strand <- chartr("G", "A", chrII)
alphabetFrequency(minus_strand)
matchPattern(reverseComplement(pattern), minus_strand)
matchPattern(reverseComplement(pattern), chrII)
```

---

detail

*Show (display) detailed object content*

---

**Description**

This is a variant of [show](#), offering a more detailed display of object content.

**Usage**

```
detail(x, ...)
```

**Arguments**

**x** An object. The default simply invokes [show](#).

**...** Additional arguments. The default definition makes no use of these arguments.

**Value**

None; the function is invoked for its side effect (detailed display of object content).

**Author(s)**

Martin Morgan

**Examples**

```
origMAlign <-  
  readDNAMultipleAlignment(filepath =  
    system.file("extdata",  
                "msx2_mRNA.aln",  
                package="Biostrings"),  
    format="clustal")  
  
detail(origMAlign)
```

---

dinucleotideFrequencyTest

*Pearson's chi-squared Test and G-tests for String Position Dependence*

---

**Description**

Performs Person's chi-squared test, G-test, or William's corrected G-test to determine dependence between two nucleotide positions.

**Usage**

```
dinucleotideFrequencyTest(x, i, j, test = c("chisq", "G", "adjG"),  
  simulate.p.value = FALSE, B = 2000)
```

**Arguments**

x	A <a href="#">DNAMultipleAlignment</a> or <a href="#">RNAMultipleAlignment</a> object.
i, j	Single integer values for positions to test for dependence.
test	One of "chisq" (Person's chi-squared test), "G" (G-test), or "adjG" (William's corrected G-test). See Details section.
simulate.p.value	a logical indicating whether to compute p-values by Monte Carlo simulation.
B	an integer specifying the number of replicates used in the Monte Carlo test.

**Details**

The null and alternative hypotheses for this function are:

**H0:** positions i and j are independent

**H1:** otherwise

Let O and E be the observed and expected probabilities for base pair combinations at positions i and j respectively. Then the test statistics are calculated as:

test="chisq": stat =  $\sum(\text{abs}(O - E)^2/E)$

test="G": stat =  $2 * \sum(O * \log(O/E))$

test="adjG": stat =  $2 * \sum(O * \log(O/E))/q$ , where  $q = 1 + ((df - 1)^2 - 1)/(6 * \text{length}(x) * (df - 2))$

Under the null hypothesis, these test statistics are approximately distributed chi-squared( $df = ((\text{distinct bases at } i) - 1) * ((\text{distinct bases at } j) - 1)$ ).

**Value**

An htest object. See help(chisq.test) for more details.

**Author(s)**

P. Aboyoun

**References**

Ellrott, K., Yang, C., Sladek, F.M., Jiang, T. (2002) "Identifying transcription factor binding sites through Markov chain optimizations", *Bioinformatics*, 18 (Suppl. 2), S100-S109.

Sokal, R.R., Rohlf, F.J. (2003) "Biometry: The Principle and Practice of Statistics in Biological Research", W.H. Freeman and Company, New York.

Tomovic, A., Oakeley, E. (2007) "Position dependencies in transcription factor binding sites", *Bioinformatics*, 23, 933-941.

Williams, D.A. (1976) "Improved Likelihood ratio tests for complete contingency tables", *Biometrika*, 63, 33-37.

**See Also**

[nucleotideFrequencyAt](#), [XStringSet-class](#), [chisq.test](#)

**Examples**

```
data(HNF4alpha)
dinucleotideFrequencyTest(HNF4alpha, 1, 2)
dinucleotideFrequencyTest(HNF4alpha, 1, 2, test = "G")
dinucleotideFrequencyTest(HNF4alpha, 1, 2, test = "adjG")
```

---

DNAStrng-class	<i>DNAStrng objects</i>
----------------	-------------------------

---

### Description

A DNAStrng object allows efficient storage and manipulation of a long DNA sequence.

### Details

The DNAStrng class is a direct [XString](#) subclass (with no additional slot). Therefore all functions and methods described in the [XString](#) man page also work with a DNAStrng object (inheritance).

Unlike the [BString](#) container that allows storage of any single string (based on a single-byte character set) the DNAStrng container can only store a string based on the DNA alphabet (see below). In addition, the letters stored in a DNAStrng object are encoded in a way that optimizes fast search algorithms.

### The DNA alphabet

This alphabet contains all letters from the IUPAC Extended Genetic Alphabet (see [?IUPAC\\_CODE\\_MAP](#)) + the gap ("-") and the hard masking ("+") letters. It is stored in the DNA\_ALPHABET constant (character vector). The alphabet method also returns DNA\_ALPHABET when applied to a DNAStrng object and is provided for convenience only.

### Constructor-like functions and generics

In the code snippet below, x can be a single string (character vector of length 1), a [BString](#) object or an [RNAStrng](#) object.

```
DNAStrng(x="", start=1, nchar=NA): Tries to convert x into a DNAStrng object by reading nchar letters starting at position start in x.
```

### Accessor methods

In the code snippet below, x is a DNAStrng object.

```
alphabet(x, baseOnly=FALSE): If x is a DNAStrng object, then return the DNA alphabet (see above). See the corresponding man pages when x is a BString, RNAStrng or AAStrng object.
```

### Author(s)

H. Pages

### See Also

[IUPAC\\_CODE\\_MAP](#), [letter](#), [XString-class](#), [RNAStrng-class](#), [reverseComplement](#), [alphabetFrequency](#)

**Examples**

```
DNA_BASES
DNA_ALPHABET
d <- DNASTring("TTGAAAA-CTC-N")
length(d)
alphabet(d) # DNA_ALPHABET
alphabet(d, baseOnly=TRUE) # DNA_BASES
```

---

findPalindromes	<i>Searching a sequence for palindromes or complemented palindromes</i>
-----------------	---

---

**Description**

The findPalindromes and findComplementedPalindromes functions can be used to find palindromic or complemented palindromic regions in a sequence.

palindromeArmLength, palindromeLeftArm, palindromeRightArm, complementedPalindromeArmLength, complementedPalindromeLeftArm and complementedPalindromeRightArm are utility functions for operating on palindromic or complemented palindromic sequences.

**Usage**

```
findPalindromes(subject, min.armlength=4, max.looplevelength=1, min.looplevelength=0, max.mismatch=0)
palindromeArmLength(x, max.mismatch=0, ...)
palindromeLeftArm(x, max.mismatch=0, ...)
palindromeRightArm(x, max.mismatch=0, ...)
```

```
findComplementedPalindromes(subject, min.armlength=4, max.looplevelength=1, min.looplevelength=0, max.mismatch=0)
complementedPalindromeArmLength(x, max.mismatch=0, ...)
complementedPalindromeLeftArm(x, max.mismatch=0, ...)
complementedPalindromeRightArm(x, max.mismatch=0, ...)
```

**Arguments**

subject	An <a href="#">XString</a> object containing the subject string, or an <a href="#">XStringViews</a> object.
min.armlength	An integer giving the minimum length of the arms of the palindromes (or complemented palindromes) to search for.
max.looplevelength	An integer giving the maximum length of "the loop" (i.e the sequence separating the 2 arms) of the palindromes (or complemented palindromes) to search for. Note that by default (max.looplevelength=1), findPalindromes will search for strict palindromes (or complemented palindromes) only.
min.looplevelength	An integer giving the minimum length of "the loop" of the palindromes (or complemented palindromes) to search for.
max.mismatch	The maximum number of mismatching letters allowed between the 2 arms of the palindromes (or complemented palindromes) to search for.

- x An [XString](#) object containing a 2-arm palindrome or complemented palindrome, or an [XStringViews](#) object containing a set of 2-arm palindromes or complemented palindromes.
- ... Additional arguments to be passed to or from methods.

### Details

The `findPalindromes` function finds palindromic substrings in a subject string. The palindromes that can be searched for are either strict palindromes or 2-arm palindromes (the former being a particular case of the latter) i.e. palindromes where the 2 arms are separated by an arbitrary sequence called "the loop".

Use the `findComplementedPalindromes` function to find complemented palindromic substrings in a [DNString](#) subject (in a complemented palindrome the 2 arms are reverse-complementary sequences).

### Value

`findPalindromes` and `findComplementedPalindromes` return an [XStringViews](#) object containing all palindromes (or complemented palindromes) found in subject (one view per palindromic substring found).

`palindromeArmLength` and `complementedPalindromeArmLength` return the arm length (integer) of the 2-arm palindrome (or complemented palindrome) `x`. It will raise an error if `x` has no arms. Note that any sequence could be considered a 2-arm palindrome if we were OK with arms of length 0 but we are not: `x` must have arms of length greater or equal to 1 in order to be considered a 2-arm palindrome. The same apply to 2-arm complemented palindromes. When applied to an [XStringViews](#) object `x`, `palindromeArmLength` and `complementedPalindromeArmLength` behave in a vectorized fashion by returning an integer vector of the same length as `x`.

`palindromeLeftArm` and `complementedPalindromeLeftArm` return an object of the same class as the original object `x` and containing the left arm of `x`.

`palindromeRightArm` does the same as `palindromeLeftArm` but on the right arm of `x`.

Like `palindromeArmLength`, both `palindromeLeftArm` and `palindromeRightArm` will raise an error if `x` has no arms. Also, when applied to an [XStringViews](#) object `x`, both behave in a vectorized fashion by returning an [XStringViews](#) object of the same length as `x`.

### Author(s)

H. Pages

### See Also

[maskMotif](#), [matchPattern](#), [matchLRPatterns](#), [matchProbePair](#), [XStringViews-class](#), [DNString-class](#)

### Examples

```
## Note that complemented palindromes (like palindromes) can be nested
findComplementedPalindromes(DNString("ACGTTNAACGT-ACGTTNAACGT"))
```

```
## A real use case
library(BSgenome.Dmelanogaster.UCSC.dm3)
chrX <- Dmelanogaster$chrX
chrX_pals <- findComplementedPalindromes(chrX, min.armlength=50, max.looplevelength=20)
complementedPalindromeArmLength(chrX_pals) # 251

## Of course, whitespaces matter
palindromeArmLength(BString("was it a car or a cat I saw"))

## Note that the 2 arms of a strict palindrome (or strict complemented
## palindrome) are equal to the full sequence.
palindromeLeftArm(BString("Delia saw I was aileD"))
complementedPalindromeLeftArm(DNAString("N-ACGTT-AACGT-N"))
palindromeLeftArm(DNAString("N-AAA-N-N-TTT-N"))
```

---

GENETIC\_CODE

*The Standard Genetic Code*


---

## Description

Two predefined objects (GENETIC\_CODE and RNA\_GENETIC\_CODE) that represent The Standard Genetic Code.

## Usage

```
GENETIC_CODE
RNA_GENETIC_CODE
```

## Details

Formally, a genetic code is a mapping between tri-nucleotide sequences called codons, and amino acids.

The Standard Genetic Code (aka The Canonical Genetic Code, or simply The Genetic Code) is the particular mapping that encodes the vast majority of genes in nature.

GENETIC\_CODE and RNA\_GENETIC\_CODE are predefined named character vectors that represent this mapping.

## Value

GENETIC\_CODE and RNA\_GENETIC\_CODE are both named character vectors of length 64 (the number of all possible tri-nucleotide sequences) where each element is a single letter representing either an amino acid or the stop codon "\*" (aka termination codon).

The names of the GENETIC\_CODE vector are the DNA codons i.e. the tri-nucleotide sequences (directed 5' to 3') that are assumed to belong to the "coding DNA strand" (aka "sense DNA strand" or "non-template DNA strand") of the gene.

The names of the RNA\_GENETIC\_CODE are the RNA codons i.e. the tri-nucleotide sequences (directed 5' to 3') that are assumed to belong to the mRNA of the gene.



Note that the values in the GENETIC\_CODE and RNA\_GENETIC\_CODE vectors are the same, only their names are different. The names of the latter are those of the former where all occurrences of T (thymine) have been replaced by U (uracil).

**Author(s)**

H. Pages

**References**

<http://www.ncbi.nlm.nih.gov/Taxonomy/Utils/wprintgc.cgi>

**See Also**

[AA\\_ALPHABET](#), [AMINO\\_ACID\\_CODE](#), [translate](#), [trinucleotideFrequency](#), [DNAString](#), [RNAString](#), [AAString](#)

**Examples**

```
GENETIC_CODE
GENETIC_CODE[["ATG"]] # codon ATG is translated into M (Methionine)
sort(table(GENETIC_CODE)) # the same amino acid can be encoded by 1
                        # to 6 different codons

RNA_GENETIC_CODE
all(GENETIC_CODE == RNA_GENETIC_CODE) # TRUE
```

---

getSeq

*getSeq*

---

**Description**

A generic function for extracting a set of sequences (or subsequences) from a sequence container like a [BSgenome](#) object or other.

**Usage**

```
getSeq(x, ...)
```

**Arguments**

*x* A [BSgenome](#) object or any other supported object. Do `showMethods("getSeq")` to get the list of all supported types for *x*.

*...* Any additional arguments needed by the specialized methods.

**Value**

An [XString](#) object or an [XStringSet](#) object or a character vector containing the extracted sequence(s). See man pages of individual methods for the details e.g. with [?getSeq,BSgenome-method](#) to access the man page of the method for [BSgenome](#) objects (make sure the [BSgenome](#) package is loaded first).

**See Also**

[getSeq,BSgenome-method](#), [XString-class](#), [XStringSet-class](#)

**Examples**

```
## Note that you need to load the package(s) defining the specialized
## methods to have showMethods() display them and to be able to access
## their man pages:
library(BSgenome)
showMethods("getSeq")
```

---

gregexpr2

*A replacement for R standard gregexpr function*

---

**Description**

This is a replacement for the standard `gregexpr` function that does exact matching only. Standard `gregexpr()` misses matches when they are overlapping. The `gregexpr2` function finds all matches but it only works in "fixed" mode i.e. for exact matching (regular expressions are not supported).

**Usage**

```
gregexpr2(pattern, text)
```

**Arguments**

pattern	character string to be matched in the given character vector
text	a character vector where matches are sought

**Value**

A list of the same length as `text` each element of which is an integer vector as in `gregexpr`, except that the starting positions of all (even overlapping) matches are given. Note that, unlike `gregexpr`, `gregexpr2` doesn't attach a "match.length" attribute to each element of the returned list because, since it only works in "fixed" mode, then all the matches have the length of the pattern. Another difference with `gregexpr` is that with `gregexpr2`, the `pattern` argument must be a single (non-NA, non-empty) string.

**Author(s)**

H. Pages

**See Also**

[gregexpr](#), [matchPattern](#)

**Examples**

```
gregexpr("aa", c("XaaaYaa", "a"), fixed=TRUE)
gregexpr2("aa", c("XaaaYaa", "a"))
```

---

HNF4alpha

*Known HNF4alpha binding sequences*

---

**Description**

Seventy one known HNF4alpha binding sequences

**Details**

A DNAStrngSet containing 71 known binding sequences for HNF4alpha.

**Author(s)**

P. Aboyoun

**References**

Ellrott, K., Yang, C., Sladek, F.M., Jiang, T. (2002) "Identifying transcription factor binding sites through Markov chain optimizations", *Bioinformatics*, 18 (Suppl. 2), S100-S109.

**Examples**

```
data(HNF4alpha)
HNF4alpha
```

---

InDel-class

*InDel objects*

---

**Description**

The InDel class is a container for storing insertion and deletion information.

**Details**

This is a generic class that stores any insertion and deletion information.

**Accessor methods**

In the code snippets below, `x` is a `InDel` object.

`insertion(x)`: The insertion information.

`deletion(x)`: The deletion information.

**Author(s)**

P. Aboyoun

**See Also**

[pairwiseAlignment](#), [PairwiseAlignments-class](#)

---

injectHardMask

*Injecting a hard mask in a sequence*

---

**Description**

`injectHardMask` allows the user to "fill" the masked regions of a sequence with an arbitrary letter (typically the "+" letter).

**Usage**

```
injectHardMask(x, letter="+")
```

**Arguments**

<code>x</code>	A <a href="#">MaskedXString</a> or <a href="#">XStringViews</a> object.
<code>letter</code>	A single letter.

**Details**

The name of the `injectHardMask` function was chosen because of the primary use that it is intended for: converting a pile of active "soft masks" into a "hard mask". Here the pile of active "soft masks" refers to the active masks that have been put on top of a sequence. In Biostrings, the original sequence and the masks defined on top of it are bundled together in one of the dedicated containers for this: the [MaskedBString](#), [MaskedDNAString](#), [MaskedRNAString](#) and [MaskedAAS-tring](#) containers (this is the [MaskedXString](#) family of containers). The original sequence is always stored unmodified in a [MaskedXString](#) object so no information is lost. This allows the user to activate/deactivate masks without having to worry about losing the letters that are in the regions that are masked/unmasked. Also this allows better memory management since the original sequence never needs to be copied, even when the set of active/inactive masks changes.

However, there are situations where the user might want to *really* get rid of the letters that are in some particular regions by replacing them with a junk letter (e.g. "+") that is guaranteed to not interfere with the analysis that s/he is currently doing. For example, it's very likely that a set of

motifs or short reads will not contain the "+" letter (this could easily be checked) so they will never hit the regions filled with "+". In a way, it's like the regions filled with "+" were masked but we call this kind of masking "hard masking".

Some important differences between "soft" and "hard" masking:

injectHardMask creates a (modified) copy of the original sequence. Using "soft masking" does not.

A function that is "mask aware" like `alphabetFrequency` or `matchPattern` will really skip the masked regions when "soft masking" is used i.e. they will not walk thru the regions that are under active masks. This might lead to some speed improvements when a high percentage of the original sequence is masked. With "hard masking", the entire sequence is walked thru.

Matches cannot span over masked regions with "soft masking". With "hard masking" they can.

### Value

An `XString` object of the same length as the original object `x` if `x` is a `MaskedXString` object, or of the same length as `subject(x)` if it's an `XStringViews` object.

### Author(s)

H. Pages

### See Also

[maskMotif](#), [MaskedXString-class](#), [replaceLetterAt](#), [chartr](#), [XString](#), [XStringViews-class](#)

### Examples

```
## -----
## A. WITH AN XStringViews OBJECT
## -----
v2 <- Views("abCDefgHIJK", start=c(8, 3), end=c(14, 4))
injectHardMask(v2)
injectHardMask(v2, letter="=")

## -----
## B. WITH A MaskedXString OBJECT
## -----
mask0 <- Mask(mask.width=29, start=c(3, 10, 25), width=c(6, 8, 5))
x <- DNASTring("ACACAAGTAGATAGACTNNGAGAGACGC")
masks(x) <- mask0
x
subject <- injectHardMask(x)

## Matches can span over masked regions with "hard masking":
matchPattern("ACggggggA", subject, max.mismatch=6)
## but not with "soft masking":
matchPattern("ACggggggA", x, max.mismatch=6)
```

---

IUPAC\_CODE\_MAP

*The IUPAC Extended Genetic Alphabet*

---

### Description

The IUPAC\_CODE\_MAP named character vector contains the mapping from the IUPAC nucleotide ambiguity codes to their meaning.

The mergeIUPACLetters function provides the reverse mapping.

### Usage

```
IUPAC_CODE_MAP  
mergeIUPACLetters(x)
```

### Arguments

x                    A vector of non-empty character strings made of IUPAC letters.

### Details

IUPAC nucleotide ambiguity codes are used for representing sequences of nucleotides where the exact nucleotides that occur at some given positions are not known with certainty.

### Value

IUPAC\_CODE\_MAP is a named character vector where the names are the IUPAC nucleotide ambiguity codes and the values are their corresponding meanings. The meaning of each code is described by a string that enumerates the base letters ("A", "C", "G" or "T") associated with the code.

The value returned by mergeIUPACLetters is an unnamed character vector of the same length as its argument x where each element is an IUPAC nucleotide ambiguity code.

### Author(s)

H. Pages

### References

[http://www.chick.manchester.ac.uk/SiteSeer/IUPAC\\_codes.html](http://www.chick.manchester.ac.uk/SiteSeer/IUPAC_codes.html)

IUPAC-IUB SYMBOLS FOR NUCLEOTIDE NOMENCLATURE: Cornish-Bowden (1985) *Nucl. Acids Res.* 13: 3021-3030.

### See Also

[DNAStrng](#), [RNAString](#)

## Examples

```
IUPAC_CODE_MAP
some_iupac_codes <- c("R", "M", "G", "N", "V")
IUPAC_CODE_MAP[some_iupac_codes]
mergeIUPACLetters(IUPAC_CODE_MAP[some_iupac_codes])

mergeIUPACLetters(c("Ca", "Acc", "aA", "MAAmC", "gM", "AB", "bS", "mk"))
```

---

letter

*Subsetting a string*

---

## Description

Extract a substring from a string by picking up individual letters by their position.

## Usage

```
letter(x, i)
```

## Arguments

**x** A character vector, or an [XString](#), [XStringViews](#) or [MaskedXString](#) object.

**i** An integer vector with no NAs.

## Details

Unlike with the `substr` or `substring` functions, `i` must contain valid positions.

## Value

A character vector of length 1 when `x` is an [XString](#) or [MaskedXString](#) object (the masks are ignored for the latter).

A character vector of the same length as `x` when `x` is a character vector or an [XStringViews](#) object.

Note that, because `i` must contain valid positions, all non-NA elements in the result are guaranteed to have exactly `length(i)` characters.

## See Also

[subseq](#), [XString-class](#), [XStringViews-class](#), [MaskedXString-class](#)

**Examples**

```
x <- c("abcd", "ABC")
i <- c(3, 1, 1, 2, 1)

## With a character vector:
letter(x[1], 3:1)
letter(x, 3)
letter(x, i)
#letter(x, 4)          # Error!

## With a BString object:
letter(BString(x[1]), i) # returns a character vector
BString(x[1])[i]       # returns a BString object

## With an XStringViews object:
x2 <- as(BStringSet(x), "Views")
letter(x2, i)
```

---

letterFrequency	<i>Calculate the frequency of letters in a biological sequence, or the consensus matrix of a set of sequences</i>
-----------------	---

---

**Description**

Given a biological sequence (or a set of biological sequences), the `alphabetFrequency` function computes the frequency of each letter of the relevant [alphabet](#).

`letterFrequency` is similar, but more compact if one is only interested in certain letters. It can also tabulate letters "in common".

`letterFrequencyInSlidingView` is a more specialized version of `letterFrequency` for (non-masked) [XString](#) objects. It tallies the requested letter frequencies for a fixed-width view, or window, that is conceptually slid along the entire input sequence.

The `consensusMatrix` function computes the consensus matrix of a set of sequences, and the `consensusString` function creates the consensus sequence from the consensus matrix based upon specified criteria.

In this man page we call "DNA input" (or "RNA input") an [XString](#), [XStringSet](#), [XStringViews](#) or [MaskedXString](#) object of base type DNA (or RNA).

**Usage**

```
alphabetFrequency(x, as.prob=FALSE, ...)
hasOnlyBaseLetters(x)
uniqueLetters(x)

letterFrequency(x, letters, OR="|", as.prob=FALSE, ...)
letterFrequencyInSlidingView(x, view.width, letters, OR="|", as.prob=FALSE)
```



```

consensusMatrix(x, as.prob=FALSE, shift=0L, width=NULL, ...)

## S4 method for signature matrix
consensusString(x, ambiguityMap="?", threshold=0.5)
## S4 method for signature DNASTringSet
consensusString(x, ambiguityMap=IUPAC_CODE_MAP,
                threshold=0.25, shift=0L, width=NULL)
## S4 method for signature RNASTringSet
consensusString(x,
                ambiguityMap=
                structure(as.character(RNASTringSet(DNASTringSet(IUPAC_CODE_MAP))),
                        names=
                        as.character(RNASTringSet(DNASTringSet(names(IUPAC_CODE_MAP))))),
                threshold=0.25, shift=0L, width=NULL)

```

### Arguments

x	<p>An <a href="#">XString</a>, <a href="#">XStringSet</a>, <a href="#">XStringViews</a> or <a href="#">MaskedXString</a> object for <code>alphabetFrequency</code>, <code>letterFrequency</code>, or <code>uniqueLetters</code>.</p> <p>DNA or RNA input for <code>hasOnlyBaseLetters</code>.</p> <p>An <a href="#">XString</a> object for <code>letterFrequencyInSlidingView</code>.</p> <p>A character vector, or an <a href="#">XStringSet</a> or <a href="#">XStringViews</a> object for <code>consensusMatrix</code>.</p> <p>A consensus matrix (as returned by <code>consensusMatrix</code>), or an <a href="#">XStringSet</a> or <a href="#">XStringViews</a> object for <code>consensusString</code>.</p>
as.prob	If TRUE then probabilities are reported, otherwise counts (the default).
view.width	For <code>letterFrequencyInSlidingView</code> , the constant (e.g. 35, 48, 1000) size of the "window" to slide along x. The specified letters are tabulated in each window of length <code>view.width</code> . The rows of the result (see value) correspond to the various windows.
letters	For <code>letterFrequency</code> or <code>letterFrequencyInSlidingView</code> , a character vector (e.g. "C", "CG", <code>c("C", "G")</code> ) giving the letters to tabulate. When x is DNA or RNA input, letters must come from <code>alphabet(x)</code> . Except with <code>OR=0</code> , multi-character elements of letters ( <code>nchar &gt; 1</code> ) are taken as groupings of letters into subsets, to be tabulated in common ("or"d), as if their <code>alphabetFrequency</code> 's were added ( <a href="#">Arithmetic</a> ). The columns of the result (see value) correspond to the individual and sets of letters which are counted separately. Unrelated (and, with some post-processing, related) counts may of course be obtained in separate calls.
OR	For <code>letterFrequency</code> or <code>letterFrequencyInSlidingView</code> , the string (default <code> </code> ) to use as a separator in forming names for the "grouped" columns, e.g. "C G". The otherwise exceptional value 0 (zero) disables or'ing and is provided for convenience, allowing a single multi-character string (or several strings) of letters that should be counted separately. If some but not all letters are to be counted separately, they must reside in separate elements of letters (with <code>nchar = 1</code> unless they are to be grouped with other letters), and <code>OR</code> cannot be 0.
ambiguityMap	Either a single character to use when agreement is not reached or a named character vector where the names are the ambiguity characters and the values are the

	combinations of letters that comprise the ambiguity (e.g. <code>link{IUPAC_CODE_MAP}</code> ). When <code>ambiguityMap</code> is a named character vector, occurrences of ambiguous letters in <code>x</code> are replaced with their base alphabet letters that have been equally weighted to sum to 1. (See Details for some examples.)
threshold	The minimum probability threshold for an agreement to be declared. When <code>ambiguityMap</code> is a single character, <code>threshold</code> is a single number in (0, 1]. When <code>ambiguityMap</code> is a named character vector (e.g. <code>link{IUPAC_CODE_MAP}</code> ), <code>threshold</code> is a single number in (0, 1/sum(nchar(ambiguityMap) == 1)].
...	Further arguments to be passed to or from other methods. For the <a href="#">XStringViews</a> and <a href="#">XStringSet</a> methods, the <code>collapse</code> argument is accepted. Except for <code>letterFrequency</code> or <code>letterFrequencyInSlidingView</code> , and with DNA or RNA input, the <code>baseOnly</code> argument is accepted. If <code>baseOnly</code> is <code>TRUE</code> , the returned vector (or matrix) only contains the frequencies of the letters that belong to the "base" alphabet of <code>x</code> i.e. to the alphabet returned by <code>alphabet(x, baseOnly=TRUE)</code> .
shift	An integer vector (recycled to the length of <code>x</code> ) specifying how each sequence in <code>x</code> should be (horizontally) shifted with respect to the first column of the consensus matrix to be returned. By default ( <code>shift=0</code> ), each sequence in <code>x</code> has its first letter aligned with the first column of the matrix. A positive <code>shift</code> value means that the corresponding sequence must be shifted to the right, and a negative <code>shift</code> value that it must be shifted to the left. For example, a shift of 5 means that it must be shifted 5 positions to the right (i.e. the first letter in the sequence must be aligned with the 6th column of the matrix), and a shift of -3 means that it must be shifted 3 positions to the left (i.e. the 4th letter in the sequence must be aligned with the first column of the matrix).
width	The number of columns of the returned matrix for the <code>consensusMatrix</code> method for <a href="#">XStringSet</a> objects. When <code>width=NULL</code> (the default), then this method returns a matrix that has just enough columns to have its last column aligned with the rightmost letter of all the sequences in <code>x</code> after those sequences have been shifted (see the <code>shift</code> argument above). This ensures that any wider consensus matrix would be a "padded with zeros" version of the matrix returned when <code>width=NULL</code> . The length of the returned sequence for the <code>consensusString</code> method for <a href="#">XStringSet</a> objects.

## Details

`alphabetFrequency`, `letterFrequency`, and `letterFrequencyInSlidingView` are generic functions defined in the `Biostrings` package.

`letterFrequency` is similar to `alphabetFrequency` but specific to the letters of interest, hence more compact, especially with OR non-zero.

`letterFrequencyInSlidingView` yields the same result, on the sequence `x`, that `letterFrequency` would, if applied to the hypothetical (and possibly huge) [XStringViews](#) object consisting of all the intervals of length `view.width` on `x`. Taking advantage of the knowledge that successive "views" are nearly identical, for letter counting purposes, it is both lighter and faster.

For `letterFrequencyInSlidingView`, a masked ([MaskedXString](#)) object `x` is only supported through a cast to an (ordinary) [XString](#) such as `unmasked` (which includes its masked regions).

When `consensusString` is executed with a named character `ambiguityMap` argument, it weights each input string equally and assigns an equal probability to each of the base letters represented by an ambiguity letter. So for DNA and a threshold of 0.25, a "G" and an "R" would result in an "R" since  $1/2 \text{ "G"} + 1/2 \text{ "R"} = 3/4 \text{ "G"} + 1/4 \text{ "A"} \Rightarrow \text{"R"}$ ; two "G"'s and one "R" would result in a "G" since  $2/3 \text{ "G"} + 1/3 \text{ "R"} = 5/6 \text{ "G"} + 1/6 \text{ "A"} \Rightarrow \text{"G"}$ ; and one "A" and one "N" would result in an "N" since  $1/2 \text{ "A"} + 1/2 \text{ "N"} = 5/8 \text{ "A"} + 1/8 \text{ "C"} + 1/8 \text{ "G"} + 1/8 \text{ "T"} \Rightarrow \text{"N"}$ .

## Value

`alphabetFrequency` returns an integer vector when `x` is an [XString](#) or [MaskedXString](#) object. When `x` is an [XStringSet](#) or [XStringViews](#) object, then it returns an integer matrix with `length(x)` rows where the `i`-th row contains the frequencies for `x[[i]]`. If `x` is a DNA or RNA input, then the returned vector is named with the letters in the alphabet. If the `baseOnly` argument is `TRUE`, then the returned vector has only 5 elements: 4 elements corresponding to the 4 nucleotides + the 'other' element.

`letterFrequency` returns, similarly, an integer vector or matrix, but restricted and/or collated according to letters and OR.

`letterFrequencyInSlidingView` returns, for an [XString](#) object `x` of length (`nchar`) `L`, an integer matrix with `L-view.width+1` rows, the `i`-th of which holding the letter frequencies of `substring(x, i, i+view.width-1)`.

`hasOnlyBaseLetters` returns `TRUE` or `FALSE` indicating whether or not `x` contains only base letters (i.e. As, Cs, Gs and Ts for DNA input and As, Cs, Gs and Us for RNA input).

`uniqueLetters` returns a vector of 1-letter or empty strings. The empty string is used to represent the nul character if `x` happens to contain any. Note that this can only happen if the base class of `x` is [BString](#).

An integer matrix with letters as row names for `consensusMatrix`.

A standard character string for `consensusString`.

## Author(s)

H. Pages and P. Aboyoun; H. Jaffee for `letterFrequency` and `letterFrequencyInSlidingView`

## See Also

[alphabet](#), [coverage](#), [oligonucleotideFrequency](#), [countPDict](#), [XString-class](#), [XStringSet-class](#), [XStringViews-class](#), [MaskedXString-class](#), [strsplit](#)

## Examples

```
## -----
## alphabetFrequency()
## -----
data(yeastSEQCHR1)
yeast1 <- DNASTring(yeastSEQCHR1)

alphabetFrequency(yeast1)
alphabetFrequency(yeast1, baseOnly=TRUE)

hasOnlyBaseLetters(yeast1)
```

```

uniqueLetters(yeast1)

## With input made of multiple sequences:
library(drosophila2probe)
probes <- DNASTringSet(drosophila2probe)
alphabetFrequency(probes[1:50], baseOnly=TRUE)
alphabetFrequency(probes, baseOnly=TRUE, collapse=TRUE)

## -----
## letterFrequency()
## -----
letterFrequency(probes[[1]], letters="ACGT", OR=0)
base_letters <- alphabet(probes, baseOnly=TRUE)
base_letters
letterFrequency(probes[[1]], letters=base_letters, OR=0)
base_letter_freqs <- letterFrequency(probes, letters=base_letters, OR=0)
head(base_letter_freqs)
GC_content <- letterFrequency(probes, letters="CG")
head(GC_content)
letterFrequency(probes, letters="CG", collapse=TRUE)

## -----
## letterFrequencyInSlidingView()
## -----
data(yeastSEQCHR1)
x <- DNASTring(yeastSEQCHR1)
view.width <- 48
letters <- c("A", "CG")
two_columns <- letterFrequencyInSlidingView(x, view.width, letters)
head(two_columns)
tail(two_columns)
three_columns <- letterFrequencyInSlidingView(x, view.width, letters, OR=0)
head(three_columns)
tail(three_columns)
stopifnot(identical(two_columns[ , "C|G"],
                    three_columns[ , "C"] + three_columns[ , "G"]))

## Note that, alternatively, three_columns can also be obtained by
## creating the views on x (as a Views object) and by calling
## alphabetFrequency() on it. But, of course, that is be *much* less
## efficient (both, in terms of memory and speed) than using
## letterFrequencyInSlidingView():
v <- Views(x, start=seq_len(length(x) - view.width + 1), width=view.width)
v
three_columns2 <- alphabetFrequency(v, baseOnly=TRUE)[ , c("A", "C", "G")]
stopifnot(identical(three_columns2, three_columns))

## Set the width of the view to length(x) to get the global frequencies:
letterFrequencyInSlidingView(x, letters="ACGTN", view.width=length(x), OR=0)

## -----
## consensus*()
## -----

```

```

## Read in ORF data:
file <- system.file("extdata", "someORF.fa", package="Biostrings")
orf <- readDNASTringSet(file)

## To illustrate, the following example assumes the ORF data
## to be aligned for the first 10 positions (patently false):
orf10 <- DNASTringSet(orf, end=10)
consensusMatrix(orf10, baseOnly=TRUE)

## The following example assumes the first 10 positions to be aligned
## after some incremental shifting to the right (patently false):
consensusMatrix(orf10, baseOnly=TRUE, shift=0:6)
consensusMatrix(orf10, baseOnly=TRUE, shift=0:6, width=10)

## For the character matrix containing the "exploded" representation
## of the strings, do:
as.matrix(orf10, use.names=FALSE)

## consensusMatrix() can be used to just compute the alphabet frequency
## for each position in the input sequences:
consensusMatrix(probes, baseOnly=TRUE)

## After sorting, the first 5 probes might look similar (at least on
## their first bases):
consensusString(sort(probes)[1:5])
consensusString(sort(probes)[1:5], ambiguityMap = "N", threshold = 0.5)

## Consensus involving ambiguity letters in the input strings
consensusString(DNASTringSet(c("NNNN", "ACTG")))
consensusString(DNASTringSet(c("AANN", "ACTG")))
consensusString(DNASTringSet(c("ACAG", "ACAR")))
consensusString(DNASTringSet(c("ACAG", "ACAR", "ACAG")))

## -----
## C. RELATIONSHIP BETWEEN consensusMatrix() AND coverage()
## -----
## Applying colSums() on a consensus matrix gives the coverage that
## would be obtained by piling up (after shifting) the input sequences
## on top of an (imaginary) reference sequence:
cm <- consensusMatrix(orf10, shift=0:6, width=10)
colSums(cm)

## Note that this coverage can also be obtained with:
as.integer(coverage(IRanges(rep(1, length(orf)), width(orf)), shift=0:6, width=10))

```

**Description**

This function accepts a character vector and computes the length of the longest substring containing only letter for each element of x.

**Usage**

```
longestConsecutive(seq, letter)
```

**Arguments**

seq	Character vector.
letter	Character vector of length 1, containing one single character.

**Details**

The elements of x can be in upper case, lower case or mixed. NAs are handled.

**Value**

An integer vector of the same length as x.

**Author(s)**

W. Huber

**Examples**

```
v = c("AAACTGTGFG", "GGGAATT", "CCAAAAAAAAAATT")
longestConsecutive(v, "A")
```

---

lowlevel-matching      *Low-level matching functions*

---

**Description**

In this man page we define precisely and illustrate what a "match" of a pattern P in a subject S is in the context of the Biostrings package. This definition of a "match" is central to most pattern matching functions available in this package: unless specified otherwise, most of them will adhere to the definition provided here.

hasLetterAt checks whether a sequence or set of sequences has the specified letters at the specified positions.

neditAt, isMatchingAt and which.isMatchingAt are low-level matching functions that only look for matches at the specified positions in the subject.

**Usage**

```

hasLetterAt(x, letter, at, fixed=TRUE)

## neditAt() and related utils:
neditAt(pattern, subject, at=1,
         with.indels=FALSE, fixed=TRUE)
neditStartingAt(pattern, subject, starting.at=1,
                with.indels=FALSE, fixed=TRUE)
neditEndingAt(pattern, subject, ending.at=1,
               with.indels=FALSE, fixed=TRUE)

## isMatchingAt() and related utils:
isMatchingAt(pattern, subject, at=1,
              max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE)
isMatchingStartingAt(pattern, subject, starting.at=1,
                     max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE)
isMatchingEndingAt(pattern, subject, ending.at=1,
                   max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE)

## which.isMatchingAt() and related utils:
which.isMatchingAt(pattern, subject, at=1,
                   max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE,
                   follow.index=FALSE, auto.reduce.pattern=FALSE)
which.isMatchingStartingAt(pattern, subject, starting.at=1,
                            max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE,
                            follow.index=FALSE, auto.reduce.pattern=FALSE)
which.isMatchingEndingAt(pattern, subject, ending.at=1,
                          max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE,
                          follow.index=FALSE, auto.reduce.pattern=FALSE)

```

**Arguments**

x	A character vector, or an <a href="#">XString</a> or <a href="#">XStringSet</a> object.
letter	A character string or an <a href="#">XString</a> object containing the letters to check.
at, starting.at, ending.at	An integer vector specifying the starting (for starting.at and at) or ending (for ending.at) positions of the pattern relatively to the subject. With <code>auto.reduce.pattern</code> (below), either a single integer or a constant vector of length <code>nchar(pattern)</code> (below), to which the former is immediately converted. For the <code>hasLetterAt</code> function, <code>letter</code> and <code>at</code> must have the same length.
pattern	The pattern string (but see <code>auto.reduce.pattern</code> , below).
subject	A character vector, or an <a href="#">XString</a> or <a href="#">XStringSet</a> object containing the subject sequence(s).
max.mismatch, min.mismatch	Integer vectors of length $\geq 1$ recycled to the length of the <code>at</code> (or <code>starting.at</code> , or <code>ending.at</code> ) argument. More details below.
with.indels	See details below.

fixed	<p>Only with a <a href="#">DNString</a> or <a href="#">RNString</a>-based subject can a fixed value other than the default (TRUE) be used.</p> <p>If TRUE (the default), an IUPAC ambiguity code in the pattern can only match the same code in the subject, and vice versa. If FALSE, an IUPAC ambiguity code in the pattern can match any letter in the subject that is associated with the code, and vice versa. See <a href="#">IUPAC_CODE_MAP</a> for more information about the IUPAC Extended Genetic Alphabet.</p> <p>fixed can also be a character vector, a subset of <code>c("pattern", "subject")</code>. <code>fixed=c("pattern", "subject")</code> is equivalent to <code>fixed=TRUE</code> (the default). An empty vector is equivalent to <code>fixed=FALSE</code>. With <code>fixed="subject"</code>, ambiguities in the pattern only are interpreted as wildcards. With <code>fixed="pattern"</code>, ambiguities in the subject only are interpreted as wildcards.</p>
follow.index	<p>Whether the single integer returned by <code>which.isMatchingAt</code> (and related utils) should be the first <code>*value*</code> in <code>at</code> for which a match occurred, or its <code>*index*</code> in <code>at</code> (the default).</p>
auto.reduce.pattern	<p>Whether <code>pattern</code> should be effectively shortened by 1 letter, from its beginning for <code>which.isMatchingStartingAt</code> and from its end for <code>which.isMatchingEndingAt</code>, for each successive <code>(at, max.mismatch)</code> "pair".</p>

## Details

A "match" of pattern P in subject S is a substring S' of S that is considered similar enough to P according to some distance (or metric) specified by the user. 2 distances are supported by most pattern matching functions in the Biostrings package. The first (and simplest) one is the "number of mismatching letters". It is defined only when the 2 strings to compare have the same length, so when this distance is used, only matches that have the same number of letters as P are considered. The second one is the "edit distance" (aka Levenshtein distance): it's the minimum number of operations needed to transform P into S', where an operation is an insertion, deletion, or substitution of a single letter. When this metric is used, matches can have a different number of letters than P.

The `nediAt` function implements these 2 distances. If `with.indels` is FALSE (the default), then the first distance is used i.e. `nediAt` returns the "number of mismatching letters" between the pattern P and the substring S' of S starting at the positions specified in `at` (note that `nediAt` is vectorized so a long vector of integers can be passed thru the `at` argument). If `with.indels` is TRUE, then the "edit distance" is used: for each position specified in `at`, P is compared to all the substrings S' of S starting at this position and the smallest distance is returned. Note that this distance is guaranteed to be reached for a substring of length  $< 2 * \text{length}(P)$  so, of course, in practice, P only needs to be compared to a small number of substrings for every starting position.

## Value

`hasLetterAt`: A logical matrix with one row per element in `x` and one column per letter/position to check. When a specified position is invalid with respect to an element in `x` then the corresponding matrix element is set to NA.

`nediAt`: If `subject` is an [XString](#) object, then return an integer vector of the same length as `at`. If `subject` is an [XStringSet](#) object, then return the integer matrix with `length(at)` rows and `length(subject)` columns defined by:



```
sapply(unname(subject),
      function(x) neditAt(pattern, x, ...))
```

neditStartingAt is identical to neditAt except that the at argument is now called starting.at. neditEndingAt is similar to neditAt except that the at argument is now called ending.at and must contain the ending positions of the pattern relatively to the subject.

isMatchingAt: If subject is an [XString](#) object, then return the logical vector defined by:

```
min.mismatch <= neditAt(...) <= max.mismatch
```

If subject is an [XStringSet](#) object, then return the logical matrix with length(at) rows and length(subject) columns defined by:

```
sapply(unname(subject),
      function(x) isMatchingAt(pattern, x, ...))
```

isMatchingStartingAt is identical to isMatchingAt except that the at argument is now called starting.at. isMatchingEndingAt is similar to isMatchingAt except that the at argument is now called ending.at and must contain the ending positions of the pattern relatively to the subject.

which.isMatchingAt: The default behavior (follow.index=FALSE) is as follow. If subject is an [XString](#) object, then return the single integer defined by:

```
which(isMatchingAt(...))[1]
```

If subject is an [XStringSet](#) object, then return the integer vector defined by:

```
sapply(unname(subject),
      function(x) which.isMatchingAt(pattern, x, ...))
```

If follow.index=TRUE, then the returned value is defined by:

```
at[which.isMatchingAt(..., follow.index=FALSE)]
```

which.isMatchingStartingAt is identical to which.isMatchingAt except that the at argument is now called starting.at. which.isMatchingEndingAt is similar to which.isMatchingAt except that the at argument is now called ending.at and must contain the ending positions of the pattern relatively to the subject.

### See Also

[nucleotideFrequencyAt](#), [matchPattern](#), [matchPDict](#), [matchLRPatterns](#), [trimLRPatterns](#), [IUPAC\\_CODE\\_MAP](#), [XString-class](#), [align-utils](#)

**Examples**

```

## -----
## hasLetterAt()
## -----
x <- DNASTringSet(c("AAACGT", "AACGT", "ACGT", "TAGGA"))
hasLetterAt(x, "AAAAA", 1:6)

## hasLetterAt() can be used to answer questions like: "which elements
## in x have an A at position 2 and a G at position 4?"
q1 <- hasLetterAt(x, "AG", c(2, 4))
which(rowSums(q1) == 2)

## or "how many probes in the drosophila2 chip have T, G, T, A at
## position 2, 4, 13 and 20, respectively?"
library(drosophila2probe)
probes <- DNASTringSet(drosophila2probe)
q2 <- hasLetterAt(probes, "TGTA", c(2, 4, 13, 20))
sum(rowSums(q2) == 4)
## or "whats the probability to have an A at position 25 if there is
## one at position 13?"
q3 <- hasLetterAt(probes, "AACGT", c(13, 25, 25, 25))
sum(q3[, 1] & q3[, 2]) / sum(q3[, 1])
## Probabilities to have other bases at position 25 if there is an A
## at position 13:
sum(q3[, 1] & q3[, 3]) / sum(q3[, 1]) # C
sum(q3[, 1] & q3[, 4]) / sum(q3[, 1]) # G
sum(q3[, 1] & q3[, 5]) / sum(q3[, 1]) # T

## See ?nucleotideFrequencyAt for another way to get those results.

## -----
## neditAt() / isMatchingAt() / which.isMatchingAt()
## -----
subject <- DNASTring("GTATA")

## Pattern "AT" matches subject "GTATA" at position 3 (exact match)
neditAt("AT", subject, at=3)
isMatchingAt("AT", subject, at=3)

## ... but not at position 1
neditAt("AT", subject)
isMatchingAt("AT", subject)

## ... unless we allow 1 mismatching letter (inexact match)
isMatchingAt("AT", subject, max.mismatch=1)

## Here we look at 6 different starting positions and find 3 matches if
## we allow 1 mismatching letter
isMatchingAt("AT", subject, at=0:5, max.mismatch=1)

## No match
neditAt("NT", subject, at=1:4)

```

```

isMatchingAt("NT", subject, at=1:4)

## 2 matches if N is interpreted as an ambiguity (fixed=FALSE)
neditAt("NT", subject, at=1:4, fixed=FALSE)
isMatchingAt("NT", subject, at=1:4, fixed=FALSE)

## max.mismatch != 0 and fixed=FALSE can be used together
neditAt("NCA", subject, at=0:5, fixed=FALSE)
isMatchingAt("NCA", subject, at=0:5, max.mismatch=1, fixed=FALSE)

some_starts <- c(10:-10, NA, 6)
subject <- DNASTring("ACGTGCA")
is_matching <- isMatchingAt("CAT", subject, at=some_starts, max.mismatch=1)
some_starts[is_matching]

which.isMatchingAt("CAT", subject, at=some_starts, max.mismatch=1)
which.isMatchingAt("CAT", subject, at=some_starts, max.mismatch=1,
                    follow.index=TRUE)

## -----
## WITH INDELS
## -----
subject <- BString("ABCDEFxxxCDEFxxxABBCDE")

neditAt("ABCDEF", subject, at=9)
neditAt("ABCDEF", subject, at=9, with.indels=TRUE)
isMatchingAt("ABCDEF", subject, at=9, max.mismatch=1, with.indels=TRUE)
isMatchingAt("ABCDEF", subject, at=9, max.mismatch=2, with.indels=TRUE)
neditAt("ABCDEF", subject, at=17)
neditAt("ABCDEF", subject, at=17, with.indels=TRUE)
neditEndingAt("ABCDEF", subject, ending.at=22)
neditEndingAt("ABCDEF", subject, ending.at=22, with.indels=TRUE)

```

---

MaskedXString-class    *MaskedXString objects*

---

## Description

The MaskedBString, MaskedDNASTring, MaskedRNASTring and MaskedAAString classes are containers for storing masked sequences.

All those containers derive directly (and with no additional slots) from the MaskedXString virtual class.

## Details

In Biostrings, a pile of masks can be put on top of a sequence. A pile of masks is represented by a [MaskCollection](#) object and the sequence by an [XString](#) object. A MaskedXString object is the result of bundling them together in a single object.

Note that, no matter what masks are put on top of it, the original sequence is always stored unmodified in a MaskedXString object. This allows the user to activate/deactivate masks without having to worry about losing the information stored in the masked/unmasked regions. Also this allows efficient memory management since the original sequence never needs to be copied (modifying it would require to make a copy of it first - sequences cannot and should never be modified in place in Biostrings), even when the set of active/inactive masks changes.

### Accessor methods

In the code snippets below, `x` is a MaskedXString object. For `masks(x)` and `masks(x) <- y`, it can also be an XString object and `y` must be NULL or a MaskCollection object.

`unmasked(x)`: Turns `x` into an XString object by dropping the masks.

`masks(x)`: Turns `x` into a MaskCollection object by dropping the sequence.

`masks(x) <- y`: If `x` is an XString object and `y` is NULL, then this doesn't do anything.

If `x` is an XString object and `y` is a MaskCollection object, then this turns `x` into a MaskedXString object by putting the masks in `y` on top of it.

If `x` is a MaskedXString object and `y` is NULL, then this is equivalent to `x <- unmasked(x)`.

If `x` is a MaskedXString object and `y` is a MaskCollection object, then this replaces the masks currently on top of `x` by the masks in `y`.

`alphabet(x)`: Equivalent to `alphabet(unmasked(x))`. See [?alphabet](#) for more information.

`length(x)`: Equivalent to `length(unmasked(x))`. See [?length,XString-method](#) for more information.

### "maskedwidth" and related methods

In the code snippets below, `x` is a MaskedXString object.

`maskedwidth(x)`: Get the number of masked letters in `x`. A letter is considered masked iff it's masked by at least one active mask.

`maskedratio(x)`: Equivalent to `maskedwidth(x) / length(x)`.

`nchar(x)`: Equivalent to `length(x) - maskedwidth(x)`.

### Coercion

In the code snippets below, `x` is a MaskedXString object.

`as(x, "Views")`: Turns `x` into a Views object where the views are the unmasked regions of the original sequence ("unmasked" means not masked by at least one active mask).

### Other methods

In the code snippets below, `x` is a MaskedXString object.

`collapse(x)`: Collapses the set of masks in `x` into a single mask made of all active masks.

`gaps(x)`: Reverses all the masks i.e. each mask is replaced by a mask where previously unmasked regions are now masked and previously masked regions are now unmasked.

**Author(s)**

H. Pages

**See Also**

- [maskMotif](#)
- [injectHardMask](#)
- [alphabetFrequency](#)
- [reverseComplement](#)
- [XString-class](#)
- [MaskCollection-class](#)
- [Views-class](#)

**Examples**

```
## -----  
## A. MASKING BY POSITION  
## -----  
mask0 <- Mask(mask.width=29, start=c(3, 10, 25), width=c(6, 8, 5))  
x <- DNASTring("ACACAAGTAGATAGACTNNGAGAGACGC")  
length(x) # same as width(mask0)  
nchar(x) # same as length(x)  
masks(x) <- mask0  
x  
length(x) # has not changed  
nchar(x) # has changed  
gaps(x)  
  
## Prepare a MaskCollection object of 3 masks (mymasks) by running the  
## examples in the man page for these objects:  
example(MaskCollection, package="IRanges")  
  
## Put it on x:  
masks(x) <- mymasks  
x  
alphabetFrequency(x)  
  
## Deactivate all masks:  
active(masks(x)) <- FALSE  
x  
  
## Activate mask "C":  
active(masks(x))["C"] <- TRUE  
x  
  
## Turn MaskedXString object into a Views object:  
as(x, "Views")  
  
## Drop the masks:
```

```

masks(x) <- NULL
x
alphabetFrequency(x)

## -----
## B. MASKING BY CONTENT
## -----
## See ?maskMotif for masking by content

```

---

maskMotif	<i>Masking by content (or by position)</i>
-----------	--

---

## Description

Functions for masking a sequence by content (or by position).

## Usage

```

maskMotif(x, motif, min.block.width=1, ...)
mask(x, start=NA, end=NA, pattern)

```

## Arguments

x	The sequence to mask.
motif	The motif to mask in the sequence.
min.block.width	The minimum width of the blocks to mask.
...	Additional arguments for matchPattern.
start	An integer vector containing the starting positions of the regions to mask.
end	An integer vector containing the ending positions of the regions to mask.
pattern	The motif to mask in the sequence.

## Value

A [MaskedXString](#) object for maskMotif and an [XStringViews](#) object for mask.

## Author(s)

H. Pages

## See Also

[read.Mask](#), [matchPattern](#), [XString-class](#), [MaskedXString-class](#), [XStringViews-class](#), [MaskCollection-class](#)

**Examples**

```

## -----
## EXAMPLE 1
## -----

maskMotif(BString("AbcbcbcbEEEE"), "bcb")
maskMotif(BString("AbcbcbcbEEEE"), "bcb")

## maskMotif() can be used in an incremental way to mask more than 1
## motif. Note that maskMotif() does not try to mask again whats
## already masked (i.e. the new mask will never overlaps with the
## previous masks) so the order in which the motifs are masked actually
## matters as it will affect the total set of masked positions.
x0 <- BString("AbcbEEEEEEbcbcbEEEEcbcbcb")
x1 <- maskMotif(x0, "E")
x1
x2 <- maskMotif(x1, "bcb")
x2
x3 <- maskMotif(x2, "b")
x3
## Note that inverting the order in which "b" and "bcb" are masked would
## lead to a different final set of masked positions.
## Also note that the order doesnt matter if the motifs to mask dont
## overlap (we assume that the motifs are unique) i.e. if the prefix of
## each motif is not the suffix of any other motif. This is of course
## the case when all the motifs have only 1 letter.

## -----
## EXAMPLE 2
## -----

x <- DNASTring("ACACAACACTAGATAGNACTNNGAGAGACGC")

## Mask the N-blocks
x1 <- maskMotif(x, "N")
x1
as(x1, "Views")
gaps(x1)
as(gaps(x1), "Views")

## Mask the AC-blocks
x2 <- maskMotif(x1, "AC")
x2
gaps(x2)

## Mask the GA-blocks
x3 <- maskMotif(x2, "GA", min.block.width=5)
x3 # masks 2 and 3 overlap
gaps(x3)

## -----
## EXAMPLE 3

```

```

## -----
library(BSgenome.Dmelanogaster.UCSC.dm3)
chrU <- Dmelanogaster$chrU
chrU
alphabetFrequency(chrU)
chrU <- maskMotif(chrU, "N")
chrU
alphabetFrequency(chrU)
as(chrU, "Views")
as(gaps(chrU), "Views")

mask2 <- Mask(mask.width=length(chrU),
              start=c(50000, 350000, 543900), width=25000)
names(mask2) <- "some ugly regions"
masks(chrU) <- append(masks(chrU), mask2)
chrU
as(chrU, "Views")
as(gaps(chrU), "Views")

## -----
## EXAMPLE 4
## -----
## Note that unlike maskMotif(), mask() returns an XStringViews object!

## masking "by position"
mask("AxyxyxBC", 2, 6)

## masking "by content"
mask("AxyxyxBC", "xyx")
noN_chrU <- mask(chrU, "N")
noN_chrU
alphabetFrequency(noN_chrU, collapse=TRUE)

```

---

match-utils

*Utility functions operating on the matches returned by a high-level matching function*

---

## Description

Miscellaneous utility functions operating on the matches returned by a high-level matching function like [matchPattern](#), [matchPDict](#), etc...

## Usage

```

mismatch(pattern, x, fixed=TRUE)
nmatch(pattern, x, fixed=TRUE)
nmismatch(pattern, x, fixed=TRUE)
## S4 method for signature MIndex
coverage(x, shift=0L, width=NULL, weight=1L)

```



```
## S4 method for signature MaskedXString
coverage(x, shift=0L, width=NULL, weight=1L)
```

### Arguments

pattern	The pattern string.
x	An <a href="#">XStringViews</a> object for mismatch (typically, one returned by <code>matchPattern(pattern, subject)</code> ). An <a href="#">MIndex</a> object for coverage, or any object for which a coverage method is defined. See <a href="#">?coverage</a> .
fixed	See <a href="#">?lowlevel-matching</a> .
shift, width	See <a href="#">?coverage</a> .
weight	An integer vector specifying how much each element in x counts.

### Details

The mismatch function gives the positions of the mismatching letters of a given pattern relatively to its matches in a given subject.

The nmatch and nmismatch functions give the number of matching and mismatching letters produced by the mismatch function.

The coverage function computes the "coverage" of a subject by a given pattern or set of patterns.

### Value

mismatch: a list of integer vectors.

nmismatch: an integer vector containing the length of the vectors produced by mismatch.

coverage: an [Rle](#) object indicating the coverage of x. See [?coverage](#) for the details. If x is an [MIndex](#) object, the coverage of a given position in the underlying sequence (typically the subject used during the search that returned x) is the number of matches (or hits) it belongs to.

### See Also

[lowlevel-matching](#), [matchPattern](#), [matchPDict](#), [XString-class](#), [XStringViews-class](#), [MIndex-class](#), [coverage](#), [align-utils](#)

### Examples

```
## -----
## mismatch() / nmismatch()
## -----
subject <- DNASTring("ACGTGCA")
m <- matchPattern("NCA", subject, max.mismatch=1, fixed=FALSE)
mismatch("NCA", m)
nmismatch("NCA", m)

## -----
## coverage()
## -----
coverage(m)
```

## See ?matchPDict for examples of using coverage() on an MIndex object...

---

matchLRPatterns      *Find paired matches in a sequence*

---

### Description

The matchLRPatterns function finds paired matches in a sequence i.e. matches specified by a left pattern, a right pattern and a maximum distance between the left pattern and the right pattern.

### Usage

```
matchLRPatterns(Lpattern, Rpattern, max.gaplength, subject,
               max.Lmismatch=0, max.Rmismatch=0,
               with.Lindels=FALSE, with.Rindels=FALSE,
               Lfixed=TRUE, Rfixed=TRUE)
```

### Arguments

Lpattern	The left part of the pattern.
Rpattern	The right part of the pattern.
max.gaplength	The max length of the gap in the middle i.e the max distance between the left and right parts of the pattern.
subject	An <a href="#">XString</a> , <a href="#">XStringViews</a> or <a href="#">MaskedXString</a> object containing the target sequence.
max.Lmismatch	The maximum number of mismatching letters allowed in the left part of the pattern. If non-zero, an inexact matching algorithm is used (see the <a href="#">matchPattern</a> function for more information).
max.Rmismatch	Same as max.Lmismatch but for the right part of the pattern.
with.Lindels	If TRUE then indels are allowed in the left part of the pattern. In that case max.Lmismatch is interpreted as the maximum "edit distance" allowed in the left part of the pattern. See the with.indels argument of the <a href="#">matchPattern</a> function for more information.
with.Rindels	Same as with.Lindels but for the right part of the pattern.
Lfixed	Only with a <a href="#">DNAString</a> or <a href="#">RNAString</a> subject can a Lfixed value other than the default (TRUE) be used. With Lfixed=FALSE, ambiguities (i.e. letters from the IUPAC Extended Genetic Alphabet (see <a href="#">IUPAC_CODE_MAP</a> ) that are not from the base alphabet) in the left pattern \_and\_ in the subject are interpreted as wildcards i.e. they match any letter that they stand for. Lfixed can also be a character vector, a subset of c("pattern", "subject"). Lfixed=c("pattern", "subject") is equivalent to Lfixed=TRUE (the default). An empty vector is equivalent to Lfixed=FALSE. With Lfixed="subject",

ambiguities in the pattern only are interpreted as wildcards. With `Lfixed="pattern"`, ambiguities in the subject only are interpreted as wildcards.

`Rfixed` Same as `Lfixed` but for the right part of the pattern.

### Value

An [XStringViews](#) object containing all the matches, even when they are overlapping (see the examples below), and where the matches are ordered from left to right (i.e. by ascending starting position).

### Author(s)

H. Pages

### See Also

[matchPattern](#), [matchProbePair](#), [trimLRPatterns](#), [findPalindromes](#), [reverseComplement](#), [XString-class](#), [XStringViews-class](#), [MaskedXString-class](#)

### Examples

```
library(BSgenome.Dmelanogaster.UCSC.dm3)
subject <- Dmelanogaster$chr3R
Lpattern <- "AGCTCCGAG"
Rpattern <- "TTGTTACA"
matchLRPatterns(Lpattern, Rpattern, 500, subject) # 1 match

## Note that matchLRPatterns() will return all matches, even when they are
## overlapping:
subject <- DNASTring("AAATTAACCCTT")
matchLRPatterns("AA", "TT", 0, subject) # 1 match
matchLRPatterns("AA", "TT", 1, subject) # 2 matches
matchLRPatterns("AA", "TT", 3, subject) # 3 matches
matchLRPatterns("AA", "TT", 7, subject) # 4 matches
```

---

matchPattern

*String searching functions*

---

### Description

A set of functions for finding all the occurrences (aka "matches" or "hits") of a given pattern (typically short) in a (typically long) reference sequence or set of reference sequences (aka the subject)

**Usage**

```
matchPattern(pattern, subject,
             max.mismatch=0, min.mismatch=0,
             with.indels=FALSE, fixed=TRUE,
             algorithm="auto")
```

```
countPattern(pattern, subject,
             max.mismatch=0, min.mismatch=0,
             with.indels=FALSE, fixed=TRUE,
             algorithm="auto")
```

```
vmatchPattern(pattern, subject,
              max.mismatch=0, min.mismatch=0,
              with.indels=FALSE, fixed=TRUE,
              algorithm="auto", ...)
```

```
vcountPattern(pattern, subject,
              max.mismatch=0, min.mismatch=0,
              with.indels=FALSE, fixed=TRUE,
              algorithm="auto", ...)
```

**Arguments**

pattern	The pattern string.
subject	An <a href="#">XString</a> , <a href="#">XStringViews</a> or <a href="#">MaskedXString</a> object for matchPattern and countPattern. An <a href="#">XStringSet</a> or <a href="#">XStringViews</a> object for vmatchPattern and vcountPattern.
max.mismatch, min.mismatch	The maximum and minimum number of mismatching letters allowed (see <a href="#">?lowlevel-matching</a> for the details). If non-zero, an algorithm that supports inexact matching is used.
with.indels	If TRUE then indels are allowed. In that case, min.mismatch must be 0 and max.mismatch is interpreted as the maximum "edit distance" allowed between the pattern and a match. Note that in order to avoid pollution by redundant matches, only the "best local matches" are returned. Roughly speaking, a "best local match" is a match that is locally both the closest (to the pattern P) and the shortest. More precisely, a substring S' of the subject S is a "best local match" iff: <ul style="list-style-type: none"> <li>(a) <math>nedit(P, S) \leq max.mismatch</math></li> <li>(b) for every substring S1 of S: <math>nedit(P, S1) &gt; nedit(P, S)</math></li> <li>(c) for every substring S2 of S that contains S: <math>nedit(P, S2) \geq nedit(P, S)</math></li> </ul>

One nice property of "best local matches" is that their first and last letters are guaranteed to match the letters in P that they align with.

fixed	If TRUE (the default), an IUPAC ambiguity code in the pattern can only match the same code in the subject, and vice versa. If FALSE, an IUPAC ambiguity code in the pattern can match any letter in the subject that is associated with the code, and vice versa. See <a href="#">?lowlevel-matching</a> for more information.
algorithm	One of the following: "auto", "naive-exact", "naive-inexact", "boyer-moore", "shift-or" or "indels".
...	Additional arguments for methods.

### Details

Available algorithms are: "naive exact", "naive inexact", "Boyer-Moore-like", "shift-or" and "indels". Not all of them can be used in all situations: restrictions apply depending on the "search criteria" i.e. on the values of the pattern, subject, max.mismatch, min.mismatch, with.indels and fixed arguments.

It is important to note that the `algorithm` argument is not part of the search criteria. This is because the supported algorithms are interchangeable, that is, if 2 different algorithms are compatible with a given search criteria, then choosing one or the other will not affect the result (but will most likely affect the performance). So there is no "wrong choice" of algorithm (strictly speaking).

Using `algorithm="auto"` (the default) is recommended because then the best suited algorithm will automatically be selected among the set of algorithms that are valid for the given search criteria.

### Value

An [XStringViews](#) object for `matchPattern`.

A single integer for `countPattern`.

An [MIndex](#) object for `vmatchPattern`.

An integer vector for `vcountPattern`, with each element in the vector corresponding to the number of matches in the corresponding element of subject.

### Note

Use [matchPDict](#) if you need to match a (big) set of patterns against a reference sequence.

Use [pairwiseAlignment](#) if you need to solve a (Needleman-Wunsch) global alignment, a (Smith-Waterman) local alignment, or an (ends-free) overlap alignment problem.

### See Also

[lowlevel-matching](#), [matchPDict](#), [pairwiseAlignment](#), [mismatch](#), [matchLRPatterns](#), [matchProbePair](#), [maskMotif](#), [alphabetFrequency](#), [XStringViews-class](#), [MIndex-class](#)

### Examples

```
## -----
## A. matchPattern()/countPattern()
## -----

## A simple inexact matching example with a short subject:
```

```

x <- DNASTring("AAGCGCGATATG")
m1 <- matchPattern("GCNNNAT", x)
m1
m2 <- matchPattern("GCNNNAT", x, fixed=FALSE)
m2
as.matrix(m2)

## With DNA sequence of yeast chromosome number 1:
data(yeastSEQCHR1)
yeast1 <- DNASTring(yeastSEQCHR1)
PpiI <- "GAACNNNNCTC" # a restriction enzyme pattern
match1.PpiI <- matchPattern(PpiI, yeast1, fixed=FALSE)
match2.PpiI <- matchPattern(PpiI, yeast1, max.mismatch=1, fixed=FALSE)

## With a genome containing isolated Ns:
library(BSgenome.Celegans.UCSC.ce2)
chrII <- Celegans[["chrII"]]
alphabetFrequency(chrII)
matchPattern("N", chrII)
matchPattern("TGGGTGTCTTT", chrII) # no match
matchPattern("TGGGTGTCTTT", chrII, fixed=FALSE) # 1 match

## Using wildcards ("N") in the pattern on a genome containing N-blocks:
library(BSgenome.Dmelanogaster.UCSC.dm3)
chrX <- maskMotif(Dmelanogaster$chrX, "N")
as(chrX, "Views") # 4 non masked regions
matchPattern("TTTATGNTTGGTA", chrX, fixed=FALSE)
## Can also be achieved with no mask:
masks(chrX) <- NULL
matchPattern("TTTATGNTTGGTA", chrX, fixed="subject")

## -----
## B. vmatchPattern()/vcountPattern()
## -----

Ebox <- DNASTring("CANNTG")
subject <- Celegans$upstream5000
mindex <- vmatchPattern(Ebox, subject, fixed=FALSE)
count_index <- countIndex(mindex) # Get the number of matches per
# subject element.
sum(count_index) # Total number of matches.
table(count_index)
i0 <- which(count_index == max(count_index))
subject[i0] # The subject element with most matches.

## The matches in subject[i0] as an IRanges object:
mindex[[i0]]
## The matches in subject[i0] as an XStringViews object:
Views(subject[[i0]], mindex[[i0]])

## -----
## C. WITH INDELS
## -----

```

```

library(BSgenome.Celegans.UCSC.ce2)
subject <- Celegans$chrI
pattern1 <- DNASTring("ACGGACCTAATGTTATC")
pattern2 <- DNASTring("ACGGACCTVATGTTRTC")

## Allowing up to 2 mismatching letters doesnt give any match:
m1a <- matchPattern(pattern1, subject, max.mismatch=2)

## But allowing up to 2 edit operations gives 3 matches:
system.time(m1b <- matchPattern(pattern1, subject, max.mismatch=2,
                               with.indels=TRUE))

m1b

## pairwiseAlignment() returns the (first) best match only:
if (interactive()) {
  mat <- nucleotideSubstitutionMatrix(match=1, mismatch=0, baseOnly=TRUE)
  ## Note that this call to pairwiseAlignment() will need to
  ## allocate 733.5 Mb of memory (i.e. length(pattern) * length(subject)
  ## * 3 bytes).
  system.time(pwa <- pairwiseAlignment(pattern1, subject, type="local",
                                       substitutionMatrix=mat,
                                       gapOpening=0, gapExtension=1))

  pwa
}

## With IUPAC ambiguities in the pattern:
m2a <- matchPattern(pattern2, subject, max.mismatch=2,
                    fixed="subject")
m2b <- matchPattern(pattern2, subject, max.mismatch=2,
                    with.indels=TRUE, fixed="subject")

## All the matches in m1b and m2a should also appear in m2b:
stopifnot(suppressWarnings(all(ranges(m1b) %in% ranges(m2b))))
stopifnot(suppressWarnings(all(ranges(m2a) %in% ranges(m2b))))

## -----
## D. WHEN with.indels=TRUE, ONLY "BEST LOCAL MATCHES" ARE REPORTED
## -----

## With deletions in the subject:
subject <- BString("ACDEFxxxCDEFxxxABCE")
matchPattern("ABCDEF", subject, max.mismatch=2, with.indels=TRUE)
matchPattern("ABCDEF", subject, max.mismatch=2)

## With insertions in the subject:
subject <- BString("AiBCDiEFxxxABCdiiFxxxAiBCDEFxxxABCiDEF")
matchPattern("ABCDEF", subject, max.mismatch=2, with.indels=TRUE)
matchPattern("ABCDEF", subject, max.mismatch=2)

## With substitutions (note that the "best local matches" can introduce
## indels and therefore be shorter than 6):
subject <- BString("AsCDEFxxxABDCEFxxxBACDEFxxxABCEDF")

```

```
matchPattern("ABCDEF", subject, max.mismatch=2, with.indels=TRUE)
matchPattern("ABCDEF", subject, max.mismatch=2)
```

---

 matchPDict

*Matching a dictionary of patterns against a reference*


---

## Description

A set of functions for finding all the occurrences (aka "matches" or "hits") of a set of patterns (aka the dictionary) in a reference sequence or set of reference sequences (aka the subject)

The following functions differ in what they return: `matchPDict` returns the "where" information i.e. the positions in the subject of all the occurrences of every pattern; `countPDict` returns the "how many times" information i.e. the number of occurrences for each pattern; and `whichPDict` returns the "who" information i.e. which patterns in the input dictionary have at least one match.

`vcountPDict` and `vwhichPDict` are vectorized versions of `countPDict` and `whichPDict`, respectively, that is, they work on a set of reference sequences in a vectorized fashion.

This man page shows how to use these functions (aka the \*PDict functions) for exact matching of a constant width dictionary i.e. a dictionary where all the patterns have the same length (same number of nucleotides).

See [?matchPDict-inexact](#) for how to use these functions for inexact matching or when the original dictionary has a variable width.

## Usage

```
matchPDict(pdict, subject,
           max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE,
           algorithm="auto", verbose=FALSE)
countPDict(pdict, subject,
           max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE,
           algorithm="auto", verbose=FALSE)
whichPDict(pdict, subject,
           max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE,
           algorithm="auto", verbose=FALSE)

vcountPDict(pdict, subject,
            max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE,
            algorithm="auto", collapse=FALSE, weight=1L,
            verbose=FALSE, ...)
vwhichPDict(pdict, subject,
            max.mismatch=0, min.mismatch=0, with.indels=FALSE, fixed=TRUE,
            algorithm="auto", verbose=FALSE)
```



**Arguments**

pdict	<p>A <a href="#">PDict</a> object containing the preprocessed dictionary.</p> <p>All these functions also work with a dictionary that has not been preprocessed (in other words, the pdict argument can receive an <a href="#">XStringSet</a> object). Of course, it won't be as fast as with a preprocessed dictionary, but it will generally be slightly faster than using <a href="#">matchPattern/countPattern</a> or <a href="#">vmatchPattern/vcountPattern</a> in a "lapply/sapply loop", because, here, looping is done at the C-level. However, by using a non-preprocessed dictionary, many of the restrictions that apply to preprocessed dictionaries don't apply anymore. For example, the dictionary doesn't need to be rectangular or to be a <a href="#">DNAStrngSet</a> object: it can be any type of <a href="#">XStringSet</a> object and have a variable width.</p>
subject	<p>An <a href="#">XString</a> or <a href="#">MaskedXString</a> object containing the subject sequence for <a href="#">matchPDict</a>, <a href="#">countPDict</a> and <a href="#">whichPDict</a>.</p> <p>An <a href="#">XStringSet</a> object containing the subject sequences for <a href="#">vcountPDict</a> and <a href="#">vwhichPDict</a>.</p> <p>For now, only subjects of base class <a href="#">DNAStrng</a> are supported.</p>
max.mismatch, min.mismatch	<p>The maximum and minimum number of mismatching letters allowed (see <a href="#">?isMatchingAt</a> for the details). This man page focuses on exact matching of a constant width dictionary so <code>max.mismatch=0</code> in the examples below. See <a href="#">?matchPDict-inexact</a> for inexact matching.</p>
with.indels	<p>Only supported by <a href="#">countPDict</a>, <a href="#">whichPDict</a>, <a href="#">vcountPDict</a> and <a href="#">vwhichPDict</a> at the moment, and only when the input dictionary is non-preprocessed (i.e. <a href="#">XStringSet</a>).</p> <p>If TRUE then indels are allowed. In that case, <code>min.mismatch</code> must be 0 and <code>max.mismatch</code> is interpreted as the maximum "edit distance" allowed between any pattern and any of its matches. See <a href="#">?matchPattern</a> for more information.</p>
fixed	<p>Whether IUPAC ambiguity codes should be interpreted literally or not (see <a href="#">?isMatchingAt</a> for more information). This man page focuses on exact matching of a constant width dictionary so <code>fixed=TRUE</code> in the examples below. See <a href="#">?matchPDict-inexact</a> for inexact matching.</p>
algorithm	<p>Ignored if pdict is a preprocessed dictionary (i.e. a <a href="#">PDict</a> object). Otherwise, can be one of the following: "auto", "naive-exact", "naive-inexact", "boyer-moore" or "shift-or". See <a href="#">?matchPattern</a> for more information. Note that "indels" is not supported for now.</p>
verbose	TRUE or FALSE.
collapse, weight	<p><code>collapse</code> must be FALSE, 1, or 2.</p> <p>If <code>collapse=FALSE</code> (the default), then <code>weight</code> is ignored and <a href="#">vcountPDict</a> returns the full matrix of counts (M0). If <code>collapse=1</code>, then M0 is collapsed "horizontally" i.e. it is turned into a vector with length equal to <code>length(pdicit)</code>. If <code>weight=1L</code> (the default), then this vector is defined by <code>rowSums(M0)</code>. If <code>collapse=2</code>, then M0 is collapsed "vertically" i.e. it is turned into a vector with length equal to <code>length(subject)</code>. If <code>weight=1L</code> (the default), then this vector is defined by <code>colSums(M0)</code>.</p>

If collapse=1 or collapse=2, then the elements in subject (collapse=1) or in pdict (collapse=2) can be weighted thru the weight argument. In that case, the returned vector is defined by `M0 %% rep(weight, length.out=length(subject))` and `rep(weight, length.out=length(pdict)) %% M0`, respectively.

... Additional arguments for methods.

## Details

In this man page, we assume that you know how to preprocess a dictionary of DNA patterns that can then be used with any of the \*PDict functions described here. Please see ?PDict if you don't.

When using the \*PDict functions for exact matching of a constant width dictionary, the standard way to preprocess the original dictionary is by calling the PDict constructor on it with no extra arguments. This returns the preprocessed dictionary in a PDict object that can be used with any of the \*PDict functions.

## Value

If M denotes the number of patterns in the pdict argument (`M <- length(pdict)`), then matchPDict returns an MIndex object of length M, and countPDict an integer vector of length M.

whichPDict returns an integer vector made of the indices of the patterns in the pdict argument that have at least one match.

If N denotes the number of sequences in the subject argument (`N <- length(subject)`), then vcountPDict returns an integer matrix with M rows and N columns, unless the collapse argument is used. In that case, depending on the type of weight, an integer or numeric vector is returned (see above for the details).

vwhichPDict returns a list of N integer vectors.

## Author(s)

H. Pages

## References

Aho, Alfred V.; Margaret J. Corasick (June 1975). "Efficient string matching: An aid to bibliographic search". Communications of the ACM 18 (6): 333-340.

## See Also

[PDict-class](#), [MIndex-class](#), [matchPDict-inexact](#), [isMatchingAt](#), [coverage](#), [MIndex-method](#), [matchPattern](#), [alphabetFrequency](#), [DNAStringSet-class](#), [XStringViews-class](#), [MaskedDNAString-class](#)

## Examples

```
## -----
## A. A SIMPLE EXAMPLE OF EXACT MATCHING
## -----

## Creating the pattern dictionary:
library(drosophila2probe)
```

```

dict0 <- DNAStrngSet(drosophila2probe)
dict0                                     # The original dictionary.
length(dict0)                             # Hundreds of thousands of patterns.
pdict0 <- PDict(dict0)                    # Store the original dictionary in
                                           # a PDict object (preprocessing).

## Using the pattern dictionary on chromosome 3R:
library(BSgenome.Dmelanogaster.UCSC.dm3)
chr3R <- Dmelanogaster$chr3R              # Load chromosome 3R
chr3R
mi0 <- matchPDict(pdict0, chr3R)          # Search...

## Looking at the matches:
start_index <- startIndex(mi0)            # Get the start index.
length(start_index)                       # Same as the original dictionary.
start_index[[8220]]                       # Starts of the 8220th pattern.
end_index <- endIndex(mi0)                # Get the end index.
end_index[[8220]]                         # Ends of the 8220th pattern.
count_index <- countIndex(mi0)           # Get the number of matches per pattern.
count_index[[8220]]
mi0[[8220]]                               # Get the matches for the 8220th pattern.
start(mi0[[8220]])                       # Equivalent to startIndex(mi0)[[8220]].
sum(count_index)                          # Total number of matches.
table(count_index)
i0 <- which(count_index == max(count_index))
pdict0[[i0]]                              # The pattern with most occurrences.
mi0[[i0]]                                  # Its matches as an IRanges object.
Views(chr3R, mi0[[i0]])                   # And as an XStringViews object.

## Get the coverage of the original subject:
cov3R <- as.integer(coverage(mi0, width=length(chr3R)))
max(cov3R)
mean(cov3R)
sum(cov3R != 0) / length(cov3R)           # Only 2.44% of chr3R is covered.
if (interactive()) {
  plotCoverage <- function(cx, start, end)
  {
    plot.new()
    plot.window(c(start, end), c(0, 20))
    axis(1)
    axis(2)
    axis(4)
    lines(start:end, cx[start:end], type="l")
  }
  plotCoverage(cov3R, 27600000, 27900000)
}

## -----
## B. NAMING THE PATTERNS
## -----

## The names of the original patterns, if any, are propagated to the
## PDict and MIndex objects:

```

```

names(dict0) <- mkAllStrings(letters, 4)[seq_len(length(dict0))]
dict0
dict0[["abcd"]]
pdict0n <- PDict(dict0)
names(pdict0n)[1:30]
pdict0n[["abcd"]]
mi0n <- matchPDict(pdict0n, chr3R)
names(mi0n)[1:30]
mi0n[["abcd"]]

## This is particularly useful when unlisting an MIndex object:
unlist(mi0)[1:10]
unlist(mi0n)[1:10] # keep track of where the matches are coming from

## -----
## C. PERFORMANCE
## -----

## If getting the number of matches is what matters only (without
## regarding their positions), then countPDict() will be faster,
## especially when there is a high number of matches:

count_index0 <- countPDict(pdict0, chr3R)
stopifnot(identical(count_index0, count_index))

if (interactive()) {
  ## Whats the impact of the dictionary width on performance?
  ## Below is some code that can be used to figure out (will take a long
  ## time to run). For different widths of the original dictionary, we
  ## look at:
  ##   o pptime: preprocessing time (in sec.) i.e. time needed for
  ##             building the PDict object from the truncated input
  ##             sequences;
  ##   o nnodes: nb of nodes in the resulting Aho-Corasick tree;
  ##   o nupatt: nb of unique truncated input sequences;
  ##   o matchtime: time (in sec.) needed to find all the matches;
  ##   o totalcount: total number of matches.
  getPDictStats <- function(dict, subject)
  {
    ans_width <- width(dict[1])
    ans_pptime <- system.time(pdict <- PDict(dict))["elapsed"]
    pptb <- pdict@threeparts@pptb
    ans_nnodes <- nnodes(pptb)
    ans_nupatt <- sum(!duplicated(pdict))
    ans_matchtime <- system.time(
      mi0 <- matchPDict(pdict, subject)
    )["elapsed"]
    ans_totalcount <- sum(countIndex(mi0))
    list(
      width=ans_width,
      pptime=ans_pptime,
      nnodes=ans_nnodes,
      nupatt=ans_nupatt,

```

```

        matchtime=ans_matchtime,
        totalcount=ans_totalcount
    )
}
stats <- lapply(8:25,
               function(width)
                 getPDictStats(DNAStringSet(dict0, end=width), chr3R))
stats <- data.frame(do.call(rbind, stats))
stats
}

## -----
## D. USING A NON-PREPROCESSED DICTIONARY
## -----

dict3 <- DNAStringSet(mkAllStrings(DNA_BASES, 3)) # all trinucleotides
dict3
pdict3 <- PDict(dict3)

## The 3 following calls are equivalent (from faster to slower):
res3a <- countPDict(pdict3, chr3R)
res3b <- countPDict(dict3, chr3R)
res3c <- sapply(dict3,
                function(pattern) countPattern(pattern, chr3R))
stopifnot(identical(res3a, res3b))
stopifnot(identical(res3a, res3c))

## One reason for using a non-preprocessed dictionary is to get rid of
## all the constraints associated with preprocessing, e.g., when
## preprocessing with \link{PDict}, the input dictionary must
## be DNA and a Trusted Band must be defined (explicitly or implicitly).
## See ?\link{PDict} for more information about these constraints.
## In particular, using a non-preprocessed dictionary can be
## useful for the kind of inexact matching that cant be achieved
## with a \link{PDict} object (if performance is not an issue).
## See ?\link{matchPDict-inexact} for more information about
## inexact matching.

dictD <- xscat(dict3, "N", reverseComplement(dict3))

## The 2 following calls are equivalent (from faster to slower):
resDa <- matchPDict(dictD, chr3R, fixed=FALSE)
resDb <- sapply(dictD,
               function(pattern)
                 matchPattern(pattern, chr3R, fixed=FALSE))
stopifnot(all(sapply(seq_len(length(dictD)),
                    function(i)
                      identical(resDa[[i]], as(resDb[[i]], "IRanges")))))

## -----
## E. vcountPDict()
## -----
subject <- Dmelanogaster$upstream1000[1:100]

```

```

subject
mat1 <- vcountPDict(pdickt0, subject)
dim(mat1) # length(pdickt0) x length(subject)
nhit_per_probe <- rowSums(mat1)
table(nhit_per_probe)

## Without vcountPDict(), mat1 could have been computed with:
mat2 <- sapply(unname(subject), function(x) countPDict(pdickt0, x))
stopifnot(identical(mat1, mat2))
## but using vcountPDict() is faster (10x or more, depending of the
## average length of the sequences in subject).

if (interactive()) {
  ## This will fail (with message "allocMatrix: too many elements
  ## specified") because, on most platforms, vectors and matrices in R
  ## are limited to 2^31 elements:
  subject <- Dmelanogaster$upstream1000
  vcountPDict(pdickt0, subject)
  length(pdickt0) * length(Dmelanogaster$upstream1000)
  1 * length(pdickt0) * length(Dmelanogaster$upstream1000) # > 2^31
  ## But this will work:
  nhit_per_seq <- vcountPDict(pdickt0, subject, collapse=2)
  sum(nhit_per_seq >= 1) # nb of subject sequences with at least 1 hit
  table(nhit_per_seq)
  which(nhit_per_seq == 37) # 603
  sum(countPDict(pdickt0, subject[[603]])) # 37
}

## -----
## F. RELATIONSHIP BETWEEN vcountPDict(), countPDict() AND
## vcountPattern()
## -----
pdickt3 <- PDict(dict3)
subject <- Dmelanogaster$upstream1000
subject

## The 4 following calls are equivalent (from faster to slower):
mat3a <- vcountPDict(pdickt3, subject)
mat3b <- vcountPDict(dict3, subject)
mat3c <- sapply(dict3,
                function(pattern) vcountPattern(pattern, subject))
mat3d <- sapply(unname(subject),
                function(x) countPDict(pdickt3, x))
stopifnot(identical(mat3a, mat3b))
stopifnot(identical(mat3a, t(mat3c)))
stopifnot(identical(mat3a, mat3d))

## The 3 following calls are equivalent (from faster to slower):
nhitpp3a <- vcountPDict(pdickt3, subject, collapse=1) # rowSums(mat3a)
nhitpp3b <- vcountPDict(dict3, subject, collapse=1)
nhitpp3c <- sapply(dict3,
                  function(pattern) sum(vcountPattern(pattern, subject)))
stopifnot(identical(nhitpp3a, nhitpp3b))

```

```

stopifnot(identical(nhitpp3a, nhitpp3c))

## The 3 following calls are equivalent (from faster to slower):
nhitps3a <- vcountPDict(pdct3, subject, collapse=2) # colSums(mat3a)
nhitps3b <- vcountPDict(dict3, subject, collapse=2)
nhitps3c <- sapply(unname(subject),
                  function(x) sum(countPDict(pdct3, x)))
stopifnot(identical(nhitps3a, nhitps3b))
stopifnot(identical(nhitps3a, nhitps3c))

## -----
## G. vwhichPDict()
## -----
## The 4 following calls are equivalent (from faster to slower):
vwp3a <- vwhichPDict(pdct3, subject)
vwp3b <- vwhichPDict(dict3, subject)
vwp3c <- lapply(seq_len(ncol(mat3a)), function(j) which(mat3a[, j] != 0L))
vwp3d <- lapply(unname(subject), function(x) whichPDict(pdct3, x))
stopifnot(identical(vwp3a, vwp3b))
stopifnot(identical(vwp3a, vwp3c))
stopifnot(identical(vwp3a, vwp3d))

table(sapply(vwp3a, length))
which.min(sapply(vwp3a, length))
## Get the trinucleotides not represented in reference sequence 9181:
dict3[-vwp3a[[9181]]] # 21 trinucleotides

## -----
## H. MAPPING PROBE SET IDS BETWEEN CHIPS WITH vwhichPDict()
## -----
## Here we show a simple (and very naive) algorithm for mapping probe
## set IDs between the hgu95av2 and hgu133a chips (Affymetrix).
## 2 probe set IDs are considered mapped iff they share at least one
## probe.
## WARNING: This example takes about 25 minutes to run.
if (interactive()) {

  library(hgu95av2probe)
  library(hgu133aprobe)
  probes1 <- DNASTringSet(hgu95av2probe)
  probes2 <- DNASTringSet(hgu133aprobe)
  pdict2 <- PDict(probes2)

  ## Get the mapping from probes1 to probes2 (based on exact matching):
  map1to2 <- vwhichPDict(pdict2, probes1) # takes about 10 minutes

  ## The following helper function uses the probe level mapping to induce
  ## the mapping at the probe set IDs level (from hgu95av2 to hgu133a).
  ## To keep things simple, 2 probe set IDs are considered mapped iff
  ## each of them contains at least one probe mapped to one probe of
  ## the other:
  mapProbeSetIDs1to2 <- function(psID)
    unique(hgu133aprobe$Probe.Set.Name[unlist(

```

```

    map1to2[hgu95av2probe$Probe.Set.Name == psID]
  ]])

## Use the helper function to build the complete mapping:
psIDs1 <- unique(hgu95av2probe$Probe.Set.Name)
mapPSIDs1to2 <- lapply(psIDs1, mapProbeSetIDs1to2) # about 3 min.
names(mapPSIDs1to2) <- psIDs1

## Do some basic stats:
table(sapply(mapPSIDs1to2, length))

## [ADVANCED USERS ONLY]
## An alternative that is slightly faster is to put all the probes
## (hgu95av2 + hgu133a) in a single PDict object and then query its
## dups0 slot directly. This slot is a Dups object containing the
## mapping between duplicated patterns.
## Note that we can do this only because all the probes have the
## same length (25) and because we are doing exact matching:

probes12 <- DNASTringSet(c(hgu95av2probe$sequence, hgu133aprobe$sequence))
pdict12 <- PDict(probes12)
dups0 <- pdict12@dups0

mapProbeSetIDs1to2alt <- function(psID)
{
  ii1 <- unique(togroup(dups0, which(hgu95av2probe$Probe.Set.Name == psID)))
  ii2 <- members(dups0, ii1) - length(probes1)
  ii2 <- ii2[ii2 >= 1L]
  unique(hgu133aprobe$Probe.Set.Name[ii2])
}

mapPSIDs1to2alt <- lapply(psIDs1, mapProbeSetIDs1to2alt) # about 10 min.
names(mapPSIDs1to2alt) <- psIDs1

## mapPSIDs1to2alt and mapPSIDs1to2 contain the same mapping:
stopifnot(identical(lapply(mapPSIDs1to2alt, sort),
                       lapply(mapPSIDs1to2, sort)))
}

```

---

matchPDict-inexact      *Inexact matching with matchPDict()/countPDict()/whichPDict()*

---

## Description

The matchPDict, countPDict and whichPDict functions efficiently find the occurrences in a text (the subject) of all patterns stored in a preprocessed dictionary.

This man page shows how to use these functions for inexact (or fuzzy) matching or when the original dictionary has a variable width.

See [?matchPDict](#) for how to use these functions for exact matching of a constant width dictionary i.e. a dictionary where all the patterns have the same length (same number of nucleotides).



## Details

In this man page, we assume that you know how to preprocess a dictionary of DNA patterns that can then be used with `matchPDict`, `countPDict` or `whichPDict`. Please see `?PDict` if you don't.

`matchPDict` and family support different kinds of inexact matching but with some restrictions. Inexact matching is controlled via the definition of a Trusted Band during the preprocessing step and/or via the `max.mismatch`, `min.mismatch` and `fixed` arguments. Defining a Trusted Band is also required when the original dictionary is not rectangular (variable width), even for exact matching. See `?PDict` for how to define a Trusted Band.

Here is how `matchPDict` and family handle the Trusted Band defined on `pdict`:

- (1) Find all the exact matches of all the elements in the Trusted Band.
- (2) For each element in the Trusted Band that has at least one exact match, compare the head and the tail of this element with the flanking sequences of the matches found in (1).

Note that the number of exact matches found in (1) will decrease exponentially with the width of the Trusted Band. Here is a simple guideline in order to get reasonably good performance: if `TBW` is the width of the Trusted Band (`TBW <- tb.width(pdickt)`) and `L` the number of letters in the subject (`L <- nchar(subject)`), then  $L / (4^{TBW})$  should be kept as small as possible, typically  $< 10$  or  $20$ .

In addition, when a Trusted Band has been defined during preprocessing, then `matchPDict` and family can be called with `fixed=FALSE`. In this case, IUPAC ambiguity codes in the head or the tail of the `PDict` object are treated as ambiguities.

Finally, `fixed="pattern"` can be used to indicate that IUPAC ambiguity codes in the subject should be treated as ambiguities. It only works if the density of codes is not too high. It works whether or not a Trusted Band has been defined on `pdickt`.

## Author(s)

H. Pages

## References

Aho, Alfred V.; Margaret J. Corasick (June 1975). "Efficient string matching: An aid to bibliographic search". *Communications of the ACM* 18 (6): 333-340.

## See Also

[PDict-class](#), [MIndex-class](#), [matchPDict](#)

## Examples

```
## -----
## A. USING AN EXPLICIT TRUSTED BAND
## -----

library(drosophila2probe)
dict0 <- DNAStrngSet(drosophila2probe)
dict0 # the original dictionary
```

```

## Preprocess the original dictionary by defining a Trusted Band that
## spans nucleotides 1 to 9 of each pattern.
pdict9 <- PDict(dict0, tb.end=9)
pdict9
tail(pdict9)
sum(duplicated(pdict9))
table(patternFrequency(pdict9))

library(BSgenome.Dmelanogaster.UCSC.dm3)
chr3R <- Dmelanogaster$chr3R
chr3R
table(countPDict(pdict9, chr3R, max.mismatch=1))
table(countPDict(pdict9, chr3R, max.mismatch=3))
table(countPDict(pdict9, chr3R, max.mismatch=5))

## -----
## B. COMPARISON WITH EXACT MATCHING
## -----

## When the original dictionary is of constant width, exact matching
## (i.e. max.mismatch=0 and fixed=TRUE) will be more efficient with
## a full-width Trusted Band (i.e. a Trusted Band that covers the entire
## dictionary) than with a Trusted Band of width < width(dict0).
pdict0 <- PDict(dict0)
count0 <- countPDict(pdict0, chr3R)
count0b <- countPDict(pdict9, chr3R, max.mismatch=0)
identical(count0b, count0) # TRUE

## -----
## C. USING AN EXPLICIT TRUSTED BAND ON A VARIABLE WIDTH DICTIONARY
## -----

## Here is a small variable width dictionary that contains IUPAC
## ambiguities (pattern 1 and 3 contain an N):
dict0 <- DNAStrngSet(c("TACCNG", "TAGT", "CGGNT", "AGTAG", "TAGT"))
## (Note that pattern 2 and 5 are identical.)

## If we only want to do exact matching, then it is recommended to use
## the widest possible Trusted Band i.e. to set its width to
## min(width(dict0)) because this is what will give the best
## performance. However, when dict0 contains IUPAC ambiguities (like
## in our case), it could be that one of them is falling into the
## Trusted Band so we get an error (only base letters can go in the
## Trusted Band for now):
## Not run:
  PDict(dict0, tb.end=min(width(dict0))) # Error!

## End(Not run)

## In our case, the Trusted Band cannot be wider than 3:
pdict <- PDict(dict0, tb.end=3)
tail(pdict)

```

```

subject <- DNASTring("TAGTACCAGTTTCGGG")

m <- matchPDict(pdict, subject)
countIndex(m) # pattern 2 and 5 have 1 exact match
m[[2]]

## We can take advantage of the fact that our Trusted Band doesnt cover
## the entire dictionary to allow inexact matching on the uncovered parts
## (the tail in our case):

m <- matchPDict(pdict, subject, fixed=FALSE)
countIndex(m) # now pattern 1 has 1 match too
m[[1]]

m <- matchPDict(pdict, subject, max.mismatch=1)
countIndex(m) # now pattern 4 has 1 match too
m[[4]]

m <- matchPDict(pdict, subject, max.mismatch=1, fixed=FALSE)
countIndex(m) # now pattern 3 has 1 match too
m[[3]] # note that this match is "out of limit"
Views(subject, m[[3]])

m <- matchPDict(pdict, subject, max.mismatch=2)
countIndex(m) # pattern 4 gets 1 additional match
m[[4]]

## Unlist all matches:
unlist(m)

## -----
## D. WITH IUPAC AMBIGUITY CODES IN THE SUBJECT
## -----
pdict <- PDict(c("ACAC", "TCCG"))
as.list(matchPDict(pdict, DNASTring("ACNCCGT")))
as.list(matchPDict(pdict, DNASTring("ACNCCGT"), fixed="pattern"))
as.list(matchPDict(pdict, DNASTring("ACWCCGT"), fixed="pattern"))
as.list(matchPDict(pdict, DNASTring("ACRCCGT"), fixed="pattern"))
as.list(matchPDict(pdict, DNASTring("ACKCCGT"), fixed="pattern"))

dict <- DNASTringSet(c("TTC", "CTT"))
pdict <- PDict(dict)
subject <- DNASTring("CYTCACTTC")
mi1 <- matchPDict(pdict, subject, fixed="pattern")
mi2 <- matchPDict(dict, subject, fixed="pattern")
stopifnot(identical(as.list(mi1), as.list(mi2)))

```

## Description

In the context of a computer-simulated PCR experiment, one wants to find the amplicons mapped to a given primer pair. The `matchProbePair` function can be used for this: given a forward and a reverse probe (i.e. the chromosome-specific sequences of the forward and reverse primers used for the experiment) and a target sequence (generally a chromosome sequence), the `matchProbePair` function will return all the "theoretical amplicons" mapped to this probe pair.

## Usage

```
matchProbePair(Fprobe, Rprobe, subject, algorithm="auto", logfile=NULL, verbose=FALSE)
```

## Arguments

<code>Fprobe</code>	The forward probe.
<code>Rprobe</code>	The reverse probe.
<code>subject</code>	A <a href="#">DNAStrng</a> object (or an <a href="#">XStringViews</a> object with a <a href="#">DNAStrng</a> subject) containing the target sequence.
<code>algorithm</code>	One of the following: "auto", "naive-exact", "naive-inexact", "boyer-moore" or "shift-or". See <a href="#">matchPattern</a> for more information.
<code>logfile</code>	A file used for logging.
<code>verbose</code>	TRUE or FALSE.

## Details

The `matchProbePair` function does the following: (1) find all the "plus hits" i.e. the `Fprobe` and `Rprobe` matches on the "plus" strand, (2) find all the "minus hits" i.e. the `Fprobe` and `Rprobe` matches on the "minus" strand and (3) from the set of all (plus\\_hit, minus\\_hit) pairs, extract and return the subset of "reduced matches" i.e. the (plus\\_hit, minus\\_hit) pairs such that (a) plus\\_hit <= minus\\_hit and (b) there are no hits (plus or minus) between plus\\_hit and minus\\_hit. This set of "reduced matches" is the set of "theoretical amplicons".

## Value

An [XStringViews](#) object containing the set of "theoretical amplicons".

## Author(s)

H. Pages

## See Also

[matchPattern](#), [matchLRPatterns](#), [findPalindromes](#), [reverseComplement](#), [XStringViews-class](#)

**Examples**

```

library(BSgenome.Dmelanogaster.UCSC.dm3)
subject <- Dmelanogaster$chr3R

## With 20-nucleotide forward and reverse probes:
Fprobe <- "AGCTCCGAGTTCCTGCAATA"
Rprobe <- "CGTTGTTTCAAATATGCGG"
matchProbePair(Fprobe, Rprobe, subject) # 1 "theoretical amplicon"

## With shorter forward and reverse probes, the risk of having multiple
## "theoretical amplicons" increases:
Fprobe <- "AGCTCCGAGTTC"
Rprobe <- "CGTTGTTTCAA"
matchProbePair(Fprobe, Rprobe, subject) # 2 "theoretical amplicons"
Fprobe <- "AGCTCCGAGTT"
Rprobe <- "CGTTGTTTACA"
matchProbePair(Fprobe, Rprobe, subject) # 9 "theoretical amplicons"

```

---

matchprobes	<i>A function to match a query sequence to the sequences of a set of probes.</i>
-------------	--

---

**Description**

The query sequence, a character string (probably representing a transcript of interest), is scanned for the presence of exact matches to the sequences in the character vector records. The indices of the set of matches are returned.

The function is inefficient: it works on R's character vectors, and the actual matching algorithm is of time complexity  $\text{length}(\text{query}) \times \text{length}(\text{records})!$

See [matchPattern](#), [vmatchPattern](#) and [matchPDict](#) for more efficient sequence matching functions.

**Usage**

```
matchprobes(query, records, probepos=FALSE)
```

**Arguments**

query	A character vector. For example, each element may represent a gene (transcript) of interest. See Details.
records	A character vector. For example, each element may represent the probes on a DNA array.
probepos	A logical value. If TRUE, return also the start positions of the matches in the query sequence.

**Details**

`toupper` is applied to the arguments `query` and `records` before matching. The intention of this is to make the matching case-insensitive. The function is embarrassingly naive. The matching is done using the C library function `strstr`.

**Value**

A list. Its first element is a list of the same length as the input vector. Each element of the list is a numeric vector containing the indices of the probes that have a perfect match in the query sequence.

If `probepos` is `TRUE`, the returned list has a second element: it is of the same shape as described above, and gives the respective positions of the matches.

**Author(s)**

R. Gentleman, Laurent Gautier, Wolfgang Huber

**See Also**

[matchPattern](#), [vmatchPattern](#), [matchPDict](#)

**Examples**

```
if(require("hgu95av2probe")){
  data("hgu95av2probe")
  seq <- hgu95av2probe$sequence[1:20]
  target <- paste(seq, collapse="")
  matchprobes(target, seq, probepos=TRUE)
}
```

---

matchPWM

*PWM creating, matching, and related utilities*

---

**Description**

Position Weight Matrix (PWM) creating, matching, and related utilities for DNA data. (PWM for amino acid sequences are not supported.)

**Usage**

```
PWM(x, type = c("log2probratio", "prob"),
     prior.params = c(A=0.25, C=0.25, G=0.25, T=0.25))

matchPWM(pwm, subject, min.score="80%", with.score=FALSE, ...)
countPWM(pwm, subject, min.score="80%", ...)
PWMscoreStartingAt(pwm, subject, starting.at=1)

## Utility functions for basic manipulation of the Position Weight Matrix
```

```

maxWeights(x)
minWeights(x)
maxScore(x)
minScore(x)
unitScale(x)
## S4 method for signature matrix
reverseComplement(x, ...)

```

## Arguments

x	For PWM: a rectangular character vector or rectangular DNASTringSet object ("rectangular" means that all elements have the same number of characters) with no IUPAC ambiguity letters, or a Position Frequency Matrix represented as an integer matrix with row names containing at least A, C, G and T (typically the result of a call to <a href="#">consensusMatrix</a> ). For maxWeights, minWeights, maxScore, minScore, unitScale and reverseComplement: a Position Weight Matrix represented as a numeric matrix with row names A, C, G and T.
type	The type of Position Weight Matrix, either "log2probratio" or "prob". See Details section for more information.
prior.params	A positive numeric vector, which represents the parameters of the Dirichlet conjugate prior, with names A, C, G, and T. See Details section for more information.
pwm	A Position Weight Matrix represented as a numeric matrix with row names A, C, G and T.
subject	Typically a DNASTring object. A Views object on a DNASTring subject, a MaskedDNASTring object, or a single character string, are also supported. IUPAC ambiguity letters in subject are ignored (i.e. assigned weight 0) with a warning.
min.score	The minimum score for counting a match. Can be given as a character string containing a percentage (e.g. "85%") of the highest possible score or as a single number.
with.score	TRUE or FALSE. If TRUE, then the score of each hit is included in the returned object in a metadata column named score. Say the returned object is hits, this metadata column can then be accessed with mcols(hits)\$score.
starting.at	An integer vector specifying the starting positions of the Position Weight Matrix relatively to the subject.
...	Additional arguments for methods.

## Details

The PWM function uses a multinomial model with a Dirichlet conjugate prior to calculate the estimated probability of base *b* at position *i*. As mentioned in the Arguments section, `prior.params` supplies the parameters for the DNA bases A, C, G, and T in the Dirichlet prior. These values result in a position independent initial estimate of the probabilities for the bases to be  $\text{priorProbs} = \text{prior.params} / \text{sum}(\text{prior.params})$  and the posterior (data infused) estimate for the probabilities for the bases in each of the positions to

be `postProbs = (consensusMatrix(x) + prior.params)/(length(x) + sum(prior.params))`.  
 When `type = "log2probratio"`, the `PWM = unitScale(log2(postProbs/priorProbs))`. When  
`type = "prob"`, the `PWM = unitScale(postProbs)`.

### Value

A numeric matrix representing the Position Weight Matrix for PWM.

A numeric vector containing the Position Weight Matrix-based scores for `PWMScoreStartingAt`.

An [XStringViews](#) object for `matchPWM`.

A single integer for `countPWM`.

A vector containing the max weight for each position in `pwm` for `maxWeights`.

A vector containing the min weight for each position in `pwm` for `minWeights`.

The highest possible score for a given Position Weight Matrix for `maxScore`.

The lowest possible score for a given Position Weight Matrix for `minScore`.

The modified numeric matrix given by `(x - minScore(x)/ncol(x))/(maxScore(x) - minScore(x))`  
 for `unitScale`.

A PWM obtained by reverting the column order in PWM `x` and by reassigning each row to its  
 complementary nucleotide for `reverseComplement`.

### Author(s)

H. Pages and P. Aboyoun

### References

Wasserman, WW, Sandelin, A., (2004) Applied bioinformatics for the identification of regulatory  
 elements, *Nat Rev Genet.*, 5(4):276-87.

### See Also

[consensusMatrix](#), [matchPattern](#), [reverseComplement](#), [DNAString-class](#), [XStringViews-class](#)

### Examples

```
## Data setup:
data(HNF4alpha)
library(BSgenome.Dmelanogaster.UCSC.dm3)
chr3R <- Dmelanogaster$chr3R
chr3R

## Create a PWM from a PFM or directly from a rectangular
## DNAStringSet object:
pfm <- consensusMatrix(HNF4alpha)
pwm <- PWM(pfm) # same as PWM(HNF4alpha)

## Perform some general routines on the PWM:
round(pwm, 2)
maxWeights(pwm)
```



```

maxScore(pwm)
reverseComplement(pwm)

## Score the first 5 positions:
PWMscoreStartingAt(pwm, unmasked(chr3R), starting.at=1:5)

## Match the plus strand:
hits <- matchPWM(pwm, chr3R)
nhit <- countPWM(pwm, chr3R) # same as length(hits)

## Use with.score=TRUE to get the scores of the hits:
hits <- matchPWM(pwm, chr3R, with.score=TRUE)
head(mcols(hits)$score)
min(mcols(hits)$score / maxScore(pwm)) # should be >= 0.8

## The scores can also easily be post-calculated:
scores <- PWMscoreStartingAt(pwm, subject(hits), start(hits))

## Match the minus strand:
matchPWM(reverseComplement(pwm), chr3R)

```

---

MIndex-class

*MIndex objects*


---

## Description

The MIndex class is the basic container for storing the matches of a set of patterns in a subject sequence.

## Details

An MIndex object contains the matches (start/end locations) of a set of patterns found in an [XString](#) object called "the subject string" or "the subject sequence" or simply "the subject".

[matchPDict](#) function returns an MIndex object.

## Accessor methods

In the code snippets below, *x* is an MIndex object.

`length(x)`: The number of patterns that matches are stored for.

`names(x)`: The names of the patterns that matches are stored for.

`startIndex(x)`: A list containing the starting positions of the matches for each pattern.

`endIndex(x)`: A list containing the ending positions of the matches for each pattern.

`countIndex(x)`: An integer vector containing the number of matches for each pattern. Equivalent to `elementLengths(x)`.

**Subsetting methods**

In the code snippets below, `x` is an `MIndex` object.

`x[[i]]`: Extract the matches for the `i`-th pattern as an `IRanges` object.

**Coercion**

In the code snippets below, `x` is an `MIndex` object.

`as(x, "CompressedIRangesList")`: Turns `x` into an `CompressedIRangesList` object. This coercion changes `x` from one `RangesList` subtype to another with the underlying `Ranges` values remaining unchanged.

**Other utility methods and functions**

In the code snippets below, `x` and `mindex` are `MIndex` objects and `subject` is the `XString` object containing the sequence in which the matches were found.

`unlist(x, recursive=TRUE, use.names=TRUE)`: Return all the matches in a single `IRanges` object. `recursive` and `use.names` are ignored.

`extractAllMatches(subject, mindex)`: Return all the matches in a single `XStringViews` object.

**Author(s)**

H. Pages

**See Also**

[matchPDict](#), [PDict-class](#), [IRanges-class](#), [XStringViews-class](#)

**Examples**

```
## See ?matchPDict and ?matchPDict-inexact for some examples.
```

---

misc

*Some miscellaneous stuff*

---

**Description**

Some miscellaneous stuff.

**Usage**

```
N50(csizes)
```

**Arguments**

`csizes`            A vector containing the contig sizes.

**Value**

N50: The N50 value as an integer.

**The N50 contig size**

**Definition** The N50 contig size of an assembly (aka the N50 value) is the size of the largest contig such that the contigs larger than that have at least 50% the bases of the assembly.

**How is it calculated?** It is calculated by adding the sizes of the biggest contigs until you reach half the total size of the contigs. The N50 value is then the size of the contig that was added last (i.e. the smallest of the big contigs covering 50% of the genome).

**What for?** The N50 value is a standard measure of the quality of a de novo assembly.

**Author(s)**

Nicolas Delhomme <delhomme@embl.de>

**See Also**

[XStringSet-class](#)

**Examples**

```
# Generate 10 random contigs of sizes comprised between 100 and 10000:
my.contig <- DNASTringSet(
  sapply(
    sample(c(100:10000), 10),
    function(size)
      paste(sample(DNA_BASES, size, replace=TRUE), collapse="")
    )
)

# Get their sizes:
my.size <- width(my.contig)

# Calculate the N50 value of this set of contigs:
my.contig.N50 <- N50(my.size)
```

---

MultipleAlignment-class

*MultipleAlignment objects*

---

**Description**

The MultipleAlignment class is a container for storing multiple sequence alignments.

**Usage**

```
## Constructors:
DNAMultipleAlignment(x=character(), start=NA, end=NA, width=NA,
  use.names=TRUE, rowmask=NULL, colmask=NULL)
RNAMultipleAlignment(x=character(), start=NA, end=NA, width=NA,
  use.names=TRUE, rowmask=NULL, colmask=NULL)
AAMultipleAlignment(x=character(), start=NA, end=NA, width=NA,
  use.names=TRUE, rowmask=NULL, colmask=NULL)

## Read functions:
readDNAMultipleAlignment(filepath, format)
readRNAMultipleAlignment(filepath, format)
readAAMultipleAlignment(filepath, format)

## Write funtions:
write.phylip(x, filepath)

## ... and more (see below)
```

**Arguments**

x	Either a character vector (with no NAs), or an <a href="#">XString</a> , <a href="#">XStringSet</a> or <a href="#">XStringViews</a> object containing strings with the same number of characters. If writing out a Phylip file, then x would be a <a href="#">MultipleAlignment</a> object
start,end,width	Either NA, a single integer, or an integer vector of the same length as x specifying how x should be "narrowed" (see <a href="#">?narrow</a> in the <b>IRanges</b> package for the details).
use.names	TRUE or FALSE. Should names be preserved?
filepath	A character vector (of arbitrary length when reading, of length 1 when writing) containing the paths to the files to read or write. Note that special values like "" or " cmd" (typically supported by other I/O functions in R) are not supported here. Also filepath cannot be a connection.
format	Either "fasta" (the default), stockholm, or "clustal".
rowmask	a <a href="#">NormalIRanges</a> object that will set masking for rows
colmask	a <a href="#">NormalIRanges</a> object that will set masking for columns

**Details**

The `MultipleAlignment` class is designed to hold and represent multiple sequence alignments. The rows and columns within an alignment can be masked for ad hoc analyses.

**Accessor methods**

In the code snippets below, x is a `MultipleAlignment` object.

`unmasked(x)`: The underlying [XStringSet](#) object containing the multiple sequence alignment.

`rownames(x)`: NULL or a character vector of the same length as `x` containing a short user-provided description or comment for each sequence in `x`.

`rowmask(x)`, `rowmask(x, append, invert) <- value`: Gets and sets the [NormalIRanges](#) object representing the masked rows in `x`. The `append` argument takes `union`, `replace` or `intersect` to indicate how to combine the new value with `rowmask(x)`. The `invert` argument takes a logical argument to indicate whether or not to invert the new mask. The `value` argument can be of any class that is coercible to a [NormalIRanges](#) via the `as` function.

`colmask(x)`, `colmask(x, append, invert) <- value`: Gets and sets the [NormalIRanges](#) object representing the masked columns in `x`. The `append` argument takes `union`, `replace` or `intersect` to indicate how to combine the new value with `colmask(x)`. The `invert` argument takes a logical argument to indicate whether or not to invert the new mask. The `value` argument can be of any class that is coercible to a [NormalIRanges](#) via the `as` function.

`maskMotif(x, motif, min.block.width=1, ...)`: Returns a `MultipleAlignment` object with a modified column mask based upon motifs found in the consensus string where the consensus string keeps all the columns but drops the masked rows.

**motif** The motif to mask.

**min.block.width** The minimum width of the blocks to mask.

**...** Additional arguments for `matchPattern`.

`maskGaps(x, min.fraction, min.block.width)`: Returns a `MultipleAlignment` object with a modified column mask based upon gaps in the columns. In particular, this mask is defined by `min.block.width` or more consecutive columns that have `min.fraction` or more of their non-masked rows containing gap codes.

**min.fraction** A value in  $[0, 1]$  that indicates the minimum fraction needed to call a gap in the consensus string (default is 0.5).

**min.block.width** A positive integer that indicates the minimum number of consecutive gaps to mask, as defined by `min.fraction` (default is 4).

`nrow(x)`: Returns the number of sequences aligned in `x`.

`ncol(x)`: Returns the number of characters for each alignment in `x`.

`dim(x)`: Equivalent to `c(nrow(x), ncol(x))`.

`maskednrow(x)`: Returns the number of masked aligned sequences in `x`.

`maskedncol(x)`: Returns the number of masked aligned characters in `x`.

`maskeddim(x)`: Equivalent to `c(maskednrow(x), maskedncol(x))`.

`maskedratio(x)`: Equivalent to `maskeddim(x) / dim(x)`.

`nchar(x)`: Returns the number of unmasked aligned characters in `x`, i.e. `ncol(x) - maskedncol(x)`.

`alphabet(x)`: Equivalent to `alphabet(unmasked(x))`.

## Coercion

In the code snippets below, `x` is a `MultipleAlignment` object.

`as(from, "DNAStringSet")`, `as(from, "RNAStringSet")`, `as(from, "AAStringSet")`, `as(from, "BStringSet")`:  
Creates an instance of the specified [XStringSet](#) object subtype that contains the unmasked regions of the multiple sequence alignment in `x`.

`as.character(x, use.names)`: Convert `x` to a character vector containing the unmasked regions of the multiple sequence alignment. `use.names` controls whether or not `rownames(x)` should be used to set the names of the returned vector (default is TRUE).

`as.matrix(x, use.names)`: Returns a character matrix containing the "exploded" representation of the unmasked regions of the multiple sequence alignment. `use.names` controls whether or not `rownames(x)` should be used to set the row names of the returned matrix (default is TRUE).

## Utilities

In the code snippets below, `x` is a `MultipleAlignment` object.

`consensusMatrix(x, as.prob, baseOnly)`: Creates an integer matrix containing the column frequencies of the underlying alphabet with masked columns being represented with NA values. If `as.prob` is TRUE, then probabilities are reported, otherwise counts are reported (the default). If `baseOnly` is TRUE, then the non-base letters are collapsed into an "other" category.

`consensusString(x, ...)`: Creates a consensus string for `x` with the symbol "#" representing a masked column. See [consensusString](#) for details on the arguments.

`consensusViews(x, ...)`: Similar to the `consensusString` method. It returns a [XStringViews](#) on the consensus string containing subsequence contigs of non-masked columns. Unlike the `consensusString` method, the masked columns in the underlying string contain a consensus value rather than the "#" symbol.

`alphabetFrequency(x, as.prob, collapse)`: Creates an integer matrix containing the row frequencies of the underlying alphabet. If `as.prob` is TRUE, then probabilities are reported, otherwise counts are reported (the default). If `collapse` is TRUE, then returns the overall frequency instead of the frequency by row.

`detail(x, invertColMask, hideMaskedCols)`: Allows for a full pager driven display of the object so that masked cols and rows can be removed and the entire sequence can be visually inspected. If `hideMaskedCols` is set to its default value of TRUE then the output will hide all the the masked columns in the output. Otherwise, all columns will be displayed along with a row to indicate the masking status. If `invertColMask` is TRUE then any displayed mask will be flipped so as to represent things in a way consistent with Phylip style files instead of the mask that is actually stored in the `MultipleAlignment` object. Please notice that `invertColMask` will be ignored if `hideMaskedCols` is set to its default value of TRUE since in that case it will not make sense to show any masking information in the output. Masked rows are always hidden in the output.

## Author(s)

P. Aboyoun and M. Carlson

## See Also

[XStringSet-class](#), [MaskedXString-class](#)

## Examples

```
## create an object from file
origMAlign <-
```

```
readDNAMultipleAlignment(filepath =
                        system.file("extdata",
                                    "msx2_mRNA.aln",
                                    package="Biostrings"),
                        format="clustal")

## list the names of the sequences in the alignment
rownames(origMAlign)

## rename the sequences to be the underlying species for MSX2
rownames(origMAlign) <- c("Human", "Chimp", "Cow", "Mouse", "Rat",
                          "Dog", "Chicken", "Salmon")
origMAlign

## See a detailed pager view
if (interactive()) {
  detail(origMAlign)
}

## operations to mask rows
## For columns, just use colmask() and do the same kinds of operations
rowMasked <- origMAlign
rowmask(rowMasked) <- IRanges(start=1, end=3)
rowMasked

## remove rowumn masks
rowmask(rowMasked) <- NULL
rowMasked

## "select" rows of interest
rowmask(rowMasked, invert=TRUE) <- IRanges(start=4, end=7)
rowMasked

## or mask the rows that intersect with masked rows
rowmask(rowMasked, append="intersect") <- IRanges(start=1, end=5)
rowMasked

## TATA-masked
tataMasked <- maskMotif(origMAlign, "TATA")
colmask(tataMasked)

## automatically mask rows based on consecutive gaps
autoMasked <- maskGaps(origMAlign, min.fraction=0.5, min.block.width=4)
colmask(autoMasked)
autoMasked

## calculate frequencies
alphabetFrequency(autoMasked)
consensusMatrix(autoMasked, baseOnly=TRUE)[, 84:90]

## get consensus values
consensusString(autoMasked)
consensusViews(autoMasked)
```

```
## cluster the masked alignments
sdist <- stringDist(as(autoMasked,"DNAStringSet"), method="hamming")
clust <- hclust(sdist, method = "single")
plot(clust)
fourgroups <- cutree(clust, 4)
fourgroups

## write out the alignment object (with current masks) to Phylip format
write.phylip(x = autoMasked, filepath = tempfile("foo.txt",tempdir()))
```

---

needwunsQS

*(Deprecated) Needleman-Wunsch Global Alignment*

---

## Description

Simple gap implementation of Needleman-Wunsch global alignment algorithm.

## Usage

```
needwunsQS(s1, s2, substmat, gappen = 8)
```

## Arguments

s1, s2	an R character vector of length 1 or an <a href="#">XString</a> object.
substmat	matrix of alignment score values.
gappen	penalty for introducing a gap in the alignment.

## Details

Follows specification of Durbin, Eddy, Krogh, Mitchison (1998). This function has been deprecated and is being replaced by `pairwiseAlignment`.

## Value

An instance of class "PairwiseAlignments".

## Author(s)

Vince Carey (<stvjc@channing.harvard.edu>) (original author) and H. Pages (current maintainer).

## References

R. Durbin, S. Eddy, A. Krogh, G. Mitchison, Biological Sequence Analysis, Cambridge UP 1998, sec 2.3.



**See Also**

[pairwiseAlignment](#), [PairwiseAlignments-class](#), [substitution.matrices](#)

**Examples**

```
## Not run:
## This function has been deprecated
## Use pairwiseAlignment instead.

## nucleotide alignment
mat <- matrix(-5L, nrow = 4, ncol = 4)
for (i in seq_len(4)) mat[i, i] <- 0L
rownames(mat) <- colnames(mat) <- DNA_ALPHABET[1:4]
s1 <- DNASTring(paste(sample(DNA_ALPHABET[1:4], 1000, replace=TRUE), collapse=""))
s2 <- DNASTring(paste(sample(DNA_ALPHABET[1:4], 1000, replace=TRUE), collapse=""))
nw0 <- needwunsQS(s1, s2, mat, gappen = 0)
nw1 <- needwunsQS(s1, s2, mat, gappen = 1)
nw5 <- needwunsQS(s1, s2, mat, gappen = 5)

## amino acid alignment
needwunsQS("PAWHEAE", "HEAGAWGHEE", substmat = "BLOSUM50")

## End(Not run)
```

---

nucleotideFrequency	<i>Calculate the frequency of oligonucleotides in a DNA or RNA sequence (and other related functions)</i>
---------------------	---

---

**Description**

Given a DNA or RNA sequence (or a set of DNA or RNA sequences), the `oligonucleotideFrequency` function computes the frequency of all possible oligonucleotides of a given length (called the "width" in this particular context) in a sliding window that is shifted step nucleotides at a time.

The `dinucleotideFrequency` and `trinucleotideFrequency` functions are convenient wrappers for calling `oligonucleotideFrequency` with `width=2` and `width=3`, respectively.

The `nucleotideFrequencyAt` function computes the frequency of the short sequences formed by extracting the nucleotides found at some fixed positions from each sequence of a set of DNA or RNA sequences.

In this man page we call "DNA input" (or "RNA input") an [XString](#), [XStringSet](#), [XStringViews](#) or [MaskedXString](#) object of base type DNA (or RNA).

**Usage**

```
oligonucleotideFrequency(x, width, step=1,
                        as.prob=FALSE, as.array=FALSE,
                        fast.moving.side="right", with.labels=TRUE, ...)
```

```

## S4 method for signature XStringSet
oligonucleotideFrequency(x, width, step=1,
                          as.prob=FALSE, as.array=FALSE,
                          fast.moving.side="right", with.labels=TRUE,
                          simplify.as="matrix")

dinucleotideFrequency(x, step=1,
                      as.prob=FALSE, as.matrix=FALSE,
                      fast.moving.side="right", with.labels=TRUE, ...)

trinucleotideFrequency(x, step=1,
                       as.prob=FALSE, as.array=FALSE,
                       fast.moving.side="right", with.labels=TRUE, ...)

nucleotideFrequencyAt(x, at,
                      as.prob=FALSE, as.array=TRUE,
                      fast.moving.side="right", with.labels=TRUE, ...)

## Some related functions:
oligonucleotideTransitions(x, left=1, right=1, as.prob=FALSE)

mkAllStrings(alphabet, width, fast.moving.side="right")

```

### Arguments

x	Any DNA or RNA input for the *Frequency and oligonucleotideTransitions functions. An <a href="#">XStringSet</a> or <a href="#">XStringViews</a> object of base type DNA or RNA for nucleotideFrequencyAt.
width	The number of nucleotides per oligonucleotide for oligonucleotideFrequency. The number of letters per string for mkAllStrings.
step	How many nucleotides should the window be shifted before counting the next oligonucleotide (i.e. the sliding window step; default 1). If step is smaller than width, oligonucleotides will overlap; if the two arguments are equal, adjacent oligonucleotides will be counted (an efficient way to count codons in an ORF); and if step is larger than width, nucleotides will be sampled step nucleotides apart.
at	An integer vector containing the positions to look at in each element of x.
as.prob	If TRUE then probabilities are reported, otherwise counts (the default).
as.array, as.matrix	Controls the "shape" of the returned object. If TRUE (the default for nucleotideFrequencyAt) then it's a numeric matrix (or array), otherwise it's just a "flat" numeric vector i.e. a vector with no dim attribute (the default for the *Frequency functions).
fast.moving.side	Which side of the strings should move fastest? Note that, when as.array is TRUE, then the supplied value is ignored and the effective value is "left".
with.labels	If TRUE then the returned object is named.

...	Further arguments to be passed to or from other methods.
simplify.as	Together with the <code>as.array</code> and <code>as.matrix</code> arguments, controls the "shape" of the returned object when the input <code>x</code> is an <a href="#">XStringSet</a> or <a href="#">XStringViews</a> object. Supported <code>simplify.as</code> values are "matrix" (the default), "list" and "collapsed". If <code>simplify.as</code> is "matrix", the returned object is a matrix with <code>length(x)</code> rows where the <i>i</i> -th row contains the frequencies for <code>x[[i]]</code> . If <code>simplify.as</code> is "list", the returned object is a list of the same length as <code>length(x)</code> where the <i>i</i> -th element contains the frequencies for <code>x[[i]]</code> . If <code>simplify.as</code> is "collapsed", then the the frequencies are computed for the entire object <code>x</code> as a whole (i.e. frequencies cumulated across all sequences in <code>x</code> ).
left, right	The number of nucleotides per oligonucleotide for the rows and columns respectively in the transition matrix created by <code>oligonucleotideTransitions</code> .
alphabet	The alphabet to use to make the strings.

**Value**

If `x` is an [XString](#) or [MaskedXString](#) object, the `*Frequency` functions return a numeric vector of length  $4^{\text{width}}$ . If `as.array` (or `as.matrix`) is TRUE, then this vector is formatted as an array (or matrix). If `x` is an [XStringSet](#) or [XStringViews](#) object, the returned object has the shape specified by the `simplify.as` argument.

**Author(s)**

H. Pages and P. Aboyoun; K. Vlahovicek for the `step` argument

**See Also**

[alphabetFrequency](#), [alphabet](#), [hasLetterAt](#), [XString-class](#), [XStringSet-class](#), [XStringViews-class](#), [MaskedXString-class](#), [GENETIC\\_CODE](#), [AMINO\\_ACID\\_CODE](#), [reverseComplement](#), [rev](#)

**Examples**

```
## -----
## A. BASIC *Frequency() EXAMPLES
## -----
data(yeastSEQCHR1)
yeast1 <- DNASTring(yeastSEQCHR1)

dinucleotideFrequency(yeast1)
trinucleotideFrequency(yeast1)
oligonucleotideFrequency(yeast1, 4)

## Get the counts of tetranucleotides overlapping by one nucleotide:
oligonucleotideFrequency(yeast1, 4, step=3)

## Get the counts of adjacent tetranucleotides, starting from the first
## nucleotide:
oligonucleotideFrequency(yeast1, 4, step=4)

## Subset the sequence to change the starting nucleotide (here we start
```

```

## counting from third nucleotide:
yeast2 <- subseq(yeast1, start=3)
oligonucleotideFrequency(yeast2, 4, step=4)

## Get the less and most represented 6-mers:
f6 <- oligonucleotideFrequency(yeast1, 6)
f6[f6 == min(f6)]
f6[f6 == max(f6)]

## Get the result as an array:
tri <- trinucleotideFrequency(yeast1, as.array=TRUE)
tri["A", "A", "C"] # == trinucleotideFrequency(yeast1)["AAC"]
tri["T", , ] # frequencies of trinucleotides starting with a "T"

## With input made of multiple sequences:
library(drosophila2probe)
probes <- DNASTringSet(drosophila2probe)
dfmat <- dinucleotideFrequency(probes) # a big matrix
dinucleotideFrequency(probes, simplify.as="collapsed")
dinucleotideFrequency(probes, simplify.as="collapsed", as.matrix=TRUE)

## -----
## B. OBSERVED DINUCLEOTIDE FREQUENCY VERSUS EXPECTED DINUCLEOTIDE
## FREQUENCY
## -----
## The expected frequency of dinucleotide "ab" based on the frequencies
## of its individual letters "a" and "b" is:
## exp_Fab = Fa * Fb / N if the 2 letters are different (e.g. CG)
## exp_Faa = Fa * (Fa-1) / N if the 2 letters are the same (e.g. TT)
## where Fa and Fb are the frequencies of "a" and "b" (respectively) and
## N the length of the sequence.

## Here is a simple function that implements the above formula for a
## DNASTring object x. The expected frequencies are returned in a 4x4
## matrix where the rownames and colnames correspond to the 1st and 2nd
## base in the dinucleotide:
expectedDinucleotideFrequency <- function(x)
{
  # Individual base frequencies.
  bf <- alphabetFrequency(x, baseOnly=TRUE)[DNA_BASES]
  (as.matrix(bf) %*% t(bf) - diag(bf)) / length(x)
}

## On Celegans chrI:
library(BSgenome.Celegans.UCSC.ce2)
chrI <- Celegans$chrI
obs_df <- dinucleotideFrequency(chrI, as.matrix=TRUE)
obs_df # CG has the lowest frequency
exp_df <- expectedDinucleotideFrequency(chrI)
## A sanity check:
stopifnot(as.integer(sum(exp_df)) == sum(obs_df))

## Ratio of observed frequency to expected frequency:

```

```

obs_df / exp_df # TA has the lowest ratio, not CG!

## -----
## C. nucleotideFrequencyAt()
## -----
nucleotideFrequencyAt(probes, 13)
nucleotideFrequencyAt(probes, c(13, 20))
nucleotideFrequencyAt(probes, c(13, 20), as.array=FALSE)

## nucleotideFrequencyAt() can be used to answer questions like: "how
## many probes in the drosophila2 chip have T, G, T, A at position
## 2, 4, 13 and 20, respectively?"
nucleotideFrequencyAt(probes, c(2, 4, 13, 20))["T", "G", "T", "A"]
## or "whats the probability to have an A at position 25 if there is
## one at position 13?"
nf <- nucleotideFrequencyAt(probes, c(13, 25))
sum(nf["A", "A"]) / sum(nf["A", ])
## Probabilities to have other bases at position 25 if there is an A
## at position 13:
sum(nf["A", "C"]) / sum(nf["A", ]) # C
sum(nf["A", "G"]) / sum(nf["A", ]) # G
sum(nf["A", "T"]) / sum(nf["A", ]) # T

## See ?hasLetterAt for another way to get those results.

## -----
## D. oligonucleotideTransitions()
## -----
## Get nucleotide transition matrices for yeast1
oligonucleotideTransitions(yeast1)
oligonucleotideTransitions(yeast1, 2, as.prob=TRUE)

## -----
## E. ADVANCED *Frequency() EXAMPLES
## -----
## Note that when dropping the dimensions of the tri array, elements
## in the resulting vector are ordered as if they were obtained with
## fast.moving.side="left":
triL <- trinucleotideFrequency(yeast1, fast.moving.side="left")
all(as.vector(tri) == triL) # TRUE

## Convert the trinucleotide frequency into the amino acid frequency
## based on translation:
tri1 <- trinucleotideFrequency(yeast1)
names(tri1) <- GENETIC_CODE[names(tri1)]
sapply(split(tri1, names(tri1)), sum) # 12512 occurrences of the stop codon

## When the returned vector is very long (e.g. width >= 10), using
## with.labels=FALSE can improve performance significantly.
## Here for example, the observed speed up is between 25x and 500x:
f12 <- oligonucleotideFrequency(yeast1, 12, with.labels=FALSE) # very fast!

## With the use of step, trinucleotideFrequency() is a very fast way to

```

```

## calculate the codon usage table in an ORF (or a set of ORFs).
## Taking the same example as in ?codons:
file <- system.file("extdata", "someORF.fa", package="Biostrings")
my_ORFs <- readDNASTringSet(file)
## Strip flanking 1000 nucleotides around each ORF and remove first
## sequence as it contains an intron:
my_ORFs <- DNASTringSet(my_ORFs, start=1001, end=-1001)[-1]
## Codon usage for each ORF:
codon_usage <- trinucleotideFrequency(my_ORFs, step=3)
## Codon usage across all ORFs:
global_codon_usage <- trinucleotideFrequency(my_ORFs, step=3,
                                             simplify.as="collapsed")
stopifnot(all(colSums(codon_usage) == global_codon_usage)) # sanity check

## Some related functions:
dict1 <- mkAllStrings(LETTERS[1:3], 4)
dict2 <- mkAllStrings(LETTERS[1:3], 4, fast.moving.side="left")
stopifnot(identical(reverse(dict1), dict2))

```

---

padAndClip

*Pad and clip strings*

---

## Description

padAndClip first conceptually pads the supplied strings with an infinite number of padding letters on both sides, then clip them.

stackStrings is a convenience wrapper to padAndClip that turns a variable-width set of strings into a rectangular (i.e. constant-width) set, by padding and clipping the strings, after conceptually shifting them horizontally.

## Usage

```
padAndClip(x, views, Lpadding.letter=" ", Rpadding.letter=" ",
          remove.out.of.view.strings=FALSE)
```

```
stackStrings(x, from, to, shift=0L,
            Lpadding.letter=" ", Rpadding.letter=" ",
            remove.out.of.view.strings=FALSE)
```

## Arguments

**x** An [XStringSet](#) object containing the strings to pad and clip.

**views** A [Ranges](#) object (recycled to the length of x if necessary) defining the region to keep for each string. Because the strings are first conceptually padded with an infinite number of padding letters on both sides, regions can go beyond string limits.

<code>Lpadding.letter</code> , <code>Rpadding.letter</code>	A single letter to use for padding on the left, and another one to use for padding on the right. Note that the default letter (" ") does not work if, for example, <code>x</code> is a <code>DNAStrngSet</code> object, because the space is not a valid DNA letter (see <code>?DNA_ALPHABET</code> ). So the <code>Lpadding.letter</code> and <code>Rpadding.letter</code> arguments <i>must</i> be supplied if <code>x</code> is not a <code>BStringSet</code> object. For example, if <code>x</code> is a <code>DNAStrngSet</code> object, a typical choice is to use "+".
<code>remove.out.of.view.strings</code>	TRUE or FALSE. Whether or not to remove the strings that are out of view in the returned object.
<code>from</code> , <code>to</code>	Another way to specify the region to keep for each string, but with the restriction that <code>from</code> and <code>to</code> must be single integers. So only 1 region can be specified, and the same region is used for all the strings.
<code>shift</code>	An integer vector (recycled to the length of <code>x</code> if necessary) specifying the amount of shifting (in number of letters) to apply to each string before doing pad and clip. Positive values shift to the right and negative values to the left.

### Value

For `padAndClip`: An `XStringSet` object. If `remove.out.of.view.strings` is FALSE, it has the same length and names as `x`, and its "shape", which is described by the integer vector returned by `width()`, is the same as the shape of the `views` argument after recycling.

The class of the returned object is the direct concrete subclass of `XStringSet` that `x` belongs to or derives from. There are 4 direct concrete subclasses of the `XStringSet` virtual class: `BStringSet`, `DNAStrngSet`, `RNAStrngSet`, and `AAStringSet`. If `x` is an *instance* of one of those classes, then the returned object has the same class as `x` (i.e. in that case, `padAndClip` acts as an endomorphism). But if `x` *derives* from one of those 4 classes, then the returned object is downgraded to the class `x` derives from. In that case, `padAndClip` does not act as an endomorphism.

For `stackStrings`: Same as `padAndClip`. In addition it is guaranteed to have a rectangular shape i.e. to be a constant-width `XStringSet` object.

### Author(s)

H. Pages

### See Also

- The `stackStringsFromBam` function in the **Rsamtools** package for stacking the read sequences (or their quality strings) stored in a BAM file on a region of interest.
- The `XStringViews` class to formally represent a set of views on a single string.
- The `extractAt` and `replaceAt` functions for extracting/replacing arbitrary substrings from/in a string or set of strings.
- The `XStringSet` class.
- The `Ranges` class in the **IRanges** package.

**Examples**

```
x <- BStringSet(c(seq1="ABCD", seq2="abcdefghijk", seq3="", seq4="XYZ"))

padAndClip(x, IRanges(3, 8:5), Lpadding.letter=">", Rpadding.letter="<")
padAndClip(x, IRanges(1:-2, 7), Lpadding.letter=">", Rpadding.letter="<")

stackStrings(x, 2, 8)

stackStrings(x, -2, 8, shift=c(0, -11, 6, 7),
             Lpadding.letter="#", Rpadding.letter=".")

stackStrings(x, -2, 8, shift=c(0, -14, 6, 7),
             Lpadding.letter="#", Rpadding.letter=".")

stackStrings(x, -2, 8, shift=c(0, -14, 6, 7),
             Lpadding.letter="#", Rpadding.letter=".",
             remove.out.of.view.strings=TRUE)

library(hgu95av2probe)
probes <- DNASTringSet(hgu95av2probe)
probes

stackStrings(probes, 0, 26,
             Lpadding.letter="+", Rpadding.letter="-")

options(showHeadLines=15)
stackStrings(probes, 3, 23, shift=6*c(1:5, -(1:5)),
             Lpadding.letter="+", Rpadding.letter="N",
             remove.out.of.view.strings=TRUE)
```

---

pairwiseAlignment      *Optimal Pairwise Alignment*

---

**Description**

Solves (Needleman-Wunsch) global alignment, (Smith-Waterman) local alignment, and (ends-free) overlap alignment problems.

**Usage**

```
pairwiseAlignment(pattern, subject, ...)

## S4 method for signature ANY,ANY
pairwiseAlignment(pattern, subject,
                  patternQuality=PhredQuality(22L),
                  subjectQuality=PhredQuality(22L),
                  type="global",
                  substitutionMatrix=NULL, fuzzyMatrix=NULL,
                  gapOpening=-10, gapExtension=-4,
```



```

        scoreOnly=FALSE)

## S4 method for signature QualityScaledXStringSet,QualityScaledXStringSet
pairwiseAlignment(pattern, subject,
                  type="global",
                  substitutionMatrix=NULL, fuzzyMatrix=NULL,
                  gapOpening=-10, gapExtension=-4,
                  scoreOnly=FALSE)

```

### Arguments

pattern	a character vector of any length, an <a href="#">XString</a> , or an <a href="#">XStringSet</a> object.
subject	a character vector of length 1, an <a href="#">XString</a> , or an <a href="#">XStringSet</a> object of length 1.
patternQuality, subjectQuality	objects of class <a href="#">XStringQuality</a> representing the respective quality scores for pattern and subject that are used in a quality-based method for generating a substitution matrix. These two arguments are ignored if <code>!is.null(substitutionMatrix)</code> or if its respective string set (pattern, subject) is of class <a href="#">QualityScaledXStringSet</a> .
type	type of alignment. One of "global", "local", "overlap", "global-local", and "local-global" where "global" = align whole strings with end gap penalties, "local" = align string fragments, "overlap" = align whole strings without end gap penalties, "global-local" = align whole strings in pattern with consecutive subsequence of subject, "local-global" = align consecutive subsequence of pattern with whole strings in subject.
substitutionMatrix	substitution matrix representing the fixed substitution scores for an alignment. It cannot be used in conjunction with patternQuality and subjectQuality arguments.
fuzzyMatrix	fuzzy match matrix for quality-based alignments. It takes values between 0 and 1; where 0 is an unambiguous mismatch, 1 is an unambiguous match, and values in between represent a fraction of "matchiness". (See details section below.)
gapOpening	the cost for opening a gap in the alignment.
gapExtension	the incremental cost incurred along the length of the gap in the alignment.
scoreOnly	logical to denote whether or not to return just the scores of the optimal pairwise alignment.
...	optional arguments to generic function to support additional methods.

### Details

Quality-based alignments are based on the paper the Bioinformatics article by Ketil Malde listed in the Reference section below. Let  $\epsilon_i$  be the probability of an error in the base read. For "Phred" quality measures  $Q$  in  $[0, 99]$ , these error probabilities are given by  $\epsilon_i = 10^{-Q/10}$ . For "Solexa" quality measures  $Q$  in  $[-5, 99]$ , they are given by  $\epsilon_i = 1 - 1/(1 + 10^{-Q/10})$ . Assuming independence within and between base reads, the combined error probability of a mismatch when the underlying bases do match is  $\epsilon_c = \epsilon_1 + \epsilon_2 - (n/(n - 1)) * \epsilon_1 * \epsilon_2$ , where  $n$  is the number of

letters in the underlying alphabet (i.e.  $n = 4$  for DNA input,  $n = 20$  for amino acid input, otherwise  $n$  is the number of distinct letters in the input). Using  $\epsilon_c$ , the substitution score is given by  $b * \log_2(\gamma_{x,y} * (1 - \epsilon_c) * n + (1 - \gamma_{x,y}) * \epsilon_c * (n / (n - 1)))$ , where  $b$  is the bit-scaling for the scoring and  $\gamma_{x,y}$  is the probability that characters  $x$  and  $y$  represents the same underlying information (e.g. using IUPAC,  $\gamma_{A,A} = 1$  and  $\gamma_{A,N} = 1/4$ ). In the arguments listed above `fuzzyMatch` represents  $\gamma_{x,y}$  and `patternQuality` and `subjectQuality` represents  $\epsilon_1$  and  $\epsilon_2$  respectively.

If `scoreOnly == FALSE`, a pairwise alignment with the maximum alignment score is returned. If more than one pairwise alignment produces the maximum alignment score, then the alignment with the smallest initial deletion whose mismatches occur before its insertions and deletions is chosen. For example, if `pattern = "AGTA"` and `subject = "AACTAACTA"`, then the alignment `pattern: [1] AG-TA; subject: [1] AACTA` is chosen over `pattern: [1] A-GTA; subject: [1] AACTA` or `pattern: [1] AG-TA; subject: [5] AACTA` if they all achieve the maximum alignment score.

### Value

If `scoreOnly == FALSE`, an instance of class `PairwiseAlignments` or `PairwiseAlignmentsSingleSubject` is returned. If `scoreOnly == TRUE`, a numeric vector containing the scores for the optimal pairwise alignments is returned.

### Note

Use `matchPattern` or `vmatchPattern` if you need to find all the occurrences (eventually with indels) of a given pattern in a reference sequence or set of sequences.

Use `matchPDict` if you need to match a (big) set of patterns against a reference sequence.

### Author(s)

P. Aboyoun and H. Pages

### References

- R. Durbin, S. Eddy, A. Krogh, G. Mitchison, Biological Sequence Analysis, Cambridge UP 1998, sec 2.3.
- B. Haubold, T. Wiehe, Introduction to Computational Biology, Birkhauser Verlag 2006, Chapter 2.
- K. Malde, The effect of sequence quality on sequence alignment, Bioinformatics 2008 24(7):897-900.

### See Also

`writePairwiseAlignments`, `stringDist`, `PairwiseAlignments-class`, `XStringQuality-class`, `substitution.matrices`, `matchPattern`

### Examples

```
## Nucleotide global, local, and overlap alignments
s1 <-
  DNASTring("ACTTCACCAGCTCCCTGGCGGTAAGTTGATCAAAGGAAACGCAAAGTTTTCAAG")
s2 <-
  DNASTring("GTTTCACTACTTCCTTTGGGTAAGTAAATATATAAAATATATAAAATATAATTTTCATC")
```

```

# First use a fixed substitution matrix
mat <- nucleotideSubstitutionMatrix(match = 1, mismatch = -3, baseOnly = TRUE)
globalAlign <-
  pairwiseAlignment(s1, s2, substitutionMatrix = mat,
                    gapOpening = -5, gapExtension = -2)
localAlign <-
  pairwiseAlignment(s1, s2, type = "local", substitutionMatrix = mat,
                    gapOpening = -5, gapExtension = -2)
overlapAlign <-
  pairwiseAlignment(s1, s2, type = "overlap", substitutionMatrix = mat,
                    gapOpening = -5, gapExtension = -2)

# Then use quality-based method for generating a substitution matrix
pairwiseAlignment(s1, s2,
                  patternQuality = SolexaQuality(rep(c(22L, 12L), times = c(36, 18))),
                  subjectQuality = SolexaQuality(rep(c(22L, 12L), times = c(40, 20))),
                  scoreOnly = TRUE)

# Now assume cant distinguish between C/T and G/A
pairwiseAlignment(s1, s2,
                  patternQuality = SolexaQuality(rep(c(22L, 12L), times = c(36, 18))),
                  subjectQuality = SolexaQuality(rep(c(22L, 12L), times = c(40, 20))),
                  type = "local")
mapping <- diag(4)
dimnames(mapping) <- list(DNA_BASES, DNA_BASES)
mapping["C", "T"] <- mapping["T", "C"] <- 1
mapping["G", "A"] <- mapping["A", "G"] <- 1
pairwiseAlignment(s1, s2,
                  patternQuality = SolexaQuality(rep(c(22L, 12L), times = c(36, 18))),
                  subjectQuality = SolexaQuality(rep(c(22L, 12L), times = c(40, 20))),
                  fuzzyMatrix = mapping,
                  type = "local")

## Amino acid global alignment
pairwiseAlignment(AAString("PAWHEAE"), AAString("HEAGAWGHEE"),
                  substitutionMatrix = "BLOSUM50",
                  gapOpening = 0, gapExtension = -8)

```

---

## PairwiseAlignments-class

*PairwiseAlignments, PairwiseAlignmentsSingleSubject, and PairwiseAlignmentsSingleSubjectSummary objects*

---

### Description

The `PairwiseAlignments` class is a container for storing a set of pairwise alignments.

The `PairwiseAlignmentsSingleSubject` class is a container for storing a set of pairwise alignments with a single subject.

The `PairwiseAlignmentsSingleSubjectSummary` class is a container for storing the summary of a set of pairwise alignments.

### Usage

```
## Constructors:
## When subject is missing, pattern must be of length 2
## S4 method for signature XString,XString
PairwiseAlignments(pattern, subject,
  type = "global", substitutionMatrix = NULL, gapOpening = 0, gapExtension = -1)
## S4 method for signature XStringSet,missing
PairwiseAlignments(pattern, subject,
  type = "global", substitutionMatrix = NULL, gapOpening = 0, gapExtension = -1)
## S4 method for signature character,character
PairwiseAlignments(pattern, subject,
  type = "global", substitutionMatrix = NULL, gapOpening = 0, gapExtension = -1,
  baseClass = "BString")
## S4 method for signature character,missing
PairwiseAlignments(pattern, subject,
  type = "global", substitutionMatrix = NULL, gapOpening = 0, gapExtension = -1,
  baseClass = "BString")
```

### Arguments

<code>pattern</code>	a character vector of length 1 or 2, an <code>XString</code> , or an <code>XStringSet</code> object of length 1 or 2.
<code>subject</code>	a character vector of length 1 or an <code>XString</code> object.
<code>type</code>	type of alignment. One of "global", "local", "overlap", "global-local", and "local-global" where "global" = align whole strings with end gap penalties, "local" = align string fragments, "overlap" = align whole strings without end gap penalties, "global-local" = align whole strings in pattern with consecutive subsequence of subject, "local-global" = align consecutive subsequence of pattern with whole strings in subject.
<code>substitutionMatrix</code>	substitution matrix for the alignment. If <code>NULL</code> , the diagonal values and off-diagonal values are set to 0 and 1 respectively.
<code>gapOpening</code>	the cost for opening a gap in the alignment.
<code>gapExtension</code>	the incremental cost incurred along the length of the gap in the alignment.
<code>baseClass</code>	the base <code>XString</code> class to use in the alignment.

### Details

Before we define the notion of alignment, we introduce the notion of "filled-with-gaps subsequence". A "filled-with-gaps subsequence" of a string `string1` is obtained by inserting 0 or any number of gaps in a subsequence of `s1`. For example `L-A-ND` and `A-N-D` are "filled-with-gaps subsequences" of `LAND`. An alignment between two strings `string1` and `string2` results in two strings (`align1` and `align2`) that have the same length and are "filled-with-gaps subsequences" of `string1` and `string2`.

For example, this is an alignment between LAND and LEAVES:

```
L-A
LEA
```

An alignment can be seen as a compact representation of one set of basic operations that transforms string1 into align1. There are 3 different kinds of basic operations: "insertions" (gaps in align1), "deletions" (gaps in align2), "replacements". The above alignment represents the following basic operations:

```
insert E at pos 2
insert V at pos 4
insert E at pos 5
replace by S at pos 6 (N is replaced by S)
delete at pos 7 (D is deleted)
```

Note that "insert X at pos i" means that all letters at a position  $\geq i$  are moved 1 place to the right before X is actually inserted.

There are many possible alignments between two given strings string1 and string2 and a common problem is to find the one (or those ones) with the highest score, i.e. with the lower total cost in terms of basic operations.

### Object extraction methods

In the code snippets below, x is a PairwiseAlignments object, except otherwise noted.

pattern(x): The AlignedXStringSet object for the pattern.

subject(x): The AlignedXStringSet object for the subject.

summary(object, ...): Generates a summary for the PairwiseAlignments.

### General information methods

In the code snippets below, x is a PairwiseAlignments object, except otherwise noted.

alphabet(x): Equivalent to alphabet(unaligned(subject(x))).

length(x): The length of the aligned(pattern(x)) and aligned(subject(x)). There is a method for PairwiseAlignmentsSingleSubjectSummary as well.

type(x): The type of the alignment ("global", "local", "overlap", "global-local", or "local-global"). There is a method for PairwiseAlignmentsSingleSubjectSummary as well.

### Aligned sequence methods

In the code snippets below, x is a PairwiseAlignmentsSingleSubject object, except otherwise noted.

`aligned(x, degap = FALSE, gapCode="-", endgapCode="-")`: If `degap = FALSE`, "align" the alignments by returning an `XStringSet` object containing the aligned patterns without insertions. If `degap = TRUE`, returns `aligned(pattern(x), degap=TRUE)`. The `gapCode` and `endgapCode` arguments denote the code in the appropriate [alphabet](#) to use for the internal and end gaps.

`as.character(x)`: Converts `aligned(x)` to a character vector.

`as.matrix(x)`: Returns an "exploded" character matrix representation of `aligned(x)`.

`toString(x)`: Equivalent to `toString(as.character(x))`.

### Subject position methods

In the code snippets below, `x` is a `PairwiseAlignmentsSingleSubject` object, except otherwise noted.

`consensusMatrix(x, as.prob=FALSE, baseOnly=FALSE, gapCode="-", endgapCode="-")`  
See '[consensusMatrix](#)' for more information.

`consensusString(x)` See '[consensusString](#)' for more information.

`coverage(x, shift=0L, width=NULL, weight=1L)` See '[coverage,PairwiseAlignmentsSingleSubject-method](#)' for more information.

`Views(subject, start=NULL, end=NULL, width=NULL, names=NULL)`: The `XStringViews` object that represents the pairwise alignments along `unaligned(subject(subject))`. The `start` and `end` arguments must be either `NULL/NA` or an integer vector of length 1 that denotes the offset from `start(subject(subject))`.

### Numeric summary methods

In the code snippets below, `x` is a `PairwiseAlignments` object, except otherwise noted.

`nchar(x)`: The `nchar` of the `aligned(pattern(x))` and `aligned(subject(x))`. There is a method for `PairwiseAlignmentsSingleSubjectSummary` as well.

`insertion(x)`: An [CompressedIRangesList](#) object containing the locations of the insertions from the perspective of the pattern.

`deletion(x)`: An [CompressedIRangesList](#) object containing the locations of the deletions from the perspective of the pattern.

`indel(x)`: An `InDel` object containing the locations of the insertions and deletions from the perspective of the pattern.

`nindel(x)`: An `InDel` object containing the number of insertions and deletions.

`score(x)`: The score of the alignment. There is a method for `PairwiseAlignmentsSingleSubjectSummary` as well.

### Subsetting methods

`x[i]`: Returns a new `PairwiseAlignments` object made of the selected elements.

`rep(x, times)`: Returns a new `PairwiseAlignments` object made of the repeated elements.

**Author(s)**

P. Aboyoun

**See Also**

[pairwiseAlignment](#), [writePairwiseAlignments](#), [AlignedXStringSet-class](#), [XString-class](#), [XStringViews-class](#), [align-utils](#), [pid](#)

**Examples**

```
PairwiseAlignments("-PA--W-HEAE", "HEAGAWGHE-E")
pattern <- AAStrSet(c("HLDNLKGTG", "HVDDMPNAL"))
subject <- AAStr("SMDDEKMSMKL")
nw1 <- pairwiseAlignment(pattern, subject, substitutionMatrix = "BLOSUM50",
  gapOpening = -3, gapExtension = -1)
pattern(nw1)
subject(nw1)
aligned(nw1)
as.character(nw1)
as.matrix(nw1)
nchar(nw1)
score(nw1)
nw1
```

---

PairwiseAlignments-io *Write a PairwiseAlignments object to a file*

---

**Description**

The `writePairwiseAlignments` function writes a [PairwiseAlignments](#) object to a file. Only the "pair" format is supported at the moment.

**Usage**

```
writePairwiseAlignments(x, file="", Matrix=NA, block.width=50)
```

**Arguments**

- |        |   |
|--------|---|
| x      | A <a href="#">PairwiseAlignments</a> object, typically returned by the <a href="#">pairwiseAlignment</a> function.  |
| file   | A connection, or a character string naming the file to print to. If "" (the default), <code>writePairwiseAlignments</code> prints to the standard output connection (aka the console) unless redirected by <code>sink</code> . If it is " cmd", the output is piped to the command given by <code>cmd</code> , by opening a pipe connection.                            |
| Matrix | A single string containing the name of the substitution matrix (e.g. "BLOSUM50") used for the alignment. See the <code>substitutionMatrix</code> argument of the <a href="#">pairwiseAlignment</a> function for the details. See <a href="#">?substitution.matrices</a> for a list of predefined substitution matrices available in the <code>Biostings</code> package. |

`block.width` A single integer specifying the maximum number of sequence letters (including the "-" letter, which represents gaps) per line.

### Details

The "pair" format is one of the numerous pairwise sequence alignment formats supported by the EMBOSS software. See <http://emboss.sourceforge.net/docs/themes/AlignFormats.html> for a brief (and rather informal) description of this format.

### Note

This brief description of the "pair" format suggests that it is best suited for *global* pairwise alignments, because, in that case, the original pattern and subject sequences can be inferred (by just removing the gaps).

However, even though the "pair" format can also be used for non global pairwise alignments (i.e. for *global-local*, *local-global*, and *local* pairwise alignments), in that case the original pattern and subject sequences *cannot* be inferred. This is because the alignment written to the file doesn't necessarily span the entire pattern (if `type(x)` is `local-global` or `local`) or the entire subject (if `type(x)` is `global-local` or `local`).

As a consequence, the `writePairwiseAlignments` function can be used on a [PairwiseAlignments](#) object `x` containing non global alignments (i.e. with `type(x) != "global"`), but with the 2 following caveats:

1. The type of the alignments (`type(x)`) is not written to the file.
2. The original pattern and subject sequences cannot be inferred. Furthermore, there is no way to infer their lengths (because we don't know whether they were trimmed or not).

Also note that the `pairwiseAlignment` function interprets the `gapOpening` and `gapExtension` arguments differently than most other alignment tools. As a consequence the values of the `Gap_penalty` and `Extend_penalty` fields written to the file are not the same as the values that were passed to the `gapOpening` and `gapExtension` arguments. With the following relationship:

- $\text{Gap\_penalty} = - \text{gapOpening} - \text{gapExtension}$
- $\text{Extend\_penalty} = - \text{gapExtension}$

### Author(s)

H. Pages

### References

<http://emboss.sourceforge.net/docs/themes/AlignFormats.html>

### See Also

- [pairwiseAlignment](#)
- [PairwiseAlignments-class](#)
- [substitution.matrices](#)



**Examples**

```
## -----
## A. WITH ONE PAIR
## -----
pattern <- DNASTring("CGTACGTAACGTTTCGT")
subject <- DNASTring("CGTCGTCGTCGGTAA")
x1 <- pairwiseAlignment(pattern, subject)
x1
writePairwiseAlignments(x1)
writePairwiseAlignments(x1, block.width=10)
## The 2 bottom-right numbers (16 and 15) are the lengths of
## the original pattern and subject, respectively.

x2 <- pairwiseAlignment(pattern, subject, type="global-local")
x2 # score is different!
writePairwiseAlignments(x2)
## By just looking at the file, we cant tell the length of the
## original subject! Could be 13, could be more...

## -----
## B. WITH MORE THAN ONE PAIR (AND NAMED PATTERNS)
## -----
pattern <- DNASTringSet(c(myp1="ACCA", myp2="ACGCA", myp3="ACGGCA"))
x3 <- pairwiseAlignment(pattern, subject)
x3
writePairwiseAlignments(x3)

## -----
## C. REPRODUCING THE ALIGNMENT SHOWN AT
##   http://emboss.sourceforge.net/docs/themes/alnformats/align.pair
## -----
pattern <- c("TSPASIRPPAGPSSRPAMVSSRRTRPSPPGPRRPTGRPCCSAAPRRPQAT",
            "GGWKTCSGTCTTSTSTRHRGRSGWSARTTTAACLRASRKSMAACRSRSAG",
            "SRPNRFAPTLMSSCITSTTGPPAWAGDRSHE")
subject <- c("TSPASIRPPAGPSSRRPSPGPRRPTGRPCCSAAPRRPQATGGWKTCSGT",
            "CTTSTSTRHRGRSGWRASRKSMAACRSRSAGSRPNRFAPTLMSSCITSTT",
            "GPPAWAGDRSHE")
pattern <- unlist(AAStringSet(pattern))
subject <- unlist(AAStringSet(subject))
pattern # original pattern
subject # original subject
data(BLOSUM62)
x4 <- pairwiseAlignment(pattern, subject,
                        substitutionMatrix=BLOSUM62,
                        gapOpening=-9.5, gapExtension=-0.5)
x4
writePairwiseAlignments(x4, Matrix="BLOSUM62")
```

## Description

The PDict class is a container for storing a preprocessed dictionary of DNA patterns that can later be passed to the `matchPDict` function for fast matching against a reference sequence (the subject).

PDict is the constructor function for creating new PDict objects.

## Usage

```
PDict(x, max.mismatch=NA, tb.start=NA, tb.end=NA, tb.width=NA,
      algorithm="ACtree2", skip.invalid.patterns=FALSE)
```

## Arguments

<code>x</code>	A character vector, a <code>DNAStrngSet</code> object or an <code>XStringViews</code> object with a <code>DNAStrng</code> subject.
<code>max.mismatch</code>	A single non-negative integer or NA. See the "Allowing a small number of mismatching letters" section below.
<code>tb.start, tb.end, tb.width</code>	A single integer or NA. See the "Trusted Band" section below.
<code>algorithm</code>	"ACtree2" (the default) or "Twobit".
<code>skip.invalid.patterns</code>	This argument is not supported yet (and might in fact be replaced by the <code>filter</code> argument very soon).

## Details

THIS IS STILL WORK IN PROGRESS!

If the original dictionary `x` is a character vector or an `XStringViews` object with a `DNAStrng` subject, then the PDict constructor will first try to turn it into a `DNAStrngSet` object.

By default (i.e. if PDict is called with `max.mismatch=NA`, `tb.start=NA`, `tb.end=NA` and `tb.width=NA`) the following limitations apply: (1) the original dictionary can only contain base letters (i.e. only As, Cs, Gs and Ts), therefore IUPAC ambiguity codes are not allowed; (2) all the patterns in the dictionary must have the same length ("constant width" dictionary); and (3) later `matchPdct` can only be used with `max.mismatch=0`.

A Trusted Band can be used in order to relax these limitations (see the "Trusted Band" section below).

If you are planning to use the resulting PDict object in order to do inexact matching where valid hits are allowed to have a small number of mismatching letters, then see the "Allowing a small number of mismatching letters" section below.

Two preprocessing algorithms are currently supported: `algorithm="ACtree2"` (the default) and `algorithm="Twobit"`. With the "ACtree2" algorithm, all the oligonucleotides in the Trusted Band are stored in a 4-ary Aho-Corasick tree. With the "Twobit" algorithm, the 2-bit-per-letter signatures of all the oligonucleotides in the Trusted Band are computed and the mapping from these signatures to the 1-based position of the corresponding oligonucleotide in the Trusted Band is stored in a way that allows very fast lookup. Only PDict objects preprocessed with the "ACtree2" algo can then be used with `matchPdct` (and family) and with `fixed="pattern"` (instead of `fixed=TRUE`, the default), so that IUPAC ambiguity codes in the subject are treated as ambiguities. PDict objects

obtained with the "Twobit" algo don't allow this. See [?matchPDict-inexact](#) for more information about support of IUPAC ambiguity codes in the subject.

## Trusted Band

What's a Trusted Band?

A Trusted Band is a region defined in the original dictionary where the limitations described above will apply.

Why use a Trusted Band?

Because the limitations described above will apply to the Trusted Band only! For example the Trusted Band cannot contain IUPAC ambiguity codes but the "head" and the "tail" can (see below for what those are). Also with a Trusted Band, if `matchPdDict` is called with a non-null `max.mismatch` value then mismatching letters will be allowed in the head and the tail. Or, if `matchPdDict` is called with `fixed="subject"`, then IUPAC ambiguity codes in the head and the tail will be treated as ambiguities.

How to specify a Trusted Band?

Use the `tb.start`, `tb.end` and `tb.width` arguments of the `PDict` constructor in order to specify a Trusted Band. This will divide each pattern in the original dictionary into three parts: a left part, a middle part and a right part. The middle part is defined by its starting and ending nucleotide positions given relatively to each pattern thru the `tb.start`, `tb.end` and `tb.width` arguments. It must have the same length for all patterns (this common length is called the width of the Trusted Band). The left and right parts are defined implicitly: they are the parts that remain before (prefix) and after (suffix) the middle part, respectively. Therefore three [DNAStrngSet](#) objects result from this division: the first one is made of all the left parts and forms the head of the `PDict` object, the second one is made of all the middle parts and forms the Trusted Band of the `PDict` object, and the third one is made of all the right parts and forms the tail of the `PDict` object.

In other words you can think of the process of specifying a Trusted Band as drawing 2 vertical lines on the original dictionary (note that these 2 lines are not necessarily straight lines but the horizontal space between them must be constant). When doing this, you are dividing the dictionary into three regions (from left to right): the head, the Trusted Band and the tail. Each of them is a [DNAStrngSet](#) object with the same number of elements than the original dictionary and the original dictionary could easily be reconstructed from those three regions.

The width of the Trusted Band must be  $\geq 1$  because Trusted Bands of width 0 are not supported.

Finally note that calling `PDict` with `tb.start=NA`, `tb.end=NA` and `tb.width=NA` (the default) is equivalent to calling it with `tb.start=1`, `tb.end=-1` and `tb.width=NA`, which results in a full-width Trusted Band i.e. a Trusted Band that covers the entire dictionary (no head and no tail).

## Allowing a small number of mismatching letters

TODO

## Accessor methods

In the code snippets below, `x` is a `PDict` object.

`length(x)`: The number of patterns in `x`.



```

pdict0
class(pdict0)
length(pdict0)           # Same as length(dict0).
tb.width(pdict0)        # The width of the (implicit)
                        # Trusted Band.

sum(duplicated(pdict0))
table(patternFrequency(pdict0)) # 9 patterns are repeated 3 times.
pdict0[[1]]
pdict0[[5]]

## -----
## B. NO HEAD AND A TAIL
## -----
dict1 <- c("ACNG", "GT", "CGT", "AC")
pdict1 <- PDict(dict1, tb.end=2)
pdict1
class(pdict1)
length(pdict1)
width(pdict1)
head(pdict1)
tb(pdict1)
tb.width(pdict1)
width(tb(pdict1))
tail(pdict1)
pdict1[[3]]

```

---

phiX174Phage

*Versions of bacteriophage phiX174 complete genome and sample short reads*

---

## Description

Six versions of the complete genome for bacteriophage  $\phi$  X174 as well as a small number of Solexa short reads, qualities associated with those short reads, and counts for the number times those short reads occurred.

## Details

The phiX174Phage object is a DNASTringSet containing the following six naturally occurring versions of the bacteriophage  $\phi$  X174 genome cited in Smith et al.:

**Genbank:** The version of the genome from GenBank (NC\\_001422.1, GI:9626372).

**RF70s:** A preparation of  $\phi$  X double-stranded replicative form (RF) of DNA by Clyde A. Hutchinson III from the late 1970s.

**SS78:** A preparation of  $\phi$  X virion single-stranded DNA from 1978.

**Bull:** The sequence of wild-type  $\phi$  X used by Bull et al.

**G'97:** The  $\phi$  X replicative form (RF) of DNA from Bull et al.

**NEB'03:** A  $\phi$  X replicative form (RF) of DNA from New England BioLabs (NEB).

The `srPhiX174` object is a `DNAStrngSet` containing short reads from a Solexa machine.

The `quPhiX174` object is a `BStringSet` containing Solexa quality scores associated with `srPhiX174`.

The `wtPhiX174` object is an integer vector containing counts associated with `srPhiX174`.

## References

[http://www.genome.jp/dbget-bin/www\\_bget?refseq+NC\\_001422](http://www.genome.jp/dbget-bin/www_bget?refseq+NC_001422)

Bull, J. J., Badgett, M. R., Wichman, H. A., Huelsenbeck, Hillis, D. M., Gulati, A., Ho, C. & Molineux, J. (1997) *Genetics* 147, 1497-1507.

Smith, Hamilton O.; Clyde A. Hutchison, Cynthia Pfannkoch, J. Craig Venter (2003-12-23). "Generating a synthetic genome by whole genome assembly: {phi}X174 bacteriophage from synthetic oligonucleotides". *Proceedings of the National Academy of Sciences* 100 (26): 15440-15445. doi:10.1073/pnas.2237126100.

## Examples

```
data(phiX174Phage)
nchar(phiX174Phage)
genBankPhage <- phiX174Phage[[1]]
genBankSubstring <- substring(genBankPhage, 2793-34, 2811+34)

data(srPhiX174)
srPhiX174
quPhiX174
summary(wtPhiX174)

alignPhiX174 <-
  pairwiseAlignment(srPhiX174, genBankSubstring,
                    patternQuality = SolexaQuality(quPhiX174),
                    subjectQuality = SolexaQuality(99L),
                    type = "global-local")
summary(alignPhiX174, weight = wtPhiX174)
```

---

pid

*Percent Sequence Identity*

---

## Description

Calculates the percent sequence identity for a pairwise sequence alignment.

## Usage

```
pid(x, type="PID1")
```

## Arguments

`x` a `PairwiseAlignments` object.

`type` one of percent sequence identity. One of "PID1", "PID2", "PID3", and "PID4". See Details for more information.

## Details

Since there is no universal definition of percent sequence identity, the pid function calculates this statistic in the following types:

"PID1":  $100 * (\text{identical positions}) / (\text{aligned positions} + \text{internal gap positions})$

"PID2":  $100 * (\text{identical positions}) / (\text{aligned positions})$

"PID3":  $100 * (\text{identical positions}) / (\text{length shorter sequence})$

"PID4":  $100 * (\text{identical positions}) / (\text{average length of the two sequences})$

## Value

A numeric vector containing the specified sequence identity measures.

## Author(s)

P. Aboyoun

## References

A. May, Percent Sequence Identity: The Need to Be Explicit, *Structure* 2004, 12(5):737.

G. Raghava and G. Barton, Quantification of the variation in percentage identity for protein sequence alignments, *BMC Bioinformatics* 2006, 7:415.

## See Also

[pairwiseAlignment](#), [PairwiseAlignments-class](#), [match-utils](#)

## Examples

```
s1 <- DNASTring("AGTATAGATGATAGAT")
s2 <- DNASTring("AGTAGATAGATGGATGATAGATA")

palign1 <- pairwiseAlignment(s1, s2)
palign1
pid(palign1)

palign2 <-
  pairwiseAlignment(s1, s2,
    substitutionMatrix =
      nucleotideSubstitutionMatrix(match = 2, mismatch = 10, baseOnly = TRUE))
palign2
pid(palign2, type = "PID4")
```

---

`pmatchPattern`                      *Longest Common Prefix/Suffix/Substring searching functions*

---

### Description

Functions for searching the Longest Common Prefix/Suffix/Substring of two strings.

WARNING: These functions are experimental and might not work properly! Full documentation will come later.

Please send questions/comments to [hpages@fhcrc.org](mailto:hpages@fhcrc.org)

Thanks for your comprehension!

### Usage

```
lcprefix(s1, s2)
lcsuffix(s1, s2)
lcsubstr(s1, s2)
pmatchPattern(pattern, subject, maxlength.out=1L)
```

### Arguments

<code>s1</code>	1st string, a character string or an <a href="#">XString</a> object.
<code>s2</code>	2nd string, a character string or an <a href="#">XString</a> object.
<code>pattern</code>	The pattern string.
<code>subject</code>	An <a href="#">XString</a> object containing the subject string.
<code>maxlength.out</code>	The maximum length of the output i.e. the maximum number of views in the returned object.

### See Also

[matchPattern](#), [XStringViews-class](#), [XString-class](#)

---

QualityScaledXStringSet-class  
*QualityScaledBStringSet, QualityScaledDNAStrngSet, QualityScaledRNAStrngSet and QualityScaledAAStrngSet objects*

---

### Description

The [QualityScaledBStringSet](#) class is a container for storing a [BStringSet](#) object with an [XStringQuality](#) object.

Similarly, the [QualityScaledDNAStrngSet](#) (or [QualityScaledRNAStrngSet](#), or [QualityScaledAAStrngSet](#)) class is a container for storing a [DNAStrngSet](#) (or [RNAStrngSet](#), or [AAStrngSet](#)) objects with an [XStringQuality](#) object.



**Usage**

```
## Constructors:  
QualityScaledBStringSet(x, quality)  
QualityScaledDNAStrngSet(x, quality)  
QualityScaledRNAStrngSet(x, quality)  
QualityScaledAAStringSet(x, quality)
```

**Arguments**

x                    Either a character vector, or an [XString](#), [XStringSet](#) or [XStringViews](#) object.  
quality             An [XStringQuality](#) object.

**Details**

The [QualityScaledBStringSet](#), [QualityScaledDNAStrngSet](#), [QualityScaledRNAStrngSet](#) and [QualityScaledAAStringSet](#) functions are constructors that can be used to "naturally" turn x into an [QualityScaledXStringSet](#) object of the desired base type.

**Accessor methods**

The [QualityScaledXStringSet](#) class derives from the [XStringSet](#) class hence all the accessor methods defined for an [XStringSet](#) object can also be used on an [QualityScaledXStringSet](#) object. Common methods include (in the code snippets below, x is an [QualityScaledXStringSet](#) object):

`length(x)`: The number of sequences in x.

`width(x)`: A vector of non-negative integers containing the number of letters for each element in x.

`nchar(x)`: The same as `width(x)`.

`names(x)`: NULL or a character vector of the same length as x containing a short user-provided description or comment for each element in x.

`quality(x)`: The quality of the strings.

**Subsetting and appending**

In the code snippets below, x and values are [XStringSet](#) objects, and i should be an index specifying the elements to extract.

`x[i]`: Return a new [QualityScaledXStringSet](#) object made of the selected elements.

**Author(s)**

P. Aboyoun

**See Also**

[BStringSet-class](#), [DNAStrngSet-class](#), [RNAStrngSet-class](#), [AAStringSet-class](#), [XStringQuality-class](#)

**Examples**

```
x1 <- DNASTringSet(c("TTGA", "CTCN"))
q1 <- PhredQuality(c("++,-", "6789"))
qx1 <- QualityScaledDNASTringSet(x1, q1)
qx1
```

---

 replaceAt

*Extract/replace arbitrary substrings from/in a string or set of strings.*


---

**Description**

extractAt extracts multiple subsequences from **XString** object x, or from the individual sequences of **XStringSet** object x, at the ranges of positions specified thru at.

replaceAt performs multiple subsequence replacements (a.k.a. substitutions) in **XString** object x, or in the individual sequences of **XStringSet** object x, at the ranges of positions specified thru at.

**Usage**

```
extractAt(x, at)
replaceAt(x, at, value="")
```

**Arguments**

- x                    An **XString** or **XStringSet** object.
- at                    Typically a **Ranges** object if x is an **XString** object, and a **RangesList** object if x is an **XStringSet** object.
- Alternatively, the ranges can be specified with only 1 number per range (its start position), in which case they are considered to be empty ranges (a.k.a. zero-width ranges). So if at is a numeric vector, an **IntegerList** object, or a list of numeric vectors, each number in it is interpreted as the start position of a zero-width range. This is useful when using replaceAt to perform insertions.
- The following applies only if x is an **XStringSet** object:
- at is recycled to the length of x if necessary. If at is a **Ranges** object (or a numeric vector), it is first turned into a **RangesList** object of length 1 and then this **RangesList** object is recycled to the length of x. This is useful for specifying the same ranges across all sequences in x. The *effective shape* of at is described by its length together with the lengths of its list elements *after* recycling.
- As a special case, extractAt accepts at and value to be both of length 0, in which case it just returns x unmodified (no-op).
- value                The replacement sequences.
- If x is an **XString** object, value is typically a character vector or an **XStringSet** object that is recycled to the length of at (if necessary).
- If x is an **XStringSet** object, value is typically a list of character vectors or a **CharacterList** or **XStringSetList** object. If necessary, it is recycled "vertically" first and then "horizontally" to bring it into the *effective shape* of at (see above).

"Vertical recycling" is the usual recycling whereas "horizontal recycling" recycles the individual list elements .

As a special case, `extractAt` accepts `at` and `value` to be both of length 0, in which case it just returns `x` unmodified (no-op).

### Value

For `extractAt`: An `XStringSet` object of the same length as `at` if `x` is an `XString` object. An `XStringSetList` object of the same length as `x` (and same *effective shape* as `at`) if `x` is an `XStringSet` object.

For `replaceAt`: An object of the same class as `x`. If `x` is an `XStringSet` object, its length and names and metadata columns are preserved.

### Author(s)

H. Pages

### See Also

- The `subseq` and `subseq<-` functions in the `XVector` package for simpler forms of subsequence extractions or replacements.
- The `replaceLetterAt` function for a DNA-specific single-letter replacement functions useful for SNP injections.
- The `padAndClip` function for padding and clipping strings.
- The `XString`, `XStringSet`, and `XStringSetList` classes.
- The `Ranges`, `RangesList`, `IntegerList`, and `CharacterList` classes in the `IRanges` package.

### Examples

```
## -----
## (A) ON AN XString OBJECT
## -----
x <- BString("abcdefghijklm")

at1 <- IRanges(5:1, width=3)
extractAt(x, at1)
names(at1) <- LETTERS[22:26]
extractAt(x, at1)

at2 <- IRanges(c(1, 5, 12), c(3, 4, 12), names=c("X", "Y", "Z"))
extractAt(x, at2)
extractAt(x, rev(at2))

value <- c("+", "-", "*")
replaceAt(x, at2, value=value)
replaceAt(x, rev(at2), value=rev(value))

at3 <- IRanges(c(14, 1, 1, 1, 1, 11), c(13, 0, 10, 0, 0, 10))
value <- 1:6
```

```

replaceAt(x, at3, value=value)          # "24536klm1"
replaceAt(x, rev(at3), value=rev(value)) # "54236klm1"

## Deletions:
stopifnot(replaceAt(x, at2) == "defghijklm")
stopifnot(replaceAt(x, rev(at2)) == "defghijklm")
stopifnot(replaceAt(x, at3) == "klm")
stopifnot(replaceAt(x, rev(at3)) == "klm")

## Insertions:
at4 <- IRanges(c(6, 10, 2, 5), width=0)
stopifnot(replaceAt(x, at4, value="-") == "a-bcd-e-fghi-jklm")
stopifnot(replaceAt(x, start(at4), value="-") == "a-bcd-e-fghi-jklm")
at5 <- c(5, 1, 6, 5) # 2 insertions before position 5
replaceAt(x, at5, value=c("+", "-", "*", "/"))

## No-ops:
stopifnot(replaceAt(x, NULL, value=NULL) == x)
stopifnot(replaceAt(x, at2, value=extractAt(x, at2)) == x)
stopifnot(replaceAt(x, at3, value=extractAt(x, at3)) == x)
stopifnot(replaceAt(x, at4, value=extractAt(x, at4)) == x)
stopifnot(replaceAt(x, at5, value=extractAt(x, at5)) == x)

## The order of successive transformations matters:
## T1: insert "+" before position 1 and 4
## T2: insert "-" before position 3

## T1 followed by T2
x2a <- replaceAt(x, c(1, 4), value="+")
x3a <- replaceAt(x2a, 3, value="-")

## T2 followed by T1
x2b <- replaceAt(x, 3, value="-")
x3b <- replaceAt(x2b, c(1, 4), value="+")

## T1 and T2 simultaneously:
x3c <- replaceAt(x, c(1, 3, 4), value=c("+", "-", "+"))

## ==> x3a, x3b, and x3c are all different!

## Append "*" to x3c:
replaceAt(x3c, length(x3c) + 1L, value="*")

## -----
## (B) ON AN XStringSet OBJECT
## -----
x <- BStringSet(c(seq1="ABCD", seq2="abcdefghijk", seq3="XYZ"))

at5 <- IRangesList(IRanges(c(2, 1), c(3, 0)),
                  IRanges(c(7, 2, 12, 7), c(6, 5, 11, 8)),
                  IRanges(2, 2))
## Set inner names on at5.
unlisted_at5 <- unlist(at5)

```

```

names(unlisted_at5) <-
  paste0("rg", sprintf("%02d", seq_along(unlisted_at5)))
at5 <- relist(unlisted_at5, at5)

extractAt(x, at5) # same as as(mapply(extractAt, x, at5), "List")
extractAt(x, at5[3]) # same as as(mapply(extractAt, x, at5[3]), "List")

replaceAt(x, at5, value=extractAt(x, at5)) # no-op
replaceAt(x, at5) # deletions

at6 <- IRangesList(IRanges(1:5, width=0),
  IRanges(c(6, 8, 10, 7, 2, 5),
    width=c(0, 2, 0, 0, 0, 0)),
  IRanges(c(1, 2, 1), width=c(0, 1, 0)))
replaceAt(x, at6, value="-")
value6 <- relist(paste0("[", seq_along(unlist(at6)), "]"), at6)
replaceAt(x, at6, value=value6)
replaceAt(x, at6, value=as(c("+", "-", "*"), "List"))

## Append "*" to all sequences:
replaceAt(x, as(width(x) + 1L, "List"), value="*")

## -----
## (C) ADVANCED EXAMPLES
## -----
library(hgu95av2probe)
probes <- DNASTringSet(hgu95av2probe)

## Split the probes in 5-mer chunks:
at <- successiveIRanges(rep(5, 5))
extractAt(probes, at)

## Replace base 13 by its complement:
at <- IRanges(13, width=1)
base13 <- extractAt(probes, at)
base13comp <- relist(complement(unlist(base13)), base13)
replaceAt(probes, at, value=base13comp)
## See ?xscat for a more efficient way to do this.

## Replace all the occurrences of a given pattern with another pattern:
midx <- vmatchPattern("VCGTT", probes, fixed=FALSE)
matches <- extractAt(probes, midx)
unlist(matches)
unique(unlist(matches))
probes2 <- replaceAt(probes, midx, value="--+-")

## See strings with 2 or more substitutions:
probes2[elementLengths(midx) >= 2]

## 2 sanity checks:
stopifnot(all(replaceAt(probes, midx, value=matches) == probes))
probes2b <- gsub("[ACG]CGTT", "--+-", as.character(probes))
stopifnot(identical(as.character(probes2), probes2b))

```

---

replaceLetterAt	<i>Replacing letters in a sequence (or set of sequences) at some specified locations</i>
-----------------	--

---

### Description

replaceLetterAt first makes a copy of a sequence (or set of sequences) and then replaces some of the original letters by new letters at the specified locations.

.inplaceReplaceLetterAt is the IN PLACE version of replaceLetterAt: it will modify the original sequence in place i.e. without copying it first. Note that in place modification of a sequence is fundamentally dangerous because it alters all objects defined in your session that make reference to the modified sequence. NEVER use .inplaceReplaceLetterAt, unless you know what you are doing!

### Usage

```
replaceLetterAt(x, at, letter, if.not.extending="replace", verbose=FALSE)
```

```
## NEVER USE THIS FUNCTION!
```

```
.inplaceReplaceLetterAt(x, at, letter)
```

### Arguments

x	A <a href="#">DNAStrng</a> or rectangular <a href="#">DNAStrngSet</a> object.
at	The locations where the replacements must occur. If x is a <a href="#">DNAStrng</a> object, then at is typically an integer vector with no NAs but a logical vector or <a href="#">Rle</a> object is valid too. Locations can be repeated and in this case the last replacement to occur at a given location prevails. If x is a rectangular <a href="#">DNAStrngSet</a> object, then at must be a matrix of logicals with the same dimensions as x.
letter	The new letters. If x is a <a href="#">DNAStrng</a> object, then letter must be a <a href="#">DNAStrng</a> object or a character vector (with no NAs) with a total number of letters (sum(nchar(letter))) equal to the number of locations specified in at. If x is a rectangular <a href="#">DNAStrngSet</a> object, then letter must be a <a href="#">DNAStrngSet</a> object or a character vector of the same length as x. In addition, the number of letters in each element of letter must match the number of locations specified in the corresponding row of at (all(width(letter) == rowSums(at))).
if.not.extending	What to do if the new letter is not "extending" the old letter? The new letter "extends" the old letter if both are IUPAC letters and the new letter is as specific or less specific than the old one (e.g. M extends A, Y extends Y, but Y doesn't extend S). Possible values are "replace" (the default) for replacing in all cases, "skip" for not replacing when the new letter does not extend the old letter, "merge" for merging the new IUPAC letter with the old one, and "error" for raising an error.

Note that the gap ("-") and hard masking ("+") letters are not extending or extended by any other letter.

Also note that "merge" is the only value for the `if.not.extending` argument that guarantees the final result to be independent on the order the replacement is performed (although this is only relevant when `at` contains duplicated locations, otherwise the result is of course always independent on the order, whatever the value of `if.not.extending` is).

`verbose` When TRUE, a warning will report the number of skipped or merged letters.

### Details

`.inplaceReplaceLetterAt` semantic is equivalent to calling `replaceLetterAt` with `if.not.extending="merge"` and `verbose=FALSE`.

Never use `.inplaceReplaceLetterAt`! It is used by the `injectSNPs` function in the `BSgenome` package, as part of the "lazy sequence loading" mechanism, for altering the original sequences of a `BSgenome` object at "sequence-load time". This alteration consists in injecting the IUPAC ambiguity letters representing the SNPs into the just loaded sequence, which is the only time where in place modification of the external data of an `XString` object is safe.

### Value

A `DNASTring` or `DNASTringSet` object of the same shape (i.e. length and width) as the original object `x` for `replaceLetterAt`.

### Author(s)

H. Pages

### See Also

- The `replaceAt` function for extracting or replacing arbitrary subsequences from/in a sequence or set of sequences.
- `IUPAC_CODE_MAP` for the mapping between IUPAC nucleotide ambiguity codes and their meaning.
- The `chartr` and `injectHardMask` functions.
- The `DNASTring` and `DNASTringSet` class.
- The `injectSNPs` function and the `BSgenome` class in the `BSgenome` package.

### Examples

```
## Replace letters of a DNASTring object:
replaceLetterAt(DNASTring("AAMAA"), c(5, 1, 3, 1), "TYNC")
replaceLetterAt(DNASTring("AAMAA"), c(5, 1, 3, 1), "TYNC", if.not.extending="merge")

## Replace letters of a DNASTringSet object (sorry for the totally
## artificial example with absolutely no biological meaning):
library(drosophila2probe)
probes <- DNASTringSet(drosophila2probe)
```

```

at <- matrix(c(TRUE, TRUE, FALSE, FALSE, FALSE, TRUE, FALSE, FALSE),
            nrow=length(probes), ncol=width(probes)[1],
            byrow=TRUE)
letter_subject <- DNASTring(paste(rep.int("-", width(probes)[1]), collapse=""))
letter <- as(Views(letter_subject, start=1, end=rowSums(at)), "XStringSet")
replaceLetterAt(probes, at, letter)

```

---

reverseComplement	<i>Sequence reversing and complementing</i>
-------------------	---

---

## Description

Use these functions for reversing sequences and/or complementing DNA or RNA sequences.

## Usage

```

complement(x, ...)
reverseComplement(x, ...)

```

## Arguments

x	A <a href="#">DNASTring</a> , <a href="#">RNAString</a> , <a href="#">DNASTringSet</a> , <a href="#">RNAStringSet</a> , <a href="#">XStringViews</a> (with <a href="#">DNASTring</a> or <a href="#">RNAString</a> subject), <a href="#">MaskedDNASTring</a> or <a href="#">MaskedRNAString</a> object for complement and reverseComplement.
...	Additional arguments to be passed to or from methods.

## Details

See [?reverse](#) for reversing an [XString](#), [XStringSet](#) or [XStringViews](#) object.

If x is a [DNASTring](#) or [RNAString](#) object, complement(x) returns an object where each base in x is "complemented" i.e. A, C, G, T in a [DNASTring](#) object are replaced by T, G, C, A respectively and A, C, G, U in a [RNAString](#) object are replaced by U, G, C, A respectively.

Letters belonging to the IUPAC Extended Genetic Alphabet are also replaced by their complement (M <-> K, R <-> Y, S <-> S, V <-> B, W <-> W, H <-> D, N <-> N) and the gap ("-") and hard masking ("+") letters are unchanged.

reverseComplement(x) is equivalent to reverse(complement(x)) but is faster and more memory efficient.

## Value

An object of the same class and length as the original object.

## See Also

[reverse](#), [DNASTring-class](#), [RNAString-class](#), [DNASTringSet-class](#), [RNAStringSet-class](#), [XStringViews-class](#), [MaskedXString-class](#), [chartr](#), [findPalindromes](#), [IUPAC\\_CODE\\_MAP](#)



**Examples**

```

## -----
## A. SOME SIMPLE EXAMPLES
## -----

x <- DNASTring("ACGT-YN-")
reverseComplement(x)

library(drosophila2probe)
probes <- DNASTringSet(drosophila2probe)
probes
alphabetFrequency(probes, collapse=TRUE)
rcprobes <- reverseComplement(probes)
rcprobes
alphabetFrequency(rcprobes, collapse=TRUE)

## -----
## B. OBTAINING THE MISMATCH PROBES OF A CHIP
## -----

pm2mm <- function(probes)
{
  probes <- DNASTringSet(probes)
  subseq(probes, start=13, end=13) <- complement(subseq(probes, start=13, end=13))
  probes
}
mmprobes <- pm2mm(probes)
mmprobes
alphabetFrequency(mmprobes, collapse=TRUE)

## -----
## C. SEARCHING THE MINUS STRAND OF A CHROMOSOME
## -----
## Applying reverseComplement() to the pattern before calling
## matchPattern() is the recommended way of searching hits on the
## minus strand of a chromosome.

library(BSgenome.Dmelanogaster.UCSC.dm3)
chrX <- Dmelanogaster$chrX
pattern <- DNASTring("ACCAACNNGGTTG")
matchPattern(pattern, chrX, fixed=FALSE) # 3 hits on strand +
rcpattern <- reverseComplement(pattern)
rcpattern
m0 <- matchPattern(rcpattern, chrX, fixed=FALSE)
m0 # 5 hits on strand -

## Applying reverseComplement() to the subject instead of the pattern is not
## a good idea for 2 reasons:
## (1) Chromosome sequences are generally big and sometimes very big
##     so computing the reverse complement of the positive strand will
##     take time and memory proportional to its length.
chrXminus <- reverseComplement(chrX) # needs to allocate 22M of memory!

```

```

chrXminus
## (2) Chromosome locations are generally given relatively to the positive
## strand, even for features located in the negative strand, so after
## doing this:
m1 <- matchPattern(pattern, chrXminus, fixed=FALSE)
## the start/end of the matches are now relative to the negative strand.
## You need to apply reverseComplement() again on the result if you want
## them to be relative to the positive strand:
m2 <- reverseComplement(m1) # allocates 22M of memory, again!
## and finally to apply rev() to sort the matches from left to right
## (53 direction) like in m0:
m3 <- rev(m2) # same as m0, finally!

## WARNING: Before you try the example below on human chromosome 1, be aware
## that it will require the allocation of about 500Mb of memory!
if (interactive()) {
  library(BSgenome.Hsapiens.UCSC.hg18)
  chr1 <- Hsapiens$chr1
  matchPattern(pattern, reverseComplement(chr1)) # DONT DO THIS!
  matchPattern(reverseComplement(pattern), chr1) # DO THIS INSTEAD
}

```

---

RNAString-class

*RNAString objects*


---

## Description

An RNAString object allows efficient storage and manipulation of a long RNA sequence.

## Details

The RNAString class is a direct [XString](#) subclass (with no additional slot). Therefore all functions and methods described in the [XString](#) man page also work with an RNAString object (inheritance).

Unlike the [BString](#) container that allows storage of any single string (based on a single-byte character set) the RNAString container can only store a string based on the RNA alphabet (see below). In addition, the letters stored in an RNAString object are encoded in a way that optimizes fast search algorithms.

## The RNA alphabet

This alphabet contains all letters from the IUPAC Extended Genetic Alphabet (see [?IUPAC\\_CODE\\_MAP](#)) where "T" is replaced by "U" + the gap ("-") and the hard masking ("+") letters. It is stored in the RNA\_ALPHABET constant (character vector). The alphabet method also returns RNA\_ALPHABET when applied to an RNAString object and is provided for convenience only.

### Constructor-like functions and generics

In the code snippet below, `x` can be a single string (character vector of length 1), a [BString](#) object or a [DNAString](#) object.

```
RNAString(x="", start=1, nchar=NA): Tries to convert x into an RNAString object by reading nchar letters starting at position start in x.
```

### Accessor methods

In the code snippet below, `x` is an `RNAString` object.

```
alphabet(x, baseOnly=FALSE): If x is an RNAString object, then return the RNA alphabet (see above). See the corresponding man pages when x is a BString, DNAString or AAString object.
```

### Author(s)

H. Pages

### See Also

[IUPAC\\_CODE\\_MAP](#), [letter](#), [XString-class](#), [DNAString-class](#), [reverseComplement](#), [alphabetFrequency](#)

### Examples

```
RNA_BASES
RNA_ALPHABET
d <- DNAString("TTGAAAA-CTC-N")
r <- RNAString(d)
r
alphabet(r) # RNA_ALPHABET
alphabet(r, baseOnly=TRUE) # RNA_BASES

## When comparing an RNAString object with a DNAString object,
## U and T are considered equals:
r == d # TRUE
```

---

stringDist

*String Distance/Alignment Score Matrix*

---

### Description

Computes the Levenshtein edit distance or pairwise alignment score matrix for a set of strings.

**Usage**

```
stringDist(x, method = "levenshtein", ignoreCase = FALSE, diag = FALSE, upper = FALSE, ...)
## S4 method for signature XStringSet
stringDist(x, method = "levenshtein", ignoreCase = FALSE, diag = FALSE,
           upper = FALSE, type = "global", quality = PhredQuality(22L),
           substitutionMatrix = NULL, fuzzyMatrix = NULL, gapOpening = 0,
           gapExtension = -1)
## S4 method for signature QualityScaledXStringSet
stringDist(x, method = "quality", ignoreCase = FALSE,
           diag = FALSE, upper = FALSE, type = "global", substitutionMatrix = NULL,
           fuzzyMatrix = NULL, gapOpening = 0, gapExtension = -1)
```

**Arguments**

x	a character vector or an <a href="#">XStringSet</a> object.
method	calculation method. One of "levenshtein", "hamming", "quality", or "substitutionMatrix".
ignoreCase	logical value indicating whether to ignore case during scoring.
diag	logical value indicating whether the diagonal of the matrix should be printed by <code>print.dist</code> .
upper	logical value indicating whether the upper triangle of the matrix should be printed by <code>print.dist</code> .
type	(applicable when <code>method = "quality"</code> or <code>method = "substitutionMatrix"</code> ). type of alignment. One of "global", "local", and "overlap", where "global" = align whole strings with end gap penalties, "local" = align string fragments, "overlap" = align whole strings without end gap penalties.
quality	(applicable when <code>method = "quality"</code> ). object of class <a href="#">XStringQuality</a> representing the quality scores for x that are used in a quality-based method for generating a substitution matrix.
substitutionMatrix	(applicable when <code>method = "substitutionMatrix"</code> ). symmetric matrix representing the fixed substitution scores in the alignment.
fuzzyMatrix	(applicable when <code>method = "quality"</code> ). fuzzy match matrix for quality-based alignments. It takes values between 0 and 1; where 0 is an unambiguous mismatch, 1 is an unambiguous match, and values in between represent a fraction of "matchiness".
gapOpening	(applicable when <code>method = "quality"</code> or <code>method = "substitutionMatrix"</code> ). penalty for opening a gap in the alignment.
gapExtension	(applicable when <code>method = "quality"</code> or <code>method = "substitutionMatrix"</code> ). penalty for extending a gap in the alignment
...	optional arguments to generic function to support additional methods.

**Details**

When `method = "hamming"`, uses the underlying `neditStartingAt` code to calculate the distances, where the Hamming distance is defined as the number of substitutions between two strings

of equal length. Otherwise, uses the underlying pairwiseAlignment code to compute the distance/alignment score matrix.

**Value**

Returns an object of class "dist".

**Author(s)**

P. Aboyoun

**See Also**

[dist](#), [agrep](#), [pairwiseAlignment](#), [substitution.matrices](#)

**Examples**

```
stringDist(c("lazy", "HaZy", "crAZy"))
stringDist(c("lazy", "HaZy", "crAZy"), ignoreCase = TRUE)

data(phiX174Phage)
plot(hclust(stringDist(phiX174Phage), method = "single"))

data(srPhiX174)
stringDist(srPhiX174[1:4])
stringDist(srPhiX174[1:4], method = "quality",
           quality = SolexaQuality(quPhiX174[1:4]),
           gapOpening = -10, gapExtension = -4)
```

---

substitution.matrices *Scoring matrices*

---

**Description**

Predefined substitution matrices for nucleotide and amino acid alignments.

**Usage**

```
data(BLOSUM45)
data(BLOSUM50)
data(BLOSUM62)
data(BLOSUM80)
data(BLOSUM100)
data(PAM30)
data(PAM40)
data(PAM70)
data(PAM120)
data(PAM250)
nucleotideSubstitutionMatrix(match = 1, mismatch = 0, baseOnly = FALSE, type = "DNA")
```

```
qualitySubstitutionMatrices(fuzzyMatch = c(0, 1), alphabetLength = 4L, qualityClass = "PhredQuality",
errorSubstitutionMatrices(errorProbability, fuzzyMatch = c(0, 1), alphabetLength = 4L, bitScale = 1)
```

### Arguments

match	the scoring for a nucleotide match.
mismatch	the scoring for a nucleotide mismatch.
baseOnly	TRUE or FALSE. If TRUE, only uses the letters in the "base" alphabet i.e. "A", "C", "G", "T".
type	either "DNA" or "RNA".
fuzzyMatch	a named or unnamed numeric vector representing the base match probability.
errorProbability	a named or unnamed numeric vector representing the error probability.
alphabetLength	an integer representing the number of letters in the underlying string alphabet. For DNA and RNA, this would be 4L. For Amino Acids, this could be 20L.
qualityClass	a character string of "PhredQuality", "SolexaQuality", or "IlluminaQuality".
bitScale	a numeric value to scale the quality-based substitution matrices. By default, this is 1, representing bit-scale scoring.

### Format

The BLOSUM and PAM matrices are square symmetric matrices with integer coefficients, whose row and column names are identical and unique: each name is a single letter representing a nucleotide or an amino acid.

nucleotideSubstitutionMatrix produces a substitution matrix for all IUPAC nucleic acid codes based upon match and mismatch parameters.

errorSubstitutionMatrices produces a two element list of numeric square symmetric matrices, one for matches and one for mismatches.

qualitySubstitutionMatrices produces the substitution matrices for Phred or Solexa quality-based reads.

### Details

The BLOSUM and PAM matrices are not unique. For example, the definition of the widely used BLOSUM62 matrix varies depending on the source, and even a given source can provide different versions of "BLOSUM62" without keeping track of the changes over time. NCBI provides many matrices here <ftp://ftp.ncbi.nih.gov/blast/matrices/> but their definitions don't match those of the matrices bundled with their stand-alone BLAST software available here <ftp://ftp.ncbi.nih.gov/blast/>. The BLOSUM45, BLOSUM62, BLOSUM80, PAM30 and PAM70 matrices were taken from NCBI stand-alone BLAST software.

The BLOSUM50, BLOSUM100, PAM40, PAM120 and PAM250 matrices were taken from <ftp://ftp.ncbi.nih.gov/blast/matrices/>.

The quality matrices computed in qualitySubstitutionMatrices are based on the paper by Ketil Malde. Let  $\epsilon_i$  be the probability of an error in the base read. For "Phred" quality measures  $Q$  in  $[0, 99]$ , these error probabilities are given by  $\epsilon_i = 10^{-Q/10}$ . For "Solexa" quality measures  $Q$  in  $[-5, 99]$ , they are given by  $\epsilon_i = 1 - 1/(1 + 10^{-Q/10})$ . Assuming independence within and between

base reads, the combined error probability of a mismatch when the underlying bases do match is  $\epsilon_c = \epsilon_1 + \epsilon_2 - (n/(n-1)) * \epsilon_1 * \epsilon_2$ , where  $n$  is the number of letters in the underlying alphabet. Using  $\epsilon_c$ , the substitution score is given by when two bases match is given by  $b * \log_2(\gamma_{x,y} * (1 - \epsilon_c) * n + (1 - \gamma_{x,y}) * \epsilon_c * (n/(n-1)))$ , where  $b$  is the bit-scaling for the scoring and  $\gamma_{x,y}$  is the probability that characters  $x$  and  $y$  represents the same underlying information (e.g. using IUPAC,  $\gamma_{A,A} = 1$  and  $\gamma_{A,N} = 1/4$ ). In the arguments listed above `fuzzyMatch` represents  $\gamma_{x,y}$  and `errorProbability` represents  $\epsilon_i$ .

### Author(s)

H. Pages and P. Aboyoun

### References

K. Malde, The effect of sequence quality on sequence alignment, Bioinformatics, Feb 23, 2008.

### See Also

[pairwiseAlignment](#), [PairwiseAlignments-class](#), [DNAString-class](#), [AAString-class](#), [PhredQuality-class](#), [SolexaQuality-class](#), [IlluminaQuality-class](#)

### Examples

```
s1 <-
  DNAString("ACTTCACCAGCTCCCTGGCGGTAAGTTGATCAAAGGAAACGCAAAGTTTTCAAG")
s2 <-
  DNAString("GTTTCACTACTTCCTTCGGGTAAGTAAATATATAAAATATATAAAATATAATTTTCATC")

## Fit a global pairwise alignment using edit distance scoring
pairwiseAlignment(s1, s2,
  substitutionMatrix = nucleotideSubstitutionMatrix(0, -1, TRUE),
  gapOpening = 0, gapExtension = -1)

## Examine quality-based match and mismatch bit scores for DNA/RNA
## strings in pairwiseAlignment.
## By default patternQuality and subjectQuality are PhredQuality(22L).
qualityMatrices <- qualitySubstitutionMatrices()
qualityMatrices["22", "22", "1"]
qualityMatrices["22", "22", "0"]

pairwiseAlignment(s1, s2)

## Get the substitution scores when the error probability is 0.1
subscores <- errorSubstitutionMatrices(errorProbability = 0.1)
submat <- matrix(subscores[,,"0"], 4, 4)
diag(submat) <- subscores[,,"1"]
dimnames(submat) <- list(DNA_ALPHABET[1:4], DNA_ALPHABET[1:4])
submat
pairwiseAlignment(s1, s2, substitutionMatrix = submat)

## Align two amino acid sequences with the BLOSUM62 matrix
aa1 <- AAString("HXBLVYMGCHFDCXVBEHIKQZ")
```

```

aa2 <- AAString("QRNYMYCFQCISGNEYKQN")
pairwiseAlignment(aa1, aa2, substitutionMatrix = "BLOSUM62", gapOpening = -3, gapExtension = -1)

## See how the gap penalty influences the alignment
pairwiseAlignment(aa1, aa2, substitutionMatrix = "BLOSUM62", gapOpening = -6, gapExtension = -2)

## See how the substitution matrix influences the alignment
pairwiseAlignment(aa1, aa2, substitutionMatrix = "BLOSUM50", gapOpening = -3, gapExtension = -1)

if (interactive()) {
  ## Compare our BLOSUM62 with BLOSUM62 from ftp://ftp.ncbi.nih.gov/blast/matrices/
  data(BLOSUM62)
  BLOSUM62["Q", "Z"]
  file <- "ftp://ftp.ncbi.nih.gov/blast/matrices/BLOSUM62"
  b62 <- as.matrix(read.table(file, check.names=FALSE))
  b62["Q", "Z"]
}

```

---

toComplex

*Turning a DNA sequence into a vector of complex numbers*


---

### Description

The toComplex utility function turns a [DNAStrng](#) object into a complex vector.

### Usage

```
toComplex(x, baseValues)
```

### Arguments

x	A <a href="#">DNAStrng</a> object.
baseValues	A named complex vector containing the values associated to each base e.g. <code>c(A=1+0i, G=0+1i, T=-1+0i, C=0-1i)</code>

### Value

A complex vector of the same length as x.

### Author(s)

H. Pages

### See Also

[DNAStrng](#)



**Examples**

```
seq <- DNASTring("accacctgaccattgtcct")
baseValues1 <- c(A=1+0i, G=0+1i, T=-1+0i, C=0-1i)
toComplex(seq, baseValues1)

## GC content:
baseValues2 <- c(A=0, C=1, G=1, T=0)
sum(as.integer(toComplex(seq, baseValues2)))
## Note that there are better ways to do this (see ?alphabetFrequency)
```

---

translate

*DNA/RNA transcription and translation*


---

**Description**

Functions for transcription and/or translation of DNA or RNA sequences, and related utilities.

**Usage**

```
## Transcription:
transcribe(x)
cDNA(x)

## Translation:
codons(x)
translate(x)

## Related utilities:
dna2rna(x)
rna2dna(x)
```

**Arguments**

x            A [DNASTring](#) object for transcribe and dna2rna.  
              An [RNAString](#) object for cDNA and rna2dna.  
              A [DNASTring](#), [RNAString](#), [MaskedDNASTring](#) or [MaskedRNAString](#) object for  
              codons.  
              A [DNASTring](#), [RNAString](#), [DNASTringSet](#), [RNAStringSet](#), [MaskedDNASTring](#)  
              or [MaskedRNAString](#) object for translate.

**Details**

transcribe reproduces the biological process of DNA transcription that occurs in the cell. It takes the naive approach to treat the whole sequence x as if it was a single exon. See [extractTranscripts](#) for a more powerful version that allows the user to extract a set of transcripts specified by the starts and ends of their exons as well as the strand from which the transcript is coming.

cDNA reproduces the process of synthesizing complementary DNA from a mature mRNA template.

translate reproduces the biological process of RNA translation that occurs in the cell. The input of the function can be either RNA or coding DNA. The Standard Genetic Code (see ?GENETIC\_CODE) is used to translate codons into amino acids. codons is a utility for extracting the codons involved in this translation without translating them.

dna2rna and rna2dna are low-level utilities for converting sequences from DNA to RNA and vice-versa. All what this conversion does is to replace each occurrence of T by a U and vice-versa.

### Value

An [RNAString](#) object for transcribe and dna2rna.

A [DNAString](#) object for cDNA and rna2dna.

Note that if the sequence passed to transcribe or cDNA is considered to be oriented 5'-3', then the returned sequence is oriented 3'-5'.

An [XStringViews](#) object with 1 view per codon for codons. When x is a [MaskedDNAString](#) or [MaskedRNAString](#) object, its masked parts are interpreted as introns and filled with the + letter in the returned object. Therefore codons that span across masked regions are represented by views that have a width > 3 and contain the + letter. Note that each view is guaranteed to contain exactly 3 base letters.

An [AAString](#) object for translate.

### See Also

[reverseComplement](#), [GENETIC\\_CODE](#), [DNAString-class](#), [RNAString-class](#), [AAString-class](#), [XStringSet-class](#), [XStringViews-class](#), [MaskedXString-class](#)

### Examples

```
file <- system.file("extdata", "someORF.fa", package="Biostrings")
x <- readDNAStringSet(file)
x

## The first and last 1000 nucleotides are not part of the ORFs:
x <- DNAStringSet(x, start=1001, end=-1001)

## Before calling translate() on an ORF, we need to mask the introns
## if any. We can get this information from the SGD database
## (http://www.yeastgenome.org/).
## According to SGD, the 1st ORF (YAL001C) has an intron at 71..160
## (see http://db.yeastgenome.org/cgi-bin/locus.pl?locus=YAL001C)
y1 <- x[[1]]
mask1 <- Mask(length(y1), start=71, end=160)
masks(y1) <- mask1
y1
translate(y1)

## Codons
codons(y1)
which(width(codons(y1)) != 3)
codons(y1)[20:28]
```

```

## Translation on the - strand:
dna <- DNASTringSet(c("ATC", "GCTG", "CGACT"))
translate(reverseComplement(dna))

## Translate sequences on both + and - strand across all
## possible reading frames (i.e., codon position 1, 2 or 3):
## First create a DNASTringSet of + and - strand sequences,
## removing the nucleotides prior to the reading frame start position.
dnaSubseq <- lapply(1:3, function(pos, dna)
  subseq(c(dna, reverseComplement(dna)), start=pos), dna)
## Translation of dnaSubseq produces a list of length 3, each with 6
## elements (3 + strand results followed by 3 - strand results).
lapply(dnaSubseq, translate)

## translate() throws a warning when the length of the sequence is not
## divisible by 3. To avoid this warning wrap the function in
## suppressWarnings().

```

---

trimLRPatterns

*Trim Flanking Patterns from Sequences*


---

## Description

The trimLRPatterns function trims left and/or right flanking patterns from sequences.

## Usage

```

trimLRPatterns(Lpattern = "", Rpattern = "", subject,
              max.Lmismatch = 0, max.Rmismatch = 0,
              with.Lindels = FALSE, with.Rindels = FALSE,
              Lfixed = TRUE, Rfixed = TRUE, ranges = FALSE)

```

## Arguments

Lpattern	The left pattern.
Rpattern	The right pattern.
subject	An <a href="#">XString</a> object, <a href="#">XStringSet</a> object, or character vector containing the target sequence(s).
max.Lmismatch	Either an integer vector of length $nLp = nchar(Lpattern)$ representing an absolute number of mismatches (or edit distance if with.Lindels is TRUE) or a single numeric value in the interval $[0, 1)$ representing a mismatch rate when aligning terminal substrings (suffixes) of Lpattern with the beginning (prefix) of subject following the conventions set by <a href="#">neditStartingAt</a> , <a href="#">isMatchingStartingAt</a> , etc. When max.Lmismatch is 0L or a numeric value in the interval $[0, 1)$ , it is taken as a "rate" and is converted to <code>as.integer(1:nLp * max.Lmismatch)</code> , analogous to <a href="#">agrep</a> (which, however, employs <a href="#">ceiling</a> ).

Otherwise, `max.Lmismatch` is treated as an integer vector where negative numbers are used to prevent trimming at the  $i$ -th location. When an input integer vector is shorter than `nLp`, it is augmented with enough `-1`s at the beginning to bring its length up to `nLp`. Elements of `max.Lmismatch` beyond the first `nLp` are ignored.

Once the integer vector is constructed using the rules given above, when `with.Lindels` is `FALSE`, `max.Lmismatch[i]` is the number of acceptable mismatches (errors) between the suffix substring(`Lpattern`, `nLp - i + 1`, `nLp`) of `Lpattern` and the first  $i$  letters of `subject`. When `with.Lindels` is `TRUE`, `max.Lmismatch[i]` represents the allowed "edit distance" between that suffix of `Lpattern` and `subject`, starting at position 1 of `subject` (as in [matchPattern](#) and [isMatchingStartingAt](#)). For a given element `s` of the subject, the initial segment (prefix) substring(`s`, 1, `j`) of `s` is trimmed if `j` is the largest  $i$  for which there is an acceptable match, if any.

<code>max.Rmismatch</code>	Same as <code>max.Lmismatch</code> but with <code>Rpattern</code> , along with <code>with.Rindels</code> (below), and its initial segments (prefixes) substring( <code>Rpattern</code> , 1, <code>i</code> ). For a given element <code>s</code> of the subject, with <code>nS = nchar(s)</code> , the terminal segment (suffix) substring( <code>s</code> , <code>nS - j + 1</code> , <code>nS</code> ) of <code>s</code> is trimmed if <code>j</code> is the largest $i$ for which there is an acceptable match, if any.
<code>with.Lindels</code>	If <code>TRUE</code> , indels are allowed in the alignments of the suffixes of <code>Lpattern</code> with the subject, at its beginning. See the <code>with.indels</code> arguments of the <a href="#">matchPattern</a> and <a href="#">neditStartingAt</a> functions for detailed information.
<code>with.Rindels</code>	Same as <code>with.Lindels</code> but for alignments of the prefixes of <code>Rpattern</code> with the subject, at its end. See the <code>with.indels</code> arguments of the <a href="#">matchPattern</a> and <a href="#">neditEndingAt</a> functions for detailed information.
<code>Lfixed</code> , <code>Rfixed</code>	Whether IUPAC extended letters in the left or right pattern should be interpreted as ambiguities (see <a href="#">?lowlevel-matching</a> for the details).
<code>ranges</code>	If <code>TRUE</code> , then return the ranges to use to trim subject. If <code>FALSE</code> , then returned the trimmed subject.

### Value

A new [XString](#) object, [XStringSet](#) object, or character vector with the "longest" flanking matches removed, as described above.

### Author(s)

P. Aboyoun and H. Jaffee

### See Also

[matchPattern](#), [matchLRPatterns](#), [lowlevel-matching](#), [XString-class](#), [XStringSet-class](#)

### Examples

```
Lpattern <- "TTCTGCTTG"
Rpattern <- "GATCGGAAG"
subject <- DNAStr("TTCTGCTTGACGTGATCGGA")
```

```

subjectSet <- DNASTringSet(c("TGCTTGACGGCAGATCGG", "TTCTGCTTGGATCGGAAG"))

## Only allow for perfect matches on the flanks
trimLRPatterns(Lpattern = Lpattern, subject = subject)
trimLRPatterns(Rpattern = Rpattern, subject = subject)
trimLRPatterns(Lpattern = Lpattern, Rpattern = Rpattern, subject = subjectSet)

## Allow for perfect matches on the flanking overlaps
trimLRPatterns(Lpattern = Lpattern, Rpattern = Rpattern, subject = subjectSet,
               max.Lmismatch = 0, max.Rmismatch = 0)

## Allow for mismatches on the flanks
trimLRPatterns(Lpattern = Lpattern, Rpattern = Rpattern, subject = subject,
               max.Lmismatch = 0.2, max.Rmismatch = 0.2)
maxMismatches <- as.integer(0.2 * 1:9)
maxMismatches
trimLRPatterns(Lpattern = Lpattern, Rpattern = Rpattern, subject = subjectSet,
               max.Lmismatch = maxMismatches, max.Rmismatch = maxMismatches)

## Produce ranges that can be an input into other functions
trimLRPatterns(Lpattern = Lpattern, Rpattern = Rpattern, subject = subjectSet,
               max.Lmismatch = 0, max.Rmismatch = 0, ranges = TRUE)
trimLRPatterns(Lpattern = Lpattern, Rpattern = Rpattern, subject = subject,
               max.Lmismatch = 0.2, max.Rmismatch = 0.2, ranges = TRUE)

```

---

xscat	<i>Concatenate sequences contained in XString, XStringSet and/or XStringViews objects</i>
-------	---

---

## Description

This function mimics the semantic of `paste(..., sep="")` but accepts [XString](#), [XStringSet](#) or [XStringViews](#) arguments and returns an [XString](#) or [XStringSet](#) object.

## Usage

```
xscat(...)
```

## Arguments

... One or more character vectors (with no NAs), [XString](#), [XStringSet](#) or [XStringViews](#) objects.

## Value

An [XString](#) object if all the arguments are either [XString](#) objects or character strings. An [XStringSet](#) object otherwise.

**Author(s)**

H. Pages

**See Also**[XString-class](#), [XStringSet-class](#), [XStringViews-class](#), [paste](#)**Examples**

```
## Return a BString object:
xscat(BString("abc"), BString("EF"))
xscat(BString("abc"), "EF")
xscat("abc", "EF")

## Return a BStringSet object:
xscat(BStringSet("abc"), "EF")

## Return a DNABStringSet object:
xscat(c("t", "a"), DNABString("N"))

## Arguments are recycled to the length of the longest argument:
res1a <- xscat("x", LETTERS, c("3", "44", "555"))
res1b <- paste0("x", LETTERS, c("3", "44", "555"))
stopifnot(identical(as.character(res1a), as.character(res1b)))

## Concatenating big XStringSet objects:
library(drosophila2probe)
probes <- DNABStringSet(drosophila2probe)
mm <- complement(narrow(probes, start=13, end=13))
left <- narrow(probes, end=12)
right <- narrow(probes, start=14)
xscat(left, mm, right)

## Collapsing an XStringSet (or XStringViews) object with a small
## number of elements:
probes1000 <- as.list(probes[1:1000])
y1 <- do.call(xscat, probes1000)
y2 <- do.call(c, probes1000) # slightly faster than the above
y1 == y2 # TRUE
## Note that this method wont be efficient when the number of
## elements to collapse is big (> 10000) so we need to provide a
## collapse() (or xscollapse()) function in Biostrings that will be
## efficient at doing this. Please request this on the Bioconductor
## mailing list (http://bioconductor.org/help/mailling-list/) if you
## need it.
```

**Description**

The BString class is a general container for storing a big string (a long sequence of characters) and for making its manipulation easy and efficient.

The [DNAStrng](#), [RNAString](#) and [AAString](#) classes are similar containers but with the more biology-oriented purpose of storing a DNA sequence ([DNAStrng](#)), an RNA sequence ([RNAString](#)), or a sequence of amino acids ([AAString](#)).

All those containers derive directly (and with no additional slots) from the XString virtual class.

**Details**

The 2 main differences between an XString object and a standard character vector are: (1) the data stored in an XString object are not copied on object duplication and (2) an XString object can only store a single string (see the [XStringSet](#) container for an efficient way to store a big collection of strings in a single object).

Unlike the [DNAStrng](#), [RNAString](#) and [AAString](#) containers that accept only a predefined set of letters (the alphabet), a BString object can be used for storing any single string based on a single-byte character set.

**Constructor-like functions and generics**

In the code snippet below, x can be a single string (character vector of length 1) or an XString object.

`BString(x="", start=1, nchar=NA)`: Tries to convert x into a BString object by reading nchar letters starting at position start in x.

**Accessor methods**

In the code snippets below, x is an XString object.

`alphabet(x)`: NULL for a BString object. See the corresponding man pages when x is a [DNAStrng](#), [RNAString](#) or [AAString](#) object.

`length(x)` or `nchar(x)`: Get the length of an XString object, i.e., its number of letters.

**Coercion**

In the code snippets below, x is an XString object.

`as.character(x)`: Converts x to a character string.

`toString(x)`: Equivalent to `as.character(x)`.

**Subsetting**

In the code snippets below, x is an XString object.

`x[i]`: Return a new XString object made of the selected letters (subscript i must be an NA-free numeric vector specifying the positions of the letters to select). The returned object belongs to the same class as x.

Note that, unlike `subseq`, `x[i]` does copy the sequence data and therefore will be very inefficient for extracting a big number of letters (e.g. when i contains millions of positions).

## Equality

In the code snippets below, e1 and e2 are XString objects.

e1 == e2: TRUE if e1 is equal to e2. FALSE otherwise.

Comparison between two XString objects of different base types (e.g. a BString object and a [DNAStrng](#) object) is not supported with one exception: a [DNAStrng](#) object and an [RNAS-trng](#) object can be compared (see [RNAStrng-class](#) for more details about this).

Comparison between a BString object and a character string is also supported (see examples below).

e1 != e2: Equivalent to !(e1 == e2).

## Author(s)

H. Pages

## See Also

[subseq](#), [letter](#), [DNAStrng-class](#), [RNAStrng-class](#), [AAString-class](#), [XStringSet-class](#), [XStringViews-class](#), [reverseComplement](#), [compact](#), [XVector-class](#)

## Examples

```
b <- BString("I am a BString object")
b
length(b)

## Extracting a linear subsequence:
subseq(b)
subseq(b, start=3)
subseq(b, start=-3)
subseq(b, end=-3)
subseq(b, end=-3, width=5)

## Subsetting:
b2 <- b[length(b):1]      # better done with reverse(b)

as.character(b2)

b2 == b                   # FALSE
b2 == as.character(b2)   # TRUE

## b[1:length(b)] is equal but not identical to b!
b == b[1:length(b)]      # TRUE
identical(b, 1:length(b)) # FALSE
## This is because subsetting an XString object with [ makes a copy
## of part or all its sequence data. Hence, for the resulting object,
## the internal slot containing the memory address of the sequence
## data differs from the original. This is enough for identical() to
## see the 2 objects as different.

## Compacting. As a particular type of XVector objects, XString
```



```
## objects can optionally be compacted. Compacting is done typically
## before serialization. See ?compact for more information.
```

---

XStringPartialMatches-class

*XStringPartialMatches objects*

---

### Description

WARNING: This class is currently under development and might not work properly! Full documentation will come later.

Please DO NOT TRY TO USE it for now. Thanks for your comprehension!

### Accessor methods

In the code snippets below, `x` is an XStringPartialMatches object.

`subpatterns(x)`: Not ready yet.

`pattern(x)`: Not ready yet.

### Standard generic methods

In the code snippets below, `x` is an XStringPartialMatches objects, and `i` can be a numeric or logical vector.

`x[i]`: Return a new XStringPartialMatches object made of the selected views. `i` can be a numeric vector, a logical vector, NULL or missing. The returned object has the same subject as `x`.

### Author(s)

H. Pages

### See Also

[XStringViews-class](#), [XString-class](#), [letter](#)

---

XStringQuality-class *PhredQuality, SolexaQuality and IlluminaQuality objects*

---

### Description

Objects for storing string quality measures.

### Usage

```
## Constructors:
PhredQuality(x)
SolexaQuality(x)
IlluminaQuality(x)

## alphabet and encoding
## S4 method for signature XStringQuality
alphabet(x)
## S4 method for signature XStringQuality
encoding(x)
```

### Arguments

**x** Either a character vector, [BString](#), [BStringSet](#), integer vector, or number vector of error probabilities.

### Details

[PhredQuality](#) objects store characters that are interpreted as [0 - 99] quality measures by subtracting 33 from their ASCII decimal representation (e.g. ! = 0, " = 1, \# = 2, ...). Quality measures *q* encode probabilities as  $-10 * \log_{10}(p)$ .

[SolexaQuality](#) objects store characters that are interpreted as [-5 - 99] quality measures by subtracting 64 from their ASCII decimal representation (e.g. ; = -5, < = -4, = = -3, ...). Quality measures *q* encode probabilities as  $-10 * (\log_{10}(p) - \log_{10}(1 - p))$ .

[IlluminaQuality](#) objects store characters that are interpreted as [0 - 99] quality measures by subtracting 64 from their ASCII decimal representation (e.g. @ = 0, A = 1, B = 2, ...). Quality measures *q* encode probabilities as  $-10 * \log_{10}(p)$

### Alphabet and encoding

In the code snippets below, *x* is an [XStringQuality](#) object.

`alphabet(x)`: Valid letters in this quality score; not all letters are encountered in actual sequencing runs.

`encoding(x)`: Map between letters and their corresponding integer encoding. Use `as.integer` and `as.numeric` to coerce objects to their integer and probability representations.

**Author(s)**

P. Aboyoun

**See Also**[pairwiseAlignment](#), [PairwiseAlignments-class](#), [DNAString-class](#), [BStringSet-class](#)**Examples**

```
PhredQuality(0:40)
SolexaQuality(0:40)
IlluminaQuality(0:40)

PhredQuality(seq(1e-4,0.5,length=10))
SolexaQuality(seq(1e-4,0.5,length=10))
IlluminaQuality(seq(1e-4,0.5,length=10))

x <- SolexaQuality(BStringSet(c(a="@ABC", b="abcd")))
as.matrix(x)
```

---

`XStringSet-class`*XStringSet objects*

---

**Description**

The BStringSet class is a container for storing a set of [BString](#) objects and for making its manipulation easy and efficient.

Similarly, the DNAStringSet (or RNAStringSet, or AAStringSet) class is a container for storing a set of [DNAString](#) (or [RNAString](#), or [AAString](#)) objects.

All those containers derive directly (and with no additional slots) from the XStringSet virtual class.

**Usage**

```
## Constructors:
BStringSet(x=character(), start=NA, end=NA, width=NA, use.names=TRUE)
DNAStringSet(x=character(), start=NA, end=NA, width=NA, use.names=TRUE)
RNAStringSet(x=character(), start=NA, end=NA, width=NA, use.names=TRUE)
AAStringSet(x=character(), start=NA, end=NA, width=NA, use.names=TRUE)

## Accessor-like methods:
## S4 method for signature character
width(x)
## S4 method for signature XStringSet
nchar(x, type="chars", allowNA=FALSE)

## ... and more (see below)
```

**Arguments**

<code>x</code>	Either a character vector (with no NAs), or an <a href="#">XString</a> , <a href="#">XStringSet</a> or <a href="#">XStringViews</a> object.
<code>start, end, width</code>	Either NA, a single integer, or an integer vector of the same length as <code>x</code> specifying how <code>x</code> should be "narrowed" (see <a href="#">?narrow</a> for the details).
<code>use.names</code>	TRUE or FALSE. Should names be preserved?
<code>type, allowNA</code>	Ignored.

**Details**

The `BStringSet`, `DNAStrngSet`, `RNAStrngSet` and `AAStringSet` functions are constructors that can be used to turn input `x` into an `XStringSet` object of the desired base type.

They also allow the user to "narrow" the sequences contained in `x` via proper use of the `start`, `end` and/or `width` arguments. In this context, "narrowing" means dropping a prefix or/and a suffix of each sequence in `x`. The "narrowing" capabilities of these constructors can be illustrated by the following property: if `x` is a character vector (with no NAs), or an `XStringSet` (or [XStringViews](#)) object, then the 3 following transformations are equivalent:

```
BStringSet(x, start=mystart, end=myend, width=mywidth)
subseq(BStringSet(x), start=mystart, end=myend, width=mywidth)
BStringSet(subseq(x, start=mystart, end=myend, width=mywidth))
```

Note that, besides being more convenient, the first form is also more efficient on character vectors.

**Accessor-like methods**

In the code snippets below, `x` is an `XStringSet` object.

`length(x)`: The number of sequences in `x`.

`width(x)`: A vector of non-negative integers containing the number of letters for each element in `x`. Note that `width(x)` is also defined for a character vector with no NAs and is equivalent to `nchar(x, type="bytes")`.

`names(x)`: NULL or a character vector of the same length as `x` containing a short user-provided description or comment for each element in `x`. These are the only data in an `XStringSet` object that can safely be changed by the user. All the other data are immutable! As a general recommendation, the user should never try to modify an object by accessing its slots directly.

`alphabet(x)`: Return NULL, [DNA\\_ALPHABET](#), [RNA\\_ALPHABET](#) or [AA\\_ALPHABET](#) depending on whether `x` is a `BStringSet`, `DNAStrngSet`, `RNAStrngSet` or `AAStringSet` object.

`nchar(x)`: The same as `width(x)`.

**Subsequence extraction and related transformations**

In the code snippets below, `x` is a character vector (with no NAs), or an `XStringSet` (or [XStringViews](#)) object.

`subseq(x, start=NA, end=NA, width=NA)`: Applies `subseq` on each element in `x`. See [?`subseq`](#) for the details.

Note that this is similar to what `substr` does on a character vector. However there are some noticeable differences:

- (1) the arguments are `start` and `stop` for `substr`;
- (2) the SEW interface (`start/end/width`) interface of `subseq` is richer (e.g. support for negative `start` or `end` values); and
- (3) `subseq` checks that the specified `start/end/width` values are valid i.e., unlike `substr`, it throws an error if they define "out of limits" subsequences or subsequences with a negative width.

`narrow(x, start=NA, end=NA, width=NA, use.names=TRUE)`: Same as `subseq`. The only differences are: (1) `narrow` has a `use.names` argument; and (2) all the things `narrow` and `subseq` work on ([IRanges](#), [XStringSet](#) or [XStringViews](#) objects for `narrow`, [XVector](#) or [XStringSet](#) objects for `subseq`). But they both work and do the same thing on an [XStringSet](#) object.

`threebands(x, start=NA, end=NA, width=NA)`: Like the method for [IRanges](#) objects, the `threebands` methods for character vectors and [XStringSet](#) objects extend the capability of `narrow` by returning the 3 set of subsequences (the left, middle and right subsequences) associated to the narrowing operation. See [?`threebands`](#) in the [IRanges](#) package for the details.

`subseq(x, start=NA, end=NA, width=NA) <- value`: A vectorized version of the `subseq<-` method for [XVector](#) objects. See [?`subseq<-`](#) for the details.

### Subsetting and appending

In the code snippets below, `x` and `values` are [XStringSet](#) objects, and `i` should be an index specifying the elements to extract.

`x[i]`: Return a new [XStringSet](#) object made of the selected elements.

`x[[i]]`: Extract the `i`-th [XString](#) object from `x`.

`append(x, values, after=length(x))`: Add sequences in `values` to `x`.

### Set operations

In the code snippets below, `x` and `y` are [XStringSet](#) objects

`union(x, y, ...)`: Union of `x` and `y`.

`intersect(x, y, ...)`: Intersection of `x` and `y`.

`setdiff(x, y, ...)`: Asymmetric set difference of `x` and `y`.

`setequal(x, y)`: Set equality of `x` to `y`.

### Other methods

In the code snippets below, `x` is an [XStringSet](#) object.

`unlist(x)`: Turns `x` into an [XString](#) object by combining the sequences in `x` together. Fast equivalent to `do.call(c, as.list(x))`.

`as.character(x, use.names=TRUE)`: Converts `x` to a character vector of the same length as `x`. The `use.names` argument controls whether or not `names(x)` should be propagated to the names of the returned vector.

`as.matrix(x, use.names=TRUE)`: Returns a character matrix containing the "exploded" representation of the strings. Can only be used on an XStringSet object with equal-width strings. The `use.names` argument controls whether or not `names(x)` should be propagated to the row names of the returned matrix.

`toString(x)`: Equivalent to `toString(as.character(x))`.

`show(x)`: By default the `show` method displays 5 head and 5 tail lines. The number of lines can be altered by setting the global options `showHeadLines` and `showTailLines`. If the object length is less than the sum of the options, the full object is displayed. These options affect GRanges, GappedAlignments, Ranges and XString objects.

### Author(s)

H. Pages

### See Also

[XStringSet-comparison](#), [XString-class](#), [XStringViews-class](#), [XStringSetList-class](#), [subseq](#), [narrow](#), [substr](#), [compact](#), [XVectorList-class](#)

### Examples

```
## -----
## A. USING THE XStringSet CONSTRUCTORS ON A CHARACTER VECTOR OR FACTOR
## -----
## Note that there is no XStringSet() constructor, but an XStringSet
## family of constructors: BStringSet(), DNStringSet(), RNStringSet(),
## etc...
x0 <- c("#CTC-NACCGAT", "#TTGA", "TACCTAGAG")
width(x0)
x1 <- BStringSet(x0)
x1

## 3 equivalent ways to obtain the same BStringSet object:
BStringSet(x0, start=4, end=-3)
subseq(x1, start=4, end=-3)
BStringSet(subseq(x0, start=4, end=-3))

dna0 <- DNStringSet(x0, start=4, end=-3)
dna0
names(dna0)
names(dna0)[2] <- "seqB"
dna0

## When the input vector contains a lot of duplicates, turning it into
## a factor first before passing it to the constructor will produce an
## XStringSet object that is more compact in memory:
library(hgu95av2probe)
x2 <- sample(hgu95av2probe$sequence, 999000, replace=TRUE)
dna2a <- DNStringSet(x2)
dna2b <- DNStringSet(factor(x2)) # slower but result is more compact
object.size(dna2a)
```

```

object.size(dna2b)

## -----
## B. USING THE XStringSet CONSTRUCTORS ON A SINGLE SEQUENCE (XString
##   OBJECT OR CHARACTER STRING)
## -----
x3 <- "abcdefghij"
BStringSet(x3, start=2, end=6:2) # behaves like substring(x3, 2, 6:2)
BStringSet(x3, start=-(1:6))
x4 <- BString(x3)
BStringSet(x4, end=-(1:6), width=3)

## Randomly extract 1 million 40-mers from C. elegans chrI:
extractRandomReads <- function(subject, nread, readlength)
{
  if (!is.integer(readlength))
    readlength <- as.integer(readlength)
  start <- sample(length(subject) - readlength + 1L, nread,
                 replace=TRUE)
  DNABStringSet(subject, start=start, width=readlength)
}
library(BSgenome.Celegans.UCSC.ce2)
rndreads <- extractRandomReads(Celegans$chrI, 1000000, 40)
## Notes:
## - This takes only 2 or 3 seconds versus several hours for a solution
##   using substring() on a standard character string.
## - The short sequences in rndreads can be seen as the result of a
##   simulated high-throughput sequencing experiment. A non-realistic
##   one though because:
##   (a) It assumes that the underlying technology is perfect (the
##       generated reads have no technology induced errors).
##   (b) It assumes that the sequenced genome is exactly the same as the
##       reference genome.
##   (c) The simulated reads can contain IUPAC ambiguity letters only
##       because the reference genome contains them. In a real
##       high-throughput sequencing experiment, the sequenced genome
##       of course doesnt contain those letters, but the sequencer
##       can introduce them in the generated reads to indicate ambiguous
##       base-calling.
##   (d) The simulated reads come from the plus strand only of a single
##       chromosome.
## - See the getSeq() function in the BSgenome package for how to
##   circumvent (d) i.e. how to generate reads that come from the whole
##   genome (plus and minus strands of all chromosomes).

## -----
## C. USING THE XStringSet CONSTRUCTORS ON AN XStringSet OBJECT
## -----
library(drosophila2probe)
probes <- DNABStringSet(drosophila2probe)
probes

RNABStringSet(probes, start=2, end=-5) # does NOT copy the sequence data!

```

```

## -----
## D. USING THE XStringSet CONSTRUCTORS ON AN ORDINARY list OF XString
##   OBJECTS
## -----
probes10 <- head(probes, n=10)
set.seed(33)
shuffled_nucleotides <- lapply(probes10, sample)
shuffled_nucleotides

DNAStrngSet(shuffled_nucleotides) # does NOT copy the sequence data!

## Note that the same result can be obtained in a more compact way with
## just:
set.seed(33)
endoapply(probes10, sample)

## -----
## E. USING subseq() ON AN XStringSet OBJECT
## -----
subseq(probes, start=2, end=-5)

subseq(probes, start=13, end=13) <- "N"
probes

## Add/remove a prefix:
subseq(probes, start=1, end=0) <- "--"
probes
subseq(probes, end=2) <- ""
probes

## Do more complicated things:
subseq(probes, start=4:7, end=7) <- c("YYYY", "YYY", "YY", "Y")
subseq(probes, start=4, end=6) <- subseq(probes, start=-2:-5)
probes

## -----
## F. UNLISTING AN XStringSet OBJECT
## -----
library(drosophila2probe)
probes <- DNAStrngSet(drosophila2probe)
unlist(probes)

## -----
## G. COMPACTING AN XStringSet OBJECT
## -----
## As a particular type of XVectorList objects, XStringSet objects can
## optionally be compacted. Compacting is done typically before
## serialization. See ?compact for more information.
library(drosophila2probe)
probes <- DNAStrngSet(drosophila2probe)

y <- subseq(probes[1:12], start=5)

```



```

probes@pool
y@pool
object.size(probes)
object.size(y)

y0 <- compact(y)
y0@pool
object.size(y0)

```

---

XStringSet-comparison *Comparing and ordering the elements in one or more XStringSet objects*

---

## Description

Methods for comparing and ordering the elements in one or more [XStringSet](#) objects.

## Details

Element-wise (aka "parallel") comparison of 2 [XStringSet](#) objects is based on the lexicographic order between 2 [BString](#), [DNString](#), [RNString](#), or [AAString](#) objects.

For [DNStringSet](#) and [RNStringSet](#) objects, the letters in the respective alphabets (i.e. [DNA\\_ALPHABET](#) and [RNA\\_ALPHABET](#)) are ordered based on a predefined code assigned to each letter. The code assigned to each letter can be retrieved with:

```

dna_codes <- as.integer(DNString(paste(DNA_ALPHABET, collapse="")))
names(dna_codes) <- DNA_ALPHABET

rna_codes <- as.integer(RNString(paste(RNA_ALPHABET, collapse="")))
names(rna_codes) <- RNA_ALPHABET

```

Note that this order does NOT depend on the locale in use. Also note that comparing DNA sequences with RNA sequences is supported and in that case T and U are considered to be the same letter.

For [BStringSet](#) and [AAStringSet](#) objects, the alphabetical order is defined by the C collation. Note that, at the moment, [AAStringSet](#) objects are treated like [BStringSet](#) objects i.e. the alphabetical order is NOT defined by the order of the letters in [AA\\_ALPHABET](#). This might change at some point.

## compare() and related methods

In the code snippets below, x and y are [XStringSet](#) objects.

`compare(x, y)`: Performs element-wise (aka "parallel") comparison of x and y, that is, returns an integer vector where the i-th element is less than, equal to, or greater than zero if the i-th element in x is considered to be respectively less than, equal to, or greater than the i-th element in y. If x and y don't have the same length, then the shortest is recycled to the length of the longest (the standard recycling rules apply).

`x == y`, `x != y`, `x <= y`, `x >= y`, `x < y`, `x > y`: Equivalent to `compare(x, y) == 0`, `compare(x, y) != 0`, `compare(x, y) <= 0`, `compare(x, y) >= 0`, `compare(x, y) < 0`, and `compare(x, y) > 0`, respectively.

### order() and related methods

In the code snippets below, `x` is an [XStringSet](#) object.

`is.unsorted(x, strictly=FALSE)`: Return a logical values specifying if `x` is unsorted. The `strictly` argument takes logical value indicating if the check should be for `_strictly_` increasing values.

`order(x, decreasing=FALSE)`: Return a permutation which rearranges `x` into ascending or descending order.

`rank(x, ties.method=c("first", "min"))`: Rank `x` in ascending order.

`sort(x, decreasing=FALSE)`: Sort `x` into ascending or descending order.

### duplicated() and unique()

In the code snippets below, `x` is an [XStringSet](#) object.

`duplicated(x)`: Return a logical vector whose elements denotes duplicates in `x`.

`unique(x)`: Return the subset of `x` made of its unique elements.

### match() and %in%

In the code snippets below, `x` and `table` are [XStringSet](#) objects.

`match(x, table, nomatch=NA_integer_)`: Returns an integer vector containing the first positions of an identical match in `table` for the elements in `x`.

`x %in% table`: Returns a logical vector indicating which elements in `x` match identically with an element in `table`.

### Author(s)

H. Pages

### See Also

[XStringSet-class](#), [==](#), [is.unsorted](#), [order](#), [rank](#), [sort](#), [duplicated](#), [unique](#), [match](#), [%in%](#)

### Examples

```
## -----
## A. SIMPLE EXAMPLES
## -----

dna <- DNASTringSet(c("AAA", "TC", "", "TC", "AAA", "CAAC", "G"))
match(c("", "G", "AA", "TC"), dna)

library(drosophila2probe)
```

```

fly_probes <- DNASTringSet(drosophila2probe)
sum(duplicated(fly_probes)) # 481 duplicated probes

is.unsorted(fly_probes) # TRUE
fly_probes <- sort(fly_probes)
is.unsorted(fly_probes) # FALSE
is.unsorted(fly_probes, strictly=TRUE) # TRUE, because of duplicates
is.unsorted(unique(fly_probes), strictly=TRUE) # FALSE

## Nb of probes that are the reverse complement of another probe:
nb1 <- sum(reverseComplement(fly_probes) %in% fly_probes)
stopifnot(identical(nb1, 455L)) # 455 probes

## Probes shared between drosophila2probe and hgu95av2probe:
library(hgu95av2probe)
human_probes <- DNASTringSet(hgu95av2probe)
m <- match(fly_probes, human_probes)
stopifnot(identical(sum(!is.na(m)), 493L)) # 493 shared probes

## -----
## B. AN ADVANCED EXAMPLE
## -----
## We want to compare the first 5 bases with the 5 last bases of each
## probe in drosophila2probe. More precisely, we want to compute the
## percentage of probes for which the first 5 bases are the reverse
## complement of the 5 last bases.

library(drosophila2probe)
probes <- DNASTringSet(drosophila2probe)

first5 <- narrow(probes, end=5)
last5 <- narrow(probes, start=-5)
nb2 <- sum(first5 == reverseComplement(last5))
stopifnot(identical(nb2, 17L))

## Percentage:
100 * nb2 / length(probes) # 0.0064 %

## If the probes were random DNA sequences, a probe would have 1 chance
## out of 4^5 to have this property so the percentage would be:
100 / 4^5 # 0.098 %

## With randomly generated probes:
set.seed(33)
random_dna <- sample(DNASTring(paste(DNA_BASES, collapse="")),
                    sum(width(probes)), replace=TRUE)
random_probes <- successiveViews(random_dna, width(probes))
random_probes
random_probes <- as(random_probes, "XStringSet")
random_probes

random_first5 <- narrow(random_probes, end=5)
random_last5 <- narrow(random_probes, start=-5)

```

```
nb3 <- sum(random_first5 == reverseComplement(random_last5))
100 * nb3 / length(random_probes) # 0.099 %
```

---

XStringSet-io

*Read/write an XStringSet object from/to a file*


---

## Description

Functions to read/write an [XStringSet](#) object from/to a file.

## Usage

```
## Read FASTA (or FASTQ) files in an XStringSet object:
readBStringSet(filepath, format="fasta",
               nrec=-1L, skip=0L, use.names=TRUE)
readDNAStrngSet(filepath, format="fasta",
               nrec=-1L, skip=0L, use.names=TRUE)
readRNAStrngSet(filepath, format="fasta",
               nrec=-1L, skip=0L, use.names=TRUE)
readAAStrngSet(filepath, format="fasta",
               nrec=-1L, skip=0L, use.names=TRUE)

## Extract basic information about FASTA (or FASTQ) files
## without actually loading the sequence data:
fasta.info(filepath, nrec=-1L, skip=0L, use.names=TRUE, seqtype="B")
fastq.geometry(filepath, nrec=-1L, skip=0L)

## Write an XStringSet object to a FASTA (or FASTQ) file:
writeXStringSet(x, filepath, append=FALSE, format="fasta", ...)

## Serialize an XStringSet object:
saveXStringSet(x, objname, dirpath=".", save.dups=FALSE, verbose=TRUE)
```

## Arguments

filepath	A character vector (of arbitrary length when reading, of length 1 when writing) containing the path(s) to the file(s) to read or write. Note that special values like "" or " cmd" (typically supported by other I/O functions in R) are not supported here. Also filepath cannot be a connection.
format	Either "fasta" (the default) or "fastq".
nrec	Single integer. The maximum of number of records to read in. Negative values are ignored.
skip	Single non-negative integer. The number of records of the data file(s) to skip before beginning to read in records.

use.names	Should the returned vector be named? For FASTA the names are taken from the record description lines. For FASTQ they are taken from the record sequence ids. Dropping the names can help reducing memory footprint e.g. for a FASTQ file containing millions of reads.
seqtype	A single string specifying the type of sequences contained in the FASTA file(s). Supported sequence types: <ul style="list-style-type: none"> <li>• "B" for anything i.e. any letter is a valid one-letter sequence code.</li> <li>• "DNA" for DNA sequences i.e. only letters in <a href="#">DNA_ALPHABET</a> (case ignored) are valid one-letter sequence codes.</li> <li>• "RNA" for RNA sequences i.e. only letters in <a href="#">RNA_ALPHABET</a> (case ignored) are valid one-letter sequence codes.</li> <li>• "AA" for Amino Acid sequences. Currently treated as "B" but this will change in the near future i.e. only letters in <a href="#">AA_ALPHABET</a> (case ignored) will be valid one-letter sequence codes.</li> </ul> Invalid one-letter sequence codes are ignored with a warning.
x	For writeXStringSet, the object to write to file. For saveXStringSet, the object to serialize.
append	TRUE or FALSE. If TRUE output will be appended to file; otherwise, it will overwrite the contents of file. See <a href="#">?cat</a> for the details.
...	Further format-specific arguments. If format="fasta", the width argument (single integer) can be used to specify the maximum number of letters per line of sequence. If format="fastq", the qualities argument ( <a href="#">BStringSet</a> object) can be used to specify the qualities. If the qualities are omitted, then the fake quality ',' is assigned to each letter in x and written to the file.
objname	The name of the serialized object.
dirpath	The path to the directory where to save the serialized object.
save.dups	TRUE or FALSE. If TRUE then the <a href="#">Dups</a> object describing how duplicated elements in x are related to each other is saved too. For advanced users only.
verbose	TRUE or FALSE.

## Details

Only FASTA and FASTQ files are supported for now. The qualities stored in the FASTQ records are ignored.

Reading functions `readBStringSet`, `readDNAStrngSet`, `readRNAStrngSet` and `readAAStrngSet` load sequences from an input file (or set of input files) into an [XStringSet](#) object. When multiple input files are specified, they are read in the corresponding order and their data are stored in the returned object in that order. Note that when multiple input FASTQ files are specified, all must have the same "width" (i.e. all their sequences must have the same length).

The `fasta.info` utility returns an integer vector with one element per FASTA record in the input files. Each element is the length of the sequence found in the corresponding record, that is, the number of valid one-letter sequence codes in the record. See description of the `seqtype` argument above for how to control the set of valid one-letter sequence codes.

The `fastq.geometry` utility returns an integer vector describing the "geometry" of the FASTQ files i.e. a vector of length 2 where the first element is the total number of FASTQ records in the files

and the second element the common "width" of these files (this width is NA if the files contain no FASTQ records or records with different widths).

writeXStringSet writes an [XStringSet](#) object to a file. WARNING: Please be aware that using writeXStringSet on a [BStringSet](#) object that contains the '\n' (LF) or '\r' (CR) characters or the FASTA markup characters '>' or ';' is almost guaranteed to produce a broken FASTA file!

Serializing an [XStringSet](#) object with saveXStringSet is equivalent to using the standard save mechanism. But it will try to reduce the size of x in memory first before calling save. Most of the times this leads to a much reduced size on disk.

## References

[http://en.wikipedia.org/wiki/FASTA\\_format](http://en.wikipedia.org/wiki/FASTA_format)

## See Also

[XStringSet-class](#), [BString-class](#), [DNAString-class](#), [RNAString-class](#), [AAString-class](#)

## Examples

```
## -----
## A. READ/WRITE FASTA FILES
## -----
filepath <- system.file("extdata", "someORF.fa", package="Biostrings")
fasta.info(filepath, seqtype="DNA")
x <- readDNAStringSet(filepath)
x
out1 <- tempfile()
writeXStringSet(x, out1)

## -----
## B. READ/WRITE FASTQ FILES
## -----
filepath <- system.file("extdata", "s_1_sequence.txt",
                        package="Biostrings")
fastq.geometry(filepath)
readDNAStringSet(filepath, format="fastq")

library(BSgenome.Celegans.UCSC.ce2)
## Create a "sliding window" on chr I:
sw_start <- seq.int(1, length(Celegans$chrI)-50, by=50)
sw <- Views(Celegans$chrI, start=sw_start, width=10)
my_fake_shortreads <- as(sw, "XStringSet")
my_fake_ids <- sprintf("ID%06d", seq_len(length(my_fake_shortreads)))
names(my_fake_shortreads) <- my_fake_ids
my_fake_shortreads

## Fake quality ; will be assigned to each base in my_fake_shortreads:
out2 <- tempfile()
writeXStringSet(my_fake_shortreads, out2, format="fastq")

## Passing qualities thru the qualities argument:
```

```

my_fake_qual = rep.int(BStringSet("DCBA@?>=<;"),
                        length(my_fake_shortreads))
my_fake_qual
out3 <- tempfile()
writeXStringSet(my_fake_shortreads, out3, format="fastq",
                qualities=my_fake_qual)

## -----
## C. SERIALIZATION
## -----
saveXStringSet(my_fake_shortreads, "my_fake_shortreads", dirpath=tempdir())

```

---

XStringSetList-class *XStringSetList* objects

---

## Description

The XStringSetList class is a virtual container for storing a list of [XStringSet](#) objects.

## Usage

```

## Constructors:
DNAStrngSetList(..., use.names=TRUE)
AAStringSetList(..., use.names=TRUE)

```

## Arguments

...	Character vector(s) (with no NAs), or <a href="#">XStringSet</a> object(s), or <a href="#">XStringViews</a> object(s) to be concatenated into a <a href="#">XStringSetList</a> .
use.names	TRUE or FALSE. Should names be preserved?

## Details

Concrete flavors of the XStringSetList container are the BStringSetList, DNAStrngSetList, RNAS-trngSetList and AAStringSetList containers for storing a list of [BStringSet](#), [DNAStrngSet](#), [RNAS-trngSet](#) and [AAStringSet](#) objects, respectively. These four containers are direct subclasses of XStringSetList with no additional slots.

Currently DNAStrngSetList() and AAStringSetList() are the only XStringSetList constructors. The XStringSetList class itself is virtual and has no constructor.

## Methods

The XStringSetList class extends the [List](#) class defined in the **IRanges** package. Using a less technical jargon, this just means that an XStringSetList object is a list-like object that can be manipulated like an ordinary list. Or, said otherwise, most of the operations that work on an ordinary list (e.g. length, names, [, [[, c, unlist, etc...) should work on an XStringSetList object. In addition, Bioconductor specific list operations like [elementLengths](#) and [PartitioningByEnd](#) (defined in the **IRanges** package) are supported too.

**Author(s)**

H. Pages

**See Also**[XStringSet-class](#), [List-class](#)**Examples**

```
## -----
## A. THE XStringSetList CONSTRUCTORS
## -----
## Currently DNASTringSetList() and AAStringSetList() are the only
## constructors. Others will be developed when the use case arises.

dna1 <- c("AAA", "AC", "", "T", "GGATA")
dna2 <- c("G", "TT", "C")

x <- DNASTringSetList(dna1, dna2)
x

DNASTringSetList(DNASTringSet(dna1), DNASTringSet(dna2))

DNASTringSetList(dna1, DNASTringSet(dna2))

DNASTringSetList(DNASTringSet(dna1), dna2)

DNASTringSetList(dna1, RNASTringSet(DNASTringSet(dna2)))

DNASTringSetList(list(dna1, dna2))

DNASTringSetList(CharacterList(dna1, dna2))

## Empty object (i.e. zero-length):
DNASTringSetList()

## Not empty (length is 1):
DNASTringSetList(character(0))

## -----
## B. UNLISTING AN XStringSetList OBJECT
## -----
length(x)
elementLengths(x)
unlist(x)
x[[1]]
x[[2]]
as.list(x)

names(x) <- LETTERS[1:length(x)]
x[["A"]]
x[["B"]]
```



```

as.list(x) # named list

## -----
## B. USING THE GROUPING CORE API ON PartitioningByEnd(x)
## -----
PartitioningByEnd(x)
length(PartitioningByEnd(x))
nobj(PartitioningByEnd(x))
grouplength(PartitioningByEnd(x)) # same as unname(sapply(x, length))

## -----
## C. USING THE RANGES CORE API ON PartitioningByEnd(x)
## -----
start(PartitioningByEnd(x))
end(PartitioningByEnd(x))
width(PartitioningByEnd(x)) # same as grouplength(PartitioningByEnd(x))

```

---

XStringViews-class      *The XStringViews class*

---

## Description

The XStringViews class is the basic container for storing a set of views (start/end locations) on the same sequence (an [XString](#) object).

## Details

An XStringViews object contains a set of views (start/end locations) on the same [XString](#) object called "the subject string" or "the subject sequence" or simply "the subject". Each view is defined by its start and end locations: both are integers such that start <= end. An XStringViews object is in fact a particular case of an [Views](#) object (the XStringViews class contains the [Views](#) class) so it can be manipulated in a similar manner: see [?Views](#) for more information. Note that two views can overlap and that a view can be "out of limits" i.e. it can start before the first letter of the subject or/and end after its last letter.

## Constructor

`Views(subject, start=NULL, end=NULL, width=NULL, names=NULL)`: See [?Views](#) in the `IRanges` package for the details.

## Accessor-like methods

All the accessor-like methods defined for `Views` objects work on `XStringViews` objects. In addition, the following accessors are defined for `XStringViews` objects:

`nchar(x)`: A vector of non-negative integers containing the number of letters in each view. Values in `nchar(x)` coincide with values in `width(x)` except for "out of limits" views where they are lower.

**Other methods**

In the code snippets below, `x`, `object`, `e1` and `e2` are `XStringViews` objects, and `i` can be a numeric or logical vector.

`e1 == e2`: A vector of logicals indicating the result of the view by view comparison. The views in the shorter of the two `XStringViews` object being compared are recycled as necessary.

Like for comparison between `XString` objects, comparison between two `XStringViews` objects with subjects of different classes is not supported with one exception: when the subjects are `DNAStrng` and `RNAString` instances.

Also, like with `XString` objects, comparison between an `XStringViews` object with a `BString` subject and a character vector is supported (see examples below).

`e1 != e2`: Equivalent to `!(e1 == e2)`.

`as.character(x, use.names=TRUE, check.limits=TRUE)`: Converts `x` to a character vector of the same length as `x`. The `use.names` argument controls whether or not `names(x)` should be propagated to the names of the returned vector. The `check.limits` argument controls whether or not an error should be raised if `x` has "out of limit" views. If `check.limits` is `FALSE` then "out of limit" views are trimmed with a warning.

`as.matrix(x, use.names=TRUE)`: Returns a character matrix containing the "exploded" representation of the views. Can only be used on an `XStringViews` object with equal-width views. The `use.names` argument controls whether or not `names(x)` should be propagated to the row names of the returned matrix.

`toString(x)`: Equivalent to `toString(as.character(x))`.

**Author(s)**

H. Pages

**See Also**

[Views-class](#), [gaps](#), [XString-class](#), [XStringSet-class](#), [letter](#), [MIndex-class](#)

**Examples**

```
## One standard way to create an XStringViews object is to use
## the Views() constructor.
```

```
## Views on a DNASrting object:
s <- DNASrting("-CTC-N")
v4 <- Views(s, start=3:0, end=5:8)
v4
subject(v4)
length(v4)
start(v4)
end(v4)
width(v4)
```

```
## Attach a comment to views #3 and #4:
names(v4)[3:4] <- "out of limits"
names(v4)
```

```

## A more programatical way to "tag" the "out of limits" views:
names(v4)[start(v4) < 1 | nchar(subject(v4)) < end(v4)] <- "out of limits"
## or just:
names(v4)[nchar(v4) < width(v4)] <- "out of limits"

## Two equivalent ways to extract a view as an XString object:
s2a <- v4[[2]]
s2b <- subseq(subject(v4), start=start(v4)[2], end=end(v4)[2])
identical(s2a, s2b) # TRUE

## It is an error to try to extract an "out of limits" view:
#v4[[3]] # Error!

v12 <- Views(DNAString("TAATAATG"), start=-2:9, end=0:11)
v12 == DNAString("TAA")
v12[v12 == v12[4]]
v12[v12 == v12[1]]
v12[3] == Views(RNAString("AU"), start=0, end=2)

## Here the first view doesnt even overlap with the subject:
Views(BString("aaa--b"), start=-3:4, end=-3:4 + c(3:6, 6:3))

## start and end are recycled:
subject <- "abcdefghij"
Views(subject, start=2:1, end=4)
Views(subject, start=5:7, end=nchar(subject))
Views(subject, start=1, end=5:7)

## Applying gaps() to an XStringViews object:
v2 <- Views("abCDefgHIJK", start=c(8, 3), end=c(14, 4))
gaps(v2)

## Coercion:
as(v12, "XStringSet") # same as as(v12, "DNAStringSet")
rna <- as(v12, "RNAStringSet")
as(rna, "Views")

```

---

yeastSEQCHR1

*An annotation data file for CHR1 in the yeastSEQ package*


---

## Description

This is a single character string containing DNA sequence of yeast chromosome number 1. The data were obtained from the Saccharomyces Genome Database ([ftp://genome-ftp.stanford.edu/pub/yeast/data\\_download/sequence/genomic\\_sequence/chromosomes/fasta/](ftp://genome-ftp.stanford.edu/pub/yeast/data_download/sequence/genomic_sequence/chromosomes/fasta/)).

## Details

Annotation based on data provided by Yeast Genome project.

Source data built: Yeast Genome data are built at various time intervals. Sources used were downloaded Fri Nov 21 14:00:47 2003 Package built: Fri Nov 21 14:00:47 2003

### References

<http://www.yeastgenome.org/DownloadContents.shtml>

### Examples

```
data(yeastSEQCHR1)
nchar(yeastSEQCHR1)
```

# Index

- !=, BString, character-method (XString-class), 118
- !=, XString, XString-method (XString-class), 118
- !=, XString, XStringViews-method (XStringViews-class), 137
- !=, XStringViews, XString-method (XStringViews-class), 137
- !=, XStringViews, XStringViews-method (XStringViews-class), 137
- !=, XStringViews, character-method (XStringViews-class), 137
- !=, character, BString-method (XString-class), 118
- !=, character, XStringViews-method (XStringViews-class), 137
- \*Topic **character**
  - stringDist, 107
- \*Topic **classes**
  - AAString-class, 3
  - AlignedXStringSet-class, 6
  - BOC\_SubjectString-class, 9
  - DNString-class, 13
  - InDel-class, 19
  - MaskedXString-class, 35
  - MIndex-class, 65
  - MultipleAlignment-class, 67
  - PairwiseAlignments-class, 83
  - PDict-class, 89
  - QualityScaledXStringSet-class, 96
  - RNString-class, 106
  - XString-class, 118
  - XStringPartialMatches-class, 121
  - XStringQuality-class, 122
  - XStringSet-class, 123
  - XStringSetList-class, 135
  - XStringViews-class, 137
- \*Topic **cluster**
  - stringDist, 107
- \*Topic **datasets**
  - HNF4alpha, 19
  - phiX174Phage, 93
  - substitution.matrices, 109
  - yeastSEQCHR1, 139
- \*Topic **data**
  - AMINO\_ACID\_CODE, 8
  - GENETIC\_CODE, 16
  - IUPAC\_CODE\_MAP, 22
  - substitution.matrices, 109
- \*Topic **distribution**
  - dinucleotideFrequencyTest, 11
- \*Topic **htest**
  - dinucleotideFrequencyTest, 11
- \*Topic **manip**
  - chartr, 9
  - detail, 10
  - getSeq, 17
  - gregexpr2, 18
  - injectHardMask, 20
  - letterFrequency, 24
  - longestConsecutive, 29
  - maskMotif, 38
  - matchprobes, 61
  - matchPWM, 62
  - misc, 66
  - nucleotideFrequency, 73
  - padAndClip, 78
  - PairwiseAlignments-io, 87
  - replaceAt, 98
  - replaceLetterAt, 102
  - reverseComplement, 104
  - translate, 113
  - xscat, 117
  - XStringSet-io, 132
- \*Topic **methods**
  - AAString-class, 3
  - align-utils, 4
  - AlignedXStringSet-class, 6

- BOC\_SubjectString-class, 9
- chartr, 9
- DNAStrng-class, 13
- findPalindromes, 14
- InDel-class, 19
- letter, 23
- letterFrequency, 24
- lowlevel-matching, 30
- MaskedXString-class, 35
- maskMotif, 38
- match-utils, 40
- matchLRPatterns, 42
- matchPattern, 43
- matchPDict, 48
- matchPDict-inexact, 56
- matchProbePair, 59
- matchPWM, 62
- MIndex-class, 65
- misc, 66
- MultipleAlignment-class, 67
- needwunsQS, 72
- nucleotideFrequency, 73
- padAndClip, 78
- pairwiseAlignment, 80
- PairwiseAlignments-class, 83
- PDict-class, 89
- pid, 94
- pmatchPattern, 96
- QualityScaledXStringSet-class, 96
- replaceAt, 98
- reverseComplement, 104
- RNAString-class, 106
- toComplex, 112
- translate, 113
- trimLRPatterns, 115
- xscat, 117
- XString-class, 118
- XStringPartialMatches-class, 121
- XStringQuality-class, 122
- XStringSet-class, 123
- XStringSet-comparison, 129
- XStringSetList-class, 135
- XStringViews-class, 137
- \*Topic **models**
  - needwunsQS, 72
  - pairwiseAlignment, 80
- \*Topic **multivariate**
  - stringDist, 107
- \*Topic **utilities**
  - AMINO\_ACID\_CODE, 8
  - GENETIC\_CODE, 16
  - injectHardMask, 20
  - IUPAC\_CODE\_MAP, 22
  - matchPWM, 62
  - PairwiseAlignments-io, 87
  - replaceLetterAt, 102
  - substitution.matrices, 109
  - XStringSet-io, 132
- .inplaceReplaceLetterAt
  - (replaceLetterAt), 102
- ==, 130
- ==, BString, character-method
  - (XString-class), 118
- ==, XString, XString-method
  - (XString-class), 118
- ==, XString, XStringViews-method
  - (XStringViews-class), 137
- ==, XStringViews, XString-method
  - (XStringViews-class), 137
- ==, XStringViews, XStringViews-method
  - (XStringViews-class), 137
- ==, XStringViews, character-method
  - (XStringViews-class), 137
- ==, character, BString-method
  - (XString-class), 118
- ==, character, XStringViews-method
  - (XStringViews-class), 137
- [, AlignedXStringSet0-method
  - (AlignedXStringSet-class), 6
- [, PairwiseAlignments-method
  - (PairwiseAlignments-class), 83
- [, QualityScaledXStringSet-method
  - (QualityScaledXStringSet-class), 96
- [, XStringPartialMatches-method
  - (XStringPartialMatches-class), 121
- [<-, AlignedXStringSet0-method
  - (AlignedXStringSet-class), 6
- [<-, PairwiseAlignments-method
  - (PairwiseAlignments-class), 83
- [[, ByPos\_MIndex-method (MIndex-class), 65
- [[, PDict-method (PDict-class), 89
- %in%, 130
- AA\_ALPHABET, 17, 124, 129, 133

- AA\_ALPHABET (AAString-class), 3
- AAMultipleAlignment
  - (MultipleAlignment-class), 67
- AAMultipleAlignment-class
  - (MultipleAlignment-class), 67
- AAString, 4, 8, 13, 17, 107, 114, 119, 123, 129
- AAString (AAString-class), 3
- AAString-class, 3, 111, 114, 120, 134
- AAStringSet, 79, 96, 129, 135
- AAStringSet (XStringSet-class), 123
- AAStringSet-class, 97
- AAStringSet-class (XStringSet-class), 123
- AAStringSetList (XStringSetList-class), 135
- AAStringSetList-class
  - (XStringSetList-class), 135
- ACTree2 (PDict-class), 89
- ACTree2-class (PDict-class), 89
- agrep, 109, 115
- align-utils, 4, 33, 41, 87
- aligned (AlignedXStringSet-class), 6
- aligned, AlignedXStringSet0-method
  - (AlignedXStringSet-class), 6
- aligned, PairwiseAlignmentsSingleSubject-method
  - (PairwiseAlignments-class), 83
- AlignedXStringSet
  - (AlignedXStringSet-class), 6
- AlignedXStringSet-class, 6, 6, 87
- AlignedXStringSet0
  - (AlignedXStringSet-class), 6
- AlignedXStringSet0-class
  - (AlignedXStringSet-class), 6
- alphabet, 5, 24, 25, 27, 36, 75, 86
- alphabet (XString-class), 118
- alphabet, ANY-method (XString-class), 118
- alphabet, XStringQuality-method
  - (XStringQuality-class), 122
- alphabetFrequency, 4, 10, 13, 37, 45, 50, 75, 107
- alphabetFrequency (letterFrequency), 24
- alphabetFrequency, DNAStrng-method
  - (letterFrequency), 24
- alphabetFrequency, DNAStrngSet-method
  - (letterFrequency), 24
- alphabetFrequency, MaskedXString-method
  - (letterFrequency), 24
- alphabetFrequency, MultipleAlignment-method
  - (MultipleAlignment-class), 67
- alphabetFrequency, RNAStrng-method
  - (letterFrequency), 24
- alphabetFrequency, RNAStrngSet-method
  - (letterFrequency), 24
- alphabetFrequency, XString-method
  - (letterFrequency), 24
- alphabetFrequency, XStringSet-method
  - (letterFrequency), 24
- alphabetFrequency, XStringViews-method
  - (letterFrequency), 24
- AMINO\_ACID\_CODE, 4, 8, 17, 75
- append, QualityScaledXStringSet, QualityScaledXStringSet-method
  - (QualityScaledXStringSet-class), 96
- Arithmetic, 25
- as.character, AlignedXStringSet0-method
  - (AlignedXStringSet-class), 6
- as.character, MaskedXString-method
  - (MaskedXString-class), 35
- as.character, MultipleAlignment-method
  - (MultipleAlignment-class), 67
- as.character, PairwiseAlignmentsSingleSubject-method
  - (PairwiseAlignments-class), 83
- as.character, XString-method
  - (XString-class), 118
- as.character, XStringSet-method
  - (XStringSet-class), 123
- as.character, XStringViews-method
  - (XStringViews-class), 137
- as.integer, IlluminaQuality-method
  - (XStringQuality-class), 122
- as.integer, PhredQuality-method
  - (XStringQuality-class), 122
- as.integer, SolexaQuality-method
  - (XStringQuality-class), 122
- as.list, MTB\_PDICT-method (PDict-class), 89
- as.matrix, MultipleAlignment-method
  - (MultipleAlignment-class), 67
- as.matrix, PairwiseAlignmentsSingleSubject-method
  - (PairwiseAlignments-class), 83
- as.matrix, XStringQuality-method
  - (XStringQuality-class), 122
- as.matrix, XStringSet-method
  - (XStringSet-class), 123
- as.matrix, XStringViews-method
  - (XStringViews-class), 137

- as.numeric, IlluminaQuality-method  
(XStringQuality-class), 122
- as.numeric, PhredQuality-method  
(XStringQuality-class), 122
- as.numeric, SolexaQuality-method  
(XStringQuality-class), 122
- as.vector, XStringSet-method  
(XStringSet-class), 123
  
- BLOSUM100 (substitution.matrices), 109
- BLOSUM45 (substitution.matrices), 109
- BLOSUM50 (substitution.matrices), 109
- BLOSUM62 (substitution.matrices), 109
- BLOSUM80 (substitution.matrices), 109
- BOC2\_SubjectString  
(BOC\_SubjectString-class), 9
- BOC2\_SubjectString-class  
(BOC\_SubjectString-class), 9
- BOC\_SubjectString  
(BOC\_SubjectString-class), 9
- BOC\_SubjectString-class, 9
- BSgenome, 17, 18, 103
- BString, 3–5, 13, 27, 106, 107, 122, 123, 129
- BString (XString-class), 118
- BString-class, 134
- BString-class (XString-class), 118
- BStringSet, 5, 79, 96, 122, 129, 133–135
- BStringSet (XStringSet-class), 123
- BStringSet-class, 97, 123
- BStringSet-class (XStringSet-class), 123
- BStringSetList (XStringSetList-class),  
135
- BStringSetList-class  
(XStringSetList-class), 135
- ByPos\_MIndex-class (MIndex-class), 65
  
- c, 25
- cat, 133
- cDNA (translate), 113
- ceiling, 115
- CharacterList, 98, 99
- chartr, 9, 9, 10, 21, 103, 104
- chartr, ANY, ANY, MaskedXString-method  
(chartr), 9
- chartr, ANY, ANY, XString-method (chartr),  
9
- chartr, ANY, ANY, XStringSet-method  
(chartr), 9
  
- chartr, ANY, ANY, XStringViews-method  
(chartr), 9
- chisq.test, 12
- class:AAMultipleAlignment  
(MultipleAlignment-class), 67
- class:AAStrng (AAStrng-class), 3
- class:AAStrngSet (XStringSet-class),  
123
- class:AAStrngSetList  
(XStringSetList-class), 135
- class:ACTree2 (PDict-class), 89
- class:AlignedXStringSet  
(AlignedXStringSet-class), 6
- class:AlignedXStringSet0  
(AlignedXStringSet-class), 6
- class:BOC2\_SubjectString  
(BOC\_SubjectString-class), 9
- class:BOC\_SubjectString  
(BOC\_SubjectString-class), 9
- class:BString (XString-class), 118
- class:BStringSet (XStringSet-class), 123
- class:BStringSetList  
(XStringSetList-class), 135
- class:ByPos\_MIndex (MIndex-class), 65
- class:DNAMultipleAlignment  
(MultipleAlignment-class), 67
- class:DNAStrng (DNAStrng-class), 13
- class:DNAStrngSet (XStringSet-class),  
123
- class:DNAStrngSetList  
(XStringSetList-class), 135
- class:Expanded\_TB\_PDICT (PDict-class),  
89
- class:IlluminaQuality  
(XStringQuality-class), 122
- class:InDel (InDel-class), 19
- class:MaskedAAStrng  
(MaskedXString-class), 35
- class:MaskedBString  
(MaskedXString-class), 35
- class:MaskedDNAStrng  
(MaskedXString-class), 35
- class:MaskedRNAStrng  
(MaskedXString-class), 35
- class:MaskedXString  
(MaskedXString-class), 35
- class:MIndex (MIndex-class), 65
- class:MTB\_PDICT (PDict-class), 89



- class:MultipleAlignment  
(MultipleAlignment-class), 67
- class:PairwiseAlignments  
(PairwiseAlignments-class), 83
- class:PairwiseAlignmentsSingleSubject  
(PairwiseAlignments-class), 83
- class:PairwiseAlignmentsSingleSubjectSummary  
(PairwiseAlignments-class), 83
- class:PDict (PDict-class), 89
- class:PDict3Parts (PDict-class), 89
- class:PhredQuality  
(XStringQuality-class), 122
- class:PreprocessedTB (PDict-class), 89
- class:QualityAlignedXStringSet  
(AlignedXStringSet-class), 6
- class:QualityScaledAAStringSet  
(QualityScaledXStringSet-class),  
96
- class:QualityScaledBStringSet  
(QualityScaledXStringSet-class),  
96
- class:QualityScaledDNAStringSet  
(QualityScaledXStringSet-class),  
96
- class:QualityScaledRNAStringSet  
(QualityScaledXStringSet-class),  
96
- class:QualityScaledXStringSet  
(QualityScaledXStringSet-class),  
96
- class:RNAMultipleAlignment  
(MultipleAlignment-class), 67
- class:RNAString (RNAString-class), 106
- class:RNAStringSet (XStringSet-class),  
123
- class:RNAStringSetList  
(XStringSetList-class), 135
- class:SolexaQuality  
(XStringQuality-class), 122
- class:TB\_PDICT (PDict-class), 89
- class:Twobit (PDict-class), 89
- class:XString (XString-class), 118
- class:XStringPartialMatches  
(XStringPartialMatches-class),  
121
- class:XStringQuality  
(XStringQuality-class), 122
- class:XStringSet (XStringSet-class), 123
- class:XStringSetList  
(XStringSetList-class), 135
- class:XStringViews  
(XStringViews-class), 137
- codons (translate), 113
- codons, DNAString-method (translate), 113
- codons, MaskedDNAString-method  
(translate), 113
- codons, MaskedRNAString-method  
(translate), 113
- codons, RNAString-method (translate), 113
- coerce, AAString, MaskedAAString-method  
(MaskedXString-class), 35
- coerce, ANY, AAStringSet-method  
(XStringSet-class), 123
- coerce, ANY, BStringSet-method  
(XStringSet-class), 123
- coerce, ANY, DNAStringSet-method  
(XStringSet-class), 123
- coerce, ANY, RNAStringSet-method  
(XStringSet-class), 123
- coerce, ANY, XStringSet-method  
(XStringSet-class), 123
- coerce, BString, IlluminaQuality-method  
(XStringQuality-class), 122
- coerce, BString, MaskedBString-method  
(MaskedXString-class), 35
- coerce, BString, PhredQuality-method  
(XStringQuality-class), 122
- coerce, BString, SolexaQuality-method  
(XStringQuality-class), 122
- coerce, BStringSet, IlluminaQuality-method  
(XStringQuality-class), 122
- coerce, BStringSet, PhredQuality-method  
(XStringQuality-class), 122
- coerce, BStringSet, SolexaQuality-method  
(XStringQuality-class), 122
- coerce, character, AAMultipleAlignment-method  
(MultipleAlignment-class), 67
- coerce, character, AAString-method  
(XString-class), 118
- coerce, character, BString-method  
(XString-class), 118
- coerce, character, DNAMultipleAlignment-method  
(MultipleAlignment-class), 67
- coerce, character, DNAString-method  
(XString-class), 118
- coerce, character, IlluminaQuality-method

- (XStringQuality-class), 122
- coerce, character, PhredQuality-method (XStringQuality-class), 122
- coerce, character, RNAMultipleAlignment-method (MultipleAlignment-class), 67
- coerce, character, RNASTring-method (XString-class), 118
- coerce, character, SolexaQuality-method (XStringQuality-class), 122
- coerce, character, XString-method (XString-class), 118
- coerce, DNASTring, MaskedDNASTring-method (MaskedXString-class), 35
- coerce, IlluminaQuality, integer-method (XStringQuality-class), 122
- coerce, IlluminaQuality, numeric-method (XStringQuality-class), 122
- coerce, integer, IlluminaQuality-method (XStringQuality-class), 122
- coerce, integer, PhredQuality-method (XStringQuality-class), 122
- coerce, integer, SolexaQuality-method (XStringQuality-class), 122
- coerce, MaskedAAString, AAString-method (MaskedXString-class), 35
- coerce, MaskedBString, BString-method (MaskedXString-class), 35
- coerce, MaskedDNASTring, DNASTring-method (MaskedXString-class), 35
- coerce, MaskedRNASTring, RNASTring-method (MaskedXString-class), 35
- coerce, MaskedXString, MaskCollection-method (MaskedXString-class), 35
- coerce, MaskedXString, MaskedAAString-method (MaskedXString-class), 35
- coerce, MaskedXString, MaskedBString-method (MaskedXString-class), 35
- coerce, MaskedXString, MaskedDNASTring-method (MaskedXString-class), 35
- coerce, MaskedXString, MaskedRNASTring-method (MaskedXString-class), 35
- coerce, MaskedXString, NormalIRanges-method (MaskedXString-class), 35
- coerce, MaskedXString, Views-method (MaskedXString-class), 35
- coerce, MaskedXString, XStringViews-method (MaskedXString-class), 35
- coerce, MIndex, CompressedIRangesList-method (MIndex-class), 65
- coerce, MultipleAlignment, AAStringSet-method (MultipleAlignment-class), 67
- coerce, MultipleAlignment, BStringSet-method (MultipleAlignment-class), 67
- coerce, MultipleAlignment, DNASTringSet-method (MultipleAlignment-class), 67
- coerce, MultipleAlignment, RNASTringSet-method (MultipleAlignment-class), 67
- coerce, numeric, IlluminaQuality-method (XStringQuality-class), 122
- coerce, numeric, PhredQuality-method (XStringQuality-class), 122
- coerce, numeric, SolexaQuality-method (XStringQuality-class), 122
- coerce, PhredQuality, integer-method (XStringQuality-class), 122
- coerce, PhredQuality, numeric-method (XStringQuality-class), 122
- coerce, RNASTring, MaskedRNASTring-method (MaskedXString-class), 35
- coerce, SolexaQuality, integer-method (XStringQuality-class), 122
- coerce, SolexaQuality, numeric-method (XStringQuality-class), 122
- coerce, XString, AAString-method (XString-class), 118
- coerce, XString, BString-method (XString-class), 118
- coerce, XString, DNASTring-method (XString-class), 118
- coerce, XString, RNASTring-method (XString-class), 118
- coerce, XStringQuality, matrix-method (XStringQuality-class), 122
- coerce, XStringSet, Views-method (XStringViews-class), 137
- coerce, XStringSet, XStringViews-method (XStringViews-class), 137
- coerce, XStringViews, AAStringSet-method (XStringViews-class), 137
- coerce, XStringViews, BStringSet-method (XStringViews-class), 137
- coerce, XStringViews, DNASTringSet-method (XStringViews-class), 137
- coerce, XStringViews, RNASTringSet-method (XStringViews-class), 137
- coerce, XStringViews, XStringSet-method

- (XStringViews-class), 137
- collapse, MaskedXString-method
  - (MaskedXString-class), 35
- colmask (MultipleAlignment-class), 67
- colmask, MultipleAlignment-method
  - (MultipleAlignment-class), 67
- colmask<- (MultipleAlignment-class), 67
- colmask<-, MultipleAlignment, ANY-method
  - (MultipleAlignment-class), 67
- colmask<-, MultipleAlignment, NormalIRanges-method
  - (MultipleAlignment-class), 67
- colmask<-, MultipleAlignment, NULL-method
  - (MultipleAlignment-class), 67
- compact, 120, 126
- compare, ANY, XStringSet-method
  - (XStringSet-comparison), 129
- compare, XStringSet, ANY-method
  - (XStringSet-comparison), 129
- compare, XStringSet, XStringSet-method
  - (XStringSet-comparison), 129
- compareStrings (align-utils), 4
- compareStrings, AlignedXStringSet0, AlignedXStringSet-method
  - (align-utils), 4
- compareStrings, character, character-method
  - (align-utils), 4
- compareStrings, PairwiseAlignments, missing-method
  - (align-utils), 4
- compareStrings, XString, XString-method
  - (align-utils), 4
- compareStrings, XStringSet, XStringSet-method
  - (align-utils), 4
- complement (reverseComplement), 104
- complement, DNASTring-method
  - (reverseComplement), 104
- complement, DNASTringSet-method
  - (reverseComplement), 104
- complement, MaskedDNASTring-method
  - (reverseComplement), 104
- complement, MaskedRNASTring-method
  - (reverseComplement), 104
- complement, RNASTring-method
  - (reverseComplement), 104
- complement, RNASTringSet-method
  - (reverseComplement), 104
- complement, XStringViews-method
  - (reverseComplement), 104
- complementedPalindromeArmLength
  - (findPalindromes), 14
- complementedPalindromeArmLength, DNASTring-method
  - (findPalindromes), 14
- complementedPalindromeArmLength, XStringViews-method
  - (findPalindromes), 14
- complementedPalindromeLeftArm
  - (findPalindromes), 14
- complementedPalindromeLeftArm, DNASTring-method
  - (findPalindromes), 14
- complementedPalindromeLeftArm, XStringViews-method
  - (findPalindromes), 14
- complementedPalindromeRightArm
  - (findPalindromes), 14
- complementedPalindromeRightArm, DNASTring-method
  - (findPalindromes), 14
- complementedPalindromeRightArm, XStringViews-method
  - (findPalindromes), 14
- CompressedIRangesList, 66, 86
- computeAllFlinks (PDict-class), 89
- computeAllFlinks, ATree2-method
  - (PDict-class), 89
- consensusMatrix, 6, 63, 64, 86
- consensusMatrix, AlignedXStringSet-method
  - (letterFrequency), 24
- consensusMatrix, character-method
  - (letterFrequency), 24
- consensusMatrix, matrix-method
  - (letterFrequency), 24
- consensusMatrix, MultipleAlignment-method
  - (MultipleAlignment-class), 67
- consensusMatrix, PairwiseAlignmentsSingleSubject-method
  - (align-utils), 4
- consensusMatrix, XStringSet-method
  - (letterFrequency), 24
- consensusMatrix, XStringViews-method
  - (letterFrequency), 24
- consensusString, 70, 86
- consensusString (letterFrequency), 24
- consensusString, AAMultipleAlignment-method
  - (MultipleAlignment-class), 67
- consensusString, ANY-method
  - (letterFrequency), 24
- consensusString, BStringSet-method
  - (letterFrequency), 24
- consensusString, DNAMultipleAlignment-method
  - (MultipleAlignment-class), 67
- consensusString, DNASTringSet-method
  - (letterFrequency), 24
- consensusString, matrix-method
  - (letterFrequency), 24

- consensusString, MultipleAlignment-method (MultipleAlignment-class), 67
- consensusString, RNAMultipleAlignment-method (MultipleAlignment-class), 67
- consensusString, RNAStrngSet-method (letterFrequency), 24
- consensusString, XStringViews-method (letterFrequency), 24
- consensusViews (MultipleAlignment-class), 67
- consensusViews, AAMultipleAlignment-method (MultipleAlignment-class), 67
- consensusViews, DNAMultipleAlignment-method (MultipleAlignment-class), 67
- consensusViews, MultipleAlignment-method (MultipleAlignment-class), 67
- consensusViews, RNAMultipleAlignment-method (MultipleAlignment-class), 67
- countIndex (MIndex-class), 65
- countIndex, ByPos\_MIndex-method (MIndex-class), 65
- countIndex, MIndex-method (MIndex-class), 65
- countPattern, 49
- countPattern (matchPattern), 43
- countPattern, BOC2\_SubjectString-method (BOC\_SubjectString-class), 9
- countPattern, character-method (matchPattern), 43
- countPattern, MaskedXString-method (matchPattern), 43
- countPattern, XString-method (matchPattern), 43
- countPattern, XStringSet-method (matchPattern), 43
- countPattern, XStringViews-method (matchPattern), 43
- countPDict, 27
- countPDict (matchPDict), 48
- countPDict, MaskedXString-method (matchPDict), 48
- countPDict, XString-method (matchPDict), 48
- countPDict, XStringSet-method (matchPDict), 48
- countPDict, XStringViews-method (matchPDict), 48
- countPWM (matchPWM), 62
- countPWM, character-method (matchPWM), 62
- countPWM, DNAStrng-method (matchPWM), 62
- countPWM, MaskedDNAStrng-method (matchPWM), 62
- countPWM, XStringViews-method (matchPWM), 62
- coverage, 5, 27, 41
- coverage, AlignedXStringSet0-method (align-utils), 4
- coverage, MaskedXString-method (match-utils), 40
- coverage, MIndex-method (match-utils), 40
- coverage, PairwiseAlignmentsSingleSubject-method, 86
- coverage, PairwiseAlignmentsSingleSubject-method (align-utils), 4
- coverage, PairwiseAlignmentsSingleSubjectSummary-method (align-utils), 4
- deletion (InDel-class), 19
- deletion, InDel-method (InDel-class), 19
- deletion, PairwiseAlignments-method (PairwiseAlignments-class), 83
- detail, 10
- detail, MultipleAlignment-method (MultipleAlignment-class), 67
- dim, MultipleAlignment-method (MultipleAlignment-class), 67
- dinucleotideFrequency (nucleotideFrequency), 73
- dinucleotideFrequencyTest, 11
- dinucleotideFrequencyTest, DNAStrngSet-method (dinucleotideFrequencyTest), 11
- dinucleotideFrequencyTest, RNAStrngSet-method (dinucleotideFrequencyTest), 11
- dist, 109
- dna2rna (translate), 113
- DNA\_ALPHABET, 79, 92, 124, 129, 133
- DNA\_ALPHABET (DNAStrng-class), 13
- DNA\_BASES (DNAStrng-class), 13
- DNAMultipleAlignment (MultipleAlignment-class), 67
- DNAMultipleAlignment-class (MultipleAlignment-class), 67
- DNAStrng, 4, 15, 17, 22, 32, 42, 49, 60, 63, 90, 92, 102–104, 107, 112–114, 119, 120, 123, 129, 138
- DNAStrng (DNAStrng-class), 13

- DNASTring-class, [13](#), [15](#), [64](#), [104](#), [107](#), [111](#), [114](#), [120](#), [123](#), [134](#)
- DNASTringSet, [11](#), [49](#), [79](#), [90](#), [91](#), [96](#), [102–104](#), [113](#), [129](#), [135](#)
- DNASTringSet (XStringSet-class), [123](#)
- DNASTringSet-class, [50](#), [92](#), [97](#), [104](#)
- DNASTringSet-class (XStringSet-class), [123](#)
- DNASTringSetList
  - (XStringSetList-class), [135](#)
- DNASTringSetList-class
  - (XStringSetList-class), [135](#)
- duplicate, [130](#)
- duplicate, PDict-method (PDict-class), [89](#)
- duplicate, PreprocessedTB-method (PDict-class), [89](#)
- Dups, [133](#)
- elementLengths, [135](#)
- elementLengths, MIndex-method (MIndex-class), [65](#)
- encoding, XStringQuality-method (XStringQuality-class), [122](#)
- end, AlignedXStringSet0-method (AlignedXStringSet-class), [6](#)
- endIndex (MIndex-class), [65](#)
- endIndex, ByPos\_MIndex-method (MIndex-class), [65](#)
- errorSubstitutionMatrices
  - (substitution.matrices), [109](#)
- Expanded\_TB\_PDICT (PDict-class), [89](#)
- Expanded\_TB\_PDICT-class (PDict-class), [89](#)
- extractAllMatches (matchPDICT), [48](#)
- extractAt, [79](#)
- extractAt (replaceAt), [98](#)
- extractAt, XString-method (replaceAt), [98](#)
- extractAt, XStringSet-method (replaceAt), [98](#)
- extractTranscripts, [113](#)
- fasta.info (XStringSet-io), [132](#)
- fastq.geometry (XStringSet-io), [132](#)
- findComplementedPalindromes
  - (findPalindromes), [14](#)
- findComplementedPalindromes, DNASTring-method (findPalindromes), [14](#)
- findComplementedPalindromes, MaskedXString-method (findPalindromes), [14](#)
- findComplementedPalindromes, XStringViews-method (findPalindromes), [14](#)
- findPalindromes, [14](#), [43](#), [60](#), [104](#)
- findPalindromes, MaskedXString-method (findPalindromes), [14](#)
- findPalindromes, XString-method (findPalindromes), [14](#)
- findPalindromes, XStringViews-method (findPalindromes), [14](#)
- gaps, [138](#)
- gaps, MaskedXString-method (MaskedXString-class), [35](#)
- GENETIC\_CODE, [8](#), [16](#), [75](#), [114](#)
- getSeq, [17](#)
- getSeq, BSgenome-method, [18](#)
- gregexpr, [19](#)
- gregexpr2, [18](#)
- hasAllFlinks (PDict-class), [89](#)
- hasAllFlinks, ACTree2-method (PDict-class), [89](#)
- hasLetterAt, [75](#)
- hasLetterAt (lowlevel-matching), [30](#)
- hasOnlyBaseLetters (letterFrequency), [24](#)
- hasOnlyBaseLetters, DNASTring-method (letterFrequency), [24](#)
- hasOnlyBaseLetters, DNASTringSet-method (letterFrequency), [24](#)
- hasOnlyBaseLetters, MaskedXString-method (letterFrequency), [24](#)
- hasOnlyBaseLetters, RNASTring-method (letterFrequency), [24](#)
- hasOnlyBaseLetters, RNASTringSet-method (letterFrequency), [24](#)
- hasOnlyBaseLetters, XStringViews-method (letterFrequency), [24](#)
- head, PDICT3Parts-method (PDict-class), [89](#)
- head, TB\_PDICT-method (PDict-class), [89](#)
- HNF4alpha, [19](#)
- IlluminaQuality (XStringQuality-class), [122](#)
- IlluminaQuality-class, [111](#)
- IlluminaQuality-class
  - (XStringQuality-class), [122](#)

- InDel (InDel-class), 19
- indel (AlignedXStringSet-class), 6
- indel, AlignedXStringSet0-method (AlignedXStringSet-class), 6
- indel, PairwiseAlignments-method (PairwiseAlignments-class), 83
- InDel-class, 19
- initialize, ACTree2-method (PDict-class), 89
- initialize, BOC2\_SubjectString-method (BOC\_SubjectString-class), 9
- initialize, BOC\_SubjectString-method (BOC\_SubjectString-class), 9
- initialize, PreprocessedTB-method (PDict-class), 89
- initialize, Twobit-method (PDict-class), 89
- injectHardMask, 20, 37, 103
- injectHardMask, MaskedXString-method (injectHardMask), 20
- injectHardMask, XStringViews-method (injectHardMask), 20
- injectSNPs, 103
- insertion (InDel-class), 19
- insertion, InDel-method (InDel-class), 19
- insertion, PairwiseAlignments-method (PairwiseAlignments-class), 83
- IntegerList, 98, 99
- intersect, XStringSet, XStringSet-method (XStringSet-class), 123
- IRanges, 66, 125
- IRanges-class, 66
- is.unsorted, 130
- isMatchingAt, 49, 50
- isMatchingAt (lowlevel-matching), 30
- isMatchingEndingAt (lowlevel-matching), 30
- isMatchingEndingAt, character-method (lowlevel-matching), 30
- isMatchingEndingAt, XString-method (lowlevel-matching), 30
- isMatchingEndingAt, XStringSet-method (lowlevel-matching), 30
- isMatchingStartingAt, 115, 116
- isMatchingStartingAt (lowlevel-matching), 30
- isMatchingStartingAt, character-method (lowlevel-matching), 30
- isMatchingStartingAt, XString-method (lowlevel-matching), 30
- isMatchingStartingAt, XStringSet-method (lowlevel-matching), 30
- IUPAC\_CODE\_MAP, 13, 22, 32, 33, 42, 92, 103, 104, 106, 107
- lcprefix (pmatchPattern), 96
- lcprefix, character, character-method (pmatchPattern), 96
- lcprefix, character, XString-method (pmatchPattern), 96
- lcprefix, XString, character-method (pmatchPattern), 96
- lcprefix, XString, XString-method (pmatchPattern), 96
- lcs substr (pmatchPattern), 96
- lcs substr, character, character-method (pmatchPattern), 96
- lcs substr, character, XString-method (pmatchPattern), 96
- lcs substr, XString, character-method (pmatchPattern), 96
- lcs substr, XString, XString-method (pmatchPattern), 96
- lcsuffix (pmatchPattern), 96
- lcsuffix, character, character-method (pmatchPattern), 96
- lcsuffix, character, XString-method (pmatchPattern), 96
- lcsuffix, XString, character-method (pmatchPattern), 96
- lcsuffix, XString, XString-method (pmatchPattern), 96
- length, AlignedXStringSet0-method (AlignedXStringSet-class), 6
- length, MaskedXString-method (MaskedXString-class), 35
- length, MIndex-method (MIndex-class), 65
- length, PairwiseAlignments-method (PairwiseAlignments-class), 83
- length, PairwiseAlignmentsSingleSubjectSummary-method (PairwiseAlignments-class), 83
- length, PDict-method (PDict-class), 89
- length, PDict3Parts-method (PDict-class), 89
- length, PreprocessedTB-method (PDict-class), 89
- letter, 4, 13, 23, 107, 120, 121, 138

- letter, character-method (letter), 23
- letter, MaskedXString-method (letter), 23
- letter, XString-method (letter), 23
- letter, XStringViews-method (letter), 23
- letterFrequency, 24
- letterFrequency, MaskedXString-method (letterFrequency), 24
- letterFrequency, XString-method (letterFrequency), 24
- letterFrequency, XStringSet-method (letterFrequency), 24
- letterFrequency, XStringViews-method (letterFrequency), 24
- letterFrequencyInSlidingView (letterFrequency), 24
- letterFrequencyInSlidingView, XString-method (letterFrequency), 24
- List, 135
- List-class, 136
- longestConsecutive, 29
- lowlevel-matching, 30, 41, 45, 116
  
- mask (maskMotif), 38
- MaskCollection, 35, 36
- MaskCollection-class, 37, 38
- MaskedAAString, 20
- MaskedAAString (MaskedXString-class), 35
- MaskedAAString-class (MaskedXString-class), 35
- MaskedBString, 20
- MaskedBString (MaskedXString-class), 35
- MaskedBString-class (MaskedXString-class), 35
- maskeddim (MultipleAlignment-class), 67
- maskeddim, MultipleAlignment-method (MultipleAlignment-class), 67
- MaskedDNAStrng, 20, 63, 104, 113, 114
- MaskedDNAStrng (MaskedXString-class), 35
- MaskedDNAStrng-class, 50
- MaskedDNAStrng-class (MaskedXString-class), 35
- maskedncol (MultipleAlignment-class), 67
- maskedncol, MultipleAlignment-method (MultipleAlignment-class), 67
- maskednrow (MultipleAlignment-class), 67
- maskednrow, MultipleAlignment-method (MultipleAlignment-class), 67
- maskedratio, MaskedXString-method (MaskedXString-class), 35
- maskedratio, MultipleAlignment-method (MultipleAlignment-class), 67
- MaskedRNAStrng, 20, 104, 113, 114
- MaskedRNAStrng (MaskedXString-class), 35
- MaskedRNAStrng-class (MaskedXString-class), 35
- maskedwidth, MaskedXString-method (MaskedXString-class), 35
- MaskedXString, 9, 20, 21, 23–27, 38, 42, 44, 49, 73, 75
- MaskedXString (MaskedXString-class), 35
- MaskedXString-class, 10, 21, 23, 27, 35, 38, 43, 70, 75, 104, 114
- maskGaps (MultipleAlignment-class), 67
- maskGaps, MultipleAlignment-method (MultipleAlignment-class), 67
- maskMotif, 15, 21, 37, 38, 45
- maskMotif, MaskedXString, character-method (maskMotif), 38
- maskMotif, MaskedXString, XString-method (maskMotif), 38
- maskMotif, MultipleAlignment, ANY-method (MultipleAlignment-class), 67
- maskMotif, XString, ANY-method (maskMotif), 38
- masks (MaskedXString-class), 35
- masks, MaskedXString-method (MaskedXString-class), 35
- masks, XString-method (MaskedXString-class), 35
- masks<- (MaskedXString-class), 35
- masks<-, MaskedXString, MaskCollection-method (MaskedXString-class), 35
- masks<-, MaskedXString, NULL-method (MaskedXString-class), 35
- masks<-, XString, ANY-method (MaskedXString-class), 35
- masks<-, XString, NULL-method (MaskedXString-class), 35
- match, 130
- match, ANY, XStringSet-method (XStringSet-comparison), 129
- match, XStringSet, ANY-method (XStringSet-comparison), 129
- match, XStringSet, XStringSet-method

- (XStringSet-comparison), 129
- match-utils, 6, 40, 95
- matchLRPatterns, 15, 33, 42, 45, 60, 116
- matchLRPatterns, MaskedXString-method (matchLRPatterns), 42
- matchLRPatterns, XString-method (matchLRPatterns), 42
- matchLRPatterns, XStringViews-method (matchLRPatterns), 42
- matchPattern, 10, 15, 19, 33, 38, 40–42, 43, 43, 49, 50, 60–62, 64, 82, 96, 116
- matchPattern, BOC2\_SubjectString-method (BOC\_SubjectString-class), 9
- matchPattern, BOC\_SubjectString-method (BOC\_SubjectString-class), 9
- matchPattern, character-method (matchPattern), 43
- matchPattern, MaskedXString-method (matchPattern), 43
- matchPattern, XString-method (matchPattern), 43
- matchPattern, XStringSet-method (matchPattern), 43
- matchPattern, XStringViews-method (matchPattern), 43
- matchPDict, 33, 40, 41, 45, 48, 56, 57, 61, 62, 65, 66, 82, 90, 92
- matchPDict, MaskedXString-method (matchPDict), 48
- matchPDict, XString-method (matchPDict), 48
- matchPDict, XStringSet-method (matchPDict), 48
- matchPDict, XStringViews-method (matchPDict), 48
- matchPDict-exact (matchPDict), 48
- matchPDict-inexact, 50, 56
- matchProbePair, 15, 43, 45, 59
- matchProbePair, DNAStrng-method (matchProbePair), 59
- matchProbePair, MaskedDNAStrng-method (matchProbePair), 59
- matchProbePair, XStringViews-method (matchProbePair), 59
- matchprobes, 61
- matchPWM, 62
- matchPWM, character-method (matchPWM), 62
- matchPWM, DNAStrng-method (matchPWM), 62
- matchPWM, MaskedDNAStrng-method (matchPWM), 62
- matchPWM, XStringViews-method (matchPWM), 62
- maxScore (matchPWM), 62
- maxScore, ANY-method (matchPWM), 62
- maxWeights (matchPWM), 62
- maxWeights, matrix-method (matchPWM), 62
- mergeIUPACLetters (IUPAC\_CODE\_MAP), 22
- MIndex, 41, 45, 50
- MIndex (MIndex-class), 65
- MIndex-class, 41, 45, 50, 57, 65, 138
- minScore (matchPWM), 62
- minScore, ANY-method (matchPWM), 62
- minWeights (matchPWM), 62
- minWeights, matrix-method (matchPWM), 62
- misc, 66
- mismatch, 45
- mismatch (match-utils), 40
- mismatch, AlignedXStringSet0, missing-method (align-utils), 4
- mismatch, ANY, XStringViews-method (match-utils), 40
- mismatchSummary (align-utils), 4
- mismatchSummary, AlignedXStringSet0-method (align-utils), 4
- mismatchSummary, PairwiseAlignmentsSingleSubject-method (align-utils), 4
- mismatchSummary, PairwiseAlignmentsSingleSubjectSummary-method (align-utils), 4
- mismatchSummary, QualityAlignedXStringSet-method (align-utils), 4
- mismatchTable (align-utils), 4
- mismatchTable, AlignedXStringSet0-method (align-utils), 4
- mismatchTable, PairwiseAlignments-method (align-utils), 4
- mismatchTable, QualityAlignedXStringSet-method (align-utils), 4
- mkAllStrings (nucleotideFrequency), 73
- MTB\_PDICT (PDICT-class), 89
- MTB\_PDICT-class (PDICT-class), 89
- MultipleAlignment, 68
- MultipleAlignment (MultipleAlignment-class), 67
- MultipleAlignment-class, 67
- N50 (misc), 66
- names, MIndex-method (MIndex-class), 65



- names, PDict-method (PDict-class), 89
- names<-, MIndex-method (MIndex-class), 65
- names<-, PDict-method (PDict-class), 89
- narrow, 68, 124, 126
- narrow, character-method (XStringSet-class), 123
- narrow, QualityScaledXStringSet-method (QualityScaledXStringSet-class), 96
- nchar, 27
- nchar, AlignedXStringSet0-method (AlignedXStringSet-class), 6
- nchar, MaskedXString-method (MaskedXString-class), 35
- nchar, MultipleAlignment-method (MultipleAlignment-class), 67
- nchar, PairwiseAlignments-method (PairwiseAlignments-class), 83
- nchar, PairwiseAlignmentsSingleSubjectSummary-method (PairwiseAlignments-class), 83
- nchar, XString-method (XString-class), 118
- nchar, XStringSet-method (XStringSet-class), 123
- nchar, XStringViews-method (XStringViews-class), 137
- ncol, MultipleAlignment-method (MultipleAlignment-class), 67
- nedit (align-utils), 4
- nedit, PairwiseAlignments-method (align-utils), 4
- nedit, PairwiseAlignmentsSingleSubjectSummary-method (align-utils), 4
- neditAt (lowlevel-matching), 30
- neditEndingAt, 116
- neditEndingAt (lowlevel-matching), 30
- neditEndingAt, character-method (lowlevel-matching), 30
- neditEndingAt, XString-method (lowlevel-matching), 30
- neditEndingAt, XStringSet-method (lowlevel-matching), 30
- neditStartingAt, 115, 116
- neditStartingAt (lowlevel-matching), 30
- neditStartingAt, character-method (lowlevel-matching), 30
- neditStartingAt, XString-method (lowlevel-matching), 30
- neditStartingAt, XStringSet-method (lowlevel-matching), 30
- neditStartingAt, XString-method (lowlevel-matching), 30
- neditStartingAt, XStringSet-method (lowlevel-matching), 30
- needwunsQS, 72
- needwunsQS, character, character-method (needwunsQS), 72
- needwunsQS, character, XString-method (needwunsQS), 72
- needwunsQS, XString, character-method (needwunsQS), 72
- needwunsQS, XString, XString-method (needwunsQS), 72
- nindel (AlignedXStringSet-class), 6
- nindel, AlignedXStringSet0-method (AlignedXStringSet-class), 6
- nindel, PairwiseAlignments-method (PairwiseAlignments-class), 83
- nindel, PairwiseAlignmentsSingleSubjectSummary-method (PairwiseAlignments-class), 83
- nmatch (match-utils), 40
- nmatch, ANY, XStringViews-method (match-utils), 40
- nmatch, PairwiseAlignments, missing-method (align-utils), 4
- nmatch, PairwiseAlignmentsSingleSubjectSummary, missing-method (align-utils), 4
- nmismatch (match-utils), 40
- nmismatch, AlignedXStringSet0, missing-method (align-utils), 4
- nmismatch, ANY, XStringViews-method (match-utils), 40
- nmismatch, PairwiseAlignments, missing-method (align-utils), 4
- nmismatch, PairwiseAlignmentsSingleSubjectSummary, missing-method (align-utils), 4
- nnodes (PDict-class), 89
- nnodes, ATree2-method (PDict-class), 89
- NormalIRanges, 69
- nrow, MultipleAlignment-method (MultipleAlignment-class), 67
- nucleotideFrequency, 73
- nucleotideFrequencyAt, 12, 33
- nucleotideFrequencyAt (nucleotideFrequency), 73
- nucleotideFrequencyAt, XStringSet-method (nucleotideFrequency), 73
- nucleotideFrequencyAt, XStringViews-method (nucleotideFrequency), 73
- nucleotideSubstitutionMatrix

- (substitution.matrices), 109
- oligonucleotideFrequency, 27
- oligonucleotideFrequency
  - (nucleotideFrequency), 73
- oligonucleotideFrequency,MaskedXString-method
  - (nucleotideFrequency), 73
- oligonucleotideFrequency,XString-method
  - (nucleotideFrequency), 73
- oligonucleotideFrequency,XStringSet-method
  - (nucleotideFrequency), 73
- oligonucleotideFrequency,XStringViews-method
  - (nucleotideFrequency), 73
- oligonucleotideTransitions
  - (nucleotideFrequency), 73
- order, 130
- padAndClip, 78, 99
- pairwiseAlignment, 6, 8, 20, 45, 73, 80, 87, 88, 95, 109, 111, 123
- pairwiseAlignment,ANY,ANY-method
  - (pairwiseAlignment), 80
- pairwiseAlignment,ANY,QualityScaledXStringSet-method
  - (pairwiseAlignment), 80
- pairwiseAlignment,QualityScaledXStringSet,ANY-method
  - (pairwiseAlignment), 80
- pairwiseAlignment,QualityScaledXStringSet,QualityScaledXStringSet-method
  - (pairwiseAlignment), 80
- PairwiseAlignments, 82, 87, 88, 94
- PairwiseAlignments
  - (PairwiseAlignments-class), 83
- PairwiseAlignments,character,character-method
  - (PairwiseAlignments-class), 83
- PairwiseAlignments,character,missing-method
  - (PairwiseAlignments-class), 83
- PairwiseAlignments,XString,XString-method
  - (PairwiseAlignments-class), 83
- PairwiseAlignments,XStringSet,missing-method
  - (PairwiseAlignments-class), 83
- PairwiseAlignments-class, 6, 73, 82, 83, 88, 95, 111, 123
- PairwiseAlignments-io, 87
- PairwiseAlignmentsSingleSubject, 82
- PairwiseAlignmentsSingleSubject
  - (PairwiseAlignments-class), 83
- PairwiseAlignmentsSingleSubject,character,character-method
  - (PairwiseAlignments-class), 83
- PairwiseAlignmentsSingleSubject,character,missing-method
  - (PairwiseAlignments-class), 83
- PairwiseAlignmentsSingleSubject,XString,XString-method
  - (PairwiseAlignments-class), 83
- PairwiseAlignmentsSingleSubject,XStringSet,missing-method
  - (PairwiseAlignments-class), 83
- PairwiseAlignmentsSingleSubject-class
  - (PairwiseAlignments-class), 83
- PairwiseAlignmentsSingleSubjectSummary
  - (PairwiseAlignments-class), 83
- PairwiseAlignmentsSingleSubjectSummary-class
  - (PairwiseAlignments-class), 83
- palindromeArmLength (findPalindromes), 14
- palindromeArmLength,XString-method
  - (findPalindromes), 14
- palindromeArmLength,XStringViews-method
  - (findPalindromes), 14
- palindromeLeftArm (findPalindromes), 14
- palindromeLeftArm,XString-method
  - (findPalindromes), 14
- palindromeLeftArm,XStringViews-method
  - (findPalindromes), 14
- palindromeRightArm (findPalindromes), 14
- palindromeRightArm,XString-method
  - (findPalindromes), 14
- palindromeRightArm,XStringViews-method
  - (findPalindromes), 14
- PAM120 (substitution.matrices), 109
- PAM250 (substitution.matrices), 109
- PAM30 (substitution.matrices), 109
- PAM40 (substitution.matrices), 109
- PAM70 (substitution.matrices), 109
- partitioning (XStringSetList-class), 135
- PartitioningByEnd, 135
- paste, 118
- pattern (XStringPartialMatches-class), 121
- pattern,PairwiseAlignments-method
  - (PairwiseAlignments-class), 83
- pattern,XStringPartialMatches-method
  - (XStringPartialMatches-class), 121
- patternFrequency (PDict-class), 89
- patternFrequency,PDict-method
  - (PDict-class), 89
- PDict (PDict-class), 89
- PDict,character-method (PDict-class), 89
- PDict,missing-method (PDict-class), 89
- PDict,character-method (PDict-class), 89

- PDict,DNAStringSet-method  
(PDict-class), 89
- PDict,probletable-method (PDict-class),  
89
- PDict,XStringViews-method  
(PDict-class), 89
- PDict-class, 50, 57, 66, 89
- PDict3Parts (PDict-class), 89
- PDict3Parts-class (PDict-class), 89
- phiX174Phage, 93
- PhredQuality (XStringQuality-class), 122
- PhredQuality-class, 111
- PhredQuality-class  
(XStringQuality-class), 122
- pid, 87, 94
- pid,PairwiseAlignments-method (pid), 94
- pmatchPattern, 96
- pmatchPattern,character-method  
(pmatchPattern), 96
- pmatchPattern,XString-method  
(pmatchPattern), 96
- pmatchPattern,XStringViews-method  
(pmatchPattern), 96
- PreprocessedTB (PDict-class), 89
- PreprocessedTB-class (PDict-class), 89
- print.needwunsQS (needwunsQS), 72
- PWM (matchPWM), 62
- PWM,character-method (matchPWM), 62
- PWM,DNAStringSet-method (matchPWM), 62
- PWM,matrix-method (matchPWM), 62
- PWMScoreStartingAt (matchPWM), 62
  
- quality  
(QualityScaledXStringSet-class),  
96
- quality,QualityScaledXStringSet-method  
(QualityScaledXStringSet-class),  
96
- QualityAlignedXStringSet  
(AlignedXStringSet-class), 6
- QualityAlignedXStringSet-class  
(AlignedXStringSet-class), 6
- QualityScaledAAStringSet  
(QualityScaledXStringSet-class),  
96
- QualityScaledAAStringSet-class  
(QualityScaledXStringSet-class),  
96
  
- QualityScaledBStringSet  
(QualityScaledXStringSet-class),  
96
- QualityScaledBStringSet-class  
(QualityScaledXStringSet-class),  
96
- QualityScaledDNAStringSet  
(QualityScaledXStringSet-class),  
96
- QualityScaledDNAStringSet-class  
(QualityScaledXStringSet-class),  
96
- QualityScaledRNAStringSet  
(QualityScaledXStringSet-class),  
96
- QualityScaledRNAStringSet-class  
(QualityScaledXStringSet-class),  
96
- QualityScaledXStringSet, 81
- QualityScaledXStringSet  
(QualityScaledXStringSet-class),  
96
- QualityScaledXStringSet-class, 96
- qualitySubstitutionMatrices  
(substitution.matrices), 109
- quPhiX174 (phiX174Phage), 93
  
- Ranges, 66, 78, 79, 98, 99
- RangesList, 66, 98, 99
- rank, 130
- read.Mask, 38
- readAAMultipleAlignment  
(MultipleAlignment-class), 67
- readAAStringSet (XStringSet-io), 132
- readBStringSet (XStringSet-io), 132
- readDNAMultipleAlignment  
(MultipleAlignment-class), 67
- readDNAStringSet (XStringSet-io), 132
- readRNAMultipleAlignment  
(MultipleAlignment-class), 67
- readRNAStringSet (XStringSet-io), 132
- rep,AlignedXStringSet0-method  
(AlignedXStringSet-class), 6
- rep,PairwiseAlignments-method  
(PairwiseAlignments-class), 83
- replaceAt, 79, 98, 103
- replaceAt,XString-method (replaceAt), 98
- replaceAt,XStringSet-method  
(replaceAt), 98

- replaceLetterAt, *10, 21, 99, 102*
- replaceLetterAt, DNASTring-method  
(replaceLetterAt), *102*
- replaceLetterAt, DNASTringSet-method  
(replaceLetterAt), *102*
- rev, *75*
- reverse, *104*
- reverse, MaskedXString-method  
(reverseComplement), *104*
- reverseComplement, *10, 13, 37, 43, 60, 64, 75, 104, 107, 114, 120*
- reverseComplement, DNASTring-method  
(reverseComplement), *104*
- reverseComplement, DNASTringSet-method  
(reverseComplement), *104*
- reverseComplement, MaskedDNASTring-method  
(reverseComplement), *104*
- reverseComplement, MaskedRNASTring-method  
(reverseComplement), *104*
- reverseComplement, matrix-method  
(matchPWM), *62*
- reverseComplement, RNASTring-method  
(reverseComplement), *104*
- reverseComplement, RNASTringSet-method  
(reverseComplement), *104*
- reverseComplement, XStringViews-method  
(reverseComplement), *104*
- Rle, *41, 102*
- rna2dna (translate), *113*
- RNA\_ALPHABET, *124, 129, 133*
- RNA\_ALPHABET (RNASTring-class), *106*
- RNA\_BASES (RNASTring-class), *106*
- RNA\_GENETIC\_CODE (GENETIC\_CODE), *16*
- RNAMultipleAlignment  
(MultipleAlignment-class), *67*
- RNAMultipleAlignment-class  
(MultipleAlignment-class), *67*
- RNASTring, *4, 13, 17, 22, 32, 42, 104, 113, 114, 119, 120, 123, 129, 138*
- RNASTring (RNASTring-class), *106*
- RNASTring-class, *13, 104, 106, 114, 120, 134*
- RNASTringSet, *11, 79, 96, 104, 113, 129, 135*
- RNASTringSet (XStringSet-class), *123*
- RNASTringSet-class, *97, 104*
- RNASTringSet-class (XStringSet-class),  
*123*
- RNASTringSetList  
(XStringSetList-class), *135*
- RNASTringSetList-class  
(XStringSetList-class), *135*
- rowmask (MultipleAlignment-class), *67*
- rowmask, MultipleAlignment-method  
(MultipleAlignment-class), *67*
- rowmask<- (MultipleAlignment-class), *67*
- rowmask<-, MultipleAlignment, ANY-method  
(MultipleAlignment-class), *67*
- rowmask<-, MultipleAlignment, NormalIRanges-method  
(MultipleAlignment-class), *67*
- rowmask<-, MultipleAlignment, NULL-method  
(MultipleAlignment-class), *67*
- rownames, MultipleAlignment-method  
(MultipleAlignment-class), *67*
- rownames<-, MultipleAlignment-method  
(MultipleAlignment-class), *67*
- saveXStringSet (XStringSet-io), *132*
- score, PairwiseAlignments-method  
(PairwiseAlignments-class), *83*
- score, PairwiseAlignmentsSingleSubjectSummary-method  
(PairwiseAlignments-class), *83*
- seqtype, AAString-method  
(XString-class), *118*
- seqtype, AlignedXStringSet0-method  
(AlignedXStringSet-class), *6*
- seqtype, BString-method (XString-class),  
*118*
- seqtype, DNASTring-method  
(XString-class), *118*
- seqtype, MaskedXString-method  
(MaskedXString-class), *35*
- seqtype, MultipleAlignment-method  
(MultipleAlignment-class), *67*
- seqtype, PairwiseAlignments-method  
(PairwiseAlignments-class), *83*
- seqtype, RNASTring-method  
(XString-class), *118*
- seqtype, XStringSet-method  
(XStringSet-class), *123*
- seqtype, XStringSetList-method  
(XStringSetList-class), *135*
- seqtype, XStringViews-method  
(XStringViews-class), *137*
- seqtype<-, MaskedXString-method  
(MaskedXString-class), *35*
- seqtype<-, XString-method  
(XString-class), *118*

- seqtype<-, XStringSet-method  
(XStringSet-class), 123
- seqtype<-, XStringSetList-method  
(XStringSetList-class), 135
- seqtype<-, XStringViews-method  
(XStringViews-class), 137
- setdiff, XStringSet, XStringSet-method  
(XStringSet-class), 123
- setequal, XStringSet, XStringSet-method  
(XStringSet-class), 123
- show, 10
- show, ATree2-method (PDict-class), 89
- show, AlignedXStringSet0-method  
(AlignedXStringSet-class), 6
- show, MaskedXString-method  
(MaskedXString-class), 35
- show, MIndex-method (MIndex-class), 65
- show, MTB\_PDICT-method (PDict-class), 89
- show, MultipleAlignment-method  
(MultipleAlignment-class), 67
- show, PairwiseAlignments-method  
(PairwiseAlignments-class), 83
- show, PairwiseAlignmentsSingleSubjectSummary-method  
(PairwiseAlignments-class), 83
- show, QualityScaledXStringSet-method  
(QualityScaledXStringSet-class),  
96
- show, TB\_PDICT-method (PDict-class), 89
- show, Twobit-method (PDict-class), 89
- show, XString-method (XString-class), 118
- show, XStringPartialMatches-method  
(XStringPartialMatches-class),  
121
- show, XStringSet-method  
(XStringSet-class), 123
- show, XStringSetList-method  
(XStringSetList-class), 135
- show, XStringViews-method  
(XStringViews-class), 137
- SolexaQuality (XStringQuality-class),  
122
- SolexaQuality-class, 111
- SolexaQuality-class  
(XStringQuality-class), 122
- sort, 130
- srPhiX174 (phiX174Phage), 93
- stackStrings (padAndClip), 78
- stackStringsFromBam, 79
- start, AlignedXStringSet0-method  
(AlignedXStringSet-class), 6
- startIndex (MIndex-class), 65
- startIndex, ByPos\_MIndex-method  
(MIndex-class), 65
- stringDist, 82, 107
- stringDist, character-method  
(stringDist), 107
- stringDist, QualityScaledXStringSet-method  
(stringDist), 107
- stringDist, XStringSet-method  
(stringDist), 107
- strsplit, 27
- subject, PairwiseAlignments-method  
(PairwiseAlignments-class), 83
- subpatterns  
(XStringPartialMatches-class),  
121
- subpatterns, XStringPartialMatches-method  
(XStringPartialMatches-class),  
121
- subseq, 23, 99, 120, 125, 126
- subseq, character-method  
(XStringSet-class), 123
- subseq, MaskedXString-method  
(MaskedXString-class), 35
- subseq<-, character-method  
(XStringSet-class), 123
- subseq<-, XStringSet-method  
(XStringSet-class), 123
- substitution.matrices, 73, 82, 87, 88, 109,  
109
- substr, 125, 126
- substr, XString-method (XString-class),  
118
- substring, 27
- substring, XString-method  
(XString-class), 118
- summary, PairwiseAlignmentsSingleSubject-method  
(PairwiseAlignments-class), 83
- tail, PDict3Parts-method (PDict-class),  
89
- tail, TB\_PDICT-method (PDict-class), 89
- tb (PDict-class), 89
- tb, PDict3Parts-method (PDict-class), 89
- tb, PreprocessedTB-method (PDict-class),  
89
- tb, TB\_PDICT-method (PDict-class), 89

- tb.width (PDict-class), 89
- tb.width, PDict3Parts-method (PDict-class), 89
- tb.width, PreprocessedTB-method (PDict-class), 89
- tb.width, TB\_PDICT-method (PDict-class), 89
- TB\_PDICT (PDict-class), 89
- TB\_PDICT-class (PDict-class), 89
- threebands, 125
- threebands, character-method (XStringSet-class), 123
- toComplex, 112
- toComplex, DNASTring-method (toComplex), 112
- toString, AlignedXStringSet0-method (AlignedXStringSet-class), 6
- toString, MaskedXString-method (MaskedXString-class), 35
- toString, PairwiseAlignmentsSingleSubject-method (PairwiseAlignments-class), 83
- toString, XString-method (XString-class), 118
- toString, XStringSet-method (XStringSet-class), 123
- toString, XStringViews-method (XStringViews-class), 137
- toupper, 62
- transcribe (translate), 113
- translate, 17, 113
- translate, DNASTring-method (translate), 113
- translate, DNASTringSet-method (translate), 113
- translate, MaskedDNASTring-method (translate), 113
- translate, MaskedRNASTring-method (translate), 113
- translate, RNASTring-method (translate), 113
- translate, RNASTringSet-method (translate), 113
- trimLRPatterns, 33, 43, 115
- trimLRPatterns, character-method (trimLRPatterns), 115
- trimLRPatterns, XString-method (trimLRPatterns), 115
- trimLRPatterns, XStringSet-method (trimLRPatterns), 115
- trinucleotideFrequency, 17
- trinucleotideFrequency (nucleotideFrequency), 73
- Twobit (PDict-class), 89
- Twobit-class (PDict-class), 89
- type (PairwiseAlignments-class), 83
- type, PairwiseAlignments-method (PairwiseAlignments-class), 83
- type, PairwiseAlignmentsSingleSubjectSummary-method (PairwiseAlignments-class), 83
- unaligned (AlignedXStringSet-class), 6
- unaligned, AlignedXStringSet0-method (AlignedXStringSet-class), 6
- union, XStringSet, XStringSet-method (XStringSet-class), 123
- unique, 130
- uniqueLetters (letterFrequency), 24
- uniqueLetters, MaskedXString-method (letterFrequency), 24
- uniqueLetters, XString-method (letterFrequency), 24
- uniqueLetters, XStringSet-method (letterFrequency), 24
- uniqueLetters, XStringViews-method (letterFrequency), 24
- unitScale (matchPWM), 62
- unlist, MIndex-method (MIndex-class), 65
- unlist, XStringSet-method (XStringSet-class), 123
- unmasked, 26
- unmasked (MaskedXString-class), 35
- unmasked, MaskedXString-method (MaskedXString-class), 35
- unmasked, MultipleAlignment-method (MultipleAlignment-class), 67
- updateObject, XString-method (XString-class), 118
- updateObject, XStringSet-method (XStringSet-class), 123
- vcountPattern, 49
- vcountPattern (matchPattern), 43
- vcountPattern, character-method (matchPattern), 43
- vcountPattern, MaskedXString-method (matchPattern), 43

- vcountPattern, XString-method  
(matchPattern), 43
- vcountPattern, XStringSet-method  
(matchPattern), 43
- vcountPattern, XStringViews-method  
(matchPattern), 43
- vcountPDict (matchPDict), 48
- vcountPDict, MaskedXString-method  
(matchPDict), 48
- vcountPDict, XString-method  
(matchPDict), 48
- vcountPDict, XStringSet-method  
(matchPDict), 48
- vcountPDict, XStringViews-method  
(matchPDict), 48
- Views, 36, 63, 137
- Views, character-method  
(XStringViews-class), 137
- Views, MaskedXString-method  
(MaskedXString-class), 35
- Views, PairwiseAlignmentsSingleSubject-method  
(PairwiseAlignments-class), 83
- Views, XString-method  
(XStringViews-class), 137
- Views-class, 37, 138
- vmatchPattern, 49, 61, 62, 82
- vmatchPattern (matchPattern), 43
- vmatchPattern, character-method  
(matchPattern), 43
- vmatchPattern, MaskedXString-method  
(matchPattern), 43
- vmatchPattern, XString-method  
(matchPattern), 43
- vmatchPattern, XStringSet-method  
(matchPattern), 43
- vmatchPattern, XStringViews-method  
(matchPattern), 43
- vmatchPDict (matchPDict), 48
- vmatchPDict, ANY-method (matchPDict), 48
- vmatchPDict, MaskedXString-method  
(matchPDict), 48
- vmatchPDict, XString-method  
(matchPDict), 48
- vwhichPDict (matchPDict), 48
- vwhichPDict, MaskedXString-method  
(matchPDict), 48
- vwhichPDict, XString-method  
(matchPDict), 48
- vwhichPDict, XStringSet-method  
(matchPDict), 48
- vwhichPDict, XStringViews-method  
(matchPDict), 48
- vwhichPDict, XStringSet-method  
(matchPDict), 48
- vwhichPDict, XStringViews-method  
(matchPDict), 48
- width, AlignedXStringSet0-method  
(AlignedXStringSet-class), 6
- width, character-method  
(XStringSet-class), 123
- width, PDict-method (PDict-class), 89
- width, PDict3Parts-method (PDict-class),  
89
- width, PreprocessedTB-method  
(PDict-class), 89
- width0 (MIndex-class), 65
- width0, MIndex-method (MIndex-class), 65
- write.phylip (MultipleAlignment-class),  
67
- writePairwiseAlignments, 82, 87
- writePairwiseAlignments  
(PairwiseAlignments-io), 87

writeXStringSet (XStringSet-io), [132](#)  
wtPhiX174 (phiX174Phage), [93](#)

xscat, [117](#)

XString, [3](#), [9](#), [13–15](#), [18](#), [21](#), [23–27](#), [31–33](#),  
[35](#), [36](#), [42](#), [44](#), [49](#), [65](#), [66](#), [68](#), [72](#), [73](#),  
[75](#), [81](#), [84](#), [96–99](#), [103](#), [104](#), [106](#),  
[115–117](#), [124](#), [125](#), [137](#), [138](#)

XString (XString-class), [118](#)

XString-class, [4](#), [6](#), [10](#), [13](#), [18](#), [23](#), [27](#), [33](#),  
[37](#), [38](#), [41](#), [43](#), [75](#), [87](#), [96](#), [107](#), [116](#),  
[118](#), [118](#), [121](#), [126](#), [138](#)

XStringPartialMatches-class, [121](#)

XStringQuality, [81](#), [96](#), [97](#), [108](#)

XStringQuality (XStringQuality-class),  
[122](#)

XStringQuality-class, [82](#), [97](#), [122](#)

XStringSet, [9](#), [18](#), [24–27](#), [31–33](#), [44](#), [49](#), [68](#),  
[69](#), [73–75](#), [78](#), [79](#), [81](#), [84](#), [97–99](#),  
[104](#), [108](#), [115–117](#), [119](#), [129](#), [130](#),  
[132–135](#)

XStringSet (XStringSet-class), [123](#)

XStringSet-class, [6](#), [10](#), [12](#), [18](#), [27](#), [67](#), [70](#),  
[75](#), [114](#), [116](#), [118](#), [120](#), [123](#), [130](#),  
[134](#), [136](#), [138](#)

XStringSet-comparison, [126](#), [129](#)

XStringSet-io, [132](#)

XStringSetList, [98](#), [99](#), [135](#)

XStringSetList (XStringSetList-class),  
[135](#)

XStringSetList-class, [126](#), [135](#)

XStringViews, [5](#), [9](#), [14](#), [15](#), [20](#), [21](#), [23–27](#), [38](#),  
[41–45](#), [60](#), [64](#), [66](#), [68](#), [70](#), [73–75](#), [79](#),  
[90](#), [97](#), [104](#), [114](#), [117](#), [124](#), [125](#), [135](#)

XStringViews (XStringViews-class), [137](#)

XStringViews-class, [6](#), [10](#), [15](#), [21](#), [23](#), [27](#),  
[38](#), [41](#), [43](#), [45](#), [50](#), [60](#), [64](#), [66](#), [75](#), [87](#),  
[92](#), [96](#), [104](#), [114](#), [118](#), [120](#), [121](#), [126](#),  
[137](#)

XVector, [125](#)

XVector-class, [120](#)

XVectorList-class, [126](#)

yeastSEQCHR1, [139](#)