

Package ‘antiProfiles’

October 7, 2014

Maintainer Hector Corrada Bravo <hcorrada@gmail.com>

Author Hector Corrada Bravo, Rafael A. Irizarry and Jeffrey T. Leek

Version 1.4.0

License Artistic-2.0

Title Implementation of gene expression anti-profiles

Description Implements gene expression anti-profiles as described in Corrada Bravo et al., BMC Bioinformatics 2012, 13:272 doi:10.1186/1471-2105-13-272.

Depends R (>= 3.0), matrixStats (>= 0.5), methods (>= 2.14),

biocViews GeneExpression,Classification

Suggests antiProfilesData, RColorBrewer

Collate 'AllClasses.r' 'AllGenerics.r' 'show-methods.r'
'antiProfiles-package.r' 'ap-methods.r' 'apCounts-methods.r'
'apReorder-methods.r' 'apStats.r' 'accessors.r'

R topics documented:

antiProfiles-package	2
AntiProfile-class	2
AntiProfileStats-class	3
apCount	4
apReorder	5
apStats	5
buildAntiProfile	6
TissueSpecAntiProfile-class	7
Index	9

antiProfiles-package *Gene Expression Anti-profiles*

Description

This package implements the anti-profile method of Corrada Bravo et al., BMC Bioinformatics 2012, 13:272 doi:10.1186/1471-2105-13-272.

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

AntiProfile-class *A gene expression anti-profile*

Description

This class encapsulates anti-profiles. Objects of this class should be built from [AntiProfileStats](#) objects using the [buildAntiProfile](#) method. Anti-profile scores can be computed for new samples using the [apCount](#) method.

Usage

```
## Accessors  
  
getProbesetIds(object)  
getNormalRegions(object)
```

Arguments

object Object of class (or inheriting from) [AntiProfile](#)

Accessors

In the following code object is a [AntiProfile](#) object.

getProbesetIds: vector of Affymetrix ids for probesets included in the anti-profile (character)
getNormalRegions: median and upper boundary of normal expression regions (numeric matrix of dimension s-by-2, where s is the size of the anti-profile)

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

See Also

[AntiProfileStats](#) for the class of objects from which anti-profiles are built. [buildAntiProfile](#) for the method used to construct objects of this class. [apCount](#) for the function used to calculate anti-profile scores from objects of this class.

Examples

```
if (require(antiProfilesData)) {
  data(apColonData)
  colonStats=apStats(exprs(apColonData), pData(apColonData)$Status)
  colonAP = buildAntiProfile(colonStats, tissueSpec=FALSE, sigsize=10)
  show(colonAP)

  head(getProbesetIds(colonAP))
  head(getNormalRegions(colonAP))
}
```

AntiProfileStats-class

Statistics used to build anti-profiles

Description

This class stores statistics required to build anti-profiles. Objects of this class should be built using the [apStats](#) function. To build anti-profiles from objects of this class, use the [buildAntiProfile](#) function.

Usage

```
## Accessors
getProbeStats(object)
```

Arguments

object Object of class [AntiProfileStats](#)

Accessors

In the following code object is a [AntiProfileStats](#) object.

getProbeStats: Gets probeset statistics. A data.frame with columns

affyid: Affymetrix probeset id (character)

SD0: Normal expression standard deviation aggregated over tissue types (numeric)

SD1: Cancer expression standard deviation aggregated over tumor types (numeric)

stat: The log₂-variance ratio statistic (numeric)

meds0: Median normal expression aggregated over tissue types (numeric)

mads0: Median absolute deviation of normal expression aggregate over tissue types (numeric)

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

See Also

[apStats](#) to construct objects of this class, [buildAntiProfile](#) to build anti-profiles from objects of this class.

Examples

```
if (require(antiProfilesData)) {
  data(apColonData)
  colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)
  show(getProbeStats(colonStats))
}
```

apCount

Obtain the anti-profile score for a set of samples

Description

This function applies the given anti-profile to a new set of samples. Rownames in the expression matrix are used to match probenames in the AntiProfile object.

Arguments

`fit` an object of class AntiProfile as produced by the buildAntiProfile method
`expr` a matrix of gene expression, rownames are used as identifiers

Value

a numeric vector of anti-profile scores

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

Examples

```
if (require(antiProfilesData)) {
  data(apColonData)

  # compute statistics
  colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)

  # create an anti-profile, ignoring tissue-specificity of probesets, with 10 probesets
  ap = buildAntiProfile(colonStats, tissueSpec=FALSE, sigsize=10)
```

```
# get counts for the original dataset
counts =apCount(ap, exprs(apColonData))
}
```

apReorder

Reorder an AntiProfileStats object

Description

Reorders given AntiProfileStats object using provided ordering o

Arguments

stats An object of class AntiProfileStats
o A numeric vector giving new probe ordering

Value

A reordered AntiProfileStats object

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

Examples

```
if (require(antiProfilesData)) {
  data(apColonData)
  colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)
  o = sample(seq(len=nrow(slot(colonStats,"probes"))))
  newStats = apReorder(colonStats, o)
}
```

apStats

Compute statistics used to construct antiProfile

Description

This function calculates normal ranges of expressions and variance ratios for all probesets. To create an anti-profile, call buildAntiProfile on the output of this function

Usage

```
apStats(e, cl, tiss = NULL, minL = 10, cutoff = 5,
  OnCutoff = 2.54)
```

Arguments

e	matrix of gene expression, with one column per sample
cl	vector of normal/cancer indicators as 0/1
tiss	vector of tissue types for each sample
minL	minimum number of samples of a given tissue/class to compute stats
cutoff	median absolute deviation multiplier used to determine proportion of samples within normal range of expression
OnCutoff	gene expression barcode z-score to determine if a gene is expressed

Value

An object of class SuccsStats

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

See Also

[AntiProfileStats](#) for the type of object returned. [buildAntiProfile](#) to construct anti-profiles with objects returned by this function.

Examples

```
if (require(antiProfilesData)) {
  data(apColonData)
  colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)
}
```

buildAntiProfile *Create an anti-profile from a AntiProfileStats object*

Description

This function creates anti-profile using statistics stored in a AntiProfileStats object

Arguments

stats	an object of class AntiProfileStats as produced by the apStats function
tissueSpec	use tissue-specific regions of normal expression
tissueFilter	use only tissue-specific genes in the anti-profile
sigsize	desired size of signature, if NULL, computed from statCutoff
cutoff	median absolute deviation multiplier used to define normal regions of expression
statCutoff	cutoff used to include probesets in anti-profile

Value

an object of class `AntiProfilesSig` or `AntiProfilesTissueSig` depending on the `tissueSpec` argument

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

Examples

```
if (require(antiProfilesData)) {
  # create an anti-profile, ignoring tissue-specificity of probesets, with 10 probesets
  data(apColonData)
  colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)
  ap = buildAntiProfile(colonStats, tissueSpec=FALSE, sigsize=10)
}
```

TissueSpecAntiProfile-class

A gene expression anti-profile using tissue-specific regions

Description

This class encapsulates anti-profiles with tissue-specific normal expression regions. Objects of this class should be built from `AntiProfileStats` objects using the `buildAntiProfile` method. Anti-profile scores can be computed for new samples using the `apCount` method.

Usage

```
## Accessors

## S4 method for signature TissueSpecAntiProfile
getProbesetIds(object)
## S4 method for signature TissueSpecAntiProfile
getNormalRegions(object)
getNormalTissueRegions(object)
```

Arguments

object Object of class `TissueSpecAntiProfile`

Accessors

In the following code `object` is a `TissueSpecAntiProfile` object.

`getProbesetIds`: vector of Affymetrix ids for probesets included in the anti-profile (character)

`getNormalRegions`: median and upper boundary of normal expression regions (numeric matrix of dimension `s`-by-2, where `s` is the size of the anti-profile)

getNormalTissueRegions: median and upper boundary of normal expression regions (numeric array of dimension s -by-2-by- t , where s is the size of the anti-profile, and t the number of normal tissues used in the anti-profile)

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

See Also

[AntiProfileStats](#) for the class of objects from which anti-profiles are built. [buildAntiProfile](#) for the method used to construct objects of this class. [apCount](#) for the function used to calculate anti-profile scores from objects of this class. #'

Examples

```
if (require(antiProfilesData)) {
  data(apColonData)
  # fake tissues
  tissue=rep(c("colon", "lung"), len=length(sampleNames(apColonData)))
  tissStats=apStats(exprs(apColonData), pData(apColonData)$Status, tiss=tissue, minL=3)
  tissAP=buildAntiProfile(tissStats, sigsize=10)
  show(tissAP)

  head(getProbesetIds(tissAP))
  head(getNormalRegions(tissAP))
  head(getNormalTissueRegions(tissAP))
}
```


Index

AntiProfile, 2
AntiProfile-class, 2
antiProfiles-package, 2
AntiProfileStats, 2, 3, 6–8
AntiProfileStats-class, 3
apCount, 2, 3, 4, 7, 8
apCount, AntiProfile, matrix-method
 (apCount), 4
apCount, TissueSpecAntiProfile, matrix-method
 (apCount), 4
apReorder, 5
apReorder, AntiProfileStats, numeric-method
 (apReorder), 5
apStats, 3, 4, 5

buildAntiProfile, 2–4, 6, 6–8
buildAntiProfile, AntiProfileStats-method
 (buildAntiProfile), 6

getNormalRegions (AntiProfile-class), 2
getNormalRegions, AntiProfile-method
 (AntiProfile-class), 2
getNormalRegions, TissueSpecAntiProfile-method
 (TissueSpecAntiProfile-class),
 7
getNormalTissueRegions
 (TissueSpecAntiProfile-class),
 7
getNormalTissueRegions, TissueSpecAntiProfile-method
 (TissueSpecAntiProfile-class),
 7
getProbesetIds (AntiProfile-class), 2
getProbesetIds, AntiProfile-method
 (AntiProfile-class), 2
getProbesetIds, TissueSpecAntiProfile-method
 (TissueSpecAntiProfile-class),
 7
getProbeStats (AntiProfileStats-class),
 3
getProbeStats, AntiProfileStats-method
 (AntiProfileStats-class), 3
TissueSpecAntiProfile, 7
TissueSpecAntiProfile-class, 7