

RpsiXML

April 19, 2009

BIOGRID.PSIMI25

Supported PSI-MI 2.5 XML data sources

Description

Objects representing supported PSI-MI 2.5 XML data sources. They are implicitly used in interaction and/or complex parsers. The supporting list will grow as soon as there are new PSI-MI 2.5 compatible data sources available.

For usage see examples of `parsePsimi25Interaction`, `parsePsimi25Complex` and `psimi25XML2Graph`.

Details

If a new repository is added manually by the user, please read the notes in `psimi25Source-class` before coding

References

PSI-MI XML v2.5 data exchange format <http://www.psidesv.info/index.php?q=node/60>

BioGRID <http://www.thebiogrid.com>

DIP <http://dip.doe-mbi.ucla.edu/>

HPRD <http://www.hprd.org/>

IntAct <http://www.ebi.ac.uk/intact>

MINT <http://mint.bio.uniroma2.it/mint>

MIPS/CORUM <http://mips.gsf.de/>

MPact <http://mips.gsf.de/genre/proj/mpact>

availableXrefs-methods

Methods for function availableXrefs

Description

Methods for function availableXrefs. See [availableXrefs](#) for more details

Methods

- x = "list"** A list of [psimi25Interactor-class](#) objects, an logical option "intersect" can be set to tell the function whether to return the intersected or the unioned cross ref databases.
 - x = "psimi25InteractionEntry"** Similar to that of "list", "intersect" option is also provided
 - x = "psimi25Interactor"** returns the avaialble cross refences of the given interactor, "intersect" option not available
-

availableXrefs

Get cross reference(s) of interactors from PSI-MI 2.5 files

Description

PSI-MI 2.5 data exchange format encourages data providers to encode cross referenes of the interactors into the file, which prove valuable for annotating the data. These functions help finding out the available cross references of interactors.

Usage

```
availableXrefs(x, ...)
xref(x)
```

Arguments

- x** for availableXrefs, 'x' can either be an object of [psimi25Interactor-class](#), [link{psimi25InteractionEntry}](#) or a list of [psimi25Interactor-class](#) objects.
for xref, 'x' should be an object of [psimi25Interactor-class](#)
- ...** intersect, logical option. If set to TRUE then only the cross references available for every interactor are returned (intersected), otherwise all the cross references are unioned and returned. See the examples

Details

If [psimi25InteractionEntry](#) is provided as the parameter of availableXrefs, an option named "intersect" can be set to extract only those cross references intersected among all the interactors, namely the ones assigned in every interactor. Please see the examples.

Value

| | |
|----------------|---|
| xref | Returns a matrix with two columns: <code>db</code> (external database name) and <code>id</code> (external database index) |
| availableXrefs | A vector of characters, the names of external databases referenced in the file |

Author(s)

Jitao David Zhang

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)
hprdInteractors <- interactors(hprdSet)

availableXrefs(hprdSet)
xref(hprdInteractors[[1]])
availableXrefs(hprdInteractors[[1]])
```

bait

Extract bait, prey, participant, inhibitor, pubmed, confidence value, interaction type, or neutral component information from an object of psimi25Interaction-class

Description

The functions return bait/prey UniProt identifier of the given `psimi25Interaction` object.

Usage

```
bait(x)
prey(x)
participant(x)
inhibitor(x)
pubmedID(x)
confidenceValue(x)
neutralComponent(x)
```

Arguments

`x` An object of `psimi25Interaction-class`, see example

Value

The source database identifier is returned.

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

References

The UniProt database <http://www.expasy.uniprot.org/>

See Also

[psimi25Interaction-class](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

gridxml <- file.path(xmlDir, "biogrid_200804_test.xml")
gridSet <- parsePsimi25Interaction(gridxml, BIOGRID.PSIMI25)

interExp <- interactions(gridSet) [[1]]
bait(interExp)
prey(interExp)
```

complexName

Accessor functions for complex

Description

These functions are used to extract useful information of complex in the form of [psimi25Complex-class](#) object.

Usage

```
complexName (x)
complexMembers (x)
complexAttributes (x)
```

Arguments

x An object of [psimi25Complex-class](#)

Details

See examples

Value

complexName Returns the name of the complex in characters

complexMembers

A data frame of protein members building the complex and their information

complexAttributes

A named vector of character strings, the names are the attribute names while the values are attributes documented in the PSI-MI 2.5 file

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

[psimi25Complex-class](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")  
  
intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")  
intactComplexSet <- parsePsimi25Complex(intactComplexxml, INTACT.PSIMI25)  
complexSample <- complexes(intactComplexSet)[[2]]  
  
complexName(complexSample)  
complexAttributes(complexSample)  
complexMembers(complexSample)
```

complexes

Extract complexes from psimi25ComplexEntry

Description

Extract complexes from an object of [psimi25ComplexEntry-class](#)

Usage

complexes(x)

Arguments

x An object of [psimi25ComplexEntry-class](#)

Value

A list of [psimi25Complex](#)

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

References

PSI-MI 2.5 XML data exchange format <http://www.psidev.info/index.php?q=node/60>

See Also

[psimi25Complex-class](#)

Examples

```
## Not run:
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")
intactComplexSet <- parsePsimi25Complex(intactComplexxml,
INTACT.PSIMI25)

complexes(intactComplexSet)
## End(Not run)
```

eListHandler

xmlEventParse handlers for PSI-MI XML documents

Description

xmlEventParse handlers for PSI-MI XML documents

Usage

```
eListHandler()
iListHandler()
```

Details

A dump() method is supplied to deliver the list.

Value

list; see examples for structure

Author(s)

Vince Carey <stvjc@channing.harvard.edu>

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")
fn <- file.path(xmlDir, "hprd_200709_test.xml")
xmlEventParse(fn, eListHandler())$dump()
```

getAbstractByPMID *A function to obtain the abstract information via a Pubmed ID*

Description

This function takes a character vector of pubmed IDs and returns a list of pubMedAbst objects indexed by each ID.

Usage

```
getAbstractByPMID (pmID)
```

Arguments

| | |
|------|----------------------------------|
| pmID | A character vector of pubmed IDs |
|------|----------------------------------|

Value

A list of pubMedAbst objects.

Author(s)

Tony Chiang

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")
intactxml <- file.path(xmlDir, "intact_2008_test.xml")
x <- parsePsimi25Interaction(intactxml, INTACT.PSIMI25)
y <- interactions(x) [[1]]
getAbstractByPMID (pubmedID (y))
```

interactionType *Type of the interaction*

Description

Return the interaction type of the psimi25Interaction

Usage

```
interactionType (x)
```

Arguments

| | |
|---|---|
| x | An object of psimi25Interaction-class |
|---|---|

Value

A character string representing the interaction type

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

[psimi25Interaction-class](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

interExp <- interactions(hprdSet) [[1]]
interExpTyp <- interactionType(interExp)
```

interactions

List interactions in the given psimi25InteractionEntry object

Description

List interactions from an object of the [psimi25InteractionEntry-class](#) object

Usage

```
interactions(x)
```

Arguments

x An object of [psimi25InteractionEntry-class](#), see example

Value

A list of interactions

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

[psimi25InteractionEntry-class](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

interactions(hprdSet)
```

interactorInfo-methods

Methods for Function interactorInfo in Package ‘RpsiXML’

Description

See interactorInfo

Methods

```

x = "list" A list of psimi25Interactor-class objects
x = "psimi25ComplexEntry" Object of psimi25ComplexEntry-class, parsed from PSI-
MI 2.5 complex files
x = "psimi25Graph" Object of psimi25Graph-class, parsed by psimi25XML2Graph
x = "psimi25Hypergraph" Object of psimi25Hypergraph-class, parsed by psimi25XML2Graph
x = "psimi25InteractionEntry" Object of psimi25InteractionEntry-class, parsed from
PSI-MI 2.5 interaction files

```

interactorInfo *Interactor info in a matrix***Description**

The function returns the essential information of interactors in a matrix. Xrefs are left out since they have arbitrary numbers of annotation and cannot be summarized into a matrix.

Usage

```
interactorInfo(x)
```

Arguments

x An object which contains psimi25Interactor information, for example objects of psimi25InteractionEntry-class, psimi25Graph-class, psimi25Hypergraph-class or psimi25ComplexEntry-class

.

Value

A matrix of interactor information, each row represents an interactor. The columns are

| | |
|--------------|---|
| sourceDb | source database |
| sourceId | source database index |
| shortLabel | short label assigned by the source database |
| uniprotId | UniProt ID, NA if not available |
| organismName | the organism of the interactor protein |

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>

See Also

[xref](#), [availableXrefs](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

hprdInteractorInfo <- interactorInfo(hprdSet)
```

interactors-methods

Methods for Function interactors

Description

Methods to extract interactors from various data structures

Methods

```
x = "psimi25ComplexEntry" Object of psimi25ComplexEntry-class, parsed from PSI-MI 2.5 complex files
x = "psimi25Graph" Object of psimi25Graph-class, parsed by psimi25XML2Graph
x = "psimi25Hypergraph" Object of psimi25Hypergraph-class, parsed by psimi25XML2Graph
x = "psimi25InteractionEntry" Object of psimi25InteractionEntry-class, parsed from PSI-MI 2.5 interaction files
```

interactors

Interactors of the given object

Description

Return the interactors of the given object

Usage

```
interactors(x)
```

Arguments

| | |
|----------------|--|
| <code>x</code> | either an object of psimi25InteractionEntry-class or psimi25ComplexEntry-class |
|----------------|--|

Value

A matrix of interactor information

Author(s)

Tony Chiang <tchiang@ebi.ac.uk>, Jitao David Zhang <j.zhang@dkfz.de>

See Also

[psimi25InteractionEntry-class](#), [psimi25ComplexEntry-class](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")  
  
hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")  
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)  
  
interactors(hprdSet)  
  
## Not run:  
intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")  
intactComplexSet <- parsePsimi25Complex(intactComplexxml,  
INTACT.PSIMI25)  
  
interactors(intactComplexSet)  
## End(Not run)
```

list2Matrix *Converts list into matrix*

Description

Converts a named list representation of a graph into matrix

Usage

```
list2Matrix(namedList, type="interaction")
```

Arguments

| | |
|-----------|--|
| namedList | Named list. |
| type | Character: either interaction or complex |

Value

A matrix. A bait-prey matrix if type is "interaction" with baits indexing the columns and prey the rows or a protein complex incidence graph with complexes indexing the columns and proteins, the rows.

If type is interaction, the names of the list are the baits and the entries of the list correspond the prey found by each bait.

If type is complex, the names of the list are the names of the protein complex and the entries are the members of each corresponding complex.

Author(s)

Tony Chiang <tchiang@ebi.ac.uk>

null2na

Turns null or NA into character "NA"

Description

The functions turns NULL or NA into character "NA"

Usage

null2na (x)

Arguments

x A vector

Value

Either the original vector (if not NULL or logical NA) or character NA

Author(s)

Tony Chiang <tchiang@ebi.ac.uk>

Examples

```
null2na(NA)
null2na(NULL)
```

organismName

Organism name of the psimi25InteractionEntry

Description

Returns the organism name(s) of the `psimi25InteractionEntry`

Usage

organismName (x)

Arguments

x An object of `psimi25InteractionEntry-class`

Value

A vector of character strings representing the organism names of the proteins

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

[psimi25InteractionEntry-class](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")
hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)
organismName(hprdSet)
```

parseComplex

Parse complex, interactor and experiment from PSI-MI 2.5 XML node

Description

Wrappers of internal functions ("parsePsimi25Complex", "parsePsimi25Interactor", "parsePsimi25Experiment") to parse nodes from PSI-MI 2.5 XML node. By default these parsers is used in objects of [psimi25Source-class](#) without any modification. Though they can be overwritten in these objects in special cases, it is not advisory to do so due to the compatibility.

Usage

```
parseComplex(x, ...)
parseInteractor(x, ...)
parseExperiment(x, ...)
```

Arguments

| | |
|-----|--|
| x | An object of the psimi25Source-class |
| ... | Parameters passed to internal functions |

Value

Object of [psimi25Complex-class](#), \code{psimi25Complex-class} or \code{psimi25Complex-class}

Note

An newly initialized instance of [psimi25Source-class](#) contains the default form of these functions. Though they are allowd to be overwritten, it is not advisory to do so since this means the file to parse is not fully compatible with PSI-MI 2.5 standard. It is more sensible to contact the data provider before modifying or overwritting these functions.

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

parsePsimi25Interaction
Parsing PSI-MI 2.5 XML documents into interactions

Description

The PSI-MI 2.5 XML format is used widely by many repositories to record protein-protein interaction data as well as protein complex data. This functions parse such files into interactions or complexes.

`parsePsimi25Interaction` is the parser for interaction data and `parsePsimi25Complex` is the parser for complex data.

Usage

```
parsePsimi25Interaction(psimi25file, psimi25source, verbose=TRUE)
parsePsimi25Complex(psimi25file, psimi25source, verbose=FALSE)
```

Arguments

| | |
|----------------------------|--|
| <code>psimi25file</code> | character, file name or URL of the XML document |
| <code>psimi25source</code> | A supported data repository source, see also psimi25Source-class |
| <code>verbose</code> | logical, whether the parsing state should be displayed verbosely. |

Value

`psimi25Interaction` returns a list of `psimi25InteractionEntry` objects, each represents one entry in the XML document `psimi25Complex` returns a `psimi25ComplexEntry` objects, representing the complex data from one XML document.

Author(s)

Jitao David Zhang <j.zhang@dkfz-heidelberg.de>, Tony Chiang <tchiang@ebi.ac.uk>

References

PSI-MI XML v2.5 data exchange format <http://www.psidev.info/index.php?q=node/60>
BioGRID <http://www.thebiogrid.com>
DIP <http://dip.doe-mbi.ucla.edu/>
HPRD <http://www.hprd.org/>
IntAct <http://www.ebi.ac.uk/intact>
MINT <http://mint.bio.uniroma2.it/mint>
MIPS/CORUM <http://mips.gsf.de/>

See Also

[psimi25Interaction-class](#), [psimi25InteractionEntry-class](#), [psimi25Complex-class](#) [psimi25ComplexEntry-class](#),

Examples

```
# parse interaction data
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

gridxml <- file.path(xmlDir, "biogrid_200804_test.xml")
gridSet <- parsePsimi25Interaction(gridxml, BIOGRID.PSIMI25)

intactxml <- file.path(xmlDir, "intact_2008_test.xml")
intactSet <- parsePsimi25Interaction(intactxml, INTACT.PSIMI25, verbose=TRUE)

# parse complex data
intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")
intactComplexSet <- parsePsimi25Complex(intactComplexxml, INTACT.PSIMI25)
```

psimi25Complex-class
Class "psimi25Complex"

Description

A class representing complex data

Objects from the Class

Objects can be created by calls of `parsePsimi25Complex`

Slots

sourceDb: Object of class "character", short label of the source database
sourceId: Object of class "character", complex ID of the source database
shortLabel: Object of class "character", short label of the complex
fullName: Object of class "character", full name of the complex
organismName: Object of class "character", orgnism name
taxId: Object of class "character", taxonomy ID
members: Object of class "data.frame", members (UniProt ID if available)
attributes: Object of class "character", attributes of the complex

Methods

show signature(object = "psimi25Complex") : shows information of the complex
sourceDb signature(x = "psimi25Complex") : returns source database
sourceId signature(x = "psimi25Complex") : returns source ID

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

[parsePsimi25Complex](#)

Examples

```
showClass("psimi25Complex")
```

psimi25ComplexEntry-class
Class "psimi25ComplexEntry"

Description

A class representing the complex data extracted from file in PSI-MI 2.5 format.

Objects from the Class

Objects can be created by calls of the form `parsePsimi25Complex`

Slots

releaseDate: Object of class "character", release date
interactors: Object of class "matrix", interactors involved
complexes: Object of class "list", complexes

Methods

complexes signature(x = "psimi25ComplexEntry") : returns all complexes
interactors signature(x = "psimi25ComplexEntry") : returns information of interactors
show signature(object = "psimi25ComplexEntry") : shows information of all the complexes

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

[parsePsimi25Complex](#) `psimi25ComplexEntry`

Examples

```
showClass("psimi25ComplexEntry")
```

psimi25Experiment-class
Class "psimi25Experiment"

Description

Representing an experiment recorded in PSI-MI 2.5 XML files

Objects from the Class

Objects can be created by calls of the form [parseExperiment](#)

Slots

sourceDb: Object of class "character", source database short label
expSourceId: Object of class "character", experiment ID of the source database
interactionType: Object of class "character", interaction type, "Y2H", "vv", etc
expPubMed: Object of class "character", PubMed ID of the experiment

Methods

No methods defined with class "psimi25Experiment" in the signature.

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

[parseExperiment](#)

Examples

```
showClass("psimi25Experiment")
```

psimi25Graph-class Class "psimi25Graph" ~~~

Description

A graph object representing data extracted from PSI-MI 2.5 files

Objects from the Class

Objects can be created by calls of the form [psimi25XML2Graph](#)

Slots

interactors: Object of class "matrix", interactor information in a matrix, Each row represents one interactor. Source IDs are used as row names. Each column represents one annotation. Annotations include: UniProt ID, short label, organism name, and NCBI taxonomy ID. Only those interactors which are the nodes of the psimi25Graph is given.

Extends

Class [graphNEL](#), directly. Class [graphNEL](#), by class "graphNEL", distance 2.

Methods

```
show signature(object = "psimi25Graph") : show method
translateSourceID signature(r = "psimi25Graph") : translate the source ID into other
IDs
abstract signature(object="psimi25Graph") : get the abstract information for the dataset
from NCBI
```

Author(s)

Tony Chiang <tchiang@ebi.ac.uk>, Jitao David Zhang <j.zhang@dkfz.de>

See Also

[psimi25XML2Graph](#), [S4classpsimi25Hypergraph-class](#)

Examples

```
showClass("psimi25Graph")
```

psimi25Hypergraph-class
Class "psimi25Hypergraph"

Description

Class to present PSI-MI 2.5 XML data as hypergraph.

Objects from the Class

Objects can be created by calls of the form [psimi25XML2Graph](#)

Slots

interactors: Object of class "matrix", Object of class "matrix", interactor information in a matrix, Each row represents one interactor. Source IDs are used as row names. Each column represents one annotation. Annotations include: UniProt ID, short label, organism name, and NCBI taxonomy ID. Only those interactors which are the nodes of the psimi25Graph is given.

Extends

Class Hypergraph, directly.

Methods

```
initialize signature(.Object = "psimi25Hypergraph")
show signature(object = "psimi25Hypergraph"): show method
translateSourceID signature(r = "psimi25Hypergraph"): translate source ID into
other IDs
```

Author(s)

Tony Chiang <tchiang@ebi.ac.uk>, Jitao David Zhang <j.zhang@dkfz.de>

See Also

[psimi25XML2Graph](#), [S4classpsimi25Graph-class](#)

Examples

```
showClass("psimi25Hypergraph")
```

psimi25Interaction-class
Class "psimi25Interaction"

Description

A class representing interaction data

Objects from the Class

Objects can be created by calls of the form `parsePsimi25Interaction`

Slots

sourceDb: Object of class "character", source database
sourceId: Object of class "character", source database ID
interactionType: Object of class "character", character, the method used for detecting
the interaction ,such as "pull down"
expPubMed: Object of class "character", PubMed ID of the publication that describes the
experiment
expSourceId: Object of class "character", source database ID of the experiment
confidenceValue: Object of class "character", confidence value of the experimental in-
teraction
participant: Object of class "character", UniProt IDs of the participants. Important when
no bait/prey information is available
bait: Object of class "character", UniProt ID of the bait

prey: Object of class "character", UniProt ID(s) of the prey(s)
inhibitor: Object of class "character", UniProt ID of the inhibitor, NA when missing
neutralComponent: Object of class "character", UniProt ID of the neutral components,
NA when missing

Methods

interactionType signature(x = "psimi25Interaction") : finds out interaction type
show signature(object = "psimi25Interaction") : a print method
sourceDb signature(x = "psimi25Interaction") : finds out source database
sourceId signature(x = "psimi25Interaction") : returns ID of the source database
bait signature(x = "psimi25Interaction") : returns the UniProt ID of the bait
prey signature(x = "psimi25Interaction") : returns the UniProt ID(s) of the prey(s)

Author(s)

Tony Chiang <tchiang@ebi.ac.uk> , Jitao David Zhang <j.zhang@dkfz.de>

See Also

[parsePsimi25Interaction](#), [S4CLASSpsimi25Interactor-class](#), [S4CLASSpsimi25Experiment-class](#), [S4classpsimi25InteractionEntry-class](#)

Examples

```
showClass("psimi25Interaction")
```

psimi25InteractionEntry-class
Class "psimi25InteractionEntry"

Description

A class representing interaction data parsed from PSI-MI 2.5 XML files

Objects from the Class

Objects can be created by calls of the form `parsePsimi25Interaction`

Slots

organismName: Object of class "character", the unique organism name(s) of the interactors
taxId: Object of class "character", the unique NCBI taxonomy ID(s) of the interactors
releaseDate: Object of class "character", character, release date of the data entry, recorded
in the entry element of the XML file
interactors: Object of class "matrix", interactor information in a matrix, Each row repre-
sents one interactor. Source IDs are used as row names. Each column represents one anno-
tation. Annotations include: UniProt ID, short label, organism name, and NCBI taxonomy
ID
interactions: Object of class "list", list, a list of `psimi25Interaction-class` ob-
jects, each represents one interaction.

Methods

interactions signature(x = "psimi25InteractionEntry") : return a list of psimi25Interaction objects, each representing one interaction

interactors signature(x = "psimi25InteractionEntry") : a method to find all the interactors within the psimi25InteractionEntry and print them

organismName signature(x = "psimi25InteractionEntry") : returns organism names of the interactors

releaseDate signature(x = "psimi25InteractionEntry") : returns the release date, serving as a proxy for versioning

show signature(object = "psimi25InteractionEntry") : a print method

taxId signature(x = "psimi25InteractionEntry") : returns NCBI taxonomy ID

Author(s)

Tony Chiang <tchiang@ebi.ac.uk>, Jitao David Zhang <j.zhang@dkfz.de>

See Also

[parsePsimi25Interaction](#), S4 class [psimi25Interaction-class](#)

Examples

```
showClass("psimi25InteractionEntry")
```

psimi25Interactor-class

A class representing interactor from PSI-MI 2.5 XML files

Description

A class representing interactor from PSI-MI 2.5 XML files

Slots

sourceDb: Object of class "character", source database

sourceId: Object of class "character", ID of the source database

shortLabel: Object of class "character", short label of the interactor, if not available the slot will be filled with "fullName" node of the file

uniprotId: Object of class "character", UniProt ID of the interactor

organismName: Object of class "character", the unique name of the organism name

taxId: Object of class "character", the NCBI taxonomy ID

Methods

```
show signature(x = "psimi25Interactor") : a print method
sourceDb signature(x = "psimi25Interactor") : finds out source database
sourceId signature(x = "psimi25Interactor") : returns ID of the source database
```

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>

See Also

[parseInteractor](#)

Examples

```
showClass("psimi25Interactor")
```

psimi25Source-class
Class "psimi25Source"

Description

A class representing data source compatible with PSI-MI 2.5 XML data exchange format

Objects from the Class

Objects can be created by calls of the form `new ("psimi25Source", ...)`

Slots

label: Object of class "character", a meaningful unique label of the database, does not necessarily have to be the identifier used in the PSI-MI files. The value is advised to be overwritten by the objects

sourceDb: Object of class "character", the character string used in the PSI-MI files to identify the source database. The value must be overwritten by the object, depending on the database identifier used in the PSI-MI file.

uniprotSymbol: Object of class "character", the identifier of UniProt reference in "primaryRef" or "secondaryRef" attributes of the interactors, telling the parser where to find UniProt symbol of the interactors. The value must be overwritten by the objects.

parseExperiment: Object of class "function", the function to parse experiment from the PSI-MI 2.5 file. Except for special need this function should not be overwritten by the objects, since it parses the experiment node strictly according the PSI-MI standard

parseInteractor: Object of class "function", the function to parse interactor from the PSI-MI 2.5 file. Except for special need this function should not be overwritten by the objects, since it parses the interactor node strictly according the PSI-MI standard

parseComplex: Object of class "function", the function to parse complex from the PSI-MI 2.5 file. Except for special need this function should not be overwritten by the objects, since it parses the complex node strictly according the PSI-MI standard

Methods

```
parseComplex signature(x = "psimi25Source"): parse complex node of PSI-MI 2.5 file

parseExperiment signature(x = "psimi25Source"): parse experiment node of PSI-MI 2.5 file

parseInteractor signature(x = "psimi25Source"): parse interactor node of PSI-MI 2.5 file

sourceDb signature(x = "psimi25Source"): returns the source database

uniprot signature(x = "psimi25Source"): returns the uniprot identifier of the PSI-MI 2.5 XML file
```

Note

In case of a new data repository, you can first try creating a new object of the class with `label`, `sourceDb` and `uniprotSymbol` adjusted as needed. Try parsing a function with this new `psimi25Source` object. In case of warnings or errors, it may mean that the file provided is not strictly compatible with PSI-MI 2.5 data exchange format standard, please then contact the data provider.

By 02.06.08, six sources have been registered in the release version of `RpsiXML`: BIOGRID.PSIMI25, DIP.PSIMI25, HPRD.PSIMI25, INTACT.PSIMI25,, MINT.PSIMI25,MIPS.PSIMI25. Along the development we will implement more data sources under PSI-MI 25 standard.

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>

See Also

[parsePsimi25Interaction](#), [parsePsimi25Complex](#), [psimi25XML2Graph](#)

Examples

```
showClass("psimi25Source")
```

`psimi25XML2Graph` *Convert a vector of PSI-MI 2.5 XML files into graph objects*

Description

The function `psimi25XML2Graph` take a vector of XML 2.5 files from te same data source and generates a graph object based on the type of the files.

Usage

```
psimi25XML2Graph(psimi25files, psimi25source, type = "interaction",
directed = TRUE, ...)
```

Arguments

| | |
|----------------------------|--|
| <code>psimi25files</code> | Single file name or a vector of PSI-MI 2.5 XML file names or URLs. In case of splitted data the latter form is preferred. Different datasets or datasets from different sources should not be put into the same vector. |
| <code>psimi25source</code> | Source of the PSI-MI 2.5 XML file, see psimi25Source-class |
| <code>type</code> | A character string which is either "interaction" or "complex". As the value suggests, use "interaction" if the XML file contains experimental physical data, and "complex" if the file contains curated protein complex membership data. |
| <code>directed</code> | Logical, whehter the returned graph object should be directed or undirected |
| <code>...</code> | Other parameters passed to parsePsimi25Interaction |

Value

If type is "interaction", then a resulting `psimi25Graph` object is generated on the aggregation of the XML files. Otherwise if type is "complex," a resulting `psimi25HyperGraph` object is generated on the aggregate of the XML files.

Author(s)

Jitao David Zhang, Tony Chiang

See Also

[psimi25Source-class](#), [psimi25Graph-class](#), [psimi25Hypergraph-class](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

intactxml <- file.path(xmlDir, "intact_2008_test.xml")
intactGraph <- psimi25XML2Graph(intactxml, INTACT.PSIMI25, type="interaction")

intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")
intactComplexGraph <- psimi25XML2Graph(intactComplexxml, INTACT.PSIMI25, type="complex")
```

`releaseDate` *Release date of the `psimi25InteractionEntry` object*

Description

The function returns the release date of the [psimi25InteractionEntry-class](#) object, which can serve as a proxy for versioning

Usage

```
releaseDate(x)
```

Arguments

`x` An object of [psimi25InteractionEntry-class](#)

Value

A character string indicating the release date

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

[psimi25InteractionEntry-class](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

gridxml <- file.path(xmlDir, "biogrid_200804_test.xml")
gridSet <- parsePsimi25Interaction(gridxml, BIOGRID.PSIMI25)

gridRD <- releaseDate(gridSet)
```

separateXMLDataByExpt

Convert a vector of PSI-MI 2.5 XML files into graph objects based on pubmedID

Description

The function `psimi25XML2Graph` take a vector of XML 2.5 files from te same data source and generates a graph object based on the type of the files.

Usage

```
separateXMLDataByExpt (xmlFiles, psimi25source, type = "direct", directed = TRUE,
```

Arguments

| | |
|----------------------------|--|
| <code>xmlFiles</code> | Single file name or a vector of PSI-MI 2.5 XML file names or URLs. |
| <code>type</code> | A character. Currently the user can specify to cull either "direct" interactions or "indirect" interactions. |
| <code>psimi25source</code> | Source of the PSI-MI 2.5 XML file, see psimi25Source-class |
| <code>directed</code> | Logical, whehter the returned graph object should be directed or undirected. |
| <code>abstract</code> | Logical; if TRUE, the abstract information will be appended to the graph object. |
| <code>...</code> | Other parameters passed to parsePsimi25Interaction , for example <code>verbose=TRUE</code> |

Value

A list of [psimi25Graph-class](#) are generated indexed by the pubmedID of each bait-prey interaction. WARNING - the abstract information is obtained using the pubmed and buildPubMedAbst functions from the annotate package which warns the user that NCBI may block access to their site. The default is to not obtain the abstract for this reason.

Author(s)

Jitao David Zhang, Tony Chiang

See Also

[psimi25Source-class](#), [psimi25Graph-class](#), [psimi25Hypergraph-class](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

intactxml <- file.path(xmlDir, "intact_2008_test.xml")
intactGraph <- separateXMLDataByExpt(intactxml, INTACT.PSIMI25)
```

sourceDb-methods *Get source database name*

Description

The method returns source database name of the given parameter

Methods

- x = "psimi25Complex"** An object of [psimi25Complex-class](#)
- x = "psimi25Interaction"** An object of [psimi25Interaction-class](#)
- x = "psimi25Interactor"** An object of [psimi25Interactor-class](#)
- x = "psimi25Source"** An object of [psimi25Source-class](#)

sourceDb *Extracts the source database of the given parameter*

Description

Returns the name of the source database of the given object

Usage

```
sourceDb(x)
```

Arguments

x see [sourceDb-methods](#)

Value

A character string presenting the source database

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

see [sourceDb-methods](#)

sourceId-methods *Extracting ID in the source database*

Description

The method extracts source database IDs of the given parameter

Methods

x = "psimi25Complex" An object of [psimi25Complex-class](#)
x = "psimi25Interaction" An object of [psimi25Interaction-class](#)
x = "psimi25Interactor" An object of [psimi25Interactor-class](#)

sourceId *Extracts the source database ID of the given parameter*

Description

see [sourceDb-methods](#)

Usage

sourceId(x)

Arguments

x [sourceDb-methods](#)

Value

A character string presenting ID in the source database

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

See Also

see [sourceId-methods](#)

`taxId-methods` *Methods for function taxId*

Description

Returns the NCBI Taxonomy ID of the given object

Methods

`x = "psimi25Complex"` An `psimi25Complex-class` object

`x = "psimi25InteractionEntry"` An object of `psimi25InteractionEntry-class`

`taxId` *The taxonomy ID of the given parameter*

Description

Returns the taxonomy ID of the object

Usage

`taxId(x)`

Arguments

`x` An object of `psimi25InteractionEntry-class` or `psimi25Complex-class`

Value

A character string of taxIDs

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

References

PSI-MI 2.5 XML data exchange format, <http://www.psi-dev.info/index.php?q=node/60>

See Also

S4CLASS`psimi25InteractionEntry-class`

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

taxId(hprdSet)
```

translateID-methods

Translate interactors into other identifiers

Description

The method finds any annotation IDs of of `psimi25Graph-class` or `psimi25Hypergraph-class` or `psimi25Interactor-class`

Methods

- r = "psimi25Graph"** An object of `psimi25Graph-class`. It replaces the nodes with translated IDs and returns a new psimi25Graph object back.
- r = "psimi25Hypergraph"** An object of `psimi25Hypergraph-class`. Since the nodes of psimi25Hypergraph are not mutable, this method accepts a UniProt ID of interactors and returns the translated ID back. NA is also acceptable, which can be used to check interactors without mapping to UniProt
- r = "list"** A list of `psimi25Interactor-class`, returns a vector of translated identifiers back
- r = "psimi25Interactor"** An object of `psimi25Interactor-class`, returns translated identifier. Before using the method it is advisable to used `xref(x)` method to check which cross references are provided.

translateID

Finds identifiers of a given object

Description

see `translateID-methods`

Usage

`translateID(r, ...)`

Arguments

- r** An object of `psimi25Graph`, `psimi25Hypergraph`, `psimi25Interactor` or a list of `psimi25Interactor`
- ...** the symbol of the ID to translate

Details

see `translateID-methods`

Value

The object of the same class as the parameter

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>

See Also

see [translateID-methods](#)

Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

it <- interactors(hprdSet)[[1]]
translateID(it, "uniprot")
translateID(it, "entrezgene")

##Not run
intactxml <- file.path(xmlDir, "intact_2008_test.xml")
intactSet <- parsePsimi25Interaction(intactxml, INTACT.PSIMI25)
intactGraph <- psimi25XML2Graph(intactxml, INTACT.PSIMI25)
intactGraphNew <- translateID(intactGraph,"sourceId")## translate the nodes of the graph

intactSetInteractors <- interactors(intactSet)
intactXrefExample <- xref(intactSetInteractors[[1]])
translateID(intactSetInteractors,"intact")
translateID(intactSetInteractors[[1]],"intact")

intactComplexxml <- file.path(xmlDir,"intact_complexSample.xml")
intactComplexSet <- parsePsimi25Complex(intactComplexxml, INTACT.PSIMI25)
intactComplexGraph <- psimi25XML2Graph(intactComplexxml, INTACT.PSIMI25, type="complex")
translateID(intactComplexGraph, "intact", "P49432")
translateID(intactComplexGraph, "intact", NA)
## End(Not run)
```

Description

if the given parameter is an object of [psimi25Interactor-class](#), then the UniProt ID of this protein is returned. In case it is an object of [psimi25Source-class](#), the character string representing the path to UniProt is returned.

Methods

x = "psimi25Interactor" An object of [psimi25Interactor-class](#)
x = "psimi25Source" An object of [psimi25Source-class](#)

`uniprot`*The UniProt Identifier in the PSI-MI 2.5 XML file*

Description

A character string representing the UniProt identifier in primaryRef or secondaryRef attributes

Usage`uniprot (x)`**Arguments**

`x` An object of [psimi25Source-class](#)

Value

A character string of the identifier

Author(s)

Tony Chiang <tchiang@ebi.ac.uk>, Jitao David Zhang <j.zhang@dkfz.de>

See Also[psimi25Source-class](#)**Examples**`uniprot (HPRD.PSIMI25)`

`validatePSIMI25`*Validating PSI-MI 2.5 file with MIF25 XML schema*

Description

The function validates given PSI-MI 2.5 file with MIF25 XML schema provided by the Molecular Interactions Workgroup of HUPO Proteomics Standards Initiative

Usage

```
validatePSIMI25(file,  
schema = system.file("extdata/schemas/MIF25.xsd", package = "RpsiXML"),  
ignore.stderr = TRUE)
```

Arguments

`file` The name or the URL of the file to be validated
`schema` The schema file of PSI-MI 2.5 file format by default
`ignore.stderr` Whether to print out errors in the console

Details

We advice to set "ignore.stderr=FALSE" for the first time of validating. The error number of the file will be printed in the console. When the number is not 0, one can set "ignore.stderr=TRUE" and see the errors produced during the validation.

Value

The number of errors in validating the file

Note

This function sofar depends on the tool "xmllint" bundled with libxml2 library. We plan to compile it later to run independent of the tool.

Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

References

libxml2 library <http://xmlsoft.org/> PSI-MI 2.5 XML schema <http://psidev.sourceforge.net/mi/rel25/src/MIF25.xsd>

Examples

```
okFile <- system.file("extdata/psi25files/intact_2008_test.xml",
                      package="RpsiXML")
validatePSIMI25(okFile)
```

Index

*Topic classes

psimi25Complex-class, 15
psimi25ComplexEntry-class, 16
psimi25Experiment-class, 17
psimi25Graph-class, 17
psimi25Hypergraph-class, 18
psimi25Interaction-class, 19
psimi25InteractionEntry-class,
 20
psimi25Interactor-class, 21
psimi25Source-class, 22

*Topic methods

availableXrefs-methods, 2
interactorInfo-methods, 9
interactors-methods, 10
sourceDb-methods, 26
sourceId-methods, 27
taxId-methods, 28
translateID-methods, 29
uniprot-methods, 30

*Topic models

availableXrefs, 2
availableXrefs-methods, 2
bait, 3
BIOGRID.PSIMI25, 1
complexes, 5
complexName, 4
eListHandler, 6
getAbstractByPMID, 7
interactions, 8
interactionType, 7
interactorInfo, 9
interactors, 10
list2Matrix, 11
null2na, 12
organismName, 12
parseComplex, 13
parsePsimi25Interaction, 14
psimi25XML2Graph, 23
releaseDate, 24
separateXMLDataByExpt, 25
sourceDb, 26
sourceDb-methods, 26

sourceId, 27
sourceId-methods, 27
taxId, 28
translateID, 29
translateID-methods, 29
uniprot, 31
validatePSIMI25, 31

abstract, psimi25Graph-method
 (*psimi25Graph-class*), 17
availableXrefs, 2, 2, 10
availableXrefs, list-method
 (*availableXrefs-methods*), 2
availableXrefs, psimi25InteractionEntry-method
 (*availableXrefs-methods*), 2
availableXrefs, psimi25Interactor-method
 (*availableXrefs-methods*), 2
availableXrefs-methods, 2

bait, 3
bait, psimi25Interaction-method
 (*psimi25Interaction-class*),
 19
BIOGRID.PSIMI25, 1

complexAttributes (*complexName*), 4
complexes, 5
complexes, psimi25ComplexEntry-method
 (*psimi25ComplexEntry-class*),
 16
complexMembers (*complexName*), 4
complexName, 4
confidenceValue (*bait*), 3
CORUM.PSIMI25 (*BIOGRID.PSIMI25*), 1

DIP.PSIMI25 (*BIOGRID.PSIMI25*), 1

eListHandler, 6

getAbstractByPMID, 7
graphNEL, 18

HPRD.PSIMI25 (*BIOGRID.PSIMI25*), 1

iListHandler (*eListHandler*), 6

inhibitor (*bait*), 3
 initialize, psimi25Hypergraph-method
 (*psimi25Hypergraph-class*),
 18
 INTACT.PSIMI25 (*BIOGRID.PSIMI25*),
 1
 interactions, 8
 interactions, psimi25InteractionEntry-method
 (*psimi25InteractionEntry-class*),
 20
 interactionType, 7
 interactionType, psimi25Interaction-method
 (*psimi25Interaction-class*),
 19
 interactorInfo, 9
 interactorInfo, list-method
 (*interactorInfo-methods*), 9
 interactorInfo, psimi25ComplexEntry-method
 (*interactorInfo-methods*), 9
 interactorInfo, psimi25Graph-method
 (*interactorInfo-methods*), 9
 interactorInfo, psimi25Hypergraph-method
 (*interactorInfo-methods*), 9
 interactorInfo, psimi25InteractionEntry-method
 (*interactorInfo-methods*), 9
 interactorInfo-methods, 9
 interactors, 10
 interactors, psimi25ComplexEntry-method
 (*psimi25ComplexEntry-class*),
 16
 interactors, psimi25Graph-method
 (*interactors-methods*), 10
 interactors, psimi25Hypergraph-method
 (*interactors-methods*), 10
 interactors, psimi25InteractionEntry-method
 (*psimi25InteractionEntry-class*),
 20
 interactors-methods, 10
 list2Matrix, 11
 MATRIXDB.PSIMI25
 (*BIOGRID.PSIMI25*), 1
 MINT.PSIMI25 (*BIOGRID.PSIMI25*), 1
 MIPS.PSIMI25 (*BIOGRID.PSIMI25*), 1
 MPACT.PSIMI25 (*BIOGRID.PSIMI25*), 1
 neutralComponent (*bait*), 3
 null2na, 12
 organismName, 12
 organismName, psimi25InteractionEntry-method
 (*psimi25InteractionEntry-class*),
 20
 parseComplex, 13
 parseComplex, psimi25Source-method
 (*psimi25Source-class*), 22
 parseExperiment, 17
 parseExperiment (parseComplex), 13
 parseExperiment, psimi25Source-method
 (*psimi25Source-class*), 22
 parseInteractor, 22
 parseInteractor (parseComplex), 13
 parseInteractor, psimi25Source-method
 (*psimi25Source-class*), 22
 parsePsimi25Complex, 1, 16, 23
 parsePsimi25Complex
 (*parsePsimi25Interaction*),
 14
 parsePsimi25Interaction, 1, 14, 20,
 21, 23–25
 participant (*bait*), 3
 prey (*bait*), 3
 prey, psimi25Interaction-method
 (*psimi25Interaction-class*),
 19
 psimi25Complex-class, 4, 5, 13, 15, 28
 psimi25Complex-class, 15, 26–28
 psimi25ComplexEntry, 16
 psimi25ComplexEntry-class, 5, 9–11,
 15
 psimi25ComplexEntry-class, 9, 10,
 16
 psimi25Experiment-class, 20
 psimi25Experiment-class, 17
 psimi25Graph-class, 9, 19, 24–26, 29
 psimi25Graph-class, 9, 10, 17, 29
 psimi25Hypergraph-class, 9, 18, 24,
 26, 29
 psimi25Hypergraph-class, 9, 10, 18,
 29
 psimi25Interaction-class, 3, 4, 7, 8,
 15, 21
 psimi25Interaction-class, 19, 26, 27
 psimi25InteractionEntry-class,
 8–13, 15, 20, 24, 25, 28
 psimi25InteractionEntry-class, 9,
 10, 20, 28
 psimi25Interactor-class, 2, 20, 29,
 30
 psimi25Interactor-class, 2, 9, 21,
 26, 27, 29, 30
 psimi25Source-class, 1, 13, 14, 24–26,
 30, 31
 psimi25Source-class, 22, 26, 30
 psimi25XML2Graph, 1, 9, 10, 17–19, 23,

23
pubmedID (*bait*), 3

releaseDate, 24
releaseDate, psimi25InteractionEntry-method
 (*psimi25InteractionEntry-class*), 20

separateXMLDataByExpt, 25
show, psimi25Complex-method
 (*psimi25Complex-class*), 15
show, psimi25ComplexEntry-method
 (*psimi25ComplexEntry-class*),
 16
show, psimi25Graph-method
 (*psimi25Graph-class*), 17
show, psimi25Hypergraph-method
 (*psimi25Hypergraph-class*),
 18
show, psimi25Interaction-method
 (*psimi25Interaction-class*),
 19
show, psimi25InteractionEntry-method
 (*psimi25InteractionEntry-class*),
 20
show, psimi25Interactor-method
 (*psimi25Interactor-class*),
 21
sourceDb, 26
sourceDb, psimi25Complex-method
 (*sourceDb-methods*), 26
sourceDb, psimi25Interaction-method
 (*sourceDb-methods*), 26
sourceDb, psimi25Interactor-method
 (*sourceDb-methods*), 26
sourceDb, psimi25Source-method
 (*sourceDb-methods*), 26
sourceDb-methods, 26, 27
sourceDb-methods, 26
sourceId, 27
sourceId, psimi25Complex-method
 (*sourceId-methods*), 27
sourceId, psimi25Interaction-method
 (*sourceId-methods*), 27
sourceId, psimi25Interactor-method
 (*sourceId-methods*), 27
sourceId-methods, 27
sourceId-methods, 27

taxId, 28
taxId, psimi25Complex-method
 (*taxId-methods*), 28

taxId, psimi25InteractionEntry-method
 (*psimi25InteractionEntry-class*),
 20
 taxId-methods, 28
translateID, 29
translateID, list-method
 (*translateID-methods*), 29
translateID, psimi25Graph-method
 (*translateID-methods*), 29
translateID, psimi25Hypergraph-method
 (*translateID-methods*), 29
translateID, psimi25Interactor-method
 (*translateID-methods*), 29
translateID-methods, 29, 30
translateID-methods, 29

uniprot, 31
uniprot, psimi25Interactor-method
 (*uniprot-methods*), 30
uniprot, psimi25Source-method
 (*psimi25Source-class*), 22
uniprot-methods, 30

validatePSIMI25, 31

xref, 10
xref (*availableXrefs*), 2