

Using the GEOquery package

Sean Davis^{‡*}

October 22, 2008

[‡]Genetics Branch
National Cancer Institute
National Institutes of Health

Contents

| | | |
|----------|--|-----------|
| 1 | Overview of GEO | 2 |
| 1.1 | Platforms | 2 |
| 1.2 | Samples | 2 |
| 1.3 | Series | 2 |
| 1.4 | Datasets | 2 |
| 2 | Getting Started using GEOquery | 3 |
| 3 | GEOquery Data Structures | 3 |
| 3.1 | The GDS, GSM, and GPL classes | 4 |
| 3.2 | The GSE class | 8 |
| 4 | Converting to BioConductor ExpressionSets and limma MALists | 12 |
| 4.1 | Getting GSE Series Matrix files as an ExpressionSet | 12 |
| 4.2 | Converting GDS to an ExpressionSet | 13 |
| 4.3 | Converting GDS to an MAList | 16 |
| 4.4 | Converting GSE to an ExpressionSet | 19 |
| 5 | Accessing Raw Data from GEO | 22 |
| 6 | Conclusion | 22 |
| 7 | sessionInfo | 22 |

*sdavis2@mail.nih.gov

1 Overview of GEO

The NCBI Gene Expression Omnibus (GEO) serves as a public repository for a wide range of high-throughput experimental data. These data include single and dual channel microarray-based experiments measuring mRNA, genomic DNA, and protein abundance, as well as non-array techniques such as serial analysis of gene expression (SAGE), mass spectrometry proteomic data, and high-throughput sequencing data.

At the most basic level of organization of GEO, there are four basic entity types. The first three (Sample, Platform, and Series) are supplied by users; the fourth, the dataset, is compiled and curated by GEO staff from the user-submitted data.¹

1.1 Platforms

A Platform record describes the list of elements on the array (e.g., cDNAs, oligonucleotide probesets, ORFs, antibodies) or the list of elements that may be detected and quantified in that experiment (e.g., SAGE tags, peptides). Each Platform record is assigned a unique and stable GEO accession number (GPLxxx). A Platform may reference many Samples that have been submitted by multiple submitters.

1.2 Samples

A Sample record describes the conditions under which an individual Sample was handled, the manipulations it underwent, and the abundance measurement of each element derived from it. Each Sample record is assigned a unique and stable GEO accession number (GSMxxx). A Sample entity must reference only one Platform and may be included in multiple Series.

1.3 Series

A Series record defines a set of related Samples considered to be part of a group, how the Samples are related, and if and how they are ordered. A Series provides a focal point and description of the experiment as a whole. Series records may also contain tables describing extracted data, summary conclusions, or analyses. Each Series record is assigned a unique and stable GEO accession number (GSExxx). Series records are available in a couple of formats which are handled by GEOquery independently. The smaller and new GSEMatrix files are quite fast to parse; a simple flag is used by GEOquery to choose to use GSEMatrix files (see below).

1.4 Datasets

GEO DataSets (GDSxxx) are curated sets of GEO Sample data. A GDS record represents a collection of biologically and statistically comparable GEO Samples and forms the basis

¹See <http://www.ncbi.nih.gov/geo> for more information

of GEO's suite of data display and analysis tools. Samples within a GDS refer to the same Platform, that is, they share a common set of probe elements. Value measurements for each Sample within a GDS are assumed to be calculated in an equivalent manner, that is, considerations such as background processing and normalization are consistent across the dataset. Information reflecting experimental design is provided through GDS subsets.

2 Getting Started using GEOquery

Getting data from GEO is really quite easy. There is only one command that is needed, `getGEO`. This one function interprets its input to determine how to get the data from GEO and then parse the data into useful R data structures. Usage is quite simple:

```
> library(GEOquery)
```

This loads the GEOquery library.

```
> gds <- getGEO("GDS10")
```

```
File stored at:  
/tmp/RtmpnFTpz5/GDS10.soft
```

Now, `gds` contains the R data structure (of class *GDS*) that represents the GDS1 entry from GEO. You'll note that the filename used to store the download was output to the screen (but not saved anywhere) for later use to a call to `getGEO(filename=...)`.

We can do the same with any other GEO accession, such as GSM3, a GEO sample.

```
> gsm <- getGEO("GSM3")
```

```
File stored at:  
/tmp/RtmpnFTpz5/GSM3.soft
```

3 GEOquery Data Structures

The GEOquery data structures really come in two forms. The first, comprising *GDS*, *GPL*, and *GSM* all behave similarly and accessors have similar effects on each. The fourth GEOquery data structure, *GSE* is a composite data type made up of a combination of *GSM* and *GPL* objects. I will explain the first three together first.

3.1 The GDS, GSM, and GPL classes

Each of these classes is comprised of a metadata header (taken nearly verbatim from the SOFT format header) and a GEODataTable. The GEODataTable has two simple parts, a Columns part which describes the column headers on the Table part. There is also a *show* method for each class. For example, using the gsm from above:

```
> Meta(gsm)

$channel_count
[1] "1"

$contact_address
[1] "6 Center Drive"

$contact_city
[1] "Bethesda"

$contact_country
[1] "USA"

$contact_department
[1] "LCDB"

$contact_email
[1] "oliver@helix.nih.gov"

$contact_fax
[1] "301-496-5239"

$contact_institute
[1] "NIDDK, NIH"

$contact_name
[1] "Brian,,Oliver"

$contact_phone
[1] "301-496-5495"

$contact_state
[1] "MD"

$contact_web_link
[1] "http://www.nidk.nih.gov/intram/people/boliver.htm"
```

\$`contact_zip/postal_code`

[1] "20892"

\$data_row_count

[1] "3456"

\$description

[1] "Testis dissected from adult (12-24 hours post-eclosion) Drosophila melanogaster of

[2] "Keywords = gonad, male, sex"

\$geo_accession

[1] "GSM3"

\$last_update_date

[1] "May 27 2005"

\$molecule_ch1

[1] "total RNA"

\$organism_ch1

[1] "Drosophila melanogaster"

\$platform_id

[1] "GPL5"

\$series_id

[1] "GSE462"

\$source_name_ch1

[1] "y w[67c1]/Y testis"

\$status

[1] "Public on Oct 18 2000"

\$submission_date

[1] "Oct 18 2000"

\$supplementary_file

[1] "NONE"

\$title

```
[1] "testis a"
```

```
$type
```

```
[1] "RNA"
```

```
> Table(gsm)[1:5, ]
```

| | ID_REF | SIGNAL_RAW | BKD_FORM | NORM_FORM | BKD_RAW | NORM_VALUE | CONST |
|---|--------|------------|----------|-----------|-------------|-------------|-------|
| 1 | 1 | 138392.65 | no | no | 101113.7775 | 395070.1312 | 39542 |
| 2 | 2 | 100973.49 | no | no | 101113.7775 | 395070.1312 | 39542 |
| 3 | 3 | 118994.03 | no | no | 101113.7775 | 395070.1312 | 39542 |
| 4 | 4 | 108126.05 | yes | no | 101113.7775 | 395070.1312 | 39542 |
| 5 | 5 | 293362.11 | no | no | 101113.7775 | 395070.1312 | 39542 |

```
VALUE
```

| | |
|---|-------------|
| 1 | 76820.87249 |
| 2 | 39401.7125 |
| 3 | 57422.25249 |
| 4 | 46554.2725 |
| 5 | 231790.3324 |

```
> Columns(gsm)
```

| | Column | Description |
|---|------------|--|
| 1 | ID_REF | |
| 2 | SIGNAL_RAW | raw signal |
| 3 | BKD_FORM | |
| 4 | NORM_FORM | |
| 5 | BKD_RAW | raw background as taken in four quarters of microarray |
| 6 | NORM_VALUE | normalization value |
| 7 | CONST | constant value |
| 8 | VALUE | |

The *GPL* behaves exactly as the *GSM* class. However, the *GDS* has a bit more information associated with the *Columns* method:

```
> Columns(gds)
```

| | sample | tissue | strain | disease.state |
|---|--------|--------|--------|--------------------|
| 1 | GSM582 | spleen | NOD | diabetic |
| 2 | GSM589 | spleen | NOD | diabetic |
| 3 | GSM583 | spleen | Idd3 | diabetic-resistant |
| 4 | GSM590 | spleen | Idd3 | diabetic-resistant |
| 5 | GSM584 | spleen | Idd5 | diabetic-resistant |
| 6 | GSM591 | spleen | Idd5 | diabetic-resistant |

| | | | | |
|----|--------|--------|---|--------------------|
| 7 | GSM585 | spleen | Idd3+Idd5 | diabetic-resistant |
| 8 | GSM592 | spleen | Idd3+Idd5 | diabetic-resistant |
| 9 | GSM586 | spleen | Idd9 | diabetic-resistant |
| 10 | GSM593 | spleen | Idd9 | diabetic-resistant |
| 11 | GSM587 | spleen | B10.H2g7 | nondiabetic |
| 12 | GSM594 | spleen | B10.H2g7 | nondiabetic |
| 13 | GSM588 | spleen | B10.H2g7 Idd3 | nondiabetic |
| 14 | GSM595 | spleen | B10.H2g7 Idd3 | nondiabetic |
| 15 | GSM596 | thymus | NOD | diabetic |
| 16 | GSM603 | thymus | NOD | diabetic |
| 17 | GSM597 | thymus | Idd3 | diabetic-resistant |
| 18 | GSM604 | thymus | Idd3 | diabetic-resistant |
| 19 | GSM598 | thymus | Idd5 | diabetic-resistant |
| 20 | GSM605 | thymus | Idd5 | diabetic-resistant |
| 21 | GSM599 | thymus | Idd3+Idd5 | diabetic-resistant |
| 22 | GSM606 | thymus | Idd3+Idd5 | diabetic-resistant |
| 23 | GSM600 | thymus | Idd9 | diabetic-resistant |
| 24 | GSM607 | thymus | Idd9 | diabetic-resistant |
| 25 | GSM601 | thymus | B10.H2g7 | nondiabetic |
| 26 | GSM608 | thymus | B10.H2g7 | nondiabetic |
| 27 | GSM602 | thymus | B10.H2g7 Idd3 | nondiabetic |
| 28 | GSM609 | thymus | B10.H2g7 Idd3 | nondiabetic |
| | | | | description |
| 1 | | | Value for GSM582: NOD_S1; src: Spleen | |
| 2 | | | Value for GSM589: NOD_S2; src: Spleen | |
| 3 | | | Value for GSM583: Idd3_S1; src: Spleen | |
| 4 | | | Value for GSM590: Idd3_S2; src: Spleen | |
| 5 | | | Value for GSM584: Idd5_S1; src: Spleen | |
| 6 | | | Value for GSM591: Idd5_S2; src: Spleen | |
| 7 | | | Value for GSM585: Idd3+5_S1; src: Spleen | |
| 8 | | | Value for GSM592: Idd3+5_S2; src: Spleen | |
| 9 | | | Value for GSM586: Idd9_S1; src: Spleen | |
| 10 | | | Value for GSM593: Idd9_S2; src: Spleen | |
| 11 | | | Value for GSM587: B10.H2g7_S1; src: Spleen | |
| 12 | | | Value for GSM594: B10.H2g7_S2; src: Spleen | |
| 13 | | | Value for GSM588: B10.H2g7 Idd3_S1; src: Spleen | |
| 14 | | | Value for GSM595: B10.H2g7 Idd3_S2; src: Spleen | |
| 15 | | | Value for GSM596: NOD_T1; src: Thymus | |
| 16 | | | Value for GSM603: NOD_T2; src: Thymus | |
| 17 | | | Value for GSM597: Idd3_T1; src: Thymus | |
| 18 | | | Value for GSM604: Idd3_T2; src: Thymus | |
| 19 | | | Value for GSM598: Idd5_T1; src: Thymus | |

```

20         Value for GSM605: Idd5_T2; src: Thymus
21     Value for GSM599: Idd3+5_T1; src: Thymus
22     Value for GSM606: Idd3+5_T2; src: Thymus
23     Value for GSM600: Idd9_T1; src: Thymus
24     Value for GSM607: Idd9_T2; src: Thymus
25     Value for GSM601: B10.H2g7_T1; src: Thymus
26     Value for GSM608: B10.H2g7_T2; src: Thymus
27 Value for GSM602: B10.H2g7 Idd3_T1; src: Thymus
28 Value for GSM609: B10.H2g7 Idd3_T2; src: Thymus

```

3.2 The GSE class

The *GSE* is the most confusing of the GEO entities. A GSE entry can represent an arbitrary number of samples run on an arbitrary number of platforms. The *GSE* has a metadata section, just like the other classes. However, it doesn't have a *GEODDataTable*. Instead, it contains two lists, accessible using *GPLLlist* and *GSMList*, that are each lists of *GPL* and *GSM* objects. To show an example:

```
> gse <- getGEO("GSE462", GSEMatrix = FALSE)
```

```
File stored at:
```

```
/tmp/RtmpnFTpz5/GSE462.soft
```

```
Parsing....
```

```
^PLATFORM = GPL5
```

```
^SAMPLE = GSM3
```

```
^SAMPLE = GSM4
```

```
^SAMPLE = GSM5
```

```
^SAMPLE = GSM6
```

```
^SAMPLE = GSM7
```

```
^SAMPLE = GSM8
```

```
^SAMPLE = GSM9
```

```
> Meta(gse)
```

```
$contact_address
```

```
[1] "6 Center Drive"
```

```
$contact_city
```

```
[1] "Bethesda"
```

```
$contact_country
```

```
[1] "USA"
```

```
$contact_department
```


[1] "LCDB"

\$contact_email

[1] "oliver@helix.nih.gov"

\$contact_fax

[1] "301-496-5239"

\$contact_institute

[1] "NIDDK, NIH"

\$contact_name

[1] "Brian,,Oliver"

\$contact_phone

[1] "301-496-5495"

\$contact_state

[1] "MD"

\$contact_web_link

[1] "http://www.niddk.nih.gov/intram/people/boliver.htm"

\$`contact_zip/postal_code`

[1] "20892"

\$contributor

[1] "Justen,,Andrews" "Gerard,G,Bouffard" "Chris,,Cheadle"

[4] "Jining,,LÃij" "Kevin,G,Becker" "Brian,,Oliver"

\$geo_accession

[1] "GSE462"

\$last_update_date

[1] "Oct 28 2005"

\$platform_id

[1] "GPL5"

\$pubmed_id

[1] "11116097"

```

$sample_id
[1] "GSM10" "GSM3" "GSM4" "GSM5" "GSM6" "GSM7" "GSM8" "GSM9"

$status
[1] "Public on Jul 16 2003"

$submission_date
[1] "Jun 25 2003"

$summary
[1] "Identification and annotation of all the genes in the sequenced Drosophila genome i

$title
[1] "Analysis of transcription in the Drosophila melanogaster testis"

$type
[1] "other"

> names(GSMList(gse))

[1] "GSM10" "GSM3" "GSM4" "GSM5" "GSM6" "GSM7" "GSM8" "GSM9"

> GSMList(gse)[[1]]

An object of class "GSM"
channel_count
[1] "1"
contact_address
[1] "6 Center Drive"
contact_city
[1] "Bethesda"
contact_country
[1] "USA"
contact_department
[1] "LCDB"
contact_email
[1] "oliver@helix.nih.gov"
contact_fax
[1] "301-496-5239"
contact_institute
[1] "NIDDK, NIH"
contact_name
[1] "Brian,,Oliver"

```

```

contact_phone
[1] "301-496-5495"
contact_state
[1] "MD"
contact_web_link
[1] "http://www.niddk.nih.gov/intram/people/boliver.htm"
contact_zip/postal_code
[1] "20892"
data_row_count
[1] "3456"
description
[1] "Whole adult male minus (12-24 hours post-eclosion) Drosophila melanogaster of the g
geo_accession
[1] "GSM10"
last_update_date
[1] "Mar 09 2006"
molecule_ch1
[1] "total RNA"
organism_ch1
[1] "Drosophila melanogaster"
platform_id
[1] "GPL5"
series_id
[1] "GSE462"
source_name_ch1
[1] "y w[67c1] female"
status
[1] "Public on Oct 18 2000"
submission_date
[1] "Oct 18 2000"
title
[1] "female b"
type
[1] "RNA"
An object of class "GEODataTable"
***** Column Descriptions *****
      Column      Description
1      ID_REF
2 SIGNAL_RAW      raw signal
3      BKD_FORM
4      NORM_FORM
5      BKD_RAW      raw background

```

```

6 NORM_VALUE normalization value
7     CONST      constant value
8     VALUE
***** Data Table *****
  ID_REF SIGNAL_RAW BKD_FORM NORM_FORM  BKD_RAW NORM_VALUE CONST  VALUE
1     1     4486.49      0         0 3379.579  23337.54 39542 55845.45
2     2     3482.51      0         0 3379.579  23337.54 39542 41058.05
3     3     3812.39      0         0 3379.579  23337.54 39542 45916.78
4     4     3257.56      1         0 3379.579  23337.54 39542 37744.81
5     5     5436.91      0         0 3379.579  23337.54 39542 69843.97
3450 more rows ...

```

```
> names(GPLList(gse))
```

```
[1] "GPL5"
```

See below for an additional, preferred method of obtaining GSE information.

4 Converting to BioConductor ExpressionSets and limma MALists

GEO datasets are (unlike some of the other GEO entities), quite similar to the *limma* data structure *MAList* and to the *Biobase* data structure *ExpressionSet*. Therefore, there are two functions, `GDS2MA` and `GDS2eSet` that accomplish that task.

4.1 Getting GSE Series Matrix files as an ExpressionSet

GEO Series are collections of related experiments. In addition to being available as SOFT format files, which are quite large, NCBI GEO has prepared a simpler format file based on tab-delimited text. The `getGEO` function can handle this format and will parse very large GSEs quite quickly. The data structure returned from this parsing is a list of *ExpressionSets*. As an example, we download and parse GSE2553.

```
> gse2553 <- getGEO("GSE2553", GSEMatrix = TRUE)
```

```

Found 1 file(s)
GSE2553_series_matrix.txt.gz
File stored at:
/tmp/RtmpnFTpz5/GPL1977.soft

```

```
> show(gse2553)
```

```

$GSE2553_series_matrix.txt.gz
ExpressionSet (storageMode: lockedEnvironment)
assayData: 12600 features, 181 samples
  element names: exprs
phenoData
  sampleNames: GSM48681, GSM48682, ..., GSM48861 (181 total)
  varLabels and varMetadata description:
    title: NA
    geo_accession: NA
    ...: ...
    data_row_count: NA
    (27 total)
featureData
  featureNames: 1, 2, ..., 12600 (12600 total)
  fvarLabels and fvarMetadata description:
    ID: NA
    PenAt: NA
    ...: ...
    Chimeric_Cluster_IDs: NA
    (13 total)
  additional fvarMetadata: Column, Description
experimentData: use 'experimentData(object)'
Annotation: GPL1977

```

```
> show(pData(phenoData(gse2553[[1]]))[1:5, c(1, 6, 8)])
```

| | | title | type |
|----------|---|---|------|
| GSM48681 | Patient sample ST18, | Dermatofibrosarcoma | RNA |
| GSM48682 | Patient sample ST410, | Ewing Sarcoma | RNA |
| GSM48683 | Patient sample ST130, | Sarcoma, NOS | RNA |
| GSM48684 | Patient sample ST293, | Malignant Peripheral Nerve Sheath Tumor | RNA |
| GSM48685 | Patient sample ST367, | Liposarcoma | RNA |
| | source_name_ch1 | | |
| GSM48681 | Dermatofibrosarcoma | | |
| GSM48682 | Ewing Sarcoma | | |
| GSM48683 | Sarcoma, NOS | | |
| GSM48684 | Malignant Peripheral Nerve Sheath Tumor | | |
| GSM48685 | Liposarcoma | | |

4.2 Converting GDS to an ExpressionSet

Taking our `gds` object from above, we can simply do:

```
> eset <- GDS2eSet(gds, do.log2 = TRUE)
```

File stored at:
/tmp/RtmpnFTpz5/GPL24.annot

Now, `eset` is an *ExpressionSet* that contains the same information as in the GEO dataset, including the sample information, which we can see here:

```
> eset
```

```
ExpressionSet (storageMode: lockedEnvironment)
assayData: 39114 features, 28 samples
  element names: exprs
phenoData
  sampleNames: GSM582, GSM589, ..., GSM609 (28 total)
  varLabels and varMetadata description:
    sample: NA
    tissue: NA
    ...: ...
    description: NA
    (5 total)
featureData
  featureNames: 1, 2, ..., 39114 (39114 total)
  fvarLabels and fvarMetadata description:
    ID: ID from Platform data table
    Gene.title: Entrez Gene name
    ...: ...
    GO.Component.1: Gene Ontology Component identifier
    (21 total)
  additional fvarMetadata: Column
experimentData: use 'experimentData(object)'
  pubMedIds: 11827943
Annotation:
```

```
> pData(eset)
```

| | sample | tissue | strain | disease.state |
|--------|--------|--------|-----------|--------------------|
| GSM582 | GSM582 | spleen | NOD | diabetic |
| GSM589 | GSM589 | spleen | NOD | diabetic |
| GSM583 | GSM583 | spleen | Idd3 | diabetic-resistant |
| GSM590 | GSM590 | spleen | Idd3 | diabetic-resistant |
| GSM584 | GSM584 | spleen | Idd5 | diabetic-resistant |
| GSM591 | GSM591 | spleen | Idd5 | diabetic-resistant |
| GSM585 | GSM585 | spleen | Idd3+Idd5 | diabetic-resistant |
| GSM592 | GSM592 | spleen | Idd3+Idd5 | diabetic-resistant |
| GSM586 | GSM586 | spleen | Idd9 | diabetic-resistant |

| | | | | |
|--------|--------|-------------------|-------------------|--------------------|
| GSM593 | GSM593 | spleen | Idd9 | diabetic-resistant |
| GSM587 | GSM587 | spleen | B10.H2g7 | nondiabetic |
| GSM594 | GSM594 | spleen | B10.H2g7 | nondiabetic |
| GSM588 | GSM588 | spleen | B10.H2g7 Idd3 | nondiabetic |
| GSM595 | GSM595 | spleen | B10.H2g7 Idd3 | nondiabetic |
| GSM596 | GSM596 | thymus | NOD | diabetic |
| GSM603 | GSM603 | thymus | NOD | diabetic |
| GSM597 | GSM597 | thymus | Idd3 | diabetic-resistant |
| GSM604 | GSM604 | thymus | Idd3 | diabetic-resistant |
| GSM598 | GSM598 | thymus | Idd5 | diabetic-resistant |
| GSM605 | GSM605 | thymus | Idd5 | diabetic-resistant |
| GSM599 | GSM599 | thymus | Idd3+Idd5 | diabetic-resistant |
| GSM606 | GSM606 | thymus | Idd3+Idd5 | diabetic-resistant |
| GSM600 | GSM600 | thymus | Idd9 | diabetic-resistant |
| GSM607 | GSM607 | thymus | Idd9 | diabetic-resistant |
| GSM601 | GSM601 | thymus | B10.H2g7 | nondiabetic |
| GSM608 | GSM608 | thymus | B10.H2g7 | nondiabetic |
| GSM602 | GSM602 | thymus | B10.H2g7 Idd3 | nondiabetic |
| GSM609 | GSM609 | thymus | B10.H2g7 Idd3 | nondiabetic |
| | | | | description |
| GSM582 | | Value for GSM582: | NOD_S1; | src: Spleen |
| GSM589 | | Value for GSM589: | NOD_S2; | src: Spleen |
| GSM583 | | Value for GSM583: | Idd3_S1; | src: Spleen |
| GSM590 | | Value for GSM590: | Idd3_S2; | src: Spleen |
| GSM584 | | Value for GSM584: | Idd5_S1; | src: Spleen |
| GSM591 | | Value for GSM591: | Idd5_S2; | src: Spleen |
| GSM585 | | Value for GSM585: | Idd3+5_S1; | src: Spleen |
| GSM592 | | Value for GSM592: | Idd3+5_S2; | src: Spleen |
| GSM586 | | Value for GSM586: | Idd9_S1; | src: Spleen |
| GSM593 | | Value for GSM593: | Idd9_S2; | src: Spleen |
| GSM587 | | Value for GSM587: | B10.H2g7_S1; | src: Spleen |
| GSM594 | | Value for GSM594: | B10.H2g7_S2; | src: Spleen |
| GSM588 | | Value for GSM588: | B10.H2g7 Idd3_S1; | src: Spleen |
| GSM595 | | Value for GSM595: | B10.H2g7 Idd3_S2; | src: Spleen |
| GSM596 | | Value for GSM596: | NOD_T1; | src: Thymus |
| GSM603 | | Value for GSM603: | NOD_T2; | src: Thymus |
| GSM597 | | Value for GSM597: | Idd3_T1; | src: Thymus |
| GSM604 | | Value for GSM604: | Idd3_T2; | src: Thymus |
| GSM598 | | Value for GSM598: | Idd5_T1; | src: Thymus |
| GSM605 | | Value for GSM605: | Idd5_T2; | src: Thymus |
| GSM599 | | Value for GSM599: | Idd3+5_T1; | src: Thymus |
| GSM606 | | Value for GSM606: | Idd3+5_T2; | src: Thymus |

```

GSM600      Value for GSM600: Idd9_T1; src: Thymus
GSM607      Value for GSM607: Idd9_T2; src: Thymus
GSM601      Value for GSM601: B10.H2g7_T1; src: Thymus
GSM608      Value for GSM608: B10.H2g7_T2; src: Thymus
GSM602      Value for GSM602: B10.H2g7 Idd3_T1; src: Thymus
GSM609      Value for GSM609: B10.H2g7 Idd3_T2; src: Thymus

```

4.3 Converting GDS to an MAList

No annotation information (called platform information by GEO) was retrieved from because *ExpressionSet* does not contain slots for gene information, typically. However, it is easy to obtain this information. First, we need to know what platform this GDS used. Then, another call to `getGEO` will get us what we need.

```
> Meta(gds)$platform
```

```
[1] "GPL24"
```

```
> gpl <- getGEO("GPL5")
```

File stored at:

```
/tmp/RtmpnFTpz5/GPL5.soft
```

So, `gpl` now contains the information for GPL5 from GEO. Unlike *ExpressionSet*, the limma *MAList* does store gene annotation information, so we can use our newly created `gpl` of class *GPL* in a call to `GDS2MA` like so:

```
> MA <- GDS2MA(gds, GPL = gpl)
```

```
> MA
```

An object of class "MAList"

```
$M
```

| | GSM582 | GSM589 | GSM583 | GSM590 | GSM584 | GSM591 | GSM585 | GSM592 | GSM586 | GSM593 |
|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| [1,] | 101 | 54 | 111 | 55 | 87 | 30 | 99 | 43 | 105 | 56 |
| [2,] | 26 | 23 | 30 | 27 | 19 | 22 | 32 | 19 | 24 | 25 |
| [3,] | NA | NA | NA | NA | NA | NA | NA | NA | NA | NA |
| [4,] | 233 | 162 | 252 | 178 | 214 | 144 | 238 | 147 | 250 | 166 |
| [5,] | NA | NA | NA | NA | NA | NA | NA | NA | NA | NA |
| | GSM587 | GSM594 | GSM588 | GSM595 | GSM596 | GSM603 | GSM597 | GSM604 | GSM598 | GSM605 |
| [1,] | 43 | 14 | 112 | 43 | 97 | 36 | 117 | 40 | 125 | 45 |
| [2,] | 14 | 49 | 32 | 29 | 31 | 22 | 26 | 26 | 35 | 26 |
| [3,] | NA | 7 | NA | 4 | 10 | 22 | NA | 15 | NA | 23 |
| [4,] | 86 | 22 | 236 | 139 | 216 | 112 | 241 | 130 | 270 | 144 |
| [5,] | NA | NA | NA | 3 | NA | NA | NA | NA | NA | NA |

| | GSM599 | GSM606 | GSM600 | GSM607 | GSM601 | GSM608 | GSM602 | GSM609 |
|------|--------|--------|--------|--------|--------|--------|--------|--------|
| [1,] | 99 | 1 | 109 | 38 | 87 | 18 | 72 | 16 |
| [2,] | 18 | 13 | 25 | 32 | 28 | 40 | 14 | 41 |
| [3,] | NA | 29 | 9 | 25 | 11 | 40 | NA | 22 |
| [4,] | 239 | 148 | 211 | 139 | 208 | 16 | 174 | 15 |
| [5,] | NA | NA | NA | NA | NA | NA | NA | NA |

39109 more rows ...

\$A
NULL

\$targets

| | sample | tissue | strain | disease.state |
|---|--------|--------|--------|--------------------|
| 1 | GSM582 | spleen | NOD | diabetic |
| 2 | GSM589 | spleen | NOD | diabetic |
| 3 | GSM583 | spleen | Idd3 | diabetic-resistant |
| 4 | GSM590 | spleen | Idd3 | diabetic-resistant |
| 5 | GSM584 | spleen | Idd5 | diabetic-resistant |

description

1 Value for GSM582: NOD_S1; src: Spleen
2 Value for GSM589: NOD_S2; src: Spleen
3 Value for GSM583: Idd3_S1; src: Spleen
4 Value for GSM590: Idd3_S2; src: Spleen
5 Value for GSM584: Idd5_S1; src: Spleen

23 more rows ...

\$genes

| | ID | GB_ACC | BSCC_ID | CLONE_ID | SUB.ARRAY | DUPLICATE | ROW | COLUMN | PCR_QC | SPOT_ID |
|---|----|----------|---------|-------------|-----------|-----------|-----|--------|--------|---------|
| 1 | 1 | AI944549 | bs03g07 | FBgn0033989 | | 1 | a | 1 | 1 | passed |
| 2 | 2 | AI944695 | bs04c11 | FBgn0032821 | | 1 | a | 1 | 2 | passed |
| 3 | 3 | AI944741 | bs04h01 | FBgn0034374 | | 1 | a | 1 | 3 | passed |
| 4 | 4 | AI944801 | bs05f04 | FBgn0039421 | | 1 | a | 1 | 4 | failed |
| 5 | 5 | AI945043 | bs08c11 | FBgn0045370 | | 1 | a | 1 | 5 | passed |

1
2
3
4 gi|4505995|ref|NP_002697.1|PPPM1B| protein phosphatase 1B (formerly 2C), magnesium-dep
5

| | E_VAL | SPOT_QC |
|---|-------|---------|
| 1 | 2e-08 | 44364 |
| 2 | <NA> | 16957 |

```
3 <NA> 17896
4 1e-25 16363
5 <NA> 83502
39109 more rows ...
```

```
$notes
```

```
[[1]]
```

```
[1] "able_begin"
```

```
$channel_count
```

```
[1] "1"
```

```
$description
```

```
[1] "Examination of spleen and thymus of type 1 diabetes nonobese diabetic (NOD) mouse,
```

```
$feature_count
```

```
[1] "39114"
```

```
$order
```

```
[1] "none"
```

```
$platform
```

```
[1] "GPL24"
```

```
$platform_organism
```

```
[1] "Mus musculus"
```

```
$platform_technology_type
```

```
[1] "in situ oligonucleotide"
```

```
$pubmed_id
```

```
[1] "11827943"
```

```
$reference_series
```

```
[1] "GSE11"
```

```
$sample_count
```

```
[1] "28"
```

```
$sample_organism
```

```
[1] "Mus musculus"
```

```

$sample_type
[1] "RNA"

$title
[1] "Type 1 diabetes gene expression profiling"

$type
[1] "gene expression array-based"

$update_date
[1] "Jul 15 2003"

$value_type
[1] "count"

```

Now, *MA* is of class *MAList* and contains not only the data, but the sample information and gene information associated with GDS1.

4.4 Converting GSE to an ExpressionSet

First, make sure that using the method described above in the section “Getting GSE Series Matrix files as an ExpressionSet” for using GSE Series Matrix files is not sufficient for the task, as it is much faster and simpler. If it is not (i.e., other columns from each GSM are needed), then this method will be needed.

Converting a *GSE* object to an *ExpressionSet* object currently takes a bit of R data manipulation due to the varied data that can be stored in a *GSE* and the underlying *GSM* and *GPL* objects. However, using a simple example will hopefully be illustrative of the technique.

First, we need to make sure that all of the *GSMs* are from the same platform:

```

> gsmplatforms <- lapply(GSMList(gse), function(x) {
+   Meta(x)$platform
+ })
> gsmplatforms

$GSM10
[1] "GPL5"

$GSM3
[1] "GPL5"

$GSM4
[1] "GPL5"

```

```
$GSM5
[1] "GPL5"
```

```
$GSM6
[1] "GPL5"
```

```
$GSM7
[1] "GPL5"
```

```
$GSM8
[1] "GPL5"
```

```
$GSM9
[1] "GPL5"
```

Indeed, they all used GPL5 as their platform (which we could have determined by looking at the GPLList for `gse`, which shows only one GPL for this particular GSE.). So, now we would like to know what column represents the data that we would like to extract. Looking at the first few rows of the Table of a single GSM will likely give us an idea (and by the way, GEO uses a convention that the column that contains the single “measurement” for each array is called the “VALUE” column, which we could use if we don’t know what other column is most relevant).

```
> Table(GSMList(gse)[[1]])[1:5, ]
```

| | ID_REF | SIGNAL_RAW | BKD_FORM | NORM_FORM | BKD_RAW | NORM_VALUE | CONST | VALUE |
|---|--------|------------|----------|-----------|----------|------------|-------|----------|
| 1 | 1 | 4486.49 | 0 | 0 | 3379.579 | 23337.54 | 39542 | 55845.45 |
| 2 | 2 | 3482.51 | 0 | 0 | 3379.579 | 23337.54 | 39542 | 41058.05 |
| 3 | 3 | 3812.39 | 0 | 0 | 3379.579 | 23337.54 | 39542 | 45916.78 |
| 4 | 4 | 3257.56 | 1 | 0 | 3379.579 | 23337.54 | 39542 | 37744.81 |
| 5 | 5 | 5436.91 | 0 | 0 | 3379.579 | 23337.54 | 39542 | 69843.97 |

```
> Columns(GSMList(gse)[[1]])[1:5, ]
```

| | Column | Description |
|---|------------|----------------|
| 1 | ID_REF | |
| 2 | SIGNAL_RAW | raw signal |
| 3 | BKD_FORM | |
| 4 | NORM_FORM | |
| 5 | BKD_RAW | raw background |

We will indeed use the “VALUE” column. We then want to make a matrix of these values like so:

```

> probesets <- Table(GPLList(gse)[[1]])$ID
> data.matrix <- do.call("cbind", lapply(GSMList(gse), function(x) {
+   tab <- Table(x)
+   mymatch <- match(probesets, tab$ID_REF)
+   return(tab$VALUE[mymatch])
+ }))
> data.matrix <- apply(data.matrix, 2, function(x) {
+   as.numeric(as.character(x))
+ })
> data.matrix <- log2(data.matrix)
> data.matrix[1:5, ]

```

| | GSM10 | GSM3 | GSM4 | GSM5 | GSM6 | GSM7 | GSM8 | GSM9 |
|------|----------|----------|----------|----------|----------|----------|----------|----------|
| [1,] | 15.76915 | 16.22921 | 16.13000 | 15.65034 | 17.09214 | 15.45853 | 16.09474 | 15.23515 |
| [2,] | 15.32538 | 15.26597 | NaN | 15.20406 | 16.47596 | 14.85776 | 15.14885 | 14.89007 |
| [3,] | 15.48673 | 15.80932 | 14.16259 | 15.18048 | 16.21235 | 15.06094 | 15.38242 | 14.96986 |
| [4,] | 15.20399 | 15.50663 | 13.41582 | 15.05939 | 16.18593 | 14.79861 | 14.80460 | 15.01923 |
| [5,] | 16.09185 | 17.82246 | 18.38270 | 16.24570 | 16.60964 | 15.90011 | 16.00962 | 15.88859 |

Note that we do a “match” to make sure that the values and the platform information are in the same order. Finally, to make the *ExpressionSet* object:

```

> require(Biobase)
> rownames(data.matrix) <- probesets
> colnames(data.matrix) <- names(GSMList(gse))
> pdata <- data.frame(samples = names(GSMList(gse)))
> rownames(pdata) <- names(GSMList(gse))
> pheno <- as(pdata, "AnnotatedDataFrame")
> eset2 <- new("ExpressionSet", exprs = data.matrix, phenoData = pheno)
> eset2

```

```

ExpressionSet (storageMode: lockedEnvironment)
assayData: 3455 features, 8 samples
  element names: exprs
phenoData
  sampleNames: GSM10, GSM3, ..., GSM9 (8 total)
  varLabels and varMetadata description:
    samples: NA
featureData
  featureNames: 1, 2, ..., 3455 (3455 total)
  fvarLabels and fvarMetadata description: none
experimentData: use 'experimentData(object)'
Annotation:

```

So, using a combination of `lapply` on the `GSMList`, one can extract as many columns of interest as necessary to build the data structure of choice. Because the GSM data from the GEO website are fully downloaded and included in the `GSE` object, one can extract foreground and background as well as quality for two-channel arrays, for example. Getting array annotation is also a bit more complicated, but by replacing “platform” in the `lapply` call to get platform information for each array, one can get other information associated with each array. Future work with this package will likely focus on better tools for manipulating `GSE` data.

5 Accessing Raw Data from GEO

NCBI GEO accepts (but has not always required) raw data such as .CEL files, .CDF files, images, etc. Sometimes, it is useful to get quick access to such data. A single function, `getGEOSuppFiles`, can take as an argument a GEO accession and will download all the raw data associate with that accession. By default, the function will create a directory in the current working directory to store the raw data for the chosen GEO accession. Combining a simple `sapply` statement or other loop structure with `getGEOSuppFiles` makes for a very simple way to get gobs of raw data quickly and easily without needing to know the specifics of GEO raw data URLs.

6 Conclusion

The `GEOquery` package provides a bridge to the vast array resources contained in the NCBI GEO repositories. By maintaining the full richness of the GEO data rather than focusing on getting only the “numbers”, it is possible to integrate GEO data into current Bioconductor data structures and to perform analyses on that data quite quickly and easily. These tools will hopefully open GEO data more fully to the array community at large.

7 sessionInfo

- R version 2.8.0 (2008-10-20), x86_64-unknown-linux-gnu
- Locale: LC_CTYPE=en_US;LC_NUMERIC=C;LC_TIME=en_US;LC_COLLATE=en_US;LC_MONETARY=C;LC_M
- Base packages: base, datasets, graphics, grDevices, methods, stats, tools, utils
- Other packages: Biobase 2.2.0, GEOquery 2.6.0, limma 2.16.0, RCurl 0.91-0