

# BSgenome.Hsapiens.UCSC.hg17

October 17, 2011

---

Hsapiens

*Homo sapiens (Human) full genome (UCSC version hg17)*

---

## Description

Homo sapiens (Human) full genome as provided by UCSC (hg17, May 2004) and stored in Biostrings objects.

## Note

This BSgenome data package was made from the following source data files:

sequences: chromFa.zip, upstream1000.zip, upstream2000.zip, upstream5000.zip  
from <http://hgdownload.cse.ucsc.edu/goldenPath/hg17/bigZips/>  
AGAPS masks: all the chr\*\_gap.txt.gz files from <ftp://hgdownload.cse.ucsc.edu/goldenPath/hg17/bigZips/>  
RM masks: <http://hgdownload.cse.ucsc.edu/goldenPath/hg17/bigZips/chromOut.zip>  
TRF masks: <http://hgdownload.cse.ucsc.edu/goldenPath/hg17/bigZips/chromTrf.zip>

See [?BSgenomeForge](#) and the BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the BSgenome software package for how to make a BSgenome data package.

## Author(s)

H. Pages

## See Also

[BSgenome-class](#), [DNAString-class](#), [available.genomes](#), [BSgenomeForge](#)

## Examples

```
Hsapiens
seqlengths(Hsapiens)
Hsapiens$chr1 # same as Hsapiens[["chr1"]]

if ("AGAPS" %in% masknames(Hsapiens)) {

  ## Check that the assembly gaps contain only Ns:
  checkOnlyNsInGaps <- function(seq)
```

```
{
  ## Replace all masks by the inverted AGAPS mask
  masks(seq) <- gaps(masks(seq)["AGAPS"])
  unique_letters <- uniqueLetters(seq)
  if (any(unique_letters != "N"))
    stop("assembly gaps contain more than just Ns")
}

## A message will be printed each time a sequence is removed
## from the cache:
options(verbose=TRUE)

for (seqname in seqnames(Hsapiens)) {
  cat("Checking sequence", seqname, "... ")
  seq <- Hsapiens[[seqname]]
  checkOnlyNsInGaps(seq)
  cat("OK\n")
}

## See the GenomeSearching vignette in the BSgenome software
## package for some examples of genome-wide motif searching using
## Biostrings and the BSgenome data packages:
if (interactive())
  vignette("GenomeSearching", package="BSgenome")
```

# Index

## \*Topic **data**

Hsapiens, [1](#)

## \*Topic **package**

Hsapiens, [1](#)

available.genomes, [1](#)

BSgenome-class, [1](#)

BSgenome.Hsapiens.UCSC.hg17  
(*Hsapiens*), [1](#)

BSgenome.Hsapiens.UCSC.hg17-package  
(*Hsapiens*), [1](#)

BSgenomeForge, [1](#)

DNASTring-class, [1](#)

Hsapiens, [1](#)