

# MLP

October 25, 2011

---

MLP

*This function calculates p-values for each gene set based on row*

---

## Description

This function calculates p-values for each gene set based on row permutations of the gene p values or column permutations of the expression matrix; the p values can be obtained either as individual gene set p values or p values based on smoothing across gene sets of similar size.

## Usage

```
MLP(geneSet, geneStatistic, minGenes=5, maxGenes=100, rowPermutations=TRUE,
    nPermutations=100, smoothPValues=TRUE, probabilityVector=c(0.5,
    0.9, 0.95, 0.99, 0.999, 0.9999, 0.99999), df=9,
    addGeneSetDescription=TRUE)
```

## Arguments

`geneSet` is the input list of gene sets (components) and gene IDs (character vectors). A gene set can, for example, be a GO category with for each category Entrez Gene identifiers; The [getGeneSets](#) function can be used to construct the `geneSet` argument for different pathway sources.

`geneStatistic` is either a named numeric vector (if `rowPermutations` is TRUE) or a numeric matrix of pvalues (if `rowPermutations` is FALSE). The names of the numeric vector or row names of the matrix should represent the gene IDs.

`minGenes` minimum number of genes in a gene set for it to be considered (lower threshold for gene set size)

`maxGenes` maximum number of genes in a gene set for it to be considered (upper threshold for gene set size)

`rowPermutations` logical indicating whether to use row permutations (TRUE; default) or column permutations (FALSE)

`nPermutations` is the number of simulations. By default 100 permutations are conducted.

`smoothPValues` logical indicating whether one wants to calculate smoothed cut-off thresholds (TRUE; default) or not (FALSE).

probabilityVector  
vector of quantiles at which p values for each gene set are desired

df  
degrees of freedom for the smooth.spline function used in getSmoothedPValues

addGeneSetDescription  
logical indicating whether a column with the gene set description be added to the output data frame; defaults to TRUE.

### Value

data frame with four (or five) columns: totalGeneSetSize, testedGeneSetSize, geneSetStatistic and geneSetPValue and (if addDescription is set to TRUE) geneSetDescription; the rows of the data frame are ordered by ascending geneSetPValue.

### References

Raghavan, Nandini et al. (2007). The high-level similarity of some disparate gene expression measures, *Bioinformatics*, 23, 22, 3032-3038.

### Examples

```
if (require(GO.db)){
  pathExampleGeneSet <- system.file("exampleFiles", "exampleGeneSet.rda", package = "MLP")
  pathExamplePValues <- system.file("exampleFiles", "examplePValues.rda", package = "MLP")
  load(pathExampleGeneSet)
  load(pathExamplePValues)
  head(examplePValues)
  head(exampleGeneSet)
  mlpResult <- MLP(geneSet = exampleGeneSet, geneStatistic = examplePValues)
  head(mlpResult)
}
```

---

getGeneSets

*Prepare Pathway Data for the MLP Function...*

---

### Description

Prepare Pathway Data for the MLP Function

### Usage

```
getGeneSets(species="Mouse", geneSetSource, entrezIdentifiers)
```

### Arguments

species  
character vector of length one indicating the species, one of 'Mouse', 'Human' or 'Rat'; defaults to 'Mouse'.

geneSetSource  
source to be used to construct the list of pathway categories; for public data sources, the user can specify a string (one of 'GOBP', 'GOMF', 'GOCC', 'KEGG' or 'REACTOME') and BioC packages will be used to construct the list of pathway categories; for non-public data sources, the user can pass the pathway data as a dataframe with (at least) the following four columns: PATHWAYID, TAXID, PATHWAYNAME and GENEID. It is assumed all columns are of type character.

```
entrezIdentifiers
```

Entrez Gene identifiers used to subset the relevant gene set

### Details

The return value of the `getGeneSets` function has as primary use to serve as `geneSet` argument for the MLP function

### Value

object of class `geneSetMLP` which is essentially a named list of pathway categories. Each list component contains a vector of Entrez Gene identifiers related to that particular pathway

### Examples

```
if (require(GO.db) && require(org.Mm.eg.db)) {
  pathExampleData <- system.file("exampleFiles", "expressionSetGcrma.rda", package = "MLP")
  pathExamplePValues <- system.file("exampleFiles", "examplePValues.rda", package = "MLP")
  load(pathExampleData)
  load(pathExamplePValues)
  geneSet <- getGeneSets(species = "Mouse", geneSetSource = "GOBP", entrezIdentifiers = name)
  head(geneSet)
}
```

---

mlpBarplot

*Draw a Barplot for MLP Results...*


---

### Description

Draw a Barplot for MLP Results

### Usage

```
mlpBarplot(object, nRow=20, barColors, main)
```

### Arguments

<code>object</code>	object of class MLP
<code>nRow</code>	number of rows of the MLP data frame to depict in the barplot; defaults to 20.
<code>barColors</code>	vector of colors to use for the bars of the barplot; defaults to NULL; if NULL, three gray shades are used reflecting the proportion of tested genes of a gene set versus the total number of genes in a geneset. If the proportion exceeds 75%, the darkest shade is used; between 50 and 75% a moderately dark shade is used; below 50% a lighter gray shade is used.
<code>main</code>	main title; if NULL (default) "Effect of the treatment on <geneSetSource> gene sets" will be used

### Value

the midpoints of all the bars are returned invisibly (using the conventions of `barplot`); an MLP-specific barplot is drawn to the current device;

**See Also**

barplot

**Examples**

```
pathExampleMLPResult <- system.file("exampleFiles", "exampleMLPResult.rda", package = "MLP")
load(pathExampleMLPResult)
dev.new(width = 10, height = 10)
op <- par(mar = c(30, 10, 6, 2))
mlpBarplot(exampleMLPResult)
par(op)
```

---

plot.MLP

*Plot the Results of an MLP Run...*

---

**Description**

Plot the Results of an MLP Run

**Usage**

```
plot.MLP(x, y, type=c("barplot", "GOgraph", "quantileCurves"), ...)
```

**Arguments**

x	object of class 'MLP'
y	argument added to comply with generic; not used, defaults to NULL
type	character of length one; one of 'barplot', 'GOgraph' or 'quantileCurves'
...	further arguments for the plot functions for each type

**Value**

for type = "barplot", the midpoints of the barplot

**Examples**

```
pathExampleMLPResult <- system.file("exampleFiles", "exampleMLPResult.rda", package = "MLP")
load(pathExampleMLPResult)
dev.new(width = 10, height = 10)
op <- par(mar = c(30, 10, 6, 2))
plot(exampleMLPResult, type = "barplot")
par(op)
plot(exampleMLPResult, type = "quantileCurves")
if (require(GO.db) && require(Rgraphviz)){
plot(exampleMLPResult, type = "GOgraph")
}
```

---

plotGOgraph

*Graphical Representation of GO Based MLP Results...*


---

**Description**

Graphical Representation of GO Based MLP Results

**Usage**

```
plotGOgraph(object, nRow=5, main)
```

**Arguments**

object	object of class MLP (as produced by the MLP function)
nRow	number of GO IDs for which to produce the plot
main	main title of the graph; if NULL (default) the main title is set to 'GO graph'

**Value**

GO graph is plotted to the current device

**Examples**

```
if (require(GO.db) && require(Rgraphviz)){
  pathExampleMLPResult <- system.file("exampleFiles", "exampleMLPResult.rda", package = "MLP")
  load(pathExampleMLPResult)
  plotGOgraph(exampleMLPResult, main = "GO Graph")
}
```

---

plotGeneSetSignificance

*Plot the Significance for the Genes of a Given Gene Set...*


---

**Description**

Plot the Significance for the Genes of a Given Gene Set

**Usage**

```
plotGeneSetSignificance(geneSet, geneSetIdentifier, geneStatistic, annotationPac...
```

**Arguments**

geneSet	object of class 'geneSetMLP' as produced by function getGeneSets
geneSetIdentifier	identifier of the gene set for which a significance plot should be produced; character of length one
geneStatistic	named vector of gene statistics (e.g. p values); the names of the vector are Entrez Gene identifiers

`annotationPackage` name of the annotation package to be used (without .db extension); character of length one

`barColors` named vector of colors to use for the bars of the barplot; the names of the vector are Entrez Gene identifiers and the vector should be of length equal to the length of the `geneStatistic` vector defaults to NULL in which case 'grey50' is used

**Value**

no return value

**Examples**

```
pathExamplePValues <- system.file("exampleFiles", "examplePValues.rda", package = "MLP")
pathExampleGeneSet <- system.file("exampleFiles", "exampleGeneSet.rda", package = "MLP")
pathExampleMLPResult <- system.file("exampleFiles", "exampleMLPResult.rda", package = "MLP")
load(pathExampleGeneSet)
load(pathExamplePValues)
load(pathExampleMLPResult)
annotationPackage <- if (require(mouse4302mmentrezg.db)) "mouse4302mmentrezg" else "mouse4302mmentrezg"
geneSetID <- rownames(exampleMLPResult)[1]
dev.new(width = 10, height = 10)
op <- par(mar = c(25, 10, 6, 2))
plotGeneSetSignificance(
  geneSet = exampleGeneSet,
  geneSetIdentifier = geneSetID,
  geneStatistic = examplePValues,
  annotationPackage = annotationPackage
)
par(op)
```

# Index

`getGeneSets`, 1, 2

MLP, 1

`mlpBarplot`, 3

`plot.MLP`, 4

`plotGeneSetSignificance`, 5

`plotGOgraph`, 5