

Package ‘GeoDiff’

October 17, 2024

Type Package

Title Count model based differential expression and normalization on
GeoMx RNA data

Version 1.10.0

Description A series of statistical models using count generating distributions
for background modelling, feature and sample QC, normalization and differential
expression analysis on GeoMx RNA data. The application of these methods are
demonstrated by example data analysis vignette.

Imports Matrix, robust, plyr, lme4, Rcpp (>= 1.0.4.6), withr, methods,
graphics, stats, testthat, GeomxTools, NanoStringNCTools

LinkingTo Rcpp, RcppArmadillo, roptim

License MIT + file LICENSE

URL <https://github.com/Nanostring-Biostats/GeoDiff>

BugReports <https://github.com/Nanostring-Biostats/GeoDiff>

Encoding UTF-8

Suggests knitr, rmarkdown, dplyr

VignetteBuilder knitr

Depends R (>= 4.1.0), Biobase

RoxygenNote 7.1.2

biocViews GeneExpression, DifferentialExpression, Normalization

git_url <https://git.bioconductor.org/packages/GeoDiff>

git_branch RELEASE_3_19

git_last_commit ac42d5f

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-10-16

Author Nicole Ortogero [cre],
Lei Yang [aut],
Zhi Yang [aut]

Maintainer Nicole Ortogero <nortogero@nanostring.com>

Contents

| | |
|------------------|-----------|
| aggreprobe | 2 |
| BGScoreTest | 4 |
| BGScoreTest_sp | 5 |
| coefNBth | 6 |
| contrastNBth | 7 |
| demoData | 8 |
| DENBth | 8 |
| diagPoisBG | 9 |
| fitNBth | 10 |
| fitNBthDE | 13 |
| fitNBthmDE | 17 |
| fitPoisBG | 21 |
| fitPoisBG_sp | 22 |
| fitPoisthNorm | 23 |
| fitPoisthNorm_sp | 27 |
| kidney | 29 |
| NBthDEmod2 | 30 |
| NBthmDEmod2 | 30 |
| NBthmDEmod2slope | 31 |
| QuanRange | 31 |
| Index | 33 |

| | |
|------------|---|
| aggreprobe | <i>Generate aggregated counts of probes for the same target</i> |
|------------|---|

Description

Generate Generate aggregated counts of probes for the same target, based on their score test results or correlation

Generate Generate aggregated counts of probes for the same target, based on their score test results or correlation

Usage

```
aggreprobe(object, ...)

## S4 method for signature 'NanoStringGeoMxSet'
aggreprobe(
  object,
  split,
  use = c("score", "cor", "both"),
  corcutoff = 0.85,
  ...
)
```

```
## S4 method for signature 'matrix'
aggreprobe(
  object,
  probenames,
  featurenames,
  negmod,
  use = c("score", "cor", "both"),
  corcutoff = 0.85,
  ...
)
```

Arguments

| | |
|--------------|--|
| object | matrix of probes |
| ... | additional argument list that might be used |
| split | indicator variable on whether it is for multiple slides (Yes, TRUE; No, FALSE) |
| use | the method to determine outliers including score, cor, and both |
| corcutoff | the cutoff value for correlation |
| probenames | vector of names of probe |
| featurenames | vector of names of features each probe corresponding to |
| negmod | Poisson Background model object for negative probes |

Value

- remain, the list of remaining probes of targets
- probenum, numerical vector of probe numbers of targets
- featuremat, the matrix of features
- remain, the list of remaining probes of targets
- probenum, numerical vector of probe numbers of targets
- featuremat, the matrix of features

Examples

```
data("demoData")
demoData <- aggreprobe(demoData, use = "cor")
```

 BGScoreTest

Testing for features above the background

Description

Testing for features above the background using Poisson background model as reference

Testing for features above the background using Poisson background model as reference

Usage

```
BGScoreTest(object, ...)
```

```
## S4 method for signature 'NanoStringGeoMxSet'
```

```
BGScoreTest(
  object,
  split = FALSE,
  adj = 1,
  removeoutlier = FALSE,
  useprior = FALSE
)
```

```
## S4 method for signature 'matrix'
```

```
BGScoreTest(
  object,
  BGmod,
  adj = 1,
  probenum,
  removeoutlier = FALSE,
  useprior = FALSE
)
```

Arguments

| | |
|---------------|---|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| split | indicator variable on whether it is for multiple slides (Yes, TRUE; No, FALSE) |
| adj | adjustment factor for the number of feature in each gene, default =1 i.e. each target only consists of one probe |
| removeoutlier | whether to remove outlier |
| useprior | whether to use the prior that the expression level of background follows a Beta distribution, leading to a more conservative test |
| BGmod | a list of sizefact, sizefact, and countmat |
| probenum | a vector of numbers of probes in each gene |

Value

a valid GeoMx S4 object including the following items

- pvalues - Background score test pvalues, in featureData
- scores - Background score test statistics, in featureData

if split is TRUE, a valid GeoMx S4 object including the following items

- pvalues_XX - Background score test pvalues vector, column name (denoted as XX) the same as slide names, in featureData
- scores_XX - Background score test statistics vector, column name (denoted as XX) the same as slide names, in featureData

a list of following items

- pvalues - Background score test pvalues
- scores - Background score test statistics

Examples

```
data(demoData)
demoData <- fitPoisBG(demoData, size_scale = "sum")
demoData <- aggreprobe(demoData, use = "cor")
demoData <- BGScoreTest(demoData, adj = 1, useprior = FALSE)
demoData <- fitPoisBG(demoData, size_scale = "sum", groupvar = "slide name")
demoData <- BGScoreTest(demoData, adj = 1, useprior = TRUE, split = TRUE)
```

BGScoreTest_sp

Testing for features above the background, multiple slides case

Description

Testing for features above the background using Poisson background model as reference, multiple slides case

Usage

```
BGScoreTest_sp(object, ...)

## S4 method for signature 'matrix'
BGScoreTest_sp(
  object,
  BGmod,
  adj = 1,
  probenum,
  removeoutlier = FALSE,
  useprior = FALSE
)
```

Arguments

| | |
|---------------|---|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| BGmod | fitted background model, multiple slides case |
| adj | adjustment factor for the number of probes in each feature, default =1 i.e. each target only consists of one probe |
| probenum | a vector of numbers of probes in each gene |
| removeoutlier | whether to remove outlier |
| useprior | whether to use the prior that the expression level of background follows the Beta distribution, leading to a more conservative test |

Value

a list of following items

- pvalues - Background score test pvalues matrix, columns the same as slide names
- scores_sp - Background score test statistics matrix, columns the same as slide names

coefNBth

Generate list of Wald test inference results on model coefficients

Description

Generate list of Wald test inference results including parameter estimation and p value

Usage

```
coefNBth(object, ...)
```

```
## S4 method for signature 'list'
coefNBth(object, fullpara = FALSE)
```

Arguments

| | |
|----------|---|
| object | DE model, output by fitNBthDE or fitNBthmDE |
| ... | additional argument list that might be used |
| fullpara | whether to generate results on all parameters |

Value

- estimate, coefficients estimate
- wald_stat, Wald test statistics
- p_value, p value of Wald test
- se, standard error

Examples

```
data(NBthmDEmod2)
coeff <- coefNBth(NBthmDEmod2)
```

| | |
|--------------|---|
| contrastNBth | <i>Generate list of Wald test inference results on user specified contrasts</i> |
|--------------|---|

Description

Generate list of Wald test inference results including contrast estimation and p value

Usage

```
contrastNBth(object, ...)

## S4 method for signature 'list'
contrastNBth(
  object,
  test = c("two-sided", ">", "<"),
  method = diag(1, ncol(object$X)),
  baseline = rep(0, ncol(method))
)
```

Arguments

| | |
|----------|---|
| object | DE model, output by fitNBthDE or fitNBthmDE |
| ... | additional argument list that might be used |
| test | type of statistical test, choose from c("two-sided", ">", "<") |
| method | contrasts methods, only matrix of contrast vector is allowed for now, default=diag(1,ncol(object\$X)), i.e. testing the regression coefficients |
| baseline | testing baseline, default=0. |

Value

- estimate, contrasts estimate
- wald_stat, Wald test statistics
- p_value, p value of Wald test
- se, standard error

Examples

```
data(NBthmDEmod2)
coeff <- contrastNBth(NBthmDEmod2)
```

| | |
|----------|--|
| demoData | <i>A demo dataset for GeoMx Cancer Transcriptome Atlas (CTA) panel</i> |
|----------|--|

Description

A demo dataset contains 88 ROIs and 8707 features

Usage

```
data(demoData)
```

Format

A NanoStringGeoMxSet S4 object with 8707 features and 88 samples

Examples

```
data(demoData)
```

| | |
|--------|---|
| DENBth | <i>Generate DE table using the inference list generated by coefNBth or contrastNBth</i> |
|--------|---|

Description

Generate DE table using the inference list generated by coefNBth or contrastNBth

Usage

```
DENBth(object, ...)
```

```
## S4 method for signature 'list'
```

```
DENBth(object, variable, NAto1 = TRUE, padj = TRUE, padj_method = "BH")
```

Arguments

| | |
|-------------|--|
| object | inference list from coefNBth or contrastNBth |
| ... | additional argument list that might be used |
| variable | needed to construct |
| NAto1 | whether to replace NA in pvalue by 1 |
| padj | whether to adjust p value |
| padj_method | p value adjustment method, default="BH" |

Value

DEtab, DE table

Examples

```
data(NBthmDEmod2)
coeff <- coefNBth(NBthmDEmod2)
DEtab <- DENBth(coeff, variable = "regiontubule")
```

diagPoisBG

Perform diagnosis on Poisson background model

Description

Perform diagnosis on Poisson background model

Perform diagnosis on Poisson background model

Usage

```
diagPoisBG(object, ...)
```

```
## S4 method for signature 'NanoStringGeoMxSet'
diagPoisBG(
  object,
  split = FALSE,
  padj = FALSE,
  padj_method = "BH",
  cutoff = 1e-06,
  generate_ppplot = TRUE
)
```

```
## S4 method for signature 'list'
diagPoisBG(
  object,
  padj = FALSE,
  padj_method = "BH",
  cutoff = 1e-06,
  generate_ppplot = TRUE
)
```

Arguments

| | |
|--------|--|
| object | a list of sizefact, featfact, countmat, or id (if it is for multiple slides) |
| ... | additional argument list that might be used |
| split | indicator variable on whether it is for multiple slides (Yes, TRUE; No, FALSE) |
| padj | whether to adjust p value for outlier detection, default =TRUE |

padj_method p value adjustment method, default ="BH"
 cutoff p value(or adjusted p value) cutoff to determine outliers
 generate_ppplot whether to generate ppplot, default =TRUE

Value

a valid S4 object

- lowtail - A matrix of lower tail probability, in assay slot
- uptail - A matrix of upper tail probability, in assay slot
- disper (or disper_sp if non single-valued groupvar is provided) - dispersion parameter in experimentData
- low_outlier - A matrix to indicate lower outliers (0:False, 1:True) in assay slot
- upper_outlier - A matrix to indicate upper outliers (0:False, 1:True) in assay slot

a list of following items

- lowtail - A matrix of lower tail probability
- uptail - A matrix of upper tail probability
- disper - dispersion parameter
- outlier - A list of coordinates of lower and upper outliers

Examples

```

data(demoData)
demoData <- fitPoisBG(demoData, size_scale = "sum")
demoData <- diagPoisBG(demoData)
Biobase::notes(demoData)$disper
demoData <- fitPoisBG(demoData, groupvar = "slide name")
demoData <- diagPoisBG(demoData, split = TRUE)
Biobase::notes(demoData)$disper_sp
  
```

fitNBth

Negative Binomial threshold model

Description

Estimate the signal size factor for features above the background

Estimate the signal size factor for features above the background

Usage

```
fitNBth(object, ...)

## S4 method for signature 'NanoStringGeoMxSet'
fitNBth(
  object,
  split = TRUE,
  features_high = NULL,
  sizefact_BG = NULL,
  sizefact_start = sizefact_BG,
  size_scale = c("sum", "first"),
  threshold_start = NULL,
  threshold_fix = FALSE,
  tol = 1e-07,
  iterations = 8,
  start_para = c(threshold_start, 0.5),
  lower_sizefact = 0,
  lower_threshold = threshold_start/5
)

## S4 method for signature 'matrix'
fitNBth(
  object,
  features_high,
  probenum,
  sizefact_BG,
  sizefact_start = sizefact_BG,
  size_scale = c("sum", "first"),
  threshold_start,
  threshold_fix = FALSE,
  tol = 1e-07,
  iterations = 8,
  start_para = c(threshold_start, 1),
  lower_sizefact = 0,
  lower_threshold = threshold_start/5
)
```

Arguments

| | |
|----------------|--|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| split | indicator variable on whether it is for multiple slides (Yes, TRUE; No, FALSE) |
| features_high | subset of features which are well above the background |
| sizefact_BG | size factors for the background |
| sizefact_start | initial value for size factors |
| size_scale | method to scale the sizefact, sum(sizefact)=1 when size_scale="sum", sizefact[1]=1 when size_scale="first" |

| | |
|-----------------|---|
| threshold_start | initial value for threshold |
| threshold_fix | whether to fix the threshold, default=FALSE |
| tol | tolerance to determine convergence, default=1e-3 |
| iterations | maximum iterations to be run, default=5 |
| start_para | starting values for parameter estimation, default=c(threshold_start, 1) |
| lower_sizefact | lower limit for sizefact, default=0 |
| lower_threshold | lower limit for threshold |
| probenum | a vector of numbers of probes in each gene |

Value

a valid GeoMx S4 object

- para0 = "NA", in experimentData
- para, estimated parameters, "signal" "r" in rows and features in columns, in featureData
- sizefact, estimated size factor, in phenoData
- preci1 = "NA", in experimentData
- conv0 = "NA", in experimentData
- conv = "NA", in experimentData
- Im = "NA", in experimentData
- features_high, a vector of indicators, in featureData (0: No; 1: Yes; NA: not included in features_high)
- features_all = "NA", in experimentData
- threshold, estimated threshold, when threshold_fix, equals to threshold_start, in experimentData

a list of following items, some items are place holders = NA

- para0 = NA,
- para, estimated parameters, "signal" "r" in rows and features in columns
- sizefact, estimated size factor
- preci1 = NA
- conv0 = NA
- conv = NA
- Im = NA
- features_high = features_high
- features_all = NA
- threshold, estimated threshold, when threshold_fix, equals to threshold_start

Examples

```

library(Biobase)
library(dplyr)
data(demoData)
demoData <- fitPoisBG(demoData, size_scale = "sum")
demoData <- aggprobe(demoData, use = "cor")
demoData <- BGScoreTest(demoData)
thmean <- 1 * mean(fData(demoData)$featfact, na.rm = TRUE)
demo_pos <- demoData[which(!fData(demoData)$CodeClass == "Negative"), ]
demo_neg <- demoData[which(fData(demoData)$CodeClass == "Negative"), ]
sc1_scores <- fData(demo_pos)[, "scores"]
names(sc1_scores) <- fData(demo_pos)[, "TargetName"]
features_high <- ((sc1_scores > quantile(sc1_scores, probs = 0.4)) &
  (sc1_scores < quantile(sc1_scores, probs = 0.95))) |>
  which() |>
  names()
set.seed(123)
features_high <- sample(features_high, 100)
demoData <- fitNBth(demoData,
  features_high = features_high,
  sizefact_BG = demo_neg$sizefact,
  threshold_start = thmean,
  iterations = 5,
  start_para = c(200, 1),
  lower_sizefact = 0,
  lower_threshold = 100,
  tol = 1e-8)

```

fitNBthDE

Negative Binomial threshold model for differential expression analysis

Description

Negative Binomial threshold model for differential expression analysis

Negative Binomial threshold model for differential expression analysis

Usage

```

fitNBthDE(object, ...)

## S4 method for signature 'NanoStringGeoMxSet'
fitNBthDE(
  object,
  form,
  split,
  ROIs_high = NULL,
  features_high = NULL,

```

```

features_all = NULL,
sizefact_start = NULL,
sizefact_BG = NULL,
threshold_mean = NULL,
preci2 = 10000,
lower_threshold = 0.01,
prior_type = c("contrast", "equal"),
sizefactrec = TRUE,
size_scale = c("sum", "first"),
scalescalebythreshold = FALSE,
iterations = 2,
covrob = FALSE,
prec1con = 1/25,
cutoff = 10,
confac = 1
)

## S4 method for signature 'matrix'
fitNBthDE(
  form,
  annot,
  object,
  probenum,
  features_high,
  features_all,
  sizefact_start,
  sizefact_BG,
  threshold_mean,
  preci2 = 10000,
  lower_threshold = 0.01,
  prior_type = c("contrast", "equal"),
  sizefactrec = TRUE,
  size_scale = c("sum", "first"),
  scalescalebythreshold = FALSE,
  iterations = 2,
  covrob = FALSE,
  prec1con = 1/25,
  cutoff = 10,
  confac = 1
)

```

Arguments

| | |
|-----------|--|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| form | model formula |
| split | indicator variable on whether it is for multiple slides (Yes, TRUE; No, FALSE) |
| ROIs_high | ROIs with high expressions defined based on featfact and featfact |

| | |
|----------------------|---|
| features_high | subset of features which are well above the background |
| features_all | full list of features |
| sizefact_start | initial value for size factors |
| sizefact_BG | size factor for background |
| threshold_mean | average threshold level |
| preci2 | precision for the background, default=10000 |
| lower_threshold | lower limit for the threshold, default=0.01 |
| prior_type | empirical bayes prior type, choose from c("contrast", "equal") |
| sizefactrec | whether to recalculate sizefact, default=TRUE |
| size_scale | method to scale the sizefact, sum(sizefact)=1 when size_scale="sum", sizefact[1]=1 when size_scale="first" |
| sizescalebythreshold | XXXX, default = FALSE |
| iterations | how many iterations need to run to get final results, default=2, the first iteration apply the model only on features_high and construct the prior then refit the model using this prior for all genes. |
| covrob | whether to use robust covariance in calculating covariance. default=FALSE |
| preci1con | The user input constant term in specifying precision matrix 1, default=1/25 |
| cutoff | term in calculating precision matrix 1, default=10 |
| confac | The user input factor for contrast in precision matrix 1, default=1 |
| annot | annotations files with variables in the formula |
| probenum | a vector of numbers of probes in each gene, default = rep(1, NROW(object)) |

Value

a list of

- X, design matrix
- para0, estimated parameters for the first iteration, including regression coefficients, r and threshold in rows and features in columns
- para, estimated parameters, including regression coefficients, r and threshold in rows and features in columns
- sizefact, estimated sizefact
- sizefact0, estimated sizefact in iter=1
- preci1, precision matrix for regression coefficients estimated in iter=1
- Im0, Information matrix of parameters in iter=1
- Im, Information matrix of parameters in iter=2
- conv0, vector of convergence for iter=1, 0 converged, 1 not converged
- conv, vector of convergence for iter=2, 0 converged, 1 not converged
- features_high, same as the input features_high

- features_all, same as the input features_all

a list of

- X, design matrix
- para0, estimated parameters for the first iteration, including regression coefficients, r and threshold in rows and features in columns
- para, estimated parameters, including regression coefficients, r and threshold in rows and features in columns
- sizefact, estimated sizefact
- sizefact0, estimated sizefact in iter=1
- preci1, precision matrix for regression coefficients estimated in iter=1
- Im0, Information matrix of parameters in iter=1
- Im, Information matrix of parameters in iter=2
- conv0, vector of convergence for iter=1, 0 converged, 1 not converged
- conv, vector of convergence for iter=2, 0 converged, 1 not converged
- features_high, same as the input features_high
- features_all, same as the input features_all

Examples

```
library(Biobase)
library(dplyr)
data(demoData)
demoData <- demoData[, c(1:5, 33:37)]
demoData <- fitPoisBG(demoData, size_scale = "sum")
demoData <- aggregprobe(demoData, use = "cor")
demoData <- BGScoreTest(demoData)
demoData$slidename <- substr(demoData[["slide name"]], 12, 17)
thmean <- 1 * mean(fData(demoData)$featfact, na.rm = TRUE)
demo_pos <- demoData[which(!fData(demoData)$CodeClass == "Negative"), ]
demo_neg <- demoData[which(fData(demoData)$CodeClass == "Negative"), ]
sc1_scores <- fData(demo_pos)[, "scores"]
names(sc1_scores) <- fData(demo_pos)[, "TargetName"]
features_high <- ((sc1_scores > quantile(sc1_scores, probs = 0.4)) &
  (sc1_scores < quantile(sc1_scores, probs = 0.95))) |>
  which() |>
  names()
set.seed(123)
demoData <- fitNBth(demoData,
  features_high = features_high,
  sizefact_BG = demo_neg$sizefact,
  threshold_start = thmean,
  iterations = 5,
  start_para = c(200, 1),
  lower_sizefact = 0,
  lower_threshold = 100,
  tol = 1e-8)
```



```

ROIs_high <- sampleNames(demoData)[which(demoData$sizefact_fitNBth * thmean > 2)]
features_all <- rownames(demo_pos)

pData(demoData)$group <- c(rep(1, 5), rep(2, 5))

NBthDEmod1 <- fitNBthDE(
  form = ~group,
  split = FALSE,
  object = demoData,
  ROIs_high = ROIs_high,
  features_high = features_high,
  features_all = features_all,
  sizefact_start = demoData[, ROIs_high][["sizefact_fitNBth"]],
  sizefact_BG = demoData[, ROIs_high][["sizefact"]],
  preci2 = 10000,
  prior_type = "contrast",
  covrob = FALSE,
  precilcon = 1/25,
  sizescalebythreshold = TRUE
)

```

fitNBthmDE

Negative Binomial threshold mixed model for differential expression analysis

Description

Negative Binomial threshold mixed model for differential expression analysis

Negative Binomial threshold mixed model for differential expression analysis

Usage

```
fitNBthmDE(object, ...)
```

```
## S4 method for signature 'NanoStringGeoMxSet'
```

```

fitNBthmDE(
  object,
  form,
  split,
  ROIs_high = NULL,
  features_all = NULL,
  sizefact = NULL,
  sizefact_BG = NULL,
  preci1,
  threshold_mean = NULL,
  preci2 = 10000,

```

```

    sizescalebythreshold = TRUE,
    controlRandom = list()
)

## S4 method for signature 'matrix'
fitNBthmDE(
  form,
  annot,
  object,
  probenum = rep(1, NROW(object)),
  features_all,
  sizefact,
  sizefact_BG,
  preci1,
  threshold_mean = NULL,
  preci2 = 10000,
  sizescalebythreshold = TRUE,
  controlRandom = list()
)

```

Arguments

| | |
|----------------------|--|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| form | model formula |
| split | indicator variable on whether it is for multiple slides (Yes, TRUE; No, FALSE) |
| ROIs_high | ROIs with high expressions defined based on featfact and featfact |
| features_all | vector of all features to be run |
| sizefact | size factor |
| sizefact_BG | size factor for background |
| preci1 | precision matrix for regression coefficients |
| threshold_mean | average background level |
| preci2 | precision for the background, default=10000 |
| sizescalebythreshold | whether to scale the size factor, default=TRUE |
| controlRandom | list of random effect control parameters |
| annot | annotations files with variables in the formula |
| probenum | a vector of numbers of probes in each gene, default = rep(1, NROW(object)) |

Value

a list with parameter estimation #'

- X, design matrix for fixed effect
- Z, design matrix for random effect

- rt, random effect terms
- para0, =NA
- para, estimated parameters, including regression coefficients, r and threshold in rows and features in columns
- sizefact, same as input sizefact
- sizefact0, NA
- preci1, input precision matrix for regression coefficients
- Im0, NA
- Im, Information matrix of parameters
- conv0, NA
- conv, vector of convergence, 0 converged, 1 not converged
- features_high, NA
- features_all, same as the input features_all
- theta, list of estimated random effect parameters
- MAP random effect

a list with parameter estimation #'

- X, design matrix for fixed effect
- Z, design matrix for random effect
- rt, random effect terms
- para0, =NA
- para, estimated parameters, including regression coefficients, r and threshold in rows and features in columns
- sizefact, same as input sizefact
- sizefact0, NA
- preci1, input precision matrix for regression coefficients
- Im0, NA
- Im, Information matrix of parameters
- conv0, NA
- conv, vector of convergence, 0 converged, 1 not converged
- features_high, NA
- features_all, same as the input features_all
- theta, list of estimated random effect parameters(for relative covariance matrix)
- varcov, list of estimated variance covariance parameter estimation
- MAP random effect

Examples

```

library(Biobase)
library(dplyr)
data(demoData)
demoData <- demoData[, c(1:5, 33:37)]
demoData <- fitPoisBG(demoData, size_scale = "sum")
demoData <- aggprobe(demoData, use = "cor")
demoData <- BGScoreTest(demoData)
demoData$slidename <- substr(demoData[["slide name"]], 12, 17)
thmean <- 1 * mean(fData(demoData)$featfact, na.rm = TRUE)
demo_pos <- demoData[which(!fData(demoData)$CodeClass == "Negative"), ]
demo_neg <- demoData[which(fData(demoData)$CodeClass == "Negative"), ]
sc1_scores <- fData(demo_pos)[, "scores"]
names(sc1_scores) <- fData(demo_pos)[, "TargetName"]
features_high <- ((sc1_scores > quantile(sc1_scores, probs = 0.4)) &
  (sc1_scores < quantile(sc1_scores, probs = 0.95))) |>
  which() |>
  names()
set.seed(123)
demoData <- fitNBth(demoData,
  features_high = features_high,
  sizefact_BG = demo_neg$sizefact,
  threshold_start = thmean,
  iterations = 5,
  start_para = c(200, 1),
  lower_sizefact = 0,
  lower_threshold = 100,
  tol = 1e-8)
ROIs_high <- sampleNames(demoData)[which(demoData$sizefact_fitNBth * thmean > 2)]
features_all <- rownames(demo_pos)

pData(demoData)$group <- c(rep(1, 5), rep(2, 5))

NBthDEmod2 <- fitNBthDE(form = ~group,
  split = FALSE,
  object = demoData,
  ROIs_high = ROIs_high,
  features_high = features_high,
  features_all = features_all,
  sizefact_start = demoData[, ROIs_high][['sizefact_fitNBth']],
  sizefact_BG = demoData[, ROIs_high][['sizefact']],
  threshold_mean = notes(demoData)[["threshold"]],
  preci2=10000,
  prior_type="contrast",
  covrob=FALSE,
  precilcon=1/25,
  sizescalebythreshold=TRUE)

set.seed(123)
NBthmDEmod1 <- fitNBthmDE(
  form = ~ group + (1 | `slide name`),

```

```

split = FALSE,
object = demoData,
ROIs_high = ROIs_high,
features_all = features_all[1:5],
sizefact = demoData[, ROIs_high][["sizefact_fitNBth"]],
sizefact_BG = demoData[, ROIs_high][["sizefact"]],
preci1=NBthDEmod2$preci1,
threshold_mean = thmean,
preci2=10000,
scalescale = TRUE,
controlRandom=list(nu=12, nmh_e=400, thin_e=60)

```

fitPoisBG

Estimate Poisson background model for either single slide or multiple slides

Description

Estimate Poisson background model for either single slide or multiple slides

Estimate Poisson background model:

Usage

```
fitPoisBG(object, ...)
```

```
## S4 method for signature 'NanoStringGeoMxSet'
```

```
fitPoisBG(
  object,
  groupvar = NULL,
  iterations = 10,
  tol = 0.001,
  size_scale = c("sum", "first"),
  ...
)
```

```
## S4 method for signature 'matrix'
```

```
fitPoisBG(object, iterations = 10, tol = 0.001, size_scale = c("sum", "first"))
```

Arguments

| | |
|------------|--|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| groupvar | the group variable name for slide |
| iterations | maximum iterations to be run, default=10 |
| tol | tolerance to determine convergence, default = 1e-3 |
| size_scale | method to scale the sizefact, sum(sizefact)=1 when size_scale="sum", sizefact[1]=1 when size_scale="first" |

Value

a valid GeoMx S4 object if split is FALSE

- sizefact - estimated size factor in phenoData
- featfact - estimated feature factor in featureData

a valid GeoMx S4 object if split is TRUE,

- sizefact - estimated size factor in phenoData
- featfact_XX - estimated feature factor vector, column name (denoted as XX) the same as the slide id, in featureData for each unique slide
- fitPoisBG_sp_var - the column name for slide, in experimentData

a list of following items

- sizefact - estimated size factor
- featfact - estimated feature factor
- countmat - the input count matrix

Examples

```
data(demoData)
demoData <- fitPoisBG(demoData, size_scale = "sum")
data(demoData)
demoData <- fitPoisBG(demoData, groupvar = "slide name", size_scale = "sum")
```

fitPoisBG_sp

Estimate Poisson background model for multiple slides

Description

Estimate Poisson background model for multiple slides:

Usage

```
fitPoisBG_sp(object, ...)

## S4 method for signature 'matrix'
fitPoisBG_sp(
  object,
  id,
  iterations = 10,
  tol = 0.001,
  size_scale = c("sum", "first")
)
```

Arguments

| | |
|------------|--|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| id | character vector same size as sample size representing slide names of each sample |
| iterations | maximum iterations to be run, default=10 |
| tol | tolerance to determine convergence, default = 1e-3 |
| size_scale | method to scale the sizefact, sum(sizefact)=1 when size_scale="sum", sizefact[1]=1 when size_scale="first" |

Value

a list of following items

- sizefact - estimated size factor
- featfact - estimated feature factor matrix, column names the same as the slide id
- countmat - the input count matrix
- id - the input id

| | |
|---------------|--|
| fitPoisthNorm | <i>Poisson threshold model based normalization-log2 transformation for single slide or for multiple slides</i> |
|---------------|--|

Description

Poisson threshold model based normalization-log2 transformation for single slide or for multiple slides

Usage

```
fitPoisthNorm(object, ...)

## S4 method for signature 'NanoStringGeoMxSet'
fitPoisthNorm(
  object,
  split = FALSE,
  ROIs_high = NULL,
  features_high = NULL,
  features_all = NULL,
  sizefact_start = NULL,
  sizefact_BG = NULL,
  threshold_mean = NULL,
  preci2 = 10000,
  iterations = 2,
```

```

prior_type = c("contrast", "equal"),
sizefactrec = TRUE,
size_scale = c("sum", "first"),
scalescalebythreshold = FALSE,
covrob = FALSE,
precilcon = 1/25,
cutoff = 15,
confac = 1,
calhes = FALSE
)

## S4 method for signature 'matrix'
fitPoisthNorm(
  object,
  probenum = rep(1, NROW(object)),
  features_high,
  features_all,
  sizefact_start,
  sizefact_BG,
  threshold_mean,
  preci2 = 10000,
  iterations = 2,
  prior_type = c("contrast", "equal"),
  sizefactrec = TRUE,
  size_scale = c("sum", "first"),
  scalescalebythreshold = FALSE,
  covrob = FALSE,
  precilcon = 1/25,
  cutoff = 15,
  confac = 1,
  calhes = FALSE
)

```

Arguments

| | |
|----------------|--|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| split | indicator variable on whether it is for multiple slides (Yes, TRUE; No, FALSE) |
| ROIs_high | ROIs with high expressions defined based on featfact and featfact |
| features_high | subset of features which are well above the background |
| features_all | full feature vector to apply the normalization on |
| sizefact_start | initial value for size factors |
| sizefact_BG | size factor for background |
| threshold_mean | average threshold level |
| preci2 | precision for threshold, default=10000 |

| | |
|----------------------|---|
| iterations | iteration number, default=2, the first iteration using the features_high to construct the prior for parameters then refit the model on all features. precision matrix for threshold: preci2 |
| prior_type | prior type for preci1, "equal" or "contrast", default="contrast" |
| sizefactrec | XXXX, default = TRUE |
| size_scale | method to scale the sizefact, sum(sizefact)=1 when size_scale="sum", sizefact[1]=1 when size_scale="first" |
| sizescalebythreshold | XXXX, default = FALSE |
| covrob | whether to use robust covariance in calculating the prior precision matrix 1, default = FALSE |
| preci1con | The user input constant term in specifying precision matrix 1, default=1/25 |
| cutoff | term in calculating precision matrix 1, default=15 |
| confac | The user input factor for contrast in precision matrix 1, default=1 |
| calhes | The user input whether to calculate hessian: calhes, default=FALSE |
| probenum | a vector of numbers of probes in each gene |

Value

if split is FALSE, a valid GeoMx S4 object including the following items

- para0_norm, matrix of estimated parameters for iter=1, features in columns and parameters(log2 expression, threshold) in rows, in featureData.
- para_norm, matrix of estimated parameters for iter=2, features in columns and parameters(log2 expression, threshold) in rows, in featureData.
- normmat0, matrix of log2 expression for iter=1, features in columns and log2 expression in rows, in assay slot.
- normmat, matrix of log2 expression for iter=2, features in columns and log2 expression in rows, in assay lot.
- sizefact_norm, estimated sizefact, in phenoData.
- sizefact0_norm, estimated sizefact in iter=1, in phenoData.
- preci1, precision matrix 1, in experimentData.
- conv0, vector of convergence for iter=1, 0 converged, 1 not converged, in featureData
- conv, vector of convergence for iter=2, 0 converged, 1 not converged, in featureData
- features_high, same as the input features_high, in featureData
- features_all, same as the input features_all, in featureData

if split is TRUE, a valid GeoMx S4 object with the following items appended.

- threshold0, matrix of estimated threshold for iter=1, features in columns and threshold for different slides in rows, in featureData.
- threshold, matrix of estimated threshold for iter=2, features in columns and threshold for different slides in rows, in featureData.

- normmat0_sp, matrix of log2 expression for iter=1, features in columns and log2 expression in rows, in assay slot.
- normmat_sp, matrix of log2 expression for iter=2, features in columns and log2 expression in rows, in assay slot.
- sizefact_norm_sp, estimated sizefact, in phenoData
- sizefact0_norm_sp, estimated sizefact in iter=1, in phenoData
- preci1, precision matrix 1, in experimentData
- conv0_sp_XX, vector of convergence for each unique slide value for iter=1, 0 converged, 1 not converged, in featureData for each unique slide.
- conv_sp_XX, vector of convergence for each unique slide value for iter=2, 0 converged, 1 not converged, in featureData for each unique slide.
- features_high_sp, same as the input features_high, in featureData.
- features_all_sp, same as the input features_all, in featureData.

a list of following items

- para0, matrix of estimated parameters for iter=1, features in columns and parameters(log2 expression, threshold) in rows.
- para, matrix of estimated parameters for iter=2, features in columns and parameters(log2 expression, threshold) in rows.
- normmat0, matrix of log2 expression for iter=1, features in columns and log2 expression in rows.
- normmat, matrix of log2 expression for iter=2, features in columns and log2 expression in rows.
- sizefact, estimated sizefact
- sizefact0, estimated sizefact in iter=1
- preci1, precision matrix 1
- Im0, Information matrix of parameters in iter=1
- Im, Information matrix of parameters in iter=2
- conv0, vector of convergence for iter=1, 0 converged, 1 not converged
- conv, vector of convergence for iter=2, 0 converged, 1 not converged
- features_high, same as the input features_high
- features_all, same as the input features_all

Examples

```
library(Biobase)
library(dplyr)
data(demoData)
demoData <- fitPoisBG(demoData, size_scale = "sum")
demoData <- aggregprobe(demoData, use = "cor")
demoData <- BGScoreTest(demoData)
thmean <- 1 * mean(fData(demoData)$featfact, na.rm = TRUE)
demo_pos <- demoData[which(!fData(demoData)$CodeClass == "Negative"), ]
```

```

demo_neg <- demoData[which(fData(demoData)$CodeClass == "Negative"), ]
sc1_scores <- fData(demo_pos)[, "scores"]
names(sc1_scores) <- fData(demo_pos)[, "TargetName"]
features_high <- ((sc1_scores > quantile(sc1_scores, probs = 0.4)) &
  (sc1_scores < quantile(sc1_scores, probs = 0.95))) |>
  which() |>
  names()
set.seed(123)
features_high <- sample(features_high, 100)
demoData <- fitNBth(demoData,
  features_high = features_high,
  sizefact_BG = demo_neg$sizefact,
  threshold_start = thmean,
  iterations = 5,
  start_para = c(200, 1),
  lower_sizefact = 0,
  lower_threshold = 100,
  tol = 1e-8)
ROIs_high <- sampleNames(demoData)[which((quantile(fData(demoData)[["para"]][, 1],
  probs = 0.90, na.rm = TRUE) -
  notes(demoData)[["threshold"]]) * demoData$sizefact_fitNBth > 2)]
features_all <- rownames(demo_pos)
thmean <- mean(fData(demo_neg)[["featfact"]])
demoData <- fitPoisthNorm(
  object = demoData,
  split = FALSE,
  ROIs_high = ROIs_high,
  features_high = features_high,
  features_all = features_all,
  sizefact_start = demoData[, ROIs_high][["sizefact_fitNBth"]],
  sizefact_BG = demoData[, ROIs_high][["sizefact"]],
  threshold_mean = thmean,
  preci2 = 10000,
  prior_type = "contrast",
  covrob = FALSE,
  precilcon = 1 / 25
)

```

fitPoisthNorm_sp

Poisson threshold model based normalization-log2 transformation for multiple slides

Description

Poisson threshold model based normalization-log2 transformation for multiple slides

Usage

```
fitPoisthNorm_sp(object, ...)
```

```

## S4 method for signature 'matrix'
fitPoisthNorm_sp(
  object,
  probenum,
  features_high,
  features_all = colnames(object),
  sizefact_start,
  sizefact_BG,
  threshold_mean,
  preci2 = 10000,
  id,
  iterations = 2,
  prior_type = c("contrast", "equal"),
  sizefactrec = TRUE,
  size_scale = c("sum", "first"),
  sizescalebythreshold = FALSE,
  covrob = FALSE,
  preci1con = 1/25,
  cutoff = 15,
  confac = 1
)

```

Arguments

| | |
|----------------------|---|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| probenum | a vector of numbers of probes in each gene |
| features_high | subset of features which are well above the background |
| features_all | full feature vector to apply the normalization on |
| sizefact_start | initial value for size factors |
| sizefact_BG | size factor for background |
| threshold_mean | average threshold level |
| preci2 | precision for threshold, default=10000 |
| id | character vector of slide name of each sample |
| iterations | iteration number, default=2, the first iteration using the features_high to construct the prior for parameters then refit the model on all features. precision matrix for threshold: preci2 |
| prior_type | prior type for preci1, "equal" or "contrast", default="contrast" |
| sizefactrec | XXXX, default = TRUE |
| size_scale | method to scale the sizefact, sum(sizefact)=1 when size_scale="sum", sizefact[1]=1 when size_scale="first" |
| sizescalebythreshold | XXXX, default = FALSE |

| | |
|-----------|---|
| covrob | whether to use robust covariance in calculating the prior precision matrix 1, default = FALSE |
| preci1con | The user input constant term in specifying precision matrix 1, default=1/25 |
| cutoff | term in calculating precision matrix 1, default=15 |
| confac | The user input factor for contrast in precision matrix 1, default=1 |

Value

a list of following items

- threshold0, matrix of estimated threshold for iter=1, features in columns and threshold for different slides in rows.
- threshold, matrix of estimated threshold for iter=2, features in columns and threshold for different slides in rows.
- normmat0, matrix of log2 expression for iter=1, features in columns and log2 expression in rows.
- normmat, matrix of log2 expression for iter=2, features in columns and log2 expression in rows.
- sizefact, estimated sizefact
- sizefact0, estimated sizefact in iter=1
- preci1, precision matrix 1
- Im0, Information matrix in iter=1
- Im, Information matrix in iter=2
- conv0, vector of convergence for iter=1, 0 converged, 1 not converged
- conv, vector of convergence for iter=2, 0 converged, 1 not converged
- features_high, same as the input features_high
- features_all, same as the input features_all

| | |
|--------|---|
| kidney | <i>A demo dataset for GeoMx Human Whole Transcriptome Atlas (WTA) panel</i> |
|--------|---|

Description

A demo dataset contains 276 ROIs and 18642 features

Usage

```
data(kidney)
```

Format

A NanoStringGeoMxSet S4 object with 18642 features and 276 samples

Examples

```
data(kidney)
```

NBthDEmod2

A demo example output list returned by function fitNBthDE

Description

A list used to demonstrate the function coefNBth

Usage

```
data(NBthDEmod2)
```

Format

A list

Examples

```
data(NBthDEmod2)
```

NBthmDEmod2

A demo example output list returned by function fitNBthmDE

Description

A list used to demonstrate the function coefNBth

Usage

```
data(NBthmDEmod2)
```

Format

A list

Examples

```
data(NBthmDEmod2)
```

| | |
|------------------|---|
| NBthmDEmod2slope | <i>A demo example output list returned by function fitNBthmDE</i> |
|------------------|---|

Description

A list used to demonstrate the function coefNBth

Usage

```
data(NBthmDEmod2slope)
```

Format

A list

Examples

```
data(NBthmDEmod2slope)
```

| | |
|-----------|-------------------------------|
| QuanRange | <i>Compute Quantile Range</i> |
|-----------|-------------------------------|

Description

Compute Quantile Range, a metric representing signal strength for QC purpose

Compute Quantile Range, a metric representing signal strength for QC purpose

Usage

```
QuanRange(object, ...)
```

```
## S4 method for signature 'NanoStringGeoMxSet'
```

```
QuanRange(object, split = FALSE, probs, removeoutlier = FALSE, ...)
```

```
## S4 method for signature 'matrix'
```

```
QuanRange(object, probenum, BGmod, probs, removeoutlier = FALSE)
```

Arguments

| | |
|---------------|---|
| object | count matrix with features in rows and samples in columns |
| ... | additional argument list that might be used |
| split | indicator variable on whether it is for multiple slides |
| probs | numeric vector of probabilities with values in [0,1] passed to quantile |
| removeoutlier | indicator on whether to remove outliers, default: FALSE |
| probenum | a vector of numbers of probes in each gene |
| BGmod | a list of sizefact, sizefact, countmat, and id (if it is for multiple slides) |

Value

a valid S4 object with probabilities in phenoData
a matrix of quantile range in rows and probs in columns

Examples

```
data(demoData)
demoData <- fitPoisBG(demoData, size_scale = "sum")
demoData <- diagPoisBG(demoData)
demoData <- aggprobe(demoData, use = "cor")
Biobase::notes(demoData)$disper
demoData <- QuanRange(demoData, split = FALSE, probs = c(0.75, 0.8, 0.9, 0.95))

data(demoData)
demoData <- fitPoisBG(demoData, groupvar = "slide name")
demoData <- diagPoisBG(demoData, split = TRUE)
demoData <- aggprobe(demoData, use = "cor")
Biobase::notes(demoData)$disper_sp
demoData <- QuanRange(demoData, split = TRUE, probs = c(0.75, 0.8, 0.9, 0.95))
```


Index

* datasets

- demoData, 8
- kidney, 29
- NBthDEmod2, 30
- NBthmDEmod2, 30
- NBthmDEmod2slope, 31

- aggreprobe, 2
- aggreprobe, matrix-method (aggreprobe), 2
- aggreprobe, NanoStringGeoMxSet-method (aggreprobe), 2

- BGScoreTest, 4
- BGScoreTest, matrix-method (BGScoreTest), 4
- BGScoreTest, NanoStringGeoMxSet-method (BGScoreTest), 4
- BGScoreTest_sp, 5
- BGScoreTest_sp, matrix-method (BGScoreTest_sp), 5

- coefNBth, 6
- coefNBth, list-method (coefNBth), 6
- contrastNBth, 7
- contrastNBth, list-method (contrastNBth), 7

- demoData, 8
- DENBth, 8
- DENBth, list-method (DENBth), 8
- diagPoisBG, 9
- diagPoisBG, list-method (diagPoisBG), 9
- diagPoisBG, NanoStringGeoMxSet-method (diagPoisBG), 9

- fitNBth, 10
- fitNBth, matrix-method (fitNBth), 10
- fitNBth, NanoStringGeoMxSet-method (fitNBth), 10
- fitNBthDE, 13
- fitNBthDE, matrix-method (fitNBthDE), 13

- fitNBthDE, NanoStringGeoMxSet-method (fitNBthDE), 13
- fitNBthmDE, 17
- fitNBthmDE, matrix-method (fitNBthmDE), 17
- fitNBthmDE, NanoStringGeoMxSet-method (fitNBthmDE), 17
- fitPoisBG, 21
- fitPoisBG, matrix-method (fitPoisBG), 21
- fitPoisBG, NanoStringGeoMxSet-method (fitPoisBG), 21
- fitPoisBG_sp, 22
- fitPoisBG_sp, matrix-method (fitPoisBG_sp), 22
- fitPoisthNorm, 23
- fitPoisthNorm, matrix-method (fitPoisthNorm), 23
- fitPoisthNorm, NanoStringGeoMxSet-method (fitPoisthNorm), 23
- fitPoisthNorm_sp, 27
- fitPoisthNorm_sp, matrix-method (fitPoisthNorm_sp), 27

- kidney, 29

- NBthDEmod2, 30
- NBthmDEmod2, 30
- NBthmDEmod2slope, 31

- QuanRange, 31
- QuanRange, matrix-method (QuanRange), 31
- QuanRange, NanoStringGeoMxSet-method (QuanRange), 31