

# Package ‘mia’

December 5, 2025

**Type** Package

**Version** 1.19.0

**Title** Microbiome analysis

**Description** mia implements tools for microbiome analysis based on the SummarizedExperiment, SingleCellExperiment and TreeSummarizedExperiment infrastructure. Data wrangling and analysis in the context of taxonomic data is the main scope. Additional functions for common task are implemented such as community indices calculation and summarization.

**biocViews** Microbiome, Software, DataImport

**License** Artistic-2.0 | file LICENSE

**Encoding** UTF-8

**LazyData** false

**Depends** R (>= 4.0), MultiAssayExperiment, SingleCellExperiment, SummarizedExperiment, TreeSummarizedExperiment (>= 1.99.3)

**Imports** ape, BiocGenerics, BiocParallel, Biostrings, bluster, DECIPHER, decontam, DelayedArray, DelayedMatrixStats, DirichletMultinomial, dplyr, IRanges, MASS, MatrixGenerics, methods, rbiom, rlang, S4Vectors, scater, scuttle, stats, stringr, tibble, tidyr, utils, vegan, Rcpp

**Suggests** ade4, BiocStyle, biomformat, dada2, knitr, mediation, miaViz, microbiomeDataSets, NMF, patchwork, philr, phyloseq, reldist, rhdf5, rmarkdown, testthat, topicdoc, topicmodels, yaml

**LinkingTo** Rcpp

**URL** <https://microbiome.github.io/mia/>,  
<https://github.com/microbiome/mia>

**BugReports** <https://github.com/microbiome/mia/issues>

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/mia>

**git\_branch** devel

**git\_last\_commit** ba530f5

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2025-12-04

**Author** Tuomas Borman [aut, cre] (ORCID:

<<https://orcid.org/0000-0002-8563-8884>>),

Felix G.M. Ernst [aut] (ORCID: <<https://orcid.org/0000-0001-5064-0928>>),

Sudarshan A. Shetty [aut] (ORCID:

<<https://orcid.org/0000-0001-7280-9915>>),

Leo Lahti [aut] (ORCID: <<https://orcid.org/0000-0001-5537-637X>>),

Yang Cao [ctb],

Nathan D. Olson [ctb],

Levi Waldron [ctb],

Marcel Ramos [ctb],

Héctor Corrada Bravo [ctb],

Jayaram Kancharla [ctb],

Domenick Braccia [ctb],

Basil Courbayre [ctb],

Geraldson Muluh [ctb],

Giulio Benedetti [ctb],

Moritz Emanuel Beber [ctb] (ORCID:

<<https://orcid.org/0000-0003-2406-1978>>),

Chouaib Benchakra [ctb],

Akwak Jeba [ctb] (ORCID: <<https://orcid.org/0009-0007-1347-7552>>),

Himmi Lindgren [ctb],

Noah De Gunst [ctb],

Théotime Pralas [ctb],

Shadman Ishraq [ctb],

Eineje Ameh [ctb],

Artur Sannikov [ctb],

Hervé Pagès [ctb],

Rajesh Shigdel [ctb],

Katariina Pärnänen [ctb],

Pande Erawijantari [ctb],

Danielle Callan [ctb],

Sam Hillman [ctb],

Jesse Pasanen [ctb],

Eetu Tammi [ctb]

**Maintainer** Tuomas Borman <[tuomas.v.borman@utu.fi](mailto:tuomas.v.borman@utu.fi)>

## Contents

|                       |    |
|-----------------------|----|
| mia-package . . . . . | 4  |
| addAlpha . . . . .    | 5  |
| addCluster . . . . .  | 12 |

|                                   |     |
|-----------------------------------|-----|
| addContaminantQC . . . . .        | 14  |
| addDissimilarity . . . . .        | 16  |
| addDivergence . . . . .           | 20  |
| addMediation . . . . .            | 22  |
| agglomerateByPrevalence . . . . . | 26  |
| agglomerateByRank . . . . .       | 27  |
| calculateDMN . . . . .            | 34  |
| convertFromDADA2 . . . . .        | 38  |
| convertToBIOM . . . . .           | 39  |
| convertToPhyloseq . . . . .       | 41  |
| deprecate . . . . .               | 42  |
| dmn_se . . . . .                  | 50  |
| enterotype . . . . .              | 51  |
| esophagus . . . . .               | 52  |
| getAbundant . . . . .             | 53  |
| getCCA . . . . .                  | 56  |
| getCrossAssociation . . . . .     | 61  |
| getDominant . . . . .             | 67  |
| getDPCoA . . . . .                | 69  |
| getHierarchyTree . . . . .        | 71  |
| getLDA . . . . .                  | 72  |
| getMDS . . . . .                  | 74  |
| getNMDS . . . . .                 | 75  |
| getNMF . . . . .                  | 78  |
| getPERMANOVA . . . . .            | 80  |
| getPrevalence . . . . .           | 82  |
| getReducedDimAttribute . . . . .  | 88  |
| GlobalPatterns . . . . .          | 89  |
| HintikkaXOData . . . . .          | 90  |
| importHUMANn . . . . .            | 91  |
| importMetaPhlAn . . . . .         | 92  |
| importMothur . . . . .            | 93  |
| importQIIME2 . . . . .            | 95  |
| importTaxpasta . . . . .          | 98  |
| meltSE . . . . .                  | 99  |
| mergeSEs . . . . .                | 101 |
| mia-datasets . . . . .            | 104 |
| peerj13075 . . . . .              | 105 |
| rarefyAssay . . . . .             | 106 |
| splitOn . . . . .                 | 108 |
| summarizeDominance . . . . .      | 110 |
| taxonomyRanks . . . . .           | 113 |
| Tengeler2020 . . . . .            | 117 |
| Tito2024QMP . . . . .             | 118 |
| transformAssay . . . . .          | 119 |

---

mia-package

mia *Package*.

---

## Description

mia implements tools for microbiome analysis based on the SummarizedExperiment, SingleCellExperiment and TreeSummarizedExperiment infrastructure. Data wrangling and analysis in the context of taxonomic data is the main scope. Additional functions for common task are implemented such as community indices calculation and summarization.

## Author(s)

**Maintainer:** Tuomas Borman <tuomas.v.borman@utu.fi> ([ORCID](#))

Authors:

- Felix G.M. Ernst ([ORCID](#))
- Sudarshan A. Shetty ([ORCID](#))
- Leo Lahti <leo.lahti@iki.fi> ([ORCID](#))

Other contributors:

- Yang Cao [contributor]
- Nathan D. Olson [contributor]
- Levi Waldron [contributor]
- Marcel Ramos [contributor]
- Héctor Corrada Bravo [contributor]
- Jayaram Kancherla [contributor]
- Domenick Braccia [contributor]
- Basil Courbayre [contributor]
- Geraldson Mulu [contributor]
- Giulio Benedetti [contributor]
- Moritz Emanuel Beber ([ORCID](#)) [contributor]
- Chouaib Benchakra [contributor]
- Akewak Jeba ([ORCID](#)) [contributor]
- Himmi Lindgren [contributor]
- Noah De Gunst [contributor]
- Théotime Pralas [contributor]
- Shadman Ishraq [contributor]
- Eineje Ameh [contributor]
- Artur Sannikov [contributor]
- Hervé Pagès [contributor]

- Rajesh Shigdel [contributor]
- Katariina Pärnänen [contributor]
- Pande Erawijantari [contributor]
- Danielle Callan [contributor]
- Sam Hillman [contributor]
- Jesse Pasanen [contributor]
- Eetu Tammi [contributor]

### See Also

[TreeSummarizedExperiment](#)

---

|          |                                         |
|----------|-----------------------------------------|
| addAlpha | <i>Estimate alpha diversity indices</i> |
|----------|-----------------------------------------|

---

### Description

These functions estimates alpha diversity indices optionally using rarefaction.

### Usage

```
addAlpha(x, ...)

getAlpha(x, ...)

## S4 method for signature 'SummarizedExperiment'
addAlpha(x, ...)

## S4 method for signature 'SummarizedExperiment'
getAlpha(
  x,
  assay.type = "counts",
  index = c("dbp_dominance", "faith_diversity", "observed_richness", "shannon_diversity"),
  name = index,
  niter = NULL,
  BPPARAM = SerialParam(),
  ...
)
```

### Arguments

|     |                                                                                                                                                                                                                                               |
|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x   | a <a href="#">SummarizedExperiment</a> object.                                                                                                                                                                                                |
| ... | optional arguments: <ul style="list-style-type: none"> <li>• sample: Integer scalar. Specifies the rarefaction depth i.e. the number of counts drawn from each sample. (Default: <code>min(colSums2(assay(x, assay.type)))</code>)</li> </ul> |

- `tree.name`: Character scalar. Specifies which rowTree will be used. (Faith's index). (Default: "phylo")
- `node.label`: Character vector or NULL Specifies the links between rows and node labels of phylogeny tree specified by `tree.name`. If a certain row is not linked with the tree, missing instance should be noted as NA. When NULL, all the rownames should be found from the tree. (Faith's index). (Default: NULL)
- `only.tips`: (Faith's index). Logical scalar. Specifies whether to remove internal nodes when Faith's index is calculated. When `only.tips=TRUE`, those rows that are not tips of tree are removed. (Default: FALSE)
- `threshold`: (Coverage and all evenness indices). Numeric scalar. From 0 to 1, determines the threshold for coverage and evenness indices. When evenness indices are calculated values under or equal to this threshold are denoted as zeroes. For coverage index, see details. (Default: 0.5 for coverage, 0 for evenness indices)
- `quantile`: (log modulo skewness index). Numeric scalar. Arithmetic abundance classes are evenly cut up to to this quantile of the data. The assumption is that abundances higher than this are not common, and they are classified in their own group. (Default: 0.5)
- `nclasses`: (log modulo skewness index). Integer scalar. The number of arithmetic abundance classes from zero to the quantile cutoff indicated by quantile. (Default: 50)
- `ntaxa`: (absolute and relative indices). Integer scalar. The n-th position of the dominant taxa to consider. (Default: 1)
- `aggregate`: (absolute, dbp, dmn, and relative indices). Logical scalar. Aggregate the values for top members selected by `ntaxa` or not. If TRUE, then the sum of relative abundances is returned. Otherwise the relative abundance is returned for the single taxa with the indicated rank (default: `aggregate = TRUE`).
- `detection`: (observed index). Numeric scalar Selects detection threshold for the abundances (Default: 0)

|                         |                                                                                                                                                            |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>assay.type</code> | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                     |
| <code>index</code>      | Character vector. Specifies the alpha diversity indices to be calculated.                                                                                  |
| <code>name</code>       | Character vector. A name for the column of the <code>colData</code> where results will be stored. (Default: <code>index</code> )                           |
| <code>niter</code>      | Integer scalar. Specifies the number of rarefaction rounds. Rarefaction is not applied when <code>niter=NULL</code> (see Details section). (Default: NULL) |
| <code>BPPARAM</code>    | A <a href="#">BiocParallelParam</a> object specifying whether the calculation should be parallelized.                                                      |

## Details

Different diversity metrics considers different aspects of microbial community. Cassol et al. (2025) categorized alpha diversity metrics into four categories: richness, dominance, information, and phylogenetic. These categories provide complementary information, and by default, `*Alpha` function

return indices from each category: observed richness, Berger-Parker dominance, Shannon index for "information", and Faith phylogenetic index.

### Diversity:

Alpha diversity is a joint quantity that combines elements or community richness and evenness. Diversity increases, in general, when species richness or evenness increase.

The following diversity indices are available:

- 'coverage': Number of species needed to cover a given fraction of the ecosystem (50 percent by default). Tune this with the threshold argument.
- 'faith': Faith's phylogenetic alpha diversity index measures how long the taxonomic distance is between taxa that are present in the sample (Faith 1992). Larger values represent higher diversity. The current implementation is based on the Stacked Faith's Phylogenetic Diversity (SFPhD) algorithm (Armstrong et al. 2021), which produces values equivalent to `picante::pd` with the parameter `include.root=TRUE`. Using this index requires a `rowTree`. If the data includes features that are not in tree's tips but in internal nodes, there are two options. First, you can keep those features, and prune the tree to match features so that each tip can be found from the features. Other option is to remove all features that are not tips. (See only `tips` parameter)
- 'fisher': Fisher's alpha; as implemented in `vegan::fisher.alpha`. (Fisher et al. 1943)
- 'gini\_simpson': Gini-Simpson diversity i.e.  $1 - \lambda$ , where  $\lambda$  is the Simpson index, calculated as the sum of squared relative abundances. This corresponds to the diversity index 'simpson' in `vegan::diversity`. This is also called Gibbs–Martin, or Blau index in sociology, psychology and management studies. The Gini-Simpson index ( $1 - \lambda$ ) should not be confused with Simpson's dominance ( $\lambda$ ), Gini index, or inverse Simpson index ( $1/\lambda$ ).
- 'inverse\_simpson': Inverse Simpson diversity:  $1/\lambda$  where  $\lambda = \sum(p^2)$  and  $p$  refers to relative abundances. This corresponds to the diversity index 'invsimpson' in `vegan::diversity`. Don't confuse this with the closely related Gini-Simpson index
- 'log\_modulo\_skewness': The rarity index characterizes the concentration of species at low abundance. Here, we use the skewness of the frequency distribution of arithmetic abundance classes (see Magurran & McGill 2011). These are typically right-skewed; to avoid taking log of occasional negative skews, we follow Locey & Lennon (2016) and use the log-modulo transformation that adds a value of one to each measure of skewness to allow logarithmization.
- 'shannon': Shannon diversity (entropy).

### Dominance:

A dominance index quantifies the dominance of one or few species in a community. Greater values indicate higher dominance.

Dominance indices are in general negatively correlated with alpha diversity indices (species richness, evenness, diversity, rarity). More dominant communities are less diverse.

The following community dominance indices are available:

- 'absolute': Absolute index equals to the absolute abundance of the most dominant  $n$  species of the sample (specify the number with the argument `ntaxa`). Index gives positive integer values.

- 'dbp': Berger-Parker index (See Berger & Parker 1970) calculation is a special case of the 'relative' index. dbp is the relative abundance of the most abundant species of the sample. Index gives values in interval 0 to 1, where bigger value represent greater dominance.

$$dbp = \frac{N_1}{N_{tot}}$$

where  $N_1$  is the absolute abundance of the most dominant species and  $N_{tot}$  is the sum of absolute abundances of all species.

- 'core\_abundance': Core abundance index is related to core species. Core species are species that are most abundant in all samples, i.e., in whole data set. Core species are defined as those species that have prevalence over 50\ species must be prevalent in 50\ calculate the core abundance index. Core abundance index is sum of relative abundances of core species in the sample. Index gives values in interval 0 to 1, where bigger value represent greater dominance.

$$core\_abundance = \frac{N_{core}}{N_{tot}}$$

where  $N_{core}$  is the sum of absolute abundance of the core species and  $N_{tot}$  is the sum of absolute abundances of all species.

- 'gini': Gini index is probably best-known from socio-economic contexts (Gini 1921). In economics, it is used to measure, for example, how unevenly income is distributed among population. Here, Gini index is used similarly, but income is replaced with abundance. If there is small group of species that represent large portion of total abundance of microbes, the inequality is large and Gini index closer to 1. If all species has equally large abundances, the equality is perfect and Gini index equals 0. This index should not be confused with Gini-Simpson index, which quantifies diversity.
- 'dmn': McNaughton's index is the sum of relative abundances of the two most abundant species of the sample (McNaughton & Wolf, 1970). Index gives values in the unit interval:

$$dmn = (N_1 + N_2)/N_{tot}$$

where  $N_1$  and  $N_2$  are the absolute abundances of the two most dominant species and  $N_{tot}$  is the sum of absolute abundances of all species.

- 'relative': Relative index equals to the relative abundance of the most dominant n species of the sample (specify the number with the argument ntaxa). This index gives values in interval 0 to 1.

$$relative = N_1/N_{tot}$$

where  $N_1$  is the absolute abundance of the most dominant species and  $N_{tot}$  is the sum of absolute abundances of all species.

- 'simpson\_lambda': Simpson's (dominance) index or Simpson's lambda is the sum of squared relative abundances. This index gives values in the unit interval. This value equals the probability that two randomly chosen individuals belongs to the same species. The higher the probability, the greater the dominance (See e.g. Simpson 1949).

$$lambda = \sum(p^2)$$

where p refers to relative abundances.



There is also a more advanced Simpson dominance index (Simpson 1949). However, this is not provided and the simpler squared sum of relative abundances is used instead as the alternative index is not in the unit interval and it is highly correlated with the simpler variant implemented here.

### Evenness:

Evenness is a standard index in community ecology, and it quantifies how evenly the abundances of different species are distributed. The following evenness indices are provided:

By default, four indices are returned, each taking into account different aspects: richness (the number of observed unique features), dominance (Berger-Parker), information (Shannon), and phylogenetics (Faith) (Cassol et al., 2025).

The available evenness indices include the following (all in lowercase):

- `'camargo'`: Camargo's evenness (Camargo 1992)
- `'simpson_evenness'`: Simpson's evenness is calculated as inverse Simpson diversity ( $1/\lambda$ ) divided by observed species richness  $S$ :  $(1/\lambda)/S$ .
- `'pielou'`: Pielou's evenness (Pielou, 1966), also known as Shannon or Shannon-Weaver/Wiener/Weiner evenness;  $H/\ln(S)$ . The Shannon-Weaver is the preferred term; see Spellerberg and Fedor (2003).
- `'evar'`: Smith and Wilson's Evar index (Smith & Wilson 1996).
- `'bulla'`: Bulla's index (O) (Bulla 1994).

Desirable statistical evenness metrics avoid strong bias towards very large or very small abundances; are independent of richness; and range within the unit interval with increasing evenness (Smith & Wilson 1996). Evenness metrics that fulfill these criteria include at least camargo, simpson, smith-wilson, and bulla. Also see Magurran & McGill (2011) and Beisel et al. (2003) for further details.

### Richness:

The richness is calculated per sample. This is a standard index in community ecology, and it provides an estimate of the number of unique species in the community. This is often not directly observed for the whole community but only for a limited sample from the community. This has led to alternative richness indices that provide different ways to estimate the species richness.

Richness index differs from the concept of species diversity or evenness in that it ignores species abundance, and focuses on the binary presence/absence values that indicate simply whether the species was detected.

The function takes all index names in full lowercase. The user can provide the desired spelling through the argument `name` (see examples).

The following richness indices are provided.

- `'ace'`: Abundance-based coverage estimator (ACE) is another nonparametric richness index that uses sample coverage, defined based on the sum of the probabilities of the observed species. This method divides the species into abundant (more than 10 reads or observations) and rare groups in a sample and tends to underestimate the real number of species. The ACE index ignores the abundance information for the abundant species, based on the assumption that the abundant species are observed regardless of their exact abundance. We use here the bias-corrected version (O'Hara 2005, Chiu et al. 2014) implemented in `estimateR`. For an exact formulation, see `estimateR`. Note that this index comes with an additional column with standard error information.

- 'chao1': This is a nonparametric estimator of species richness. It assumes that rare species carry information about the (unknown) number of unobserved species. We use here the bias-corrected version (O'Hara 2005, Chiu et al. 2014) implemented in `estimateR`. This index implicitly assumes that every taxa has equal probability of being observed. Note that it gives a lower bound to species richness. The bias-corrected for an exact formulation, see `estimateR`. This estimator uses only the singleton and doubleton counts, and hence it gives more weight to the low abundance species. Note that this index comes with an additional column with standard error information.
- 'hill': Effective species richness aka Hill index (see e.g. Chao et al. 2016). Currently only the case 1D is implemented. This corresponds to the exponent of Shannon diversity. Intuitively, the effective richness indicates the number of species whose even distribution would lead to the same diversity than the observed community, where the species abundances are unevenly distributed.
- 'observed': The *observed richness* gives the number of species that is detected above a given detection threshold in the observed sample (default 0). This is conceptually the simplest richness index. The corresponding index in the **vegan** package is "richness".

### Rarefaction:

Rarefaction can be used to control uneven sequencing depths. Although, it is highly debated method. Some think that it is the only option that successfully controls the variation caused by uneven sampling depths. The biggest argument against rarefaction is the fact that it omits data.

Rarefaction works by sampling the counts randomly. This random sampling is done `niter` times. In each sampling iteration, sample number of random samples are drawn, and alpha diversity is calculated for this subset. After the iterative process, there are `niter` number of result that are then averaged to get the final result.

Refer to Schloss (2024) for more details on rarefaction.

### Value

`getAlpha` returns a `DataFrame`. `addAlpha` returns a `x` with additional `colData` column(s) named `name`.

### References

- Armstrong G. et al. (2021) Efficient computation of Faith's phylogenetic diversity with applications in characterizing microbiomes. *Genome Res.* 31(11):2131-2137. doi: 10.1101/gr.275777.121
- Beisel J-N. et al. (2003) A Comparative Analysis of Diversity Index Sensitivity. *Internal Rev. Hydrobiol.* 88(1):3-15. [https://portais.ufg.br/up/202/o/2003-comparative\\_evennes\\_index.pdf](https://portais.ufg.br/up/202/o/2003-comparative_evennes_index.pdf)
- Berger WH & Parker FL (1970) Diversity of Planktonic Foraminifera in Deep-Sea Sediments. *Science* 168(3937):1345-1347. doi: 10.1126/science.168.3937.1345
- Bulla L. (1994) An index of diversity and its associated diversity measure. *Oikos* 70:167-171
- Camargo, JA. (1992) New diversity index for assessing structural alterations in aquatic communities. *Bull. Environ. Contam. Toxicol.* 48:428-434.
- Cassol, I. (2025) Key features and guidelines for the application of microbial alpha diversity metrics. *Sci. Rep.* 15:622. doi: 10.1038/s41598-024-77864-y

- Chao A. (1984) Non-parametric estimation of the number of classes in a population. *Scand J Stat.* 11:265–270.
- Chao A, Chun-Huo C, Jost L (2016). Phylogenetic Diversity Measures and Their Decomposition: A Framework Based on Hill Numbers. *Biodiversity Conservation and Phylogenetic Systematics*, Springer International Publishing, pp. 141–172, doi:10.1007/978-3-319-22461-9\_8.
- Chiu, C.H., Wang, Y.T., Walther, B.A. & Chao, A. (2014). Improved nonparametric lower bound of species richness via a modified Good-Turing frequency formula. *Biometrics* 70, 671-682.
- Faith D.P. (1992) Conservation evaluation and phylogenetic diversity. *Biological Conservation* 61(1):1-10.
- Fisher R.A., Corbet, A.S. & Williams, C.B. (1943) The relation between the number of species and the number of individuals in a random sample of animal population. *Journal of Animal Ecology* 12, 42-58.
- Gini C (1921) Measurement of Inequality of Incomes. *The Economic Journal* 31(121): 124-126. doi: 10.2307/2223319
- Locey KJ and Lennon JT. (2016) Scaling laws predict global microbial diversity. *PNAS* 113(21):5970-5975; doi:10.1073/pnas.1521291113.
- Magurran AE, McGill BJ, eds (2011) *Biological Diversity: Frontiers in Measurement and Assessment* (Oxford Univ Press, Oxford), Vol 12.
- McNaughton, SJ and Wolf LL. (1970). Dominance and the niche in ecological systems. *Science* 167:13, 1–139
- O’Hara, R.B. (2005). Species richness estimators: how many species can dance on the head of a pin? *J. Anim. Ecol.* 74, 375-386.
- Pielou, EC. (1966) The measurement of diversity in different types of biological collections. *J Theoretical Biology* 13:131–144.
- Schloss PD (2024) Rarefaction is currently the best approach to control for uneven sequencing effort in amplicon sequence analyses. *mSphere* 28;9(2):e0035423. doi: 10.1128/msphere.00354-23
- Simpson EH (1949) Measurement of Diversity. *Nature* 163(688). doi: 10.1038/163688a0
- Smith B and Wilson JB. (1996) A Consumer’s Guide to Evenness Indices. *Oikos* 76(1):70-82.
- Spellerberg and Fedor (2003). A tribute to Claude Shannon (1916 –2001) and a plea for more rigorous use of species richness, species diversity and the ‘Shannon–Wiener’ Index. *Alpha Ecology & Biogeography* 12, 177–197.
- Cassol, I., Ibañez, M. & Bustamante, J.P. (2025) Key features and guidelines for the application of microbial alpha diversity metrics. *Sci Rep* 15, 622. doi:10.1038/s41598-024-77864-y

## See Also

- [plotColData](#)
- [estimator](#)
- [diversity](#)

## Examples

```
data("GlobalPatterns")
tse <- GlobalPatterns

# Calculate the default Shannon index with no rarefaction
tse <- addAlpha(tse, index = "shannon")

# Shows the estimated Shannon index
tse$shannon

# Calculate observed richness with 10 rarefaction rounds
tse <- addAlpha(tse,
  assay.type = "counts",
  index = "observed_richness",
  sample = min(colSums(assay(tse, "counts")), na.rm = TRUE),
  niter=10)

# Shows the estimated observed richness
tse$observed_richness

# One can also calculate the indices and get the results without adding
# them to colData
res <- getAlpha(tse, index = "shannon")
res |> head()
```

---

addCluster

*Clustering wrapper*


---

## Description

This function returns a SummarizedExperiment with clustering information in its colData or row-Data

## Usage

```
addCluster(
  x,
  BLUSPARAM,
  assay.type = assay_name,
  assay_name = "counts",
  by = MARGIN,
  MARGIN = "rows",
  full = FALSE,
  name = "clusters",
  clust.col = "clusters",
  ...
)
```

```
## S4 method for signature 'SummarizedExperiment'
addCluster(
  x,
  BLUSPARAM,
  assay.type = assay_name,
  assay_name = "counts",
  by = MARGIN,
  MARGIN = "rows",
  full = FALSE,
  name = "clusters",
  clust.col = "clusters",
  ...
)
```

### Arguments

|            |                                                                                                                                                             |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x          | A <a href="#">SummarizedExperiment</a> object.                                                                                                              |
| BLUSPARAM  | A <a href="#">BlusterParam</a> object specifying the algorithm to use.                                                                                      |
| assay.type | Character scalar. Specifies the name of the assay used in calculation. (Default: "counts")                                                                  |
| assay_name | Deprecated. Use assay.type instead.                                                                                                                         |
| by         | Character scalar. Determines if association is calculated row-wise / for features ('rows') or column-wise / for samples ('cols'). Must be 'rows' or 'cols'. |
| MARGIN     | Deprecated. Use by instead.                                                                                                                                 |
| full       | Logical scalar indicating whether the full clustering statistics should be returned for each method.                                                        |
| name       | Character scalar. The name to store the result in <a href="#">metadata</a>                                                                                  |
| clust.col  | Character scalar. Indicates the name of the rowData (or colData) where the data will be stored. (Default: "clusters")                                       |
| ...        | Additional parameters to use altExps for example                                                                                                            |

### Details

This is a wrapper for the clusterRows function from the [bluster](#) package.

When setting full = TRUE, the clustering information will be stored in the metadata of the object.

By default, clustering is done on the features.

### Value

addCluster returns an object of the same type as the x parameter with clustering information named clusters stored in colData or rowData.

**Examples**

```
library(bluster)
data(GlobalPatterns, package = "mia")
tse <- GlobalPatterns

# Cluster on rows using Kmeans
tse <- addCluster(tse, KmeansParam(centers = 3))

# Clustering done on the samples using Hclust
tse <- addCluster(tse,
                  by = "samples",
                  HclustParam(metric = "bray", dist.fun = vegan::vegdist))

# Getting the clusters
colData(tse)$clusters
```

---

|                  |                           |
|------------------|---------------------------|
| addContaminantQC | <i>decontam functions</i> |
|------------------|---------------------------|

---

**Description**

The decontam functions `isContaminant` and `isNotContaminant` are made available for [SummarizedExperiment](#) objects.

**Usage**

```
addContaminantQC(x, name = "isContaminant", ...)

addNotContaminantQC(x, name = "isNotContaminant", ...)

## S4 method for signature 'SummarizedExperiment'
isContaminant(
  seqtab,
  assay.type = assay_name,
  assay_name = "counts",
  concentration = NULL,
  control = NULL,
  batch = NULL,
  threshold = 0.1,
  normalize = TRUE,
  detailed = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
isNotContaminant(
  seqtab,
```

```

    assay.type = assay_name,
    assay_name = "counts",
    control = NULL,
    threshold = 0.5,
    normalize = TRUE,
    detailed = TRUE,
    ...
)

## S4 method for signature 'SummarizedExperiment'
addContaminantQC(x, name = "contaminant", ...)

## S4 method for signature 'SummarizedExperiment'
addNotContaminantQC(x, name = "not_contaminant", ...)

```

### Arguments

|               |                                                                                                                                                                                                                                                                                                             |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| name          | Character scalar. A name for the column of the colData where results will be stored. (Default: "contaminant" or "not_contaminant")                                                                                                                                                                          |
| ...           | <ul style="list-style-type: none"> <li>for isContaminant/ isNotContaminant: arguments passed on to <a href="#">decontam:isContaminant</a> or <a href="#">decontam:isNotContaminant</a></li> <li>for addContaminantQC/addNotContaminantQC: arguments passed on to isContaminant/ isNotContaminant</li> </ul> |
| seqtab, x     | a <a href="#">SummarizedExperiment</a>                                                                                                                                                                                                                                                                      |
| assay.type    | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                                                                                                                      |
| assay_name    | Deprecated. Use assay.type instead.                                                                                                                                                                                                                                                                         |
| concentration | Character scalar or NULL. Defining a column with numeric values from the colData to use as concentration information. (Default: NULL)                                                                                                                                                                       |
| control       | Character scalar or NULL. Defining a column with logical values from the colData to define control and non-control samples. (Default: NULL)                                                                                                                                                                 |
| batch         | Character scalar or NULL. Defining a column with values interpretable as a factor from the colData to use as batch information. (Default: NULL)                                                                                                                                                             |
| threshold     | Numeric scalar.. See <a href="#">decontam:isContaminant</a> or <a href="#">decontam:isNotContaminant</a>                                                                                                                                                                                                    |
| normalize     | Logical scalar. See <a href="#">decontam:isContaminant</a> or <a href="#">decontam:isNotContaminant</a>                                                                                                                                                                                                     |
| detailed      | Logical scalar. If TRUE, the return value is a data.frame containing diagnostic information on the contaminant decision. If FALSE, the return value is a logical vector containing the binary contaminant classifications. (Default: TRUE)                                                                  |

### Value

for isContaminant/ isNotContaminant a DataFrame or for addContaminantQC/addNotContaminantQC a modified object of class(x)

### See Also

[decontam:isContaminant](#), [decontam:isNotContaminant](#)

## Examples

```
data(esophagus)
# setup of some mock data just for example
colData(esophagus)$concentration <- c(1, 2, 3)
colData(esophagus)$control <- c(FALSE, FALSE, TRUE)

isContaminant(
  esophagus,
  method = "frequency",
  concentration = "concentration"
)
esophagus <- addContaminantQC(
  esophagus,
  method = "frequency",
  concentration = "concentration"
)
rowData(esophagus)

isNotContaminant(esophagus, control = "control")
esophagus <- addNotContaminantQC(esophagus, control = "control")
rowData(esophagus)
```

---

|                  |                                  |
|------------------|----------------------------------|
| addDissimilarity | <i>Calculate dissimilarities</i> |
|------------------|----------------------------------|

---

## Description

These functions are designed to calculate dissimilarities on data stored within a [TreeSummarizedExperiment](#) object. For overlap, Unifrac, and Jensen-Shannon Divergence (JSD) dissimilarities, the functions use mia internal functions, while for other types of dissimilarities, they rely on [vegdist](#) by default.

## Usage

```
addDissimilarity(x, method, ...)

getDissimilarity(x, method, ...)

## S4 method for signature 'SummarizedExperiment'
addDissimilarity(x, method = "bray", name = method, ...)

## S4 method for signature 'SummarizedExperiment'
getDissimilarity(
  x,
  method = "bray",
  assay.type = "counts",
  niter = NULL,
  transposed = FALSE,
```



```

    ...
)

## S4 method for signature 'TreeSummarizedExperiment'
getDissimilarity(
  x,
  method = "bray",
  assay.type = "counts",
  niter = NULL,
  transposed = FALSE,
  ...
)

## S4 method for signature 'ANY'
getDissimilarity(x, method = "bray", niter = NULL, ...)
```

## Arguments

|        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x      | <a href="#">TreeSummarizedExperiment</a> or matrix.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| method | Character scalar. Specifies which dissimilarity to calculate. (Default: "bray")                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| ...    | other arguments passed into <a href="#">avgdist</a> , <a href="#">vegdist</a> , or into mia internal functions: <ul style="list-style-type: none"> <li>• sample: The sampling depth in rarefaction. (Default: min(rowSums2(x)))</li> <li>• dis.fun: Character scalar. Specifies the dissimilarity function to be used.</li> <li>• transf: Function. Specifies the optional transformation applied before calculating the dissimilarity matrix.</li> <li>• tree.name: (Unifrac) Character scalar. Specifies the name of the tree from rowTree(x) that is used in calculation. Disabled when tree is specified. (Default: "phylo")</li> <li>• tree: (Unifrac) phylo. A phylogenetic tree used in calculation. (Default: NULL)</li> <li>• weighted: (Unifrac) Logical scalar. Should use weighted-Unifrac calculation? Weighted-Unifrac takes into account the relative abundance of species/taxa shared between samples, whereas unweighted-Unifrac only considers presence/absence. Default is FALSE, meaning the unweighted-Unifrac dissimilarity is calculated for all pairs of samples. (Default: FALSE)</li> <li>• node.label (Unifrac) character vector. Used only if x is a matrix. Specifies links between rows/columns and tips of tree. All the node labs must be present in tree. For the links, you can provide a vector with whose length equals to the number of rows/columns in x. Alternatively, you can provide a named vector where names represent names in abundance table and values their corresponding node in tree.</li> <li>• chunkSize: (JSD) Integer scalar. Defines the size of data send to the individual worker. Only has an effect, if BPPARAM defines more than one worker. (Default: nrow(x))</li> <li>• BPPARAM: (JSD) <a href="#">BiocParallelParam</a>. Specifies whether the calculation should be parallelized.</li> </ul> |

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                   | <ul style="list-style-type: none"> <li>• <b>detection:</b> (Overlap) Numeric scalar. Defines detection threshold for absence/presence of features. Feature that has abundance under threshold in either of samples, will be discarded when evaluating overlap between samples. (Default: 0)</li> <li>• <b>binary:</b> Logical scalar. Whether to perform presence/absence transformation before dissimilarity calculation. For Jaccard index the default is TRUE. For other dissimilarity metrics, please see <a href="#">vegdist</a>.</li> </ul> |
| <b>name</b>       | Character scalar. The name to be used to store the result in metadata of the output. (Default: method)                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>assay.type</b> | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>niter</b>      | Integer scalar. Specifies the number of rarefaction rounds. Rarefaction is not applied when niter=NULL (see Details section). (Default: NULL)                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>transposed</b> | Logical scalar. Specifies if x is transposed with cells in rows. (Default: FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## Details

Overlap reflects similarity between sample-pairs. When overlap is calculated using relative abundances, the higher the value the higher the similarity is. When using relative abundances, overlap value 1 means that all the abundances of features are equal between two samples, and 0 means that samples have completely different relative abundances.

Unifrac is calculated with [rbiom:unifrac\(\)](#).

If rarefaction is enabled, [vegan:avgdist\(\)](#) is utilized.

Rarefaction can be used to control uneven sequencing depths. Although, it is highly debated method. Some think that it is the only option that successfully controls the variation caused by uneven sampling depths. The biggest argument against rarefaction is the fact that it omits data.

Rarefaction works by sampling the counts randomly. This random sampling is done niter times. In each sampling iteration, sample number of random samples are drawn, and dissimilarity is calculated for this subset. After the iterative process, there are niter number of result that are then averaged to get the final result.

Refer to Schloss (2024) for more details on rarefaction.

## Value

`getDissimilarity` returns a sample-by-sample dissimilarity matrix.

`addDissimilarity` returns x that includes dissimilarity matrix in its metadata.

## References

For unifrac dissimilarity: <http://bmf.colorado.edu/unifrac/>

See also additional descriptions of Unifrac in the following articles:

Lozupone, Hamady and Knight, "Unifrac - An Online Tool for Comparing Microbial Community Diversity in a Phylogenetic Context.", BMC Bioinformatics 2006, 7:371

Lozupone, Hamady, Kelley and Knight, “Quantitative and qualitative (beta) diversity measures lead to different insights into factors that structure microbial communities.” *Appl Environ Microbiol.* 2007

Lozupone C, Knight R. “Unifrac: a new phylogenetic method for comparing microbial communities.” *Appl Environ Microbiol.* 2005 71 (12):8228-35.

For JSD dissimilarity: Jensen-Shannon Divergence and Hilbert space embedding. Bent Fuglede and Flemming Topsøe University of Copenhagen, Department of Mathematics <http://www.math.ku.dk/~topsoe/ISIT2004JSD.pdf>

For rarefaction: Schloss PD (2024) Rarefaction is currently the best approach to control for uneven sequencing effort in amplicon sequence analyses. *mSphere* 28;9(2):e0035423. doi: 10.1128/msphere.00354-23

### See Also

[http://en.wikipedia.org/wiki/Jensen-Shannon\\_divergence](http://en.wikipedia.org/wiki/Jensen-Shannon_divergence)

### Examples

```
library(mia)
library(scater)

# load dataset
data(GlobalPatterns)
tse <- GlobalPatterns

### Overlap dissimilarity

tse <- addDissimilarity(tse, method = "overlap", detection = 0.25)
metadata(tse)[["overlap"]][1:6, 1:6]

### JSD dissimilarity

tse <- addDissimilarity(tse, method = "jsd")
metadata(tse)[["jsd"]][1:6, 1:6]

# Multi Dimensional Scaling applied to JSD dissimilarity matrix
tse <- addMDS(tse, method = "overlap", assay.type = "counts")
reducedDim(tse, "MDS") |> head()

### Unifrac dissimilarity

res <- getDissimilarity(tse, method = "unifrac", weighted = FALSE)
dim(as.matrix(res))

tse <- addDissimilarity(tse, method = "unifrac", weighted = TRUE)
metadata(tse)[["unifrac"]][1:6, 1:6]

### Bray dissimilarity

# Bray is usually applied to relative abundances so we have to apply
# transformation first
```

```

tse <- transformAssay(tse, method = "relabundance")
res <- getDissimilarity(tse, method = "bray", assay.type = "relabundance")
as.matrix(res)[1:6, 1:6]

# If applying rarefaction, the input must be count matrix and transformation
# method specified in function call (Note: increase niter)
rclr <- function(x){
  vegan::decostand(x, method="rclr")
}
res <- getDissimilarity(
  tse, method = "euclidean", transf = rclr, niter = 2L)
as.matrix(res)[1:6, 1:6]

```

---

addDivergence

*Estimate divergence*


---

## Description

Estimate divergence against a given reference sample.

## Usage

```

addDivergence(x, name = "divergence", ...)

getDivergence(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  reference = "median",
  method = "bray",
  ...
)

## S4 method for signature 'SummarizedExperiment'
addDivergence(x, name = "divergence", ...)

## S4 method for signature 'SummarizedExperiment'
getDivergence(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  reference = "median",
  method = "bray",
  ...
)

```

**Arguments**

|            |                                                                                                                                                                                                                                                                                                                                                                       |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x          | a <a href="#">SummarizedExperiment</a> object.                                                                                                                                                                                                                                                                                                                        |
| name       | Character scalar. The name to be used to store the result in metadata of the output. (Default: method)                                                                                                                                                                                                                                                                |
| ...        | optional arguments passed to <a href="#">addDissimilarity</a> . Additionally: <ul style="list-style-type: none"> <li>• dimred: Character scalar. Specifies the name of dimension reduction result from <code>reducedDim(x)</code>. If used, these values are used to calculate divergence instead of the assay. Can be disabled with NULL. (Default: NULL)</li> </ul> |
| assay.type | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                                                                                                                                                                                |
| assay_name | Deprecated. Use <code>assay.type</code> instead.                                                                                                                                                                                                                                                                                                                      |
| reference  | Character scalar. A column name from <code>colData(x)</code> or either "mean" or "median". If column name is specified, the column must include reference samples for each sample. If "mean" or "median" is specified, the mean or median of the entire dataset is calculated and used as the reference value. (Default: "median")                                    |
| method     | Character scalar. Specifies which dissimilarity to calculate. (Default: "bray")                                                                                                                                                                                                                                                                                       |

**Details**

Microbiota divergence (heterogeneity / spread) within a given sample set can be quantified by the average sample dissimilarity or beta diversity with respect to a given reference sample.

The calculation makes use of the function `getDissimilarity()`. The divergence measure is sensitive to sample size. Subsampling or bootstrapping can be applied to equalize sample sizes between comparisons.

**Value**

x with additional [colData](#) named name

**See Also**

- [addAlpha](#)
- [addDissimilarity](#)
- [plotColData](#)

**Examples**

```
data(GlobalPatterns)
tse <- GlobalPatterns

# By default, reference is median of all samples. The name of column where
# results is "divergence" by default, but it can be specified.
tse <- addDivergence(tse)

# The method that are used to calculate distance in divergence and
```

```
# reference can be specified. Here, euclidean distance is used. Reference is
# the first sample. It is recommended # to add reference to colData.
tse[["reference"]] <- rep(colnames(tse)[[1]], ncol(tse))
tse <- addDivergence(
  tse, name = "divergence_first_sample",
  reference = "reference",
  method = "euclidean")

# Here we compare samples to global mean
tse <- addDivergence(tse, name = "divergence_average", reference = "mean")

# All three divergence results are stored in colData.
colData(tse)
```

---

|              |                                   |
|--------------|-----------------------------------|
| addMediation | <i>Perform mediation analysis</i> |
|--------------|-----------------------------------|

---

## Description

getMediation and addMediation provide a wrapper of [mediate](#) for [SummarizedExperiment](#).

## Usage

```
addMediation(x, ...)

getMediation(x, ...)

## S4 method for signature 'SummarizedExperiment'
addMediation(
  x,
  outcome,
  treatment,
  name = "mediation",
  mediator = NULL,
  assay.type = NULL,
  dimred = NULL,
  family = gaussian(),
  covariates = NULL,
  p.adj.method = "holm",
  add.metadata = TRUE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
getMediation(
  x,
```

```

    outcome,
    treatment,
    mediator = NULL,
    assay.type = NULL,
    dimred = NULL,
    family = gaussian(),
    covariates = NULL,
    p.adj.method = "holm",
    add.metadata = TRUE,
    sort = FALSE,
    verbose = TRUE,
    ...
)

```

### Arguments

|                           |                                                                                                                                                     |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>            | a <a href="#">SummarizedExperiment</a> .                                                                                                            |
| <code>...</code>          | additional parameters that can be passed to <a href="#">mediate</a> .                                                                               |
| <code>outcome</code>      | Character scalar. Indicates the <code>colData</code> variable used as outcome in the model.                                                         |
| <code>treatment</code>    | Character scalar. Indicates the <code>colData</code> variable used as treatment in the model.                                                       |
| <code>name</code>         | Character scalar. A name for the column of the <code>colData</code> where results will be stored. (Default: "mediation")                            |
| <code>mediator</code>     | Character scalar. Indicates the <code>colData</code> variable used as mediator in the model. (Default: NULL)                                        |
| <code>assay.type</code>   | Character scalar. Specifies the assay used for feature-wise mediation analysis. (Default: NULL)                                                     |
| <code>dimred</code>       | Character scalar. Indicates the reduced dimension result in <code>reducedDims(object)</code> for component-wise mediation analysis. (Default: NULL) |
| <code>family</code>       | Character scalar. A specification for the outcome model link function. (Default: <code>gaussian("identity")</code> )                                |
| <code>covariates</code>   | Character scalar or character vector. Indicates the <code>colData</code> variables used as covariates in the model. (Default: NULL)                 |
| <code>p.adj.method</code> | Character scalar. Selects adjustment method of p-values. Passed to <code>p.adjust</code> function. (Default: "holm")                                |
| <code>add.metadata</code> | Logical scalar. Should the model metadata be returned. (Default: TRUE)                                                                              |
| <code>verbose</code>      | Logical scalar. Should execution messages be printed. (Default: TRUE)                                                                               |
| <code>sort</code>         | Logical scalar. Should the results be sorted by decreasing significance in terms of <code>ACME_pval</code> . (Default: FALSE)                       |

### Details

This wrapper of [mediate](#) for [SummarizedExperiment](#) provides a simple method to analyse the effect of a treatment variable on an outcome variable found in `colData(se)` through the mediation of either another variable in `colData` (argument `mediator`) or an assay (argument `assay.type`) or a `reducedDim` (argument `dimred`). Importantly, those three arguments are mutually exclusive.

**Value**

getMediation returns a `data.frame` of adjusted p-values and effect sizes for the ACMEs and ADEs of every mediator given as input, whereas addMediation returns an updated `SummarizedExperiment` instance with the same `data.frame` stored in the metadata as "mediation" or as specified in the name argument. Its columns include:

**mediator** the mediator variable  
**acme** the Average Causal Mediation Effect (ACME) estimate  
**acme\_pval** the original p-value for the ACME estimate  
**acme\_lower** the lower bound of the CI for the ACME estimate  
**acme\_upper** the upper bound of the CI for the ACME estimate  
**ade** the Average Direct Effect (ADE) estimate  
**ade\_pval** the original p-value for the ADE estimate  
**ade\_lower** the lower bound of the CI for the ADE estimate  
**ade\_upper** the upper bound of the CI for the ADE estimate  
**total** the Total Effect estimate  
**total\_lower** the lower bound of the CI for the Total Effect estimate  
**total\_upper** the upper bound of the CI for the Total Effect estimate  
**total\_pval** the original p-value for the Total Effect estimate  
**acme\_padj** the adjusted p-value for the ACME estimate  
**ade\_padj** the adjusted p-value for the ADE estimate  
**total\_padj** the adjusted p-value for the Total Effect estimate

The original output of `mediate` for each analysed mediator is stored as the "model\_metadata" attribute of the resulting `data.frame` and can be accessed via the `attr` function.

**Examples**

```
## Not run:
# Import libraries
library(mia)
library(miaViz)
library(scater)

# Load dataset
data(hitchip1006, package = "miaTime")
tse <- hitchip1006

# Agglomerate features by family (merely to speed up execution)
tse <- agglomerateByRank(tse, rank = "Phylum")
# Convert BMI variable to numeric
tse$bmi_group <- as.numeric(tse$bmi_group)

# Analyse mediated effect of nationality on BMI via alpha diversity
# 100 permutations were done to speed up execution, but ~1000 are recommended
```



```
med_df <- getMediation(  
  tse,  
  outcome = "bmi_group",  
  treatment = "nationality",  
  mediator = "diversity",  
  covariates = c("sex", "age"),  
  treat.value = "Scandinavia",  
  control.value = "CentralEurope",  
  boot = TRUE, sims = 100)  
  
# Visualise model statistics  
plotMediation(med_df)  
  
# Apply clr transformation to counts assay  
tse <- transformAssay(tse, method = "clr", pseudocount = 1)  
  
# Analyse mediated effect of nationality on BMI via clr-transformed features  
# 100 permutations were done to speed up execution, but ~1000 are recommended  
tse <- addMediation(  
  tse, name = "assay_mediation",  
  outcome = "bmi_group",  
  treatment = "nationality",  
  assay.type = "clr",  
  covariates = c("sex", "age"),  
  treat.value = "Scandinavia",  
  control.value = "CentralEurope",  
  boot = TRUE, sims = 100,  
  p.adj.method = "fdr")  
  
# Show results for first 5 mediators  
head(metadata(tse)$assay_mediation, 5)  
  
# Perform ordination  
tse <- addMDS(  
  tse, name = "MDS", method = "euclidean", assay.type = "clr",  
  ncomponents = 3)  
  
# Analyse mediated effect of nationality on BMI via NMDS components  
# 100 permutations were done to speed up execution, but ~1000 are recommended  
tse <- addMediation(  
  tse, name = "reddim_mediation",  
  outcome = "bmi_group",  
  treatment = "nationality",  
  dimred = "MDS",  
  covariates = c("sex", "age"),  
  treat.value = "Scandinavia",  
  control.value = "CentralEurope",  
  boot = TRUE, sims = 100,  
  p.adj.method = "fdr")  
  
# Show results for first 5 mediators  
head(metadata(tse)$reddim_mediation, 5)
```

```
# Access model metadata
attr(metadata(tse)$reddim_mediation, "model_metadata")

## End(Not run)
```

---

agglomerateByPrevalence

*Agglomerate data based on population prevalence*

---

## Description

Agglomerate data based on population prevalence

## Usage

```
agglomerateByPrevalence(x, ...)

## S4 method for signature 'SummarizedExperiment'
agglomerateByPrevalence(
  x,
  rank = NULL,
  other.name = other_label,
  other_label = "Other",
  ...
)

## S4 method for signature 'TreeSummarizedExperiment'
agglomerateByPrevalence(
  x,
  rank = NULL,
  other.name = other_label,
  other_label = "Other",
  update.tree = TRUE,
  ...
)
```

## Arguments

|             |                                                                                                                                                                                        |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x           | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                             |
| ...         | arguments passed to <code>agglomerateByRank</code> function for <code>SummarizedExperiment</code> objects and other functions. See <a href="#">agglomerateByRank</a> for more details. |
| rank        | Character scalar. Defines a taxonomic rank. Must be a value of <code>taxonomyRanks()</code> function.                                                                                  |
| other.name  | Character scalar. Used as the label for the summary of non-prevalent taxa. (default: "Other")                                                                                          |
| other_label | Deprecated. use <code>other.name</code> instead.                                                                                                                                       |
| update.tree | Logical scalar. Should <code>rowTree()</code> also be merged? (Default: TRUE)                                                                                                          |

## Details

agglomerateByPrevalence sums up the values of assays at the taxonomic level specified by rank (by default the highest taxonomic level available) and selects the summed results that exceed the given population prevalence at the given detection level. The other summed values (below the threshold) are agglomerated in an additional row taking the name indicated by other.name (by default "Other").

## Value

agglomerateByPrevalence returns a taxonomically-agglomerated object of the same class as x and based on prevalent taxonomic results.

## Examples

```
## Data can be aggregated based on prevalent taxonomic results
data(GlobalPatterns)
tse <- GlobalPatterns
tse <- transformAssay(tse, method = "relabundance")
tse <- agglomerateByPrevalence(
  tse,
  rank = "Phylum",
  assay.type = "relabundance",
  detection = 1/100,
  prevalence = 50/100)

tse

# Here data is aggregated at the taxonomic level "Phylum". The five phyla
# that exceed the population prevalence threshold of 50/100 represent the
# five first rows of the assay in the aggregated data. The sixth and last row
# named by default "Other" takes the summed up values of all the other phyla
# that are below the prevalence threshold.

assay(tse)[,1:5]
```

---

|                   |                                                                       |
|-------------------|-----------------------------------------------------------------------|
| agglomerateByRank | <i>Agglomerate data using taxonomic information or other grouping</i> |
|-------------------|-----------------------------------------------------------------------|

---

## Description

Agglomeration functions can be used to sum-up data based on specific criteria such as taxonomic ranks, variables or prevalence.

agglomerateByRank can be used to sum up data based on associations with certain taxonomic ranks, as defined in rowData. Only available [taxonomyRanks](#) can be used.

agglomerateByVariable and agglomerateByModule merge data on rows or columns of a SummarizedExperiment as defined by a factor alongside the chosen dimension. This function allows agglomeration of data based on other variables than taxonomy ranks. Metadata from the rowData or colData are retained

as defined by archetype. `assay` are agglomerated, i.e. summed up. If the assay contains values other than counts or absolute values, this can lead to meaningless values being produced.

`agglomerateByRanks` takes a `SummarizedExperiment`, splits it along the taxonomic ranks, aggregates the data per rank, converts the input to a `SingleCellExperiment` objects and stores the aggregated data as alternative experiments. `unsplitByRanks` takes these alternative experiments and flattens them again into a single `SummarizedExperiment`.

## Usage

```
agglomerateByRank(x, ...)

agglomerateByVariable(x, ...)

agglomerateByModule(x, ...)

agglomerateByRanks(x, ...)

unsplitByRanks(x, ...)

## S4 method for signature 'TreeSummarizedExperiment'
agglomerateByRank(
  x,
  rank = taxonomyRanks(x)[1],
  update.tree = agglomerateTree,
  agglomerate.tree = agglomerateTree,
  agglomerateTree = TRUE,
  ...
)

## S4 method for signature 'SingleCellExperiment'
agglomerateByRank(
  x,
  rank = taxonomyRanks(x)[1],
  altexp = NULL,
  altexp.rm = strip_altexp,
  strip_altexp = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
agglomerateByRank(
  x,
  rank = taxonomyRanks(x)[1],
  empty.rm = TRUE,
  empty.fields = c(NA, "", " ", "\t", "-", "_"),
  ...
)
```

```
## S4 method for signature 'TreeSummarizedExperiment'
agglomerateByVariable(
  x,
  by,
  group = f,
  f,
  update.tree = mergeTree,
  mergeTree = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
agglomerateByVariable(x, by, group = f, f, ...)

## S4 method for signature 'SummarizedExperiment'
agglomerateByModule(x, by, group, na.rm = FALSE)

## S4 method for signature 'SummarizedExperiment'
agglomerateByRanks(
  x,
  ranks = taxonomyRanks(x),
  na.rm = TRUE,
  as.list = FALSE,
  ...
)

## S4 method for signature 'SingleCellExperiment'
agglomerateByRanks(
  x,
  ranks = taxonomyRanks(x),
  na.rm = TRUE,
  as.list = FALSE,
  ...
)

## S4 method for signature 'TreeSummarizedExperiment'
agglomerateByRanks(
  x,
  ranks = taxonomyRanks(x),
  na.rm = TRUE,
  as.list = FALSE,
  ...
)

splitByRanks(x, ...)

## S4 method for signature 'SingleCellExperiment'
unsplitByRanks(
```

```

    x,
    ranks = taxonomyRanks(x),
    keep.dimred = keep_reducedDims,
    keep_reducedDims = FALSE,
    ...
)

## S4 method for signature 'TreeSummarizedExperiment'
unsplitByRanks(
  x,
  ranks = taxonomyRanks(x),
  keep.dimred = keep_reducedDims,
  keep_reducedDims = FALSE,
  ...
)

```

## Arguments

|                               |                                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>                | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                                                                                                                                                                                                                         |
| <code>...</code>              | arguments passed to <code>agglomerateByRank</code> function for <code>SummarizedExperiment</code> objects and other functions. See <a href="#">agglomerateByRank</a> for more details.                                                                                                                                                                                             |
| <code>rank</code>             | Character scalar. Defines a taxonomic rank. Must be a value of <code>taxonomyRanks()</code> function.                                                                                                                                                                                                                                                                              |
| <code>update.tree</code>      | Logical scalar. Should <code>rowTree()</code> also be merged? (Default: TRUE)                                                                                                                                                                                                                                                                                                      |
| <code>agglomerate.tree</code> | Deprecated. Use <code>update.tree</code> instead.                                                                                                                                                                                                                                                                                                                                  |
| <code>agglomerateTree</code>  | Deprecated. Use <code>update.tree</code> instead.                                                                                                                                                                                                                                                                                                                                  |
| <code>altexp</code>           | Character scalar or integer scalar. Specifies an alternative experiment containing the input data.                                                                                                                                                                                                                                                                                 |
| <code>altexp.rm</code>        | Logical scalar. Should alternative experiments be removed prior to agglomeration? This prevents too many nested alternative experiments by default. (Default: TRUE)                                                                                                                                                                                                                |
| <code>strip_altexp</code>     | Deprecated. Use <code>altexp.rm</code> instead.                                                                                                                                                                                                                                                                                                                                    |
| <code>empty.rm</code>         | Logical scalar. Defines whether rows including <code>empty.fields</code> in specified rank will be excluded. (Default: TRUE)                                                                                                                                                                                                                                                       |
| <code>empty.fields</code>     | Character vector. Defines which values should be regarded as empty. (Default: <code>c(NA, "", " ", "\t")</code> ). They will be removed if <code>na.rm = TRUE</code> before agglomeration.                                                                                                                                                                                         |
| <code>by</code>               | Character scalar. Determines if data is merged row-wise / for features ('rows') or column-wise / for samples ('cols'). Must be 'rows' or 'cols'.                                                                                                                                                                                                                                   |
| <code>group</code>            | Character scalar, character vector or factor vector. A column name from <code>rowData(x)</code> or <code>colData(x)</code> or alternatively a vector specifying how the merging is performed. If vector, the value must be the same length as <code>nrow(x)/ncol(x)</code> . Rows or columns corresponding to the same level will be merged. If <code>length(levels(group))</code> |

|                               |                                                                                                                                                                                                                                                                                                        |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                               | <code>== nrow(x)/ncol(x)</code> , <code>x</code> will be returned unchanged. For <code>agglomerateByModule</code> , <code>group</code> should specify one or several names of logical or numeric binary variables from the <code>rowData(x)/colData(x)</code> by which to agglomerate rows or columns. |
| <code>f</code>                | Deprecated. Use <code>group</code> instead.                                                                                                                                                                                                                                                            |
| <code>mergeTree</code>        | Deprecated. Use <code>update.tree</code> instead.                                                                                                                                                                                                                                                      |
| <code>na.rm</code>            | Logical scalar. Should NA values be omitted? (Default: TRUE)                                                                                                                                                                                                                                           |
| <code>ranks</code>            | Character vector. Defines taxonomic ranks. Must all be values of <code>taxonomyRanks()</code> function.                                                                                                                                                                                                |
| <code>as.list</code>          | Logical scalar. Should the list of <code>SummarizedExperiment</code> objects be returned by the function <code>agglomerateByRanks</code> as a <code>SimpleList</code> or stored in <code>altExps</code> ? (Default: FALSE)                                                                             |
| <code>keep.dimred</code>      | Logical scalar. Should the <code>reducedDims(x)</code> be transferred to the result? Please note, that this breaks the link between the data used to calculate the reduced dims. (Default: FALSE)                                                                                                      |
| <code>keep_reducedDims</code> | Deprecated. Use <code>keep.dimred</code> instead.                                                                                                                                                                                                                                                      |

## Details

Agglomeration sums up the values of assays at the specified taxonomic level. With certain assays, e.g. those that include binary or negative values, this summing can produce meaningless values. In those cases, consider performing agglomeration first, and then applying the transformation afterwards.

`agglomerateByVariable` works similarly to [sumCountsAcrossFeatures](#). However, additional support for `TreeSummarizedExperiment` was added and science field agnostic names were used. In addition the `archetype` argument lets the user select how to preserve row or column data. For merge data of assays the function from `scuttle` are used.

`agglomerateByModule` allows to agglomerate features or samples based on one or multiple variables of logical or numeric binary (0/1) type. It is particularly useful for agglomerating by taxonomic or functional modules, each defined by a logical or binary variable in the `rowData`, as features can belong to several modules.

`agglomerateByRanks` will use by default all available taxonomic ranks, but this can be controlled by setting `ranks` manually. NA values are removed by default, since they would not make sense, if the result should be used for `unsplitByRanks` at some point. The input data remains unchanged in the returned `SingleCellExperiment` objects.

`unsplitByRanks` will remove any NA value on each taxonomic rank so that no ambiguous data is created. In addition, a column `taxonomicLevel` is created or overwritten in the `rowData` to specify from which alternative experiment this originates from. This can also be used for [splitAltExps](#) to split the result along the same factor again. The input data from the base objects is not returned, only the data from the `altExp()`. Be aware that changes to `rowData` of the base object are not returned, whereas only the `colData` of the base object is kept.

## Value

`agglomerateByRank` returns a taxonomically-agglomerated, optionally-pruned object of the same class as `x`. `agglomerateByVariable` and `agglomerateByModule` return an object of the same class as `x` with the specified entries merged into one entry in all relevant components.

For `agglomerateByRanks`: If `as.list = TRUE` : SummarizedExperiment objects in a SimpleList  
 If `as.list = FALSE` : The SummarizedExperiment passed as a parameter and now containing the SummarizedExperiment objects in its `altExps`

For `unsplitByRanks`: `x`, with `rowData` and `assay` data replaced by the `unsplit` data. `colData` of `x` is kept as well and any existing `rowTree` is dropped as well, since existing `rowLinks` are not valid anymore.

## See Also

[splitOn](#) [unsplitOn](#) [agglomerateByVariable](#), [sumCountsAcrossFeatures](#), [agglomerateByRank](#), [altExps](#), [splitAltExps](#)

## Examples

```
### Agglomerate data based on taxonomic information

data(GlobalPatterns)
# print the available taxonomic ranks
colnames(rowData(GlobalPatterns))
taxonomyRanks(GlobalPatterns)

# agglomerate at the Family taxonomic rank
x1 <- agglomerateByRank(GlobalPatterns, rank="Family")
## How many taxa before/after agglomeration?
nrow(GlobalPatterns)
nrow(x1)

# Do not agglomerate the tree
x2 <- agglomerateByRank(
  GlobalPatterns, rank="Family", update.tree = FALSE)
nrow(x2) # same number of rows, but
rowTree(x1) # ... different
rowTree(x2) # ... tree

# If assay contains binary or negative values, summing might lead to
# meaningless values, and you will get a warning. In these cases, you might
# want to do agglomeration again at chosen taxonomic level.
tse <- transformAssay(GlobalPatterns, method = "pa")
tse <- agglomerateByRank(tse, rank = "Genus")
tse <- transformAssay(tse, method = "pa")

# Removing empty labels by setting empty.rm = TRUE
sum(is.na(rowData(GlobalPatterns)$Family))
x3 <- agglomerateByRank(GlobalPatterns, rank="Family", empty.rm = TRUE)
nrow(x3) # different from x2

# Because all the rownames are from the same rank, rownames do not include
# prefixes, in this case "Family:".
print(rownames(x3[1:3,]))

# To add them, use getTaxonomyLabels function.
rownames(x3) <- getTaxonomyLabels(x3, with.rank = TRUE)
```



```

print(rownames(x3[1:3,]))

# use 'empty.ranks.rm' to remove columns that include only NAs
x4 <- agglomerateByRank(
  GlobalPatterns, rank="Phylum", empty.ranks.rm = TRUE)
head(rowData(x4))

# If the assay contains NAs, you might want to specify na.rm=TRUE,
# since summing-up NAs lead to NA
x5 <- GlobalPatterns
# Replace first value with NA
assay(x5)[1,1] <- NA
x6 <- agglomerateByRank(x5, "Kingdom")
head( assay(x6) )
# Use na.rm=TRUE
x6 <- agglomerateByRank(x5, "Kingdom", na.rm = TRUE)
head( assay(x6) )

## Look at enterotype dataset...
data(enterotype)
## Print the available taxonomic ranks. Shows only 1 available rank,
## not useful for agglomerateByRank
taxonomyRanks(enterotype)

### Merge TreeSummarizedExperiments on rows and columns

data(esophagus)
esophagus
plot(rowTree(esophagus))
# Get a factor for merging
f <- factor(regmatches(rownames(esophagus),
  regexpr("[0-9]*_[0-9]*", rownames(esophagus))))
merged <- agglomerateByVariable(
  esophagus, by = "rows", f, update.tree = TRUE)
plot(rowTree(merged))
#
data(GlobalPatterns)
GlobalPatterns
merged <- agglomerateByVariable(
  GlobalPatterns, by = "cols", colData(GlobalPatterns)$SampleType)
merged

## Agglomerate by multiple modules

# Generate 30 random modules
N_module <- 30L
modules <- sample(
  c(TRUE, FALSE),
  size = nrow(tse) * N_module,
  prob = c(0.2, 0.8),
  replace = TRUE
)

```

```

# Convert modules to matrix
modules <- matrix(modules, nrow = nrow(tse))

# Add module names as colnames
colnames(modules) <- paste0("module_", seq_len(ncol(modules)))

# Add modules to rowData
rowData(tse) <- cbind(rowData(tse), modules)

# Extract module columns
module_columns <- grep("module_", colnames(rowData(tse)), value = TRUE)

# Agglomerate based on modules
tse_module <- agglomerateByModule(tse, by = 1, group = module_columns)

# Optionally, store results into altExp slot
altExp(tse, "modules") <- tse_module

data(GlobalPatterns)
# print the available taxonomic ranks
taxonomyRanks(GlobalPatterns)

# agglomerateByRanks
#
tse <- agglomerateByRanks(GlobalPatterns)
altExps(tse)
altExp(tse, "Kingdom")
altExp(tse, "Species")

# unsplitByRanks
tse <- unsplitByRanks(tse)
tse

```

---

calculatedDMN

*Dirichlet-Multinomial Mixture Model: Machine Learning for Microbiome Data*

---

## Description

These functions are accessors for functions implemented in the [DirichletMultinomial](#) package

## Usage

```
calculatedDMN(x, ...)
```

```
getDMN(x, name = "DMN", ...)
```

```
bestDMNFit(x, name = "DMN", type = c("laplace", "AIC", "BIC"), ...)
```

```

calculateDMNgroup(x, ...)

performDMNgroupCV(x, ...)

getBestDMNFit(x, name = "DMN", type = c("laplace", "AIC", "BIC"), ...)

## S4 method for signature 'ANY'
calculateDMN(
  x,
  k = 1,
  BPPARAM = SerialParam(),
  seed = runif(1, 0, .Machine$integer.max),
  ...
)

## S4 method for signature 'SummarizedExperiment'
calculateDMN(
  x,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  transposed = FALSE,
  ...
)

runDMN(x, name = "DMN", ...)

## S4 method for signature 'SummarizedExperiment'
getDMN(x, name = "DMN")

## S4 method for signature 'SummarizedExperiment'
bestDMNFit(x, name = "DMN", type = c("laplace", "AIC", "BIC"))

## S4 method for signature 'SummarizedExperiment'
getBestDMNFit(x, name = "DMN", type = c("laplace", "AIC", "BIC"))

## S4 method for signature 'ANY'
calculateDMNgroup(
  x,
  variable,
  k = 1,
  seed = runif(1, 0, .Machine$integer.max),
  ...
)

## S4 method for signature 'SummarizedExperiment'
calculateDMNgroup(
  x,

```

```

    variable,
    assay.type = assay_name,
    assay_name = exprs_values,
    exprs_values = "counts",
    transposed = FALSE,
    ...
)

## S4 method for signature 'ANY'
performDMNgroupCV(
  x,
  variable,
  k = 1,
  seed = runif(1, 0, .Machine$integer.max),
  ...
)

## S4 method for signature 'SummarizedExperiment'
performDMNgroupCV(
  x,
  variable,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  transposed = FALSE,
  ...
)

```

## Arguments

|              |                                                                                                                      |
|--------------|----------------------------------------------------------------------------------------------------------------------|
| x            | a numeric matrix with samples as rows or a <a href="#">SummarizedExperiment</a> object.                              |
| ...          | optional arguments not used.                                                                                         |
| name         | Character scalar. The name to store the result in <a href="#">metadata</a>                                           |
| type         | Character scalar. The type of measure used for the goodness of fit. One of 'laplace', 'AIC' or 'BIC'.                |
| k            | Numeric scalar. The number of Dirichlet components to fit. See <a href="#">dmn</a> . (Default: 1)                    |
| BPPARAM      | A <a href="#">BiocParallelParam</a> object specifying whether the calculation should be parallelized.                |
| seed         | Numeric scalar. Random number seed. See <a href="#">dmn</a>                                                          |
| assay.type   | Character scalar. Specifies the name of the assay used in calculation. (Default: "counts")                           |
| assay_name   | Deprecated. Use <code>assay.type</code> instead.                                                                     |
| exprs_values | Deprecated. Use <code>assay.type</code> instead.                                                                     |
| transposed   | Logical scalar. Is x transposed with samples in rows? (Default: FALSE)                                               |
| variable     | Character scalar. A variable from <code>colData</code> to use as a grouping variable. Must be a character of factor. |

**Value**

calculateDMN and getDMN return a list of DMN objects, one element for each value of k provided.

bestDMNFit returns the index for the best fit and getBestDMNFit returns a single DMN object.

calculateDMNgroup returns a [DMNGroup](#) object

performDMNgroupCV returns a `data.frame`

**See Also**

[DMN-class](#), [DMNGroup-class](#), [dmn](#), [dmngroup](#), [cvidmngroup](#), [accessors for DMN objects](#)

**Examples**

```
f1 <- system.file(package="DirichletMultinomial", "extdata", "Twins.csv")
counts <- as.matrix(read.csv(f1, row.names=1))
f1 <- system.file(package="DirichletMultinomial", "extdata", "TwinStudy.t")
pheno0 <- scan(f1)
lvls <- c("Lean", "Obese", "Overwt")
pheno <- factor(lvls[pheno0 + 1], levels=lvls)
colData <- DataFrame(pheno = pheno)

tse <- TreeSummarizedExperiment(assays = list(counts = counts),
                                colData = colData)

library(bluster)

# Compute DMM algorithm and store result in metadata
tse <- addCluster(tse, name = "DMM", DmmParam(k = 1:3, type = "laplace"),
                 by = "samples", full = TRUE)

# Get the list of DMN objects
metadata(tse)$DMM$dmm

# Get and display which objects fits best
bestFit <- metadata(tse)$DMM$best
bestFit

# Get the model that generated the best fit
bestModel <- metadata(tse)$DMM$dmm[[bestFit]]
bestModel

# Get the sample-cluster assignment probability matrix
head(metadata(tse)$DMM$prob)

# Get the weight of each component for the best model
bestModel@mixture$Weight
```

---

|                  |                                                               |
|------------------|---------------------------------------------------------------|
| convertFromDADA2 | Create a TreeSummarizedExperiment object from 'DADA2' results |
|------------------|---------------------------------------------------------------|

---

## Description

Create a TreeSummarizedExperiment object from 'DADA2' results

## Usage

```
convertFromDADA2(...)
```

## Arguments

... Additional arguments. For convertFromDADA2, see mergePairs function for more details.

## Details

convertFromDADA2 is a wrapper for the mergePairs function from the dada2 package. A count matrix is constructed via makeSequenceTable(mergePairs(...)) and rownames are dynamically created as ASV(N) with N from 1 to nrow of the count tables. The colnames and rownames from the output of makeSequenceTable are stored as colnames and in the referenceSeq slot of the TreeSummarizedExperiment, respectively.

## Value

convertFromDADA2 returns an object of class [TreeSummarizedExperiment](#)

## Examples

```
### Coerce DADA2 results to a TreeSE object
if(requireNamespace("dada2")) {
  fnF <- system.file("extdata", "sam1F.fastq.gz", package="dada2")
  fnR = system.file("extdata", "sam1R.fastq.gz", package="dada2")
  dadaF <- dada2::dada(fnF, selfConsist=TRUE)
  dadaR <- dada2::dada(fnR, selfConsist=TRUE)

  tse <- convertFromDADA2(dadaF, fnF, dadaR, fnR)
  tse
}
```

---

|               |                                                                         |
|---------------|-------------------------------------------------------------------------|
| convertToBIOM | <i>Convert a TreeSummarizedExperiment object to/from 'BIOM' results</i> |
|---------------|-------------------------------------------------------------------------|

---

## Description

For convenience, a few functions are available to convert BIOM, DADA2 and phyloseq objects to [TreeSummarizedExperiment](#) objects, and [TreeSummarizedExperiment](#) objects to phyloseq objects.

## Usage

```
convertToBIOM(x, assay.type = "counts", ...)

importBIOM(file, ...)

convertFromBIOM(
  x,
  prefix.rm = removeTaxaPrefixes,
  removeTaxaPrefixes = FALSE,
  rank.from.prefix = rankFromPrefix,
  rankFromPrefix = FALSE,
  artifact.rm = remove.artifacts,
  remove.artifacts = FALSE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
convertToBIOM(x, assay.type = "counts", ...)
```

## Arguments

|                    |                                                                                                                                                                                                   |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x                  | <a href="#">TreeSummarizedExperiment</a>                                                                                                                                                          |
| assay.type         | Character scalar. The name of assay. (Default: "counts")                                                                                                                                          |
| ...                | Additional arguments. Not used currently.                                                                                                                                                         |
| file               | BIOM file location                                                                                                                                                                                |
| prefix.rm          | Logical scalar. Should taxonomic prefixes be removed? The prefixes is removed only from detected taxa columns meaning that rank.from.prefix should be enabled in the most cases. (Default: FALSE) |
| removeTaxaPrefixes | Deprecated. Use prefix.rm instead.                                                                                                                                                                |
| rank.from.prefix   | Logical scalar. If file does not have taxonomic ranks on feature table, should they be scraped from prefixes? (Default: FALSE)                                                                    |
| rankFromPrefix     | Deprecated. Use rank.from.prefix instead.                                                                                                                                                         |

`artifact.rm` Logical scalar. If file have some taxonomic character naming artifacts, should they be removed. (default (Default: FALSE))

`remove.artifacts` Deprecated. Use `artifact.rm` instead.

### Details

`convertFromBIOM` coerces a `biom` object to a `TreeSummarizedExperiment` object.

`convertToBIOM` coerces a `TreeSummarizedExperiment` object to a `biom` object.

`importBIOM` loads a BIOM file and creates a `TreeSummarizedExperiment` object from the BIOM object contained in the loaded file.

### Value

`convertFromBIOM` returns an object of class `TreeSummarizedExperiment`

`importBIOM` returns an object of class `TreeSummarizedExperiment`

### See Also

`importQIIME2` `importMothur`

`importMetaPhlAn` `convertFromPhyloseq` `convertFromBIOM` `convertFromDADA2` `importQIIME2`  
`importMothur` `importHUMANn`

### Examples

```
# Convert BIOM results to a TreeSE
# Load biom file
library(biomformat)
biom_file <- system.file("extdata", "rich_dense_otu_table.biom",
                        package = "biomformat")

# Make TreeSE from BIOM object
biom_object <- biomformat::read_biom(biom_file)
tse <- convertFromBIOM(biom_object)

# Convert TreeSE object to BIOM
biom <- convertToBIOM(tse)

# Load biom file
library(biomformat)
biom_file <- system.file(
  "extdata", "rich_dense_otu_table.biom", package = "biomformat")

# Make TreeSE from biom file
tse <- importBIOM(biom_file)

# Get taxonomyRanks from prefixes and remove prefixes
tse <- importBIOM(
  biom_file, rank.from.prefix = TRUE, prefix.rm = TRUE)
```



```
# Load another biom file
biom_file <- system.file(
  "extdata", "Aggregated_humanization2.biom", package = "mia")

# Clean artifacts from taxonomic data
tse <- importBIOM(biom_file, artifact.rm = TRUE)
```

---

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| convertToPhyloseq | Create a TreeSummarizedExperiment object from a phyloseq object |
|-------------------|-----------------------------------------------------------------|

---

## Description

Create a TreeSummarizedExperiment object from a phyloseq object

Create a phyloseq object from a TreeSummarizedExperiment object

## Usage

```
convertToPhyloseq(x, ...)

convertFromPhyloseq(x)

## S4 method for signature 'SummarizedExperiment'
convertToPhyloseq(x, assay.type = "counts", assay_name = NULL, ...)

## S4 method for signature 'TreeSummarizedExperiment'
convertToPhyloseq(x, tree.name = tree_name, tree_name = "phylo", ...)
```

## Arguments

|            |                                                                                                                            |
|------------|----------------------------------------------------------------------------------------------------------------------------|
| x          | a <a href="#">TreeSummarizedExperiment</a> object                                                                          |
| ...        | Additional arguments. Not used currently.                                                                                  |
| assay.type | Character scalar. Specifies the name of assay used. (Default: "counts")                                                    |
| assay_name | Deprecated. Use assay.type instead.                                                                                        |
| tree.name  | Character scalar. Specifies the name of the tree to be included in the phyloseq object that is created, (Default: "phylo") |
| tree_name  | Deprecated. Use tree.name instead.                                                                                         |

## Details

convertFromPhyloseq converts phyloseq objects into [TreeSummarizedExperiment](#) objects. All data stored in a phyloseq object is transferred.

convertToPhyloseq creates a phyloseq object from a [TreeSummarizedExperiment](#) object. By using assay.type, it is possible to specify which table from assay is added to the phyloseq object.

**Value**

convertFromPhyloseq returns an object of class `TreeSummarizedExperiment`

convertToPhyloseq returns an object of class `phyloseq`

**Examples**

```
### Coerce a phyloseq object to a TreeSE object
if (requireNamespace("phyloseq")) {
  data(GlobalPatterns, package="phyloseq")
  convertFromPhyloseq(GlobalPatterns)
  data(enterotype, package="phyloseq")
  convertFromPhyloseq(enterotype)
  data(esophagus, package="phyloseq")
  convertFromPhyloseq(esophagus)
}

### Coerce a TreeSE object to a phyloseq object
# Get tse object
data(GlobalPatterns)
tse <- GlobalPatterns

# Create a phyloseq object from it
phy <- convertToPhyloseq(tse)
phy

# By default the chosen table is counts, but if there are other tables,
# they can be chosen with assay.type.

# Counts relative abundances table
tse <- transformAssay(tse, method = "relabundance")
phy2 <- convertToPhyloseq(tse, assay.type = "relabundance")
phy2
```

---

deprecate

---

*These functions will be deprecated. Please use other functions instead.*


---

**Description**

These functions will be deprecated. Please use other functions instead.

**Usage**

```
cluster(x, ...)

## S4 method for signature 'SummarizedExperiment'
cluster(x, ...)
```

```
addTaxonomyTree(x, ...)

## S4 method for signature 'SummarizedExperiment'
addTaxonomyTree(x, ...)

taxonomyTree(x, ...)

## S4 method for signature 'SummarizedExperiment'
taxonomyTree(x, ...)

mergeRows(x, ...)

## S4 method for signature 'SummarizedExperiment'
mergeRows(x, ...)

## S4 method for signature 'TreeSummarizedExperiment'
mergeRows(x, ...)

mergeCols(x, ...)

## S4 method for signature 'SummarizedExperiment'
mergeCols(x, ...)

## S4 method for signature 'TreeSummarizedExperiment'
mergeCols(x, ...)

mergeFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
mergeFeatures(x, ...)

## S4 method for signature 'TreeSummarizedExperiment'
mergeFeatures(x, ...)

mergeSamples(x, ...)

## S4 method for signature 'SummarizedExperiment'
mergeSamples(x, ...)

## S4 method for signature 'TreeSummarizedExperiment'
mergeSamples(x, ...)

mergeFeaturesByRank(x, ...)

## S4 method for signature 'SummarizedExperiment'
mergeFeaturesByRank(x, ...)

## S4 method for signature 'SingleCellExperiment'
```

```
mergeFeaturesByRank(x, ...)

mergeFeaturesByPrevalence(x, ...)

## S4 method for signature 'SummarizedExperiment'
mergeFeaturesByPrevalence(x, ...)

getExperimentCrossAssociation(x, ...)

## S4 method for signature 'MultiAssayExperiment'
getExperimentCrossAssociation(x, ...)

## S4 method for signature 'SummarizedExperiment'
getExperimentCrossAssociation(x, ...)

## S4 method for signature 'TreeSummarizedExperiment'
mergeFeaturesByRank(x, ...)

testExperimentCrossAssociation(x, ...)

## S4 method for signature 'ANY'
testExperimentCrossAssociation(x, ...)

testExperimentCrossCorrelation(x, ...)

## S4 method for signature 'ANY'
testExperimentCrossCorrelation(x, ...)

getExperimentCrossCorrelation(x, ...)

## S4 method for signature 'ANY'
getExperimentCrossCorrelation(x, ...)

loadFromBiom(...)

loadFromQIIME2(...)

readQZA(...)

loadFromMothur(...)

loadFromMetaphlan(...)

loadFromHumann(...)

countDominantFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
```

```
countDominantFeatures(x, ...)

subsetByRareTaxa(x, ...)

## S4 method for signature 'ANY'
subsetByRareTaxa(x, ...)

subsetByRareFeatures(x, ...)

## S4 method for signature 'ANY'
subsetByRareFeatures(x, ...)

subsetByPrevalentTaxa(x, ...)

## S4 method for signature 'ANY'
subsetByPrevalentTaxa(x, ...)

subsetByPrevalentFeatures(x, ...)

## S4 method for signature 'ANY'
subsetByPrevalentFeatures(x, ...)

countDominantTaxa(x, ...)

## S4 method for signature 'SummarizedExperiment'
countDominantTaxa(x, ...)

full_join(x, ...)

## S4 method for signature 'ANY'
full_join(x, ...)

inner_join(x, ...)

## S4 method for signature 'ANY'
inner_join(x, ...)

left_join(x, ...)

## S4 method for signature 'ANY'
left_join(x, ...)

right_join(x, ...)

## S4 method for signature 'ANY'
right_join(x, ...)

plotNMDS(x, ...)
```

```
estimateDivergence(x, ...)

## S4 method for signature 'SummarizedExperiment'
estimateDivergence(x, ...)

meltAssay(x, ...)

## S4 method for signature 'SummarizedExperiment'
meltAssay(x, ...)

transformSamples(x, ...)

## S4 method for signature 'SummarizedExperiment'
transformSamples(x, ...)

ZTransform(x, ...)

## S4 method for signature 'SummarizedExperiment'
ZTransform(x, ...)

relAbundanceCounts(x, ...)

## S4 method for signature 'SummarizedExperiment'
relAbundanceCounts(x, ...)

transformCounts(x, ...)

transformFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
transformFeatures(x, ...)

getUniqueFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
getUniqueFeatures(x, ...)

getUniqueTaxa(x, ...)

## S4 method for signature 'SummarizedExperiment'
getUniqueTaxa(x, ...)

getTopFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
getTopFeatures(x, ...)
```

```
getTopTaxa(x, ...)

## S4 method for signature 'SummarizedExperiment'
getTopTaxa(x, ...)

getRareFeatures(x, ...)

## S4 method for signature 'ANY'
getRareFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
getRareFeatures(x, ...)

getRareTaxa(x, ...)

## S4 method for signature 'ANY'
getRareTaxa(x, ...)

## S4 method for signature 'SummarizedExperiment'
getRareTaxa(x, ...)

getPrevalentFeatures(x, ...)

## S4 method for signature 'ANY'
getPrevalentFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
getPrevalentFeatures(x, ...)

getPrevalentTaxa(x, ...)

## S4 method for signature 'ANY'
getPrevalentTaxa(x, ...)

## S4 method for signature 'SummarizedExperiment'
getPrevalentTaxa(x, ...)

subsampleCounts(x, ...)

## S4 method for signature 'SummarizedExperiment'
subsampleCounts(x, ...)

addPerSampleDominantFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
addPerSampleDominantFeatures(x, ...)

addPerSampleDominantTaxa(x, ...)
```

```
## S4 method for signature 'SummarizedExperiment'
addPerSampleDominantTaxa(x, ...)

perSampleDominantFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
perSampleDominantFeatures(x, ...)

perSampleDominantTaxa(x, ...)

## S4 method for signature 'SummarizedExperiment'
perSampleDominantTaxa(x, ...)

makePhyloseqFromTreeSE(x, ...)

## S4 method for signature 'SummarizedExperiment'
makePhyloseqFromTreeSE(x)

## S4 method for signature 'TreeSummarizedExperiment'
makePhyloseqFromTreeSE(x)

makePhyloseqFromTreeSummarizedExperiment(x)

## S4 method for signature 'ANY'
makePhyloseqFromTreeSummarizedExperiment(x)

makeTreeSummarizedExperimentFromPhyloseq(x)

## S4 method for signature 'ANY'
makeTreeSummarizedExperimentFromPhyloseq(x)

makeTreeSEFromBiom(...)

makeTreeSummarizedExperimentFromBiom(...)

makeTreeSEFromDADA2(...)

makeTreeSummarizedExperimentFromDADA2(...)

makeTreeSEFromPhyloseq(x)

estimateEvenness(x, ...)

## S4 method for signature 'ANY'
estimateEvenness(x, ...)

estimateRichness(x, ...)
```



```
## S4 method for signature 'ANY'
estimateRichness(x, ...)

estimateDiversity(x, ...)

## S4 method for signature 'ANY'
estimateDiversity(x, ...)

estimateFaith(x, ...)

## S4 method for signature 'ANY'
estimateFaith(x, ...)

estimateDominance(x, ...)

## S4 method for signature 'ANY'
estimateDominance(x, ...)

subsetSamples(x, ...)

subsetFeatures(x, ...)

subsetTaxa(x, ...)

## S4 method for signature 'SummarizedExperiment'
subsetSamples(x, ...)

## S4 method for signature 'SummarizedExperiment'
subsetFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
subsetTaxa(x, ...)

relabundance(x, ...)

relabundance(x) <- value

## S4 method for signature 'SummarizedExperiment'
relabundance(x)

## S4 replacement method for signature 'SummarizedExperiment'
relabundance(x) <- value

runOverlap(x, ...)

## S4 method for signature 'SummarizedExperiment'
runOverlap(x, ...)
```

```

calculateOverlap(x, ...)

## S4 method for signature 'ANY'
calculateOverlap(x, ...)

calculateJSD(x, ...)

## S4 method for signature 'ANY'
calculateJSD(x, ...)

runJSD(x, ...)

## S4 method for signature 'SummarizedExperiment'
runJSD(x, ...)

calculateUnifrac(x, ...)

## S4 method for signature 'ANY'
calculateUnifrac(x, ...)

runUnifrac(mat, tree, ...)

```

### Arguments

|       |                                                |
|-------|------------------------------------------------|
| x     | A <a href="#">SummarizedExperiment</a> object. |
| ...   | Additional parameters. See dedicated function. |
| value | a matrix to store as the ‘relabundance’ assay  |
| mat   | An abundance matrix                            |
| tree  | A phylogenetic tree                            |

---

dmn\_se

*Twins’ microbiome data from 278 individuals*


---

### Description

dmn\_se is a dataset on twins’ microbiome where samples are stratified by their community composition through Dirichlet Multinomial Mixtures (DMM). It was derived from the **DirichletMultinomial** package.

### Usage

```
data(dmn_se)
```

**Format**

A SummarizedExperiment with 130 features and 278 samples. The rowData contains no taxonomic information. The colData includes:

**pheno** participant's weight condition (Lean, Overwt and Obese)

**Author(s)**

Turnbaugh, PJ et al.

**References**

Holmes I, Harris K, Quince C (2012). Dirichlet Multinomial Mixtures: Generative Models for Microbial Metagenomics. PLoS ONE 7(2): e30126. <https://doi.org/10.1371/journal.pone.0030126>

Turnbaugh PJ, Hamady M, Yatsunenko T, Cantarel BL, Duncan A, et al. (2009). A core gut microbiome in obese and lean twins. Nature 457: 480–484. <https://doi.org/10.1038/nature07540>

**See Also**

[mia-datasets](#) [calculateDMN](#)

---

enterotype

*Human gut microbiome dataset from 22 subjects based on shotgun DNA sequencing*

---

**Description**

The enterotype data of the human gut microbiome includes taxonomic profiling for 280 fecal samples from 22 subjects based on shotgun DNA sequencing. The authors claimed that the data naturally clumps into three community-level clusters, or "enterotypes", that are not immediately explained by sequencing technology or demographic features of the subjects. In a later addendum from 2014 the authors stated that enterotypes should not be seen as discrete clusters, but as a way of stratifying samples to reduce complexity. It was converted into a TreeSummarizedExperiment from the **phyloseq** package.

**Usage**

`data(enterotype)`

**Format**

A TreeSummarizedExperiment with 553 features and 280 samples. The rowData contains taxonomic information at Genus level. The colData includes:

**Enterotype** enterotype the sample belongs to (1, 2 and 3)

**Sample\_ID** sample ID of samples from all studies

**SeqTech** sequencing technology

**SampleID** sample ID of complete samples

**Project** original project from which sample was obtained (gill06, turnbaugh09, MetaHIT, MicroObes, MicroAge and kurokawa07)

**Nationality** participant's nationality (american, danish, spanish, french, italian and japanese)

**Gender** participant's gender (F or M)

**Age** participant's age (0.25 – 87)

**ClinicalStatus** participant's clinical status (healthy, obese, CD, UC and elderly)

#### Author(s)

Arumugam, M., Raes, J., et al.

#### Source

[http://www.bork.embl.de/Docu/Arumugam\\_et\\_al\\_2011/downloads.html](http://www.bork.embl.de/Docu/Arumugam_et_al_2011/downloads.html)

#### References

Arumugam, M., et al. (2011). Enterotypes of the human gut microbiome. *Nature*, 473(7346), 174-180. <https://doi.org/10.1038/nature09944>

Arumugam, M., et al. (2014). Addendum: Enterotypes of the human gut microbiome. *Nature* 506, 516 (2014). <https://doi.org/10.1038/nature13075>

#### See Also

[mia-datasets](#)

---

esophagus

*Human esophageal community from 3 individuals*

---

#### Description

This small dataset from a human esophageal community includes 3 samples from 3 human adults based on biopsies analysed with 16S rDNA PCR. The 16S rRNA sequence processing is provided in the *mothur* wiki from the link below. It was converted into a *TreeSummarizedExperiment* from the **phyloseq** package.

#### Usage

```
data(esophagus)
```

#### Format

A *TreeSummarizedExperiment* with 58 features and 3 samples. The *rowData* contains no taxonomic information. The *colData* is empty.

**Author(s)**

Pei et al. <zhiheng.pei@med.nyu.edu>.

**Source**

[http://www.mothur.org/wiki/Esophageal\\_community\\_analysis](http://www.mothur.org/wiki/Esophageal_community_analysis)

**References**

Pei, Z., Bini, E. J., Yang, L., Zhou, M., Francois, F., & Blaser, M. J. (2004). Bacterial biota in the human distal esophagus. *Proceedings of the National Academy of Sciences of the United States of America*, 101(12), 4250-4255. <https://doi.org/10.1073/pnas.0306398101>

McMurdie, J. & Holmes, S. (2013) *phyloseq*: An R Package for reproducible interactive analysis and graphics of microbiome census data. *PLoS ONE*. 8(4):e61217. <https://doi.org/10.1371/journal.pone.0061217>

**See Also**

[mia-datasets](#)

---

getAbundant

*Determine abundant and rare taxa. Rare taxa can be further classified to conditionally rare and permanently rare.*

---

**Description**

These functions determine abundant and rare taxa based on the abundances of taxa. Compared to [getPrevalent](#) and [getRare](#), these functions determine abundant and rare taxa based on abundance while the first mentioned are based on prevalence.

**Usage**

```
getAbundant(x, ...)  
  
getLowAbundant(x, ...)  
  
getConditionallyLowAbundant(x, ...)  
  
getPermanentlyLowAbundant(x, ...)  
  
getAbundanceClass(x, ...)  
  
addAbundanceClass(x, ...)  
  
## S4 method for signature 'SingleCellExperiment'  
getAbundant(x, ...)
```

```
## S4 method for signature 'SummarizedExperiment'
getAbundant(x, assay.type = "relabundance", ...)

## S4 method for signature 'ANY'
getAbundant(x, abundant.th = 1/100, ...)

## S4 method for signature 'SingleCellExperiment'
getLowAbundant(x, ...)

## S4 method for signature 'SummarizedExperiment'
getLowAbundant(x, assay.type = "relabundance", abundant.th = 1/100, ...)

## S4 method for signature 'ANY'
getLowAbundant(x, abundant.th = 1/100, ...)

## S4 method for signature 'SingleCellExperiment'
getConditionallyLowAbundant(x, ...)

## S4 method for signature 'SummarizedExperiment'
getConditionallyLowAbundant(x, assay.type = "relabundance", ...)

## S4 method for signature 'ANY'
getConditionallyLowAbundant(x, abundant.th = 1/100, crt.th = 100, ...)

## S4 method for signature 'SingleCellExperiment'
getPermanentlyLowAbundant(x, ...)

## S4 method for signature 'SummarizedExperiment'
getPermanentlyLowAbundant(x, assay.type = "relabundance", ...)

## S4 method for signature 'ANY'
getPermanentlyLowAbundant(x, abundant.th = 1/100, prt.th = 5, ...)

## S4 method for signature 'SingleCellExperiment'
getAbundanceClass(x, ...)

## S4 method for signature 'SummarizedExperiment'
getAbundanceClass(x, assay.type = "relabundance", ...)

## S4 method for signature 'ANY'
getAbundanceClass(x, abundant.th = 1/100, crt.th = 100, prt.th = 5, ...)

## S4 method for signature 'SingleCellExperiment'
addAbundanceClass(x, ...)

## S4 method for signature 'SummarizedExperiment'
addAbundanceClass(x, name = "abundance_class", ...)
```

**Arguments**

|                          |                                                                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>           | a <code>SummarizedExperiment</code> object.                                                                                       |
| <code>...</code>         | additional arguments.                                                                                                             |
| <code>assay.type</code>  | Character scalar. Specifies the name of assay used in calculation. (Default: "relabundance")                                      |
| <code>abundant.th</code> | Numeric scalar. Specifies threshold that is used to separate abundant features from rare. (Default: 1/100)                        |
| <code>crt.th</code>      | Numeric scalar. Specifies threshold that is used to separate conditionally rare features from other rare features. (Default: 100) |
| <code>prt.th</code>      | Numeric scalar. Specifies threshold that is used to separate permanently rare features from other rare features. (Default: 5)     |
| <code>name</code>        | Character scalar. Specifies name of column in <code>rowData</code> where the results will be stored. (Default: "abundance_class") |

**Details**

These functions identify abundant and rare taxa in a dataset. Abundant taxa are characterized by high average abundance across the dataset, while rare taxa are characterized by consistently low abundance.

Conditionally rare taxa exhibit variable abundance, being abundant in some samples and rare in others. In contrast, permanently rare taxa consistently maintain low abundance across all samples.

- Abundant taxa: Taxa with an average abundance exceeding `abundant.th`.
- Low abundant / rare taxa: Taxa with an average abundance not exceeding `abundant.th`. Optionally, if specified, they must also satisfy the condition  $crt.th \geq \frac{abundance_{max}}{abundance_{min}} > prt.th$ .
- Conditionally rare or low abundant taxa (CRT): Taxa with an average abundance not exceeding `abundant.th` and with a maximum-to-minimum abundance ratio ( $\frac{abundance_{max}}{abundance_{min}}$ ) greater than `crt.th`.
- Permanently rare or low abundant taxa (PRT): Taxa with an average abundance not exceeding `abundant.th` and with a maximum-to-minimum abundance ratio ( $\frac{abundance_{max}}{abundance_{min}}$ ) less than or equal to `prt.th`.

**Value**

For `getAbundant`, `getLowAbundant`, `getConditionallyLowAbundant`, and `getPermanentlyLowAbundant` a vector of taxa. For `getAbundanceClass` a vector of abundance classes for each feature. For `addAbundanceClass`, a `SummarizedExperiment` object.

**References**

Sizhong Y. et al. (2017) Community structure of rare methanogenic archaea: insight from a single functional group- *FEMS Microbiol. Ecol.* 93(11). <https://doi.org/10.1093/femsec/fix126>

**See Also**

[getPrevalent](#) and [getRare](#)

**Examples**

```

data(GlobalPatterns)
tse <- GlobalPatterns

# Agglomerate to family level
tse <- agglomerateByRank(tse, rank = "Family")
# Transform to relative abundances. Note that we add pseudocount. This is
# because otherwise we cannot calculate CRT and PRT due to zeroes and
# zero division in calculating abundance ratio.
tse <- transformAssay(tse, method = "relabundance", pseudocount = TRUE)

# Get abundant taxa
abundant <- getAbundant(tse, assay.type = "relabundance")
abundant |> head()

# Get all rare taxa that have average relative abundance below 10%
rare <- getLowAbundant(
  tse, assay.type = "relabundance", abundant.th = 10/100)
rare |> head()

# Get rare taxa that are not permanently or conditionally rare
rare <- getLowAbundant(
  tse, assay.type = "relabundance", prt.th = 5, crt.th = 100)
rare |> head()

# Get permanently rare taxa
prt <- getPermanentlyLowAbundant(
  tse, assay.type = "relabundance", prt.th = 5)
prt |> head()

# Get conditionally rare taxa
prt <- getConditionallyLowAbundant(
  tse, assay.type = "relabundance", crt.th = 100)
prt |> head()

# To classify all features, one can use *AbundantClass function
tse <- addAbundanceClass(tse)
# When one uses add* function, the results are stored to rowData
rowData(tse)

```

**Description**

These functions perform Canonical Correspondence Analysis on data stored in a SummarizedExperiment.



**Usage**

```
getCCA(x, ...)  
  
addCCA(x, ...)  
  
getRDA(x, ...)  
  
addRDA(x, ...)  
  
calculateCCA(x, ...)  
  
runCCA(x, ...)  
  
## S4 method for signature 'ANY'  
getCCA(x, formula, data, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
getCCA(  
  x,  
  formula = NULL,  
  col.var = variables,  
  variables = NULL,  
  test.signif = TRUE,  
  assay.type = assay_name,  
  assay_name = exprs_values,  
  exprs_values = "counts",  
  ...  
)  
  
## S4 method for signature 'SingleCellExperiment'  
addCCA(x, altexp = NULL, name = "CCA", ...)  
  
calculateRDA(x, ...)  
  
runRDA(x, ...)  
  
## S4 method for signature 'ANY'  
getRDA(x, formula, data, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
getRDA(  
  x,  
  formula = NULL,  
  col.var = variables,  
  variables = NULL,  
  test.signif = TRUE,  
  assay.type = assay_name,  
  assay_name = exprs_values,
```

```

    exprs_values = NULL,
    dis.name = NULL,
    ...
)

## S4 method for signature 'SingleCellExperiment'
addRDA(x, altexp = NULL, name = "RDA", ...)

```

## Arguments

|             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x           | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| ...         | additional arguments passed to <code>vegan::cca</code> or <code>vegan::dbRDA</code> and other internal functions. <ul style="list-style-type: none"> <li>• <code>method</code>: a dissimilarity measure to be applied in dbRDA and possible following homogeneity test. (Default: "euclidean")</li> <li>• <code>scale</code>: Logical scalar. Should the expression values be standardized? <code>scale</code> is disabled when using *RDA functions. Please scale before performing RDA. (Default: TRUE)</li> <li>• <code>na.action</code>: function. Action to take when missing values for any of the variables in formula are encountered. (Default: <code>na.fail</code>)</li> <li>• <code>full</code>: Logical scalar. Should all the results from the significance calculations be returned. When FALSE, only summary tables are returned. (Default: FALSE)</li> <li>• <code>homogeneity.test</code>: Character scalar. Specifies the significance test used to analyse <a href="#">vegan::betadisper</a> results. Options include 'permanova' (<a href="#">vegan::permutest</a>), 'anova' (<a href="#">stats::anova</a>) and 'tukeyhsd' (<a href="#">stats::TukeyHSD</a>). (Default: "permanova")</li> <li>• <code>permutations</code>: Integer scalar. Specifies the number of permutations for significance testing in <code>vegan::anova.cca</code>. (Default: 999)</li> <li>• <code>subset.result</code>: Logical result. Specifies whether to subset x to match the result if some samples were removed during calculation. (Default: TRUE)</li> <li>• <code>binary</code>: Logical scalar. Whether to perform presence/absence transformation before dissimilarity calculation. For Jaccard index the default is TRUE. For other dissimilarity metrics, please see <a href="#">vegdist</a>.</li> </ul> |
| formula     | formula. If x is a <a href="#">SummarizedExperiment</a> a formula can be supplied. Based on the right-hand side of the given formula <code>colData</code> is subset to <code>col.var</code> . <code>col.var</code> and formula can be missing, which turns the CCA analysis into a CA analysis and dbRDA into PCoA/MDS.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| data        | <code>data.frame</code> or coercible to one. The covariance table including covariates defined by formula.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| col.var     | Character scalar. When x is a <a href="#">SummarizedExperiment</a> , <code>col.var</code> can be used to specify variables from <code>colData</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| variables   | Deprecated. Use <code>col.var</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| test.signif | Logical scalar. Should the PERMANOVA and analysis of multivariate homogeneity of group dispersions be performed. (Default: TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

|                           |                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------|
| <code>assay.type</code>   | Character scalar. Specifies the name of assay used in calculation. (Default: NULL)                                   |
| <code>assay_name</code>   | Deprecated. Use <code>assay.type</code> instead.                                                                     |
| <code>exprs_values</code> | Deprecated. Use <code>assay.type</code> instead.                                                                     |
| <code>altexp</code>       | Character scalar or integer scalar. Specifies an alternative experiment containing the input data.                   |
| <code>name</code>         | Character scalar. A name for the <code>reducedDim()</code> where results will be stored. (Default: "CCA")            |
| <code>dis.name</code>     | Character scalar. Specifies the name of dissimilarity matrix from metadata slot used in calculation. (Default: NULL) |

### Details

\*CCA functions utilize `vegan::cca` and \*RDA functions `vegan::dbRDA`. By default, `dbRDA` is done with euclidean distances, which is equivalent to RDA. `col.var` and `formula` can be missing, which turns the CCA analysis into a CA analysis and `dbRDA` into PCoA/MDS.

Significance tests are done with `vegan::anova.cca` (PERMANOVA). Group dispersion, i.e., homogeneity within groups is analyzed with [vegan::betadisper](#) (multivariate homogeneity of groups dispersions (variances)) and statistical significance of homogeneity is tested with a test specified by `homogeneity.test` parameter.

### Value

For `getCCA` a matrix with samples as rows and CCA dimensions as columns. Attributes include output from [scores](#), eigenvalues, the `cca/rda` object and significance analysis results.

For `addCCA` a modified `x` with the results stored in `reducedDim` as the given name.

### See Also

For more details on the actual implementation see [cca](#) and [dbrda](#)

### Examples

```
library(miaViz)
data("enterotype", package = "mia")
tse <- enterotype

# Perform CCA and exclude any sample with missing ClinicalStatus
tse <- addCCA(
  tse,
  assay.type = "counts",
  formula = data ~ ClinicalStatus,
  na.action = na.exclude
)

# Plot CCA
plotCCA(tse, "CCA", colour_by = "ClinicalStatus")

# Fetch significance results
```

```

getReducedDimAttribute(tse, dimred = "CCA", name = "significance")

tse <- transformAssay(tse, method = "relabundance")

# Specify dissimilarity measure
tse <- addRDA(
  tse,
  formula = data ~ ClinicalStatus,
  assay.type = "relabundance",
  method = "bray",
  name = "RDA_bray",
  na.action = na.exclude
)

# To scale values when using *RDA functions, use
# transformAssay(MARGIN = "features", ...)
tse <- transformAssay(tse, method = "standardize", MARGIN = "features")

# Data might include taxa that do not vary. Remove those because after
# z-transform their value is NA
tse <- tse[rowSums(is.na(assay(tse, "standardize"))) == 0, ]

# Calculate RDA
tse <- addRDA(
  tse,
  formula = data ~ ClinicalStatus,
  assay.type = "standardize",
  name = "rda_scaled",
  na.action = na.omit
)

# Plot RDA
plotRDA(tse, "rda_scaled", colour_by = "ClinicalStatus")

# A common choice along with PERMANOVA is ANOVA when statistical significance
# of homogeneity of groups is analysed. Moreover, full significance test
# results can be returned.
tse <- transformAssay(tse, method = "clr", pseudocount = 1)
tse <- addRDA(
  tse,
  assay.type = "clr",
  formula = data ~ ClinicalStatus,
  homogeneity.test = "anova",
  full = TRUE
)

# Example showing how to pass extra parameters, such as 'permutations',
# to anova.cca
tse <- addRDA(
  tse,
  assay.type = "clr",
  formula = data ~ ClinicalStatus,
  permutations = 500
)

```

```

    )

# In dbRDA, dissimilarity matrix is calculated internally which is
# computationally heavy operation. If you have large number of samples, and
# you want to fit multiple dbRDA models, you might want to consider
# pre-calculation of dissimilarity matrix as the same matrix will be used for
# all models. You can then run dbRDA with the pre-calculated dissimilarity
# avoiding redundant dissimilarity calculations.
tse <- addDissimilarity(tse, assay.type = "relabundance", method = "bray")
tse <- addRDA(
  tse,
  formula = data ~ ClinicalStatus,
  dis.name = "bray",
  name = "RDA_precalc_bray",
  na.action = na.exclude
)

```

---

|                     |                                                                    |
|---------------------|--------------------------------------------------------------------|
| getCrossAssociation | <i>Calculate correlations between features of two experiments.</i> |
|---------------------|--------------------------------------------------------------------|

---

## Description

Calculate correlations between features of two experiments.

## Usage

```

getCrossAssociation(x, ...)

## S4 method for signature 'MultiAssayExperiment'
getCrossAssociation(
  x,
  experiment1 = 1,
  experiment2 = 2,
  assay.type1 = assay_name1,
  assay_name1 = NULL,
  assay.type2 = assay_name2,
  assay_name2 = NULL,
  altexp1 = NULL,
  altexp2 = NULL,
  col.var1 = colData_variable1,
  colData_variable1 = NULL,
  col.var2 = colData_variable2,
  colData_variable2 = NULL,
  by = MARGIN,
  MARGIN = 1,
  method = "kendall",
  mode = "table",

```

```

    p.adj.method = p_adj_method,
    p_adj_method = c("fdr", "BH", "bonferroni", "BY", "hochberg", "holm", "hommel", "none"),
    p.adj.threshold = p_adj_threshold,
    p_adj_threshold = NULL,
    cor.threshold = cor_threshold,
    cor_threshold = NULL,
    sort = FALSE,
    filter.self.cor = filter_self_correlations,
    filter_self_correlations = FALSE,
    verbose = TRUE,
    test.signif = test_significance,
    test_significance = FALSE,
    show.warnings = show_warnings,
    show_warnings = TRUE,
    paired = FALSE,
    ...
)

## S4 method for signature 'SummarizedExperiment'
getCrossAssociation(x, experiment2 = x, ...)

```

## Arguments

|             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x           | A <a href="#">MultiAssayExperiment</a> or <a href="#">SummarizedExperiment</a> object.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| ...         | Additional arguments: <ul style="list-style-type: none"> <li>• symmetric: Logical scalar. Specifies if measure is symmetric or not. When symmetric = TRUE, associations are calculated only for unique variable-pairs, and they are assigned to corresponding variable-pair. This decreases the number of calculations in 2-fold meaning faster execution. (By default: FALSE)</li> <li>• association.fun: A function that is used to calculate (dis-)similarity between features. Function must take matrix as an input and give numeric values as an output. Adjust method and other parameters correspondingly. Supported functions are, for example, stats::dist and vegan::vegdist.</li> <li>• dimred1 Character scalar or numeric scalar. Specifies reduced dimensionality from the reducedDim of experiment 1. (Default: NULL)</li> <li>• dimred2 Character scalar or numeric scalar. Specifies reduced dimensionality from the reducedDim of experiment 2. (Default: NULL)</li> </ul> |
| experiment1 | Character scalar or numeric scalar. Selects the experiment 1 from experiments(x) of MultiassayExperiment object. (Default: 1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| experiment2 | Character scalar or numeric scalar. Selects the experiment 2 from experiments(x) of MultiAssayExperiment object or altExp(x) of TreeSummarizedExperiment object. Alternatively, experiment2 can also be TreeSE object when x is TreeSE object. (Default: 2 when x is MAE and x when x is TreeSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| assay.type1 | Character scalar. Specifies the name of the assay in experiment 1 to be transformed. (Default: NULL)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

|                   |                                                                                                                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| assay_name1       | Deprecated. Use assay.type1 instead.                                                                                                                                                                       |
| assay.type2       | Character scalar. Specifies the name of the assay in experiment 2 to be transformed. (Default: NULL)                                                                                                       |
| assay_name2       | Deprecated. Use assay.type2 instead.                                                                                                                                                                       |
| altexp1           | Character scalar or numeric scalar. Specifies alternative experiment from the altExp of experiment 1. If NULL, then the experiment is itself and altExp option is disabled. (Default: NULL)                |
| altexp2           | Character scalar or numeric scalar. Specifies alternative experiment from the altExp of experiment 2. If NULL, then the experiment is itself and altExp option is disabled. (Default: NULL)                |
| col.var1          | Character scalar. Specifies column(s) from colData of experiment 1. If col.var1 is used, assay.type1 is disabled. (Default: NULL)                                                                          |
| colData_variable1 | Deprecated. Use col.var1 instead.                                                                                                                                                                          |
| col.var2          | Character scalar. Specifies column(s) from colData of experiment 2. If col.var2 is used, assay.type2 is disabled. (Default: NULL)                                                                          |
| colData_variable2 | Deprecated. Use col.var2 instead.                                                                                                                                                                          |
| by                | ACharacter scalar. Determines if association are calculated row-wise / for features ('rows') or column-wise / for samples ('cols'). Must be 'rows' or 'cols'.                                              |
| MARGIN            | Deprecated. Use by instead.                                                                                                                                                                                |
| method            | Character scalar. Defines the association method ('kendall', 'pearson', or 'spearman' for continuous/numeric; 'categorical' for discrete) (Default: "kendall")                                             |
| mode              | Character scalar. Specifies the output format Available formats are 'table' and 'matrix'. (Default: "table")                                                                                               |
| p.adj.method      | Character scalar. Specifies adjustment method of p-values. Passed to p.adjust function. (Default: "fdr")                                                                                                   |
| p_adj_method      | Deprecated. Use p.adj.method instead.                                                                                                                                                                      |
| p.adj.threshold   | Numeric scalar. From 0 to 1, specifies adjusted p-value threshold for filtering. (Default: NULL)                                                                                                           |
| p_adj_threshold   | Deprecated. Use p.dj.threshold instead.                                                                                                                                                                    |
| cor.threshold     | Numeric scalar. From 0 to 1, specifies correlation threshold for filtering. (Default: NULL)                                                                                                                |
| cor_threshold     | Deprecated. Use cor.threshold instead.                                                                                                                                                                     |
| sort              | Logical scalar. Specifies whether to sort features or not in result matrices. Used method is hierarchical clustering. (Default: FALSE)                                                                     |
| filter.self.cor   | Logical scalar. Specifies whether to filter out correlations between identical items. Applies only when correlation between experiment itself is tested, i.e., when assays are identical. (Default: FALSE) |

|                                       |                                                                                                                                                                     |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>filter_self_correlations</code> | Deprecated. Use <code>filter.self.cor</code> instead.                                                                                                               |
| <code>verbose</code>                  | Logical scalar. Specifies whether to get messages about progress of calculation. (Default: FALSE)                                                                   |
| <code>test.signif</code>              | Logical scalar. Specifies whether to test statistical significance of associations. (Default: FALSE)                                                                |
| <code>test_significance</code>        | Deprecated. Use <code>test.signif</code> instead.                                                                                                                   |
| <code>show.warnings</code>            | Logical scalar. specifies whether to show warnings that might occur when correlations and p-values are calculated. (Default: FALSE)                                 |
| <code>show_warnings</code>            | Deprecated. use <code>show.warnings</code> instead.                                                                                                                 |
| <code>paired</code>                   | Logical scalar. Specifies if samples are paired or not. colnames must match between twp experiments. paired is disabled when <code>by = 1</code> . (Default: FALSE) |

## Details

The function `getCrossAssociation` calculates associations between features of two experiments. By default, it not only computes associations but also tests their significance. If desired, setting `test.signif` to FALSE disables significance calculation.

We recommend the non-parametric Kendall's tau as the default method for association analysis. Kendall's tau has desirable statistical properties and robustness at lower sample sizes. Spearman rank correlation can provide faster solutions when running times are critical.

## Value

This function returns associations in table or matrix format. In table format, returned value is a data frame that includes features and associations (and p-values) in columns. In matrix format, returned value is a one matrix when only associations are calculated. If also significances are tested, then returned value is a list of matrices.

## Examples

```
data(HintikkaXOData)
mae <- HintikkaXOData

# Subset so that less observations / quicker to run, just for example
mae[[1]] <- mae[[1]][1:20, 1:10]
mae[[2]] <- mae[[2]][1:20, 1:10]
# Several rows in the counts assay have a standard deviation of zero
# Remove them, since they do not add useful information about
# cross-association
mae[[1]] <- mae[[1]][rowSds(assay(mae[[1]])) > 0, ]
# Transform data
mae[[1]] <- transformAssay(mae[[1]], method = "rclr")

# Calculate cross-correlations
result <- getCrossAssociation(
  mae, method = "pearson", assay.type1 = "counts", assay.type2 = "nmr",
  show.warnings = FALSE, verbose = FALSE)
```



```

# Show first 5 entries
head(result, 5)

# Use altExp option to specify alternative experiment from the experiment
altExp(mae[[1]], "Phylum") <- agglomerateByRank(mae[[1]], rank = "Phylum")
# Transform data
altExp(mae[[1]], "Phylum") <- transformAssay(
  altExp(mae[[1]], "Phylum"), method = "relabundance")
# When mode = "matrix", the return value is a matrix
result <- getCrossAssociation(
  mae, experiment2 = 2, assay.type1 = "relabundance", assay.type2 = "nmr",
  altexp1 = "Phylum", method = "pearson", mode = "matrix",
  show.warnings = FALSE, verbose = FALSE)
# Show first 5 entries
head(result, 5)

# If test.signif = TRUE, then getCrossAssociation additionally returns
# significances
# filter.self.cor = TRUE filters self correlations
# p.adj.threshold can be used to filter those features that do not
# have any correlations whose p-value is lower than the threshold
result <- getCrossAssociation(
  mae[[1]], experiment2 = mae[[1]], method = "pearson",
  assay.type1 = "counts", assay.type2 = "counts",
  filter.self.cor = TRUE, p.adj.threshold = 0.05, test.signif = TRUE,
  show.warnings = FALSE, verbose = FALSE)
# Show first 5 entries
head(result, 5)

# Returned value is a list of matrices
names(result)

# Calculate Bray-Curtis dissimilarity between samples. If dataset includes
# paired samples, you can use paired = TRUE.
result <- getCrossAssociation(
  mae[[1]], mae[[1]], by = 2, paired = FALSE,
  assay.type1 = "counts", assay.type2 = "counts",
  association.fun = getDissimilarity, method = "bray",
  show.warnings = FALSE, verbose = FALSE)

# If experiments are equal and measure is symmetric
# (e.g., taxa1 vs taxa2 == taxa2 vs taxa1),
# it is possible to speed-up calculations by calculating association only
# for unique variable-pairs. Use "symmetric" to choose whether to measure
# association for only other half of of variable-pairs.
result <- getCrossAssociation(
  mae, experiment1 = "microbiota", experiment2 = "microbiota",
  assay.type1 = "counts", assay.type2 = "counts", symmetric = TRUE,
  show.warnings = FALSE, verbose = FALSE)

# For big data sets, the calculations might take a long time.
# To speed them up, you can take a random sample from the data.
# When dealing with complex biological problems, random samples can be

```

```

# enough to describe the data. Here, our random sample is 30 % of whole data.
sample_size <- 0.3
tse <- mae[[1]]
tse_sub <- tse[ sample( seq_len( nrow(tse) ), sample_size * nrow(tse) ), ]
result <- getCrossAssociation(
  tse_sub, assay.type1 = "counts", assay.type2 = "counts",
  show.warnings = FALSE, verbose = FALSE)

# It is also possible to choose variables from colData and calculate
# association between assay and sample metadata or between variables of
# sample metadata
mae[[1]] <- addAlpha(mae[[1]])
# col.var works similarly to assay.type. Instead of fetching
# an assay named assay.type from assay slot, it fetches a column named
# col.var from colData.
result <- getCrossAssociation(
  mae[[1]], assay.type1 = "counts",
  col.var2 = c("shannon_diversity", "dbp_dominance"),
  test.signif = TRUE, show.warnings = FALSE, verbose = FALSE)

# If your data contains TreeSE with alternative experiment in altExp,
# correlations can be calculated as follows.

# Create TreeSE with altExp
tse <- mae[[1]]
altExp(tse, "metabolites") <- mae[[2]]
# Calculate
res <- getCrossAssociation(
  tse,
  altexp2 = "metabolites",
  assay.type1 = "rclr",
  assay.type2 = "nmr",
  show.warnings = FALSE, verbose = FALSE
)

# To calculate correlation of features to principal coordinates, you have to
# first calculate PCoA...
library(scater)
tse <- addMDS(tse, assay.type = "rclr", method = "euclidean")
# ...then calculate the correlation.
res <- getCrossAssociation(tse, assay.type1 = "rclr", dimred2 = "MDS",
  show.warnings = FALSE, verbose = FALSE)
head(res)

# In ecological studies the association analyses are sometimes carried out
# only for those samples that have observations. You can ignore zeroes by
# replacing them with NA.
mat <- assay(tse, "counts")
mat[ mat == 0 ] <- NA
assay(tse, "non_zero", withDimnames = FALSE) <- mat
res2 <- getCrossAssociation(
  tse, tse,
  assay.type1 = "non_zero", assay.type2 = "non_zero"

```

)

---

getDominant

*Get dominant taxa*

---

## Description

These functions return information about the most dominant taxa in a [SummarizedExperiment](#) object.

## Usage

```
getDominant(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  group = rank,
  rank = NULL,
  other.name = "Other",
  n = NULL,
  complete = TRUE,
  ...
)
```

```
addDominant(x, name = "dominant_taxa", other.name = "Other", n = NULL, ...)
```

```
## S4 method for signature 'SummarizedExperiment'
```

```
getDominant(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  group = rank,
  rank = NULL,
  other.name = "Other",
  n = NULL,
  complete = TRUE,
  ...
)
```

```
## S4 method for signature 'SummarizedExperiment'
```

```
addDominant(
  x,
  name = "dominant_taxa",
  other.name = "Other",
  n = NULL,
  complete = FALSE,
```

```
    ...  
  )
```

## Arguments

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x          | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                                                                                                                                                                                                                                                                                        |
| assay.type | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                                                                                                                                                                                                                                                            |
| assay_name | Deprecated. Use assay.type instead.                                                                                                                                                                                                                                                                                                                                                                                                               |
| group      | Character scalar. Defines a group. Must be one of the columns from rowData(x). (Default: NULL)                                                                                                                                                                                                                                                                                                                                                    |
| rank       | Deprecated. Use group instead.                                                                                                                                                                                                                                                                                                                                                                                                                    |
| other.name | Character scalar. A name for features that are not included in n the most frequent dominant features in the data. (Default: "Other")                                                                                                                                                                                                                                                                                                              |
| n          | Numeric scalar. The number of features that are the most frequent dominant features. Default is NULL, which defaults that each sample is assigned a dominant taxon. (Default: NULL)                                                                                                                                                                                                                                                               |
| complete   | Logical scalar. A value to manage multiple dominant taxa for a sample. Default for getDominant is TRUE to include all equally dominant taxa for each sample. complete = FALSE samples one taxa for the samples that have multiple. Default for addDominant is FALSE to add a column with only one dominant taxon assigned for each sample into colData. complete = TRUE adds a list that includes all dominant taxa for each sample into colData. |
| ...        | Additional arguments passed on to agglomerateByRank() when rank is specified.                                                                                                                                                                                                                                                                                                                                                                     |
| name       | Character scalar. A name for the column of the colData where results will be stored. (Default: "dominant_taxa")                                                                                                                                                                                                                                                                                                                                   |

## Details

addDominant extracts the most abundant taxa in a [SummarizedExperiment](#) object, and stores the information in the colData. It is a wrapper for getDominant.

With group parameter, it is possible to agglomerate rows based on groups. If the value is one of the columns in taxonomyRanks(), agglomerateByRank() is applied. Otherwise, agglomerateByVariable() is utilized. E.g. if 'Genus' rank is used, all abundances of same Genus are added together, and agglomerated features are returned. See corresponding functions for additional arguments to deal with missing values or special characters.

## Value

getDominant returns a named character vector x while addDominant returns [SummarizedExperiment](#) with additional column in colData named \*name\*.

**Examples**

```
data(GlobalPatterns)
x <- GlobalPatterns

# Finds the dominant taxa.
sim.dom <- getDominant(x, group = "Genus")

# Add information to colData
x <- addDominant(x, group = "Genus", name = "dominant_genera")
colData(x)
```

getDPCoA

*Calculation of Double Principal Correspondance analysis***Description**

Double Principal Correspondance analysis is made available via the ade4 package in typical fashion. Results are stored in the reducedDims and are available for all the expected functions.

**Usage**

```
getDPCoA(x, y, ...)

## S4 method for signature 'ANY,ANY'
getDPCoA(
  x,
  y,
  ncomponents = 2,
  ntop = NULL,
  subset.row = subset_row,
  subset_col = NULL,
  scale = FALSE,
  transposed = FALSE,
  ...
)

## S4 method for signature 'TreeSummarizedExperiment,missing'
getDPCoA(
  x,
  ...,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  tree.name = tree_name,
  tree_name = "phylo"
)
```

```
calculateDPCoA(x, ...)
```

```
addDPCoA(x, ..., altexp = NULL, name = "DPCoA")
```

```
runDPCoA(x, ...)
```

## Arguments

|              |                                                                                                                                                                                                            |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x            | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                                                 |
| y            | a dist or a symmetric matrix compatible with ade4:dpcoa                                                                                                                                                    |
| ...          | Currently not used.                                                                                                                                                                                        |
| ncomponents  | Numeric scalar. Indicates the number of DPCoA dimensions to obtain. (Default: 2)                                                                                                                           |
| ntop         | Numeric scalar. Specifies the number of features with the highest variances to use for dimensionality reduction. Alternatively NULL, if all features should be used. (Default: NULL)                       |
| subset.row   | Character Vector. Specifies the subset of features to use for dimensionality reduction. This can be a character vector of row names, an integer vector of row indices or a logical vector. (Default: NULL) |
| subset_row   | Deprecated. Use subset.row instead.                                                                                                                                                                        |
| scale        | Logical scalar. Should the expression values be standardized? (Default: FALSE)                                                                                                                             |
| transposed   | Logical scalar. Specifies if x is transposed with cells in rows. (Default: FALSE)                                                                                                                          |
| assay.type   | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                     |
| assay_name   | Deprecated. Use assay.type instead.                                                                                                                                                                        |
| exprs_values | Deprecated. Use assay.type instead.                                                                                                                                                                        |
| tree.name    | Character scalar. Specifies the name of the tree to be included in the phyloseq object that is created, (Default: "phylo")                                                                                 |
| tree_name    | Deprecated. Use tree.name instead.                                                                                                                                                                         |
| altexp       | Character scalar or integer scalar. Specifies an alternative experiment containing the input data. (Default: NULL)                                                                                         |
| name         | Character scalar. A name for the column of the colData where results will be stored. (Default: "DPCoA")                                                                                                    |

## Details

For addDPCoA a [TreeSummarizedExperiment](#) containing the expression values as well as a rowTree to calculate y using [cophenetic.phylo](#).

In addition to the reduced dimension on the features, the reduced dimension for samples are returned as well as sample\_red attribute. eig, feature\_weights and sample\_weights are returned as attributes as well.

**Value**

For getDPCoA a matrix with samples as rows and CCA dimensions as columns

For addDPCoA a modified x with the results stored in reducedDim as the given name

**See Also**

[plotReducedDim reducedDims](#)

**Examples**

```
data(esophagus)
dpcoa <- getDPCoA(esophagus)
head(dpcoa)

esophagus <- addDPCoA(esophagus)
reducedDims(esophagus)

library(scater)
plotReducedDim(esophagus, "DPCoA")
```

---

|                  |                                 |
|------------------|---------------------------------|
| getHierarchyTree | <i>Calculate hierarchy tree</i> |
|------------------|---------------------------------|

---

**Description**

These functions generate a hierarchy tree using taxonomic information from a [SummarizedExperiment](#) object and add this hierarchy tree into the rowTree.

**Usage**

```
getHierarchyTree(x, ...)

addHierarchyTree(x, ...)

## S4 method for signature 'SummarizedExperiment'
getHierarchyTree(x, ...)

## S4 method for signature 'SummarizedExperiment'
addHierarchyTree(x, ...)
```

**Arguments**

|     |                                            |
|-----|--------------------------------------------|
| x   | <a href="#">TreeSummarizedExperiment</a> . |
| ... | optional arguments not used currently.     |

## Details

`addHierarchyTree` calculates a hierarchy tree from the available taxonomic information and add it to `rowTree`.

`getHierarchyTree` generates a hierarchy tree from the available taxonomic information. Internally it uses `toTree` and `resolveLoop` to sanitize data if needed.

Please note that a hierarchy tree is not an actual phylogenetic tree. A phylogenetic tree represents evolutionary relationships among features. On the other hand, a hierarchy tree organizes species into a hierarchical structure based on their taxonomic ranks.

## Value

- `addHierarchyTree`: a `TreeSummarizedExperiment` whose phylo tree represents the hierarchy among available taxonomy information.
- `getHierarchyTree`: a phylo tree representing the hierarchy among available taxonomy information.

## Examples

```
# Generate a tree based on taxonomic rank hierarchy (a hierarchy tree).
data(GlobalPatterns)
tse <- GlobalPatterns
getHierarchyTree(tse)

# Add a hierarchy tree to a TreeSummarizedExperiment.
# Please note that any tree already stored in rowTree() will be overwritten.
tse <- addHierarchyTree(tse)
tse
```

---

getLDA

*Latent Dirichlet Allocation*

---

## Description

These functions perform Latent Dirichlet Allocation on data stored in a `TreeSummarizedExperiment` object.

## Usage

```
getLDA(x, ...)

addLDA(x, ...)

## S4 method for signature 'SummarizedExperiment'
getLDA(x, k = 2, assay.type = "counts", eval.metric = "perplexity", ...)

## S4 method for signature 'SummarizedExperiment'
addLDA(x, k = 2, assay.type = "counts", name = "LDA", ...)
```



**Arguments**

|             |                                                                                                                                                                                                                                                                                                                    |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x           | a <a href="#">TreeSummarizedExperiment</a> object.                                                                                                                                                                                                                                                                 |
| ...         | optional arguments passed to <a href="#">LDA</a>                                                                                                                                                                                                                                                                   |
| k           | Integer vector. A number of latent vectors/topics. (Default: 2)                                                                                                                                                                                                                                                    |
| assay.type  | Character scalar. Specifies which assay to use for LDA ordination. (Default: "counts")                                                                                                                                                                                                                             |
| eval.metric | Character scalar. Specifies evaluation metric that will be used to select the model with the best fit. Must be either "perplexity" ( <code>topicmodels::perplexity</code> ) or "coherence" ( <code>topicdoc::topic_coherence</code> , the best model is selected based on mean coherence). (Default: "perplexity") |
| name        | Character scalar. The name to be used to store the result in the reducedDims of the output. (Default: "LDA")                                                                                                                                                                                                       |

**Details**

The functions `getLDA` and `addLDA` internally use [LDA](#) to compute the ordination matrix and feature loadings.

**Value**

For `getLDA`, the ordination matrix with feature loadings matrix as attribute "loadings".

For `addLDA`, a [TreeSummarizedExperiment](#) object is returned containing the ordination matrix in `reducedDim(..., name)` with feature loadings matrix as attribute "loadings".

**Examples**

```
data(GlobalPatterns)
tse <- GlobalPatterns

# Reduce the number of features
tse <- agglomerateByPrevalence(tse, rank="Phylum")

# Run LDA and add the result to reducedDim(tse, "LDA")
tse <- addLDA(tse)

# Extract feature loadings
loadings <- getReducedDimAttribute(tse, "LDA", "loadings")
head(loadings)

# Estimate models with number of topics from 2 to 10
tse <- addLDA(tse, k = c(2, 3, 4, 5, 6, 7, 8, 9, 10), name = "LDA_10")
# Get the evaluation metrics
tab <- getReducedDimAttribute(tse, "LDA_10", "eval_metrics")
# Plot
plot(tab[["k"]], tab[["perplexity"]], xlab = "k", ylab = "perplexity")
```

getMDS

*Perform multi-dimensional scaling (MDS)*

## Description

Perform multi-dimensional scaling (MDS) also know as Principal Coordinate Analysis (PCoA). These functions are wrappers for `scater::calculateMDS`.

## Usage

```
getMDS(x, ...)

addMDS(x, ...)

## S4 method for signature 'SingleCellExperiment'
addMDS(x, name = "MDS", ...)

## S4 method for signature 'SingleCellExperiment'
getMDS(x, assay.type = "counts", ...)

## S4 method for signature 'TreeSummarizedExperiment'
getMDS(x, assay.type = "counts", ...)
```

## Arguments

|            |                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x          | a <code>SummarizedExperiment</code> object.                                                                                                                                                                                                                                                                                                                                                                                |
| ...        | additional arguments. <ul style="list-style-type: none"> <li>FUN: Function. A function that is applied to calculate dissimilarity. (Default: <code>getDissimilarity</code>)</li> <li><code>\item \code{subset.result}: \code{Logical result}</code>. Specifies whether to subset <code>\code{x}</code> to match the result if some samples were removed during calculation. (Default: <code>\code{TRUE}</code>)</li> </ul> |
| name       | Character scalar. A name for the <code>reducedDim()</code> where results will be stored. (Default: "MDS")                                                                                                                                                                                                                                                                                                                  |
| assay.type | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                                                                                                                                                                                                                                     |

## Details

These functions are wrappers for `scater::calculateMDS` and `scater::runMDS`. While `getMDS` returns the results, `addMDS` adds them to `reducedDim(x)`. The difference is that these functions apply microbiome-specific options such as `getDissimilarity` function by default.

See `scater::calculateMDS` for details.

**Value**

getMDS returns a MDS results. addMDS returns a x with MDS results added to its reducedDim(x, name).

**See Also**

[scater::calculateMDS](#) and [getDissimilarity](#)

**Examples**

```
library(mia)
library(scater)
library(patchwork)

data(GlobalPatterns)
tse <- GlobalPatterns

# Calculate PCoA with Bray-Curtis dissimilarity
tse <- transformAssay(tse, method = "relabundance")
tse <- addMDS(tse, assay.type = "relabundance", method = "bray")

# Calculate PCoA with Unifrac and rarefaction. (Note: increase iterations)
tse <- addMDS(tse, method = "unifrac", name = "unifrac")

# Calculate PCoA with Unifrac and rarefaction. (Note: increase iterations)
tse <- addMDS(tse, method = "unifrac", name = "unifrac_rare", niter = 2L)

# Visualize results
p1 <- plotReducedDim(tse, "unifrac", colour_by = "SampleType") +
  labs(title = "Not rarefied")
p2 <- plotReducedDim(tse, "unifrac_rare", colour_by = "SampleType") +
  labs(title = "Rarefied")
p1 + p2
```

---

getNMDS

---

*Perform non-metric MDS on sample-level data*


---

**Description**

Perform non-metric multi-dimensional scaling (nMDS) on samples, based on the data in a `SingleCellExperiment` object.

**Usage**

```
getNMDS(x, ...)

## S4 method for signature 'ANY'
getNMDS(
```

```

    x,
    FUN = vegdist,
    nmds.fun = nmdsFUN,
    nmdsFUN = c("isoMDS", "monoMDS"),
    ncomponents = 2,
    ntop = 500,
    subset.row = subset_row,
    subset_row = NULL,
    scale = FALSE,
    transposed = FALSE,
    keep.dist = keep_dist,
    keep_dist = FALSE,
    ...
)

## S4 method for signature 'SummarizedExperiment'
getNMDS(
  x,
  ...,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  FUN = vegdist
)

## S4 method for signature 'SingleCellExperiment'
getNMDS(
  x,
  ...,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  dimred = NULL,
  ndimred = n_dimred,
  n_dimred = NULL,
  FUN = vegdist
)

calculateNMDS(x, ...)

addNMDS(x, ..., altexp = NULL, name = "NMDS")

runNMDS(x, ...)

```

## Arguments

**x** [TreeSummarizedExperiment](#).

**...** additional arguments to pass to FUN and nmds.fun.

|                           |                                                                                                                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>FUN</code>          | Function or Character scalar. A value with a function name returning a <a href="#">dist</a> object                                                                                                                   |
| <code>nmds.fun</code>     | Character scalar. A value to choose the scaling implementation, either “isoMDS” for <a href="#">MASS::isoMDS</a> or “monoMDS” for <a href="#">vegan::monoMDS</a>                                                     |
| <code>nmdsFUN</code>      | Deprecated. Use <code>nmds.fun</code> instead.                                                                                                                                                                       |
| <code>ncomponents</code>  | Numeric scalar. Indicates the number of DPCoA dimensions to obtain. (Default: 2)                                                                                                                                     |
| <code>ntop</code>         | Numeric scalar. Specifies the number of features with the highest variances to use for dimensionality reduction. Alternatively NULL, if all features should be used. (Default: NULL)                                 |
| <code>subset.row</code>   | Character Vector. Specifies the subset of features to use for dimensionality reduction. This can be a character vector of row names, an integer vector of row indices or a logical vector. (Default: NULL)           |
| <code>subset_row</code>   | Deprecated. Use <code>subset.row</code> instead.                                                                                                                                                                     |
| <code>scale</code>        | Logical scalar. Should the expression values be standardized? (Default: FALSE)                                                                                                                                       |
| <code>transposed</code>   | Logical scalar. Specifies if <code>x</code> is transposed with cells in rows. (Default: FALSE)                                                                                                                       |
| <code>keep.dist</code>    | Logical scalar. Indicates whether the <code>dist</code> object calculated by <code>FUN</code> should be stored as ‘dist’ attribute of the matrix returned/stored by <code>getNMDS/ addNMDS</code> . (Default: FALSE) |
| <code>keep_dist</code>    | Deprecated. Use <code>keep.dist</code> instead.                                                                                                                                                                      |
| <code>assay.type</code>   | Character scalar. Specifies the name of assay used in calculation. (Default: “counts”)                                                                                                                               |
| <code>assay_name</code>   | Deprecated. Use <code>assay.type</code> instead.                                                                                                                                                                     |
| <code>exprs_values</code> | Deprecated. Use <code>assay.type</code> instead.                                                                                                                                                                     |
| <code>dimred</code>       | Character scalar or integer scalar. Specifies the existing dimensionality reduction results to use.                                                                                                                  |
| <code>ndimred</code>      | integer vector. Specifies the dimensions to use if <code>dimred</code> is specified.                                                                                                                                 |
| <code>n_dimred</code>     | Deprecated. Use <code>ndimred</code> instead.                                                                                                                                                                        |
| <code>altexp</code>       | Character scalar or integer scalar. Specifies an alternative experiment containing the input data. (Default: NULL)                                                                                                   |
| <code>name</code>         | Character scalar. A name for the column of the <code>colData</code> where results will be stored. (Default: “NMDS”)                                                                                                  |

## Details

For `addNMDS` a [TreeSummarizedExperiment](#)

Either [MASS::isoMDS](#) or [vegan::monoMDS](#) are used internally to compute the NMDS components. If you supply a custom `FUN`, make sure that the arguments of `FUN` and `nmds.fun` do not collide.

## Value

For `getNMDS`, a matrix is returned containing the MDS coordinates for each sample (row) and dimension (column).

**See Also**

[MASS::isoMDS](#), [vegan::monoMDS](#) for NMDS component calculation.  
[plotMDS](#), to quickly visualize the results.

**Examples**

```
# generate some example data
mat <- matrix(1:60, nrow = 6)
df <- DataFrame(n = c(1:6))
tse <- TreeSummarizedExperiment(assays = list(counts = mat),
                                rowData = df)

#
getNMF(tse)

#
data(esophagus)
esophagus <- addNMF(esophagus, FUN = vegan::vegdist, name = "BC")
esophagus <- addNMF(esophagus, FUN = vegan::vegdist, name = "euclidean",
                    method = "euclidean")
reducedDims(esophagus)
```

---

getNMF

---

*Non-negative Matrix Factorization*


---

**Description**

These functions perform Non-negative Matrix Factorization on data stored in a [TreeSummarizedExperiment](#) object.

**Usage**

```
getNMF(x, ...)

addNMF(x, ...)

## S4 method for signature 'SummarizedExperiment'
getNMF(x, k = 2, assay.type = "counts", eval.metric = "evar", ...)

## S4 method for signature 'SummarizedExperiment'
addNMF(
  x,
  k = 2,
  assay.type = "counts",
  eval.metric = "evar",
  name = "NMF",
  ...
)
```

## Arguments

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>           | a <a href="#">TreeSummarizedExperiment</a> object.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>...</code>         | optional arguments passed to <code>nmf::NMF</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <code>k</code>           | numeric vector. A number of latent vectors/topics. (Default: 2)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>assay.type</code>  | Character scalar. Specifies which assay to use for NMF ordination. (Default: "counts")                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>eval.metric</code> | Character scalar. Specifies the evaluation metric that will be used to select the model with the best fit. Must be one of the following options: "evan" (explained variance; maximized), "sparseness.basis" (degree of sparsity in the basis matrix; maximized), "sparseness.coef" (degree of sparsity in the coefficient matrix; maximized), "rss" (residual sum of squares; minimized), "silhouette.coef" (quality of clustering based on the coefficient matrix; maximized), "silhouette.basis" (quality of clustering based on the basis matrix; maximized), "cophenetic" (correlation between cophenetic distances and original distances; maximized), "dispersion" (spread of data points within clusters; minimized). (Default: "evan") |
| <code>name</code>        | Character scalar. The name to be used to store the result in the <code>reducedDims</code> of the output. (Default: "NMF")                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

## Details

The functions `getNMF` and `addNMF` internally use `nmf::NMF` compute the ordination matrix and feature loadings.

If `k` is a vector of integers, NMF output is calculated for all the rank values contained in `k`, and the best fit is selected based on `eval.metric` value.

## Value

For `getNMF`, the ordination matrix with feature loadings matrix as attribute "loadings".

For `addNMF`, a [TreeSummarizedExperiment](#) object is returned containing the ordination matrix in `reducedDims(x, name)` with the following attributes:

- "loadings" which is a matrix containing the feature loadings
- "NMF\_output" which is the output of function `nmf::NMF`
- "best\_fit" which is the result of the best fit if `k` is a vector of integers

## Examples

```
data(GlobalPatterns)
tse <- GlobalPatterns

# Reduce the number of features
tse <- agglomerateByPrevalence(tse, rank = "Phylum")

# Run NMF and add the result to reducedDim(tse, "NMF").
tse <- addNMF(tse, k = 2, name = "NMF")
```

```
# Extract feature loadings
loadings_NMF <- getReducedDimAttribute(tse, "NMF", "loadings")
head(loadings_NMF)

# Estimate models with number of topics from 2 to 4. Perform 2 runs.
tse <- addNMF(tse, k = c(2, 3, 4), name = "NMF_4", nrun = 2)

# Extract feature loadings
loadings_NMF_4 <- getReducedDimAttribute(tse, "NMF_4", "loadings")
head(loadings_NMF_4)
```

---

|              |                                                                              |
|--------------|------------------------------------------------------------------------------|
| getPERMANOVA | <i>Calculate PERMANOVA (Permutational Multivariate Analysis of Variance)</i> |
|--------------|------------------------------------------------------------------------------|

---

## Description

These functions perform PERMANOVA to assess the significance of group differences based on a specified dissimilarity matrix. The results can be returned directly or added to metadata in an object of class `TreeSummarizedExperiment`.

## Usage

```
getPERMANOVA(x, ...)

addPERMANOVA(x, ...)

## S4 method for signature 'SingleCellExperiment'
getPERMANOVA(x, ...)

## S4 method for signature 'SummarizedExperiment'
getPERMANOVA(x, assay.type = "counts", formula = NULL, col.var = NULL, ...)

## S4 method for signature 'ANY'
getPERMANOVA(x, formula, data, method = "bray", test.homogeneity = TRUE, ...)

## S4 method for signature 'SummarizedExperiment'
addPERMANOVA(x, name = "permanova", ...)
```

## Arguments

|                  |                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>   | a <a href="#">SummarizedExperiment</a> object.                                                                                                                                                                                                                                                                                                                                     |
| <code>...</code> | additional arguments passed to <code>vegan::adonis2</code> . <ul style="list-style-type: none"> <li><code>by</code>: Character scalar. Specifies how significance is calculated. (Default: "margin")</li> <li><code>na.action</code>: function. Action to take when missing values for any of the variables in formula are encountered. (Default: <code>na.fail</code>)</li> </ul> |



|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                  | <ul style="list-style-type: none"> <li>• full Logical scalar. should all the results from the homogeneity calculations be returned. When FALSE, only summary tables are returned. (Default: FALSE)</li> <li>• homogeneity.test: Character scalar. Specifies the significance test used to analyse <code>vegan::betadisper</code> results. Options include 'permanova' (<code>vegan::permutest</code>), 'anova' (<code>stats::anova</code>) and 'tukeyhsd' (<code>stats::TukeyHSD</code>). (Default: "permanova")</li> </ul> |
| assay.type       | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| formula          | formula. If x is a <code>SummarizedExperiment</code> a formula can be supplied. Based on the right-hand side of the given formula colData is subset to col.var. col.var and formula can be missing, which turns the CCA analysis into a CA analysis and dbRDA into PCoA/MDS.                                                                                                                                                                                                                                                |
| col.var          | Character scalar. When x is a <code>SummarizedExperiment</code> , col.var can be used to specify variables from colData.                                                                                                                                                                                                                                                                                                                                                                                                    |
| data             | data.frame or coercible to one. The covariance table including covariates defined by formula.                                                                                                                                                                                                                                                                                                                                                                                                                               |
| method           | Character scalar. A dissimilarity metric used in PERMANOVA and group dispersion calculation. (Default: "bray")                                                                                                                                                                                                                                                                                                                                                                                                              |
| test.homogeneity | Logical scalar. Should the homogeneity of group dispersions be evaluated? (Default: TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| name             | Character scalar. A name for the results that will be stored to metadata. (Default: "permanova")                                                                                                                                                                                                                                                                                                                                                                                                                            |

## Details

PERMANOVA is a non-parametric method used to test whether the centroids of different groups (as defined by the formula or covariates) are significantly different in terms of multivariate space.

PERMANOVA relies on the assumption of group homogeneity, meaning the groups should be distinct and have similar variances within each group. This assumption is essential as PERMANOVA is sensitive to differences in within-group dispersion, which can otherwise confound results. This is why the functions return homogeneity test results by default.

The functions utilize `vegan::adonis2` to compute PERMANOVA. For homogeneity testing, `vegan::betadisper` along with `vegan::permutest` are utilized by default, which allow testing for equal dispersion across groups and validate the homogeneity assumption.

PERMANOVA and distance-based redundancy analysis (dbRDA) are closely related methods for analyzing multivariate data. PERMANOVA is non-parametric, making fewer assumptions about the data. In contrast, dbRDA assumes a linear relationship when constructing the ordination space, although it also employs a PERMANOVA-like approach to test the significance of predictors within this space. dbRDA offers a broader scope overall, as it provides visualization of the constrained ordination, which can reveal patterns and relationships. However, when the underlying data structure is non-linear, the results from the two methods can differ significantly due to dbRDA's reliance on linear assumptions.

**Value**

getPERMANOVA returns the PERMANOVA results or a list containing the PERMANOVA results and homogeneity test results if `test.homogeneity = TRUE`. `addPERMANOVA` adds these results to metadata of `x`.

**See Also**

For more details on the actual implementation see [vegan::adonis2](#), [vegan::betadisper](#), and [vegan::permutest](#). See also [addCCA](#) and [addRDA](#)

**Examples**

```
data(GlobalPatterns)
tse <- GlobalPatterns

# Apply relative transformation
tse <- transformAssay(tse, method = "relabundance")
# Perform PERMANOVA
tse <- addPERMANOVA(
  tse,
  assay.type = "relabundance",
  method = "bray",
  formula = x ~ SampleType,
  permutations = 99
)
# The results are stored to metadata
metadata(tse)[["permanova"]]

# Calculate dbRDA
rda_res <- getRDA(
  tse, assay.type = "relabundance", method = "bray",
  formula = x ~ SampleType, permutations = 99)
# Significance results are similar to PERMANOVA
attr(rda_res, "significance")
```

---

getPrevalence

---

*Calculation prevalence information for features across samples*


---

**Description**

These functions calculate the population prevalence for taxonomic ranks in a [SummarizedExperiment](#) object.

**Usage**

```
getPrevalence(x, ...)
```

```
getPrevalent(x, ...)
```

```
getRare(x, ...)

subsetByPrevalent(x, ...)

subsetByRare(x, ...)

getPrevalentAbundance(
  x,
  assay.type = assay_name,
  assay_name = "relabundance",
  ...
)

addPrevalentAbundance(x, ...)

addPrevalence(x, ...)

## S4 method for signature 'SummarizedExperiment'
addPrevalence(x, name = "prevalence", ...)

## S4 method for signature 'ANY'
getPrevalence(
  x,
  detection = 0,
  include.lowest = include_lowest,
  include_lowest = FALSE,
  sort = FALSE,
  na.rm = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
getPrevalence(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  rank = NULL,
  ...
)

## S4 method for signature 'ANY'
getPrevalent(
  x,
  prevalence = 50/100,
  include.lowest = include_lowest,
  include_lowest = FALSE,
  ...
)
```

```

)

## S4 method for signature 'SummarizedExperiment'
getPrevalent(
  x,
  rank = NULL,
  prevalence = 50/100,
  include.lowest = include_lowest,
  include_lowest = FALSE,
  ...
)

## S4 method for signature 'ANY'
getRare(
  x,
  prevalence = 50/100,
  include.lowest = include_lowest,
  include_lowest = FALSE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
getRare(
  x,
  rank = NULL,
  prevalence = 50/100,
  include.lowest = include_lowest,
  include_lowest = FALSE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
subsetByPrevalent(x, rank = NULL, ...)

## S4 method for signature 'TreeSummarizedExperiment'
subsetByPrevalent(x, update.tree = TRUE, ...)

## S4 method for signature 'SummarizedExperiment'
subsetByRare(x, rank = NULL, ...)

## S4 method for signature 'TreeSummarizedExperiment'
subsetByRare(x, update.tree = TRUE, ...)

## S4 method for signature 'SummarizedExperiment'
addPrevalentAbundance(x, name = "prevalent_abundance", ...)

## S4 method for signature 'ANY'
getPrevalentAbundance(

```

```

    x,
    assay.type = assay_name,
    assay_name = "relabundance",
    ...
)

## S4 method for signature 'SummarizedExperiment'
getPrevalentAbundance(x, assay.type = assay_name, assay_name = "counts", ...)

```

## Arguments

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x              | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| ...            | additional arguments <ul style="list-style-type: none"> <li>• If <code>!is.null(rank)</code> arguments are passed on to <a href="#">agglomerateByRank</a>. See <a href="#">?agglomerateByRank</a> for more details.</li> <li>• for <code>getPrevalent</code>, <code>getRare</code>, <code>subsetByPrevalent</code> and <code>subsetByRare</code> additional parameters passed to <code>getPrevalence</code></li> <li>• for <code>getPrevalentAbundance</code> additional parameters passed to <code>getPrevalent</code></li> </ul> |
| assay.type     | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| assay_name     | Deprecated. Use <code>assay.type</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| name           | Character scalar. Specifies name of column in <code>rowData</code> where the results will be stored. (Default: "prevalence")                                                                                                                                                                                                                                                                                                                                                                                                       |
| detection      | Numeric scalar. Detection threshold for absence/presence. If <code>as_relative = FALSE</code> , it sets the counts threshold for a taxon to be considered present. If <code>as_relative = TRUE</code> , it sets the relative abundance threshold for a taxon to be considered present. (Default: 0)                                                                                                                                                                                                                                |
| include.lowest | Logical scalar. Should the lower boundary of the detection and prevalence cutoffs be included? (Default: FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                    |
| include_lowest | Deprecated. Use <code>include.lowest</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| sort           | Logical scalar. Should the result be sorted by prevalence? (Default: FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| na.rm          | Logical scalar. Should NA values be omitted? (Default: TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| rank           | Character scalar. Defines a taxonomic rank. Must be a value of <code>taxonomyRanks()</code> function.                                                                                                                                                                                                                                                                                                                                                                                                                              |
| prevalence     | Prevalence threshold (in 0 to 1). The required prevalence is strictly greater by default. To include the limit, set <code>include.lowest</code> to TRUE.                                                                                                                                                                                                                                                                                                                                                                           |
| update.tree    | Logical scalar. Should <code>rowTree()</code> also be agglomerated? (Default: TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## Details

`getPrevalence` calculates the frequency of samples that exceed the detection threshold. For `SummarizedExperiment` objects, the prevalence is calculated for the selected taxonomic rank, otherwise for the rows. The absolute population prevalence can be obtained by multiplying the prevalence by the number of samples (`ncol(x)`).

The core abundance index from `getPrevalentAbundance` gives the relative proportion of the core species (in between 0 and 1). The core taxa are defined as those that exceed the given population prevalence threshold at the given detection level as set for `getPrevalent`.

`subsetPrevalent` and `subsetRareFeatures` return a subset of `x`. The subset includes the most prevalent or rare taxa that are calculated with `getPrevalent` or `getRare` respectively.

`getPrevalent` returns taxa that are more prevalent with the given detection threshold for the selected taxonomic rank.

`getRare` returns complement of `getPrevalent`.

## Value

`subsetPrevalent` and `subsetRareFeatures` return subset of `x`.

All other functions return a named vectors:

- `getPrevalence` returns a numeric vector with the names being set to either the row names of `x` or the names after agglomeration. `addPrevalence` adds these results to `rowData(x)`.
- `getPrevalentAbundance` returns a numeric vector with the names corresponding to the column name of `x` and include the joint abundance of prevalent taxa.
- `getPrevalent` and `getRare` return a character vector with only the names exceeding the threshold set by prevalence, if the rownames of `x` is set. Otherwise an integer vector is returned matching the rows in `x`.

## References

A Salonen et al. The adult intestinal core microbiota is determined by analysis depth and health status. *Clinical Microbiology and Infection* 18(S4):16 20, 2012. To cite the R package, see `citation('mia')`

## See Also

[agglomerateByRank](#), [getTop](#)

## Examples

```
data(GlobalPatterns)
tse <- GlobalPatterns
# Get prevalence estimates for individual ASV/OTU
prevalence.frequency <- getPrevalence(tse,
                                     detection = 0,
                                     sort = TRUE)

head(prevalence.frequency)

# Get prevalence estimates for phyla
# - the getPrevalence function itself always returns population frequencies
prevalence.frequency <- getPrevalence(tse,
                                     rank = "Phylum",
                                     detection = 0,
                                     sort = TRUE)

head(prevalence.frequency)
```

```

# - to obtain population counts, multiply frequencies with the sample size,
# which answers the question "In how many samples is this phylum detectable"
prevalence.count <- prevalence.frequency * ncol(tse)
head(prevalence.count)

# Detection threshold 1 (strictly greater by default);
# Note that the data (GlobalPatterns) is here in absolute counts
# (and not compositional, relative abundances)
# Prevalence threshold 50 percent (strictly greater by default)
prevalent <- getPrevalent(
  tse,
  rank = "Phylum",
  detection = 10,
  prevalence = 50/100)
head(prevalent)

# Add relative abundance data
tse <- transformAssay(tse, assay.type = "counts", method = "relabundance")

# Gets a subset of object that includes prevalent taxa
altExp(tse, "prevalent") <- subsetByPrevalent(tse,
                                              rank = "Family",
                                              assay.type = "relabundance",
                                              detection = 0.001,
                                              prevalence = 0.55)

altExp(tse, "prevalent")

# getRare returns the inverse
rare <- getRare(tse,
  rank = "Phylum",
  assay.type = "relabundance",
  detection = 1/100,
  prevalence = 50/100)
head(rare)

# Gets a subset of object that includes rare taxa
altExp(tse, "rare") <- subsetByRare(
  tse,
  rank = "Class",
  assay.type = "relabundance",
  detection = 0.001,
  prevalence = 0.001)
altExp(tse, "rare")

# Names of both experiments, prevalent and rare, can be found from slot
# altExpNames
tse

data(esophagus)
getPrevalentAbundance(esophagus, assay.type = "counts")

```

---

getReducedDimAttribute

*Utilization functions for TreeSummarizedExperiment objects*


---

## Description

A set of utility functions designed to facilitate operations with TreeSummarizedExperiment objects

## Usage

```
getReducedDimAttribute(x, ...)
```

```
## S4 method for signature 'SingleCellExperiment'
getReducedDimAttribute(x, dimred = 1L, name = NULL, ...)
```

## Arguments

|        |                                                                                                                                               |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| x      | a <a href="#">SummarizedExperiment</a> object.                                                                                                |
| ...    | additional arguments, not used currently.                                                                                                     |
| dimred | Character scalar or integer scalar. A name or index of dimension reduction results. (Default: 1L)                                             |
| name   | Character vector. A name of values retrieved from attributes of reducedDim(x, dimred). If NULL, all the values are retrieved. (Default: NULL) |

## Details

getReducedDimAttribute is a utility function that retrieves specific elements from the attributes of reducedDim in a TreeSummarizedExperiment object. These attributes may contain loadings, statistical test results, or other metadata, depending on the methods used to generate the results.

## Value

The extracted element from the reducedDim attribute.

## See Also

[runCCA](#), [addNMF](#), and [addLDA](#)

## Examples

```
data(GlobalPatterns)
tse <- GlobalPatterns

# Reduce the number of features
tse <- agglomerateByPrevalence(tse, rank = "Phylum")

# Run NMF and add the result to reducedDim(tse, "NMF").
```



```
tse <- addNMF(tse, k = 1, name = "NMF")

# Extract feature loadings
res <- getReducedDimAttribute(tse, dimred = "NMF", name = "loadings")
res |> head()
```

GlobalPatterns

*Global patterns of 16S rRNA diversity at a depth of millions of sequences per sample.*

## Description

GlobalPatterns compared the microbial communities from 25 environmental samples and three known "mock communities" at an average depth of 3.1 million reads per sample. Authors reproduced diversity patterns seen in many other published studies, while investigating technical bias by applying the same techniques to simulated microbial communities of known composition. Special thanks are given to J. Gregory Caporaso for providing the OTU-clustered data files for inclusion in the **phyloseq** package, from which this data was converted to TreeSummarizedExperiment.

## Usage

```
data(GlobalPatterns)
```

## Format

A TreeSummarizedExperiment with 19216 features and 26 samples. The rowData contains taxonomic information at Kingdom, Phylum, Class, Order, Family, Genus and Species levels. The colData includes:

**X.SampleID** Sample ID taken from the corresponding study

**Primer** primer used for sequencing

**Final\_Barcode** final barcode (6 nucleotides)

**Barcode\_truncated\_plus\_T** truncated barcode with an added tyrosine (6 nucleotides)

**Barcode\_full\_length** complete barcode with a length of 11 nucleotides

**SampleType** sampling type by collection site (Soil, Feces, Skin, Tongue, Freshwater, Creek Freshwater, Ocean, Estuary Sediment and Mock)

**Description** additional information (sampling location, environmental factors and study type)

## Author(s)

Caporaso, J. G., et al.

## References

Caporaso, J. G., et al. (2011). Global patterns of 16S rRNA diversity at a depth of millions of sequences per sample. PNAS, 108, 4516-4522. <https://doi.org/10.1073/pnas.1000080107>

**See Also**

[mia-datasets](#)

---

HintikkaXOData

*Multionics dataset from 40 rat samples*

---

**Description**

HintikkaXO is a multionics dataset from a rat experiment studying effect of fat and prebiotics in diet. It contains high-throughput profiling data from 40 rat samples, including 39 biomarkers, 38 metabolites (NMR), and 12706 OTUs from 318 species, measured from Cecum. This is diet comparison study with High/Low fat diet and xylo-oligosaccharide supplementation. Column metadata is common for all experiments (microbiota, metabolites, biomarkers) and is described below.

**Usage**

```
data(HintikkaXOData)
```

**Format**

A MultiAssayExperiment with 3 experiments (microbiota, metabolites and biomarkers). rowData of the microbiota experiment contains taxonomic information at Phylum, Class, Order, Family, Genus, Species and OTU levels. The metabolites and biomarkers experiments contain 38 NMR metabolites and 39 biomarkers, respectively. The colData includes:

**Sample** Sample ID (character)

**Rat** Rat ID (factor)

**Site** Site of measurement ("Cecum"); single value

**Diet** Diet group (factor; combination of the Fat and XOS fields)

**Fat** Fat in Diet (factor; Low/High)

**XOS** XOS Diet Supplement (numeric; 0/1)

**Author(s)**

Hintikka L et al.

**References**

Hintikka L et al. (2021): Xylo-oligosaccharides in prevention of hepatic steatosis and adipose tissue inflammation: associating taxonomic and metabolomic patterns in fecal microbiota with bi-clustering. International Journal of Environmental Research and Public Health 18(8):4049. <https://doi.org/10.3390/ijerph18084049>

**See Also**

[mia-datasets](#)

---

|              |                                                          |
|--------------|----------------------------------------------------------|
| importHUMAnN | <i>Import HUMAnN results to TreeSummarizedExperiment</i> |
|--------------|----------------------------------------------------------|

---

## Description

Import HUMAnN results to TreeSummarizedExperiment

## Arguments

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>file</code>     | Character scalar. Defines the file path of the HUMAnN file. The file must be in merged HUMAnN format.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>col.data</code> | a DataFrame-like object that includes sample names in rownames, or a single character value defining the file path of the sample metadata file. The file must be in tsv format (Default: NULL).                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>colData</code>  | Deprecated. Use <code>col.data</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>...</code>      | additional arguments: <ul style="list-style-type: none"> <li>• <code>assay.type</code>: Character scalar. Specifies the name of the assay used in calculation. (Default: "counts")</li> <li>• <code>prefix.rm</code>: Logical scalar. Should taxonomic prefixes be removed? (Default: FALSE)</li> <li>• <code>remove.suffix</code>: Logical scalar. Should suffixes of sample names be removed? HUMAnN pipeline adds suffixes to sample names. Suffixes are formed from file names. By selecting <code>remove.suffix = TRUE</code>, you can remove pattern from end of sample names that is shared by all. (Default: FALSE)</li> </ul> |

## Details

Import HUMAnN (currently version 3.0 supported) results of functional predictions based on metagenome composition (e.g. pathways or gene families). The input must be in merged HUMAnN format. (See [the HUMAnN documentation and humann\\_join\\_tables method](#).)

The function parses gene/pathway information along with taxonomy information from the input file. This information is stored to `rowData`. Abundances are stored to assays.

Usually the workflow includes also taxonomy data from Metaphlan. See [importMetaPhlAn](#) to load the data to TreeSE.

## Value

A [TreeSummarizedExperiment](#) object

## References

Beghini F, McIver LJ, Blanco-Míguez A, Dubois L, Asnicar F, Maharjan S, Mailyan A, Manghi P, Scholz M, Thomas AM, Valles-Colomer M, Weingart G, Zhang Y, Zolfo M, Huttenhower C, Franzosa EA, & Segata N (2021) Integrating taxonomic, functional, and strain-level profiling of diverse microbial communities with bioBakery 3. *eLife*. 10:e65088.

See Also

```
importMetaPhlAn convertFromPhyloseq convertFromBIOM convertFromDADA2 importQIIME2
importMothur
```

Examples

```
# File path
file_path <- system.file("extdata", "humann_output.tsv", package = "mia")
# Import data
tse <- importHUMANN(file_path)
tse
```

---

|                 |                                                             |
|-----------------|-------------------------------------------------------------|
| importMetaPhlAn | <i>Import Metaphlan results to TreeSummarizedExperiment</i> |
|-----------------|-------------------------------------------------------------|

---

Description

Import Metaphlan results to TreeSummarizedExperiment

Arguments

|             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| file        | NULL or DataFrame-like object. Defines the file path of the Metaphlan file. The file must be in merged Metaphlan format.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| col.data    | a DataFrame-like object that includes sample names in rownames, or a single character value defining the file path of the sample metadata file. The file must be in tsv format (Default: NULL).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| colData     | Deprecated. use col.data instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| sample_meta | Deprecated. Use col.data instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| tree.file   | Character scalar. Defines the file path of the phylogenetic tree. (Default: NULL).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| phy_tree    | Deprecated. Use tree.file instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| ...         | additional arguments: <ul style="list-style-type: none"><li>• assay.type: Character scalar. Specifies the name of the assay used in calculation. (Default: "metaphlan")</li><li>• prefix.rm: Logical scalar. Should taxonomic prefixes be removed? (Default: FALSE)</li><li>• remove.suffix: Logical scalar. Should suffixes of sample names be removed? Metaphlan pipeline adds suffixes to sample names. Suffixes are formed from file names. By selecting remove.suffix = TRUE, you can remove pattern from end of sample names that is shared by all. (Default: FALSE)</li><li>• set.ranks: Logical scalar. Should the columns in the rowData that are treated as taxonomy ranks be updated according to the ranks found in the imported data? (Default: FALSE)</li></ul> |

## Details

Import Metaphlan (versions 2, 3 and 4 supported) results. Input must be in merged Metaphlan format. (See [the Metaphlan documentation and merge\\_metaphlan\\_tables method](#).) Data is imported so that data at the lowest rank is imported as a TreeSummarizedExperiment object. Data at higher rank is imported as a SummarizedExperiment objects which are stored to altExp of TreeSummarizedExperiment object.

Currently Metaphlan versions 2, 3, and 4 are supported.

## Value

A [TreeSummarizedExperiment](#) object

## References

Beghini F, McIver LJ, Blanco-Míguez A, Dubois L, Asnicar F, Maharjan S, Mailyan A, Manghi P, Scholz M, Thomas AM, Valles-Colomer M, Weingart G, Zhang Y, Zolfo M, Huttenhower C, Franzosa EA, & Segata N (2021) Integrating taxonomic, functional, and strain-level profiling of diverse microbial communities with bioBakery 3. *eLife*. 10:e65088. doi: 10.7554/eLife.65088

## See Also

[convertFromPhyloseq](#) [convertFromBIOM](#) [convertFromDADA2](#) [importQIIME2](#) [importMothur](#)

## Examples

```
# (Data is from tutorial
# https://github.com/biobakery/biobakery/wiki/metaphlan3#merge-outputs)

# File path
file_path <- system.file(
  "extdata", "merged_abundance_table.txt", package = "mia")
# Import data
tse <- importMetaPhlAn(file_path)
# Data at the lowest rank
tse
# Data at higher rank is stored in altExp
altExps(tse)
# Higher rank data is in SE format, for example, Phylum rank
altExp(tse, "phylum")
```

---

importMothur

---

*Import Mothur results as a TreeSummarizedExperiment*


---

## Description

This method creates a TreeSummarizedExperiment object from Mothur files provided as input.

**Usage**

```
importMothur(
  assay.file = sharedFile,
  sharedFile,
  taxonomyFile = NULL,
  row.file = taxonomyFile,
  designFile = NULL,
  col.file = designFile
)
```

**Arguments**

|              |                                                                                                                                                                                                    |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| assay.file   | Character scalar. Defines the file path of the feature table to be imported. The File has to be in shared file format as defined in Mothur documentation.                                          |
| sharedFile   | Deprecated. Use assay.file instead.                                                                                                                                                                |
| taxonomyFile | Deprecated. Use row.file instead.                                                                                                                                                                  |
| row.file     | Character scalar. Defines the file path of the taxonomy table to be imported. The File has to be in taxonomy file or constaxonomy file format as defined in Mothur documentation. (Default: NULL). |
| designFile   | Deprecated. Use col.file instead.                                                                                                                                                                  |
| col.file     | Character scalar. Defines file path of the sample metadata to be imported. The File has to be in design file format as defined in Mothur documentation. (Default: NULL).                           |

**Details**

Results exported from Mothur can be imported as a SummarizedExperiment using importMothur. Except for the assay.file, the other data types, row.file, and col.file, are optional, but are highly encouraged to be provided.

**Value**

A [TreeSummarizedExperiment](#) object

**References**

<https://mothur.org/> [https://mothur.org/wiki/shared\\_file/](https://mothur.org/wiki/shared_file/) [https://mothur.org/wiki/taxonomy\\_file/](https://mothur.org/wiki/taxonomy_file/) [https://mothur.org/wiki/constaxonomy\\_file/](https://mothur.org/wiki/constaxonomy_file/) [https://mothur.org/wiki/design\\_file/](https://mothur.org/wiki/design_file/)

**See Also**

[convertFromPhyloseq](#) [convertFromBIOM](#) [convertFromDADA2](#) [importQIIME2](#)

## Examples

```
# Abundance table
counts <- system.file("extdata", "mothur_example.shared", package = "mia")
# Taxa table (in "cons.taxonomy" or "taxonomy" format)
taxa <- system.file(
  "extdata", "mothur_example.cons.taxonomy", package = "mia")
#taxa <- system.file("extdata", "mothur_example.taxonomy", package = "mia")
# Sample meta data
meta <- system.file("extdata", "mothur_example.design", package = "mia")

# Creates se object from files
se <- importMothur(assay.file = counts, row.file = taxa, col.file = meta)
# Convert SE to TreeSE
tse <- as(se, "TreeSummarizedExperiment")
tse
```

---

importQIIME2

---

*Import QIIME2 results to TreeSummarizedExperiment*


---

## Description

Results exported from QIIME2 can be imported as a TreeSummarizedExperiment using importQIIME2. Except for the assay.file, the other data types, row.file, refseq.file and tree.file, are optional, but are highly encouraged to be provided.

Import the QIIME2 artifacts to R.

## Usage

```
importQIIME2(
  assay.file = featureTableFile,
  featureTableFile,
  row.file = taxonomyTableFile,
  taxonomyTableFile = NULL,
  col.file = sampleMetaFile,
  sampleMetaFile = NULL,
  as.refseq = featureNamesAsRefSeq,
  featureNamesAsRefSeq = TRUE,
  refseq.file = refSeqFile,
  refSeqFile = NULL,
  tree.file = phyTreeFile,
  phyTreeFile = NULL,
  ...
)

importQZA(file, temp.dir = temp, temp = tempdir(), ...)
```

## Arguments

|                                   |                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>assay.file</code>           | Character scalar. Defines the file path of the feature table to be imported.                                                                                                                                                                                                                                                    |
| <code>featureTableFile</code>     | Deprecated. use <code>assay.file</code> instead.                                                                                                                                                                                                                                                                                |
| <code>row.file</code>             | Character scalar or NULL. Defines the file path of the taxonomy table to be imported. (default: NULL).                                                                                                                                                                                                                          |
| <code>taxonomyTableFile</code>    | Deprecated. use <code>row.file</code> instead.                                                                                                                                                                                                                                                                                  |
| <code>col.file</code>             | Character scalar or NULL. Defines the file path of the sample metadata to be imported. The file has to be in tsv format. (Default: NULL).                                                                                                                                                                                       |
| <code>sampleMetaFile</code>       | Deprecated. Use <code>col.file</code> instead.                                                                                                                                                                                                                                                                                  |
| <code>as.refseq</code>            | Logical scalar or NULL. Should the feature names of the feature table be regarded as reference sequences? This setting will be disregarded, if <code>refseq.file</code> is not NULL. If the feature names do not contain valid DNA characters only, the reference sequences will not be set.                                    |
| <code>featureNamesAsRefSeq</code> | Deprecated. Use <code>as.refseq</code> instead.                                                                                                                                                                                                                                                                                 |
| <code>refseq.file</code>          | Character scalar or NULL. Defines the file path of the reference sequences for each feature. (Default: NULL).                                                                                                                                                                                                                   |
| <code>refSeqFile</code>           | Deprecated. Use <code>refseq.file</code> instead.                                                                                                                                                                                                                                                                               |
| <code>tree.file</code>            | Character scalar. Defines the file path of the phylogenetic tree. (Default: NULL).                                                                                                                                                                                                                                              |
| <code>phyTreeFile</code>          | Deprecated. Use <code>tree.file</code> instead.                                                                                                                                                                                                                                                                                 |
| <code>...</code>                  | additional arguments: <ul style="list-style-type: none"> <li>• <code>temp.dir</code>: the temporary directory used for decompressing the data. (default: <code>tempdir()</code>)</li> <li>• <code>prefix.rm</code>: TRUE or FALSE: Should taxonomic prefixes be removed? (default: <code>prefix.rm = FALSE</code>)</li> </ul>   |
| <code>file</code>                 | character, path of the input qza file. Only files in format of <code>BIOMV210DirFmt</code> (feature table), <code>TSVTaxonomyDirectoryFormat</code> (taxonomic table), <code>NewickDirectoryFormat</code> (phylogenetic tree ) and <code>DNASequencesDirectoryFormat</code> (representative sequences) are supported right now. |
| <code>temp.dir</code>             | character, a temporary directory in which the qza file will be decompressed to, default <code>tempdir()</code> .                                                                                                                                                                                                                |
| <code>temp</code>                 | Deprecated. Use <code>temp.dir</code> instead.                                                                                                                                                                                                                                                                                  |

## Details

Both arguments `as.refseq` and `refseq.file` can be used to define reference sequences of features. `as.refseq` is only taken into account, if `refseq.file` is NULL. No reference sequences are tried to be created, if `featureNameAsRefSeq` is FALSE and `refseq.file` is NULL.



**Value**

A `TreeSummarizedExperiment` object

matrix object for feature table, `DataFrame` for taxonomic table, `ape::phylo` object for phylogenetic tree, `Biostrings::DNAStringSet` for representative sequences of taxa.

**Author(s)**

Yang Cao

**References**

Bolyen E et al. 2019: Reproducible, interactive, scalable and extensible microbiome data science using QIIME 2. *Nature Biotechnology* 37: 852–857. <https://doi.org/10.1038/s41587-019-0209-9>  
<https://qiime2.org>

**See Also**

[convertFromPhyloseq](#) [convertFromBIOM](#) [convertFromDADA2](#) [importMothur](#)

**Examples**

```
assay.file <- system.file("extdata", "table.qza", package = "mia")
row.file <- system.file("extdata", "taxonomy.qza", package = "mia")
col.file <- system.file("extdata", "sample-metadata.tsv", package = "mia")
tree.file <- system.file("extdata", "tree.qza", package = "mia")
refseq.file <- system.file("extdata", "refseq.qza", package = "mia")
tse <- importQIIME2(
  assay.file = assay.file,
  row.file = row.file,
  col.file = col.file,
  refseq.file = refseq.file,
  tree.file = tree.file
)

tse
# Read individual files
assay.file <- system.file("extdata", "table.qza", package = "mia")
row.file <- system.file("extdata", "taxonomy.qza", package = "mia")
col.file <- system.file("extdata", "sample-metadata.tsv", package = "mia")

assay <- importQZA(assay.file)
rowdata <- importQZA(row.file, prefix.rm = TRUE)
coldata <- read.table(col.file, header = TRUE, sep = "\t", comment.char = "")

# Assign rownames
rownames(coldata) <- coldata[, 1]
coldata[, 1] <- NULL

# Order coldata based on assay
coldata <- coldata[match(colnames(assay), rownames(coldata)), ]
```

```
# Create SE from individual files
se <- SummarizedExperiment(
  assays = list(assay), rowData = rowdata, colData = coldata)
se
```

---

|                |                                          |                          |             |                |           |
|----------------|------------------------------------------|--------------------------|-------------|----------------|-----------|
| importTaxpasta | <i>Import</i>                            | <i>taxpasta-specific</i> | <i>BIOM</i> | <i>results</i> | <i>to</i> |
|                | <a href="#">TreeSummarizedExperiment</a> |                          |             |                |           |

---

**Description**

Import taxpasta-specific BIOM results to [TreeSummarizedExperiment](#)

**Usage**

```
importTaxpasta(file, add.tree = TRUE, ...)
```

**Arguments**

- |          |                                                                                                                                                                                      |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| file     | Character scalar. Defines the file path to a BIOM file.                                                                                                                              |
| add.tree | Logical scalar. Specifies whether to calculate and add hierarchy tree using <a href="#">addHierarchyTree</a> . (Default: TRUE)                                                       |
| ...      | additional arguments <ul style="list-style-type: none"><li>set.ranks: Logical scalar. Should column names of taxonomy table be treated as taxonomy ranks? (Default: FALSE)</li></ul> |

**Details**

importTaxpasta imports data that is returned from Taxonomic Profile Aggregation and Standardization (taxpasta) pipeline. See more information on taxpasta from [taxpasta documentation](#).

**Value**

A [TreeSummarizedExperiment](#) object.

**See Also**

```
importBIOM convertFromBIOM
```

## Examples

```
## Not run:
# File path to BIOM file
file_path <- system.file("extdata", "complete.biom", package = "mia")
# Import BIOM as TreeSE, and set ranks.
tse <- importTaxpasta(file_path, set.ranks = TRUE)
# Import BIOM as TreeSE without adding hierarchy tree
tse <- importTaxpasta(file_path, add.tree = FALSE)

## End(Not run)
```

---

|        |                                                                                 |
|--------|---------------------------------------------------------------------------------|
| meltSE | Converting a <a href="#">SummarizedExperiment</a> object into a long data.frame |
|--------|---------------------------------------------------------------------------------|

---

## Description

meltSE Converts a [SummarizedExperiment](#) object into a long data.frame which can be used for tidyverse-tools.

## Usage

```
meltSE(x, ...)
```

```
## S4 method for signature 'SummarizedExperiment'
meltSE(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  add.row = add_row_data,
  add_row_data = NULL,
  add.col = add_col_data,
  add_col_data = NULL,
  row.name = feature_name,
  feature_name = "FeatureID",
  col.name = sample_name,
  sample_name = "SampleID",
  ...
)
```

```
## S4 method for signature 'SingleCellExperiment'
meltSE(x, add.dimred = NULL, ...)
```

## Arguments

x [TreeSummarizedExperiment](#).

... optional arguments:

|                           |                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                           | <ul style="list-style-type: none"> <li>• <code>check.names</code>: Logical scalar. Passed to <code>data.frame</code> function's <code>check.name</code> argument. Determines if sample names are checked that they are syntactically valid variable names and are not duplicated. If they are not, sample names are modified. (Default: TRUE)</li> </ul>                                          |
| <code>assay.type</code>   | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                                                                                                                                                                                                            |
| <code>assay_name</code>   | Deprecated. Use <code>assay.type</code> instead.                                                                                                                                                                                                                                                                                                                                                  |
| <code>add.row</code>      | Logical scalar or Character vector. To select information from the <code>rowData</code> to add to the molten assay data. If <code>add.row = NULL</code> no data will be added, if <code>add.row = TRUE</code> all data will be added and if <code>add.row</code> is a character vector, it will be used to subset to given column names in <code>rowData</code> . (Default: NULL)                 |
| <code>add_row_data</code> | Deprecated. Use <code>add.row</code> instead.                                                                                                                                                                                                                                                                                                                                                     |
| <code>add.col</code>      | Logical scalar, NULL, or character vector. Used to select information from the <code>colData</code> to add to the molten assay data. If <code>add.col = NULL</code> no data will be added, if <code>add.col = TRUE</code> all data will be added and if <code>add.col</code> is a character vector, it will be used to subset to given column names in <code>colData</code> . (Default: NULL)     |
| <code>add_col_data</code> | Deprecated. Use <code>add.col</code> instead.                                                                                                                                                                                                                                                                                                                                                     |
| <code>row.name</code>     | Character scalar. To use as the output's name for the feature identifier. (Default: "FeatureID")                                                                                                                                                                                                                                                                                                  |
| <code>feature_name</code> | Deprecated. Use <code>row.name</code> instead.                                                                                                                                                                                                                                                                                                                                                    |
| <code>col.name</code>     | Character scalar. To use as the output's name for the sample identifier. (Default: "SampleID")                                                                                                                                                                                                                                                                                                    |
| <code>sample_name</code>  | Deprecated. Use <code>col.name</code> instead.                                                                                                                                                                                                                                                                                                                                                    |
| <code>add.dimred</code>   | Logical scalar or Character vector. To select information from the <code>reducedDim</code> to add to the molten assay data. If <code>add.dimred = NULL</code> no data will be added, if <code>add.dimred = TRUE</code> all data will be added and if <code>add.dimred</code> is a character vector, it will be used to subset to given names in <code>reducedDimNames(x)</code> . (Default: NULL) |

## Details

If the `colData` contains a column "SampleID" or the `rowData` contains a column "FeatureID", they will be renamed to "SampleID\_col" and "FeatureID\_row", if row names or column names are set.

## Value

A tibble with the molten data. The assay values are given in a column named like the selected assay `assay.type`. In addition, a column "FeatureID" will contain the rownames, if set, and analogously a column "SampleID" with the colnames, if set.

## Examples

```
data(GlobalPatterns)
molten_tse <- meltSE(
  GlobalPatterns,
```

```

    assay.type = "counts",
    add.row = TRUE,
    add.col = TRUE
  )
  molten_tse

```

---

mergeSEs

---

Merge SE objects into single SE object.

---

## Description

Merge SE objects into single SE object.

## Usage

```

mergeSEs(x, ...)

## S4 method for signature 'SimpleList'
mergeSEs(
  x,
  assay.type = "counts",
  assay_name = NULL,
  join = "full",
  missing.values = missing_values,
  missing_values = NA,
  collapse.cols = collapse_samples,
  collapse_samples = FALSE,
  collapse.rows = collapse_features,
  collapse_features = TRUE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
mergeSEs(x, y = NULL, ...)

## S4 method for signature 'list'
mergeSEs(x, ...)

```

## Arguments

|            |                                                                                        |
|------------|----------------------------------------------------------------------------------------|
| x          | <a href="#">TreeSummarizedExperiment</a> .                                             |
| ...        | optional arguments (not used).                                                         |
| assay.type | Character scalar. Specifies the name of assay used in calculation. (Default: "counts") |
| assay_name | Deprecated. Use assay.type instead.                                                    |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>join</code>              | Character scalar. A value for selecting the joining method. Must be 'full', 'inner', 'left', or 'right'. 'left' and 'right' are disabled when more than two objects are being merged. (Default: "full")                                                                                                                                                                                                                                                                                                                |
| <code>missing.values</code>    | NA, 0 or Character scalar. Specifies the notation of missing values. (By default: NA)                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>missing_values</code>    | Deprecated. Use <code>missing.values</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>collapse.cols</code>     | Logical scalar. Determines whether to collapse identically named samples to one. (Default: FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>collapse_samples</code>  | Deprecated. Use <code>collapse.cols</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>collapse.rows</code>     | Logical scalar. Selects whether to collapse identically named features to one. Since all taxonomy information is taken into account, this concerns rownames-level (usually strain level) comparison. Often OTU or ASV level is just an arbitrary number series from sequencing machine meaning that the OTU information is not comparable between studies. With this option, it is possible to specify whether these strains are combined if their taxonomy information along with OTU number matches. (Default: TRUE) |
| <code>collapse_features</code> | Deprecated. Use <code>collapse.rows</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>verbose</code>           | Logical scalar. Choose whether to show messages. (Default: TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>y</code>                 | a <a href="#">SummarizedExperiment</a> object when <code>x</code> is a <a href="#">SummarizedExperiment</a> object. Disabled when <code>x</code> is a list.                                                                                                                                                                                                                                                                                                                                                            |

## Details

This function merges multiple `SummarizedExperiment` objects. It combines `rowData`, `assays`, and `colData` so that the output includes each unique row and column ones. The merging is done based on `rownames` and `colnames`. `rowTree` and `colTree` are preserved if linkage between rows/cols and the tree is found.

Equally named rows are interpreted as equal. Further matching based on `rowData` is not done. For samples, collapsing is disabled by default meaning that equally named samples that are stored in different objects are interpreted as unique. Collapsing can be enabled with `collapse.cols = TRUE` when equally named samples describe the same sample.

If, for example, all rows are not shared with individual objects, there are missing values in assays. The notation of missing can be specified with the `missing.values` argument. If input consists of `TreeSummarizedExperiment` objects, also `rowTree`, `colTree`, and `referenceSeq` are preserved if possible. The data is preserved if all the rows or columns can be found from it.

Compared to `cbind` and `rbind` `mergeSEs` allows more freely merging since `cbind` and `rbind` expect that rows and columns are matching, respectively.

You can choose joining methods from 'full', 'inner', 'left', and 'right'. In all the methods, all the samples are included in the result object. However, with different methods, it is possible to choose which rows are included.

- full – all unique features
- inner – all shared features

- left – all the features of the first object
- right – all the features of the second object

The output depends on the input. If the input contains SummarizedExperiment object, then the output will be SummarizedExperiment. When all the input objects belong to TreeSummarizedExperiment, the output will be TreeSummarizedExperiment.

### Value

A single SummarizedExperiment object.

### See Also

- TreeSummarizedExperiment::cbind
- TreeSummarizedExperiment::rbind
- [full\\_join](#)
- [inner\\_join](#)
- [left\\_join](#)
- [right\\_join](#)

### Examples

```
data(GlobalPatterns)
data(esophagus)
data(enterotype)

# Take only subsets so that it wont take so long
tse1 <- GlobalPatterns[1:100, ]
tse2 <- esophagus
tse3 <- enterotype[1:100, ]

# Merge two TreeSEs
tse <- mergeSEs(tse1, tse2)

# Merge a list of TreeSEs
list <- SimpleList(tse1, tse2, tse3)
tse <- mergeSEs(list, assay.type = "counts", missing.values = 0)
tse

# With 'join', it is possible to specify the merging method. Subsets are used
# here just to show the functionality
tse_temp <- mergeSEs(tse[1:10, 1:10], tse[5:100, 11:20], join = "left")
tse_temp

# If your objects contain samples that describe one and same sample,
# you can collapse equally named samples to one by specifying 'collapse.cols'
tse_temp <- mergeSEs(list(tse[1:10, 1], tse[1:20, 1], tse[1:5, 1]),
                     collapse.cols = TRUE,
                     join = "inner")
tse_temp
```

```
# Merge all available assays
tse <- transformAssay(tse, method="relabundance")
tse1 <- transformAssay(tse1, method="relabundance")
tse_temp <- mergeSEs(tse, tse1, assay.type = assayNames(tse))
```

---

mia-datasets

*mia datasets*


---

## Description

mia provides various datasets derived from independent experimental studies. The datasets represent instances of the TreeSummarizedExperiment and MultiAssayExperiment containers and can serve as tools to practice the mia functionality.

## Details

Currently, the following datasets are available:

- [dmn\\_se](#): A SummarizedExperiment with 130 features and 278 samples
- [enterotype](#): A TreeSummarizedExperiment with 553 features and 280 samples
- [esophagus](#): A TreeSummarizedExperiment with 58 features and 3 samples
- [GlobalPatterns](#): A TreeSummarizedExperiment with 19216 features and 26 samples
- [HintikkaX0Data](#): A MultiAssayExperiment with 3 experiments (microbiota, metabolites and biomarkers)
- [peerj13075](#): A TreeSummarizedExperiment with 674 features and 58 samples
- [Tengeler2020](#): A TreeSummarizedExperiment with 151 features and 27 samples
- [Tito2024QMP](#): A TreeSummarizedExperiment with 676 features and 589 samples

## Examples

```
# Load dataset from mia
library(mia)
data("GlobalPatterns", package = "mia")

# In this case, the dataset is a TreeSE, so it is renamed as tse
tse <- GlobalPatterns

# Print summary
tse
```



---

peerj13075

*Skin microbial profiles 58 genetically unrelated individuals*

---

## Description

peerj13075 includes skin microbial profiles of 58 volunteers with multiple factors. 16S r-RNA sequencing of V3-V4 regions was done to generate millions of read using illumina platform. A standard bioinformatic and statistical analysis done to explore skin bacterial diversity and its association with age, diet, geographical locations. The authors investigated significant association of skin microbiota with individual's geographical location.

## Usage

```
data(peerj13075)
```

## Format

A TreeSummarizedExperiment with 674 features and 58 samples. The rowData contains taxonomic information at kingdom, phylum, class, order, family and genus level. The colData includes:

**Sample** sample ID

**Geographical\_location** city where participant lives (Ahmednagar, Pune and Nashik)

**Gender** participant's gender (Male or Female)

**Age** participant's age group (Middle\_age, Adult and Elderly)

**Diet** participant's diet (Veg or Mixed)

## Author(s)

Potbhare, R., et al.

## References

Potbhare, R., RaviKumar, A., Munukka, E., Lahti, L., & Ashma, R. (2022). Skin microbiota diversity among genetically unrelated individuals of Indian origin. PeerJ, 10, e13075. <https://doi.org/10.7717/peerj.13075> Supplemental information includes OTU table and taxonomy table publicly-accessible from: <https://www.doi.org/10.7717/peerj.13075/supp-1> <https://www.doi.org/10.7717/peerj.13075/supp-2>

## See Also

[mia-datasets](#)

rarefyAssay

*Subsample Counts***Description**

rarefyAssay randomly subsamples counts within a SummarizedExperiment object and returns a new SummarizedExperiment containing the original assay and the new subsampled assay.

**Usage**

```

rarefyAssay(x, ...)

## S4 method for signature 'SummarizedExperiment'
rarefyAssay(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  sample = min_size,
  min_size = min(colSums2(assay(x, assay.type))),
  replace = FALSE,
  name = "subsampled",
  ...
)
```

**Arguments**

|            |                                                                                                                                                                                    |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x          | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                         |
| ...        | optional arguments: <ul style="list-style-type: none"> <li>• verbose: Logical scalar. Choose whether to show messages. (Default: TRUE)</li> </ul>                                  |
| assay.type | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                             |
| assay_name | Deprecated. Use assay.type instead.                                                                                                                                                |
| sample     | Integer scalar. Indicates the number of counts being simulated i.e. rarefying depth. This can equal to lowest number of total counts found in a sample or a user specified number. |
| min_size   | Deprecated. Use sample instead.                                                                                                                                                    |
| replace    | Logical scalar. Whether to perform subsampling with replacement. This works similarly to sample(..., replace = TRUE). (Default: FALSE)                                             |
| name       | Character scalar. The name for the transformed assay to be stored. (Default: method)                                                                                               |

## Details

Although the subsampling approach is highly debated in microbiome research, we include the `rarefyAssay` function because there may be some instances where it can be useful. Note that the output of `rarefyAssay` is not the equivalent as the input and any result have to be verified with the original dataset.

Subsampling/Rarefying may undermine downstream analyses and have unintended consequences. Therefore, make sure this normalization is appropriate for your data.

To maintain the reproducibility, please define the seed using `set.seed()` before implement this function.

When `replace = FALSE`, the function uses internally `vegan::rarefy` while with replacement enabled the function utilizes own implementation, inspired by `phyloseq::rarefy_even_depth`.

## Value

`rarefyAssay` return `x` with subsampled data.

## References

McMurdie PJ, Holmes S. Waste not, want not: why rarefying microbiome data is inadmissible. *PLoS computational biology*. 2014 Apr 3;10(4):e1003531.

Gloor GB, Macklaim JM, Pawlowsky-Glahn V & Egozcue JJ (2017) Microbiome Datasets Are Compositional: And This Is Not Optional. *Frontiers in Microbiology* 8: 2224. doi: 10.3389/fmicb.2017.02224

Weiss S, Xu ZZ, Peddada S, Amir A, Bittinger K, Gonzalez A, Lozupone C, Zaneveld JR, Vázquez-Baeza Y, Birmingham A, Hyde ER. Normalization and microbial differential abundance strategies depend upon data characteristics. *Microbiome*. 2017 Dec;5(1):1-8.

## See Also

- [vegan::rrarefy](#)
- [phyloseq::rarefy\\_even\\_depth](#)

## Examples

```
# When samples in TreeSE are less than specified sample, they will be
# removed. If after subsampling features are not present in any of the
# samples, they will be removed.
data(GlobalPatterns)
tse <- GlobalPatterns
set.seed(123)
tse_subsampled <- rarefyAssay(tse, sample = 60000, name = "subsampled")
tse_subsampled
dim(tse)
dim(assay(tse_subsampled, "subsampled"))
```

---

|         |                                                                                          |
|---------|------------------------------------------------------------------------------------------|
| splitOn | <i>Split TreeSummarizedExperiment column-wise or row-wise based on grouping variable</i> |
|---------|------------------------------------------------------------------------------------------|

---

## Description

Split TreeSummarizedExperiment column-wise or row-wise based on grouping variable

## Usage

```
splitOn(x, ...)

unsplitOn(x, ...)

## S4 method for signature 'SummarizedExperiment'
splitOn(x, group = f, f = NULL, ...)

## S4 method for signature 'SingleCellExperiment'
splitOn(x, group = f, f = NULL, ...)

## S4 method for signature 'TreeSummarizedExperiment'
splitOn(
  x,
  group = f,
  f = NULL,
  update.tree = update_rowTree,
  update_rowTree = TRUE,
  ...
)

## S4 method for signature 'list'
unsplitOn(x, update.tree = update_rowTree, update_rowTree = TRUE, ...)

## S4 method for signature 'SimpleList'
unsplitOn(x, update.tree = update_rowTree, update_rowTree = TRUE, ...)

## S4 method for signature 'SingleCellExperiment'
unsplitOn(
  x,
  altexp = altExpNames,
  altExpNames = names(altExps(x)),
  keep.dimred = keep_reducedDims,
  keep_reducedDims = FALSE,
  ...
)
```

**Arguments**

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x                | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| ...              | Arguments passed to <a href="#">agglomerateByVariable</a> function for SummarizedExperiment objects and other functions. See <a href="#">agglomerateByVariable</a> for more details. <ul style="list-style-type: none"> <li>• use.names: Logical scalar. Specifies whether to name elements of list by their group names. (Default: TRUE)</li> </ul>                                                                                                                                                         |
| group            | Character scalar, character vector or factor vector. A column name from <code>rowData(x)</code> or <code>colData(x)</code> or alternatively a vector specifying how the merging is performed. If vector, the value must be the same length as <code>nrow(x)/ncol(x)</code> . Rows/Cols corresponding to the same level will be merged. If <code>length(levels(group)) == nrow(x)/ncol(x)</code> , x will be returned unchanged. If group matches with both dimensions, by must be specified. (Default: NULL) |
| f                | Deprecated. Use group instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| update.tree      | Logical scalar. Should <code>rowTree()</code> also be merged? (Default: TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                |
| update_rowTree   | Deprecated. Use update.tree instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| altexp           | Character vector. Specify the alternative experiments to be unsplit. (Default: <code>names(altExps(x))</code> )                                                                                                                                                                                                                                                                                                                                                                                              |
| altExpNames      | Deprecated. Use altexp instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| keep.dimred      | Logical scalar. Should the <code>reducedDims(x)</code> be transferred to the result? Please note, that this breaks the link between the data used to calculate the reduced dims. (Default: FALSE)                                                                                                                                                                                                                                                                                                            |
| keep_reducedDims | Deprecated. Use keep.dimred instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

**Details**

`splitOn` split data based on grouping variable. Splitting can be done column-wise or row-wise. The returned value is a list of SummarizedExperiment objects; each element containing members of each group.

**Value**

For `splitOn`: SummarizedExperiment objects in a SimpleList.

For `unsplitOn`: x, with `rowData` and assay data replaced by the unsplit data. `colData` of x is kept as well and any existing `rowTree` is dropped as well, since existing `rowLinks` are not valid anymore.

**See Also**

[agglomerateByRanks](#) [agglomerateByVariable](#), [sumCountsAcrossFeatures](#), [agglomerateByRank](#), [altExps](#), [splitAltExps](#)

**Examples**

```

data(GlobalPatterns)
tse <- GlobalPatterns
# Split data based on SampleType.
se_list <- splitOn(tse, group = "SampleType")

# List of SE objects is returned.
se_list

# Create arbitrary groups
rowData(tse)$group <- sample(1:3, nrow(tse), replace = TRUE)
colData(tse)$group <- sample(1:3, ncol(tse), replace = TRUE)

# Split based on rows
# Each element is named based on their group name. If you don't want to name
# elements, use use_name = FALSE. Since "group" can be found from rowData and
# colData you must use `by`.
se_list <- splitOn(tse, group = "group", use.names = FALSE, by = 1)

# When column names are shared between elements, you can store the list to
# altExps
altExps(tse) <- se_list

altExps(tse)

# If you want to split on columns and update rowTree, you can do
se_list <- splitOn(tse, group = colData(tse)$group, update.tree = TRUE)

# If you want to combine groups back together, you can use unsplitBy
unsplitOn(se_list)

```

---

|                    |                                    |
|--------------------|------------------------------------|
| summarizeDominance | <i>Summarizing microbiome data</i> |
|--------------------|------------------------------------|

---

**Description**

To query a SummarizedExperiment for interesting features, several functions are available.

**Usage**

```

summarizeDominance(x, group = NULL, name = "dominant_taxa", ...)

getUnique(x, ...)

getTop(
  x,
  top = 5L,
  method = c("mean", "sum", "median"),

```

```

    assay.type = assay_name,
    assay_name = "counts",
    na.rm = TRUE,
    ...
)

## S4 method for signature 'SummarizedExperiment'
getTop(
  x,
  top = 5L,
  method = c("mean", "sum", "median", "prevalence"),
  assay.type = assay_name,
  assay_name = "counts",
  na.rm = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
getUnique(x, rank = NULL, ...)

## S4 method for signature 'SummarizedExperiment'
summarizeDominance(x, group = NULL, name = "dominant_taxa", ...)

## S4 method for signature 'SummarizedExperiment'
summary(object, assay.type = assay_name, assay_name = "counts")

```

## Arguments

|            |                                                                                                                                 |
|------------|---------------------------------------------------------------------------------------------------------------------------------|
| x          | <a href="#">TreeSummarizedExperiment</a> .                                                                                      |
| group      | With group, it is possible to group the observations in an overview. Must be one of the column names of colData.                |
| name       | Character scalar. A name for the column of the colData where results will be stored. (Default: "dominant_taxa")                 |
| ...        | Additional arguments passed on to <code>agglomerateByRank()</code> when rank is specified for <code>summarizeDominance</code> . |
| top        | Numeric scalar. Determines how many top taxa to return. Default is to return top five taxa. (Default: 5)                        |
| method     | Character scalar. Specify the method to determine top taxa. Either sum, mean, median or prevalence. (Default: "mean")           |
| assay.type | Character scalar. Specifies the name of the assay used in calculation. (Default: "counts")                                      |
| assay_name | Deprecated. Use <code>assay.type</code> instead.                                                                                |
| na.rm      | Logical scalar. Should NA values be omitted? (Default: TRUE)                                                                    |
| rank       | Character scalar. Defines a taxonomic rank. Must be a value of the output of <code>taxonomyRanks()</code> . (Default: NULL)     |
| object     | A <a href="#">SummarizedExperiment</a> object.                                                                                  |





```

# With group, it is possible to group observations based on specified groups
# Gets the overview of dominant taxa
dominant_taxa <- summarizeDominance(GlobalPatterns,
                                   rank = "Genus",
                                   group = "SampleType",
                                   na.rm = TRUE)

dominant_taxa

# Get an overview of sample and taxa counts
summary(GlobalPatterns, assay.type= "counts")

# Get unique taxa at a particular taxonomic rank
# sort = TRUE means that output is sorted in alphabetical order
# With na.rm = TRUE, it is possible to remove NAs
# sort and na.rm can also be used in function getTop
getUnique(GlobalPatterns, "Phylum", sort = TRUE)

```

---

taxonomyRanks

*Functions for accessing taxonomic data stored in rowData.*


---

## Description

These function work on data present in rowData and define a way to represent taxonomic data alongside the features of a SummarizedExperiment.

## Usage

```

taxonomyRanks(x)

taxonomyRankEmpty(
  x,
  rank = taxonomyRanks(x)[1L],
  empty.fields = c(NA, "", " ", "\t", "-", "_")
)

checkTaxonomy(x, ...)

getTaxonomyLabels(x, ...)

mapTaxonomy(x, ...)

## S4 method for signature 'SummarizedExperiment'
taxonomyRanks(x)

## S4 method for signature 'SummarizedExperiment'
taxonomyRankEmpty(

```

```

    x,
    rank = taxonomyRanks(x)[1],
    empty.fields = c(NA, "", " ", "\t", "-", "_")
  )

## S4 method for signature 'SummarizedExperiment'
checkTaxonomy(x)

setTaxonomyRanks(ranks)

getTaxonomyRanks()

## S4 method for signature 'SummarizedExperiment'
getTaxonomyLabels(
  x,
  empty.fields = c(NA, "", " ", "\t", "-", "_"),
  with.rank = with_rank,
  with_rank = FALSE,
  make.unique = make_unique,
  make_unique = TRUE,
  resolve.loops = resolve_loops,
  resolve_loops = FALSE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
mapTaxonomy(
  x,
  taxa = NULL,
  from = NULL,
  to = NULL,
  use.grepl = use_grepl,
  use_grepl = FALSE
)

IdTaxaToDataFrame(from)

```

## Arguments

|                           |                                                                                                                                                                                                                                                                       |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>            | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                                                                                                            |
| <code>rank</code>         | Character scalar. Defines a taxonomic rank. Must be a value of <code>taxonomyRanks()</code> function.                                                                                                                                                                 |
| <code>empty.fields</code> | Character vector. Defines which values should be regarded as empty. (Default: <code>c(NA, "", " ", "\t")</code> ). They will be removed if <code>na.rm = TRUE</code> before agglomeration.                                                                            |
| <code>...</code>          | additional arguments <ul style="list-style-type: none"> <li><code>lowest.rank</code>: A lowest taxonomy level to be considered in <code>getTaxonomyLabels</code>. Ranks lower than this will be collapsed into rank specified by <code>lowest.rank</code>.</li> </ul> |

For example, if genus level is specified, species will be collapsed into genus. If NULL, the data is not collapsed. (Default: NULL)

|                            |                                                                                                                                                                                                                                                      |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>ranks</code>         | Character vector. A vector of ranks to be set.                                                                                                                                                                                                       |
| <code>with.rank</code>     | Logical scalar. Should the level be add as a suffix? For example: "Phylum:Crenarchaeota". (Default: FALSE)                                                                                                                                           |
| <code>with_rank</code>     | Deprecated. Use <code>with.rank</code> instead.                                                                                                                                                                                                      |
| <code>make.unique</code>   | Logical scalar. Should the labels be made unique, if there are any duplicates? (Default: TRUE)                                                                                                                                                       |
| <code>make_unique</code>   | Deprecated. Use <code>make.unique</code> instead.                                                                                                                                                                                                    |
| <code>resolve.loops</code> | Logical scalar. Should <code>resolveLoops</code> be applied to the taxonomic data? Please note that has only an effect, if the data is unique. (Default: TRUE)                                                                                       |
| <code>resolve_loops</code> | Deprecated. Use <code>resolve.loops</code> instead.                                                                                                                                                                                                  |
| <code>taxa</code>          | Character vector. Used for subsetting the taxonomic information. If no information is found, NULL is returned for the individual element. (Default: NULL)                                                                                            |
| <code>from</code>          | <ul style="list-style-type: none"> <li>• For <code>mapTaxonomy</code>: character scalar. A value which must be a valid taxonomic rank. (Default: NULL)</li> <li>• otherwise a <code>Taxa</code> object as returned by <code>IdTaxa</code></li> </ul> |
| <code>to</code>            | Character Scalar. Must be a valid taxonomic rank. (Default: NULL)                                                                                                                                                                                    |
| <code>use.grepl</code>     | Logical. Should pattern matching via <code>grepl</code> be used? Otherwise literal matching is used. (Default: FALSE)                                                                                                                                |
| <code>use_grepl</code>     | Deprecated. Use <code>use.grepl</code> instead.                                                                                                                                                                                                      |

## Details

`taxonomyRanks` returns, which columns of `rowData(x)` are regarded as columns containing taxonomic information.

`taxonomyRankEmpty` checks, if a selected rank is empty of information.

`checkTaxonomy` checks, if taxonomy information is valid and whether it contains any problems. This is a soft test, which reports some diagnostic and might mature into a data validator used upon object creation.

`getTaxonomyLabels` generates a character vector per row consisting of the lowest taxonomic information possible. If data from different levels, is to be mixed, the taxonomic level is prepended by default.

`IdTaxaToDataFrame` extracts taxonomic results from results of `IdTaxa`.

`mapTaxonomy` maps the given features (taxonomic groups; `taxa`) to the specified taxonomic level (`to` argument) in `rowData` of the `SummarizedExperiment` data object (i.e. `rowData(x)[, taxonomyRanks(x)]`). If the argument `to` is not provided, then all matching taxonomy rows in `rowData` will be returned. This function allows handy conversions between different

Taxonomic information from the `IdTaxa` function of DECIPHER package are returned as a special class. With `as(taxa, "DataFrame")` the information can be easily converted to a `DataFrame` compatible with storing the taxonomic information a `rowData`. Please note that the assigned confidence information are returned as `metatdata` and can be accessed using `metadata(df)$confidence`.

**Value**

- taxonomyRanks: a character vector with all the taxonomic ranks found in `colnames(rowData(x))`
- taxonomyRankEmpty: a logical value
- mapTaxonomy: a list per element of taxa. Each element is either a `DataFrame`, a character or `NULL`. If all character results have the length of one, a single character vector is returned.

**See Also**

[agglomerateByRank](#), [toTree](#), [resolveLoop](#)

**Examples**

```
data(GlobalPatterns)
GlobalPatterns
taxonomyRanks(GlobalPatterns)

checkTaxonomy(GlobalPatterns)

table(taxonomyRankEmpty(GlobalPatterns,"Kingdom"))
table(taxonomyRankEmpty(GlobalPatterns,"Species"))

getTaxonomyLabels(GlobalPatterns[1:20,])
# Taxonomy labels represent the lowest taxonomy name that identifies each
# taxa. For instance, they can represent OTUs which does no necessarily
# tell much. In this case, you might want to get the labels with higher
# taxonomy rank
getTaxonomyLabels(GlobalPatterns[1:20,], lowest.rank = "Class")

# mapTaxonomy
## returns the unique taxonomic information
mapTaxonomy(GlobalPatterns)
# returns specific unique taxonomic information
mapTaxonomy(GlobalPatterns, taxa = "Escherichia")
# returns information on a single output
mapTaxonomy(GlobalPatterns, taxa = "Escherichia",to="Family")

# setTaxonomyRanks
tse <- GlobalPatterns
colnames(rowData(tse))[1] <- "TAXA1"

setTaxonomyRanks(colnames(rowData(tse)))
# Taxonomy ranks set to: taxa1 phylum class order family genus species

# getTaxonomyRanks is to get/check if the taxonomic ranks is set to "TAXA1"
getTaxonomyRanks()
```

---

Tengeler2020*Gut microbiota profiles of 27 individuals with ADHD and healthy controls*

---

**Description**

Tengeler2020 includes gut microbiota profiles of 27 persons with ADHD. A standard bioinformatic and statistical analysis done to demonstrate that altered microbial composition could be a driver of altered brain structure and function and concomitant changes in the animals' behavior. This was investigated by colonizing young, male, germ-free C57BL/6JOLA-Hsd mice with microbiota from individuals with and without ADHD.

**Usage**

```
data(Tengeler2020)
```

**Format**

A TreeSummarizedExperiment with 151 features and 27 samples. The rowData contains taxonomic information at Kingdom, Phylum, Class, Order, Family and Genus level. The colData includes:

**patient\_status** clinical status of the patient (ADHD or Control)

**cohort** cohort to which the patient belongs (Cohort\_1, Cohort\_2 and Cohort\_3)

**patient\_status\_vs\_cohort** combination of patient\_status and cohort

**sample\_name** unique sample ID

**Author(s)**

A.C. Tengeler, et al.

**References**

Tengeler, A.C., Dam, S.A., Wiesmann, M. et al. Gut microbiota from persons with attention-deficit/hyperactivity disorder affects the brain in mice. *Microbiome* 8, 44 (2020). <https://doi.org/10.1186/s40168-020-00816-x>

Supplemental information includes Home-cage activity, methods, results and imaging parameters and publicly-accessible from: [https://static-content.springer.com/esm/art%3A10.1186%2Fs40168-020-00816-x/MediaObjects/40168\\_2020\\_816\\_MOESM1\\_ESM.docx](https://static-content.springer.com/esm/art%3A10.1186%2Fs40168-020-00816-x/MediaObjects/40168_2020_816_MOESM1_ESM.docx) [https://static-content.springer.com/esm/art%3A10.1186%2Fs40168-020-00816-x/MediaObjects/40168\\_2020\\_816\\_MOESM2\\_ESM.docx](https://static-content.springer.com/esm/art%3A10.1186%2Fs40168-020-00816-x/MediaObjects/40168_2020_816_MOESM2_ESM.docx) [https://static-content.springer.com/esm/art%3A10.1186%2Fs40168-020-00816-x/MediaObjects/40168\\_2020\\_816\\_MOESM3\\_ESM.docx](https://static-content.springer.com/esm/art%3A10.1186%2Fs40168-020-00816-x/MediaObjects/40168_2020_816_MOESM3_ESM.docx)

**See Also**

[mia-datasets](#)

---

|             |                                                                                             |
|-------------|---------------------------------------------------------------------------------------------|
| Tito2024QMP | <i>Fecal microbiota samples from 589 patients across different colorectal cancer stages</i> |
|-------------|---------------------------------------------------------------------------------------------|

---

**Description**

The study combined Quantitative Microbiome Profiling (QMP) with extensive patient phenotyping from a group of 589 colorectal cancer (CRC) patients, advanced adenoma (AA) patients, and healthy controls. By implementing confounder control and quantitative profiling methods, the study was able to reveal potential misleading associations between microbial markers and colorectal cancer development that were driven by other factors like intestinal inflammation, rather than the cancer diagnosis itself.

**Usage**

`data(Tito2024QMP)`

**Format**

A TreeSummarizedExperiment with 676 features and 589 samples. The rowData contains species. The colData includes:

- sampleID** (character) Sample ID from the corresponding study
- diagnosis** (factor) Diagnosis type, with possible values: "ADE" (advanced adenoma), "CRC" (colorectal cancer), "CTL" (control)
- colonoscopy** (factor) Colonoscopy result, with possible values: "FIT\_Positive", "familial\_risk\_familial\_CRC\_FCC", "familial\_risk\_no", "abdomil\_complaints"

**Author(s)**

Shadman Ishraq

**References**

Raúl Y. Tito, Sara Verbandt, Marta Aguirre Vazquez, Leo Lahti, Chloe Verspecht, Verónica Lloréns-Rico, Sara Vieira-Silva, Janine Arts, Gwen Falony, Evelien Dekker, Joke Reumers, Sabine Tejpar & Jeroen Raes (2024). Microbiome confounders and quantitative profiling challenge predicted microbial targets in colorectal cancer development. Nature Medicine,30, 1339-1348. <https://doi.org/10.1038/s41591-024-02963-2>

**See Also**

[mia-datasets](#)

---

|                |                        |
|----------------|------------------------|
| transformAssay | <i>Transform assay</i> |
|----------------|------------------------|

---

## Description

Variety of transformations for abundance data, stored in assay. See details for options.

## Usage

```
transformAssay(x, ...)

## S4 method for signature 'SummarizedExperiment'
transformAssay(
  x,
  method,
  assay.type = "counts",
  assay_name = NULL,
  MARGIN = "samples",
  name = method,
  pseudocount = FALSE,
  ...
)

## S4 method for signature 'SingleCellExperiment'
transformAssay(x, altexp = NULL, ...)
```

## Arguments

|     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x   | <a href="#">TreeSummarizedExperiment</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| ... | additional arguments passed e.g. on to <code>vegan::decostand</code> or <code>philr::philr</code> . <ul style="list-style-type: none"> <li>• <code>reference</code>: Character scalar. Used to fill reference sample's column in returned assay when calculating <code>alr</code>. (Default: <code>NA</code>)</li> <li>• <code>ref_vals</code> Deprecated. Use <code>reference</code> instead.</li> <li>• <code>percentile</code>: Numeric scalar or <code>NULL</code> (<code>css</code>). Used to set the percentile value that calculates the scaling factors in the <code>css</code> normalization. If <code>NULL</code>, percentile is estimated from the data by calculating the portion of samples that exceed the threshold. (Default: <code>NULL</code>)</li> <li>• <code>scaling</code>: Numeric scalar. Adjusts the normalization scale by dividing the calculated scaling factors, effectively changing the magnitude of the normalized counts. (Default: <code>1000</code>).</li> <li>• <code>threshold</code>: Numeric scalar. For <code>"css"</code>, specifies relative difference threshold and determines the first point where the relative change in differences between consecutive quantiles exceeds this threshold. (Default: <code>0.1</code>) For <code>"cutoff"</code>, values less than or equal to the threshold are replaced with value. (Default: <code>0</code>)</li> </ul> |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          | <ul style="list-style-type: none"> <li>• <code>value</code>: Numeric scalar. For "cutoff", specifies the replacement value for counts less than or equal to the threshold. (Default: NA)</li> <li>• <code>tree</code>: phylo. Phylogeny used in PhILR transformation. If NULL, the tree is retrieved from <code>x</code>. (Default: NULL).</li> <li>• <code>node.labels</code>: Character vector. Linkages between tree and <code>x</code>. Used in PhILR transformation. (Default: NULL).</li> </ul> |
| <code>method</code>      | Character scalar. Specifies the transformation method.                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>assay.type</code>  | Character scalar. Specifies the name of assay used in calculation. (Default: "counts")                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>assay_name</code>  | Deprecated. Use <code>assay.type</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>MARGIN</code>      | Character scalar. Determines whether the transformation is applied sample (column) or feature (row) wise. (Default: "samples")                                                                                                                                                                                                                                                                                                                                                                        |
| <code>name</code>        | Character scalar. The name for the transformed assay to be stored. (Default: <code>method</code> )                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>pseudocount</code> | Logical scalar or numeric scalar. When TRUE, automatically adds half of the minimum positive value of <code>assay.type</code> (missing values ignored by default: <code>na.rm = TRUE</code> ). When FALSE, does not add any pseudocount ( <code>pseudocount = 0</code> ). Alternatively, a user-specified numeric value can be added as pseudocount. (Default: FALSE).                                                                                                                                |
| <code>altexp</code>      | Character vector or NULL. Specifies the names of alternative experiments to which the transformation should also be applied. If NULL, the transformation is only applied to the main experiment. (Default: NULL).                                                                                                                                                                                                                                                                                     |

## Details

`transformAssay` function provides a variety of options for transforming abundance data. The transformed data is calculated and stored in a new assay.

The `transformAssay` provides sample-wise (column-wise) or feature-wise (row-wise) transformation to the abundance table (assay) based on specified `MARGIN`.

The available transformation methods include:

- `'alr'`, `'chi.square'`, `'clr'`, `'frequency'`, `'hellinger'`, `'log'`, `'normalize'`, `'pa'`, `'rank'`, `'rclr'` relabundance', `'rrank'`, `'standardize'`, `'total'`: please refer to [decostand](#) for details.
- `'philr'`: please refer to [philr](#) for details.
- `'css'`: Cumulative Sum Scaling (CSS) can be used to normalize count data by accounting for differences in library sizes. By default, the function determines the normalization percentile for summing and scaling counts. If you want to specify the percentile value, good default value might be 0.5. The method is inspired by the CSS methods in [metagenomeSeq](#) package.
- `'log10'`: log10 transformation can be used for reducing the skewness of the data.

$$\log_{10} = \log_{10} x$$

where  $x$  is a single value of data.



- 'log2': log2 transformation can be used for reducing the skewness of the data.

$$\log 2 = \log_2 x$$

where  $x$  is a single value of data.

- 'difference': Pairwise differences between features. Calculates  $x - y$  for all unique feature pairs across samples, where  $x$  and  $y$  are entries of the specified assay.type.
- 'division': Pairwise ratios between features. Calculates  $x/y$  for all unique feature pairs across samples, where  $x$  and  $y$  are entries of the specified assay.type.
- 'invnorm': Inverse rank normalisation. Ranks values per sample/feature and maps them to standard normal quantiles.

$$z = \Phi^{-1} \left( \frac{r - \text{offset}}{n + 1 - 2 \text{offset}} \right)$$

Controlled by offset (default 0.5; also 0.375=Blom, 0=van der Waerden) and ties.method (passed to base::rank, default "average").

- 'pseudocount': Adds only pseudocount.
- 'cutoff': In some ecological studies, only strictly positive values are taken into account. This method keeps only values greater than threshold and replaces all other values with value.

## Value

transformAssay returns the input object x, with a new transformed abundance table named name added in the [assays](#).

## References

Paulson, J., Stine, O., Bravo, H. et al. (2013) Differential abundance analysis for microbial marker-gene surveys *Nature Methods* 10, 1200–1202. doi:10.1038/nmeth.2658

## See Also

- [vegan::decostand](#)
- [philr::philr](#)

## Examples

```
data(GlobalPatterns)
tse <- GlobalPatterns

# By specifying 'method', it is possible to apply different transformations,
# e.g. compositional transformation.
tse <- transformAssay(tse, method = "relabundance")

# The target of transformation can be specified with "assay.type"
# Pseudocount can be added by specifying 'pseudocount'.

# Perform CLR with half of the smallest positive value as pseudocount
```

```

tse <- transformAssay(
  tse, assay.type = "counts", method = "clr",
  pseudocount = TRUE
)

head(assay(tse, "clr"))

# Perform CSS normalization.
tse <- transformAssay(tse, method = "css")
head(assay(tse, "css"))

# With MARGIN, you can specify the if transformation is done for samples or
# for features. Here Z-transformation is done feature-wise.
tse <- transformAssay(tse, method = "standardize", MARGIN = "features")
head(assay(tse, "standardize"))

# Name of the stored table can be specified.
tse <- transformAssay(tse, method="hellinger", name="test")
head(assay(tse, "test"))

# pa returns presence absence table.
tse <- transformAssay(tse, method = "pa")
head(assay(tse, "pa"))

# rank returns ranks of taxa.
tse <- transformAssay(tse, method = "rank")
head(assay(tse, "rank"))

# In order to use other ranking variants, modify the chosen assay directly:
assay(tse, "rank_average", withDimnames = FALSE) <- colRanks(
  assay(tse, "counts"), ties.method = "average", preserveShape = TRUE)

# Using altexp parameter. First agglomerate the data and then apply
# transformation.
tse <- GlobalPatterns
tse <- agglomerateByRanks(tse)
tse <- transformAssay(
  tse, method = "relabundance", altexp = altExpNames(tse))
# The transformation is applied to all alternative experiments
altExp(tse, "Species")

## Not run:
# phlr transformation can be applied if the phlr package is installed.
# Subset data b taking only prevalent taxa
tse <- subsetByPrevalent(tse)
# Apply transformation
tse <- transformAssay(tse, method = "phlr", pseudocount = 1, MARGIN = 1L)
# The transformed data is added to altExp
altExp(tse, "phlr")

## End(Not run)

```

# Index

## \* datasets

- dmn\_se, [50](#)
- enterotype, [51](#)
- esophagus, [52](#)
- GlobalPatterns, [89](#)
- HintikkaX0Data, [90](#)
- mia-datasets, [104](#)
- peerj13075, [105](#)
- Tengeler2020, [117](#)
- Tito2024QMP, [118](#)
- ?agglomerateByRank, [85](#)
- addAbundanceClass (getAbundant), [53](#)
- addAbundanceClass, SingleCellExperiment-method (getAbundant), [53](#)
- addAbundanceClass, SummarizedExperiment-method (getAbundant), [53](#)
- addAlpha, [5](#), [21](#)
- addAlpha, SummarizedExperiment-method (addAlpha), [5](#)
- addCCA, [82](#)
- addCCA (getCCA), [56](#)
- addCCA, SingleCellExperiment-method (getCCA), [56](#)
- addCluster, [12](#)
- addCluster, SummarizedExperiment-method (addCluster), [12](#)
- addContaminantQC, [14](#)
- addContaminantQC, SummarizedExperiment-method (addContaminantQC), [14](#)
- addDissimilarity, [16](#), [21](#)
- addDissimilarity, SummarizedExperiment-method (addDissimilarity), [16](#)
- addDivergence, [20](#)
- addDivergence, SummarizedExperiment-method (addDivergence), [20](#)
- addDominant (getDominant), [67](#)
- addDominant, SummarizedExperiment-method (getDominant), [67](#)
- addDPCoA (getDPCoA), [69](#)
- addHierarchyTree, [98](#)
- addHierarchyTree (getHierarchyTree), [71](#)
- addHierarchyTree, SummarizedExperiment-method (getHierarchyTree), [71](#)
- addLDA, [88](#)
- addLDA (getLDA), [72](#)
- addLDA, SummarizedExperiment-method (getLDA), [72](#)
- addMDS (getMDS), [74](#)
- addMDS, SingleCellExperiment-method (getMDS), [74](#)
- addMediation, [22](#)
- addMediation, SummarizedExperiment-method (addMediation), [22](#)
- addNMDS (getNMDS), [75](#)
- addNMF, [88](#)
- addNMF (getNMF), [78](#)
- addNMF, SummarizedExperiment-method (getNMF), [78](#)
- addNotContaminantQC (addContaminantQC), [14](#)
- addNotContaminantQC, SummarizedExperiment-method (addContaminantQC), [14](#)
- addPerCellQC, [112](#)
- addPerFeatureQC, [112](#)
- addPERMANOVA (getPERMANOVA), [80](#)
- addPERMANOVA, SummarizedExperiment-method (getPERMANOVA), [80](#)
- addPerSampleDominantFeatures (deprecate), [42](#)
- addPerSampleDominantFeatures, SummarizedExperiment-method (deprecate), [42](#)
- addPerSampleDominantTaxa (deprecate), [42](#)
- addPerSampleDominantTaxa, SummarizedExperiment-method (deprecate), [42](#)
- addPrevalence (getPrevalence), [82](#)
- addPrevalence, SummarizedExperiment-method (getPrevalence), [82](#)
- addPrevalentAbundance (getPrevalence),

- 82
- addPrevalentAbundance, SummarizedExperiment-method  
(getPrevalence), 82
- addRDA, 82
- addRDA (getCCA), 56
- addRDA, SingleCellExperiment-method  
(getCCA), 56
- addTaxonomyTree (deprecate), 42
- addTaxonomyTree, SummarizedExperiment-method  
(deprecate), 42
- agglomerate-methods  
(agglomerateByRank), 27
- agglomerateByModule  
(agglomerateByRank), 27
- agglomerateByModule, SummarizedExperiment-method  
(agglomerateByRank), 27
- agglomerateByPrevalence, 26
- agglomerateByPrevalence, SummarizedExperiment-method  
(agglomerateByPrevalence), 26
- agglomerateByPrevalence, TreeSummarizedExperiment-method  
(agglomerateByPrevalence), 26
- agglomerateByRank, 26, 27, 30, 32, 85, 86,  
109, 116
- agglomerateByRank, SingleCellExperiment-method  
(agglomerateByRank), 27
- agglomerateByRank, SummarizedExperiment-method  
(agglomerateByRank), 27
- agglomerateByRank, TreeSummarizedExperiment-method  
(agglomerateByRank), 27
- agglomerateByRanks, 109
- agglomerateByRanks (agglomerateByRank),  
27
- agglomerateByRanks, SingleCellExperiment-method  
(agglomerateByRank), 27
- agglomerateByRanks, SummarizedExperiment-method  
(agglomerateByRank), 27
- agglomerateByRanks, TreeSummarizedExperiment-method  
(agglomerateByRank), 27
- agglomerateByVariable, 32, 109
- agglomerateByVariable  
(agglomerateByRank), 27
- agglomerateByVariable, SummarizedExperiment-method  
(agglomerateByRank), 27
- agglomerateByVariable, TreeSummarizedExperiment-method  
(agglomerateByRank), 27
- altExps, 32, 109
- ape::phylo, 97
- assay, 28
- assays, 121
- avgdist, 17
- bestDMNFit (calculateDMN), 34
- bestDMNFit, SummarizedExperiment-method  
(calculateDMN), 34
- BiocParallelParam, 6, 17, 36
- biom, 40
- Biostrings::DNAStringSet, 97
- bluster, 13
- BlusterParam, 13
- calculateCCA (getCCA), 56
- calculateDMN, 34, 51
- calculateDMN, ANY-method (calculateDMN),  
34
- calculateDMN, SummarizedExperiment-method  
(calculateDMN), 34
- calculateDMNgroup (calculateDMN), 34
- calculateDMNgroup, ANY-method  
(calculateDMN), 34
- calculateDMNgroup, SummarizedExperiment-method  
(calculateDMN), 34
- calculateDPCoA (getDPCoA), 69
- calculateJSD (deprecate), 42
- calculateJSD, ANY-method (deprecate), 42
- calculateNMDS (getNMDS), 75
- calculateOverlap (deprecate), 42
- calculateOverlap, ANY-method  
(deprecate), 42
- calculateRDA (getCCA), 56
- calculateUnifrac (deprecate), 42
- calculateUnifrac, ANY-method  
(deprecate), 42
- cca, 59
- checkTaxonomy (taxonomyRanks), 113
- checkTaxonomy, SummarizedExperiment-method  
(taxonomyRanks), 113
- cluster (deprecate), 42
- cluster, SummarizedExperiment-method  
(deprecate), 42
- colData, 21, 68
- convertFromBIOM, 40, 92–94, 97, 98
- convertFromBIOM (convertToBIOM), 39
- convertFromDADA2, 38, 40, 92–94, 97
- convertFromPhyloseq, 40, 92–94, 97
- convertFromPhyloseq  
(convertToPhyloseq), 41
- convertToBIOM, 39

- convertToBIOM, SummarizedExperiment-method  
(convertToBIOM), 39
- convertToPhyloseq, 41
- convertToPhyloseq, SummarizedExperiment-method  
(convertToPhyloseq), 41
- convertToPhyloseq, TreeSummarizedExperiment-method  
(convertToPhyloseq), 41
- cophenetic.phylo, 70
- countDominantFeatures (deprecate), 42
- countDominantFeatures, SummarizedExperiment-method  
(deprecate), 42
- countDominantTaxa (deprecate), 42
- countDominantTaxa, SummarizedExperiment-method  
(deprecate), 42
  
- dbrda, 59
- decontam:isContaminant, 15
- decontam:isNotContaminant, 15
- deconstand, 120
- deprecate, 42
- DirichletMultinomial, 34
- dist, 77
- diversity, 11
- dmn, 36, 37
- dmn\_se, 50, 104
- DMNGroup, 37
- dmngroup, 37
  
- enterotype, 51, 104
- esophagus, 52, 104
- estimateDivergence (deprecate), 42
- estimateDivergence, SummarizedExperiment-method  
(deprecate), 42
- estimateDiversity (deprecate), 42
- estimateDiversity, ANY-method  
(deprecate), 42
- estimateDominance (deprecate), 42
- estimateDominance, ANY-method  
(deprecate), 42
- estimateEvenness (deprecate), 42
- estimateEvenness, ANY-method  
(deprecate), 42
- estimateFaith (deprecate), 42
- estimateFaith, ANY-method (deprecate), 42
- estimateR, 9–11
- estimateRichness (deprecate), 42
- estimateRichness, ANY-method  
(deprecate), 42
- full\_join, 103
- full\_join (deprecate), 42
- full\_join, ANY-method (deprecate), 42
- getAbundanceClass (getAbundant), 53
- getAbundanceClass, ANY-method  
(getAbundant), 53
- getAbundanceClass, SingleCellExperiment-method  
(getAbundant), 53
- getAbundanceClass, SummarizedExperiment-method  
(getAbundant), 53
- getAbundant, 53
- getAbundant, ANY-method (getAbundant), 53
- getAbundant, SingleCellExperiment-method  
(getAbundant), 53
- getAbundant, SummarizedExperiment-method  
(getAbundant), 53
- getAlpha (addAlpha), 5
- getAlpha, SummarizedExperiment-method  
(addAlpha), 5
- getBestDMNFit (calculateDMN), 34
- getBestDMNFit, SummarizedExperiment-method  
(calculateDMN), 34
- getCCA, 56
- getCCA, ANY-method (getCCA), 56
- getCCA, SummarizedExperiment-method  
(getCCA), 56
- getConditionallyLowAbundant  
(getAbundant), 53
- getConditionallyLowAbundant, ANY-method  
(getAbundant), 53
- getConditionallyLowAbundant, SingleCellExperiment-method  
(getAbundant), 53
- getConditionallyLowAbundant, SummarizedExperiment-method  
(getAbundant), 53
- getCrossAssociation, 61
- getCrossAssociation, MultiAssayExperiment-method  
(getCrossAssociation), 61
- getCrossAssociation, SummarizedExperiment-method  
(getCrossAssociation), 61
- getDissimilarity, 75
- getDissimilarity (addDissimilarity), 16
- getDissimilarity, ANY-method  
(addDissimilarity), 16
- getDissimilarity, SummarizedExperiment-method  
(addDissimilarity), 16
- getDissimilarity, TreeSummarizedExperiment-method  
(addDissimilarity), 16
- getDivergence (addDivergence), 20

- getDivergence, SummarizedExperiment-method  
(addDivergence), 20
- getDMN (calculateDMN), 34
- getDMN, SummarizedExperiment-method  
(calculateDMN), 34
- getDominant, 67
- getDominant, SummarizedExperiment-method  
(getDominant), 67
- getDPCoA, 69
- getDPCoA, ANY, ANY-method (getDPCoA), 69
- getDPCoA, TreeSummarizedExperiment, missing-method  
(getDPCoA), 69
- getExperimentCrossAssociation  
(deprecate), 42
- getExperimentCrossAssociation, MultiAssayExperiment-method  
(deprecate), 42
- getExperimentCrossAssociation, SummarizedExperiment-method  
(deprecate), 42
- getExperimentCrossCorrelation  
(deprecate), 42
- getExperimentCrossCorrelation, ANY-method  
(deprecate), 42
- getHierarchyTree, 71
- getHierarchyTree, SummarizedExperiment-method  
(getHierarchyTree), 71
- getLDA, 72
- getLDA, SummarizedExperiment-method  
(getLDA), 72
- getLowAbundant (getAbundant), 53
- getLowAbundant, ANY-method  
(getAbundant), 53
- getLowAbundant, SingleCellExperiment-method  
(getAbundant), 53
- getLowAbundant, SummarizedExperiment-method  
(getAbundant), 53
- getMDS, 74
- getMDS, SingleCellExperiment-method  
(getMDS), 74
- getMDS, TreeSummarizedExperiment-method  
(getMDS), 74
- getMediation (addMediation), 22
- getMediation, SummarizedExperiment-method  
(addMediation), 22
- getNMDS, 75
- getNMDS, ANY-method (getNMDS), 75
- getNMDS, SingleCellExperiment-method  
(getNMDS), 75
- getNMDS, SummarizedExperiment-method  
(getNMDS), 75
- getNMF, 78
- getNMF, SummarizedExperiment-method  
(getNMF), 78
- getPermanentlyLowAbundant  
(getAbundant), 53
- getPermanentlyLowAbundant, ANY-method  
(getAbundant), 53
- getPermanentlyLowAbundant, SingleCellExperiment-method  
(getAbundant), 53
- getPermanentlyLowAbundant, SummarizedExperiment-method  
(getAbundant), 53
- getPERMANOVA, 80
- getPERMANOVA, ANY-method (getPERMANOVA),  
80
- getPERMANOVA, SingleCellExperiment-method  
(getPERMANOVA), 80
- getPERMANOVA, SummarizedExperiment-method  
(getPERMANOVA), 80
- getPrevalence, 82
- getPrevalence, ANY-method  
(getPrevalence), 82
- getPrevalence, SummarizedExperiment-method  
(getPrevalence), 82
- getPrevalent, 53, 55, 112
- getPrevalent (getPrevalence), 82
- getPrevalent, ANY-method  
(getPrevalence), 82
- getPrevalent, SummarizedExperiment-method  
(getPrevalence), 82
- getPrevalentAbundance (getPrevalence),  
82
- getPrevalentAbundance, ANY-method  
(getPrevalence), 82
- getPrevalentAbundance, SummarizedExperiment-method  
(getPrevalence), 82
- getPrevalentFeatures (deprecate), 42
- getPrevalentFeatures, ANY-method  
(deprecate), 42
- getPrevalentFeatures, SummarizedExperiment-method  
(deprecate), 42
- getPrevalentTaxa (deprecate), 42
- getPrevalentTaxa, ANY-method  
(deprecate), 42
- getPrevalentTaxa, SummarizedExperiment-method  
(deprecate), 42
- getRare, 53, 55
- getRare (getPrevalence), 82

- getRare, ANY-method (getPrevalence), 82
- getRare, SummarizedExperiment-method (getPrevalence), 82
- getRareFeatures (deprecate), 42
- getRareFeatures, ANY-method (deprecate), 42
- getRareFeatures, SummarizedExperiment-method (deprecate), 42
- getRareTaxa (deprecate), 42
- getRareTaxa, ANY-method (deprecate), 42
- getRareTaxa, SummarizedExperiment-method (deprecate), 42
- getRDA (getCCA), 56
- getRDA, ANY-method (getCCA), 56
- getRDA, SummarizedExperiment-method (getCCA), 56
- getReducedDimAttribute, 88
- getReducedDimAttribute, SingleCellExperiment-method (getReducedDimAttribute), 88
- getTaxonomyLabels (taxonomyRanks), 113
- getTaxonomyLabels, SummarizedExperiment-method (taxonomyRanks), 113
- getTaxonomyRanks (taxonomyRanks), 113
- getTop, 86
- getTop (summarizeDominance), 110
- getTop, SummarizedExperiment-method (summarizeDominance), 110
- getTopFeatures (deprecate), 42
- getTopFeatures, SummarizedExperiment-method (deprecate), 42
- getTopTaxa (deprecate), 42
- getTopTaxa, SummarizedExperiment-method (deprecate), 42
- getUnique (summarizeDominance), 110
- getUnique, SummarizedExperiment-method (summarizeDominance), 110
- getUniqueFeatures (deprecate), 42
- getUniqueFeatures, SummarizedExperiment-method (deprecate), 42
- getUniqueTaxa (deprecate), 42
- getUniqueTaxa, SummarizedExperiment-method (deprecate), 42
- GlobalPatterns, 89, 104
- hierarchy-tree (getHierarchyTree), 71
- HintikkaXOData, 90, 104
- IdTaxa, 115
- IdTaxaToDataFrame (taxonomyRanks), 113
- importBIOM, 98
- importBIOM (convertToBIOM), 39
- importHUMANn, 40, 91
- importMetaPhlan, 40, 91, 92, 92
- importMothur, 40, 92, 93, 93, 97
- importQIIME2, 40, 92-94, 95
- importQZA (importQIIME2), 95
- importTaxpasta, 98
- inner\_join, 103
- inner\_join (deprecate), 42
- inner\_join, ANY-method (deprecate), 42
- isContaminant (addContaminantQC), 14
- isContaminant, SummarizedExperiment-method (addContaminantQC), 14
- isNotContaminant, SummarizedExperiment-method (addContaminantQC), 14
- LDA, 93
- left\_join, 103
- left\_join (deprecate), 42
- left\_join, ANY-method (deprecate), 42
- loadFromBiom (deprecate), 42
- loadFromHumann (deprecate), 42
- loadFromMetaphlan (deprecate), 42
- loadFromMothur (deprecate), 42
- loadFromQIIME2 (deprecate), 42
- makePhyloseqFromTreeSE (deprecate), 42
- makePhyloseqFromTreeSE, SummarizedExperiment-method (deprecate), 42
- makePhyloseqFromTreeSE, TreeSummarizedExperiment-method (deprecate), 42
- makePhyloseqFromTreeSummarizedExperiment (deprecate), 42
- makePhyloseqFromTreeSummarizedExperiment, ANY-method (deprecate), 42
- makeTreeSEFromBiom (deprecate), 42
- makeTreeSEFromDADA2 (deprecate), 42
- makeTreeSEFromPhyloseq (deprecate), 42
- makeTreeSummarizedExperimentFromBiom (deprecate), 42
- makeTreeSummarizedExperimentFromDADA2 (deprecate), 42
- makeTreeSummarizedExperimentFromPhyloseq (deprecate), 42
- makeTreeSummarizedExperimentFromPhyloseq, ANY-method (deprecate), 42
- mapTaxonomy (taxonomyRanks), 113

- mapTaxonomy, SummarizedExperiment-method (taxonomyRanks), 113
- MASS::isoMDS, 77, 78
- mediate, 22–24
- meltAssay (deprecate), 42
- meltAssay, SummarizedExperiment-method (deprecate), 42
- meltSE, 99
- meltSE, SingleCellExperiment-method (meltSE), 99
- meltSE, SummarizedExperiment-method (meltSE), 99
- mergeCols (deprecate), 42
- mergeCols, SummarizedExperiment-method (deprecate), 42
- mergeCols, TreeSummarizedExperiment-method (deprecate), 42
- mergeFeatures (deprecate), 42
- mergeFeatures, SummarizedExperiment-method (deprecate), 42
- mergeFeatures, TreeSummarizedExperiment-method (deprecate), 42
- mergeFeaturesByPrevalence (deprecate), 42
- mergeFeaturesByPrevalence, SummarizedExperiment-method (deprecate), 42
- mergeFeaturesByRank (deprecate), 42
- mergeFeaturesByRank, SingleCellExperiment-method (deprecate), 42
- mergeFeaturesByRank, SummarizedExperiment-method (deprecate), 42
- mergeFeaturesByRank, TreeSummarizedExperiment-method (deprecate), 42
- mergeRows (deprecate), 42
- mergeRows, SummarizedExperiment-method (deprecate), 42
- mergeRows, TreeSummarizedExperiment-method (deprecate), 42
- mergeSamples (deprecate), 42
- mergeSamples, SummarizedExperiment-method (deprecate), 42
- mergeSamples, TreeSummarizedExperiment-method (deprecate), 42
- mergeSEs, 101
- mergeSEs, list-method (mergeSEs), 101
- mergeSEs, SimpleList-method (mergeSEs), 101
- mergeSEs, SummarizedExperiment-method (mergeSEs), 101
- metadata, 13, 36
- metagenomeSeq, 120
- mia (mia-package), 4
- mia-datasets, 104
- mia-package, 4
- MultiAssayExperiment, 62
- name, 9
- peerj13075, 104, 105
- perCellQCMetrics, 112
- perFeatureQCMetrics, 112
- performDMNgroupCV (calculateDMN), 34
- performDMNgroupCV, ANY-method (calculateDMN), 34
- performDMNgroupCV, SummarizedExperiment-method (calculateDMN), 34
- perSampleDominantFeatures (deprecate), 42
- perSampleDominantFeatures, SummarizedExperiment-method (deprecate), 42
- perSampleDominantTaxa (deprecate), 42
- perSampleDominantTaxa, SummarizedExperiment-method (deprecate), 42
- phir, 120
- phir::phir, 121
- phyloseq, 42
- phyloseq::rarefy\_even\_depth, 107
- picante::pd, 7
- plotColData, 11, 21
- plotMDS, 78
- plotNMDS (deprecate), 42
- plotReducedDim, 71
- quickPerCellQC, 112
- rarefyAssay, 106
- rarefyAssay, SummarizedExperiment-method (rarefyAssay), 106
- rbiom:unifrac(), 18
- readQZA (deprecate), 42
- reducedDims, 71
- relabundance (deprecate), 42
- relabundance, SummarizedExperiment-method (deprecate), 42
- relabundance<- (deprecate), 42
- relabundance<-, SummarizedExperiment-method (deprecate), 42



- relAbundanceCounts (deprecate), 42
- relAbundanceCounts, SummarizedExperiment-method (deprecate), 42
- resolveLoop, 72, 116
- right\_join, 103
- right\_join (deprecate), 42
- right\_join, ANY-method (deprecate), 42
- runCCA, 88
- runCCA (getCCA), 56
- runDMN (calculateDMN), 34
- runDPCoA (getDPCoA), 69
- runJSD (deprecate), 42
- runJSD, SummarizedExperiment-method (deprecate), 42
- runNMDS (getNMDS), 75
- runOverlap (deprecate), 42
- runOverlap, SummarizedExperiment-method (deprecate), 42
- runRDA (getCCA), 56
- runUnifrac (deprecate), 42
- scater::calculateMDS, 74, 75
- scater::runMDS, 74
- scores, 59
- setTaxonomyRanks (taxonomyRanks), 113
- splitAltExps, 31, 32, 109
- splitByRanks (agglomerateByRank), 27
- splitOn, 32, 108
- splitOn, SingleCellExperiment-method (splitOn), 108
- splitOn, SummarizedExperiment-method (splitOn), 108
- splitOn, TreeSummarizedExperiment-method (splitOn), 108
- stats::anova, 58, 81
- stats::TukeyHSD, 58, 81
- subsampleCounts (deprecate), 42
- subsampleCounts, SummarizedExperiment-method (deprecate), 42
- subsetByPrevalent (getPrevalence), 82
- subsetByPrevalent, SummarizedExperiment-method (getPrevalence), 82
- subsetByPrevalent, TreeSummarizedExperiment-method (getPrevalence), 82
- subsetByPrevalentFeatures (deprecate), 42
- subsetByPrevalentFeatures, ANY-method (deprecate), 42
- subsetByPrevalentTaxa (deprecate), 42
- subsetByPrevalentTaxa, ANY-method (deprecate), 42
- subsetByRare (getPrevalence), 82
- subsetByRare, SummarizedExperiment-method (getPrevalence), 82
- subsetByRare, TreeSummarizedExperiment-method (getPrevalence), 82
- subsetByRareFeatures (deprecate), 42
- subsetByRareFeatures, ANY-method (deprecate), 42
- subsetByRareTaxa (deprecate), 42
- subsetByRareTaxa, ANY-method (deprecate), 42
- subsetFeatures (deprecate), 42
- subsetFeatures, SummarizedExperiment-method (deprecate), 42
- subsetSamples (deprecate), 42
- subsetSamples, SummarizedExperiment-method (deprecate), 42
- subsetTaxa (deprecate), 42
- subsetTaxa, SummarizedExperiment-method (deprecate), 42
- sumCountsAcrossFeatures, 31, 32, 109
- SummarizedExperiment, 5, 13–15, 21–24, 36, 50, 55, 58, 62, 67, 68, 71, 74, 80–82, 88, 99, 102, 111, 112
- summarizeDominance, 110
- summarizeDominance, SummarizedExperiment-method (summarizeDominance), 110
- summary (summarizeDominance), 110
- summary, SummarizedExperiment-method (summarizeDominance), 110
- taxonomy-methods (taxonomyRanks), 113
- taxonomyRankEmpty (taxonomyRanks), 113
- taxonomyRankEmpty, SummarizedExperiment-method (taxonomyRanks), 113
- taxonomyRanks, 27, 113
- taxonomyRanks, SummarizedExperiment-method (taxonomyRanks), 113
- taxonomyTree (deprecate), 42
- taxonomyTree, SummarizedExperiment-method (deprecate), 42
- Tengeler2020, 104, 117
- testExperimentCrossAssociation (deprecate), 42
- testExperimentCrossAssociation, ANY-method (deprecate), 42

- testExperimentCrossCorrelation  
(deprecate), [42](#)
- testExperimentCrossCorrelation, ANY-method  
(deprecate), [42](#)
- Tito2024QMP, [104](#), [118](#)
- toTree, [72](#), [116](#)
- transformAssay, [119](#)
- transformAssay, SingleCellExperiment-method  
(transformAssay), [119](#)
- transformAssay, SummarizedExperiment-method  
(transformAssay), [119](#)
- transformCounts (deprecate), [42](#)
- transformFeatures (deprecate), [42](#)
- transformFeatures, SummarizedExperiment-method  
(deprecate), [42](#)
- transformSamples (deprecate), [42](#)
- transformSamples, SummarizedExperiment-method  
(deprecate), [42](#)
- TreeSummarizedExperiment, [5](#), [16](#), [17](#), [26](#),  
[30](#), [38–42](#), [58](#), [68](#), [70–73](#), [76–79](#), [85](#),  
[91](#), [93](#), [94](#), [97–99](#), [101](#), [106](#), [109](#),  
[111](#), [114](#), [119](#)
- twins (dmn\_se), [50](#)
- unsplitByRanks (agglomerateByRank), [27](#)
- unsplitByRanks, SingleCellExperiment-method  
(agglomerateByRank), [27](#)
- unsplitByRanks, TreeSummarizedExperiment-method  
(agglomerateByRank), [27](#)
- unsplitOn, [32](#)
- unsplitOn (splitOn), [108](#)
- unsplitOn, list-method (splitOn), [108](#)
- unsplitOn, SimpleList-method (splitOn),  
[108](#)
- unsplitOn, SingleCellExperiment-method  
(splitOn), [108](#)
- utilization\_functions  
(getReducedDimAttribute), [88](#)
- vegan::adonis2, [81](#), [82](#)
- vegan::betadisper, [58](#), [59](#), [81](#), [82](#)
- vegan::decostand, [121](#)
- vegan::diversity, [7](#)
- vegan::fisher.alpha, [7](#)
- vegan::monoMDS, [77](#), [78](#)
- vegan::permutest, [58](#), [81](#), [82](#)
- vegan::rrarefy, [107](#)
- vegan::avgdist(), [18](#)
- vegdist, [16–18](#), [58](#)
- ZTransform (deprecate), [42](#)
- ZTransform, SummarizedExperiment-method  
(deprecate), [42](#)