

Package ‘sizepower’

December 13, 2025

Title Sample Size and Power Calculation in Micorarray Studies
Version 1.81.0
Date 06 February 2006
Author Weiliang Qiu <weiliang.qiu@gmail.com> and Mei-Ling Ting Lee
<meilinglee@sph.osu.edu> and George Alex Whitmore
<george.whitmore@mcgill.ca>
Maintainer Weiliang Qiu <weiliang.qiu@gmail.com>
Depends stats
Description This package has been prepared to assist users in
computing either a sample size or power value for a microarray
experimental study. The user is referred to the cited
references for technical background on the methodology
underpinning these calculations. This package provides support
for five types of sample size and power calculations. These
five types can be adapted in various ways to encompass many of
the standard designs encountered in practice.
License LGPL
biocViews Microarray
git_url <https://git.bioconductor.org/packages/sizepower>
git_branch devel
git_last_commit e4dd327
git_last_commit_date 2025-10-29
Repository Bioconductor 3.23
Date/Publication 2025-12-12

Contents

power.matched	2
power.multi	3
power.randomized	4
sampleSize.matched	5
sampleSize.randomized	7

Index**9**

power.matched	<i>Power Calculations for Matched-Pairs Designs in Microarray Studies</i>
---------------	---

Description

This routine computes the individual power value for a matched-pairs design having n treatment units and n matched control units. This power value is the expected fraction of truly differentially expressed genes that will be correctly declared as differentially expressed by the tests.

Usage

```
power.matched(ER0, G0, absMu1, sigmad, n)
```

Arguments

ER0	mean number of false positives.
G0	anticipated number of genes in the experiment that are not differentially expressed.
absMu1	absolute mean difference in log-expression between treatment and control conditions as postulated under the alternative hypothesis H_1 .
sigmad	anticipated standard deviation of the difference in log-expression between matched treatment and control units. The relation between the standard deviation of the difference (sigmad) and the experimental error standard deviation (σ) is $\text{sigmad} = \sqrt{2}/\sigma$.
n	the sample size for each group.

Value

power	power.
psi1	non-centrality parameter.

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-power-matched050510.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>), George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers*, ISBN 0-7923-7087-2.

Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine*, **21**:3543-3570.

See Also

[power.randomized](#), [power.multi](#), [sampleSize.randomized](#), [sampleSize.matched](#)

Examples

```
power.matched(ER0=2, G0=5000, absMu1=1, sigmad=0.4243, n=4)
```

power.multi

Power Calculations for Multiple Treatments Design with an Isolated Treatment Effect in Microarray Studies

Description

Assume numTrt treatment conditions are being studied in either a completely randomized or randomized block design. Under the alternative hypothesis H1, one treatment is distinguished from the other numTrt - 1 treatments by exhibiting differential expression for the gene. This computer routine calculates the individual power value for the design. This power value is the expected fraction of truly differentially expressed genes that will be correctly declared as differentially expressed by the tests.

Usage

```
power.multi(ER0, G0, numTrt, absMu1, sigma, n)
```

Arguments

ER0	mean number of false positives.
G0	anticipated number of genes in the experiment that are not differentially expressed.
numTrt	total number of treatment conditions.
absMu1	the absolute difference in expression between the distinguished treatment and the other treatments on the log-intensity scale.
sigma	anticipated experimental error standard deviation of the difference in log-expression between treatments.
n	the sample size for each group.

Value

power	power.
psi1	non-centrality parameter.

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-power-isolated050510.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>), George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers*, ISBN 0-7923-7087-2.

Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine*, **21**:3543-3570.

See Also

[power.randomized](#), [power.matched](#), [sampleSize.randomized](#), [sampleSize.matched](#)

Examples

```
power.multi(ER0=2, G0=10000, numTrt=6, absMu1=0.585, sigma=0.3, n=8)
```

power.randomized	<i>Power Calculation for Completely Randomized Treatment-Control Designs in Microarray studies</i>
------------------	--

Description

This routine computes the individual power value for a completely randomized design with n treatment units and n control units ($2n$ units in total). This power value is the expected fraction of truly differentially expressed genes that will be correctly declared as differentially expressed by the tests.

Usage

```
power.randomized(ER0, G0, absMu1, sigmad, n)
```

Arguments

ER0	mean number of false positives.
G0	anticipated number of genes in the experiment that are not differentially expressed.
absMu1	absolute mean difference in log-expression between treatment and control conditions as postulated under the alternative hypothesis H1.
sigmad	anticipated standard deviation of the difference in log-expression between treatment and control conditions. The relation between the standard deviation of the difference (sigmad) and the experimental error standard deviation (sigma) is $\text{sigmad} = \sqrt{2}/\text{sigma}$.
n	the sample size for each group.

Value

power	power.
psi1	non-centrality parameter.

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-power-trt-cont050510.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>), George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers*, ISBN 0-7923-7087-2.

Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine*, **21**:3543-3570.

See Also

[power.matched](#), [power.multi](#), [sampleSize.randomized](#), [sampleSize.matched](#)

Examples

```
power.randomized(ER0=2, G0=5000, absMu1=1, sigmad=0.5657, n=8)
```

sampleSize.matched	<i>Sample Size Calculation for Matched-Pairs Designs in Microarray Studies</i>
--------------------	--

Description

This routine computes the sample size n required to achieve a specified power level for a matched-pairs design in which differential expression between n treatment units and n matched control units is of interest. The total number of experimental units for the study is $2n$.

Usage

```
sampleSize.matched(ER0, G0, power, absMu1, sigmad)
```

Arguments

ER0	mean number of false positives.
G0	anticipated number of genes in the experiment that are not differentially expressed.
power	specified power level for an individual gene, which represents the expected proportion of differentially expressed genes that will be declared as such by the tests.
absMu1	absolute mean difference in log-expression between treatment and control units as postulated under the alternative hypothesis H1.
sigmad	anticipated standard deviation of the difference in log-expression between matched treatment and control units.

Value

n	sample size for each group.
d	statistical difference between treatment and control conditions under H1 (i.e. $d = \text{absMu1} / \text{sigmad}$).

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-samplesize-matched050510.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>), George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

- Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers*, ISBN 0-7923-7087-2.
- Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine*, **21**:3543-3570.

See Also

[power.randomized](#), [power.matched](#) [power.multi](#), [sampleSize.randomized](#)

Examples

```
sampleSize.matched(ER0=1, G0=2000, power=0.9, absMu1=1, sigmad=0.5)
```

sampleSize.randomized *Sample Size Calculation for Completely Randomized Treatment-Control Designs in Microarray Studies*

Description

For any specified power, this routine computes the required sample size n for completely randomized designs in which differential expression between n treatment units and n control units is of interest. The total number of experimental units for the study is $2n$.

Usage

```
sampleSize.randomized(ER0, G0, power, absMu1, sigmad)
```

Arguments

ER0	mean number of false positives.
G0	anticipated number of genes in the experiment that are not differentially expressed.
power	specified power level for an individual gene, which represents the expected proportion of differentially expressed genes that will be declared as such by the tests.
absMu1	absolute mean difference in log-expression between treatment and control conditions as postulated under the alternative hypothesis H_1 .
sigmad	anticipated standard deviation of the difference in log-expression between treatment and control conditions. The relation between the standard deviation of the difference (sigmad) and the experimental error standard deviation (σ) is $\text{sigmad} = \sqrt{2}/\sigma$.

Value

n	sample size for each group.
d	statistical difference between treatment and control conditions under H_1 (i.e. $d = \text{absMu1}/\text{sigmad}$).

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-sampsize-trt-cont-050511r.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>), George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers*, ISBN 0-7923-7087-2.

Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine*, **21**:3543-3570.

See Also

[power.randomized](#), [power.matched](#), [power.multi](#), [sampleSize.matched](#)

Examples

```
sampleSize.randomized(ER0=1, G0=2000, power=0.9, absMu1=1, sigmad=0.566)
```

Index

* **design**

- power.matched, [2](#)
- power.multi, [3](#)
- power.randomized, [4](#)
- sampleSize.matched, [5](#)
- sampleSize.randomized, [7](#)

* **htest**

- power.matched, [2](#)
- power.multi, [3](#)
- power.randomized, [4](#)
- sampleSize.matched, [5](#)
- sampleSize.randomized, [7](#)

power.matched, [2](#), [4–6](#), [8](#)
power.multi, [3](#), [3](#), [5](#), [6](#), [8](#)
power.randomized, [3](#), [4](#), [4](#), [6](#), [8](#)

sampleSize.matched, [3–5](#), [5](#), [8](#)
sampleSize.randomized, [3–6](#), [7](#)