

Package ‘GeneNetworkBuilder’

October 16, 2019

Type Package

Version 1.26.1

Title GeneNetworkBuilder: a bioconductor package for building regulatory network using ChIP-chip/ChIP-seq data and Gene Expression Data

Author Jianhong Ou, Haibo Liu, Heidi A Tissenbaum and Lihua Julie Zhu

Maintainer Jianhong Ou <jianhong.ou@duke.edu>

Imports plyr, graph, htmlwidgets, Rgraphviz, rjson, XML, methods, grDevices, stats, graphics

Depends R (>= 2.15.1), Rcpp (>= 0.9.13)

Suggests RUnit, BiocGenerics, RBGL, knitr, simpIntLists, shiny, STRINGdb

LinkingTo Rcpp

Description Appliation for discovering direct or indirect targets of transcription factors using ChIP-chip or ChIP-seq, and microarray or RNA-seq gene expression data. Inputting a list of genes of potential targets of one TF from ChIP-chip or ChIP-seq, and the gene expression results, GeneNetworkBuilder generates a regulatory network of the TF.

License GPL (>= 2)

Lazyload yes

biocViews Sequencing, Microarray, GraphAndNetwork

VignetteBuilder knitr

RoxygenNote 6.1.1

git_url <https://git.bioconductor.org/packages/GeneNetworkBuilder>

git_branch RELEASE_3_9

git_last_commit 36a76a8

git_last_commit_date 2019-05-08

Date/Publication 2019-10-15

R topics documented:

| | |
|--------------------------------------|-----------|
| GeneNetworkBuilder-package | 2 |
| browseNetwork | 3 |
| browseNetwork-shiny | 4 |
| buildNetwork | 4 |
| ce.IDsMap | 5 |
| ce.interactionmap | 5 |
| ce.mapIDs | 6 |
| ce.miRNA.map | 7 |
| convertID | 7 |
| example.data | 8 |
| exportNetwork | 9 |
| filterNetwork | 9 |
| hs.IDsMap | 10 |
| hs.interactionmap | 11 |
| hs.mapIDs | 12 |
| hs.miRNA.map | 12 |
| networkFromGenes | 13 |
| polishNetwork | 13 |
| saveXGMML | 14 |
| uniqueExprsData | 15 |
| Index | 16 |

GeneNetworkBuilder-package

Build Regulatory Network from ChIP-chip/ChIP-seq and Expression Data

Description

Appliation for discovering direct or indirect targets of transcription factors using ChIP-chip or ChIP-seq, and microarray or RNA-seq gene expression data. Inputting a list of genes of potential targets of one TF from ChIP-chip or ChIP-seq, and the gene expression results, GeneNetworkBuilder generates a regulatory network of the TF.

Author(s)

Maintainer: Jianhong Ou Developer <jianhong.ou@duke.edu>

Authors:

- Lihua Julie Zhu Developer <Julie.Zhu@umassmed.edu>

| | |
|---------------|-----------------------|
| browseNetwork | <i>browse network</i> |
|---------------|-----------------------|

Description

plot network generated by [polishNetwork](#)

Usage

```
browseNetwork(gR = graphNEL(), layoutType = c("fdp", "dot", "neato",  
  "twopi", "circo"), width = NULL, height = NULL, maxNodes = 500,  
  ...)
```

Arguments

| | |
|------------|---|
| gR | an object of graphNEL |
| layoutType | layout type. see GraphvizLayouts |
| width | width of the figure |
| height | height of the figure |
| maxNodes | max nodes number to plot. Because if there are too many nodes, the running time will be too long. |
| ... | parameters used by GraphvizLayouts |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

Examples

```
data("ce.miRNA.map")  
data("example.data")  
data("ce.interactionmap")  
data("ce.IDsMap")  
sifNetwork<-buildNetwork(example.data$ce.bind, ce.interactionmap, level=2)  
cifNetwork<-filterNetwork(rootgene=ce.IDsMap["DAF-16"], sifNetwork=sifNetwork,  
  exprsData=uniqueExprsData(example.data$ce.exprData, "Max", condenseName='logFC'),  
  mergeBy="symbols",  
  miRNAlist=as.character(ce.miRNA.map[ , 1]), tolerance=1)  
gR<-polishNetwork(cifNetwork)  
browseNetwork(gR)
```

browseNetwork-shiny *Shiny bindings for browseNetwork*

Description

Output and render functions for using `browseNetwork` within Shiny applications and interactive Rmd documents.

Usage

```
browseNetworkOutput(outputId, width = "100%", height = "400px")
```

```
renderBrowseNetwork(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

| | |
|----------------------------|--|
| <code>outputId</code> | output variable to read from |
| <code>width, height</code> | Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended. |
| <code>expr</code> | An expression that generates a <code>browseNetwork</code> |
| <code>env</code> | The environment in which to evaluate <code>expr</code> . |
| <code>quoted</code> | Is <code>expr</code> a quoted expression (with <code>quote()</code>)? This is useful if you want to save an expression in a variable. |

buildNetwork *construct the regulatory network*

Description

Get all the connections of interesting genes from regulatory map.

Usage

```
buildNetwork(TFbindingTable, interactionmap, level = 3)
```

Arguments

| | |
|-----------------------------|---|
| <code>TFbindingTable</code> | a matrix or <code>data.frame</code> with interesting genes. Column names must be 'from', 'to' |
| <code>interactionmap</code> | Transcription regulatory map. Column names of <code>interactionmap</code> must be 'from','to' |
| <code>level</code> | Depth of node path |

Value

a `dataframe` or matrix of all the connections of interesting genes

Examples

```
data("ce.interactionmap")
data("example.data")
xx<-buildNetwork(example.data$ce.bind, ce.interactionmap, level=2)
```

`ce.IDsMap`*C.elegns gene name to wormbase identifier map*

Description

map file for converting gene name or sequence name of *Caenorhabditis elegans* to wormbase identifier

Usage`ce.IDsMap`**Format**

character vector

Details

character vector with gene name or sequence name as names and wormbase identifier as values.

Source

<http://www.wormbase.org/>

Examples

```
data(ce.IDsMap)
head(ce.IDsMap)
```

`ce.interactionmap`*transcript regulatory map of Caenorhabditis elegans*

Description

transcript regulatory map of *Caenorhabditis elegans*

Usage`ce.interactionmap`**Format**

datafram

Details

transcript regulatory map of *Caenorhabditis elegans* is generated using databases edgedb and microCosm Targets.

Source

<http://edgedb.umassmed.edu>, <http://www.ebi.ac.uk/enright-srv/microcosm/htdocs/targets/v5/>

Examples

```
data(ce.interactionmap)
head(ce.interactionmap)
```

| | |
|-----------|---|
| ce.mapIDs | <i>map file for converting from wormbase identifier to Caenorhabditis elegans gene name</i> |
|-----------|---|

Description

map file for converting from wormbase identifier to *Caenorhabditis elegans* gene name

Usage

```
ce.mapIDs
```

Format

character vector

Details

character vector with wormbase identifier as names and gene name as values.

Source

<http://www.wormbase.org/>

Examples

```
data(ce.mapIDs)
head(ce.mapIDs)
```

| | |
|--------------|--|
| ce.miRNA.map | <i>micro RNA of Caenorhabditis elegans</i> |
|--------------|--|

Description

micro RNA of *Caenorhabditis elegans*

Usage

```
ce.miRNA.map
```

Format

dataframe

Details

The first column is wormbase identifier. And the second column is miRNA names.

Source

<http://www.mirbase.org/>

Examples

```
data(ce.miRNA.map)
head(ce.miRNA.map)
```

| | |
|-----------|-----------------------------------|
| convertID | <i>convert gene IDs by id map</i> |
|-----------|-----------------------------------|

Description

For same gene, there are multiple gene alias. In order to eliminate the possibility of missing any connections, convert the gene symbols to unique gene ids is important. This function can convert the gene symbols to unique ids and convert it back according a giving map.

Usage

```
convertID(x, IDsMap, ByName = c("from", "to"))
```

Arguments

| | |
|--------|--|
| x | a matrix or dataframe contain the columns to be converted. |
| IDsMap | a character vector of the identifier map |
| ByName | the column names to be converted |

Value

a matrix or dataframe with converted gene IDs

Examples

```
data("ce.IDsMap")
bind<-cbind(from="daf-16", to=c("fkh-7", "hlh-13", "mxl-3", "nhr-3", "lfi-1"))
convertID(toupper(bind), ce.IDsMap, ByName=c("from", "to"))
```

example.data

example datasets for documentation

Description

example.data is a data list of example datasets. There is a dataset example.microarrayData, which is the example of gene expression data of a gene-chip result of *C.elegans*. Dataset example.data\$ce.bind is a TF binding matrix of ChIP-chip experiment of *C.elegans*. Dataset example.data\$cd.exprData is expression data of a gene-chip result of *C.elegans*. Dataset example.data\$hs.bind is a TF binding matrix of ChIP-chip experiment of *H.sapiens*. Dataset example.data\$hs.exprData is expression data of a combination of a gene-chip result and a RNA-SEQ result of *H.sapiens*.

Usage

```
example.data
```

Format

```
dataframe
```

Details

The dataset example.microarrayData contains columns: ID, logFC, AveExpr, t, P.Value, adj.P.Val, B, genes and symbols. The columns of ID, logFC and symbols are required by GeneNetwork-Builder. The dataset example.data\$hs.bind contains columns: ID, symbols, logFC and P.Value. The dataset example.data\$hs.exprData contains columns: from and to.

Examples

```
data(example.data)
names(example.data)
head(example.data$example.microarrayData)
head(example.data$ce.bind)
head(example.data$ce.exprData)
head(example.data$hs.bind)
head(example.data$hs.exprData)
```

| | |
|---------------|--|
| exportNetwork | <i>Save network in various formats</i> |
|---------------|--|

Description

Save graph into HTML, json or xgmml format.

Usage

```
exportNetwork(network, file, format = c("HTML", "json", "XGMML"), ...)
```

Arguments

| | |
|---------|--|
| network | output of browseNetwork |
| file | Name of the file to save to. |
| format | type in which graph shall be saved. Could be one of HTML, json or XGMML. |
| ... | Parameter could be used by saveWidget for HTML or <code>writeLines</code> for json or saveXML for XGMML. |

Examples

```
data("ce.miRNA.map")
data("example.data")
data("ce.interactionmap")
data("ce.IDsMap")
sifNetwork<-buildNetwork(example.data$ce.bind, ce.interactionmap, level=2)
cifNetwork<-filterNetwork(rootgene=ce.IDsMap["DAF-16"], sifNetwork=sifNetwork,
  exprsData=uniqueExprsData(example.data$ce.exprData, "Max", condenseName='logFC'),
  mergeBy="symbols",
  miRNAlist=as.character(ce.miRNA.map[, 1]), tolerance=1)
gR<-polishNetwork(cifNetwork)
network <- browseNetwork(gR)
exportNetwork(network, "sample.html")
```

| | |
|---------------|--|
| filterNetwork | <i>filter the regulatory network table by expression profile</i> |
|---------------|--|

Description

verify every nodes in the regulatory network by expression profile

Usage

```
filterNetwork(rootgene, sifNetwork, exprsData, mergeBy = "symbols",
  miRNAlist, remove_miRNA = FALSE, tolerance = 0, cutoffPVal = 0.01,
  cutoffLFC = 0.5, minify = TRUE, miRNAtol = FALSE)
```

Arguments

| | |
|--------------|--|
| rootgene | name of root gene. It must be the ID used in xx regulatory network |
| sifNetwork | Transcription regulatory network table. Column names of xx must be 'from','to' |
| exprsData | dataset of expression comparison data, which should contain column logFC and column given by exprsDataByName |
| mergeBy | The column name contains ID information used to merge with 'to' column of sifNetwork in exprsData |
| miRNAlist | vector of microRNA ids. |
| remove_miRNA | remove miRNA from the network or not. Bool value, TRUE or FALSE |
| tolerance | maximum number of unverified nodes in each path |
| cutoffPVal | cutoff p value of valid differential expressed gene/miRNA |
| cutoffLFC | cutoff log fold change value of a valid differential expressed gene/miRNA |
| minify | Only keep the best path if multiple paths exists for single node? Bool value, TRUE or FALSE |
| miRNAtol | take miRNA expression into account for tolerance calculation. Bool value, TRUE or FALSE |

Value

a dataframe of filtered regulatory network by expression profile

Examples

```
data("ce.miRNA.map")
data("example.data")
data("ce.interactionmap")
data("ce.IDsMap")
sifNetwork<-buildNetwork(example.data$ce.bind, ce.interactionmap, level=2)
cifNetwork<-filterNetwork(rootgene=ce.IDsMap["DAF-16"], sifNetwork=sifNetwork,
  exprsData=uniqueExprsData(example.data$ce.exprData, "Max", condenseName='logFC'),
  mergeBy="symbols",
  miRNAlist=as.character(ce.miRNA.map[ , 1]), tolerance=1)
```

hs.IDsMap

map file for converting gene name or sequence name of Homo sapiens to Entrez identifier

Description

map file for converting gene name or sequence name of *Homo sapiens* to Entrez identifier

Usage

```
hs.IDsMap
```

Format

character vector

Details

character vector with gene name as names and Entrez identifier as values.

Examples

```
data(hs.IDsMap)
head(hs.IDsMap)
```

| | |
|-------------------|--|
| hs.interactionmap | <i>transcript regulation map of Homo sapiens</i> |
|-------------------|--|

Description

transcript regulation map of *Homo sapiens*

Usage

```
hs.interactionmap
```

Format

datafram

Details

transcript regulatory map of *Homo sapiens* is generated using databases FANTOM, mirGen and microCosm Targets.

Source

<http://fantom.gsc.riken.jp/5/>, <http://www.ebi.ac.uk/enright-srv/microcosm/htdocs/targets/v5/>, http://carolina.imis.athena-innovation.gr/diana_tools/web/index.php

Examples

```
data(hs.interactionmap)
head(hs.interactionmap)
```

| | |
|-----------|---|
| hs.mapIDs | <i>map file for converting from Entrez identifier to Homo sapiens gene name</i> |
|-----------|---|

Description

map file for converting from Entrez identifier to *Homo sapiens* gene name

Usage

```
hs.mapIDs
```

Format

character vector

Details

character vector with Entrez identifier as names and gene name as values.

Examples

```
data(hs.mapIDs)
head(hs.mapIDs)
```

| | |
|--------------|----------------------------------|
| hs.miRNA.map | <i>micro RNA of Homo sapiens</i> |
|--------------|----------------------------------|

Description

micro RNA of *Homo sapiens*

Usage

```
hs.miRNA.map
```

Format

dataframe

Details

The first column is entrez identifier. And the second column is miRNA names.

Source

<http://www.mirbase.org/>

Examples

```
data(hs.miRNA.map)
head(hs.miRNA.map)
```

| | |
|------------------|---|
| networkFromGenes | <i>Build network by a list of given genes</i> |
|------------------|---|

Description

By providing a list of given genes, build a network for input of filterNetwork.

Usage

```
networkFromGenes(genes, interactionmap, level = 3)
```

Arguments

| | |
|----------------|--|
| genes | A vector of character for interested genes. |
| interactionmap | Transcription regulatory map. Column names of interactionmap must be 'from','to' |
| level | Depth of node path |

Value

a list with elements: rootgene: The nodes with maximal connetions. sifNetwork: Transcription regulatory network table.

Examples

```
data("ce.interactionmap")
data("example.data")
genes <- as.character(example.data$ce.bind$from)
xx<-networkFromGenes(example.data$ce.bind, ce.interactionmap, level=2)
```

| | |
|---------------|---|
| polishNetwork | <i>generate an object of grahpNEL to represent the regulation network</i> |
|---------------|---|

Description

generate an object of grahpNEL to represent the regulation network. Each node will has three attributes: size, borderColor and fill.

Usage

```
polishNetwork(cifNetwork, nodesDefaultSize = 48,
  useLogFCAsWeight = FALSE, nodecolor = colorRampPalette(c("green",
  "yellow", "red"))(5), nodeBg = "white", nodeBorderColor = list(gene =
  "darkgreen", miRNA = "darkblue"), edgelwd = 0.25, ...)
```

Arguments

| | |
|------------------|--|
| cifNetwork | dataframe used to draw network graph. column names of cifNetwork must contain 'from', 'to', 'logFC' and 'miRNA' |
| nodesDefaultSize | nodes default size |
| useLogFCAsWeight | how to determine the weights for each nodes. If TRUE, use logFC value as weight. If FALSE, use constant 1 as weight. |
| nodecolor | a character vector of color set. The node color will be mapped to color set by log fold change |
| nodeBg | background of node |
| nodeBorderColor | a list of border node color set. nodeBorderColor's element must be gene and miRNA |
| edgelwd | the width of edge |
| ... | any parameters can be passed to graph.par |

Value

An object of graphNEL class of the network

Examples

```
data("ce.miRNA.map")
data("example.data")
data("ce.interactionmap")
data("ce.IDsMap")
sifNetwork<-buildNetwork(example.data$ce.bind, ce.interactionmap, level=2)
cifNetwork<-filterNetwork(rootgene=ce.IDsMap["DAF-16"], sifNetwork=sifNetwork,
  exprsData=uniqueExprsData(example.data$ce.exprData, "Max", condenseName='logFC'),
  mergeBy="symbols",
  miRNAlist=as.character(ce.miRNA.map[, 1]), tolerance=1)
gR<-polishNetwork(cifNetwork)
## browseNetwork(gR)
```

saveXGMML

Save network as xgmml

Description

Save graph into xgmml format.

Usage

```
saveXGMML(network, file, ...)
```

Arguments

| | |
|---------|--|
| network | output of browseNetwork |
| file | Name of the file to save to. |
| ... | Parameter could be used by saveXML |

Index

*Topic **IO**

- exportNetwork, 9
- saveXGML, 14

*Topic **convert**

- convertID, 7

*Topic **datasets**

- ce.IDsMap, 5
- ce.interactionmap, 5
- ce.mapIDs, 6
- ce.miRNA.map, 7
- example.data, 8
- hs.IDsMap, 10
- hs.interactionmap, 11
- hs.mapIDs, 12
- hs.miRNA.map, 12

*Topic **network**

- buildNetwork, 4
- filterNetwork, 9
- networkFromGenes, 13
- polishNetwork, 13
- uniqueExprsData, 15

*Topic **plot**

- browseNetwork, 3

browseNetwork, 3, 9, 14

browseNetwork-shiny, 4

browseNetworkOutput

(browseNetwork-shiny), 4

buildNetwork, 4

ce.IDsMap, 5

ce.interactionmap, 5

ce.mapIDs, 6

ce.miRNA.map, 7

convertID, 7

example.data, 8

exportNetwork, 9

filterNetwork, 9

GeneNetworkBuilder

(GeneNetworkBuilder-package), 2

GeneNetworkBuilder-package, 2

graph.par, 14

graphNEL, 3

GraphvizLayouts, 3

hs.IDsMap, 10

hs.interactionmap, 11

hs.mapIDs, 12

hs.miRNA.map, 12

networkFromGenes, 13

polishNetwork, 3, 13

renderBrowseNetwork

(browseNetwork-shiny), 4

saveWidget, 9

saveXGML, 14

saveXML, 9

uniqueExprsData, 15