

Package ‘koinar’

December 17, 2024

Type Package

Title KoinaR - Remote machine learning inference using Koina

Version 1.1.0

Depends R (>= 4.3)

Imports httr, jsonlite, methods, utils

Suggests BiocManager, BiocStyle (>= 2.26), httpptest, knitr, lattice, msdata, OrgMassSpecR, protViz, S4Vectors, Spectra, testthat, mzR

Description A client to simplify fetching predictions from the Koina web service. Koina is a model repository enabling the remote execution of models. Predictions are generated as a response to HTTP/S requests, the standard protocol used for nearly all web traffic.

License Apache License 2.0

URL <https://github.com/wilhelm-lab/koina>

BugReports <https://github.com/wilhelm-lab/koina/issues>

Encoding UTF-8

NeedsCompilation no

RoxygenNote 7.3.2

VignetteBuilder knitr

biocViews MassSpectrometry, Proteomics, Infrastructure, Software

git_url <https://git.bioconductor.org/packages/koinar>

git_branch devel

git_last_commit 9c11c40

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2024-12-16

Author Ludwig Lautenbacher [aut, cre] (ORCID: <https://orcid.org/0000-0002-1540-5911>),
Christian Panse [aut] (ORCID: <https://orcid.org/0000-0003-1975-3064>)

Maintainer Ludwig Lautenbacher <ludwig.lautenbacher@tum.de>

Contents

Koina-class	2
predictWithKoinaModel	3
Index	5

Koina-class	<i>Koina client class</i>
-------------	---------------------------

Description

Koina client class

Value

an instance of the Koina class

Fields

`model_name` character, e.g., "Prosit_2019_intensity". See <https://koina.wilhelmlab.org/docs> for all available models.

`url` url, default is set to "koina.wilhelmlab.org".

`ssl` logical.

`disable_progress_bar` logical.

Methods

`predict(input_data, pred_as_df = TRUE, filters = list(intensities = c(1e-04, 1)))` Predict using the defined model.

Arguments:

- `input_data`: Either a dataframe or a list of arrays. 'names' must correspond to the inputs for the chosen model.

- `pred_as_df`: Logical, indicating if the results should be returned as a dataframe (TRUE) or in the original format (FALSE).

- `filters`: A list of vectors which is used to filter predictions. The key needs to equal the name of the predicted property, the first value is used as minimum the second as maximum. Ignored when 'pred_as_df' == FALSE.

Returns:

Depending on 'pred_as_df', returns either a dataframe or a list/array of predictions, applying 'min_intensity' filtering if applicable.

Author(s)

Ludwig Lautenbacher, 2024

See Also

<https://koina.wilhelmlab.org>

Examples

```
library(koinar)
prosit2019 <- koinar::Koina(
  model_name = "Prosit_2019_intensity",
  server_url = "koina.wilhelmlab.org"
)

input <- data.frame(
  peptide_sequences = c("LGGNEQVTR", "GAGSSEPVTGLDAK"),
  collision_energies = c(25, 25),
  precursor_charges = c(1, 2)
)

# Fetch the predictions by calling `predict` of the model you want to use
prediction_results <- prosit2019$predict(input)
```

predictWithKoinaModel *Predict Results Using a Koina Model*

Description

The `predictWithKoinaModel` function leverages the `predict` method of a `Koina` class instance to obtain model predictions based on the input data provided.

Usage

```
predictWithKoinaModel(koina_model, input)
```

Arguments

<code>koina_model</code>	An instance of the <code>Koina</code> class. This object encapsulates the model that will be used to make predictions.
<code>input</code>	A data frame or list of arrays containing the inputs required for the model:

Value

The function returns the prediction results from the `koina_model` object. The structure of the output depends on the specific model used and the format expected by the underlying Koina prediction API.

See Also

<https://koina.wilhelmlab.org>

Examples

```
# Load the koinar package
library(koinar)

# Create an instance of the Koina class with a specific model
prosit2019 <- koinar::Koina(
  model_name = "Prosit_2019_intensity",
  server_url = "koina.wilhelmlab.org"
)

# Prepare the input data
input <- data.frame(
  peptide_sequences = c("LGGNEQVTR", "GAGSSEPVTGLDAK"),
  collision_energies = c(25, 25),
  precursor_charges = c(1, 2)
)

# Fetch the predictions by calling the predictWithKoinaModel function
prediction_results <- predictWithKoinaModel(prosit2019, input)
```

Index

Koina (Koina-class), [2](#)
Koina-class, [2](#)
predictWithKoinaModel, [3](#)