

# Package ‘ChIPXpressData’

April 3, 2025

**Type** Package

**Title** ChIPXpress Pre-built Databases

**Version** 1.45.0

**Date** 2012-07-24

**Author** George Wu

**Maintainer** George Wu <gewu@jhsp.h.edu>

**Description** Contains pre-built mouse (GPL1261) and human (GPL570) database of gene expression profiles to be used for ChIPXpress ranking.

**License** GPL (>=2)

**Depends** bigmemory

**biocViews** Homo\_sapiens\_Data, Mus\_musculus\_Data, GEO

**git\_url** <https://git.bioconductor.org/packages/ChIPXpressData>

**git\_branch** devel

**git\_last\_commit** 14bafc0

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.21

**Date/Publication** 2025-04-03

## Contents

ChIPXpressData-package . . . . .	2
DB_GPL1261.bigmemory . . . . .	2
DB_GPL570.bigmemory . . . . .	3
GPL1261mean . . . . .	4
GPL1261var . . . . .	5
GPL570mean . . . . .	6
GPL570var . . . . .	7

<b>Index</b>	<b>8</b>
--------------	----------

ChIPXpressData-package

*ChIPXpress Gene Expression Databases*

---

### Description

Pre-built databases of gene expression profiles for ChIPXpress analysis in big.matrix format. DB\_GPL1261 contains mouse data. DB\_GPL570 contains human data.

### Details

Package: ChIPXpressData  
Type: Package  
Version: 1.00.0  
Date: 2012-07-24  
License: GPL 2.0

### Author(s)

George Wu Maintainer: George Wu <gewu@jhsphe.edu>

### References

McCall M.N., Bolstad B.M., and Irizarry R.A. (2010) Frozen robust multiarray analysis (fRMA). *Biostatistics* 11, 242-253.

Barrett T., et al. (2007) NCBI GEO: mining tens of millions of expression profiles - database and tools update. *Nucl. Acids Res.* 35, D760-D765.

---

DB\_GPL1261.bigmemory *Database of gene expression profiles from the Affymetrix Mouse 430 2.0 Array (GPL1261) in big.matrix format*

---

### Description

The data set contains 9634 mouse profiles downloaded from NCBI GEO, processed using fRMA, and normalized. It is in big.matrix format.

### Format

The format is: Formal class 'big.matrix' [package "bigmemory"] with 1 slots ..@ address:<externalptr>

## Details

The database is formatted as a `big.matrix` for more efficient loading into memory. It is stored in `DB_GPL1261.bigmemory` and the corresponding description file is `DB_GPL1261.bigmemory.desc`. To utilize the `big.matrix` format, it requires the package `bigmemory` to be loaded. See the `bigmemory` package for more information.

The database contains 20757 rows and 9643 columns. Each row represents the expression vector for each gene and each column represents the gene expression measurements for a sample from NCBI GEO obtained using the GPL1261 platform. Each gene will match uniquely to a single probe ID; only the probe with the highest variance in the compendium apriori to normalization are retained as the representative measurement for each gene.

## Source

[www.ncbi.nlm.nih.gov/geo/](http://www.ncbi.nlm.nih.gov/geo/)

## References

McCall M.N., Bolstad B.M., and Irizarry R.A. (2010) Frozen robust multiarray analysis (fRMA). *Biostatistics* 11, 242-253.

Barrett T., et al. (2007) NCBI GEO: mining tens of millions of expression profiles - database and tools update. *Nucl. Acids Res.* 35, D760-D765.

## Examples

```
## Load the GPL1261 database
library(bigmemory)
path <- system.file("extdata", package="ChIPXpressData")
DB_GPL1261 <- attach.big.matrix("DB_GPL1261.bigmemory.desc", path=path)
## DB_GPL1261 is then ready for input into the ChIPXpress function.

## To see info about the database matrix
describe(DB_GPL1261)
```

---

DB_GPL570.bigmemory	<i>Database of gene expression profiles from the Affymetrix Human U133 Plus 2.0 array (GPL570) in big.matrix format</i>
---------------------	-------------------------------------------------------------------------------------------------------------------------

---

## Description

The data set contains 18257 human profiles downloaded from NCBI GEO, processed using fRMA, and normalized. It is in `big.matrix` format.

## Format

The format is: Formal class 'big.matrix' [package "bigmemory"] with 1 slots ..@ address:<externalptr>

## Details

The database is formatted as a `big.matrix` for more efficient loading into memory. It is stored in `DB_GPL570.bigmemory` and the corresponding description file is `DB_GPL570.bigmemory.desc`. To utilize the `big.matrix` format, it requires the package `bigmemory` to be loaded. See the `bigmemory` package for more information.

The database contains 19798 rows and 18257 columns. Each row represents the expression vector for each gene and each column represents the gene expression measurements for a sample from NCBI GEO obtained using the GPL570 platform. Each gene will match uniquely to a single probe ID; only the probe with the highest variance in the compendium apriori to normalization are retained as the representative measurement for each gene.

## Source

[www.ncbi.nlm.nih.gov/geo/](http://www.ncbi.nlm.nih.gov/geo/)

## References

McCall M.N., Bolstad B.M., and Irizarry R.A. (2010) Frozen robust multiarray analysis (fRMA). *Biostatistics* 11, 242-253.

Barrett T., et al. (2007) NCBI GEO: mining tens of millions of expression profiles - database and tools update. *Nucl. Acids Res.* 35, D760-D765.

## Examples

```
## Load the GPL570 database
library(bigmemory)
path <- system.file("extdata", package="ChIPXpressData")
DB_GPL570 <- attach.big.matrix("DB_GPL570.bigmemory.desc", path=path)
## DB_GPL570 is then ready for input into the ChIPXpress function.

## To see info about the database matrix
describe(DB_GPL570)
```

---

GPL1261mean

*Mean of each probeset in the GPL1261 database*

---

## Description

Mean across all samples for each probe set in the GPL1261 compendium prior to standardization

## Usage

```
data(GPL1261mean)
```

**Format**

The format is: Named num [1:20757] 10.2 10.88 7.77 8.87 10.92 ... - attr(\*, "names")= chr [1:20757] "11972" "57437" "100678" "13481" ...

**Details**

Used to check for low expression probesets

**Source**

[www.ncbi.nlm.nih.gov/geo/](http://www.ncbi.nlm.nih.gov/geo/)

**References**

Barrett T., et al. (2007) NCBI GEO: mining tens of millions of expression profiles - database and tools update. *Nucl. Acids Res.* **35**, D760-D765.

**Examples**

```
data(GPL1261mean)
```

---

GPL1261var

*Variance of each probeset in the GPL1261 database*

---

**Description**

Variance across all samples for each probe set in the GPL1261 compendium prior to standardization

**Usage**

```
data(GPL1261var)
```

**Format**

The format is: Named num [1:20757] 0.773 0.509 1.817 0.326 0.568 ... - attr(\*, "names")= chr [1:20757] "11972" "57437" "100678" "13481" ...

**Details**

Used to check for low variance probesets

**Source**

[www.ncbi.nlm.nih.gov/geo/](http://www.ncbi.nlm.nih.gov/geo/)

**References**

Barrett T., et al. (2007) NCBI GEO: mining tens of millions of expression profiles - database and tools update. *Nucl. Acids Res.* **35**, D760-D765.

**Examples**

```
data(GPL1261var)
```

---

GPL570mean

*Mean of each probeset in the GPL570 database*

---

**Description**

Mean across all samples for each probe set in the GPL570 compendium prior to standardization

**Usage**

```
data(GPL570mean)
```

**Format**

The format is: Named num [1:19944] -9.25e-16 -6.07e-16 5.80e-16 -3.01e-16 4.10e-16 ... - attr(\*, "names")= chr [1:19944] "112597" "203102" "91937" "266675" ...

**Details**

Used to check for low expression probesets

**Source**

[www.ncbi.nlm.nih.gov/geo/](http://www.ncbi.nlm.nih.gov/geo/)

**References**

Barrett T., et al. (2007) NCBI GEO: mining tens of millions of expression profiles - database and tools update. *Nucl. Acids Res.* **35**, D760-D765.

**Examples**

```
data(GPL570mean)
```

---

`GPL570var`*Variance of each probeset in the GPL570 database*

---

**Description**

Variance across all samples for each probeset in the GPL570 compendium prior to standardization

**Usage**

```
data(GPL570var)
```

**Format**

The format is: Named num [1:19944] 0.177 0.0892 0.5552 0.4545 1.0399 ... - attr(\*, "names")= chr [1:19944] "112597" "203102" "91937" "266675" ...

**Details**

Used to check for low variance probesets

**Source**

[www.ncbi.nlm.nih.gov/geo/](http://www.ncbi.nlm.nih.gov/geo/)

**References**

Barrett T., et al. (2007) NCBI GEO: mining tens of millions of expression profiles - database and tools update. *Nucl. Acids Res.* **35**, D760-D765.

**Examples**

```
data(GPL570var)
```

# Index

- \* **datasets,GPL1261,database**
    - DB\_GPL1261.bigmemory, [2](#)
  - \* **datasets,GPL570,database**
    - DB\_GPL570.bigmemory, [3](#)
  - \* **datasets**
    - GPL1261mean, [4](#)
    - GPL1261var, [5](#)
    - GPL570mean, [6](#)
    - GPL570var, [7](#)
  - \* **package, database, ChIPXpress**
    - ChIPXpressData-package, [2](#)
- ChIPXpressData  
(ChIPXpressData-package), [2](#)
- ChIPXpressData-package, [2](#)
- DB\_GPL1261.bigmemory, [2](#)
- DB\_GPL570.bigmemory, [3](#)
- GPL1261mean, [4](#)
- GPL1261var, [5](#)
- GPL570mean, [6](#)
- GPL570var, [7](#)