

Package ‘GOSemSim’

January 2, 2025

Type Package

Title GO-terms Semantic Similarity Measures

Version 2.32.0

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Description The semantic comparisons of Gene Ontology (GO) annotations provide quantitative ways to compute similarities between genes and gene groups, and have become important basis for many bioinformatics analysis approaches. GOSemSim is an R package for semantic similarity computation among GO terms, sets of GO terms, gene products and gene clusters. GOSemSim implemented five methods proposed by Resnik, Schlicker, Jiang, Lin and Wang respectively.

Depends R (>= 3.5.0)

LinkingTo Rcpp

Imports AnnotationDbi, DBI, digest, GO.db, methods, rlang, R.utils, stats, utils, yulab.utils (>= 0.1.6)

Suggests AnnotationHub, BiocManager, clusterProfiler, DOSE, knitr, org.Hs.eg.db, prettydoc, rappdirs, readr, rmarkdown, testthat, tidy, tidyselect, ROCR

VignetteBuilder knitr

ByteCompile true

License Artistic-2.0

Encoding UTF-8

URL <https://yulab-smu.top/biomedical-knowledge-mining-book/>

BugReports <https://github.com/YuLab-SMU/GOSemSim/issues>

biocViews Annotation, GO, Clustering, Pathways, Network, Software

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/GOSemSim>

git_branch RELEASE_3_20

git_last_commit 1b53196

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-01-02

Author Guangchuang Yu [aut, cre],
 Alexey Stukalov [ctb],
 Pingfan Guo [ctb],
 Chuanle Xiao [ctb],
 Lluís Revilla Sancho [ctb]

Contents

GOSemSim-package	2
buildGOMap	3
clusterSim	3
combineScores	4
geneSim	5
godata	6
GOSemSimDATA-class	6
goSim	7
go_term_table	8
infoContentMethod	8
load_OrgDb	9
mclusterSim	9
mgeneSim	10
mgoSim	11
read.blast2go	12
read.gaf	12
tcss_cutoff	13
termSim	14
wangMethod_internal	15
Index	16

GOSemSim-package	<i>GOSemSim: GO-terms Semantic Similarity Measures</i>
------------------	--

Description

The semantic comparisons of Gene Ontology (GO) annotations provide quantitative ways to compute similarities between genes and gene groups, and have become important basis for many bioinformatics analysis approaches. GOSemSim is an R package for semantic similarity computation among GO terms, sets of GO terms, gene products and gene clusters. GOSemSim implemented five methods proposed by Resnik, Schlicker, Jiang, Lin and Wang respectively.

Author(s)

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com>

Other contributors:

- Alexey Stukalov <astukalov@gmail.com> [contributor]
- Pingfan Guo <1178431277@qq.com> [contributor]
- Chuanle Xiao <xiaochuanle@126.com> [contributor]
- Lluís Revilla Sancho <lluis.revilla@gmail.com> [contributor]

See Also

Useful links:

- <https://yulab-smu.top/biomedical-knowledge-mining-book/>
- Report bugs at <https://github.com/YuLab-SMU/GOSemSim/issues>

buildGOMap

buildGOMap

Description

Adding indirect GO annotation

Usage

```
buildGOMap(TERM2GENE)
```

Arguments

TERM2GENE data.frame with two or three columns of GO TERM, GENE and ONTOLOGY (optional)

Details

provided by a data.frame of GO TERM (column 1), GENE (column 2) and ONTOLOGY (optional) that describes GO direct annotation, this function will add indirect GO annotation of genes.

Value

data.frame, GO annotation with direct and indirect annotation

Author(s)

Yu Guangchuang

clusterSim

Semantic Similarity Between Two Gene Clusters

Description

Given two gene clusters, this function calculates semantic similarity between them.

Usage

```
clusterSim(  
  cluster1,  
  cluster2,  
  semData,  
  measure = "Wang",  
  drop = "IEA",  
  combine = "BMA"  
)
```

Arguments

cluster1	A set of gene IDs.
cluster2	Another set of gene IDs.
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.
drop	A set of evidence codes based on which certain annotations are dropped. Use NULL to keep all GO annotations.
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.

Value

similarity

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [mgoSim](#) [geneSim](#) [mgeneSim](#) [mclusterSim](#)

Examples

```
d <- godata('org.Hs.eg.db', ont="MF", computeIC=FALSE)
cluster1 <- c("835", "5261", "241", "994")
cluster2 <- c("307", "308", "317", "321", "506", "540", "378", "388", "396")
clusterSim(cluster1, cluster2, semData=d, measure="Wang")
```

combineScores	<i>combining similarity matrix to similarity score</i>
---------------	--

Description

Functions for combining similarity matrix to similarity score

Usage

```
combineScores(SimScores, combine)
```

Arguments

SimScores	similarity matrix
combine	combine method

Value

similarity value

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

geneSim

Semantic Similarity Between two Genes

Description

Given two genes, this function will calculate the semantic similarity between them, and return their semantic similarity and the corresponding GO terms

Usage

```
geneSim(gene1, gene2, semData, measure = "Wang", drop = "IEA", combine = "BMA")
```

Arguments

gene1	Entrez gene id.
gene2	Another entrez gene id.
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang" "TCSS" and "Wang" methods.
drop	A set of evidence codes based on which certain annotations are dropped. Use NULL to keep all GO annotations.
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.

Value

list of similarity value and corresponding GO.

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [mgoSim](#) [mgeneSim](#) [clusterSim](#) [mclusterSim](#)

Examples

```
d <- godata('org.Hs.eg.db', ont="MF", computeIC=FALSE)
geneSim("241", "251", semData=d, measure="Wang")
```

 godata

godata

Description

prepare GO DATA for measuring semantic similarity

Usage

```
godata(
  OrgDb = NULL,
  annoDb = NULL,
  keytype = "ENTREZID",
  ont,
  computeIC = TRUE,
  processTCSS = FALSE,
  cutoff = NULL
)
```

Arguments

OrgDb	OrgDb object (will be removed in future, please use annoDb instead)
annoDb	GO annotation database, can be OrgDb or a data.frame contains three columns of 'GENE', 'GO' and 'ONTOLOGY'.
keytype	keytype
ont	one of 'BP', 'MF', 'CC'
computeIC	logical, whether computer IC
processTCSS	logical, whether to process TCSS
cutoff	cutoff of TCSS

Value

GOSemSimDATA object

Author(s)

Guangchuang Yu

 GOSemSimDATA-class

Class "GOSemSimDATA" This class stores IC and gene to go mapping for semantic similarity measurement

Description

Class "GOSemSimDATA" This class stores IC and gene to go mapping for semantic similarity measurement

Slots

keys gene ID
ont ontology
IC IC data
geneAnno gene to GO mapping
tcssdata tcssdata
metadata metadata

goSim

Semantic Similarity Between Two GO Terms

Description

Given two GO IDs, this function calculates their semantic similarity.

Usage

```
goSim(GO1D1, GO1D2, semData, measure = "Wang")
```

Arguments

GO1D1	GO ID 1.
GO1D2	GO ID 2.
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.

Value

similarity

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[mgoSim](#) [geneSim](#) [mgeneSim](#) [clusterSim](#) [mclusterSim](#)

Examples

```
d <- godata('org.Hs.eg.db', ont="MF", computeIC=FALSE)
goSim("GO:0004022", "GO:0005515", semData=d, measure="Wang")
```

 go_term_table

Information content of GO terms

Description

These datasets are the information contents of GOterms.

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

 infoContentMethod

information content based methods

Description

Information Content Based Methods for semantic similarity measuring

Usage

```
infoContentMethod(ID1, ID2, method, godata)
```

Arguments

ID1	Ontology Term
ID2	Ontology Term
method	one of "Resnik", "Jiang", "Lin" and "Rel", "TCSS".
godata	GOSemSimDATA object

Details

implemented for methods proposed by Resnik, Jiang, Lin and Schlicker.

Value

semantic similarity score

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

load_OrgDb	<i>load_OrgDb</i>
------------	-------------------

Description

load OrgDb

Usage

```
load_OrgDb(OrgDb)
```

Arguments

OrgDb OrgDb object or OrgDb name

Value

OrgDb object

Author(s)

Guangchuang Yu <https://yulab-smu.top>

mclusterSim	<i>Pairwise Semantic Similarities for a List of Gene Clusters</i>
-------------	---

Description

Given a list of gene clusters, this function calculates pairwise semantic similarities.

Usage

```
mclusterSim(clusters, semData, measure = "Wang", drop = "IEA", combine = "BMA")
```

Arguments

clusters	A list of gene clusters.
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.
drop	A set of evidence codes based on which certain annotations are dropped. Use NULL to keep all GO annotations.
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.

Value

similarity matrix

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [mgoSim](#) [geneSim](#) [mgeneSim](#) [clusterSim](#)

Examples

```
d <- godata('org.Hs.eg.db', ont="MF", computeIC=FALSE)
cluster1 <- c("835", "5261", "241")
cluster2 <- c("578", "582")
cluster3 <- c("307", "308", "317")
clusters <- list(a=cluster1, b=cluster2, c=cluster3)
mclusterSim(clusters, semData=d, measure="Wang")
```

mgeneSim

Pairwise Semantic Similarity for a List of Genes

Description

Given a list of genes, this function calculates pairwise semantic similarities.

Usage

```
mgeneSim(
  genes,
  semData,
  measure = "Wang",
  drop = "IEA",
  combine = "BMA",
  verbose = TRUE
)
```

Arguments

genes	A list of entrez gene IDs.
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.
drop	A set of evidence codes based on which certain annotations are dropped. Use NULL to keep all GO annotations.
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.
verbose	show progress bar or not.

Value

similarity matrix

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [mgoSim](#) [geneSim](#) [clusterSim](#) [mclusterSim](#)

Examples

```
d <- godata('org.Hs.eg.db', ont="MF", computeIC=FALSE)
mgeneSim(c("835", "5261", "241"), semData=d, measure="Wang")
```

mgoSim

Semantic Similarity Between two GO terms lists

Description

Given two GO term sets, this function will calculate the semantic similarity between them, and return their semantic similarity

Usage

```
mgoSim(GO1, GO2, semData, measure = "Wang", combine = "BMA")
```

Arguments

GO1	A set of go terms.
GO2	Another set of go terms.
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.

Value

similarity

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [geneSim](#) [mgeneSim](#) [clusterSim](#) [mclusterSim](#)

Examples

```
d <- godata('org.Hs.eg.db', ont="MF", computeIC=FALSE)
go1 <- c("GO:0004022", "GO:0004024", "GO:0004023")
go2 <- c("GO:0009055", "GO:0020037")
mgoSim("GO:0003824", go2, semData=d, measure="Wang")
mgoSim(go1, go2, semData=d, measure="Wang")
```

read.blast2go

read.blast2go

Description

given a BLAST2GO file, this function extracts the information from it and make it use for TERM2GENE.

Usage

```
read.blast2go(file, add_indirect_GO = FALSE)
```

Arguments

file	BLAST2GO file
add_indirect_GO	whether add indirect GO annotation

Value

a data frame with three columns: GENE, GO and ONTOLOGY

read.gaf

read.gaf

Description

parse GAF files

Usage

```
read.gaf(file, asis = FALSE, add_indirect_GO = FALSE)
```

```
parse_gff(file, asis = FALSE, add_indirect_GO = FALSE)
```

Arguments

file	GAF file
asis	logical, whether output the original contains of the file and only works if 'add_indirect_GO = FALSE'
add_indirect_GO	whether to add indirect GO annotation

Details

given a GAF file, this function extracts the information from it

Value

A data.frame. Original table if 'asis' works, otherwise contains 3 columns of 'GENE', 'GO' and 'ONTOLOGY'

tcss_cutoff	<i>determine the topological cutoff for TCSS method</i>
-------------	---

Description

determine the topological cutoff for TCSS method

Usage

```
tcss_cutoff(
  OrgDb = NULL,
  keytype = "ENTREZID",
  ont,
  combine_method = "max",
  ppidata
)
```

Arguments

OrgDb	OrgDb object
keytype	keytype
ont	ontology: "BP", "MF", "CC"
combine_method	"max", "BMA", "avg", "rcmax", "rcmax.avg"
ppidata	A data.frame contains positive set and negative set. Positive set is PPI pairs that already verified. ppidata has three columns, column 1 and 2 are character, column 3 must be logical value:TRUE/FALSE.

Value

numeric, topological cutoff for given parameters

Examples

```
## Not run:
library(org.Hs.eg.db)
library(STRINGdb)

string_db <- STRINGdb$new(version = "11.0", species = 9606,
score_threshold = 700)
string_proteins <- string_db$get_proteins()

#get relationship
ppi <- string_db$get_interactions(string_proteins$protein_external_id)

ppi$from <- vapply(ppi$from, function(e)
  strsplit(e, "9606.")[[1]][2], character(1))
ppi$to <- vapply(ppi$to, function(e)
  strsplit(e, "9606.")[[1]][2], character(1))
len <- nrow(ppi)

#select length
s_len <- 100
pos_1 <- sample(len, s_len, replace = T)
#negative set
pos_2 <- sample(len, s_len, replace = T)
pos_3 <- sample(len, s_len, replace = T)
#union as ppidata
ppidata <- data.frame(pro1 = c(ppi$from[pos_1], ppi$from[pos_2]),
  pro2 = c(ppi$to[pos_1], ppi$to[pos_3]),
  label = c(rep(TRUE, s_len), rep(FALSE, s_len)),
  stringsAsFactors = FALSE)

cutoff <- tcss_cutoff(OrgDb = org.Hs.eg.db, keytype = "ENSEMBLPROT",
  ont = "BP", combine_method = "max", ppidata)

## End(Not run)
```

termSim

termSim

Description

measuring similarities between two term vectors.

Usage

```
termSim(
  t1,
  t2,
  semData,
  method = c("Wang", "Resnik", "Rel", "Jiang", "Lin", "TCSS")
)
```

Arguments

t1	term vector
t2	term vector
semData	GOSemSimDATA object
method	one of "Wang", "Resnik", "Rel", "Jiang", and "Lin", "TCSS".

Details

provide two term vectors, this function will calculate their similarities.

Value

score matrix

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

wangMethod_internal *wangMethod*

Description

Method Wang for semantic similarity measuring

Usage

```
wangMethod_internal(ID1, ID2, ont = "BP")
```

Arguments

ID1	Ontology Term
ID2	Ontology Term
ont	Ontology

Value

semantic similarity score

Author(s)

Guangchuang Yu <https://yulab-smu.top>

Index

- * **classes**
 - GOSemSimDATA-class, 6
- * **datasets**
 - go_term_table, 8
- * **internal**
 - GOSemSim-package, 2
- * **manip**
 - clusterSim, 3
 - geneSim, 5
 - goSim, 7
 - mclusterSim, 9
 - mgeneSim, 10
 - mgoSim, 11

buildGOMap, 3

clusterSim, 3, 5, 7, 10–12

combineScores, 4

geneSim, 4, 5, 7, 10–12

GO (go_term_table), 8

go_term_table, 8

godata, 6

GOSemSim (GOSemSim-package), 2

GOSemSim-package, 2

GOSemSimDATA-class, 6

goSim, 4, 5, 7, 10–12

gotbl (go_term_table), 8

infoContentMethod, 8

load_OrgDb, 9

mclusterSim, 4, 5, 7, 9, 11, 12

mgeneSim, 4, 5, 7, 10, 10, 12

mgoSim, 4, 5, 7, 10, 11, 11

parse_gff (read.gaf), 12

read.blast2go, 12

read.gaf, 12

show, GOSemSimDATA-method
(GOSemSimDATA-class), 6

tcss_cutoff, 13

termSim, 14

wangMethod_internal, 15