

# Package ‘scDotPlot’

March 18, 2025

**Title** Cluster a Single-cell RNA-seq Dot Plot

**Version** 1.0.0

**Description** Dot plots of single-cell RNA-seq data allow for an examination of the relationships between cell groupings (e.g. clusters) and marker gene expression. The scDotPlot package offers a unified approach to perform a hierarchical clustering analysis and add annotations to the columns and/or rows of a scRNA-seq dot plot. It works with SingleCellExperiment and Seurat objects as well as data frames.

**License** Artistic-2.0

**URL** <https://github.com/ben-laufer/scDotPlot>

**BugReports** <https://github.com/ben-laufer/scDotPlot/issues>

**biocViews** Software, Visualization, DifferentialExpression, GeneExpression, Transcription, RNASeq, SingleCell, Sequencing, Clustering

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**Depends** R (>= 4.4.0)

**Imports** aplot, BiocGenerics, cli, dplyr, ggplot2, ggsci, ggtree, grDevices, magrittr, purrr, rlang, scales, scater, Seurat, SingleCellExperiment, stats, stringr, tibble, tidy

**Suggests** AnnotationDbi, BiocStyle, knitr, rmarkdown, scran, scRNAseq, scuttle, SeuratObject, testthat, vdiff

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**LazyData** false

**git\_url** <https://git.bioconductor.org/packages/scDotPlot>

**git\_branch** RELEASE\_3\_20

**git\_last\_commit** a4792ee

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.20

**Date/Publication** 2025-03-17

**Author** Benjamin I Laufer [aut, cre],  
Brad A Friedman [aut]

**Maintainer** Benjamin I Laufer <blaufer@gmail.com>

## Contents

scDotPlot-package . . . . .	2
.annotateDotPlot . . . . .	2
.baseDotPlot . . . . .	4
.createAnno . . . . .	5
scDotPlot . . . . .	5

<b>Index</b>	<b>10</b>
--------------	-----------

---

scDotPlot-package	<i>scDotPlot: Cluster a Single-cell RNA-seq Dot Plot</i>
-------------------	--

---

### Description

Dot plots of single-cell RNA-seq data allow for an examination of the relationships between cell groupings (e.g. clusters) and marker gene expression. The scDotPlot package offers a unified approach to perform a hierarchical clustering analysis and add annotations to the columns and/or rows of a scRNA-seq dot plot. It works with SingleCellExperiment and Seurat objects as well as data frames.

### Author(s)

**Maintainer:** Benjamin I Laufer <blaufer@gmail.com>

Authors:

- Brad A Friedman

### See Also

Useful links:

- <https://github.com/ben-laufer/scDotPlot>
- Report bugs at <https://github.com/ben-laufer/scDotPlot/issues>

---

.annotateDotPlot	<i>Cluster Dot Plot</i>
------------------	-------------------------

---

### Description

Cluster Dot Plot

**Usage**

```
.annotateDotPlot(  
  dotPlot,  
  clusterRows = TRUE,  
  clusterColumns = TRUE,  
  groupAnno = FALSE,  
  featureAnno = FALSE,  
  treeWidth = 0.1,  
  treeHeight = 0.1,  
  annoWidth = 0.05,  
  annoHeight = 0.02,  
  annoColors = NULL,  
  groupLegends = TRUE,  
  featureLegends = TRUE,  
  fontSize = 11,  
  fontFamily = "",  
  flipPlot = FALSE  
)
```

**Arguments**

<code>clusterRows</code>	Logical specifying whether to perform hierarchical clustering analysis on the rows
<code>clusterColumns</code>	Logical specifying whether to perform hierarchical clustering analysis on the columns
<code>groupAnno</code>	Cell annotations that are stored as names of columns in <code>colData</code> of <code>sce</code> with annotations
<code>featureAnno</code>	Feature annotations that are stored as names of rows in <code>rowData</code> of <code>sce</code> with annotations
<code>treeWidth</code>	Numeric specifying width of the row tree relative to the <code>dotPlot</code>
<code>treeHeight</code>	Numeric specifying height of the column tree relative to the <code>dotPlot</code>
<code>annoWidth</code>	Numeric specifying the width of the row annotation relative to the <code>dotPlot</code>
<code>annoHeight</code>	Numeric specifying height of the column annotation relative to the <code>dotPlot</code>
<code>annoColors</code>	A list with a name for each annotation that contains a named vector of colors, where the name is the pairing of values to colors
<code>groupLegends</code>	Logical indicating whether to show legends for group annotations
<code>featureLegends</code>	Logical indicating whether to show legends for feature annotations
<code>fontSize</code>	Numeric specifying the base font size in pts
<code>fontFamily</code>	Character specifying the base font family
<code>flipPlot</code>	Logical indicating whether to flip the x and y coordinates

**Value**

A `aplot`

---

 .baseDotPlot

*Dot Plot Base*


---

## Description

Dot Plot Base

## Usage

```
.baseDotPlot(
  plotData,
  group = NULL,
  scale = NULL,
  AverageThreshold = NULL,
  NumDetectedThreshold = NULL,
  dotColors = NULL,
  fontSize = 11,
  fontFamily = "",
  flipPlot = FALSE
)
```

## Arguments

group	Column name from colData/metadata of the object to group cells by
scale	Logical indicating whether the data should be scaled and centered
AverageThreshold	Numeric specifying threshold for average expression, where values below AverageThreshold and NumDetectedThreshold are transparent
NumDetectedThreshold	Numeric specifying threshold for fraction of cells, where values below AverageThreshold and NumDetectedThreshold are transparent
dotColors	A character vector specifying the colors to be used in the gradient for the dots. If scale is set to TRUE, the first 3 colors will be used for the negative, zero, and positive values, respectively.
fontSize	Numeric specifying the base font size in pts
fontFamily	Character specifying the base font family
flipPlot	Logical indicating whether to flip the x and y coordinates

## Value

A ggplot2

---

.createAnno                      *Create column annotations*

---

**Description**

Create column annotations

**Usage**

```
.createAnno(  
  annoLabel,  
  annoType = c("column", "row"),  
  dotPlot = dotPlot,  
  annoColors = NULL,  
  groupLegends = TRUE,  
  featureLegends = TRUE,  
  fontSize = 11,  
  fontFamily = "",  
  flipPlot = FALSE  
)
```

**Arguments**

- annoColors            A list with a name for each annotation that contains a named vector of colors, where the name is the pairing of values to colors
- groupLegends        Logical indicating whether to show legends for group annotations
- featureLegends     Logical indicating whether to show legends for feature annotations
- fontSize            Numeric specifying the base font size in pts
- fontFamily          Character specifying the base font family
- flipPlot            Logical indicating whether to flip the x and y coordinates

**Value**

A ggplot2

---

scDotPlot                      *scDotPlot*

---

**Description**

Create dot plot of gene expression profiles that can be annotated with hierarchical clustering from [gtree](#) using [aplot](#)

**Usage**

```
## S3 method for class 'SingleCellExperiment'
scDotPlot(
  object,
  features = features,
  group = NULL,
  block = NULL,
  swap_rownames = NULL,
  scale = FALSE,
  cluster = TRUE,
  clusterRows = cluster,
  clusterColumns = cluster,
  AverageThreshold = ifelse(scale == FALSE, 0, -Inf),
  NumDetectedThreshold = 0.01,
  groupAnno = FALSE,
  featureAnno = FALSE,
  treeWidth = 0.1,
  treeHeight = 0.1,
  annoWidth = 0.05,
  annoHeight = 0.02,
  annoColors = NULL,
  dotColors = NULL,
  groupLegends = TRUE,
  featureLegends = TRUE,
  fontSize = 11,
  fontFamily = "",
  flipPlot = FALSE,
  ...
)

## S3 method for class 'Seurat'
scDotPlot(
  object,
  features = features,
  group = NULL,
  block = NULL,
  swap_rownames = NULL,
  scale = FALSE,
  cluster = TRUE,
  clusterRows = cluster,
  clusterColumns = cluster,
  AverageThreshold = ifelse(scale == FALSE, 0, -Inf),
  NumDetectedThreshold = 0.01,
  groupAnno = FALSE,
  featureAnno = FALSE,
  treeWidth = 0.1,
  treeHeight = 0.1,
  annoWidth = 0.05,
  annoHeight = 0.02,
  annoColors = NULL,
  dotColors = NULL,
  groupLegends = TRUE,
```

```

    featureLegends = TRUE,
    fontSize = 11,
    fontFamily = "",
    flipPlot = FALSE,
    ...
)

## Default S3 method:
scDotPlot(
  object,
  features = NULL,
  group = NULL,
  block = NULL,
  swap_rownames = NULL,
  scale = FALSE,
  cluster = TRUE,
  clusterRows = cluster,
  clusterColumns = cluster,
  AverageThreshold = ifelse(scale == FALSE, 0, -Inf),
  NumDetectedThreshold = 0.01,
  groupAnno = FALSE,
  featureAnno = FALSE,
  treeWidth = 0.1,
  treeHeight = 0.1,
  annoWidth = 0.05,
  annoHeight = 0.02,
  annoColors = NULL,
  dotColors = NULL,
  groupLegends = TRUE,
  featureLegends = TRUE,
  fontSize = 11,
  fontFamily = "",
  flipPlot = FALSE,
  ...
)

scDotPlot(object, ...)

```

### Arguments

object	An object with normalized data <ul style="list-style-type: none"> <li>• <a href="#">SingleCellExperiment</a></li> <li>• <a href="#">Seurat</a></li> <li>• A data.frame with the following columns: "NumDetected", "Feature", "Group", "Average"</li> </ul>
features	Character vector with genes of interest
group	Column name from colData/metadata of the object to group cells by
block	Column name from colData of a SingleCellExperiment object to use as a blocking factor (e.g. batch or sample)
swap_rownames	Column name from rowData of a SingleCellExperiment object to match to features

scale	Logical indicating whether the data should be scaled and centered
cluster	Logical specifying whether to perform hierarchical clustering analysis on both the rows and columns
clusterRows	Logical specifying whether to perform hierarchical clustering analysis on the rows
clusterColumns	Logical specifying whether to perform hierarchical clustering analysis on the columns
AverageThreshold	Numeric specifying threshold for average expression, where values below AverageThreshold and NumDetectedThreshold are transparent
NumDetectedThreshold	Numeric specifying threshold for fraction of cells, where values below AverageThreshold and NumDetectedThreshold are transparent
groupAnno	Cell annotations that are stored as names of columns in colData of sce with annotations
featureAnno	Feature annotations that are stored as names of rows in rowData of sce with annotations
treeWidth	Numeric specifying width of the row tree relative to the dotPlot
treeHeight	Numeric specifying height of the column tree relative to the dotPlot
annoWidth	Numeric specifying the width of the row annotation relative to the dotPlot
annoHeight	Numeric specifying height of the column annotation relative to the dotPlot
annoColors	A list with a name for each annotation that contains a named vector of colors, where the name is the pairing of values to colors
dotColors	A character vector specifying the colors to be used in the gradient for the dots. If scale is set to TRUE, the first 3 colors will be used for the negative, zero, and positive values, respectively.
groupLegends	Logical indicating whether to show legends for group annotations
featureLegends	Logical indicating whether to show legends for feature annotations
fontSize	Numeric specifying the base font size in pts
fontFamily	Character specifying the base font family
flipPlot	Logical indicating whether to flip the x and y coordinates
...	Additional unused arguments

## Details

The data for the dot plot is generated from different sources depending on the object:

- SingleCellExperiment: [plotDots](#)
- Seurat: [DotPlot](#)

## Value

- When cluster = TRUE, a aplot object
- When cluster = FALSE, a ggplot2 object

## References

<https://yulab-smu.top/pkgdocs/aplot.html#a-single-cell-example>

**Examples**

```
data("pbmc_small", package = "SeuratObject")
pbmc_small |>
  scDotPlot(features = Seurat::VariableFeatures(pbmc_small),
            group = "RNA_snn_res.1")
```

# Index

## \* internal

- .annotateDotPlot, 2
- .baseDotPlot, 4
- .createAnno, 5
- scDotPlot-package, 2
- .annotateDotPlot, 2
- .baseDotPlot, 4
- .createAnno, 5

aplot, 5

DotPlot, 8

ggtree, 5

plotDots, 8

scDotPlot, 5

scDotPlot-package, 2

Seurat, 7

SingleCellExperiment, 7