

Package ‘scRNAseqApp’

December 31, 2024

Title A single-cell RNAseq Shiny app-package

Version 1.6.0

Description The scRNAseqApp is a Shiny app package designed for interactive visualization of single-cell data. It is an enhanced version derived from the ShinyCell, repackaged to accommodate multiple datasets. The app enables users to visualize data containing various types of information simultaneously, facilitating comprehensive analysis. Additionally, it includes a user management system to regulate database accessibility for different users.

License GPL-3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

VignetteBuilder knitr

biocViews Visualization, SingleCell, RNASeq

Depends R (>= 4.3.0)

Imports bibtext, bslib, circlize, ComplexHeatmap, colourpicker, data.table, DBI, DT, GenomicRanges, GenomeInfoDb, gg dendro, ggforce, ggplot2, ggrepel, ggridges, grDevices, grid, gridExtra, htmltools, IRanges, jsonlite, magrittr, methods, patchwork, plotly, RColorBrewer, RefManageR, rhdf5, Rsamtools, RSQLite, rtracklayer, S4Vectors, scales, sscript, Seurat, SeuratObject, shiny, shinyhelper, shinymanager, slingshot, SingleCellExperiment, sortable, stats, tools, xfun, xml2, utils

Suggests rmarkdown, knitr, testthat, BiocStyle

Enhances celldex, future, SingleR, SummarizedExperiment, tricycle

URL <https://github.com/jianhong/scRNAseqApp>

BugReports <https://github.com/jianhong/scRNAseqApp/issues>

git_url <https://git.bioconductor.org/packages/scRNAseqApp>

git_branch RELEASE_3_20

git_last_commit f77325f

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-12-30

Author Jianhong Ou [aut, cre] (<<https://orcid.org/0000-0002-8652-2488>>)

Maintainer Jianhong Ou <jianhong.ou@duke.edu>

Contents

APPconf-class	2
APPconf-methods	3
createAppConfig	4
createDataSet	5
createSeuFromCellRanger	7
createSeuFromMatrix	7
scInit	8
scRNAseqApp	9

Index	11
--------------	-----------

APPconf-class	<i>Class "APPconf"</i>
---------------	------------------------

Description

An object of class "APPconf" represents the metadata for a dataset.

Usage

```
APPconf(...)
```

Arguments

... Each argument in ... becomes an slot in the new "APPconf"-class.

Value

A APPconf object.

Slots

title character(1). Title of the data

id character(1). Folder name of the data

species character(1). species

ref Reference information in a list with element bib, doi, pmid and entry. Entry must be an object of [bibentry](#)

type character(1). Type of the data, scRNAseq or scATACseq.

markers list. A list of data.frame represents cell markers.

keywords character. A vector of characters represents the keywords of the study.

groupCol character. The key group column name to separate the cells.

Examples

```
appconf <- readRDS(system.file("extdata", "data",
  "pbmc_small", "appconf.rds", package="scRNAseqApp"))
appconf
```

APPconf-methods

The methods for [APPconf-class](#)

Description

The assessment and replacement methods for [APPconf-class](#)

Usage

```
## S4 method for signature 'APPconf'
show(object)

## S4 method for signature 'APPconf'
x$name

## S4 replacement method for signature 'APPconf'
x$name <- value

## S4 method for signature 'APPconf,ANY,ANY'
x[[i, j, ..., exact = TRUE]]

## S4 replacement method for signature 'APPconf,ANY,ANY,ANY'
x[[i, j, ...]] <- value

## S4 method for signature 'APPconf,ANY,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'APPconf'
as.list(x, ...)

## S4 method for signature 'APPconf'
as.character(x, ...)

## S4 method for signature 'APPconf'
markers(x)

## S4 method for signature 'APPconf'
lapply(X, FUN, ...)

## S4 method for signature 'APPconf'
unlist(x, recursive = TRUE, use.names = TRUE)
```

Arguments

object	an object of APPconf
x	APPconf object.

name	A literal character string or a name (possibly backtick quoted).
value	value to replace.
i, j	indices specifying elements to extract or replace.
...	Named or unnamed arguments to form a signature.
exact	see Extract
drop	see drop
X	an APPconf cobject.
FUN	function used by <code>lapply</code>
recursive, use.names	function used by unlist

Value

A named character vector.

Examples

```
appconf <- readRDS(system.file("extdata", "data",
  "pbmc_small", "appconf.rds", package="scRNAseqApp"))
appconf
appconf$title
appconf[["title"]]
as.list(appconf)
as.character(appconf)
markers(appconf)
lapply(appconf, print)
unlist(appconf)
```

createAppConfig

Create a metadata to describe the dataset

Description

The function will return a APPconf object which contain the reference, keywords for the dataset.

Usage

```
createAppConfig(
  title,
  destinationFolder,
  species,
  doi,
  pmid,
  bibentry,
  datatype = c("scRNAseq", "scATACseq", "scMultiome"),
  markers,
  keywords,
  abstract
)
```

Arguments

title	The title of the dataset
destinationFolder	The destination folder name of the dataset without the root folder of the datasets. The data will be saved as appdataFolder/destinationFolder
species	The species of the dataset
doi, pmid	The DOI or PMID of the reference
bibentry	An object of bibentry
datatype	character(1). Type of the data, scRNAseq, scATACseq or scMultiome.
markers	A list of data.frame with gene symbols as rownames or a character vector.
keywords	The keywords for the dataset. For example the condition, cell type, tissue information The keywords will be used for whole database search
abstract	The abstract of the reference.

Value

An object of [APPconf](#) object

Examples

```
if(interactive()){
  config <- createAppConfig(
    title="pbmc_small",
    destinationFolder = "pbmc_small",
    species = "Homo sapiens",
    doi="10.1038/nbt.3192",
    datatype = "scRNAseq")
}
```

createDataSet	<i>Create a dataset Create a dataset from a Seurat object. The function will try to find the markers in the Misc data named as 'markers'. The misc data should be output of function FindAllMarkers.</i>
---------------	--

Description

Create a dataset Create a dataset from a Seurat object. The function will try to find the markers in the Misc data named as 'markers'. The misc data should be output of function FindAllMarkers.

Usage

```
createDataSet(
  appconf,
  seu,
  config,
  contrast,
  assayName,
  gexSlot = c("data", "scale.data", "counts"),
  atacAssayName,
```

```

    atacSlot = c("data", "scale.data", "counts"),
    LOCKER = FALSE,
    datafolder = "data",
    default.symbol = "rownames"
  )

```

Arguments

appconf	a list object represent the information about the dataset
seu	a Seurat object
config	config file for makeShinyFiles
contrast	The contrast group
assayName	assay in single-cell data object to use for plotting gene expression, which must match one of the following: <ul style="list-style-type: none"> • Seurat objects: "RNA" or "integrated" assay, default is "RNA"
gexSlot	layer in single-cell assay to plot. Default is to use the "data" layer
atacAssayName	assay in single-cell data object to use for plotting open chromatin.
atacSlot	layer in single-cell atac assay to plot. Default is to use the "data" layer
LOCKER	Set locker if the file is required login
datafolder	app data folder
default.symbol	character(1L) specifying the default rownames to be used. If use default, the gene symbols will be the row names of the assay. If one column name of the meta.feature of the assay is supplied, the function will try to extract the symbols from the meta.feature slot of the assay.

Value

The updated Seurat object.

Examples

```

library(Seurat)
if(interactive()){
  appconf <- createAppConfig(
    title="pbmc_small",
    destinationFolder = "pbmc_small",
    species = "Homo sapiens",
    doi="10.1038/nbt.3192",
    datatype = "scRNAseq")
  createDataSet(appconf, pbmc_small, datafolder=tempdir())
}

```

createSeuFromCellRanger
load data from cellRanger

Description

load data from cellRanger

Usage

```
createSeuFromCellRanger(outsFolder)
```

Arguments

outsFolder the outs folder of cellRanger

Value

An SeuratObject

createSeuFromMatrix *load data from a count matrix*

Description

load data from a count matrix

Usage

```
createSeuFromMatrix(matrix, meta, genes, cluster, ...)
```

Arguments

matrix	count matrix
meta	cell-level meta data
genes	character. gene names, will be the rownames of the matrix
cluster	the cluster coordinates
...	The parameter passed to read.delim when read cluster file.

Value

An SeuratObject

`scInit`*Create a scRNAseqApp project*

Description

To run `scRNAseqApp`, you need to first create a directory which contains the required files.

Usage

```
scInit(  
  app_path = getwd(),  
  root = "admin",  
  password = "scRNAseqApp",  
  datafolder = "data",  
  overwrite = FALSE,  
  app_title = "scRNAseq Database",  
  app_description =  
    "This database is a collection of\n          single cell RNA-seq data.",  
  passphrase = NULL  
)
```

Arguments

<code>app_path</code>	path, a directory where do you want to create the app
<code>root</code>	character(1), the user name for administrator
<code>password</code>	character(1), the password for administrator
<code>datafolder</code>	the folder where saved the dataset for the app
<code>overwrite</code>	logical(1), overwrite the <code>app_path</code> if there is a project.
<code>app_title, app_description</code>	character(1). The title and description of the home page.
<code>passphrase</code>	A password to protect the data inside the database.

Value

no returns. This function will copy files to `app_path`

Examples

```
if(interactive()){  
  scInit()  
}
```

 scRNAseqApp

scRNAseqApp main function

Description

create a scRNAseqApp once the initialization is done.

Usage

```
scRNAseqApp(
  app_path = getwd(),
  datafolder = "data",
  defaultDataset = "pbmc_small",
  windowTitle = "scRNAseq/scATACseq database",
  favicon = system.file("assets", "img", "favicon.ico", package = "scRNAseqApp"),
  banner = system.file("assets", "img", "banner.png", package = "scRNAseqApp"),
  footer = tagList(HTML("&copy;"), "2020 -", format(Sys.Date(), "%Y"), "jianhong@duke"),
  maxRequestSize = 1073741824,
  timeout = 30,
  theme = bs_theme(bootswatch = "lumen"),
  use_bs_themer = FALSE,
  showHelpVideo = FALSE,
  ...
)
```

Arguments

app_path	path, a directory where do you want to create the app
datafolder	the folder where saved the dataset for the app
defaultDataset	default dataset for the app.
windowTitle	The title that should be displayed by the browser window.
favicon	The favicon for the page.
banner	The banner image.
footer	The footer html contents.
maxRequestSize	Maximal upload file size. Default is 1G.
timeout	Timeout session (minutes) before logout if sleeping. Default to 30. 0 to disable.
theme	A theme.
use_bs_themer	logical(1). Used to determine the theme.
showHelpVideo	logical(1) or character(1). Show help videos in homepage or not. If an url is provided, the url will be embeded as a iframe element.
...	parameters can be passed to shinyApp except ui and server.

Value

An object that represents the app.

Examples

```
if(interactive()){  
  app_path=tempdir()  
  scInit(app_path=app_path)  
  setwd(app_path)  
  scRNAseqApp()  
}
```

Index

* APPconf

- APPconf-methods, 3
- [, APPconf, ANY, ANY, ANY-method
(APPconf-methods), 3
- [[, APPconf, ANY, ANY-method
(APPconf-methods), 3
- [[<-, APPconf, ANY, ANY, ANY-method
(APPconf-methods), 3
- \$, APPconf-method (APPconf-methods), 3
- \$<-, APPconf-method (APPconf-methods), 3

- APPconf, 5
- APPconf (APPconf-class), 2
- APPconf-class, 2, 3
- APPconf-methods, 3
- as.character, APPconf-method
(APPconf-methods), 3
- as.list, APPconf-method
(APPconf-methods), 3

- bibentry, 2

- createAppConfig, 4
- createDataSet, 5
- createSeuFromCellRanger, 7
- createSeuFromMatrix, 7

- drop, 4

- Extract, 4

- lapply, APPconf-method
(APPconf-methods), 3

- markers (APPconf-methods), 3
- markers, APPconf-method
(APPconf-methods), 3

- scInit, 8
- scRNAseqApp, 9
- show, APPconf-method (APPconf-methods), 3

- unlist, 4
- unlist, APPconf-method
(APPconf-methods), 3