

Package ‘DiscreteFDR’

February 9, 2024

Type Package

Title Multiple Testing Procedures with Adaptation for Discrete Tests

Version 1.3.7

Date 2024-02-06

Description Multiple testing procedures described in the paper Döhler, Durand and Roquain (2018) "New FDR bounds for discrete and heterogeneous tests" <[doi:10.1214/18-EJS1441](https://doi.org/10.1214/18-EJS1441)>. The main procedures of the paper (HSU and HSD), their adaptive counterparts (AHSU and AHSD), and the HBR variant are available and are coded to take as input a set of observed p-values and their discrete support under the null. A function to compute such p-values and supports for Fisher's exact tests is also provided, along with a wrapper allowing to apply discrete procedures directly from contingency tables.

License GPL-3

Encoding UTF-8

Depends R (>= 3.00)

LazyData true

RoxygenNote 7.3.1

Suggests R.rsp, knitr, rmarkdown

VignetteBuilder R.rsp, knitr

Imports Rcpp (>= 1.0.1), methods, lifecycle

LinkingTo Rcpp

URL <https://github.com/DISOhda/DiscreteFDR>

BugReports <https://github.com/DISOhda/DiscreteFDR/issues>

NeedsCompilation yes

Author Sebastian Döhler [aut, ctb],
Florian Junge [aut, ctb, cre],
Guillermo Durand [aut, ctb],
Etienne Roquain [ctb],
Christina Kihn [ctb]

Maintainer Florian Junge <diso.fbm@h-da.de>

Repository CRAN

Date/Publication 2024-02-08 23:50:15 UTC

R topics documented:

amnesia	2
DBR	3
discrete.BH	5
DiscreteFDR	7
fast.Discrete	9
fisher.pvalues.support	10
hist.DiscreteFDR	13
kernel	14
match.pvals	16
plot.DiscreteFDR	17
print.DiscreteFDR	18
summary.DiscreteFDR	19
Index	21

amnesia	<i>Amnesia and other drug reactions in the MHRA pharmacovigilance spontaneous reporting system</i>
---------	--

Description

[Deprecated]

For each of 2,446 drugs in the MHRA database (column 1), the number of cases with amnesia as an adverse event (column 2), and the number of cases with other adverse event for this drug (column 3). In total, 682,648 adverse drug reactions were reported, among them 2,044 cases of amnesia.

Note: In future versions, this dataset will be removed. It will be part of a new R package that this package will be depending on.

Usage

```
data(amnesia)
```

Format

A data frame with 2,446 rows representing drugs with the following three columns:

DrugName The name of the drug.

AmnesiaCases Number of the amnesia cases reported for the drug.

OtherAdverseCases Number of other adverse drug reactions reported for the drug.

Details

The data was collected from the Drug Analysis Prints published by the Medicines and Healthcare products Regulatory Agency (MHRA), by Heller & Gur. See references for more details.

References

R. Heller and H. Gur (2011). False discovery rate controlling procedures for discrete tests. [arXiv:1112.4627v2](#) (preprint).

Source

[Drug Analysis Prints on MHRA site](#)

DBR	<i>[HBR-λ] procedure</i>
-----	---

Description

Apply the [HBR- λ] procedure, with or without computing the critical constants, to a set of p-values and their discrete support.

Usage

```
DBR(  
  raw.pvalues,  
  pCDFlist,  
  alpha = 0.05,  
  lambda = NULL,  
  ret.crit.consts = FALSE  
)
```

Arguments

<code>raw.pvalues</code>	vector of the raw observed p-values, as provided by the end user and before matching with their nearest neighbor in the CDFs supports.
<code>pCDFlist</code>	a list of the supports of the CDFs of the p-values. Each support is represented by a vector that must be in increasing order.
<code>alpha</code>	the target FDR level, a number strictly between 0 and 1.
<code>lambda</code>	a number strictly between 0 and 1. If <code>lambda=NULL</code> (by default), then <code>lambda</code> is chosen equal to <code>alpha</code> .
<code>ret.crit.consts</code>	a boolean. If <code>TRUE</code> , critical constants are computed and returned (this is computationally intensive).

Details

[DBR- λ] is the discrete version of the [Blanchard-Roquain- λ] procedure (see References). The authors of the latter suggest to take $\lambda = \alpha$ (see their Proposition 17), which explains the choice of the default value here.

Value

A DiscreteFDR S3 class object whose elements are:

Rejected	Rejected raw p-values
Indices	Indices of rejected hypotheses
Num.rejected	Number of rejections
Adjusted	Adjusted p-values
Critical.constants	Critical constants (if requested)
Method	Character string describing the used algorithm, e.g. 'Discrete Benjamini-Hochberg procedure (step-up)'
Signif.level	Significance level alpha
Lambda	Value of lambda.
Data\$raw.pvalues	The values of raw.pvalues
Data\$pCDFlist	The values of pCDFlist
Data\$data.name	The respective variable names of raw.pvalues and pCDFlist

References

G. Blanchard and E. Roquain (2009). Adaptive false discovery rate control under independence and dependence. *Journal of Machine Learning Research*, 10, pp. 2837-2871.

See Also

[discrete.BH](#)

Examples

```
X1 <- c(4, 2, 2, 14, 6, 9, 4, 0, 1)
X2 <- c(0, 0, 1, 3, 2, 1, 2, 2, 2)
N1 <- rep(148, 9)
N2 <- rep(132, 9)
Y1 <- N1 - X1
Y2 <- N2 - X2
df <- data.frame(X1, Y1, X2, Y2)
df

#Construction of the p-values and their support
df.formatted <- fisher.pvalues.support(counts = df, input = "noassoc")
raw.pvalues <- df.formatted$raw
```

```

pCDFlist <- df.formatted$support

DBR.fast <- DBR(raw.pvalues, pCDFlist)
summary(DBR.fast)
DBR.crit <- DBR(raw.pvalues, pCDFlist, ret.crit.consts = TRUE)
summary(DBR.crit)

```

discrete.BH *[HSU], [HSD], [AHSU] and [AHSD] procedures*

Description

Apply the [HSU], [HSD], [AHSU] and [AHSD] procedures, with or without computing the critical constants, to a set of p-values and their discrete support.

Usage

```

discrete.BH(
  raw.pvalues,
  pCDFlist,
  alpha = 0.05,
  direction = "su",
  adaptive = FALSE,
  ret.crit.consts = FALSE
)

```

```

DBH(
  raw.pvalues,
  pCDFlist,
  alpha = 0.05,
  direction = "su",
  ret.crit.consts = FALSE
)

```

```

ADBH(
  raw.pvalues,
  pCDFlist,
  alpha = 0.05,
  direction = "su",
  ret.crit.consts = FALSE
)

```

Arguments

`raw.pvalues` vector of the raw observed p-values, as provided by the end user and before matching with their nearest neighbor in the CDFs supports.

pCDFlist	a list of the supports of the CDFs of the p-values. Each support is represented by a vector that must be in increasing order.
alpha	the target FDR level, a number strictly between 0 and 1.
direction	a character string specifying whether to conduct a step-up (direction="su", by default) or step-down procedure (direction="sd").
adaptive	a boolean specifying whether to conduct an adaptive procedure or not.
ret.crit.consts	a boolean. If TRUE, critical constants are computed and returned (this is computationally intensive).

Details

DBH and ADBH are wrapper functions for discrete.BH. DBH simply passes all its parameters to discrete.BH with adaptive = FALSE. ADBH does the same with adaptive = TRUE.

Value

A DiscreteFDR S3 class object whose elements are:

Rejected	Rejected raw p-values
Indices	Indices of rejected hypotheses
Num.rejected	Number of rejections
Adjusted	Adjusted p-values (only for step-down direction).
Critical.constants	Critical constants (if requested)
Method	Character string describing the used algorithm, e.g. 'Discrete Benjamini-Hochberg procedure (step-up)'
Signif.level	Significance level alpha
Data\$raw.pvalues	The values of raw.pvalues
Data\$pCDFlist	The values of pCDFlist
Data\$data.name	The respective variable names of raw.pvalues and pCDFlist

References

Döhler, S., Durand, G., & Roquain, E. (2018). New FDR bounds for discrete and heterogeneous tests. *Electronic Journal of Statistics*, 12(1), pp. 1867-1900. doi:10.1214/18EJS1441

See Also

[fast.Discrete](#), [DBR](#)

Examples

```

X1 <- c(4, 2, 2, 14, 6, 9, 4, 0, 1)
X2 <- c(0, 0, 1, 3, 2, 1, 2, 2, 2)
N1 <- rep(148, 9)
N2 <- rep(132, 9)
Y1 <- N1 - X1
Y2 <- N2 - X2
df <- data.frame(X1, Y1, X2, Y2)
df

#Construction of the p-values and their support
df.formatted <- fisher.pvalues.support(counts = df, input = "noassoc")
raw.pvalues <- df.formatted$raw
pCDFlist <- df.formatted$support
DBH.su.fast <- DBH(raw.pvalues, pCDFlist)
summary(DBH.su.fast)
DBH.sd.fast <- DBH(raw.pvalues, pCDFlist, direction = "sd")
DBH.sd.fast$Adjusted
summary(DBH.sd.fast)

DBH.su.crit <- DBH(raw.pvalues, pCDFlist, ret.crit.consts = TRUE)
summary(DBH.su.crit)
DBH.sd.crit <- DBH(raw.pvalues, pCDFlist, direction = "sd",
  ret.crit.consts = TRUE)
DBH.sd.crit$Adjusted
summary(DBH.sd.crit)

ADBH.su.fast <- ADBH(raw.pvalues, pCDFlist)
summary(ADBH.su.fast)
ADBH.sd.fast <- ADBH(raw.pvalues, pCDFlist, direction = "sd")
ADBH.sd.fast$Adjusted
summary(ADBH.sd.fast)

ADBH.su.crit <- ADBH(raw.pvalues, pCDFlist, ret.crit.consts = TRUE)
summary(ADBH.su.crit)
ADBH.sd.crit <- ADBH(raw.pvalues, pCDFlist, direction = "sd",
  ret.crit.consts = TRUE)
ADBH.sd.crit$Adjusted
summary(ADBH.sd.crit)

```

DiscreteFDR

DiscreteFDR

Description

This package implements the [HSU], [HSD], [AHSU], [AHSD] and [HBR- λ] procedures for discrete tests (see References).

Details

The functions are reorganized from the reference paper in the following way. `discrete.BH` (for Discrete Benjamini-Hochberg) implements [HSU], [HSD], [AHSU] and [AHSD], while `DBR` (for Discrete Blanchard-Roquain) implements [HBR- λ]. `DBH` and `ADBH` are wrapper functions for `discrete.BH` to access [HSU] and [HSD], as well as [AHSU] and [AHSD] directly. Their main arguments are a vector of raw observed p-values, and a list of the same length, whose elements are the discrete supports of the CDFs of the p-values.

The function `fisher.pvalues.support` allows to compute such p-values and support in the framework of a Fisher's exact test of association. It has been inspired by a help page of the package `discreteMTP`, which is no longer available on CRAN.

The function `fast.Discrete` is a wrapper for `fisher.pvalues.support` and `discrete.BH` which allows to apply discrete procedures directly to a data set of contingency tables.

We also provide the `amnesia` data set, used in our examples and in our paper. It is basically the `amnesia` data set of package `discreteMTP` (no longer on CRAN), but slightly reformatted such that each line represents a 2x2 contingency table.

No other function of the package should be used directly, as they are only internal functions called by the main ones.

Author(s)

Maintainer: Darmstadt Institute of Statistics and Operations Research <diso.fbmn@h-da.de>

Authors:

- Sebastian Döhler [contributor]
- Florian Junge [contributor]
- Guillermo Durand [contributor]

Other contributors:

- Etienne Roquain [contributor]
- Christina Kihn [contributor]

References

Döhler, S., Durand, G., & Roquain, E. (2018). New FDR bounds for discrete and heterogeneous tests. *Electronic Journal of Statistics*, 12(1), pp. 1867-1900. doi:10.1214/18EJS1441

G. Blanchard and E. Roquain (2009). Adaptive false discovery rate control under independence and dependence. *Journal of Machine Learning Research*, 10, pp. 2837-2871.

See Also

Useful links:

- <https://github.com/DISOhda/DiscreteFDR>
- Report bugs at <https://github.com/DISOhda/DiscreteFDR/issues>

fast.Discrete	<i>Fast application of discrete procedures</i>
---------------	--

Description

[Deprecated]

Apply the [HSU], [HSD], [AHSU] or [AHSD] procedure, without computing the critical constants, to a data set of 2x2 contingency tables using Fisher's exact tests.

Note: In future versions, this function will be removed and replaced by a more flexible one, which will not be limited to Fisher's exact test.

Usage

```
fast.Discrete(
  counts,
  alternative = "greater",
  input = "noassoc",
  alpha = 0.05,
  direction = "su",
  adaptive = FALSE
)
```

Arguments

counts	a data frame of two or four columns and any number of lines; each line representing a 2x2 contingency table to test. The number of columns and what they must contain depend on the value of the input argument (see Details section of fisher.pvalues.support).
alternative	same argument as in fisher.test . The three possible values are "greater" (default), "two.sided" or "less" (may be abbreviated).
input	the format of the input data frame (see Details section of fisher.pvalues.support . The three possible values are "noassoc" (default), "marginal" or "HG2011" (may be abbreviated).
alpha	the target FDR level, a number strictly between 0 and 1.
direction	a character string specifying whether to conduct a step-up (direction="su", by default) or step-down procedure (direction="sd").
adaptive	a boolean specifying whether to conduct an adaptive procedure or not.

Value

A DiscreteFDR S3 class object whose elements are:

Rejected	Rejected raw p-values
Indices	Indices of rejected hypotheses
Num.rejected	Number of rejections

Adjusted	Adjusted p-values (only for step-down direction).
Method	Character string describing the used algorithm, e.g. 'Discrete Benjamini-Hochberg procedure (step-up)'
Signif.level	Significance level alpha
Data\$raw.pvalues	The values of raw.pvalues
Data\$pCDFlist	The values of pCDFlist
Data\$data.name	The variable name of the counts dataset

See Also

[fisher.pvalues.support](#), [discrete.BH](#)

Examples

```
X1 <- c(4, 2, 2, 14, 6, 9, 4, 0, 1)
X2 <- c(0, 0, 1, 3, 2, 1, 2, 2, 2)
N1 <- rep(148, 9)
N2 <- rep(132, 9)
Y1 <- N1 - X1
Y2 <- N2 - X2
df <- data.frame(X1, Y1, X2, Y2)
df

DBH.su <- fast.Discrete(counts = df, input = "noassoc", direction = "su")
summary(DBH.su)

DBH.sd <- fast.Discrete(counts = df, input = "noassoc", direction = "sd")
DBH.sd$Adjusted
summary(DBH.sd)

ADBH.su <- fast.Discrete(counts = df, input = "noassoc", direction = "su", adaptive = TRUE)
summary(ADBH.su)

ADBH.sd <- fast.Discrete(counts = df, input = "noassoc", direction = "sd", adaptive = TRUE)
ADBH.sd$Adjusted
summary(ADBH.sd)
```

fisher.pvalues.support

Computing discrete p-values and their support for binomial and Fisher's exact tests

Description**[Deprecated]**

Computes discrete raw p-values and their support for binomial test or Fisher's exact test applied to 2x2 contingency tables summarizing counts coming from two categorical measurements.

Note: In future versions, this function will be removed. Generation of p-value supports for different exact tests, including Fisher's, will be moved to a separate package.

Usage

```
fisher.pvalues.support(counts, alternative = "greater", input = "noassoc")
```

Arguments

counts a data frame of two or four columns and any number of lines; each line represents a 2x2 contingency table to test. The number of columns and what they must contain depend on the value of the input argument, see Details.

alternative same argument as in `stats::fisher.test`. The three possible values are "greater" (default), "two.sided" or "less" and you can specify just the initial letter.

input the format of the input data frame, see Details. The three possible values are "noassoc" (default), "marginal" or "HG2011" and you can specify just the initial letter.

Details

Assume that each contingency tables compares two variables and resumes the counts of association or not with a condition. This can be resumed in the following table:

	Association	No association	Total
Variable 1	X_1	Y_1	N_1
Variable 2	X_2	Y_2	N_2
Total	$X_1 + X_2$	$Y_1 + Y_2$	$N_1 + N_2$

If `input="noassoc"`, counts has four columns which respectively contain, X_1 , Y_1 , X_2 and Y_2 . If `input="marginal"`, counts has four columns which respectively contain X_1 , N_1 , X_2 and N_2 .

If `input="HG2011"`, we are in the situation of the `amnesia` data set as in Heller & Gur (2011, see References). Each contingency table is obtained from one variable which is compared to all other variables of the study. That is, counts for "second variable" are replaced by the sum of the counts of the other variables:

	Association	No association	Total
Variable j	X_j	Y_j	N_j
Variables $\neq j$	$\sum_{i \neq j} X_i$	$\sum_{i \neq j} Y_i$	$\sum_{i \neq j} N_i$
Total	$\sum X_i$	$\sum Y_i$	$\sum N_i$

Hence counts needs to have only two columns which respectively contain X_j and Y_j .

The code for the computation of the p-values of Fisher's exact test is inspired by the example in

the help page of `p.discrete.adjust` of package `discreteMTP`, which is no longer available on CRAN.

See the Wikipedia article about Fisher's exact test, paragraph Example, for a good depiction of what the code does for each possible value of `alternative`.

Value

A list of two elements:

<code>raw</code>	raw discrete p-values.
<code>support</code>	a list of the supports of the CDFs of the p-values. Each support is represented by a vector in increasing order.

References

R. Heller and H. Gur (2011). False discovery rate controlling procedures for discrete tests. arXiv preprint. [arXiv:1112.4627v2](https://arxiv.org/abs/1112.4627v2).

"Fisher's exact test", Wikipedia, The Free Encyclopedia, accessed 2018-03-20, [link](#).

See Also

[fisher.test](#)

Examples

```
X1 <- c(4, 2, 2, 14, 6, 9, 4, 0, 1)
X2 <- c(0, 0, 1, 3, 2, 1, 2, 2, 2)
N1 <- rep(148, 9)
N2 <- rep(132, 9)
Y1 <- N1 - X1
Y2 <- N2 - X2
df <- data.frame(X1, Y1, X2, Y2)
df

#Construction of the p-values and their support
df.formatted <- fisher.pvalues.support(counts = df, input = "noassoc")
raw.pvalues <- df.formatted$raw
pCDFlist <- df.formatted$support

data(amesia)
#We only keep the first 100 lines to keep the computations fast.
#We also drop the first column to keep only columns of counts, in the Heller & Gur (2011) setting.
amesia <- amnesia[1:100,2:3]

#Construction of the p-values and their support
amesia.formatted <- fisher.pvalues.support(counts = amnesia, input = "HG2011")
raw.pvalues <- amnesia.formatted$raw
pCDFlist <- amnesia.formatted$support
```

hist.DiscreteFDR *Histogram of Raw p-Values*

Description

Computes a histogram of the raw p-values of a DiscreteFDR object.

Usage

```
## S3 method for class 'DiscreteFDR'
hist(x, breaks = "FD", plot = TRUE, ...)
```

Arguments

x	an object of class "DiscreteFDR".
breaks	as in hist ; here, the Friedman-Diaconis algorithm("FD") is used as default.
plot	a boolean If TRUE (the default), a histogram is plotted, otherwise a list of breaks and counts is returned.
...	further arguments to hist or plot.histogram , respectively.

Details

This method simply calls [hist](#) and passes the raw p-values of the object.

Value

An object of class histogram.

Examples

```
X1 <- c(4, 2, 2, 14, 6, 9, 4, 0, 1)
X2 <- c(0, 0, 1, 3, 2, 1, 2, 2, 2)
N1 <- rep(148, 9)
N2 <- rep(132, 9)
Y1 <- N1 - X1
Y2 <- N2 - X2
df <- data.frame(X1, Y1, X2, Y2)
df

#Construction of the p-values and their support
df.formatted <- fisher.pvalues.support(counts = df, input = "noassoc")
raw.pvalues <- df.formatted$raw
pCDFlist <- df.formatted$support

DBH <- DBH(raw.pvalues, pCDFlist)
hist(DBH)
```

kernel

*Kernel functions***Description****[Deprecated]**

Kernel functions that transform observed p-values or their support according to [HSU], [HSD], [AHSU], [AHSU] and [HBR- λ]. The output is used by [discrete.BH](#) or [DBR](#), respectively. `kernel_DBH_crit`, `kernel_ADBH_crit` and `kernel_DBR_crit` additionally compute and return the critical constants. The end user should not use these functions directly.

Note: In future versions, these functions will no longer be exported to the global namespace. Instead, they will be purely internal functions and will have to be called directly via `:::`, e.g. `DiscreteFDR:::kernel_DBH_fast()`.

Usage

```
kernel_DBH_fast(pCDFlist, pvalues, stepUp = FALSE, alpha = 0.05, support = 0L)
```

```
kernel_DBH_crit(pCDFlist, pvalues, sorted_pv, stepUp = FALSE, alpha = 0.05)
```

```
kernel_ADBH_fast(pCDFlist, pvalues, stepUp = FALSE, alpha = 0.05, support = 0L)
```

```
kernel_ADBH_crit(pCDFlist, pvalues, sorted_pv, stepUp = FALSE, alpha = 0.05)
```

```
kernel_DBR_fast(pCDFlist, pvalues, lambda = 0.05)
```

```
kernel_DBR_crit(pCDFlist, pvalues, sorted_pv, lambda = 0.05, alpha = 0.05)
```

Arguments

<code>pCDFlist</code>	a list of the supports of the CDFs of the p-values. Each support is represented by a vector that must be in increasing order.
<code>pvalues</code>	a numeric vector. Contains all values of the p-values supports if we search for the critical constants. If not, contains only the observed p-values. Must be sorted in increasing order!
<code>stepUp</code>	a numeric vector. Identical to <code>pvalues</code> for a step-down procedure. Equals <code>c.m</code> for a step-up procedure.
<code>alpha</code>	the target FDR level, a number strictly between 0 and 1. For <code>*.fast</code> kernels, it is only necessary, if <code>stepUp = TRUE</code> .
<code>support</code>	a numeric vector. Contains all values of the p-values supports. Ignored, if <code>stepUp = FALSE</code> . Must be sorted in increasing order!
<code>sorted_pv</code>	a vector of observed p-values, in increasing order.
<code>lambda</code>	a number strictly between 0 and 1. If <code>lambda=NULL</code> (by default), then <code>lambda</code> is chosen equal to <code>alpha</code> .

Details

When computing critical constants under step-down, that is, when using `kernel_DBH_crit`, `kernel_ADBH_crit` or `kernel_DBR_crit` with `stepUp = FALSE` (i.e. the step-down case), we still need to get transformed p-values to compute the adjusted p-values.

Value

For `kernel.DBH.fast`, `kernel.ADBH.fast` and `kernel.DBR.fast`, a vector of transformed p-values is returned. `kernel.DBH.crit`, `kernel.ADBH.crit` and `kernel.DBR.crit` return a list with critical constants (`$crit.consts`) and transformed p-values (`$pval.transf`), but if `stepUp = FALSE`, there are critical values only.

See Also

[discrete.BH](#), [fast.Discrete](#), [DBR](#)

Examples

```
X1 <- c(4, 2, 2, 14, 6, 9, 4, 0, 1)
X2 <- c(0, 0, 1, 3, 2, 1, 2, 2, 2)
N1 <- rep(148, 9)
N2 <- rep(132, 9)
Y1 <- N1 - X1
Y2 <- N2 - X2
df <- data.frame(X1, Y1, X2, Y2)
df

#Construction of the p-values and their support
df.formatted <- fisher.pvalues.support(counts = df, input = "noassoc")
raw.pvalues <- df.formatted$raw
pCDFlist <- df.formatted$support

alpha <- 0.05

# Compute the step functions from the supports

# We stay in a step-down context, where pv.numer = pv.denom,
# for the sake of simplicity

# If not searching for critical constants, we use only the observed p-values
sorted.pvals <- sort(raw.pvalues)
y.DBH.fast <- kernel_DBH_fast(pCDFlist, sorted.pvals)
y.ADBH.fast <- kernel_ADBH_fast(pCDFlist, sorted.pvals)
# transformed values
y.DBH.fast
y.ADBH.fast

# compute transformed support
pv.list <- sort(unique(unlist(pCDFlist)))
y.DBH.crit <- kernel_DBH_crit(pCDFlist, pv.list, sorted.pvals)
y.ADBH.crit <- kernel_ADBH_crit(pCDFlist, pv.list, sorted.pvals)
```

```

y.DBR.crit <- kernel_DBR_crit(pCDFlist, pv.list, sorted.pvals)
# critical constants
y.DBH.crit$crit.consts
y.ADBH.crit$crit.consts
y.DBR.crit$crit.consts
# The following exist only for step-down direction or DBR
y.DBH.crit$pval.transf
y.ADBH.crit$pval.transf
y.DBR.crit$pval.transf

```

match.pvals

Matching raw p-values with supports

Description

[Deprecated]

Constructs the observed p-values from the raw observed p-values, by rounding them to their nearest neighbor matching with the supports of their respective CDFs (as in function `p.discrete.adjust` of package `discreteMTP`, which is no longer available on CRAN). The end user should not use it directly.

Note: In future versions, this function will no longer be exported to the global namespace. Instead, it will be a purely internal function and will have to be called directly via `:::`, i.e. `DiscreteFDR:::match.pvals()`.

Usage

```
match.pvals(pCDFlist, raw.pvalues)
```

Arguments

<code>pCDFlist</code>	a list of the supports of the CDFs of the p-values. Each support is represented by a vector that must be in increasing order.
<code>raw.pvalues</code>	vector of the raw observed p-values, as provided by the end user and before matching with their nearest neighbor in the CDFs supports.

Details

Well computed raw p-values should already belong to their respective CDF support. So this function is called at the beginning of `discrete.BH`, `DBH`, `ADBH` and `DBR`, just in case raw p-values are biased.

For each raw p-value that needs to be rounded, a warning is issued.

Value

A vector where each raw p-value has been replaced by its nearest neighbor.

See Also[discrete.BH, DBR](#)**Examples**

```

toyList <- list(c(0.3,0.7,1),c(0.1,0.65,1))
toyRaw1 <- c(0.3,0.65)
match.pvals(toyList,toyRaw1)
toyRaw2 <- c(0.31,0.6)
match.pvals(toyList,toyRaw2)

```

plot.DiscreteFDR

*Plot Method for DiscreteFDR objects***Description**

Plots raw p-values of a DiscreteFDR object and highlights rejected and accepted p-values. If present, the critical values are plotted, too.

Usage

```

## S3 method for class 'DiscreteFDR'
plot(
  x,
  col = c(2, 4, 1),
  pch = c(1, 1, 1),
  lwd = c(1, 1, 1),
  type.crit = "b",
  legend = NULL,
  ...
)

```

Arguments

x	an object of class "DiscreteFDR".
col	a numeric or character vector of length 3 indicating the colors of the <ol style="list-style-type: none"> 1. rejected p-values 2. accepted p-values 3. critical values (if present).
pch	a numeric or character vector of length 3 indicating the point characters of the <ol style="list-style-type: none"> 1. rejected p-values 2. accepted p-values 3. critical values (if present and type.crit is a plot type like 'p', 'b' etc.).
lwd	a numeric vector of length 3 indicating the thickness of the points and lines.

<code>type.crit</code>	1-character string giving the type of plot desired for the critical values (e.g.: 'p', 'l' etc; see plot).
<code>legend</code>	if NULL, no legend is plotted; otherwise expecting a character string like "topleft" etc. or a numeric vector of two elements indicating (x, y) coordinates.
<code>...</code>	further arguments to plot.default .

Examples

```
X1 <- c(4, 2, 2, 14, 6, 9, 4, 0, 1)
X2 <- c(0, 0, 1, 3, 2, 1, 2, 2, 2)
N1 <- rep(148, 9)
N2 <- rep(132, 9)
Y1 <- N1 - X1
Y2 <- N2 - X2
df <- data.frame(X1, Y1, X2, Y2)
df

#Construction of the p-values and their support
df.formatted <- fisher.pvalues.support(counts = df, input = "noassoc")
raw.pvalues <- df.formatted$raw
pCDFlist <- df.formatted$support

DBH.su.fast <- DBH(raw.pvalues, pCDFlist)
DBH.su.crit <- DBH(raw.pvalues, pCDFlist, ret.crit.consts = TRUE)
DBH.sd.fast <- DBH(raw.pvalues, pCDFlist, direction = "sd")
DBH.sd.crit <- DBH(raw.pvalues, pCDFlist, direction = "sd", ret.crit.consts = TRUE)

plot(DBH.sd.fast)
plot(DBH.sd.crit, xlim = c(1, 5), ylim = c(0, 0.4))
plot(DBH.su.fast, col = c(2, 4), pch = c(2, 3), lwd = c(2, 2),
      legend = "topleft", xlim = c(1, 5), ylim = c(0, 0.4))
plot(DBH.su.crit, col = c(2, 4, 1), pch = c(1, 1, 4), lwd = c(1, 1, 2),
      type.crit = 'o', legend = c(1, 0.4), lty = 1, xlim = c(1, 5),
      ylim = c(0, 0.4))
```

`print.DiscreteFDR` *Printing DiscreteFDR results*

Description

Prints the results of discrete FDR analysis, stored in a `DiscreteFDR` S3 class object.

Usage

```
## S3 method for class 'DiscreteFDR'
print(x, ...)
```

Arguments

`x` an object of class "DiscreteFDR".

`...` further arguments to be passed to or from other methods. They are ignored in this function.

Value

The respective input object is invisibly returned via `invisible(x)`.

Examples

```
X1 <- c(4, 2, 2, 14, 6, 9, 4, 0, 1)
X2 <- c(0, 0, 1, 3, 2, 1, 2, 2, 2)
N1 <- rep(148, 9)
N2 <- rep(132, 9)
Y1 <- N1 - X1
Y2 <- N2 - X2
df <- data.frame(X1, Y1, X2, Y2)
df

#Construction of the p-values and their support
df.formatted <- fisher.pvalues.support(counts = df, input = "noassoc")
raw.pvalues <- df.formatted$raw
pCDFlist <- df.formatted$support

DBH.su.crit <- DBH(raw.pvalues, pCDFlist, direction = "su",
                  ret.crit.consts = TRUE)
print(DBH.su.crit)
```

summary.DiscreteFDR *Summarizing Discrete FDR Results*

Description

summary method for class "DiscreteFDR"

Usage

```
## S3 method for class 'DiscreteFDR'
summary(object, ...)

## S3 method for class 'summary.DiscreteFDR'
print(x, max = NULL, ...)
```

Arguments

object	an object of class "DiscreteFDR".
...	further arguments passed to or from other methods.
x	an object of class "summary.DiscreteFDR".
max	numeric or NULL, specifying the maximal number of <i>rows</i> of the p-value table to be printed. By default, when NULL, <code>getOption("max.print")</code> is used.

Details

`summary.DiscreteFDR` objects include all data of an `DiscreteFDR` object, but also include an additional table which includes the raw p-values, their indices, the respective critical values (if present), the adjusted p-values (if present) and a logical column to indicate rejection. The table is sorted in ascending order by the raw p-values.

`print.summary.DiscreteFDR` simply prints the same output as `print.DiscreteFDR`, but also prints the p-value table.

Value

`summary.DiscreteFDR` computes and returns a list that includes all the data of an input `DiscreteFDR`, plus

Table	a <code>data.frame</code> , sorted by the raw p-values, that contains the indices, that raw p-values themselves, their respective critical values (if present), their adjusted p-values (if present) and a logical column to indicate rejection.
-------	--

Examples

```
X1 <- c(4, 2, 2, 14, 6, 9, 4, 0, 1)
X2 <- c(0, 0, 1, 3, 2, 1, 2, 2, 2)
N1 <- rep(148, 9)
N2 <- rep(132, 9)
Y1 <- N1 - X1
Y2 <- N2 - X2
df <- data.frame(X1, Y1, X2, Y2)
df

#Construction of the p-values and their support
df.formatted <- fisher.pvalues.support(counts = df, input = "noassoc")
raw.pvalues <- df.formatted$raw
pCDFlist <- df.formatted$support

DBH.sd.crit <- DBH(raw.pvalues, pCDFlist, direction = "sd",
                  ret.crit.consts = TRUE)
summary(DBH.sd.crit)
```

Index

* datasets

amnesia, [2](#)

ADBH, [8](#), [16](#)

ADBH (discrete.BH), [5](#)

amnesia, [2](#), [11](#)

DBH, [8](#), [16](#)

DBH (discrete.BH), [5](#)

DBR, [3](#), [6](#), [8](#), [14–17](#)

discrete.BH, [4](#), [5](#), [8](#), [10](#), [14–17](#)

DiscreteFDR, [7](#)

DiscreteFDR-package (DiscreteFDR), [7](#)

fast.Discrete, [6](#), [8](#), [9](#), [15](#)

fisher.pvalues.support, [8–10](#), [10](#)

fisher.test, [9](#), [12](#)

hist, [13](#)

hist.DiscreteFDR, [13](#)

kernel, [14](#)

kernel_ADBH_crit (kernel), [14](#)

kernel_ADBH_fast (kernel), [14](#)

kernel_DBH_crit (kernel), [14](#)

kernel_DBH_fast (kernel), [14](#)

kernel_DBR_crit (kernel), [14](#)

kernel_DBR_fast (kernel), [14](#)

match.pvals, [16](#)

plot, [18](#)

plot.default, [18](#)

plot.DiscreteFDR, [17](#)

plot.histogram, [13](#)

print.DiscreteFDR, [18](#)

print.summary.DiscreteFDR

(summary.DiscreteFDR), [19](#)

stats::fisher.test, [11](#)

summary.DiscreteFDR, [19](#)