

# Package ‘mongolstats’

January 18, 2026

**Type** Package

**Title** Mongolian 'NSO' 'PXWeb' Data and Boundaries (Tidy Client)

**Version** 0.1.0

**Description** A 'tidyverse'-friendly client for the National Statistics Office of Mongolia 'PXWeb' API <<https://data.1212.mn/>> with helpers to discover tables, variables, and fetch statistical data. Also includes utilities to retrieve Mongolia administrative boundaries (ADM0-ADM2) as 'sf' objects from open sources for mapping and spatial analysis.

**Depends** R (>= 4.1.0)

**Imports** htr2, jsonlite, tibble, dplyr, purrr, stringr, sf, memoise, cachem, rappdirs, stringi, stringdist, curl

**Suggests** testthat (>= 3.0.0), knitr, rmarkdown, pkgdown, roxygen2, lifecycle, pxweb, remotes, httptest2, covr, lintr, styler, future, future.apply, cli, ggplot2, scales, forcats, tidyr, lubridate

**VignetteBuilder** knitr

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Config/testthat/edition** 3

**URL** <https://temuulene.github.io/mongolstats/>,  
<https://data.1212.mn/pxweb/>

**BugReports** <https://github.com/temuulene/mongolstats/issues>

**License** MIT + file LICENSE

**NeedsCompilation** no

**Author** Temuulen Enebish [aut, cre]

**Maintainer** Temuulen Enebish <temuulen@gmail.com>

**Repository** CRAN

**Date/Publication** 2026-01-18 11:00:02 UTC

## Contents

as_px_query . . . . .	2
mn_boundaries . . . . .	3
mn_boundaries_normalize . . . . .	4
mn_boundary_keys . . . . .	4
mn_fuzzy_join_by_name . . . . .	5
mn_join_by_name . . . . .	6
nso_cache_clear . . . . .	6
nso_cache_disable . . . . .	7
nso_cache_enable . . . . .	7
nso_cache_status . . . . .	8
nso_data . . . . .	8
nso_dims . . . . .	9
nso_dim_values . . . . .	10
nso_fetch . . . . .	10
nso_itms . . . . .	11
nso_itms_by_sector . . . . .	12
nso_itms_detail . . . . .	12
nso_itms_search . . . . .	13
nso_offline_disable . . . . .	13
nso_offline_enable . . . . .	14
nso_options . . . . .	14
nso_package . . . . .	15
nso_period_seq . . . . .	16
nso_query . . . . .	17
nso_rebuild_px_index . . . . .	17
nso_search . . . . .	18
nso_sectors . . . . .	19
nso_subsectors . . . . .	19
nso_table_meta . . . . .	20
nso_table_periods . . . . .	20
<b>Index</b>	<b>22</b>

---

as\_px\_query

*Convert a query to a PXWeb body*

---

### Description

Convert a query to a PXWeb body

### Usage

```
as_px_query(x, lang = .px_lang())
```

**Arguments**

x                    An nso\_query object.  
lang                PX language: "en" or "mn" (defaults to current option).

**Value**

A list suitable to send as JSON body to PXWeb.

**Examples**

```
q <- nso_query("DT_NS0_0300_001V2", list(Year = "2023"))  
body <- as_px_query(q)
```

---

mn_boundaries	<i>Mongolia administrative boundaries (sf)</i>
---------------	--

---

**Description**

Downloads Mongolia boundaries for ADM0/ADM1/ADM2 from the GeoBoundaries API and returns an sf object. Results can be cached by the caller as needed.

**Usage**

```
mn_boundaries(level = c("ADM0", "ADM1", "ADM2"))
```

**Arguments**

level                One of "ADM0", "ADM1", "ADM2".

**Value**

An sf object with polygons for the requested level.

**Examples**

```
# Get aimag (province) boundaries  
aimags <- mn_boundaries("ADM1")  
head(aimags)
```

mn\_boundaries\_normalize

*Add normalized name columns to boundaries*

---

### Description

Add normalized name columns to boundaries

### Usage

```
mn_boundaries_normalize(g, name_col = "shapeName")
```

### Arguments

`g` sf object from `mn_boundaries()`  
`name_col` Column with English names (default 'shapeName').

### Value

sf with `name_std` column added.

### Examples

```
aimags <- mn_boundaries("ADM1")  
aimags <- mn_boundaries_normalize(aimags)  
head(aimags$name_std)
```

---

mn\_boundary\_keys

*Boundary keys/crosswalk helper*

---

### Description

Boundary keys/crosswalk helper

### Usage

```
mn_boundary_keys(level = "ADM1")
```

### Arguments

`level` Boundary level.

### Value

tibble with key columns from GeoBoundaries and normalized names.

**Examples**

```
keys <- mn_boundary_keys("ADM1")
head(keys)
```

---

mn\_fuzzy\_join\_by\_name *Fuzzy join data to boundaries by name*

---

**Description**

Fuzzy join data to boundaries by name

**Usage**

```
mn_fuzzy_join_by_name(
  data,
  name_col,
  level = "ADM1",
  boundaries = NULL,
  max_distance = 2,
  method = c("osa", "lv", "jw", "dl")
)
```

**Arguments**

data	Data frame with a name column.
name_col	Column in data containing names.
level	Boundary level.
boundaries	Optional pre-fetched boundaries.
max_distance	Maximum string distance for a match (default 2).
method	Distance method passed to <code>stringdist::stringdist</code> .

**Value**

sf with best fuzzy matches joined.

**Examples**

```
# Join even with minor spelling differences
pop_data <- data.frame(aimag = c("Ulanbatar", "Darhan"), pop = c(1500000, 100000))
sf_joined <- mn_fuzzy_join_by_name(pop_data, "aimag", level = "ADM1")
```

---

mn_join_by_name	<i>Join data to boundaries by (normalized) names</i>
-----------------	--

---

**Description**

Join data to boundaries by (normalized) names

**Usage**

```
mn_join_by_name(data, name_col, level = "ADM1", boundaries = NULL)
```

**Arguments**

data	Data frame with a name column.
name_col	Column in data that contains names to join on.
level	Boundary level, passed to mn_boundaries() if boundaries not provided.
boundaries	Optional pre-fetched boundaries.

**Value**

sf with joined data.

**Examples**

```
pop_data <- data.frame(aimag = c("Ulaanbaatar", "Darkhan-Uul"), pop = c(1500000, 100000))  
sf_joined <- mn_join_by_name(pop_data, "aimag", level = "ADM1")
```

---

nso_cache_clear	<i>Clear cached entries</i>
-----------------	-----------------------------

---

**Description**

Clear cached entries

**Usage**

```
nso_cache_clear()
```

**Value**

No return value, called for side effects.

**Examples**

```
nso_cache_clear()
```

---

nso_cache_disable	<i>Disable caching</i>
-------------------	------------------------

---

**Description**

Disable caching

**Usage**

```
nso_cache_disable()
```

**Value**

No return value, called for side effects.

**Examples**

```
nso_cache_disable()
```

---

nso_cache_enable	<i>Enable or configure caching</i>
------------------	------------------------------------

---

**Description**

Caches table lists and codebooks on disk to speed up repeated calls. Optionally set a time-to-live (TTL) for cache entries.

**Usage**

```
nso_cache_enable(dir = NULL, ttl = NULL)
```

**Arguments**

dir	Directory for cache; defaults to user cache dir.
ttl	Optional TTL in seconds for cached entries (applies to the disk cache). If NULL, entries persist until cleared.

**Value**

Cache directory path (invisibly).

**Examples**

```
# Enable caching in a temporary directory (for demo purposes)
cache_dir <- nso_cache_enable(dir = tempdir())

# Check status
nso_cache_status()

# Disable when done
nso_cache_disable()
```

---

nso_cache_status	<i>Cache status</i>
------------------	---------------------

---

**Description**

Report current cache configuration and basic stats.

**Usage**

```
nso_cache_status()
```

**Value**

A list with enabled, dir, and has\_cache.

**Examples**

```
nso_cache_status()
```

---

nso_data	<i>Fetch statistical data for a table (PXWeb)</i>
----------	---

---

**Description**

Fetch statistical data for a table (PXWeb)

**Usage**

```
nso_data(
  tbl_id,
  selections,
  labels = c("none", "en", "mn", "both"),
  value_name = getOption("mongolstats.value_name", "value"),
  include_raw = getOption("mongolstats.attach_raw", FALSE)
)
```



**Arguments**

tbl_id	Table identifier (e.g., "DT_NSO_0300_001V2").
selections	Named list mapping variable labels (e.g., Year, Sex) to desired codes or labels.
labels	Label handling: "none" (codes only), "en", "mn", or "both".
value_name	Name of the numeric value column in the result (default: "value").
include_raw	If TRUE, attach the raw PX payload as attribute px_raw.

**Value**

A tibble with one column per dimension and a numeric value column.

**Examples**

```
# Fetch population data
pop <- nso_data(
  tbl_id = "DT_NSO_0300_001V2",
  selections = list(Year = "2023")
)
head(pop)
```

---

nso\_dims

*List dimensions for a PXWeb table*


---

**Description**

Returns one row per dimension with basic metadata.

**Usage**

```
nso_dims(tbl_id)
```

**Arguments**

tbl_id	Table identifier (e.g., "DT_NSO_0300_001V2").
--------	---

**Value**

A tibble with columns: dim (display name), code (dimension code), is\_time (logical), and n\_values (number of values for the dimension).

**Examples**

```
dims <- nso_dims("DT_NSO_0300_001V2")
dims
```

---

nso_dim_values	<i>List values for a table dimension</i>
----------------	--

---

**Description**

Returns codes and optional labels for a specific dimension.

**Usage**

```
nso_dim_values(tbl_id, dim, labels = c("code", "en", "mn", "both"))
```

**Arguments**

tbl_id	Table identifier (e.g., "DT_NSO_0300_001V2").
dim	Dimension name or code (case-insensitive; exact match preferred).
labels	One of "code", "en", "mn", or "both" to control returned label columns.

**Value**

A tibble with at least code; may include label\_en and/or label\_mn.

**Examples**

```
values <- nso_dim_values("DT_NSO_0300_001V2", "Year")
head(values)
```

---

nso_fetch	<i>Fetch a query and return a tibble</i>
-----------	--

---

**Description**

Executes an nso\_query and returns a tidy tibble with one column per dimension and a numeric value column. Use labels to add \_en/\_mn columns for each dimension.

**Usage**

```
nso_fetch(
  x,
  labels = c("code", "en", "mn", "both"),
  value_name = getOption("mongolstats.value_name", "value"),
  include_raw = getOption("mongolstats.attach_raw", FALSE)
)
```

**Arguments**

x	An nso_query object.
labels	One of "code", "en", "mn", or "both" (mapped to internal API).
value_name	Name of the numeric value column in the result (default: "value").
include_raw	If TRUE, attach the raw PX payload as attribute px_raw.

**Value**

A tibble.

**Examples**

```
q <- nso_query("DT_NSO_0300_001V2", list(Year = "2023"))
data <- nso_fetch(q)
head(data)
```

---

nso\_itms

*List available NSO tables (PXWeb)*

---

**Description**

Returns a tibble of all available tables in the NSO PXWeb catalog.

**Usage**

```
nso_itms()

nso_tables()
```

**Value**

A tibble with columns: px\_path, px\_file, tbl\_id, tbl\_eng\_nm, tbl\_nm, strt\_prd, end\_prd, list\_id.

**Examples**

```
# List all available tables
tables <- nso_itms()
head(tables)
```

---

nso\_itms\_by\_sector      *List tables under a sector or sub-sector (PXWeb path)*

---

**Description**

List tables under a sector or sub-sector (PXWeb path)

**Usage**

```
nso_itms_by_sector(list_id)
```

**Arguments**

list\_id                  Path string from nso\_sectors()/nso\_subsectors() id.

**Value**

A tibble of tables matching the specified sector path.

**Examples**

```
sectors <- nso_sectors()
tables <- nso_itms_by_sector(sectors$id[1])
```

---

nso\_itms\_detail                  *Get variable codes for a table (PXWeb)*

---

**Description**

Get variable codes for a table (PXWeb)

**Usage**

```
nso_itms_detail(tbl_id)
```

```
nso_variables(tbl_id)
```

**Arguments**

tbl\_id                  Table identifier (e.g., "DT\_NSO\_0300\_001V2").

**Value**

A tibble with variable metadata.

**Examples**

```
vars <- nso_itms_detail("DT_NS0_0300_001V2")
vars
```

---

nso_itms_search	<i>Search tables by keyword (PXWeb)</i>
-----------------	---

---

**Description**

Search tables by keyword (PXWeb)

**Usage**

```
nso_itms_search(query, fields = c("tbl_eng_nm", "tbl_nm"))
```

**Arguments**

query	A single keyword string to search for (case-insensitive).
fields	Character vector of column names to search within (defaults to English and Mongolian titles).

**Value**

A tibble of matching tables.

**Examples**

```
# Search for population tables
nso_itms_search("population")
```

---

nso_offline_disable	<i>Disable offline mode</i>
---------------------	-----------------------------

---

**Description**

Disable offline mode

**Usage**

```
nso_offline_disable()
```

**Value**

Invisibly, TRUE.

**Examples**

```
nso_offline_disable()
```

---

```
nso_offline_enable    Enable offline mode
```

---

**Description**

When enabled, HTTP requests are prevented and functions that require the network will raise a clear offline error. Cached metadata can still be used if already available via `nso_cache_enable()`.

**Usage**

```
nso_offline_enable()
```

**Value**

Invisibly, TRUE.

**Examples**

```
# Enable offline mode
nso_offline_enable()

# Check the option was set
getOption("mongolstats.offline")

# Disable to restore normal operation
nso_offline_disable()
```

---

```
nso_options    Set or get mongolstats options
```

---

**Description**

Convenience wrapper around `base::options()` for mongolstats.

**Usage**

```
nso_options(...)
```

**Arguments**

...           Named options to set. If empty, returns a named list of current mongolstats options.

**Value**

Invisibly, the previous values of the options changed, or a list of current values when called with no arguments.

**Examples**

```
# Get all current mongolstats options
nso_options()

# Set an option (save old value for restoration)
old <- nso_options(mongolstats.default_labels = "en")

# Restore original value
options(old)
```

---

nso_package	<i>Fetch multiple tables and bind (PXWeb)</i>
-------------	---

---

**Description**

Fetch multiple tables and bind (PXWeb)

**Usage**

```
nso_package(
  requests,
  labels = c("none", "en", "mn", "both"),
  parallel = getOption("mongolstats.parallel", FALSE),
  value_name = getOption("mongolstats.value_name", "value")
)
```

**Arguments**

requests	A list of records, each with tbl_id and selections (named list)
labels	Label handling as in nso_data()
parallel	If TRUE, use future.apply to fetch tables in parallel.
value_name	Name of the numeric value column in the result (default: "value").

**Value**

A tibble combining data from all requested tables, with a tbl\_id column identifying the source table.

**Examples**

```
reqs <- list(
  list(tbl_id = "DT_NSO_0300_001V2", selections = list(Year = "2023"))
)
combined <- nso_package(reqs)
```

---

nso_period_seq	<i>Create period codes</i>
----------------	----------------------------

---

**Description**

Utilities to construct NSO period codes and sequences. For monthly data, use YYYYMM; for yearly, use YYYY.

**Usage**

```
nso_period_seq(start, end, by = c("Y", "M"))
```

**Arguments**

start, end	Start and end periods as character (YYYY or YYYYMM).
by	'Y' for yearly or 'M' for monthly.

**Value**

Character vector of period codes.

**Examples**

```
# Generate yearly sequence
nso_period_seq("2020", "2024", by = "Y")

# Generate monthly sequence
nso_period_seq("202401", "202406", by = "M")
```



---

nso_query	<i>Create a PXWeb query object</i>
-----------	------------------------------------

---

**Description**

Builds a lightweight query object that records a table id and selections. Use `nso_fetch()` to execute it, or `as_px_query()` to inspect the underlying PXWeb body.

**Usage**

```
nso_query(tbl_id, selections = list())
```

**Arguments**

tbl_id	Table identifier, e.g. "DT_NSO_0300_001V2".
selections	Named list mapping dimension labels (e.g., Year, Sex) to desired codes or labels.

**Value**

An object of class `nso_query`.

**Examples**

```
# Create a query object (does not require network)
q <- nso_query("DT_NSO_0300_001V2", list(Year = "2023", Sex = "Total"))
print(q)
```

---

nso_rebuild_px_index	<i>Rebuild PXWeb index and optionally write to a file</i>
----------------------	---

---

**Description**

Crawls the PXWeb API to rebuild the table index. If `path` is provided, the index is written to that file; otherwise only the in-memory index is refreshed.

**Usage**

```
nso_rebuild_px_index(path = NULL, write = !is.null(path))
```

**Arguments**

path	Output path for JSON. If NULL (default), no file is written. For package development, use "inst/extdata/px_index.json".
write	Whether to write JSON to path. Defaults to TRUE if path is provided, FALSE otherwise.

**Value**

A tibble containing the rebuilt table index.

**Examples**

```
# Rebuild in-memory index only (takes time to crawl API)

idx <- nso_rebuild_px_index()
head(idx)
```

---

nso_search	<i>Search NSO tables</i>
------------	--------------------------

---

**Description**

Search NSO tables

**Usage**

```
nso_search(query, sector = NULL, fields = c("tbl_eng_nm", "tbl_nm"))
```

**Arguments**

query	Search string (regex, case-insensitive).
sector	Optional sector/subsector list_id to filter results.
fields	Character vector of fields to search within.

**Value**

Tibble of matching tables.

**Examples**

```
nso_search("population")
```

---

nso_sectors	<i>List top-level categories (PXWeb NSO root)</i>
-------------	---

---

**Description**

List top-level categories (PXWeb NSO root)

**Usage**

```
nso_sectors()
```

**Value**

tibble with id, type, text

**Examples**

```
sectors <- nso_sectors()
head(sectors)
```

---

nso_subsectors	<i>List children for a given path (PXWeb)</i>
----------------	---

---

**Description**

List children for a given path (PXWeb)

**Usage**

```
nso_subsectors(subid)
```

**Arguments**

subid	Path id from nso_sectors()/nso_subsectors() (e.g., 'Population, household' or 'Population, household/1_Population, household')
-------	--

**Value**

A tibble with columns: id, type, text.

**Examples**

```
sectors <- nso_sectors()
nso_subsectors(sectors$id[1])
```

---

nso_table_meta	<i>Table metadata as per-dimension codebooks</i>
----------------	--

---

**Description**

Returns a tibble with one row per dimension and a codes list-column, where each element is a tibble of codes and labels (code, label\_en, label\_mn). Useful for manual query assembly and for inspecting available categories per dimension.

**Usage**

```
nso_table_meta(tbl_id)
```

**Arguments**

tbl\_id            Table identifier (e.g., "DT\_NSO\_0300\_001V2").

**Value**

A tibble with columns: dim (display name), code (dimension code), is\_time (logical), n\_values (integer), and codes (list of tibbles).

**Examples**

```
meta <- nso_table_meta("DT_NSO_0300_001V2")
meta
```

---

nso_table_periods	<i>Get valid periods for a table (PXWeb)</i>
-------------------	--

---

**Description**

Get valid periods for a table (PXWeb)

**Usage**

```
nso_table_periods(tbl_id)
```

**Arguments**

tbl\_id            Table identifier.

**Value**

Character vector of period labels (e.g., years)

**Examples**

```
periods <- nso_table_periods("DT_NS0_0300_001V2")  
head(periods)
```

# Index

`as_px_query`, [2](#)  
`as_px_query()`, [17](#)

`base::options()`, [14](#)

`mn_boundaries`, [3](#)  
`mn_boundaries_normalize`, [4](#)  
`mn_boundary_keys`, [4](#)  
`mn_fuzzy_join_by_name`, [5](#)  
`mn_join_by_name`, [6](#)

`nso_cache_clear`, [6](#)  
`nso_cache_disable`, [7](#)  
`nso_cache_enable`, [7](#)  
`nso_cache_status`, [8](#)  
`nso_data`, [8](#)  
`nso_dim_values`, [10](#)  
`nso_dims`, [9](#)  
`nso_fetch`, [10](#)  
`nso_fetch()`, [17](#)  
`nso_itms`, [11](#)  
`nso_itms_by_sector`, [12](#)  
`nso_itms_detail`, [12](#)  
`nso_itms_search`, [13](#)  
`nso_offline_disable`, [13](#)  
`nso_offline_enable`, [14](#)  
`nso_options`, [14](#)  
`nso_package`, [15](#)  
`nso_period_seq`, [16](#)  
`nso_query`, [17](#)  
`nso_rebuild_px_index`, [17](#)  
`nso_search`, [18](#)  
`nso_sectors`, [19](#)  
`nso_subsectors`, [19](#)  
`nso_table_meta`, [20](#)  
`nso_table_periods`, [20](#)  
`nso_tables(nso_itms)`, [11](#)  
`nso_variables(nso_itms_detail)`, [12](#)