

Package ‘rCNV’

August 8, 2023

Type Package

Title Detect Copy Number Variants from SNPs Data

Version 1.2.0

Date 2023-08-01

Language en-US

Maintainer Piyal Karunaratne <piyalkarumail@yahoo.com>

Description

Functions in this package will import filtered variant call format (VCF) files of SNPs data and generate data sets to detect copy number variants, visualize them and do downstream analyses with copy number variants(e.g. Environmental association analyses).

License AGPL (>= 3)

Imports data.table, graphics, colorspace, R.utils, qgraph, stringr

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Depends R (>= 3.6.0)

Suggests rmarkdown, knitr, testthat (>= 3.0.0), covr

Config/testthat/edition 3

URL <https://piyalkarum.github.io/rCNV/>,
<https://cran.r-project.org/package=rCNV>

BugReports <https://github.com/piyalkarum/rCNV/issues>

NeedsCompilation no

Author Piyal Karunaratne [aut, cre] (<<https://orcid.org/0000-0002-1934-145X>>),
Qiujie Zhou [aut] (<<https://orcid.org/0000-0001-7351-2371>>),
Klaus Schliep [aut] (<<https://orcid.org/0000-0003-2941-0161>>),
Pascal Milesi [aut] (<<https://orcid.org/0000-0001-8580-4291>>)

Repository CRAN

Date/Publication 2023-08-08 11:10:02 UTC

R topics documented:

ad.correct	2
ADnorm	3
ADtable	4
allele.freq	4
allele.info	5
alleleINF	7
cnv	8
cpm.normal	9
depthVsSample	11
dup.plot	12
dup.validate	13
dupGet	13
exportVCF	15
get.miss	16
gt.format	16
h.zygotity	17
hetTgen	18
maf	19
norm.fact	20
power.bias	21
readVCF	22
relatedness	23
sig.hets	24
sim.als	25
vcf.stat	26
vst	27
Index	29

ad.correct	<i>Correct allele depth values</i>
------------	------------------------------------

Description

A function to correct depth values with odd number of coverage values due to sequencing anomalies or miss classification where genotype is homozygous and depth values indicate heterozygosity. The function adds a value of one to the allele with the lowest depth value for when odd number anomalies or make the depth value zero for when miss-classified. The genotype table must be provided for the latter.

Usage

```
ad.correct(het.table, gt.table = NULL, odd.correct = TRUE, verbose = TRUE)
```

Arguments

het.table allele depth table generated from the function hetTgen
gt.table genotype table generated from the function hetTgen
odd.correct logical, to correct for odd number anomalies in AD values. default TRUE
verbose logical. show progress. Default TRUE

Value

Returns the coverage corrected allele depth table similar to the output of hetTgen

Author(s)

Piyal Karunaratne

Examples

```
## Not run: adc<-ad.correct(ADtable)
```

ADnorm

Normalized allele depth example data

Description

Normalized example SNPs data of Chinook Salmon from Larson et al. 2014 The data has been normalized with TMM

Usage

```
data(ADnorm)
```

Format

An object of class list of length 2.

References

Larson, W. A., Seeb, L. W., Everett, M. V., Waples, R. K., Templin, W. D., & Seeb, J. E. (2014). Genotyping by sequencing resolves shallow population structure to inform conservation of Chinook salmon (*Oncorhynchus tshawytscha*). *Evolutionary Applications*, 7(3)

ADtable

Allele Depth (AD) example data

Description

Example SNPs data of Chinook Salmon from Larson et al. et al. 2014. The data contains only a partial snps data set of RadSeq data after filtering.

Usage

```
data(ADtable)
```

Format

An object of class `data.frame` with 3000 rows and 109 columns.

References

- Larson, W. A., Seeb, L. W., Everett, M. V., Waples, R. K., Templin, W. D., & Seeb, J. E. (2014). Genotyping by sequencing resolves shallow population structure to inform conservation of Chinook salmon (*Oncorhynchus tshawytscha*). *Evolutionary Applications*, 7(3), 355-369.
- McKinney, G. J., Waples, R. K., Seeb, L. W., & Seeb, J. E. (2017). Paralogs are revealed by proportion of heterozygotes and deviations in read ratios in genotyping by sequencing data from natural populations. *Molecular Ecology Resources*, 17(4)

allele.freq

Generate allele frequency table for individuals or populations

Description

Get alternative allele frequency across all individuals per SNP from the genotype or allele depth tables

Usage

```
allele.freq(gtt, f.typ = c("pop", "ind"), verbose = TRUE)
```

Arguments

gtt	a list or data frame of genotype and/or allele depth table produced from <code>hetTgen</code> (or similar)
f.typ	character. type of allele frequency to be calculated (individual "ind" or population "pop")
verbose	logical. whether to show the progress of the analysis

Details

If the allele frequencies to be calculated for populations from both genotype table and the allele depth table, they must be provided in a list with element names AD for allele depth table and GT for the genotype table. See the examples.

Value

Returns a data frame or a list (if both genotype and allele depth used) of allele frequencies

Author(s)

Piyal Karunaratne

Examples

```
vcf.file.path <- paste0(path.package("rCNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path=vcf.file.path)
het.table<-hetTgen(vcf,"GT")
ad.table<-hetTgen(vcf,"AD")

# for individual based AF
frQ<-allele.freq(het.table,f.typ="ind")

#for population-wise and both allele depth and genotype tables
## Not run: frQ<-allele.freq(list(AD=ad.table,GT=het.table),f.typ="pop")
```

allele.info

Get allele information for duplicate detection

Description

The function to calculate allele median ratios, proportion of heterozygotes and allele probability values under different assumptions (see details), and their chi-square significance values for duplicate detection

Usage

```
allele.info(  
  X,  
  x.norm = NULL,  
  method = c("MedR", "QN", "pca", "TMM", "TMMex"),  
  logratioTrim = 0.3,  
  sumTrim = 0.05,  
  Weighting = TRUE,  
  Acutoff = -1e+10,  
  plot.allele.cov = TRUE,  
  verbose = TRUE,
```

...
)

Arguments

X	allele depth table generated from the function <code>hetTgen</code> (non-normalized)
x.norm	a data frame of normalized allele coverage, output of <code>cpm.normal</code> . If not provided, calculated using X.
method	character. method to be used for normalization (see <code>cpm.normal</code> details). Default TMM
logratioTrim	numeric. percentage value (0 - 1) of variation to be trimmed in log transformation
sumTrim	numeric. amount of trim to use on the combined absolute levels ("A" values) for method TMM
Weighting	logical, whether to compute (asymptotic binomial precision) weights
Acutoff	numeric, cutoff on "A" values to use before trimming
plot.allele.cov	logical, plot comparative plots of allele depth coverage in homozygotes and heterozygotes
verbose	logical, whether to print progress
...	further arguments to be passed to plot

Details

Allele information generated here are individual SNP based and presents the proportion of heterozygotes, number of samples, and deviation of allele detection from a 1:1 ratio of reference and alternative alleles. The significance of the deviation is tested with Z-score test $Z = \frac{\frac{N}{2} - N_A}{\sigma_x}$, and chi-square test (see references for more details on the method).

Value

Returns a data frame of median allele ratio, proportion of heterozygotes, number of heterozygotes, and allele probability at different assumptions with their chi-square significance

Author(s)

Piyal Karunaratne, Pascal Milesi, Klaus Schliep

References

- McKinney, G. J., Waples, R. K., Seeb, L. W., & Seeb, J. E. (2017). Paralogs are revealed by proportion of heterozygotes and deviations in read ratios in genotyping by sequencing data from natural populations. *Molecular Ecology Resources*, 17(4)
- Karunaratne et al. 2022 (to be added)

Examples

```
## Not run: data(ADtable)
AI<-allele.info(ADtable,x.norm=ADnorm)
## End(Not run)
```

alleleINF	<i>Allele info example data</i>
-----------	---------------------------------

Description

Semi-randomly generated data from the function `dup.snp.info`. Data contains depth and proportion values of 2857 snps

Usage

```
data(alleleINF)
```

Format

An object of class `data.frame` with 2857 rows and 28 columns.

Source

[Chinook Salmon sequence reads McKinney et al. 2017](#)

References

- Larson, W. A., Seeb, L. W., Everett, M. V., Waples, R. K., Templin, W. D., & Seeb, J. E. (2014). Genotyping by sequencing resolves #' shallow population structure to inform conservation of Chinook salmon (*Oncorhynchus tshawytscha*). *Evolutionary Applications*, 7(3)
- McKinney, G. J., Waples, R. K., Seeb, L. W., & Seeb, J. E. (2017). Paralogs are revealed by proportion of heterozygotes and deviations in read ratios in genotyping by sequencing data from natural populations. *Molecular Ecology Resources*, 17(4)

Examples

```
data(alleleINF)
with(alleleINF,plot(medRatio~propHet))
```

cnv

*Find CNVs from deviants***Description**

Categorize deviant and non-deviant into "singlets" and "duplicates" based on the statistical approaches specified by the user. The intersection of all the stats provided will be used in the categorization. If one would like to use the intersection of at least two stats, this can be specified in the `n.ints`

Usage

```
cnv(
  data,
  test = c("z.het", "z.05", "z.all", "chi.het", "chi.05", "chi.all"),
  filter = c("intersection", "kmeans"),
  WGS = TRUE,
  ft.threshold = 0.05,
  plot = TRUE,
  verbose = TRUE,
  ...
)
```

Arguments

<code>data</code>	A data frame of allele information generated with the function <code>allele.info</code>
<code>test</code>	vector of characters. Type of test to be used for significance. See details
<code>filter</code>	character. Type of filter to be used for filtering CNVs. default <code>kmeans</code> . See details.
<code>WGS</code>	logical. test parameter. See details <code>WGS</code> is a test parameter to include or exclude coefficient of variance (<code>cv</code>) in <code>kmeans</code> . For data sets with more homogeneous depth distribution, excluding <code>cv</code> improves CNV detection. If you're not certain about this, use <code>TRUE</code> which is the default.
<code>ft.threshold</code>	confidence interval for filtering default = 0.05
<code>plot</code>	logical. Plot the detection of duplicates. default <code>TRUE</code>
<code>verbose</code>	logical. show progress
<code>...</code>	other arguments to be passed to <code>plot</code>

Details

SNP deviants are detected with both excess of heterozygosity according to HWE and deviant SNPs where depth values fall outside of the normal distribution are detected using the following methods:

- Z-score test $Z_x = \sum_{i=1}^n Z_i$; $Z_i = \frac{((N_i \times p) - N_{Ai})}{\sqrt{N_i \times p(1-p)}}$

- chi-square test $X_x^2 = \sum_{i=1}^n X_i^2$; $X_i^2 = \left(\frac{(N_i \times p - N_{Ai})^2}{N_i \times p} + \frac{(N_i \times (1-p) - (N_i - N_{Ai}))^2}{N_i \times (1-p)} \right)$

See references for more details on the methods

Users can pick among Z-score for heterozygotes (z.het, chi.het), all allele combinations (z.all, chi.all) and the assumption of no probe bias p=0.5 (z.05, chi.05)

filter will determine whether the intersection or kmeans clustering of the provided tests should be used in filtering CNVs. The intersection uses threshold values for filtering and kmeans use unsupervised clustering. Kmeans clustering is recommended if one is uncertain about the threshold values.

Value

Returns a data frame of SNPs with their detected duplication status

Author(s)

Piyal Karunaratne

Examples

```
## Not run: data(alleleINF)
DD<-cnv(alleleINF)
## End(Not run)
```

cpm.normal

Calculate normalized depth for alleles

Description

This function outputs the normalized depth values separately for each allele, calculated using normalization factor with trimmed mean of M-values of sample libraries, median ratios normalization or quantile normalization, See details.

Usage

```
cpm.normal(
  het.table,
  method = c("MedR", "QN", "pca", "TMM", "TMMex"),
  logratioTrim = 0.3,
  sumTrim = 0.05,
  Weighting = TRUE,
  Acutoff = -1e+10,
  verbose = TRUE,
  plot = TRUE
)
```

Arguments

het.table	allele depth table generated from the function hetTgen
method	character. method to be used (see details). Default TMM
logratioTrim	numeric. percentage value (0 - 1) of variation to be trimmed in log transformation
sumTrim	numeric. amount of trim to use on the combined absolute levels ("A" values) for method TMM
Weighting	logical, whether to compute (asymptotic binomial precision) weights
Acutoff	numeric, cutoff on "A" values to use before trimming (only for TMM(ex))
verbose	logical. show progress
plot	logical. Plot the boxplot of sample library sizes showing outliers

Details

This function converts an observed depth value table to an effective depth value table using several normalization methods;

1. TMM normalization (See the original publication for more information). It is different from the function normz only in calculation of the counts per million is for separate alleles instead of the total depth. The TMMex method is an extension of the TMM method for large data sets containing SNPs exceeding 10000
2. The method MedR is median ratio normalization;
3. QN - quantile normalization (see Maza, Elie, et al. 2013 for a comparison of methods).
4. PCA - a modified Kaiser's Rule applied to depth values: Sample variation of eigen values smaller than 0.7 are removed (i.e., the first eigen value < 0.7) to eliminate the effect of the library size of samples

Value

Returns a list with (AD), a data frame of normalized depth values similar to the output of hetTgen function and (outliers) a list of outlier sample names

Author(s)

Piyal Karunaratne, Qiujie Zhou

References

- Robinson MD, Oshlack A (2010). A scaling normalization method for differential expression analysis of RNA-seq data. *Genome Biology* 11, R25
- Robinson MD, McCarthy DJ and Smyth GK (2010). edgeR: a Bioconductor package for differential expression analysis of digital gene expression data. *Bioinformatics* 26
- Maza, Elie, et al. "Comparison of normalization methods for differential gene expression analysis in RNA-Seq experiments: a matter of relative size of studied transcriptomes." *Communicative & integrative biology* 6.6 (2013): e25849

Examples

```
## Not run: data(ADtable)
ADnormalized<-cpm.normal(ADtable)
## End(Not run)
```

depthVsSample	<i>Simulate median allele ratios for varying number of samples and depth values</i>
---------------	---

Description

This function will simulate the expected median allele ratios under HWE for given ranges of no. of samples and depth coverage values. This is useful if you need to find the cutoff values of allele ratios for different no. of samples and depth of coverage values in your data set.

Usage

```
depthVsSample(
  cov.len = 100,
  sam.len = 100,
  nsims = 1000,
  plot = TRUE,
  col = c("#1C86EE", "#00BFFF", "#DAA520", "#FF0000")
)
```

Arguments

cov.len	max value of depth of coverage to be simulated
sam.len	maximum no. of samples to be simulated
nsims	numerical. no. of simulations to be done for each combination of samples and depth depth and no. samples ranges
plot	logical. Whether to plot the output (a plot of no. samples vs median depth of coverage colored by median allele ratios)
col	character. Two colors to add to the gradient

Value

A matrix of median allele ratios where rows are the number of samples and columns are depth of coverage values

Author(s)

Pascal Milesi, Piyal Karunaratne

Examples

```
## Not run: depthVsSample(cov.len=100,sam.len=100)
```

`dup.plot`*Plot classified SNPs into deviants/CNVs and non-deviants/non-CNVs*

Description

The function plots detected deviants/CNVs from functions `sig.snps`, `cnv` and `dupGet` on a median ratio (MedRatio) Vs. proportion of heterozygote (PropHet) plot.

Usage

```
dup.plot(ds, ...)
```

Arguments

`ds` a data frame of detected deviants/cnvs (outputs of functions above)
`...` other graphical parameters to be passed to the function plot

Value

Returns no value, only plots proportion of heterozygotes vs allele median ratio separated by duplication status

Author(s)

Piyal Karunaratne

Examples

```
## Not run: data(alleleINF)
DD<-dupGet(alleleINF,plot=FALSE)
dup.plot(DD)
## End(Not run)
```

dup.validate	<i>Validate detected duplicates</i>
--------------	-------------------------------------

Description

This function will validate the detected duplicated-SNPs using a moving window approach (see details)

Usage

```
dup.validate(d.detect, window.size = 100, scaf.size = 10000)
```

Arguments

d.detect	a data frame of detected duplicates or deviants from the outputs of dupGet or cnv (output of dupGet)
window.size	numerical. a single value of the desired moving window size (default 100 bp)
scaf.size	numerical. scaffold size to be checked. i.e. the split size of the fragment to be checked with the specified window size. default=10000

Details

Chromosome positions correctly ordered according to a reference sequence is necessary for this function to work properly. Therefore, this function is still in development for non-mapped reference sequences.

Value

A data frame of scaffold names and their average presence in the scaffold.

Author(s)

Piyal Karunaratne

dupGet	<i>Detect deviants from SNPs; classify SNPs</i>
--------	---

Description

Detect deviant SNPs using excess of heterozygotes (alleles that do not follow HWE) and allelic-ratio deviations (alleles with ratios that do not follow a normal Z-score or chi-square distribution). See details.

Usage

```
dupGet(
  data,
  test = c("z.het", "z.05", "z.all", "chi.het", "chi.05", "chi.all"),
  intersection = FALSE,
  method = c("fisher", "chi.sq"),
  plot = TRUE,
  verbose = TRUE,
  ...
)
```

Arguments

data	data frame of the output of allele.info
test	character. type of test to be used for significance. See details
intersection	logical, whether to use the intersection of the methods specified in test (if more than one)
method	character. method for testing excess of heterozygotes. Fisher exact test (fisher) or Chi-square test (chi.sq)
plot	logical. whether to plot the detected singlets and duplicates on allele ratio vs. proportion of heterozygotes plot.
verbose	logical. show progress
...	additional parameters passed on to plot

Details

SNP deviants are detected with both excess of heterozygosity according to HWE and deviant SNPs where depth values fall outside of the normal distribution are detected using the following methods:

- Z-score test $Z_x = \sum_{i=1}^n Z_i$; $Z_i = \frac{((N_i \times p) - N_{Ai})}{\sqrt{N_i \times p(1-p)}}$
- chi-square test $X_x^2 = \sum_{i=1}^n X_i^2$; $X_i^2 = \left(\frac{(N_i \times p - N_{Ai})^2}{N_i \times p} + \frac{(N_i \times (1-p) - (N_i - N_{Ai}))^2}{N_i \times (1-p)} \right)$

See references for more details on the methods

Users can pick among Z-score for heterozygotes (z.het, chi.het), all allele combinations (z.all, chi.all) and the assumption of no probe bias p=0.5 (z.05, chi.05)

Value

Returns a data frame of snps/alleles with their duplication status

Author(s)

Piyal Karunaratne

Examples

```
## Not run: data(alleleINF)
DD<-dupGet(alleleINF)
## End(Not run)
```

exportVCF

Export VCF files

Description

A function to export tables/matrices in VCF format to VCF files

Usage

```
exportVCF(out.vcf, out.path, compress = TRUE)
```

Arguments

out.vcf	a matrix or data frame in vcf file format to be exported
out.path	a character string of output path for the vcf file; should end in the name as the vcf file and .vcf. See examples
compress	logical. whether to compress the output file. If TRUE, the file will be .gz compressed

Value

Exports a vcf file to a given destination

Author(s)

Piyal Karunaratne

Examples

```
## Not run: vcf.file.path <- paste0(path.package("rCNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path)
exportVCF(vcf, "../exVcf.vcf")
## End(Not run)
```

get.miss *Get missingness of individuals in raw vcf*

Description

A function to get the percentage of missing data of snps per SNP and per sample

Usage

```
get.miss(data, type = c("samples", "snps"), plot = TRUE, verbose = TRUE)
```

Arguments

data	a list containing imported vcf file using readVCF or genotype table generated using hetTgen
type	character. Missing percentages per sample "samples" or per SNP "snps", default both
plot	logical. Whether to plot the missingness density with ninety five percent quantile
verbose	logical. Whether to show progress

Value

Returns a data frame of allele depth or genotypes

Author(s)

Piyal Karunaratne

Examples

```
vcf.file.path <- paste0(path.package("rcNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path=vcf.file.path)
missing<-get.miss(vcf,plot=TRUE)
```

gt.format *Format genotype for BayEnv and BayPass*

Description

This function generates necessary genotype count formats for BayEnv and BayPass with a subset of SNPs

Usage

```
gt.format(gt, info, format = c("benv", "bpass"), snp.subset = NULL)
```

Arguments

gt	multi-vector. an imported data.frame of genotypes or genotype data frame generated by hetTgen or path to GT.FORMAT file generated from VCFTools
info	a data frame containing sample and population information. It must have "sample" and "population" columns
format	character. output format i.e., for BayPass or BayEnv
snp.subset	numerical. number of randomly selected subsets of SNPs. default = NULL subset

Value

Returns a list with formatted genotype data: \$bayenv - snps in horizontal format - for BayEnv (two lines per snp); \$baypass - vertical format - for BayPass (two column per snp); \$sub.bp - subsets snps for BayPass \$sub.be - subsets of snps for BayEnv

Author(s)

Piyal Karunaratne

Examples

```
## Not run: vcf.file.path <- paste0(path.package("rCNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path=vcf.file.path)
het.table<-hetTgen(vcf,"GT")
info<-unique(substr(colnames(het.table)[-c(1:3)],1,8))
GT<-gt.format(het.table,info)
## End(Not run)
```

h.zygoty

Determine per sample heterozygoty and inbreeding coefficient

Description

This function will calculate the heterozygoty on a per-sample basis from vcf files (snps), and most importantly inbreeding coefficient which is used to filter out the samples with bad mapping quality.

Usage

```
h.zygoty(vcf, plot = FALSE, pops = NA, verbose = TRUE)
```

Arguments

vcf	an imported vcf file in in a list using readVCF or a data frame of genotypes generated using hetTgen
plot	logical. Whether to plot a boxplot of inbreeding coefficients for populations. A list of populations must be provided
pops	character. A list of population names with the same length and order as the number of samples in the vcf
verbose	logical. Show progress

Value

Returns a data frame of expected “E(Hom)” and observed “O(Hom)” homozygotes with their inbreeding coefficients.

Author(s)

Piyal Karunaratne, Pascal Milesi, Klaus Schliep

Examples

```
## Not run: vcf.file.path <- paste0(path.package("rCNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path=vcf.file.path)
pp<-substr(colnames(vcf$vcf)[-c(1:9)],1,8)
hzygots<-h.zygosity(vcf,plot=TRUE,pops=pp)
## End(Not run)
```

hetTgen

Generate allele depth or genotype table

Description

hetTgen extracts the read depth and coverage values for each snp for all the individuals from a vcf file generated from readVCF (or GATK VariantsToTable: see details)

Usage

```
hetTgen(
  vcf,
  info.type = c("AD", "AD-tot", "GT", "GT-012", "GT-AB", "DP"),
  verbose = TRUE
)
```

Arguments

vcf	an imported vcf file in a list using readVCF
info.type	character. AD: allele depth value, AD-tot:total allele depth, DP=unfiltered depth (sum), GT: genotype, GT-012:genotype in 012 format, GT-AB:genotype in AB format. Default AD, See details.
verbose	logical. whether to show the progress of the analysis

Details

If you generate the depth values for allele by sample using GatK VariantsToTable option, use only -F CHROM -F POS -GF AD flags to generate the table. Or keep only the CHROM, POS, ID, ALT, and individual AD columns. For info.type GT option is provided to extract the genotypes of individuals by snp.

Value

Returns a data frame of allele depth, genotype of SNPs for all the individuals extracted from a VCF file

Author(s)

Piyal Karunaratne, Klaus Schliep

Examples

```
vcf.file.path <- paste0(path.package("rCNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path=vcf.file.path)
het.table<-hetTgen(vcf)
```

maf	<i>Remove MAF allele</i>
-----	--------------------------

Description

A function to remove the alleles with minimum allele frequency and keep only a bi-allelic matrix when loci are multi-allelic

Usage

```
maf(h.table, AD = TRUE, verbose = TRUE)
```

Arguments

h.table	allele depth table generated from the function hetTgen
AD	logical. If TRUE a allele depth table similar to hetTgen output will be returns; If FALSE, individual AD values per SNP will be returned in a list.
verbose	logical. Show progress

Value

A data frame or a list of minimum allele frequency removed allele depth

Author(s)

Piyal Karunaratne

Examples

```
## Not run: mf<-maf(ADtable)
```

norm.fact

Calculate normalization factor for each sample

Description

This function calculates the normalization factor for each sample using different methods. See details.

Usage

```
norm.fact(
  df,
  method = c("TMM", "TMMex", "MedR", "QN"),
  logratioTrim = 0.3,
  sumTrim = 0.05,
  Weighting = TRUE,
  Acutoff = -1e+10
)
```

Arguments

df	a data frame or matrix of allele depth values (total depth per snp per sample)
method	character. method to be used (see details). Default TMM
logratioTrim	numeric. percentage value (0 - 1) of variation to be trimmed in log transformation
sumTrim	numeric. amount of trim to use on the combined absolute levels ("A" values) for method TMM
Weighting	logical, whether to compute (asymptotic binomial precision) weights
Acutoff	numeric, cutoff on "A" values to use before trimming

Details

Originally described for normalization of RNA sequences (Robinson & Oshlack 2010), this function computes normalization (scaling) factors to convert observed library sizes into effective library sizes. It uses the method trimmed means of M-values proposed by Robinson & Oshlack (2010). See the original publication and edgeR package for more information. The method MedR is median ratio normalization; QN - quantile normalization (see Maza, Elie, et al. 2013 for a comparison of methods).

Value

Returns a numerical vector of normalization factors for each sample

Author(s)

Piyal Karunaratne

References

- Robinson MD, and Oshlack A (2010). A scaling normalization method for differential expression analysis of RNA-seq data. *Genome Biology* 11, R25
- Robinson MD, McCarthy DJ and Smyth GK (2010). edgeR: a Bioconductor package for differential expression analysis of digital gene expression data. *Bioinformatics* 26

Examples

```
vcf.file.path <- paste0(path.package("rCNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path)
df<-hetTgen(vcf,"AD-tot",verbose=FALSE)
norm.fact(df)
```

power.bias

Simulate and plot detection power of bias in allele ratios

Description

This function simulates 95% confidence level Z-score based detection power of allele biases for a given number of samples and a range of depths

Usage

```
power.bias(  
  Dlist = c(2, 4, 8, 16),  
  sam = 100,  
  intensity = 0.005,  
  nsims = 1000,
```

```

    p = 0.5,
    plot = TRUE
  )

```

Arguments

<code>dlist</code>	numerical. vector of depths values to be tested
<code>sam</code>	numerical. number of samples
<code>intensity</code>	numerical. frequency of bias
<code>nsims</code>	numerical. number of simulations to be done for each sample
<code>p</code>	numerical. expected allele ratio (0.5 for data with known sequencing biases)
<code>plot</code>	logical. plot the output

Value

Returns a list of detection probability values for the given range of samples and depth

Author(s)

Pascal Milesi, Piyal Karunaratne

readVCF	<i>Import VCF file</i>
---------	------------------------

Description

Function to import raw single and multi-sample VCF files. The function required the R-package `data.table` for faster importing.

Usage

```
readVCF(vcf.file.path, verbose = FALSE)
```

Arguments

<code>vcf.file.path</code>	path to the vcf file
<code>verbose</code>	logical. show progress

Value

Returns a list with vcf table in a data frame, excluding meta data.

Author(s)

Piyal Karunaratne

Examples

```
vcf.file.path <- paste0(path.package("rCNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path)
```

relatedness	<i>Determine pairwise relatedness</i>
-------------	---------------------------------------

Description

Relatedness is determined according to genome-wide relationship assessment of Yang et al. 2010 equation 6, on a per sample basis (with itself and others), using SNPs.

Usage

```
relatedness(vcf, plot = TRUE, threshold = 0.5, verbose = TRUE)
```

Arguments

vcf	an imported vcf file in a list using readVCF or a data frame of genotypes generated using hetTgen
plot	logical. Whether to plot relatedness of samples against themselves, among themselves and outliers
threshold	numerical. A value indicating to filter the individuals of relatedness among themselves. Default 0.5 (siblings)
verbose	logical. Show progress.

Details

According to Yang et al. (2010), out breeding non-related pairs should have a relatedness value of zero while the individual with itself will have a relatedness value of one. Relatedness value of ~0.5 indicates siblings.

Value

A data frame of individuals and relatedness score A_{jk}

Author(s)

Piyal Karunaratne, Klaus Schliep

References

Yang, J., Benyamin, B., McEvoy, B. et al. Common SNPs explain a large proportion of the heritability for human height. Nat Genet 42, 565569 (2010).

Examples

```
vcf.file.path <- paste0(path.package("rCNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path=vcf.file.path)
relate<-relatedness(vcf)
```

sig.hets

Identify significantly different heterozygotes from SNPs data

Description

This function will recognize the SNPs with a proportion of heterozygotes significantly higher than expected under HWE and plot deviant snps based only on the excess of heterozygotes.

Usage

```
sig.hets(  
  a.info,  
  method = c("chi.sq", "fisher"),  
  plot = TRUE,  
  verbose = TRUE,  
  ...  
)
```

Arguments

a.info	allele info table generated from filtered vcfs using the function <code>allele.info</code> or allele depth table generated from <code>hetTgen</code>
method	character. Method for testing significance. Fisher exact test (<code>fisher</code>) or Chi-square test (<code>chi.sq</code>)
plot	logical. Whether to plot the identified duplicated snps with the expected values
verbose	logical, if TRUE, the progress is shown
...	other arguments passed to plot

Value

A matrix of expected heterozygote proportions from the observed data with p-value indicating significance of deviation.

Author(s)

Piyal Karunarathne, Pascal Milesi, Klaus Schliep

Examples

```
## Not run: data(alleleINF)
AI <- alleleINF
duplicates<-sig.hets(AI,plot=TRUE)
## End(Not run)
```

sim.als

Simulate Allele Frequencies

Description

This function simulates allele frequencies of a desired population size under HWE

Usage

```
sim.als(n = 500, nrun = 10000, res = 0.001, plot = TRUE)
```

Arguments

n	desired populations size (set this value same as your actual population size for an accurate simulation)
nrun	number of simulations to run on each allele frequency. The higher this number, the closer the simulations will be to the theoretical values (at the cost of computer power); 10000 is an optimal value.
res	desired resolution of the theoretical allele frequency
plot	logical. whether to plot the simulation

Value

A list of two matrices:

1. allele_freqs: theoretical allele frequency
2. simulated_freqs: simulated frequencies at different confidence intervals

Author(s)

Piyal Karunaratne, Pascal Milesi

Examples

```
## Not run: alleles <- sim.als(n=200,nrun=1000,res=0.001,plot=TRUE)
```

vcf.stat	<i>Get sequencing quality statistics of raw VCF files (with GatK generated vcf files only)</i>
----------	--

Description

This function will generate a table similar to VariantsToTable option in GatK from raw vcf files for filtering purposes. The function will also plot all the parameters (see details & values).

Usage

```
vcf.stat(vcf, plot = TRUE, ...)
```

Arguments

vcf	an imported vcf file in data.frame or matrix format using readVCF
plot	logical. Whether to plot the (12) parameters
...	other arguments passed on to plot (e.g. col,border)

Details

For more details see instructions of GatK

Value

Returns a data frame with quality parameters from the INFO. field of the vcf

- QUAL: The Phred-scaled probability that a REF/ALT polymorphism exists at this site given sequencing data
- AC: Allele count
- AF: Allele frequency
- DP: unfiltered depth
- QD: QualByDepth - This is the variant confidence (from the QUAL field) divided by the unfiltered depth of non-hom-ref samples
- FS: FisherStrand - This is the Phred scaled probability that there is strand bias at the site
- SOR: StrandOddsRatio - This is another way to estimate strand bias using a test similar to the symmetric odds ratio test
- MQ: RMSMappingQuality - This is the root mean square mapping quality over all the reads at the site
- MQRankSum: MappingQualityRankSumTest - This is the u-based z-approximation from the Rank Sum Test for mapping qualities
- ReadPosRankSum: ReadPosRankSumTest: This is the u-based z-approximation from the Rank Sum Test for site position within reads

Author(s)

Piyal Karunaratne

Examples

```
vcf.file.path <- paste0(path.package("rCNV"), "/example.raw.vcf.gz")
vcf <- readVCF(vcf.file.path=vcf.file.path)
statistics<-vcf.stat(vcf,plot=TRUE)
```

vst

*Calculate population-wise Vst***Description**

This function calculates Vst (variant fixation index) for populations given a list of duplicated loci

Usage

```
vst(AD, pops, id.list = NULL, qGraph = TRUE, verbose = TRUE, ...)
```

Arguments

AD	data frame of total allele depth values of (duplicated, if <code>id.list</code> is not provided) SNPs
pops	character. A vector of population names for each individual. Must be the same length as the number of samples in AD
id.list	character. A vector of duplicated SNP IDs. Must match the IDs in the AD data frame
qGraph	logical. Plot the network plot based on Vst values (see details)
verbose	logical. show progress
...	additional arguments passed to <code>qgraph</code>

Details

Vst is calculated with the following equation

$$V_T = \frac{V_S}{V_T}$$

where V_T is the variance of normalized read depths among all individuals from the two populations and V_S is the average of the variance within each population, weighed for population size (see reference for more details) See `qgraph` help for details on `qgraph` output

Value

Returns a matrix of pairwise Vst values for populations

Author(s)

Piyal Karunaratne

References

Redon, Richard, et al. Global variation in copy number in the human genome. *nature* 444.7118 (2006)

Examples

```
## Not run: data(alleleINF)
data(ADtable)
DD<-dupGet(alleleINF)
ds<-DD[DD$dup.stat=="duplicated",]
ad<-ADtable[match(paste0(ds$CHROM,".",ds$POS),paste0(ADtable$CHROM,".",ADtable$POS)),]
vst(ad,pops=substr(colnames(ad)[-c(1:4)],1,11))
## End(Not run)
```

Index

* datasets

- ADnorm, 3
- ADtable, 4
- alleleINF, 7

- ad.correct, 2
- ADnorm, 3
- ADtable, 4
- allele.freq, 4
- allele.info, 5
- alleleINF, 7

- cnv, 8
- cpm.normal, 9

- depthVsSample, 11
- dup.plot, 12
- dup.validate, 13
- dupGet, 13

- exportVCF, 15

- get.miss, 16
- gt.format, 16

- h.zygotity, 17
- hetTgen, 18

- maf, 19

- norm.fact, 20

- power.bias, 21

- readVCF, 22
- relatedness, 23

- sig.hets, 24
- sim.als, 25

- vcf.stat, 26
- vst, 27